## HIKVISION ARG-2012

## LAYOUT FEATURES



## Key features

- 1.3mp (1280x960) resolution
- HD real-time video
- 3D DNR & DWDR & BLC
- IR LED's (up to 30m)
- IP66
- Compact design
- PoE
- Fix lens 4 mm

### DS-2012-1.3mp

| Camera | |
|---|---|
| Image sensor | 1/3" progressive scan CMOS |
| Min. illumination | 0.01 lux @F1.2, AGC ON, 0 lux with IR |
| Shutter time | 1/25s (1/30s) ~ 1/100,000s |
| Lens | 4mm @F2.0, angle of view: 73.1° (6mm, 12mm optional) |
| Lens mount | M12 |
| Day & night | IR cut filter with auto switch |
| Digital noise reduction | 3D DNR |
| Wide dynamic range | Digital WDR |
| **Compression Standard** | |
| Video compression | H.264 / MJPEG |
| H.264 codec profile | Main profile |
| Bit rate | 32 Kbps ~ 16 Mbps |
| Dual stream | Yes |
| **Image** | |
| Max. Image Resolution | 1280 × 960 |
| Frame rate | 50Hz: 25fps (1280 × 960), 25fps (1280 x 720) 60Hz: 30fps (1280 × 960), 30fps (1280 x 720) |
| Image settings | Saturation, brightness, contrast, sharpeness adjustable through client software or web browser |
| BLC | Yes, zone configurable |
| **Network** | |
| Network storage | NAS |
| Alarm trigger | Motion detection, dynamic analysis, tampering alarm |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional) |
| Interoperability | ONVIF, PSIA, CGI |
| Security | User Authentication, watermark, reset button |
| **Interface** | |
| Communication interface | 1 RJ45 10 M / 100 M Ethernet interface |
| **General** | |
| Operating conditions | -30 °C ~ 60 °C (-22°F ~ 140 °F)  humidity 95% or less (non-condensing) |
| Power supply | 12 VDC ± 10% , PoE (802.3af) |
| Power consumption | Max. 5W (Max. 7W with ICR on) |
| Weather proof rating | IP66 |
| IR range | Up to 30m |
| Dimension | 60.4 x 76.9 x 139.2mm |
| Weight | 500g (1.1 lbs) |