

Some Advanced Points on Classes

Stéphane Ducasse
stephane.ducasse@inria.fr
<http://stephane.ducasse.free.fr/>

Outline

Indexed Classes

Classes as Objects


Class Instance Variables and Methods

Class Variables

Pool Dictionaries



Variable size instance




How do we represent objects whose size is variable such an array

Array new: 10

Array new: 15

Two Views on Classes



Named or ***indexed*** instance variables

Named: 'addressee' of Packet

Indexed: Array


Or looking at them in another way:

Objects with pointers to other objects

Objects with arrays of bytes (word, long)

Difference for efficiency reasons: arrays of bytes
(like C strings) are faster than storing an array of

Types of Classes




Indexed	Named	Definition	Method	Examples
---------	-------	------------	--------	----------

No	Yes	#subclass:...		Packet
Yes	Yes	#variableSubclass:		Array
Yes	No	#variableByteSubclass		String

Method related to class types: #isPointers, #isBits, #isBytes, #isFixed, #isVariable, #kindOfSubclass

Constraints




Classes defined using `#subclass`: support any kind of subclasses

Classes defined using `#variableSubclass`: can only have: `variableSubclass`: or `variableByteSubclass`: subclasses

pointer classes and byte classes don't mix: e.g. only byte subclasses of byte classes.

Indexed Classes




For classes that need a variable number of instance variables

```
ArrayedCollection variableSubclass: #Array
instanceVariableNames: "
classVariableNames: "
poolDictionaries: "
category: 'Collections-Arrayed'
```

```
Array new: 4 -> #(nil nil nil nil)
```

Indexed Classes



Indexed variable is implicitly added to the list of instance variables


Only one indexed instance variable per class

Access with `#at:` and `#at:put:`

(`#at:put:` answers the value, not the receiver)

Subclasses should also be indexed

Index access



First access: anInstance at: 1
#size returns the number of indexed instance variables

Instantiated with #new: max

|t|

t := (Array new: 4).

t at: 2 put: 'lulu'.

t at: 1 -> nil

Roadmap

Indexed Classes

Classes as Objects


Class Instance Variables and Methods

Class Variables

Pool Dictionaries



The Meaning of is-a



A class defines the structure and the behavior of all its instances.

Each instance possesses its own set of values.


Instances share the behavior defined in their class with other instances via the instance of link.

cept:
me
ndt:


2
look in
the classes

1
go to the class

Lookup...



Remember: ...



Example: macNode name
macNode is an instance of Workstation
=> name is looked up in the class Workstation
name is not defined in Workstation
=> lookup continues in Node
name is defined in Node
=> lookup stops + method executed

Roadmap

Indexed Classes

Classes as Objects


Class Instance Variables and Methods

Class Variables

Pool Dictionaries




Class Methods



- As any object a (meta)class can have methods that represent the behavior of its instance: a class
- Uniformity => Same rules as for normal classes
- No constraint: just normal methods
- Can only access instance variable of the class:

Class Method Examples



NetworkManager class>>new can only access uniqueInstance class instance variable and not instance variables (like nodes).

Default Instance Creation class method:


new/new: and basicNew/basicNew: (see Direct Instance Creation)

Packet new

Specific instance creation method


Packet send: 'Smalltalk is fun' to: #lpr

Class Instance Variables



- Like any object, a class is an instance of a class that can have instance variables that represent the state of a class.
- When Point defines the new instance variable z, the instances of Point have 3 value (one for x, one for y, and one for z)
- When a metaclass defines a new instance variable, then its instance (a Class) gets a new value in addition to subclass, superclasses, methodDict...

The Singleton Pattern



- A class having only one instance
- We keep the instance created in an instance variable

WebServer **class**

instanceVariableNames: 'uniqueInstance'

WebServer class>>new

self error: 'You should use uniqueInstance to get the unique instance'

WebServer class>>uniqueInstance


uniqueInstance isNil

ifTrue: [uniqueInstance := self basicNew initialize].

^ uniqueInstance


WebServer <<singleton>>
<u>uniqueInstance</u>
uniqueInstance() resetInstance

Singleton



- WebServer being an instance of WebServer class has an instance variable named uniqueInstance.
- WebServer has a new value that is associated with uniqueInstance

Design Implications



- An instance variable of a class can be used to represent information shared by all the instances of the class. However, you should use class instance variables to represent the state of the class (like the number of instances, ...) and not information of its instance.
- Should use shared Variable instead (next Section).

Advanced Classes

Indexed Classes

Classes as Objects

Class Instance Variables and Methods

Class Variables


Pool Dictionaries



classVariable = Shared Variables


- How to share state between all the instances of a class:
Use a classVariable
- a classVariable is shared and directly accessible by all the instances of the class and subclasses
- A pretty bad name: should have been called Shared Variables (now fixed in VW)
- Shared Variable => begins with an uppercase letter
- a classVariable can be directly accessed in instance methods and class methods

classVariable = shared Variab. (Sq)



```
Magnitude subclass: #Date
  instanceVariableNames: 'julianDayNumber '
  classVariableNames: 'DaysInMonth FirstDayOfMonth
MonthNames SecondsInDay WeekDayNames '
  poolDictionaries: "
  category: 'Kernel-Magnitudes'
```


Date class>>initialize



"Initialize class variables representing the names of the months and days and the number of seconds, days in each month, and first day of each month."

```
MonthNames := #(January February March April May June July August  
September October November December ).
```


```
SecondsInDay := 24 * 60 * 60.
```

```
DaysInMonth := #(31 28 31 30 31 30 31 31 30 31 30 31 ).
```

```
FirstDayOfMonth := #(1 32 60 91 121 152 182 213 244 274 305 335 ).
```

```
WeekDayNames := #(Monday Tuesday Wednesday Thursday Friday  
Saturday Sunday ).
```

Class Variable vs. Instance Variables



julianDayNumber

"Answer the number of days (or part of a day) elapsed since noon GMT on January 1st, 4713 B.C."

↑**julianDayNumber**

Date

julianDayNumber
DaysInMonth
FirstDayOfMonth
MonthNames

julianDayNumber
monthName

Date class

initialize

monthName

"Answer the name of the month in which the receiver falls."

↑**MonthNames** at: self monthIndex


initialize

"Initialize class variables representing the names of the months and days and the number of seconds, days in each month and first day of each month."

MonthNames :=


```
*(January February March April May June July
August September October November December ).
SecondsInDay := 24 * 60 * 60.
DaysInMonth := *(31 28 31 30 31 30 31 31 30 31 30 31 ).
FirstDayOfMonth := *(1 32 60 91 121 152 182 213 244 274 305
335 ).
WeekDayNames := *(Monday Tuesday Wednesday Thursday
Friday Saturday Sunday ).
```

Class Instance Variables vs classVariables



- a classVariable is shared and directly accessible by all the instances and subclasses
- Class instance variables, just like normal instance variables, can be accessed only via class message and accessors:
 - an instance variable of a class is private to this class.
- Take care: when you change the value of a classVariable the whole inheritance tree is impacted!

Summary of Variable Visibility



NetworkManager>>detectNode: aBoolBlock

```
^nodes detect: aBoolBlock
```

instance methods

instance variables
nodes

classVariables
Domain


NetworkManager class>>new

```
uniqueInstance isNil  
  ifTrue:[ uniqueInstance := super new].  
^uniqueInstance
```

class methods


class instance variables
uniqueInstance

ClassVariables...



- ClassVariables can be used in conjunction with instance variables to cache some common values that can be changed locally in the classes.

Example



- in the Scanner class a table describes the types of the characters (strings, comments, binary....). The original table is stored into a classVariable, its value is loaded into the instance variable. It is then possible to change the value of the instance variable to have a different scanner.

Object subclass: #Scanner

instanceVariableNames: 'source mark prevEnd
hereChar token tokenType buffer **typeTable** '
classVariableNames: '**TypeTable** '

Roadmap

Indexed Classes

Classes as Objects


Class Instance Variables and Methods

Class Variables

Pool Dictionaries



poolVariables




Shared variable => begins with a uppercase letter.
Variable shared by a group of classes not linked by inheritance.

Each class possesses its own pool dictionary (containing poolVariables).

They are not inherited.

DON'T USE THEM!

Examples of PoolDictionaries



from the System: the class Text

CharacterArray subclass: #Text

instanceVariableNames: 'string runs '


classVariableNames: "

poolDictionaries: 'TextConstants '

category: 'Collections-Text'

Elements stored into TextConstants like Ctrl, CR, ESC, Space can be directly accessed from all the classes like ParagraphEditor....

Example of PoolVariables



Smalltalk at: #NetworkConstant put: Dictionary new.

NetworkConstant at: #rates put: 9000.

Packet>>computeAverageSpeed

...

NetworkConstant at: #rates

Equivalent to :

Object subclass: #Packet

instanceVariableNames: 'contents addressee
originator '

classVariableNames: 'Domain'

poolDictionaries: 'NetworkConstant'

What you should know

- Classes are objects too
- Class methods are just methods on objects that are classes
- Classes are also represented by instance variables (class instance variables)
- (Shared Variables) ClassVariables are shared among subclasses and classes (metaclass)