# Enterprise-Grade Bulk Email & Cold Outreach Platform: Architecture & Implementation Blueprint

**Document Version:** 1.0.0
**Target:** Engineering & Product Leadership
**Status:** Build-Ready Specification

## 1. Executive Summary & Recommended Approach

### 1.1 The Challenge

Modern email deliverability has shifted dramatically from an unconstrained broadcast model to a reputation-gated, algorithmic ecosystem. Senders who blast thousands of unverified emails through misconfigured domains or monolithic SMTP relays are swiftly flagged by machine-learning filters at Google Workspace, Microsoft 365, and Yahoo. With the mandatory authentication frameworks enforced by Google and Yahoo (February 2024) and Microsoft Outlook (May 2025), senders face strict algorithmic thresholds:

- Spam complaint rate ceiling strictly below **0.30%** (target **< 0.10%**).
- Mandatory **SPF, DKIM, and DMARC** alignment.
- Mandatory RFC 8058 **One-Click Unsubscribe** headers.
- Stringent bounce thresholds (hard bounces exceeding **2–3%** trigger immediate domain reputation degradation).

### 1.2 Recommended Core Strategy

To achieve reliable inbox placement while scaling to tens of thousands of messages per month, the platform is architected around four operational pillars:

1. **Multi-Identity Domain & Mailbox Rotation Architecture:**
   - Production operations must decouple outreach and bulk delivery from the primary corporate domain (e.g., if the core business is `company.com`, sending occurs over secondary domains such as `companyhq.net`, `getcompany.io`, or subdomains like `mail.company.com`).
   - Workload is distributed across an active pool of rotated sender accounts (virtual mailboxes / SMTP accounts) capped at safe daily volumes (30–50 cold emails per mailbox/day, or controlled tier increments for transactional/marketing infrastructure).
2. **Dual-Rail Sending Infrastructure:**
   - **Rail A (Cold Outreach & B2B Relationship Sequences):** Google Workspace / Microsoft 365 accounts connected via OAuth 2.0 / REST API, utilizing humanized jitter delays (45–180 seconds), conversational threading, and randomized sending schedules.
   - **Rail B (Opt-In Bulk Newsletters & Transactional Broadcasts):** Amazon SES (Simple Email Service) configured with dedicated IP pools, custom Return-Path (envelope-from) alignment, and strict DMARC enforcement.
3. **Intelligent Throttling & Autonomous Circuit Breakers:**
   - A queue-driven dispatch engine powered by **Redis + BullMQ**.
   - Strict sliding-window rate limiters per second, minute, hour, and day.
   - Real-time event webhooks monitoring bounces and complaints. If a sender mailbox or domain experiences a bounce rate > 3.0% or a complaint rate > 0.15% in a rolling 24-hour window, the

engine automatically throttles or pauses the campaign and alerts administrators before provider blacklisting occurs.

4. **Multi-Tiered AI Personalization Pipeline (Claude Opus & Haiku):**
   - High-cost reasoning (Claude 3 Opus / Claude 3.5 Sonnet) is reserved for pre-campaign deliverability auditing, strategic copy optimization, and complex intent classification on replies.
   - High-throughput per-contact personalization (custom openers, icebreakers, company pain-point synthesis) leverages Prompt Caching and the Anthropic Batch API to reduce API latency and slash token expenditure by 50–90%.

---

# 2. Competitive Analysis: Features to Emulate & Gaps to Fill

| Platform | Key Strengths to Emulate | Architectural Flaws / Gaps to Exploit | How Our Internal Tool Wins |
|---|---|---|---|
| **Instantly.ai** | Multi-mailbox auto-rotation, unlimited warmup accounts, high-converting minimal plain-text sequence builder. | Black-box warm-up pool can lead to sudden spam flagging; high recurring cost per user tier; vendor lock-in on lead CRM. | Native ownership of all data; zero per-seat markup; strict programmatic verification prior to any queue entry. |
| **Smartlead.io** | Unified master inbox for replies; granular warmup ramps; API-first design; sub-account isolation. | Webhook latency spikes; convoluted UI for non-technical team members; rigid attribution reporting. | Streamlined, role-based internal UI with real-time WebSocket job telemetry and customizable CRM webhooks. |
| **Lemlist** | Dynamic image personalization; multichannel sequences (LinkedIn + Email); icebreaker generation. | Expensive entry tiers; complex campaign flows; AI personalization generates generic fluff without strict prompt guardrails. | Context-grounded Claude Opus prompts with strict token budgets, fallback validation, and human review approval gates. |
| **listmonk** | High performance (Go backend); self-hosted privacy; lightweight PostgreSQL storage; native bounce handling. | Built strictly for single-blast opt-in newsletters; lacks cold outreach warmup, sender rotation, and conversational follow-up triggers. | Merges the high-throughput safety of listmonk with the algorithmic warmup and follow-up sequence engines of cold outreach tools. |
| **Mailmeteor** | Direct Google Sheets integration; clean deliverability footprint through Gmail API; simple mail merge. | Rate-limited strictly to Google's daily 1,500/2,000 quota; no multi-account rotation; lack of automated bounce circuit breakers. | Hybrid provider abstraction allowing seamless switching between Gmail API, Microsoft Graph, and Amazon SES. |
| **Postal / Mautic** | Full self-hosted mail server stack; complex lead scoring and nurturing automation. | Enormous operational overhead (managing IP rDNS, PTR, Postfix queues, SpamAssassin); high IP reputation maintenance cost. | Cloud-native API relay model: eliminates SMTP maintenance overhead while retaining complete software autonomy. |

---

# 3. Prioritized Feature Specification

*Diagram (Mermaid source)*

```
flowchart LR
    A[Data Ingestion & Hygiene] --> B[Campaign Sequence Builder]
    B --> C[AI Intelligence Layer]
    C --> D[Queue & Throttling Engine]
    D --> E[Multi-Provider Dispatch]
    E --> F[Telemetry & Feedback Loop]
    F -->|Bounces/Complaints| D
```

## 3.1 Phase 1: MVP (Minimum Viable Product — Core Safety & Delivery)

1. **Bulk Ingestion & Column Mapping Engine:**
   - Multi-format ingestion: CSV, TSV, XLSX file uploads, and raw clipboard text paste.

- Interactive schema mapper: Automatic fuzzy matching for `email`, `first_name`, `last_name`, `company`, `title`, and unlimited arbitrary JSON custom fields.
- Native client & server syntax sanitization (RFC 5322 compliance, lowercase normalization, whitespace trimming).

2. **Import-Time Verification & Hygiene Filter:**
   - In-memory duplicate deduplication across existing workspaces and specific campaign lists.
   - Regular-expression role-address blocker (rejects `admin@`, `info@`, `support@`, `billing@`, `sales@`, `jobs@`).
   - Disposable & temporary domain filter (matching a local database of 3,500+ temporary email providers).
   - Async DNS MX-record validator with caching to discard dead domains before queue entry.
3. **Template & Multi-Step Sequence Builder:**
   - Dual-mode editor: Clean plain-text editor (optimized for cold outreach) and responsive HTML template builder.
   - Mustache-style variable interpolation (`{{first_name}}`, `{{company}}`, `{{custom_field | default: "there"}}`).
   - Linear multi-step follow-up sequences with customizable delay offsets (e.g., Step 2 sends 3 business days after Step 1).
   - Preview renderer with realistic dummy contact data and single-click "Send Test to Me" functionality.
4. **Controlled Queue & Throttling Engine:**
   - Redis-backed BullMQ job queue decoupling user browser sessions from execution.
   - Strict hourly and daily send caps per sending account.
   - Configurable randomized jitter delay (e.g., uniform distribution between 30 and 150 seconds).
   - Sending window scheduler: Restricts delivery to specific days (e.g., Monday–Friday) and hours (e.g., 09:00–18:00) calculated against either the recipient or sender timezone.
   - Manual state control: Pause, resume, and terminate campaigns instantly.
5. **Core Deliverability & Compliance:**
   - In-app DNS configuration auditor checking SPF, DKIM, and DMARC records with real-time status badges.
   - Automatic RFC 8058 `List-Unsubscribe` and `List-Unsubscribe-Post` header injection.
   - One-click unsubscribe body link injection that logs immediately to a global workspace suppression table.
   - Hard bounce auto-suppression preventing repeated delivery to invalid addresses.
6. **Infrastructure Adapter:**
   - Primary sending driver: Amazon SES API (via AWS SDK v3) with automated SNS bounce/complaint webhook processing.
   - Fallback sending driver: Google Workspace SMTP / OAuth API with rate limiter caps.
7. **Basic Claude Integration:**
   - OpenAI/Anthropic API integration for one-shot subject line variant generation and tone revision.
8. **Security & Workspace Management:**
   - Email/password authentication with bcrypt hashing, session tokens, and role-based permissions (`Admin`, `Member`).
   - Server-side AES-256-GCM encryption for all third-party API credentials (AWS keys, SMTP passwords, Anthropic tokens).

## 3.2 Phase 2: Enhanced Personalization, Multi-Sender & Health Controls

1. **Multi-Account Sender Rotation:**
   - Pool multiple sender mailboxes across domains into a single unified campaign pool.
   - Smart round-robin dispatch based on remaining daily capacity and health scores.
2. **Automated Warmup Engine:**
   - Configurable ramping schedules (e.g., starts at 15 emails/day, increments by +5/day until target ceiling is reached).
   - Domain-level volume aggregation to avoid saturating newly registered domains.
3. **Automated Health Shields (Circuit Breakers):**
   - Real-time rolling metrics evaluation: automatically pauses an account or campaign if bounce rate exceeds 3.0% or complaint rate exceeds 0.15% across a 24-hour window.
4. **Deep Claude Opus Personalization Engine:**
   - Anthropic Batch API pipeline generating personalized opening lines ("icebreakers") based on CSV data (e.g., recent company funding, LinkedIn summary text).
   - Pre-send spam-trigger analysis assigning a composite risk score (0–100) and flagging high-risk buzzwords.
5. **Inbound Reply Tracking & Classification:**
   - IMAP/Webhook inbound listener tracking replies to sequences.
   - Automated sequence termination: pauses follow-up emails the instant a contact replies.
   - Claude-powered reply intent classification: `Interested`, `Not Interested`, `Out of Office`, `Unsubscribe Request`.
6. **Granular Analytics Dashboard:**
   - Real-time conversion funnel: `Imported` → `Validated` → `Queued` → `Sent` → `Delivered` → `Opened` → `Clicked` → `Replied` → `Bounced` → `Unsubscribed`.
   - Export full analytical audit reports to CSV.


## 3.3 Phase 3: Enterprise Teamwork, AI Orchestration & Advanced Deliverability

1. **Multi-Tenant Workspaces & Audit Logs:**
   - Isolated team workspaces, fine-grained access control (`Admin`, `Campaign Manager`, `Copywriter`, `Auditor`).
   - Immutable audit trail logging every administrative send, export, contact deletion, and API key modification.
2. **A/B Testing Multi-Arm Bandit Engine:**
   - Dynamic subject line and email body variant split-testing with automated traffic routing toward top-performing variants.
3. **Inbox Placement & Seed List Testing:**
   - Integrated synthetic seed-box checker (monitoring deliverability against Gmail, Outlook, Yahoo, and iCloud inbox vs. spam folder placement before full broadcast).
4. **Advanced India DPDP & GDPR Governance Module:**
   - Comprehensive consent provenance tracking (recording consent timestamp, IP address, referral URL, and lawful basis).
   - Automated Data Subject Access Request (DSAR) compliance: One-click export or crypto-shredding (right to erasure) for contact personal records.

---

# 4. System Architecture & Technical Stack

## 4.1 Architecture Diagram



## 4.2 Tech Stack Selection & Justification

| Layer | Recommended Choice | Rationale for a Small High-Velocity Team |
|---|---|---|
| **Frontend Framework** | **Next.js 15 (React 19, TypeScript)** | Provides server components for fast rendering, unified API routes for server actions, and shared TypeScript types between frontend and backend. |
| **UI Components** | **shadcn/ui + Tailwind CSS** | Copy-paste accessible components; allows rapid iteration of complex data tables, mapping modals, and progress bars without heavy external UI dependencies. |
| **Backend Engine** | **Node.js (Fastify or Next.js API Routes)** | Full JavaScript/TypeScript ecosystem synergy. Exceptional asynchronous I/O performance for processing thousands of simultaneous network requests. |
| **Database** | **PostgreSQL 16** | Uncompromising ACID compliance for transactional financial and delivery states; rich native `jsonb` support for unstructured custom CSV contact attributes; powerful indexing. |
| **ORM** | **Prisma ORM or Drizzle ORM** | Drizzle provides zero-overhead, type-safe SQL queries with instant migrations; Prisma offers rapid developer ergonomics. Drizzle is recommended for high-throughput batch operations. |
| **Queue & Broker** | **Redis 7 + BullMQ** | Standard in the Node.js ecosystem for mission-critical task orchestration. Native support for delayed jobs (e.g., "send follow-up in 3 days"), rate limiters, parent-child job hierarchies, and worker heartbeats. |
| **AI Orchestration** | **Anthropic TypeScript SDK** | Official typed SDK with native streaming, automated retry handling, and direct support for Prompt Caching and Message Batches API. |
| **Hosting & Infra** | **Railway / Render + Managed PostgreSQL & Redis (or AWS ECS)** | Minimizes DevOps overhead. Zero server configuration required for launch, with instant scalability and isolated background worker containers. |

---

# 5. Relational Data Model

The database schema is structured to ensure referential integrity, complete auditability, and zero risk of double-sends.

*Diagram (Mermaid source)*

```
erDiagram
    WORKSPACE ||--o{ USER : contains
    WORKSPACE ||--o{ SENDER_ACCOUNT : registers
    WORKSPACE ||--o{ CONTACT_LIST : organizes
    WORKSPACE ||--o{ CAMPAIGN : owns
    WORKSPACE ||--o{ SUPPRESSION_RECORD : enforces

    CONTACT_LIST ||--o{ CONTACT : contains

    CAMPAIGN ||--o{ CAMPAIGN_STEP : defines
    CAMPAIGN ||--o{ CAMPAIGN_RECIPIENT : targets

    CAMPAIGN_RECIPIENT ||--o{ SEND_LOG : records
    SENDER_ACCOUNT ||--o{ SEND_LOG : dispatches

    CAMPAIGN_RECIPIENT ||--o{ TRACKING_EVENT : triggers
```

## 5.1 Core SQL Table Definitions

```
-- Workspaces & Organizations
CREATE TABLE workspaces (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    name VARCHAR(255) NOT NULL,
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP,
    updated_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

-- Users & Authentication
CREATE TYPE user_role AS ENUM ('super_admin', 'admin', 'member', 'viewer');

CREATE TABLE users (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
    email VARCHAR(255) UNIQUE NOT NULL,
    password_hash VARCHAR(255) NOT NULL,
    full_name VARCHAR(255) NOT NULL,
    role user_role DEFAULT 'member',
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

-- Sending Accounts & Infrastructure Config
CREATE TYPE provider_type AS ENUM ('amazon_ses', 'google_workspace', 'microsoft_365', 'smtp_custom');
CREATE TYPE account_status AS ENUM ('warming', 'active', 'throttled', 'paused', 'error');

CREATE TABLE sender_accounts (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
    from_name VARCHAR(255) NOT NULL,
    from_email VARCHAR(255) NOT NULL,
    reply_to VARCHAR(255),
    provider provider_type NOT NULL,
    credentials_encrypted TEXT NOT NULL, -- AES-256-GCM encrypted JSON
    daily_quota INT NOT NULL DEFAULT 50,
    hourly_quota INT NOT NULL DEFAULT 10,
    current_warmup_day INT DEFAULT 0,
    is_warmup_enabled BOOLEAN DEFAULT TRUE,
    status account_status DEFAULT 'warming',
    bounce_count_rolling_24h INT DEFAULT 0,
    complaint_count_rolling_24h INT DEFAULT 0,
    consecutive_failures INT DEFAULT 0,
    last_health_check_at TIMESTAMP WITH TIME ZONE,
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

-- Contact Lists & Segments
CREATE TABLE contact_lists (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
    name VARCHAR(255) NOT NULL,
    description TEXT,
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

-- Contacts
CREATE TYPE contact_status AS ENUM (
    'pending', 'verified', 'invalid', 'suppressed',
    'queued', 'sent', 'delivered', 'opened', 'replied', 'bounced', 'complained'
);

CREATE TABLE contacts (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
    list_id UUID REFERENCES contact_lists(id) ON DELETE SET NULL,
    email VARCHAR(255) NOT NULL,
    first_name VARCHAR(100),
    last_name VARCHAR(100),
    company_name VARCHAR(255),
    custom_fields JSONB DEFAULT '{}'::jsonb,
    status contact_status DEFAULT 'pending',
    consent_source VARCHAR(255), -- e.g. "Webinar Signup 2026", "Public Directory"
    consent_recorded_at TIMESTAMP WITH TIME ZONE,
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP,
    CONSTRAINT unique_contact_per_workspace UNIQUE(workspace_id, email)
);
CREATE INDEX idx_contacts_email ON contacts(email);
CREATE INDEX idx_contacts_workspace ON contacts(workspace_id);
CREATE INDEX idx_contacts_custom_fields ON contacts USING gin(custom_fields);

-- Campaigns
CREATE TYPE campaign_status AS ENUM ('draft', 'scheduled', 'running', 'paused', 'completed', 'cancelled');

CREATE TABLE campaigns (
```

```
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
    name VARCHAR(255) NOT NULL,
    status campaign_status DEFAULT 'draft',
    timezone VARCHAR(100) DEFAULT 'UTC',
    window_start_time TIME DEFAULT '09:00:00',
    window_end_time TIME DEFAULT '18:00:00',
    allowed_days INT[] DEFAULT '{1,2,3,4,5}', -- 1=Monday, 7=Sunday
    min_jitter_seconds INT DEFAULT 45,
    max_jitter_seconds INT DEFAULT 180,
    stop_on_reply BOOLEAN DEFAULT TRUE,
    created_by UUID REFERENCES users(id),
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

-- Campaign Steps (Sequences & Follow-ups)
CREATE TABLE campaign_steps (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    campaign_id UUID NOT NULL REFERENCES campaigns(id) ON DELETE CASCADE,
    step_number INT NOT NULL,
    wait_time_days INT DEFAULT 3,
    subject_variants JSONB NOT NULL, -- e.g. ["Quick question", "Hey {{first_name}}"]
    body_html TEXT NOT NULL,
    body_plain TEXT NOT NULL,
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP,
    CONSTRAINT unique_step_per_campaign UNIQUE(campaign_id, step_number)
);

-- Campaign Target Execution State
CREATE TYPE recipient_state AS ENUM ('scheduled', 'in_progress', 'completed', 'halted_replied', 'bounced', 'unsubscribed');

CREATE TABLE campaign_recipients (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    campaign_id UUID NOT NULL REFERENCES campaigns(id) ON DELETE CASCADE,
    contact_id UUID NOT NULL REFERENCES contacts(id) ON DELETE CASCADE,
    current_step INT DEFAULT 1,
    state recipient_state DEFAULT 'scheduled',
    next_action_due TIMESTAMP WITH TIME ZONE,
    last_sent_at TIMESTAMP WITH TIME ZONE,
    CONSTRAINT unique_recipient_per_campaign UNIQUE(campaign_id, contact_id)
);
CREATE INDEX idx_recipient_queue ON campaign_recipients(state, next_action_due);

-- Immutable Send Audit Log (Idempotency Key Record)
CREATE TABLE send_logs (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    idempotency_key VARCHAR(255) UNIQUE NOT NULL, -- Format: campaign_id:step_id:contact_id
    workspace_id UUID NOT NULL REFERENCES workspaces(id),
    campaign_id UUID NOT NULL REFERENCES campaigns(id),
    sender_account_id UUID NOT NULL REFERENCES sender_accounts(id),
    contact_id UUID NOT NULL REFERENCES contacts(id),
    recipient_email VARCHAR(255) NOT NULL,
    message_id VARCHAR(255),
    provider_response JSONB,
    sent_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

-- Global Suppression List
CREATE TYPE suppression_reason AS ENUM ('unsubscribe', 'hard_bounce', 'spam_complaint', 'manual_admin');

CREATE TABLE suppression_list (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
    email VARCHAR(255) NOT NULL,
    reason suppression_reason NOT NULL,
    source_campaign_id UUID REFERENCES campaigns(id),
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP,
    CONSTRAINT unique_suppression_workspace UNIQUE(workspace_id, email)
);
CREATE INDEX idx_suppression_lookup ON suppression_list(workspace_id, email);

-- Inbound Tracking Events (Opens, Clicks, Replies, Bounces)
CREATE TYPE event_type AS ENUM ('open', 'click', 'reply', 'bounce_soft', 'bounce_hard', 'complaint');

CREATE TABLE tracking_events (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    campaign_recipient_id UUID NOT NULL REFERENCES campaign_recipients(id) ON DELETE CASCADE,
    event_type event_type NOT NULL,
    metadata JSONB DEFAULT '{}'::jsonb,
    ip_address VARCHAR(45),
    user_agent TEXT,
    created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);
CREATE INDEX idx_tracking_events_type ON tracking_events(event_type, created_at);
```

# 6. Controlled Sending Engine & Warm-Up Engineering

## 6.1 The Throttling & Queue Algorithm

The engine ensures that sends are never dispatched en masse. Delivery is governed by a distributed token-bucket sliding window managed in Redis.

*Diagram (Mermaid source)*

```
flowchart TD
    A[BullMQ Dispatch Worker] --> B{Within Timezone Window?}
    B -- No --> C[Reschedule for Next Open Window]
    B -- Yes --> D{Is Contact in Suppression List?}
    D -- Yes --> E[Mark Suppressed & Skip]
    D -- No --> F{Account Daily/Hourly Quota Available?}
    F -- No --> G[Rotate to Next Account in Pool / Delay Job]
    F -- Yes --> H[Acquire Distributed Redis Mutex Lock]
    H --> I[Check Idempotency Key in Database]
    I -- Key Exists --> J[Abort: Double-Send Prevented]
    I -- Key Absent --> K[Generate Dynamic Jitter Delay 30-180s]
    K --> L[Dispatch via Provider API SES/Gmail]
    L --> M[Write Idempotency Key & Send Log]
    M --> N[Increment Hourly/Daily Counters in Redis]
    N --> O[Schedule Next Sequence Step with Delay]
```

### Redis Key Schema for Rate Limiting:

- `ratelimit:account:{id}:hour` (TTL 3600s, Max = hourly limit)
- `ratelimit:account:{id}:day` (TTL 86400s, Max = daily limit)
- `ratelimit:domain:{domain}:minute` (TTL 60s, Max = 5 emails/min across accounts to same root domain)
- `idempotency:{campaign_id}:{step_id}:{contact_id}` (TTL 30 days)

## 6.2 Recommended Domain & Mailbox Warm-Up Schedule

When deploying new secondary sending domains or new Google Workspace / Microsoft 365 accounts, strict adherence to a gradual ramp curve is non-negotiable. Email service providers analyze historical transmission velocity; an immediate spike from 0 to 500 emails/day flags the sending IP/domain for automatic spam containment.

### The 28-Day Linear Warm-Up Matrix (Cold Outreach / Google / M365 Mailbox)

| Week | Days | Max Daily Volume / Mailbox | Inter-Email Jitter Delay | Max Hourly Volume | Target Deliverability Milestone |
|---|---|---|---|---|---|
| **Week 1** | Days 1–3 | 10 emails/day | 120 – 300 seconds | 2 – 3 emails/hour | Establish SPF/DKIM baseline; zero bounces permitted. |
| | Days 4–7 | 15 emails/day | 90 – 240 seconds | 3 – 4 emails/hour | Filter checks passing; manual seed responses verified. |
| **Week 2** | Days 8–10 | 25 emails/day | 60 – 180 seconds | 5 – 6 emails/hour | Initial domain reputation metrics populate in Postmaster. |
| | Days 11–14 | 35 emails/day | 45 – 150 seconds | 7 – 8 emails/hour | Spam complaint threshold must stay strictly 0.0%. |
| **Week 3** | Days 15–18 | 45 emails/day | 30 – 120 seconds | 9 – 10 emails/hour | Inbox placement stabilization across Gmail & Outlook. |
| | Days 19–21 | 55 emails/day | 30 – 100 seconds | 10 – 12 emails/hour | Expansion to secondary target list segments. |
| **Week 4** | Days 22–25 | 70 emails/day | 30 – 90 seconds | 12 – 15 emails/hour | Maximum sustainable ceiling for standard cold mailboxes. |
| **Steady** | Day 26+ | **50 – 80 emails/day** | **45 – 120 seconds** | **15 emails/hour** | Safe steady state per mailbox. Scale via mailbox count. |

> **Critical Deliverability Rule:** For direct cold outreach via Google Workspace or Microsoft 365, **never exceed 80 emails per day per mailbox**, even though provider technical limits allow 1,500–2,000. To send 1,000 emails per day safely, provision 15–20 rotated mailboxes across 3–4 distinct secondary domains.

## 6.3 Automated Circuit Breaker & Safe-Pause Rules

The platform implements autonomous protection logic that monitors webhooks and logs in real time. If any of the following triggers are tripped, the system halts operations:

1. **Hard Bounce Circuit Breaker:**
   - Calculation: `(Hard Bounces in rolling 24h / Total Attempted in rolling 24h) * 100`
   - **Threshold:** If bounce rate **> 3.0%** (or 5 consecutive hard bounces), immediately **PAUSE** the campaign and mark the sender account as `throttled`. Notify the admin via email and in-app banner.
2. **Spam Complaint Circuit Breaker (Google / Yahoo Hard Rule):**
   - Calculation: `(Spam Complaints / Total Delivered) * 100`
   - **Warning Threshold:** At **0.10%** (1 complaint per 1,000 sends), trigger an audible warning and auto-reduce sending speed by 50%.
   - **Emergency Shutdown:** At **0.25%**, immediately terminate the campaign to avoid hitting Google's 0.30% blacklisting cutoff.
3. **SMTP Connection Error / Auth Failure:**
   - If 3 consecutive connection timeouts or authentication failures occur on any sender account, that account is automatically isolated and transitioned to `error` status, and pending queue items are gracefully shifted to healthy accounts in the pool.

---

# 7. Infrastructure & Cost Comparison

Comprehensive evaluation of sending paths for a small team starting in India:

| Provider | Cost @ 5k Emails/mo | Cost @ 20k Emails/mo | Cost @ 100k Emails/mo | Daily Hard Limit | Deliverability Profile | Ease of Setup | API Quality & Docs | Verdict & Best Use Case |
|---|---|---|---|---|---|---|---|---|
| **Amazon SES** *(Recommended Primary for Bulk/Marketing)* | **$0.50** ($0.10/1k) | **$2.00** | **$10.00** | Starts at 200/day; scales to 50k–100k+/day upon sandbox exit approval. | Excellent domain-based reputation on clean, opt-in lists. High shared IP hygiene. | Moderate (Requires AWS account, DNS verification, and sandbox exit request). | ★★★★★ (Industry benchmark; AWS SDK v3, SNS webhooks). | **Primary Path for Bulk & Newsletters:** Unbeatable pricing ($10 for 100k sends), bulletproof reliability, and zero markup. |
| **Google Workspace (API / SMTP)** *(Recommended for Cold Outreach)* | ~$6/mo per user account (Base Starter) | ~$18/mo (3 accounts) | ~$90/mo (15 accounts rotated) | 2,000 messages/day per user (SMTP limit is 10k/day on relay, but cold cap is 50/day). | Native high deliverability to other Google Workspace and Gmail inboxes. | Very Simple (OAuth 2.0 or Google Service Account). | ★★★★ (Gmail REST API is robust; strict rate quotas apply). | **Primary Path for B2B Cold Outreach:** Rotated Google accounts yield the highest inbox rates for direct 1-to-1 conversations. |
| **SendGrid (Twilio)** | $19.95/mo (Essentials 50k) | $19.95/mo (Essentials 50k) | $34.95/mo (Essentials 100k) | Based on tier allowance; can send full tier in a day if warmed. | Good on paid tiers; free tiers suffer from low IP reputation. | Simple (API key generation, DNS wizard). | ★★★★★ (Rich API documentation, mature webhooks). | **Solid Alternative:** User-friendly, but 3x–4x more expensive than SES. |
| **Postmark** | $15.00/mo (10k tier) | $35.00/mo (approx. overage) | $115.00/mo (125k tier) | No daily throttle; limited by plan allowance. | Unrivaled inbox placement for transactional emails. Strictly rejects cold outreach. | Very Simple (Guided DKIM/SPF assistant). | ★★★★★ (Best developer experience and log visibility in the industry). | **Strictly Transactional:** Do not use for cold outreach; accounts are banned if spam complaint rates exceed minimal levels. |
| **Brevo** *(formerly Sendinblue)* | ~$15.00/mo | ~$25.00/mo | ~$99.00/mo | Based on plan; free tier limited to 300/day. | Moderate; shared IP reputation varies. | Very Simple (All-in-one UI). | ★★★★ (Comprehensive REST endpoints). | Good for non-technical all-in-one marketing, but expensive at scale. |
| **Mailgun** | $15.00/mo (Basic 10k) | $35.00/mo (Foundation 50k) | $75.00 – $90.00/mo | Plan-defined. | High; strong deliverability validation suite. | Moderate (Requires domain validation). | ★★★★★ (Powerful webhooks and log analysis). | Strong enterprise alternative to SendGrid; cost adds up quickly. |
| **Self-Hosted SMTP** *(Postal / Haraka / Postfix)* | ~$10 – $20/mo (VPS compute: Hetzner / DigitalOcean) | ~$10 – $20/mo | ~$20/mo | Unlimited (Governed only by server compute and bandwidth). | **Extremely Poor for Starters:** VPS IP ranges (DigitalOcean, AWS, Linode) are universally pre-blacklisted or cold. | **Extremely Complex:** Requires manual PTR, rDNS, TLS certs, IP warmup, feedback loops. | ★★ (Manual scripting, SMTP protocol maintenance). | **Strongly Discouraged:** Not viable for a small team starting out; deliverability will suffer immediately. |

### Strategic Recommendation for an Indian Startup / Small Team:

1. **Primary Infrastructure (Dual-Track Model):**
   - **For Opt-In Marketing & High-Volume Updates:** Use **Amazon SES (Mumbai `ap-south-1` region)**. At $10 per 100k emails, it offers the lowest cost in the market, exceptional uptime, and local data routing within India.
   - **For Targeted Cold B2B Outreach:** Use **Google Workspace accounts** on secondary domains (`.com`, `.in`, or `.co`), rotated through our custom queuing engine at 40–50 sends/day per account.
2. **Fallback Infrastructure:**
   - **SendGrid Essentials** configured as a hot secondary failover if Amazon SES experiences quota blocks or unexpected DNS outages.

---

# 8. Compliance & Deliverability Checklist

## 8.1 Technical DNS & Authentication Checklist

☐ **Dedicated Subdomain Architecture:** Never send bulk or outreach campaigns from the naked primary corporate domain (`company.com`). Always use dedicated sending domains or subdomains (e.g., `mail.company.com`, `outreach-company.com`).

☐ **SPF (Sender Policy Framework):**
- Syntactically validated TXT record published at the sending domain.
- Exactly one SPF record per domain (combining multiple mechanisms into `v=spf1 include:amazonses.com ~all`).
- Strict compliance with the 10-DNS-lookup limit (use SPF flattening if necessary).

☐ **DKIM (DomainKeys Identified Mail):**
- Minimum **2048-bit RSA key length** (1024-bit is obsolete and flagged by modern filters).
- Dual selector rotation support (e.g., `s1._domainkey.mail.company.com` and `s2._domainkey...`).
- Cryptographic signature covers all critical headers: `From`, `To`, `Subject`, `Date`, `Message-ID`, `List-Unsubscribe`.

☐ **DMARC (RFC 7489) & Alignment:**
- Published TXT record at `_dmarc.sendingdomain.com`: `v=DMARC1; p=none; rua=mailto:dmarc-reports@company.com; pct=100; adkim=r; aspf=r;`.
- Gradual progression strategy: Start at `p=none` for 30 days to collect aggregate reports, then transition to `p=quarantine`, and finally `p=reject`.
- **DMARC Alignment Verified:** The domain in the visible `From:` header must match the DKIM signing domain or the SPF return-path domain.

☐ **Custom Tracking & Return-Path Domain (CNAME Alignment):**
- Custom Return-Path configured (e.g., `bounce.mail.company.com` CNAME pointing to `feedback-smtp.ap-south-1.amazonses.com`).
- Custom SSL tracking domain (e.g., `track.mail.company.com`) replacing standard generic provider redirect links to preserve domain reputation.

☐ **FCrDNS (Forward-Confirmed Reverse DNS):**
- Verify that the sending server IP address resolves to a PTR hostname that matches the A record of the sending host.

## 8.2 Google, Yahoo & Microsoft Bulk Sender Mandates

☐ **RFC 8058 One-Click List-Unsubscribe:**
- Injected headers present in every bulk marketing message:

```
List-Unsubscribe: <https://app.company.com/api/v1/unsubscribe?token=xyz>, <mailto:unsub@mail.company.com?subject=unsubscribe>
List-Unsubscribe-Post: List-Unsubscribe=One-Click
```

☐ **Spam Rate Ceilings:**

- Active monitoring via **Google Postmaster Tools** maintaining user-reported spam rates strictly **below 0.10%** (and never crossing 0.30%).
- Registered IP ranges in **Microsoft SNDS (Smart Network Data Services)** and enrolled in **JMRP (Junk Mail Reporting Program)**.

☐ **TLS Transit Encryption:**

- Mandatory TLS 1.2 or TLS 1.3 encryption on all outgoing SMTP transport sockets.

## 8.3 Legal Frameworks: US, EU & India

*Diagram (Mermaid source)*

```
flowchart TD
    A[Incoming Recipient Record] --> B{Recipient Jurisdiction}
    B -- United States --> C[CAN-SPAM Act Rules]
    B -- European Union --> D[GDPR Strict Consent / Legitimate Interest]
    B -- India --> E[DPDP Act 2023 Explicit Consent]

    C --> C1[Include Physical Postal Address]
    C --> C2[Clear Opt-Out Honored in 10 Days]
    C --> C3[Accurate Non-Deceptive Header & Subject]

    D --> D1[Verify Prior Opt-In Consent or Documented B2B Legitimate Interest]
    D --> D2[Provide Right to Erasure & Crypto-Shredding]
    D --> D3[Maintain Data Processing Records Article 30]

    E --> E1[Section 4 & 6: Affirmative, Unbundled Consent Required]
    E --> E2[Section 2t: Work Email is Personal Data - No B2B Exemption]
    E --> E3[Instant Unconditional Consent Withdrawal]
```

### 1. India Digital Personal Data Protection (DPDP) Act, 2023:

- **No Blanket B2B Exemption:** Under Section 2(t), any corporate email that identifies a living individual (e.g., `firstname.lastname@company.com`) is classified as Digital Personal Data.
- **Affirmative, Unbundled Consent (Section 6):** Unsolicited commercial outreach using scraped or purchased lists violates the consent mandate. Every commercial communication requires verifiable, free, specific, informed, and unambiguous consent, preceded or accompanied by a clear notice.
- **Immediate Right of Withdrawal:** Unsubscribe mechanisms must be friction-free. Upon opt-out, data processing for marketing must cease immediately.
- **Severe Statutory Penalties:** Violations of consent provisions or failure to enforce data security carry financial penalties up to **₹50 crore to ₹250 crore** imposed by the Data Protection Board of India (DPBI).

### 2. United States CAN-SPAM Act:

- Truthful headers and routing information: `From`, `To`, and `Reply-To` must accurately identify the sender.
- Subject lines must not be deceptive or misleading.
- Conspicuous inclusion of a valid physical postal address of the sender.
- Clear, functioning opt-out mechanism honored within **10 business days**.
- Global suppression list integration ensuring unsubscribed contacts never receive future promotional messages.

### 3. EU General Data Protection Regulation (GDPR):

- Lawful basis: Demonstrable freely given opt-in consent, or a rigorous, documented Legitimate Interest Assessment (LIA) for strictly relevant B2B communications.

- Right to Erasure ("Right to be Forgotten"): Capability to completely purge a contact's data upon request while retaining their hashed email (`SHA-256`) in an immutable suppression list to prevent accidental re-import.

---

# 9. Claude Opus & Anthropic API Integration Architecture

## 9.1 Multi-Model Allocation & Cost Optimization Matrix

To build an enterprise-grade AI system without incurring unsustainable API bills, tasks are divided across model tiers based on complexity:

| Task | Recommended Model | Input / Output Tokens per Run | Est. Cost per 1,000 Contacts | Caching & Batching Strategy |
|---|---|---|---|---|
| **High-Risk Spam & Deliverability Audit** | **Claude 3 Opus** / Claude 3.5 Sonnet | ~1,500 in / 400 out | ~$0.08 (Sonnet) or ~$0.50 (Opus) | Run once per campaign template before launch. Prompt caching applied to deliverability rules. |
| **High-Converting Subject Line Variants** | **Claude 3.5 Sonnet** | ~800 in / 300 out | ~$0.015 per template | Evaluated once during campaign setup. Generates 5 distinct A/B options. |
| **Per-Contact Icebreaker / Line Personalization** | **Claude 3.5 Haiku** (or Sonnet for VIP leads) | ~600 in / 80 out | **$0.40 / 1,000 leads** (via Batch API) | **Anthropic Message Batches API:** 50% flat discount + asynchronous processing overnight before send window opens. |
| **Inbound Reply Intent Classification** | **Claude 3.5 Haiku** | ~400 in / 30 out | **$0.12 / 1,000 replies** | Event-driven trigger on incoming IMAP/webhook email. Single-token classification output. |

## 9.2 Cost Control & Security Safeguards

1. **Server-Side Token Isolation:** The Anthropic API key is stored strictly on the server in encrypted environment variables or HashiCorp Vault. It is never transmitted to the browser client.
2. **Campaign-Level Token Spend Caps:** Administrators can configure a hard financial limit (e.g., "$15.00 max AI spend for this campaign"). If the cap is reached, personalization falls back automatically to standard merge variables without interrupting delivery.
3. **Prompt Caching (`cache_control`):** Static context—such as sender company bio, target persona guidelines, and compliance rules—is marked with `ephemeral` cache headers, cutting input token costs by up to **90%** on recurring calls.
4. **Human-in-the-Loop Approval Queue:** When AI personalizes lines or drafts, the campaign builder displays a side-by-side review interface. Users can inspect the generated drafts, edit copy in real time, or click "Approve All" before items enter the active send queue.

## 9.3 Production Prompt Specifications

### Prompt 1: Deliverability & Spam-Risk Scoring (Claude 3.5 Sonnet / Opus)

```
System:
You are an elite email deliverability engineer and Bayesian spam filter specialist. Your task is to analyze email copy and evaluate its likelihood of triggering spam filters (SpamAssassin, Google Postmaster AI, Microsoft SmartScreen) or provoking user complaints.

Output strictly valid JSON conforming to the following TypeScript interface:
interface DeliverabilityAnalysis {
  risk_score: number; // 0 to 100, where 0 is pristine and 100 is definite spam
  verdict: "safe" | "moderate_risk" | "high_risk" | "critical";
  spam_trigger_words: string[];
  link_and_image_assessment: string;
  tone_and_intent_review: string;
  concrete_suggestions: string[];
  optimized_alternative_body: string;
}

User:
Analyze the following email campaign draft:

Subject: {{subject}}
Body Content:
{{body_content}}
```

### Prompt 2: Contextual Contact Personalization (Claude 3.5 Haiku / Sonnet via Batch API)

```
System:
You are a senior B2B sales copywriter writing personalized cold outreach.
Rules:
1. Generate a single, concise introductory sentence (max 25 words).
2. Ground the observation strictly in the provided contact and company attributes.
3. Avoid generic pleasantries ("I hope this finds you well", "Congrats on the success").
4. Sound natural, human, peer-to-peer, and relevant.

Output strictly valid JSON:
{
  "personalized_opener": "...",
  "confidence_score": 0.95
}

User:
Contact Data:
- First Name: {{first_name}}
- Company: {{company}}
- Job Title: {{title}}
- Industry/Niche: {{industry}}
- Recent Company News/Custom Data: {{custom_fields_notes}}
```

### Prompt 3: Inbound Reply Intent Classifier (Claude 3.5 Haiku)

```
System:
You are an inbound email intent classifier. Categorize the incoming email reply into exactly one category.

Categories:
- "INTERESTED": Lead is asking for a meeting, more info, demo, or showing curiosity.
- "NOT_INTERESTED": Explicit polite or impolite decline ("not right now", "no thanks", "remove me").
- "OUT_OF_OFFICE": Automated vacation responder or temporary unavailability.
- "UNSUBSCRIBE": Contact explicitly demands removal from database or threatens legal/complaint action.
- "AMBIGUOUS": Neutral acknowledgment or forward to another team member.

Output strictly valid JSON:
{
  "category": "INTERESTED" | "NOT_INTERESTED" | "OUT_OF_OFFICE" | "UNSUBSCRIBE" | "AMBIGUOUS",
  "confidence": number,
  "suggested_action": "pause_sequence" | "stop_and_suppress" | "schedule_task" | "resume_later",
  "suggested_draft_reply": string | null
}


User:
Original Email Sent:
"{{sent_body}}"

Incoming Reply Received:
"{{reply_body}}"
```

---

# 10. Phased Implementation Roadmap

Estimated timeline for an agile engineering team (1 Senior Fullstack Engineer + 1 Backend/Infra Engineer):



```
+-------------------------------------------------------------------------------+
```

## Sprint Breakdown:

### Milestone 1: Core Foundation & Data Hygiene (Weeks 1 – 2)

- **Week 1:**
  - Setup repository, Next.js 15 app structure, PostgreSQL database with Prisma/Drizzle schema.
  - Implement Auth.js session management, organization multi-tenancy, and AES-256 encrypted credential storage.
  - Build bulk CSV/XLSX uploader with draggable column-mapping interface.
- **Week 2:**
  - Build ingestion verification engine: duplicate removal, regex syntax checking, disposable email filter, and async DNS MX validator.
  - Create list segmentation and contact status tracking tables.

### Milestone 2: Queue Engine & Sending Infrastructure (Weeks 3 – 4)

- **Week 3:**
  - Deploy Redis and setup BullMQ job queue infrastructure.
  - Implement token-bucket sliding-window rate limiters (per-account hourly/daily caps, jitter calculations).
  - Build sending window gatekeeper (evaluating recipient timezone schedules).
- **Week 4:**
  - Integrate Amazon SES v3 SDK.
  - Configure SNS webhook consumers for automated bounce (`Permanent` vs `Transient`) and complaint processing.
  - Build the automated circuit breaker (auto-pausing campaigns if bounce rate > 3%).

### Milestone 3: Sequence Builder & Deliverability Framework (Weeks 5 – 6)

- **Week 5:**
  - Develop multi-step sequence builder with plain-text & HTML editors, fallback variables, and preview modes.
  - Integrate secondary sending rail (Google Workspace OAuth 2.0 / SMTP relay adapter).
  - Implement RFC 8058 One-Click Unsubscribe headers and automated global suppression list management.
- **Week 6:**
  - Build DNS health-check validator (querying live DNS for SPF, DKIM, and DMARC alignment status).
  - Implement multi-account rotation logic (round-robin dispatching across active mailboxes).
  - Implement linear warm-up ramp algorithm.

### Milestone 4: Claude AI Suite, Analytics & Hardening (Weeks 7 – 8)

- **Week 7:**
  - Connect Anthropic TypeScript SDK with Prompt Caching and Message Batches API.
  - Build the template spam-risk analyzer and contextual personalization wizard.
  - Create human-in-the-loop review interface for AI drafts.
- **Week 8:**
  - Implement inbound IMAP reply listener and automated sequence termination upon response.

- Integrate Claude Haiku reply classifier (`Interested`, `Not Interested`, `OOO`).
- Build analytics dashboard (conversion funnel, bounce rates, open/reply telemetry) with CSV export.
- Perform end-to-end stress testing with 50,000 synthetic contacts. Deploy to staging/production.

---

# 11. Security, Idempotency & Reliability Architecture

1. **Strict Send Idempotency:**
   - Every send job generates a deterministic idempotency key prior to dispatch: `idempotency:{campaign_id}:{step_id}:{contact_id}`.
   - Before any SMTP socket or API request is opened, the worker issues an atomic `SET NX` in Redis. If the key already exists, the job is discarded immediately, preventing double-sends even during worker crashes or database reconnections.
2. **Crash Recovery & Job Heartbeats:**
   - BullMQ stalled-job timers continuously monitor active workers. If a worker container crashes mid-send, unacknowledged jobs are automatically recovered and reassigned after lock expiration without data loss.
3. **Data Protection & Crypto-Shredding:**
   - Sensitive third-party API credentials are encrypted at rest using AES-256-GCM with PBKDF2 key derivation.
   - Contact deletion requests execute a soft-delete on identifiable records and write a cryptographic hash (`SHA-256(workspace_id + email)`) into the permanent suppression table, fulfilling GDPR/DPDP erasure compliance while ensuring the contact is never re-emailed.

---

# 12. Strategic Summary: Why This Architecture Protects Your Business

| Risk | The Common Mistake | How Our Platform Mitigates the Risk |
|---|---|---|
| **Primary Domain Blacklisting** | Sending cold outreach or high-volume newsletters from `mycompany.com`. | Enforces strict isolation: cold outreach uses rotated secondary domains; bulk campaigns use dedicated subdomains with distinct SPF/DKIM keys. |
| **Provider Account Termination** | Exceeding bounce or spam complaint rates on Amazon SES or Google Workspace. | Automated circuit breakers stop campaigns automatically if bounces exceed 3% or complaints exceed 0.15% before provider thresholds are crossed. |
| **Runaway AI Costs** | Invoking un-cached, synchronous Claude Opus calls for tens of thousands of rows. | Tiered model strategy: Claude 3.5 Haiku via Anthropic Message Batches API cuts costs by 90%; hard per-campaign financial caps prevent budget overruns. |
| **DPDP Act (India) Regulatory Exposure** | Scraping contacts without affirmative consent and lack of immediate opt-out. | Enforces clear consent tracking fields per contact, automated one-click unsubscribe headers, and verifiable withdrawal logs. |