

# **Tutorial of vinardo score calculation by MolAICal**

Qifeng Bai

Email: [molaical@yeah.net](mailto:molaical@yeah.net)

Homepage: <https://molaical.github.io>

School of Basic Medical Sciences

Lanzhou University

Lanzhou, Gansu 730000, P. R. China

## 1. Introduction

Scoring function can be used to evaluate binding ability between ligands and receptors. In this tutorial, the vinardo score is introduced to calculate binding score of ligands based on the grid file of SARS-CoV-2 M<sup>pro</sup>. The SARS-CoV-2 M<sup>pro</sup> which leads to the rapid spread of coronavirus disease 2019 (COVID-19) throughout the world is selected as the example target. This example can be generalized to other targets. You can refer to these two papers (<https://doi.org/10.1093/bib/bbaa161> and <https://doi.org/10.1371/journal.pone.0155183>) for the introduction of vinardo score.

## 2. Materials

### 2.1. Software requirement

1) MolAICal: <https://molaical.github.io>

### 2.2. Example files

1) All the necessary tutorial files are downloaded from:

<https://github.com/MolAICal/tutorials/tree/master/008-vinardoScore>

## 3. Procedure

Before calculating the vinardo score of ligand, the grid file of the receptor should be generated.

```
#> cd 008-vinardoScore
```

1) Create a file named “boxPar.dat”. The first line contains the coordinates of the box center. The second line contains the box lengths. It is like below:

```
-----  
-10.733 12.416 68.829  
30.0 30.0 30.0  
-----
```

2) Running command for generating the grid file of protein

```
#> molaical.exe -tool grid -i boxPar.dat -p mproNolig.pdb -n vinardoScore
```

The “mproNolig.pdb” is the PDB format file of SARS-CoV-2 M<sup>pro</sup> without ligand. It will generate the grid file named “vinardoScore.dat”

3) Calculating vinardo score of single ligand

```
#> molaical.exe -tool vinardo -i ligands/lig_1.mol2 -g vinardoScore.dat -t vinardoscore
```

It outputs like: Binding Score: -6.21 kcal/mol

**If you want to calculate vinardo score for many ligands in bulk, you can do it below steps:**

```
#> cd 008-vinardoScore/ligands
```

1. Using command “ls > ligandList.dat” in Linux console, or “dir /b > ligandList.dat” in Windows DOS console of Window. Open generated file “ligandList.dat” and delete no useful characters. For example, delete the first line contained characters “ligandList.dat”. Make sure the file “ligandList.dat” only contains the ligand names.

2. Run command as below:

```
#> molaical.exe -score vinardo -i ligands/ligandList.dat -o output.dat -g vinardoScore.dat
```

It will generate the file named “output.dat” which contains binding scores of ligands in bulk.