Prüfbericht-Nr.: *Test report no.*:	**CN23RCT9 001**	**Auftrags-Nr.:** *Order no.*:	180270222	Seite 1 von 52 *Page 1 of 52*
Kunden-Referenz-Nr.: *Client reference no.*:	N/A	**Auftragsdatum:** *Order date:*	2023-08-28	
Auftraggeber: *Client*:	Huizhou Duran Creative Technology CO.,LTD. 7 Floor, Innovation Building, Science and Technology Zone, Shihua Avenue, Dayawan District, Huizhou city, Guangdong P.R.China.			
Prüfgegenstand: *Test item*:	Portable Light			
Bezeichnung / Typ-Nr.: *Identification / Type no.*:	G-001			
Auftrags-Inhalt: *Order content*:	Test report			
Prüfgrundlage: *Test specification*:	EN IEC 60598-1:2021+A11 EN 60598-2-4:2018 EN 62471:2008 EN 62493:2015			

Wareneingangsdatum: *Date of sample receipt*:	2023-08-28
Prüfmuster-Nr.: *Test sample no:*	A003548920
Prüfzeitraum: *Testing period*:	2023-08-28 - 2023-11-21
Ort der Prüfung: *Place of testing*:	TÜV Rheinland/CCIC (Ningbo)Co.,Ltd.
Prüflaboratorium: *Testing laboratory:*	TÜV Rheinland/CCIC (Ningbo)Co.,Ltd.
Prüfergebnis*: *Test result**:	Pass



geprüft von: tested by:	X Zeen Xu	**genehmigt von:** *authorized by*:	X ChengChao Huang
Datum: *Date:*	2023-11-27	**Ausstellungsdatum:** *Issue date:*	2023-11-27
Stellung / Position:	Project Engineer	**Stellung** / Position:	Reviewer

Sonstiges / *Other*: Issue test report

Zustand des Prüfgegenstandes bei Anlieferung: *Condition of the test item at delivery*: Prüfmuster vollständig und unbeschädigt *Test item complete and undamaged*

* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* *Legend:*	*P(ass) = passed a.m. test specification(s)*	*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.
V05

Prüfbericht-Nr.: CN23RCT9 001
Test report no.:

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. *The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.*
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. *As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.*
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. *Test clauses with remark of * are subcontracted to qualified subcontractors and descripted under the respective test clause in the report.* *Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.*
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnisen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezueglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the “Zero Guard Band Rule” and “Simple Acceptance” in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.

www.tuv.com

Test Report issued under the responsibility of:

TÜVRheinland®

TEST REPORT
IEC 60598-2-4
Luminaires
Luminaires, Part 2: Particular requirements
Section 4: Portable general purpose luminaires

Report Number..... :	CN23RCT9 001
Date of issue..... :	See cover page
Total number of pages..... :	See cover page
Name of Testing Laboratory preparing the Report ..... :	TÜV Rheinland / CCIC (Ningbo) Co., Ltd. 3F, Building C13, R&D Park, No.32 Lane 299 Guanghua Road, Na-tional Hi-Tech Zone, Ningbo 315048, P.R. China.
Applicant's name..... :	Huizhou Duran Creative Technology CO.,LTD.
Address..... :	7 Floor, Innovation Building, Science and Technology Zone, Shihua Avenue, Dayawan District, Huizhou city, Guangdong P.R.China.
Test specification:	
Standard..... :	IEC 60598-2-4:2017 for use in conjunction with IEC 60598-1:2020
Test procedure..... :	Test report
Non-standard test method ..... :	N/A
TRF template used ..... :	IECEE OD-2020-F1:2020, Ed.1.3
Test Report Form No. ..... :	IEC60598_2_4I
Test Report Form(s) Originator.... :	UL (US)
Master TRF ..... :	Dated 2021-06-10

Copyright © 2021 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

This report is not valid as a CB Test Report unless signed by an approved IECEE Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.

General disclaimer:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing NCB. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.

Test item description.....:		Portable Light	
Trade Mark(s).....:		N/A	
Manufacturer.....:		Huizhou Duran Creative Technology CO.,LTD. 7 Floor, Innovation Building, Science and Technology Zone, Shihua Avenue, Dayawan District, Huizhou city, Guangdong P.R.China.	
Model/Type reference.....:		G-001	
Ratings.....:		Input: Battery(DC 9V); 1W; IP54; Ta: 35°C; Class III. Others see “General product information”	
Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):			
☒	**Testing Laboratory:**	TÜV Rheinland /CCIC(Ningbo) Co., Ltd.	
Testing location/ address .....:		3F, Building C13, R&D Park, No.32 Lane 299 Guanghua Road, National Hi-Tech Zone, Ningbo 315048, P.R.China.	
Tested by (name, function, signature).....:		See cover page	
Approved by (name, function, signature) :		See cover page	
☐	**Testing procedure: CTF Stage 1:**	N/A	
Testing location/ address .....:		N/A	
Tested by (name, function, signature).....:		N/A	
Approved by (name, function, signature) :		N/A	
☐	**Testing procedure: CTF Stage 2:**	N/A	
Testing location/ address .....:		N/A	
Tested by (name + signature) .....:		N/A	
Witnessed by (name, function, signature):		N/A	
Approved by (name, function, signature) :		N/A	
☐	**Testing procedure: CTF Stage 3:**	N/A	
☐	**Testing procedure: CTF Stage 4:**	N/A	
Testing location/ address .....:		N/A	
Tested by (name, function, signature).....:		N/A	
Witnessed by (name, function, signature):		N/A	
Approved by (name, function, signature) :		N/A	
Supervised by (name, function, signature):		N/A	

List of Attachments (including a total number of pages in each attachment):

Attachment 1: Acceptance test for Control gear according to EN 61347-2-11:2001+A1:2019 used conjunction with EN 61347-1:2015+A1. (Total 36 pages)
Attachment 2: Photo Document. (Total 14 pages)

According to the standard EN 62493:2015, the DUT belongs to unintentional radiating part of lighting equipment. Due to the reason that the DUT fulfils the inherent-compliance condition "It is a LED-light-source technology", the DUT is deemed to comply with requirements of this standard without testing.

Summary of testing:

Tests performed (name of test and test clause):	**Testing location:**
Model G-001 was selected to perform all testing except Clause 4.14.1. The LED module as an integral LED module was tested according to EN IEC 62031: 2020 + A11: 2021 see page 49. Assessment of blue light hazard to light sources and luminaires according to IEC TR 62778:2014 see page 50-52.	TÜV Rheinland / CCIC (Ningbo) Co., Ltd. 3F, Building C13, R&D Park, No.32 Lane 299 Guanghua Road, National Hi-Tech Zone, Ningbo 315048, P.R.China.

Summary of compliance with National Differences (List of countries addressed):

EU Group Difference.

The product fulfils the requirements of EN 60598-2-4:2018 used in conjunction with EN IEC 60598-1:2021 + A11.

Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

☒ **Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:**

Procedure number, issue date and title: MS-0007539/ Nov 27, 2020/Evaluation of Measurement Uncertainty in Laboratory and Decision Rule.

Calculations leading to the reported values are on file with the NCB and testing laboratory that conducted the testing.

☐ **Statement not required by the standard used for type testing**

(Note: When IEC or ISO standard requires a statement concerning the uncertainty of the measurement systems used for tests, this should be reported above. The informative text in parenthesis should be delete in both cases after selecting the applicable option)

Copy of marking plate:

English version:

G-001 Battery (DC 9V); 1W; LED; CCT: 1800-2000K; IP54; Ta: 35°C.



Made in China

Huizhou Duran Creative Technology CO.,LTD.

7 Floor, Innovation Building, Science and Technology Zone, Shihua Avenue,
Dayawan District, Huizhou city, Guangdong P.R.China.

Test item particulars.....:	Portable Light
Classification of installation and use.....:	Class III, IP54
Supply Connection.....:	--
.....:	
Possible test case verdicts:	
- test case does not apply to the test object..... :	N/A
- test object does meet the requirement ..... :	P (Pass)
- test object does not meet the requirement..... :	F (Fail)
Testing ..... :	
Date of receipt of test item ..... :	See cover page
Date (s) of performance of tests ..... :	See cover page

General remarks:

"(See Enclosure #)" refers to additional information appended to the report.
"(See appended table)" refers to a table appended to the report.

Throughout this report a ☒ comma / ☐ point is used as the decimal separator.

Clause numbers between brackets refer to clauses in IEC 60598-1

Manufacturer's Declaration per sub-clause 4.2.5 of IECEE 02:

The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided.....:	☐ **Yes** ☒ **Not applicable**

When differences exist; they shall be identified in the General product information section.

Name and address of factory (ies).....:	**HUIZHOU LIDAFENG TECHNOLOGY CO., LTD.** **Workshop Building II, Shunju Industry Zone Chayuan Village, Qiuchang Town, Huiyang District 516221, Huizhou, Guangdong P.R.China.**

General product information and other remarks:

The testing appliance is Portable Light with non-user replaceable light source, IP degree is IP54.
Class III, Ta: 35°C; CT: 1800-2000K.
Details as below table:

Model name	Parameter	Rated wattage	PCB No.	LED board no.	LED quantity
G-001	Battery(DC 9V)	1W	227668G_Y138	AQL-DSLEDV2.6	8PCS

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.4 (0)	**GENERAL TEST REQUIREMENTS**		P
4.4 (0.3)	More sections applicable..... :	Yes ☐ No ☒ Section/s:	—
4.4 (0.5)	Components	below	—
4.4 (0.7)	**Information for luminaire design in light sources standards**		—
4.4 (0.7.2)	Light source safety standard ..... :	EN IEC 62031	—
	Luminaire design in the light source safety standard		P

4.5 (2)	**CLASSIFICATION OF LUMINAIRES**		P
4.5 (2.2)	Type of protection ..... :	Class III	P
4.5 (2.3)	Degree of protection..... :	IP 54	—
4.5 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces ..... :	Yes ☒ No ☐	
4.5 (2.5)	Luminaire for normal use ..... :	Yes ☒ No ☐	—
	Luminaire for rough service ..... :	Yes ☐ No ☒	—
4.5.1 (-)	Ordinary luminaire classified “for indoor use only” .. :	Yes ☐ No ☒	—
	Luminaires other than ordinary classified “for indoor use only”..... :	Yes ☐ No ☒	—
	Luminaires other than ordinary classified for “outdoor use” and “for indoor use”..... :	Yes ☒ No ☐	—
4.5.2 (-)	Portable luminaire for outdoor use classified IPX4 or higher	IPX4	P
4.5.3 (-)	Luminaires designed for standing on a floor or table classified as suitable for direct mounting on normally flammable surfaces		N/A

4.6 (3)	**MARKING**		P
4.6 (3.2)	Mandatory markings		P
	Position of the marking	Rating label stuck on the enclosure	P
	Format of symbols/text	Height of letter and symbol is enough	P
4.6 (3.3)	Additional information	See instruction manual	P
	Language of instructions	English version	P
4.6 (3.3.1)	Combination luminaires		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.6 (3.3.2)	Nominal frequency in Hz	DC	N/A
4.6 (3.3.3)	Operating temperature	35°C	P
4.6 (3.3.5)	Wiring diagram		N/A
4.6 (3.3.6)	Special conditions		N/A
4.6 (3.3.7)	Metal halide lamp luminaire – warning		N/A
4.6 (3.3.8)	Limitation for semi-luminaires		N/A
4.6 (3.3.9)	Power factor and supply current		P
4.6 (3.3.10)	Suitability for use indoors	IP54	N/A
4.6 (3.3.11)	Luminaires with remote control		P
4.6 (3.3.12)	Clip-mounted luminaire – warning		N/A
4.6 (3.3.13)	Specifications of protective shields		N/A
4.6 (3.3.14)	Symbol for nature of supply		N/A
4.6 (3.3.15)	Rated current of socket outlet		N/A
4.6 (3.3.16)	Rough service luminaire		N/A
4.6 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments		N/A
4.6 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A
4.6 (3.3.19)	Protective conductor current in instruction if applicable		N/A
4.6 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N/A
4.6 (3.3.21)	Non replaceable and non-user replaceable light sources information provided	Non-user replaceable light sources	P
4.6 (3.3.22)	Controllable luminaires, classification of insulation provided		N/A
4.6 (3.3.23)	Luminaires without controlgear provided with necessary information for selection of appropriate component		N/A
4.6 (3.3.24)	If not supplied with terminal block, information on the packaging		N/A
4.6 (3.3.25)	Luminaires employing light sources emitting UV on mains wiring, information provided		N/A
4.6 (3.3.26)	Wall mounted luminaire using external flexible cable or cord longer than 0.3 m, information provided		N/A
4.6 (3.4)	Test with water	15s	P

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Test with hexane	15s	P
	Legible after test		P
	Label attached	Not be easily removable, show no curling	P
4.6.1 (-)	Luminaire not suitable for outdoor application		P
	Required symbol		P
	Information in the instructions		P
4.6.2 (-)	Outdoor use, socket outlet incorporated in the luminaire		N/A
	Maximum power rating marked		N/A
	Position of the marking		N/A
4.7 (4)	**CONSTRUCTION**		P
4.7 (4.2)	Components replaceable without difficulty		N/A
4.7 (4.3)	Wireways smooth and free from sharp edges		P
4.7 (4.4)	**Lampholders**		**N/A**
4.7 (4.4.1)	Integral lampholder		N/A
4.7 (4.4.2)	Wiring connection		N/A
4.7 (4.4.3)	Lampholder for end-to-end mounting		N/A
4.7 (4.4.4)	Positioning		N/A
	- pressure test (N) ..... :		—
	After test the lampholder comply with relevant standard sheets and show no damage		N/A
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N/A
	- bending test (N) ..... :		—
	After test the lampholder has not moved from its position and show no permanent deformation		N/A
4.7 (4.4.5)	Peak pulse voltage		N/A
4.7 (4.4.6)	Centre contact		N/A
4.7 (4.4.7)	Parts in rough service luminaires resistant to tracking		N/A
4.7 (4.4.8)	Lamp connectors		N/A
4.7 (4.4.9)	Caps and bases correctly used		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N/A
4.7 (4.5)	**Starter holders**		**N/A**
	Starter holder in luminaires other than class II		N/A
	Starter holder class II construction		N/A
4.7 (4.6)	**Terminal blocks**		**N/A**
	Tails		N/A
	Unsecured blocks		N/A
4.7 (4.7)	**Terminals and supply connections**		**N/A**
4.7 (4.7.1)	Contact to metal parts		N/A
4.7 (4.7.2)	Test 8 mm live conductor		N/A
	Test 8 mm earth conductor		N/A
4.7 (4.7.3)	Terminals for supply conductors		N/A
4.7 (4.7.3.1)	Welded method and material		N/A
	- stranded or solid conductor		N/A
	- spot welding		N/A
	- welding between wires		N/A
	- Type Z attachment		N/A
	- mechanical test according to 15.6.2		N/A
	- electrical test according to 15.6.3		N/A
	- heat test according to 15.6.3.2.3 and 15.6.3.2.4		N/A
4.7 (4.7.4)	Terminals other than supply connection		N/A
4.7 (4.7.5)	Heat-resistant wiring/sleeves		N/A
4.7 (4.7.6)	Multi-pole plug		N/A
	- test at 30 N		N/A
4.7 (4.8)	**Switches**		**P**
	- adequate rating		P
	- adequate fixing		P
	- polarized supply		P
	- compliance with IEC 61058-1 for electronic switches		N/A
4.7 (4.9)	**Insulating lining and sleeves**		**P**
4.7 (4.9.1)	Retainment		P

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Method of fixing ..... :	Heat-shrinkable tube	P
4.7 (4.9.2)	Insulated linings and sleeves:		P
	Resistant to a temperature > 20 °C to the wire temperature or		P
	a) & c) Insulation resistance and electric strength		N/A
	b) Ageing test. Temperature (°C)..... :		N/A
4.7 (4.10)	**Double or reinforced insulation**		**N/A**
4.7 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		N/A
	Safe installation fixed luminaires		N/A
	Capacitors and switches		N/A
4.7 (4.10.2)	Assembly gaps:		N/A
	- not coincidental		N/A
	- no straight access with test probe		N/A
4.7 (4.10.3)	Retainment of insulation:		N/A
	- fixed		N/A
	- unable to be replaced; luminaire inoperative		N/A
	- sleeves retained in position		N/A
	- lining in lampholder		N/A
4.7 (4.10.4)	Protective impedance device		N/A
	Basic and supplementary insulation bridged by resistor(s) or appropriate capacitor		N/A
	Double or reinforced insulation bridged by at least two separate resistors in series or appropriate capacitor(s)		N/A
	Capacitors comply with IEC 60384-14		N/A
	Resistors comply with test (a) in 14.2 of IEC 60065		N/A
4.7 (4.11)	**Electrical connections and current-carrying parts**		**P**
4.7 (4.11.1)	Contact pressure	Compliance check	P
4.7 (4.11.2)	Screws:		P
	- self-tapping screws		P
	- thread-cutting screws		P
4.7 (4.11.3)	Screw locking:		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- spring washer		N/A
	- rivets		N/A
4.7 (4.11.4)	Material of current-carrying parts		P
4.7 (4.14.7)	No contact to wood or mounting surface		P
4.7 (4.14.7)	Electro-mechanical contact systems		N/A
4.7 (4.12)	**Screws and connections (mechanical) and glands**		**P**
4.7 (4.12.1)	Screws not made of soft metal		P
	Screws of insulating material		N/A
	Torque test: torque (Nm); part ..... :	Fixed LED board: 0,4Nm	P
	Torque test: torque (Nm); part ..... :		N/A
	Torque test: torque (Nm); part ..... :		N/A
4.7 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N/A
4.7 (4.12.4)	Locked connections:		N/A
	- fixed arms; torque (Nm)..... :		N/A
	- lampholder; torque (Nm)..... :		N/A
	- push-button switches; torque 0,8 Nm..... :		N/A
4.7 (4.12.5)	Screwed glands; force (Nm)..... :		N/A
4.7 (4.13)	**Mechanical strength**		**P**
4.7 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm)..... :	No fragile parts	N/A
	- other parts; energy (Nm) ..... :	0,35Nm for enclosure, cover.	P
	1) live parts	Not have become accessible	P
	2) linings	Not have been impaired	P
	3) protection	Continue to afford the degree of the degree of protection	P
	4) covers	No breaking	P
4.7 (4.13.2)	Metal parts have adequate mechanical strength		P
4.7 (4.13.3)	Straight test finger	30N	P
4.7 (4.13.4)	Rough service luminaires		N/A
	- IP54 or higher		N/A
	a) fixed		N/A
	b) hand-held		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	c) delivered with a stand		N/A
	d) for temporary installations and suitable for mounting on a stand		N/A
4.7 (4.13.6)	Tumbling barrel		N/A
4.7 (4.14)	**Suspensions, fixings and means of adjusting**		**N/A**
4.7 (4.14.1)	Mechanical load:		N/A
	A) four times the weight	Not require by applicant	N/A
	B) torque 2,5 Nm		N/A
	C) bracket arm; bending moment (Nm)..... :		N/A
	D) load track-mounted luminaires		N/A
	E) clip-mounted luminaires, glass-shelve. Thickness (mm) ..... :		N/A
	Metal rod. diameter (mm) ..... :		N/A
	Fixed luminaire or independent control gear without fixing devices		N/A
4.7 (4.14.2)	Load to flexible cables		N/A
	Mass (kg) ..... :		—
	Stress in conductors (N/mm²) ..... :		N/A
	Mass (kg) of semi-luminaire ..... :		N/A
	Bending moment (Nm) of semi-luminaire ..... :		N/A
4.7 (4.14.3)	Adjusting devices:		N/A
	- flexing test; number of cycles..... :		N/A
	- strands broken..... :		N/A
	- electric strength test afterwards		P
4.7 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N/A
4.7 (4.14.5)	Guide pulleys		N/A
4.7 (4.14.6)	Strain on socket-outlets		N/A
4.7 (4.15)	**Flammable materials**		**P**
	- glow-wire test 650°C..... :	See Test Table 1.15 (13.3.2)	N/A
	- spacing ≥30 mm		N/A
	- screen withstanding test of 13.3.1		N/A
	- screen dimensions		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- no fiercely burning material		P
	- thermal protection		N/A
	- electronic circuits exempted		N/A
4.7 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N/A
	a) construction		N/A
	b) temperature sensing control		N/A
	c) surface temperature		N/A
4.7 (4.16)	**Luminaires for mounting on normally flammable surfaces**		**P**
	No lamp control gear ..... :	(compliance with Section 12)	N/A
	Provided with adaptor for a track meet the requirements for direct mounting on normally flammable surfaces		N/A
4.7 (4.16.1)	Lamp control gear spacing:		P
	- spacing 35 mm		N/A
	- spacing 10 mm		P
4.7 (4.16.2)	Thermal protection:		N/A
	- in lamp control gear		N/A
	- external		N/A
	- fixed position		N/A
	- temperature marked lamp control gear		N/A
4.7 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N/A
4.7 (4.17)	**Drain holes**		**N/A**
	Clearance at least 5 mm		N/A
4.7 (4.18)	**Resistance to corrosion**		**N/A**
4.7 (4.18.1)	- rust-resistance		N/A
4.7 (4.18.2)	- season cracking in copper		N/A
4.7 (4.18.3)	- corrosion of aluminium		N/A
4.7 (4.19)	Ignitors compatible with ballast		N/A
4.7 (4.20)	Rough service vibration		N/A
4.7 (4.21)	**Protective shield**		**N/A**
4.7 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N/A
	Shield of glass if tungsten halogen lamps		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.21.2)	Particles from a shattering lamp not impair safety		N/A
4.7 (4.21.3)	No direct path		N/A
4.7 (4.21.4)	Impact test on shield		N/A
	Glow-wire test on lamp compartment ..... :	See Test Table 1.15 (13.3.2)	N/A
4.7 (4.22)	Attachments to lamps not cause overheating or damage		N/A
4.7 (4.23)	Semi-luminaires comply Class II		N/A
4.7 (4.24)	**Photobiological hazards**		**P**
4.7 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		N/A
4.7 (4.24.2)	Retinal blue light hazard		P
	Class of risk group assessed according to IEC/TR 62778 ..... :	RG0	—
	Luminaires with E_{thr} :		N/A
	a) Fixed luminaires		N/A
	- distance x m, borderline between RG1 and RG2.. :		N/A
	- marking and instruction according 3.2.23		N/A
	b) Portable and handheld luminaires		N/A
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N/A
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N/A
4.7 (4.25)	**Mechanical hazard**		**P**
	No sharp point or edges		P
4.7 (4.26)	**Short-circuit protection**		**N/A**
4.7 (4.26.1)	Adequate means of uninsulated accessible SELV or PELV parts		N/A
4.7 (4.26.2)	Short-circuit test with test chain according 4.26.3		N/A
	Supply source ES1 PSE		N/A
	Test chain not melt through		N/A
	Test sample not exceed values of Table 12.1 and 12.2		N/A
4.7 (4.27)	**Terminal blocks with integrated screwless protective earthing contacts**		**N/A**
	Test according Annex V		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Pull test of terminal fixing (20 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Pull test of mechanical connection (50 N)		N/A
	After test, resistance < 0,05 Ω		N/A
	Voltage drop test, resistance < 0,05 Ω		N/A
4.7 (4.28)	**Fixing of thermal sensing control**		**N/A**
	Not plug-in or easily replaceable type		N/A
	Reliably kept in position		N/A
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N/A
	Not outside the luminaire enclosure		N/A
	Test of adhesive fixing:		N/A
	Max. temperature on adhesive material (°C) ..... :		—
	100 cycles between t_{min} and t_{max}		N/A
	Temperature sensing control still in position		N/A
4.7 (4.29)	**Luminaires with non-replaceable light source**		**N/A**
	Not possible to replace light source		N/A
	Live part not accessible after parts have been opened by hand or tools		N/A
4.7 (4.30)	**Luminaires with non-user replaceable light source**		**P**
	If protective cover provide protection against electric shock and marked with “caution, electric shock risk” symbol:		N/A
	At least one fixing means requiring use of tool		P
4.7 (4.31)	**Insulation between circuits**		**P**
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		P
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		N/A
4.7 (4.31.1)	SELV or PELV circuits		N/A
	Used SELV or PELV source		N/A
+	Voltage ≤ ELV		N/A
	Insulating of SELV or PELV circuits from LV supply		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Insulating of SELV or PELV circuits from other non SELV or PELV circuits		N/A
	Insulating of SELV or PELV circuits from FELV		N/A
	Insulating of SELV or PELV circuits from other SELV or PELV circuits		N/A
	SELV or PELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to make any electrical contact with socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Plugs and socket-outlets does not have protective conductor contact		N/A
4.7 (4.31.2)	FELV circuits		N/A
	Used FELV source		N/A
	Voltage ≤ ELV		N/A
	Insulating of FELV circuits from LV supply		N/A
	FELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to make any electrical contact with socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Socket-outlets have protective conductor contact		N/A
4.7 (4.31.3)	Other circuits		N/A
	Other circuits insulated from accessible parts according Table X.1		N/A
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N/A
	- conductive parts are connected together		N/A
	- test according 7.2.3		N/A
	- conductive part does not cause an electric shock in case of an insulation fault		N/A
	- equipotential bonding in master/slave applications		N/A
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N/A
	- slave luminaire constructed as class I		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.7 (4.32)	**Overvoltage protective devices**		**N/A**
	Comply with IEC 61643-11		N/A
	External to controlgear and connected to earth:		N/A
	- only in fixed luminaires		N/A
	- only connected to protective earth		N/A
4.7 (4.33)	**Luminaire powered via information technology communication cabling**		**N/A**
	Requirements for Class III luminaire		N/A
	Rated voltage within the range of ES1 and does not exceed maximum voltage of used connector		N/A
	Luminaire does not create any hazard from overvoltage	(see Annex 2)	N/A
4.7 (4.34)	**Electromagnetic fields (EMF)**		**P**
	No harmful electromagnetic fields		P
4.7 (4.35)	**Protection against moving fan blades**		**N/A**
	Test with a standard test finger		N/A
	Test with test probe acc. to Figure 13 (IEC 61032) for portable luminaire		N/A
	Blades rounded with radius ≥ 0.5 mm and:		N/A
	- hardness less than D60 Shore		N/A
	- peripheral speed less than 15 m/s		N/A
	- input power of fan ≤ 2 W at rated voltage		N/A
4.7 (4.36)	**Track-mounted luminaires**		**N/A**
	Test in accordance with Annex A of IEC60570:2003/AMD2:2019		N/A
4.7.1 (-)	Insulation not damaged when moving, adjusting or placing on support		N/A
4.7.2 (-)	Wiring fixed, to avoid rubbing		N/A
	Carrier or clips of insulation material or with insulating lining		N/A
4.7.3 (-)	Luminaire does not overturn:		P
	- at an angle of 6° for indoor use		P
	- at an angle 15° for outdoor use		P
4.7.4 (-)	Candlestick luminaires provided with switch		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Switch in candlestick luminaires with E5 or E10 lampholders switches all lamps on and off simultaneously		N/A
	Switch part of the luminaire or within 300 mm of the luminaire if with cord		N/A
4.7.5 (-)	Voltage not exceeding 25 V for E5 lampholders		N/A
	E10 lampholder voltage:		N/A
	- not exceeding 60 V for series connection		N/A
	- not exceeding 250 V for parallel connection		N/A
	Maximum rated wattage does not exceed 100 W		N/A
4.7.6 (-)	Tails not provided for luminaires for outdoor use		N/A
4.7.7 (-)	Not more than two cable entries for luminaires for outdoor use		N/A
4.7.8 (-)	Portable luminaires for outdoor use, socket-outlet degree of protection at least same as the luminaire but not less than IPX4.		N/A
	Degree of protection maintained with or without a plug inserted into the socket-outlet.		N/A
	Class II luminaires, mains socket-outlets comply with the standard and only allow connection to Class II luminaires		N/A
	Class I luminaires, mains socket-outlets comply with the standard and only allow connection to Class I or Class II luminaires		N/A
4.7.9 (-)	Lampholders and plugs resistant to tracking for luminaires for outdoor use	See Test Table 4.16 (13.4)	N/A
	Compliance to clause 13.4		N/A

4.8 (11)	**CREEPAGE DISTANCES AND CLEARANCES**	**DC 9V input**	N/A
4.8 (11.2.1)	Impulse withstand category (Normal category II)	Category II ☐ Category III ☐	—
	Category III according Annex U		N/A
	Protected against pollution, reduced creepage and clearance according Annex P of IEC 61347-1		N/A
4.8 (11.2.2)	Creepage distances for frequency up to 30 kHz	See Test Table 4.8 (11.2) I	N/A
	Creepage distances for frequency over 30 kHz:		N/A
	- Controlgear marked with $\hat{U}_{OUT}$ and f_{UOUT} according IEC 61347-1, clause 7.1, item w	See Test Table 4.8 (11.2) II	N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- Requirements according IEC 60664-4 for controlgear not covered by IEC 61347	See Test Table 4.8 (11.2) II	N/A
4.8 (11.2.3)	Clearances for frequency up to 30 kHz	See Test Table 4.8 (11.2) I	N/A
	Clearances distances for frequency over 30 kHz:		N/A
	- Controlgear marked with U_P	See Test Table 4.8 (11.2) II	N/A
	- Requirements according IEC 60664-4 for controlgear not covered by IEC 61347	See Test Table 4.8 (11.2) II	N/A

4.9 (7)	**PROVISION FOR EARTHING**		N/A
4.9 (7.2.1 + 7.2.3)	Accessible metal parts		N/A
	Metal parts in contact with supporting surface		N/A
	Resistance < 0,5 Ω..... :		N/A
	Self-tapping screws used		N/A
	Thread-forming screws		N/A
	Thread-forming screw used in a grove		N/A
	Protective earth makes contact first		N/A
	Terminal blocks with integrated screwless protective earthing contacts tested according Annex V		N/A
	Protective earthing of the luminaire not via built-in control gear		N/A
4.9 (7.2.2 + 7.2.3)	Protective earthing continuity in joints, etc.		N/A
4.9 (7.2.4)	Locking of clamping means		N/A
	Compliance with 4.7.3		N/A
4.9 (7.2.5)	Earth terminal integral part of connector socket		N/A
4.9 (7.2.6)	Earth terminal adjacent to mains terminals		N/A
4.9 (7.2.7)	Electrolytic corrosion of the protective earth terminal		N/A
4.9 (7.2.8)	Material of protective earth terminal		N/A
	Contact surface bare metal		N/A
4.9 (7.2.10)	Class II luminaire for looping-in		N/A
	Double or reinforced insulation to functional earth		N/A
4.9 (7.2.11)	Protective earthing core coloured green-yellow		N/A
	Length of protective earthing conductor		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.9 (7.2.12)	PELV circuit connected to protective earth for functional purpose		N/A
4.10 (14)	**SCREW TERMINALS**		N/A
	Separately approved; component list..... :	(see Annex 1)	N/A
	Part of the luminaire ..... :	(see Annex 3)	N/A
4.10 (15)	**SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS**		N/A
	Separately approved; component list..... :	(see Annex 1)	N/A
	Part of the luminaire ..... :	(see Annex 4)	N/A
4.11 (5)	**EXTERNAL AND INTERNAL WIRING**		P
4.11 (5.2)	**Supply connection and external wiring**		**N/A**
4.11 (5.2.1)	Means of connection..... :		N/A
	Outdoor luminaire has not PVC insulated external wiring if not Class III or SELV/PELV circuits ≤ 25 V AC/60 V DC/25 V peak interrupted DC voltage with frequency 10Hz -200 Hz or protected from outdoor environment		N/A
4.11 (5.2.2)	Type of cable..... :		N/A
	Nominal cross-sectional area (mm²)..... :		N/A
	Cables equal to IEC 60227 or IEC 60245		N/A
4.11 (5.2.3)	Type of attachment, X, Y or Z		N/A
4.11 (5.2.5)	Type Z not connected to screws		N/A
4.11 (5.2.6)	Cable entries:		N/A
	- suitable for introduction		N/A
	- adequate degree of protection		N/A
4.11 (5.2.7)	Cable entries through rigid material have rounded edges		N/A
4.11 (5.2.8)	Insulating bushings:		N/A
	- suitably fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- tubes or guards made of insulating material		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.11 (5.2.9)	Locking of screwed bushings		N/A
4.11 (5.2.10)	Cord anchorage:		N/A
	- covering protected from abrasion		N/A
	- clear how to be effective		N/A
	- no mechanical or thermal stress		N/A
	- no tying of cables into knots etc.		N/A
	- insulating material or lining		N/A
4.11 (5.2.10.1)	Cord anchorage for type X attachment:		N/A
	a) at least one part fixed		N/A
	b) types of cable		N/A
	c) no damaging of the cable		N/A
	d) whole cable can be mounted		N/A
	e) no touching of clamping screws		N/A
	f) metal screw not directly on cable		N/A
	g) replacement without special tool		N/A
	Glands not used as anchorage		N/A
	Labyrinth type anchorages		N/A
4.11 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		N/A
4.11 (5.2.10.3)	Tests:		N/A
	- impossible to push cable; unsafe		N/A
	- pull test: 25 times; pull (N) ..... :		N/A
	- torque test: torque (Nm) ..... :		N/A
	- displacement ≤ 2 mm		N/A
	- no movement of conductors		N/A
	- no damage of cable or cord		N/A
	- function independent of electrical connection		N/A
4.11 (5.2.10.4)	Luminaire with/designed for use with supply cord with maximum current of 2A:		N/A
	- Ordinary Class III luminaire supplied with SELV ≤ 25V RMS/60V DC		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- Ordinary Class III luminaire supplied with PELV ≤ 12V RMS/30V DC		N/A
	- Other than ordinary Class III luminaire supplied with voltage ≤ 12V RMS/30V DC		N/A
	Pull test of 30 N		N/A
4.11 (5.2.11)	External wiring passing into luminaire		N/A
4.11 (5.2.12)	Looping-in terminals		N/A
4.11 (5.2.13)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		N/A
4.11 (5.2.14)	Mains plug same protection		N/A
	Class III luminaire plug		N/A
	No unsafe compatibility		N/A
4.11 (5.2.15)	Connectors for Class III luminaires (IEC 60603 or IEC 62680)		N/A
4.11 (5.2.16)	Appliance inlets (IEC 60320)		N/A
	Installation couplers (IEC 61535)		N/A
	Appliance inlet or connector systems (IEC 61984)		N/A
4.11 (5.2.17)	No standardized interconnecting cables properly assembled		N/A
4.11 (5.2.18)	Used plug in accordance with		N/A
	- IEC 60083		N/A
	- other standard		N/A
4.11 (5.3)	**Internal wiring**		**P**
4.11 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		P
	- not delivered/ mounting instruction		P
	- factory assembled		P
	- socket outlet loaded (A)..... :		N/A
	- temperatures..... :	(See Annex 2)	P

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Green-yellow for protective earth only		N/A
4.11 (5.3.1.1)	Internal wiring connected directly to fixed wiring		P
	Cross-sectional area (mm²)..... :	2X24AWG	P
	Insulation thickness (mm) ..... :	Min. 0,6mm	P
	Extra insulation added where necessary		N/A
4.11 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		P
	Cross-sectional area (mm²)..... :	2X24AWG	P
4.11 (5.3.1.3)	Double or reinforced insulation for class II		N/A
4.11 (5.3.1.4)	Conductors without insulation		N/A
4.11 (5.3.1.5)	SELV or PELV current-carrying parts		N/A
4.11 (5.3.1.6)	Insulation thickness other than PVC or rubber		N/A
4.11 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		P
	Joints, raising/lowering devices		P
	Telescopic tubes etc.		N/A
	No twisting over 360°		P
4.11 (5.3.3)	Insulating bushings:		N/A
	- suitable fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- cables with protective sheath		N/A
4.11 (5.3.4)	Joints and junctions effectively insulated		N/A
4.11 (5.3.5)	Strain on internal wiring		N/A
4.11 (5.3.6)	Wire carriers		N/A
4.11 (5.3.7)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		N/A
4.11 (5.4)	**Test to determine suitability of conductors having a reduced cross-sectional area**		**N/A**

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Under test the temperature of the luminaire wiring insulation does not exceed the limits stated in Table 12.2	(See ANNEX 2)	N/A
	No damage to luminaire wiring after test		N/A
4.11.1 (-)	Cord anchorage of luminaire for indoor use made of glass or ceramic not fixed or integral		N/A
4.11.2 (-)	For Class I and Class II luminaires for indoor use, if:		N/A
	- mass < 1 kg (kg) ..... :		N/A
	- rated current ≤ 2,5 A (A)..... :		N/A
	- cable length ≤ 2 m (m) ..... :		N/A
	- the nominal cross-sectional area of copper conductor ≥ 0,5 mm² (mm²)..... :		N/A
4.11.3 (-)	Terminals, cord anchorage and inlet opening provided for luminaire for outdoor use delivered without a flexible cable or cord and a plug.		N/A
4.11.4 (-)	Non-detachable flexible cables or cords not lighter than type 245 IEC 57 for Class I and Class II luminaires for outdoor use.		N/A
4.12 (8)	**PROTECTION AGAINST ELECTRIC SHOCK**		P
4.12 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		P
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		P
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		P
	Lamp and starterholders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N/A
	Basic insulation only accessible under lamp or starter replacement		N/A
	Protection in any position		P
	Double-ended tungsten filament lamp		N/A
	Insulation lacquer not reliable		N/A
	Double-ended high-pressure discharge lamp		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Relevant warning according to 3.2.18 fitted to the luminaire		N/A
4.12 (8.2.2)	Portable luminaire adjusted in most unfavourable position		P
4.12 (8.2.3.a)	Class II luminaire:		N/A
	- basic insulated metal parts not accessible		N/A
	- required insulation from live parts in compliance with Table X.1		N/A
	- glass protective shields not used as supplementary insulation		N/A
4.12 (8.2.3.b)	Metal BC lampholder in class I luminaires connected to protective earth		N/A
4.12 (8.2.3.c)	SELV circuits with exposed current carrying parts:		N/A
	Ordinary luminaire:		N/A
	- voltage under load/ no-load AC (V) ..... :		N/A
	- voltage under load/ no-load DC (V)..... :		N/A
	- interrupted DC voltage (V)..... :		N/A
	- touch current if applicable (mA) ..... :		N/A
	One conductive part insulated		N/A
	Other than ordinary luminaire:		N/A
	- voltage under load/ no-load AC (V) ..... :		N/A
	- voltage under load/ no-load DC (V)..... :		N/A
	- interrupted DC voltage (V)..... :		N/A
4.12 (8.2.3.d)	PELV circuits with exposed current carrying parts:		N/A
	Ordinary luminaire:		N/A
	- voltage under load/ no-load AC (V) ..... :		N/A
	- voltage under load/ no-load DC (V)..... :		N/A
	Other than ordinary luminaire:		N/A
	- voltage under load/ no-load AC (V) ..... :		N/A
	- voltage under load/ no-load DC (V)..... :		N/A
	Pole not connected to earth insulated		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	Class III luminaire only for connection to SELV or PELV		N/A
4.12 (8.2.4)	Portable luminaire has protection independent of supporting surface		P
4.12 (8.2.5)	Compliance with the standard test finger or relevant probe		P
4.12 (8.2.6)	Covers reliably secured		P
4.12 (8.2.7)	Luminaire other than below with capacitor > 0,5 μF not exceed 50 V 1 min after disconnection		N/A
	Portable luminaire with capacitor > 0,1 μF (0,25) not exceed 34 V 1 s after disconnection		N/A
	Other luminaires with capacitor > 0,1 μF (0,25) with plug and track adaptors not exceed 60 V 5 s after disconnection		N/A
4.12 (-)	Class I luminaire with bayonet lampholder:		N/A
	1) cap not accessible with test finger		N/A
	2) metal lampholder is earthed		N/A
4.13 (12)	**ENDURANCE TEST AND THERMAL TEST**		P
4.13 (-)	If IP > IP 20 relevant test of (12.4), (12.5), (12.6) and (12.7) after (9.2) but before (9.3) specified in 4.14		—
4.13 (12.2)	**Selection of lamps and ballasts**		—
	Lamp used according Annex B	(Lamp used See ANNEX 2)	—
	Controlgear if separate and not supplied	(Controlgear used see ANNEX 2)	—
4.13 (12.3)	**Endurance test**		**P**
	a) mounting-position ..... :	As in normal used	—
	b) test temperature (°C)..... :	45±2°C	—
	c) total duration (h) ..... :	240h	—
	d) supply voltage (V)..... :	1,1Un	—
	d) if not equipped with controlgear, constant voltage/current (V) or (A) ..... :		—
1.13 (12.3.1d)	d) Class III luminaires powered via information technology communication cable:		—
	- voltage under normal operation (V)..... :		—

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- voltage under abnormal operation (V)..... :		
	e) luminaire ceases to operate		—
	f) luminaire with a constant light output function		N/A
4.13 (12.3.2)	After endurance test:		P
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		P
	- marking legible		P
	- no cracks, deformation etc.		P
4.13 (12.4)	**Thermal test (normal operation)**	**(See ANNEX 2)**	P
4.13 (12.5)	**Thermal test (abnormal operation)**	**(See ANNEX 2)**	N/A
4.13 (12.6)	**Thermal test (failed lamp control gear condition):**		N/A
4.13 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A) ..... :		—
	- case of abnormal conditions..... :		—
	- electronic lamp control gear		N/A
	- measured winding temperature (°C): at 1,1 Un .... :		—
	- measured mounting surface temperature (°C) at 1,1 Un ..... :		N/A
	- calculated mounting surface temperature (°C) ..... :		N/A
	- track-mounted luminaires		N/A
4.13 (12.6.2)	Temperature sensing control		N/A
	- case of abnormal conditions..... :		—
	- thermal link		N/A
	- manual reset cut-out		N/A
	- auto reset cut-out		N/A
	- measured mounting surface temperature (°C) ..... :		N/A
	- track-mounted luminaires		N/A
4.13 (12.7)	**Thermal test (failed lamp control gear in plastic luminaires):**		**N/A**
4.13 (12.7.1)	Luminaire without temperature sensing control		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.13 (12.7.1.1)	Luminaire with fluorescent lamp ≤ 70W		N/A
	Test method 12.7.1.1 or Annex W ..... :		—
	Test according to 12.7.1.1:		N/A
	- case of abnormal conditions..... :		—
	- Ballast failure at supply voltage (V) ..... :		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
	Test according to Annex W:		N/A
	- case of abnormal conditions..... :		—
	- measured winding temperature (°C): at 1,1 Un..... :		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un ..... :		—
	- calculated temperature of fixing point/exposed part (°C)..... :		—
	Ball-pressure test..... :	See Test Table 1.15 (13.2.1)	N/A
4.13 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp > 70W, transformer > 10 VA		N/A
	- case of abnormal conditions..... :		—
	- measured winding temperature (°C): at 1,1 Un..... :		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un ..... :		—
	- calculated temperature of fixing point/exposed part (°C)..... :		—
	Ball-pressure test..... :	See Test Table 1.15 (13.2.1)	N/A
4.13 (12.7.1.3)	Luminaire with short circuit proof transformers ≤ 10 VA		N/A
	- case of abnormal conditions..... :		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
4.13 (12.7.2)	Luminaire with temperature sensing control		N/A
	- thermal link ..... :	Yes ☐ No ☐	—
	- manual reset cut-out..... :	Yes ☐ No ☐	—

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- auto reset cut-out..... :	Yes ☐ No ☐	—
	- case of abnormal conditions..... :		—
	- highest measured temperature of fixing point/ exposed part (°C):..... :		—
	Ball-pressure test: ..... :	See Test Table 4.15 (13.2.1)	N/A
4.13 (-)	Luminaire for indoor use tested in overturned position (overturns < 15°)		N/A
4.14 (9)	**RESISTANCE TO DUST AND MOISTURE**		P
4.14 (-)	If IP > IP 20 the order of tests as specified in clause 4.13		N/A
4.14 (9.2)	Tests for ingress of dust, solid objects and moisture:		P
	- classification according to IP ..... :	IP54	—
	- mounting position during test..... :	In the most unfavourable position of normal use	—
	- fixing screws tightened; torque (Nm) ..... :	/	—
	- tests according to clauses..... :	Cl.9.2.1 and Cl.9.2.5	—
	- electric strength test afterwards		P
	a) no deposit in dust-proof luminaire		P
	b) no talcum in dust-tight luminaire		N/A
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N/A
	c.1) For luminaires without drain holes – no water entry		P
	c.2) For luminaires with drain holes – no hazardous water entry		N/A
	d) no water in watertight, pressure watertight, high pressure and temperature water jet-proof or high pressure and cold-water jet-proof luminaire		N/A
	e) no contact with live parts (IP 2X)		P
	e) no entry into enclosure (IP 3X and IP 4X)		N/A
	e) no contact with live parts through drain holes and ventilation slots (IP3X and IP4X)		N/A
	f) no trace of water on part of lamp requiring protection from splashing water		N/A
	g) no damage of protective shield or glass envelope		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.14 (9.3)	Humidity test 48 h	25°C, 93%	P
4.15 (10)	**INSULATION RESISTANCE AND ELECTRIC STRENGTH**		P
4.15 (10.2.1)	Insulation resistance test	Metal foil	P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø :	1MΩ for basic insulation for voltage of SELV	P
	Insulation resistance (MΩ):		P
	SELV or PELV:		P
	- between current-carrying parts of different polarity:	>500MΩ	P
	- between current-carrying parts and mounting surface .....:	>500MΩ	P
	- between current-carrying parts and metal parts of the luminaire.....:		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....:		N/A
	- Insulation bushings as described in Section 5 .:		N/A
	Other than SELV or PELV:		N/A
	- between live parts of different polarity.....:		N/A
	- between live parts and mounting surface .....:		N/A
	- between live parts and metal parts.....:		N/A
	- between live parts of different polarity through action of a switch.....:		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....:		N/A
	- Insulation bushings as described in Section 5 .:		N/A
4.15 (10.2.2)	Electric strength test	500V for SELV	P
	Dummy lamp		N/A
	Luminaires with ignitors after 24 h test		N/A
	Luminaires with manual ignitors		N/A
	Luminaires with ignitors provided with ballasts conforming to IEC 61347-2-9		N/A
	SELV or PELV:		P

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
	- between current-carrying parts of different polarity:	500V, 1min	P
	- between current-carrying parts and mounting surface .....:	500V, 1min	P
	- between current-carrying parts and metal parts of the luminaire.....:		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....:		N/A
	- Insulation bushings as described in Section 5 .:		N/A
	Other than SELV/PELV:		N/A
	- between live parts of different polarity.....:		N/A
	- between live parts and mounting surface .....:		N/A
	- between live parts and metal parts.....:		N/A
	- between live parts of different polarity through action of a switch.....:		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts .....:		N/A
	- Insulation bushings as described in Section 5 .:		N/A
4.15 (10.3)	Touch current (mA) .....:		N/A
	Protective conductor current (mA) .....:		N/A

4.16 (13)	**RESISTANCE TO HEAT, FIRE AND TRACKING**		P
4.16 (13.2.1)	Ball-pressure test.....:	See Test Table 4.16 (13.2.1)	P
4.16 (13.3.1)	Needle-flame test (10 s).....:	See Test Table 4.16 (13.3.1)	P
4.16 (13.3.2)	Glow-wire test (650°C).....:	See Test Table 4.16 (13.3.2)	P
4.16 (13.4)	Proof tracking test (IEC 60112) .....:	See Test Table 4.16 (13.4)	N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

4.8 (11.2)	TABLE I: Creepage distances and clearances							N/A
	Minimum distances (mm) for a.c. up to 30 kHz sinusoidal voltages							
	Applicable part of IEC 60598-1 Table 11.1.A*, 11.1.B* and 11.2* and Table U.1*							
Distances	Insulation type **	Measured clearance	Required		Measured creepage	Required		
			clearance	*Table		creepage	*Table	
Distance 1:	--	--	--	--	--	--	--	
Working voltage (V).....:					--			—
PTI.....:					< 600 ☐ ≥ 600 ☐			—
Pulse voltage or U_P if applicable (kV) .....:					--			—
Supplementary information: Between L and N, and between fuse.								
Distance 2:	--	--	--	--	--	--	--	
Working voltage (V).....:					--			—
PTI.....:					< 600 ☐ ≥ 600 ☐			—
Pulse voltage or U_P if applicable (kV) .....:					--			—
Supplementary information: Between live part to enclosure.								
Distance 3:	--	--	--	--	--	--	--	
Working voltage (V).....:					--			—
PTI.....:					< 600 ☐ ≥ 600 ☐			—
Pulse voltage or U_P if applicable (kV) .....:					--			—
Supplementary information: --								
** Insulation type: B – Basic; S – Supplementary; R – Reinforced. See also IEC 60598-1 Annex M.								

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

4.8 (11.2)	TABLE II: Creepage distances and clearances						N/A
	Minimum distances (mm) for a.c. higher than 30 kHz sinusoidal voltages						
	Applicable part of IEC 61347-1 Table 7 and 8* or IEC 60664-4 Table 1 and 2						
Distances	Insulation type **	Measured clearance	Required		Measured creepage	Required	
			clearance	*Table		creepage	*Table
Distance 1:	--	--	--	--	--	--	--
Working voltage (V) ..... :					--		—
Frequency if applicable (kHz) ..... :					--		—
PTI ..... :					< 600 ☐ ≥ 600 ☐		—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV) ..... :					--		—
Supplementary information: --							
Distance 2:	--	--	--	--	--	--	--
Working voltage (V) ..... :					--		—
Frequency if applicable (kHz) ..... :					--		—
PTI ..... :					< 600 ☐ ≥ 600 ☐		—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV) ..... :					--		—
Supplementary information: --							
Distance 3:	--	--	--	--	--	--	--
Working voltage (V) ..... :					--		—
Frequency if applicable (kHz) ..... :					--		—
PTI ..... :					< 600 ☐ ≥ 600 ☐		—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV) ..... :					--		—
Supplementary information: --							
** Insulation type: B – Basic; S – Supplementary; R – Reinforced.							

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

4.16 (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics		P
Allowed impression diameter (mm) .....:		**2,0**	—

Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)
White plastic cover	Annex I	82	1,1
Black body plastic	Annex I	84	1,5
Crystal	Annex I	75	0,5
Reflector cover	Annex I	81	1,2
Silver reflector	Annex I	81	1,2
Battery box	Annex I	125	1,0
LED board	Annex I	125	1,0
PCB	Annex I	125	1,0
Supplementary information: N/A			

4.16 (13.3.1)	TABLE: Needle-flame test (IEC 60695-11-5)				P

Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Battery box	Annex I	10s	No	No burning	P
LED board	Annex I	10s	No	No burning	P
PCB	Annex I	10s	No	No burning	P
Supplementary information: N/A					

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

4.16 (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)			P
Glow wire temperature .....:	650°C			—
Object/ Part No./ Material	Manufacturer/ trademark	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
White plastic cover	Annex I	No	No burning	P
Black body plastic	Annex I	No	No burning	P
Crystal	Annex I	No	No burning	P
Reflector cover	Annex I	No	No burning	P
Silver reflector	Annex I	No	No burning	P
Supplementary information: N/A				

4.16 (13.4)	TABLE: Proof tracking test (IEC 60112)				N/A
Test voltage PTI .....:	175 V				—
Object/ Part No./ Material	Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
--	--	--	--	--	--
--	--	--	--	--	--
--	--	--	--	--	--
Supplementary information: N/A					

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 1	TABLE: Critical components information					P
Object / part No.	**Code**	**Manufacturer/ trademark**	**Type / model**	**Technical data**	**Standard**	**Mark(s) of conformity[1)]**
White plastic cover	B	FORMOSA CHEMICALS & FIBRE CORP PLASTICS DIV	AG15A1-H	ABS, HB	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E162823)
Black body plastic	B	FORMOSA CHEMICALS & FIBRE CORP PLASTICS DIV	AG15A1-H	ABS, HB	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E162823)
Crystal	B	CHI MEI CORPORATION	PC-110(+)	PC, V-2	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E56070)
Reflector cover	B	FORMOSA CHEMICALS & FIBRE CORP PLASTICS DIV	AG15A1-H	ABS, HB	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E162823)
Silver reflector	B	FORMOSA CHEMICALS & FIBRE CORP PLASTICS DIV	AG15A1-H	ABS, HB	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E162823)
Battery box	B	CHI MEI CORPORATION	PC-110(+)	PC, V-2	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E56070)
Internal wire	B	SHENYU COMMUNICATIO N TECHNOLOGY INC	1354	24AWG; 30Vdc, 80°C	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E318898)
LED board	B	GOLDENMAX INTERNATIONAL TECHNOLOGY (ZHUHAI) LTD	GF432	V-0; 130°C	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E330731)
PCB	B	GOLDENMAX INTERNATIONAL TECHNOLOGY (ZHUHAI) LTD	GF432	V-0; 130°C	EN IEC 60598-1 EN 60598-2-4	Tested with appliance and UL(E330731)
LED	B	Shenzhen Heke Electronic Technology Co., Ltd	3030	VF: 3,0-3,6V; IF: 300mA; CCT: 1800-2000K	EN 62471 IEC TR 62778	Tested with appliance

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

Supplementary information:

[1)] Provided evidence ensures the agreed level of compliance. See OD-CB2039.

The codes above have the following meaning:

A - The component is replaceable with another one, also certified, with equivalent characteristics

B - The component is replaceable if authorised by the test house

C - Integrated component tested together with the appliance

D - Alternative component

License available upon request.

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Thermal tests of Section 12		P
	Type reference..... :	G-001	—
	Lamp used..... :	LED light source	—
	Lamp control gear used..... :	--	—
	Mounting position of luminaire..... :	As normal installation	—
	Supply wattage (W)..... :	Battery	—
	Supply current (A)..... :	Battery	—
	Temperatures in test 1 - 4 below are corrected for ta (°C) ..... :	35°C	—
	- abnormal operating mode..... :	N/A	—
1.12 (12.4)	- test 1: rated voltage ..... :	Battery(DC 9V)	—
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current ..... :	N/A	—
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage..... :	N/A	—
	Through wiring or looping-in wiring loaded by a current of A during the test ..... :	N/A	—
1.12 (12.5)	- test 4: 1,1 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current ..... :	N/A	—

Temperature measurements (°C)

Part	Ambient	Cl. 12.4 – normal				Cl. 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit

IEC 60598-2-4							
Clause	Requirement + Test			Result - Remark			Verdict
Mounting surface	35	52,4	--	--	90	--	--
Black body plastic	35	58,7	--	--	Ref.	--	--
White plastic cover	35	56,9	--	--	Ref.	--	--
Battery box	35	59,9	--	--	Ref.	--	--
PCB	35	58,2	--	--	130	--	--
Crystal	35	44,7	--	--	Ref.	--	--
LED board	35	55,2	--	--	130	--	--
Reflector cover	35	55,2	--	--	Ref.	--	--
Silver reflector	35	55,4	--	--	Ref.	--	--
Internal wire	35	52,8	--	--	80	--	--
Supplementary information: N/A							

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 3	**Screw terminals (part of the luminaire)**		**N/A**
(14)	**SCREW TERMINALS**		**N/A**
(14.2)	Type of terminal.....:		—
	Rated current (A).....:		—
(14.3.2.1)	One or more conductors		N/A
(14.3.2.2)	Special preparation		N/A
(14.3.2.3)	Terminal size		N/A
	Cross-sectional area (mm²).....:		—
(14.3.3)	Conductor space (mm).....:		N/A
(14.4)	Mechanical tests		N/A
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread).....:	M	N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm).....:		N/A
	Torque (Nm).....:		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N).....:		N/A
(14.4.8)	Without undue damage		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 4	**Screwless terminals (part of the luminaire)**		**N/A**
(15)	**SCREWLESS TERMINALS**		**N/A**
(15.2)	Type of terminal.....:		—
	Rated current (A).....:		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A
(15.3.3)	Stop		N/A
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5)	Terminals and connections for internal wiring		N/A
(15.5.1)	Mechanical tests		N/A
(15.5.1.1.1)	Pull test spring-type terminals (4 N, 4 samples).....:		N/A
(15.5.1.1.2)	Pull test pin or tab terminals (4 N, 4 samples).....:		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N/A
(15.5.2)	Electrical tests		N/A
	Voltage drop (mV) after 1 h (4 samples) .....:		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples).....:		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples).....:		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples).....:		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples) .....:		N/A

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
(15.6)	Terminals and connections for external wiring		N/A
(15.6.1)	Conductors		N/A
	Terminal size and rating		N/A
15.6.2	Mechanical tests		N/A
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N) .....:		N/A
(15.6.2.2)	Pull test pin or tab terminals (4 samples); pull (N) .....:		N/A
(15.6.3)	Electrical tests		N/A
	Tests according 15.6.3.1 + 15.6.3.2 in IEC 60598-1		N/A

(15.6.3.1) (15.6.3.2)	**TABLE: Contact resistance test / Heating tests**									N/A
	Voltage drop (mV) after 1 h									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)	--	--	--	--	--	--	--	--	--	--
	Voltage drop of two inseparable joints									N/A
	Voltage drop after 10th alt. 25th cycle									N/A
	Max. allowed voltage drop (mV).....:					N/A				—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)	--	--	--	--	--	--	--	--	--	--
	Voltage drop after 50th alt. 100th cycle									N/A
	Max. allowed voltage drop (mV).....:					N/A				—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)	--	--	--	--	--	--	--	--	--	--
	Continued ageing: voltage drop after 10th alt. 25th cycle									N/A
	Max. allowed voltage drop (mV).....:					N/A				—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)	--	--	--	--	--	--	--	--	--	--
	Continued ageing: voltage drop after 50th alt. 100th cycle									N/A
	Max. allowed voltage drop (mV).....:					N/A				—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)	--	--	--	--	--	--	--	--	--	--

IEC 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict

	--	--	--	--	--	--	--	--	--	--
Supplementary information: N/A										

IEC60598_2_4H ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict

ATTACHMENT TO TEST REPORT IEC 60598-2-4 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES LUMINAIRES PART 2: PARTICULAR REQUIREMENTS SECTION 4: PORTABLE GENERAL PURPOSE LUMINAIRES	
Differences according to .....:	EN 60598-2-4:2018 used in conjunction with EN IEC 60598-1:2021 + A11:2022
TRF template used.....:	IECEE OD-2020-F2:2020, Ed. 1.1
Attachment Form No.....:	EU_GD_IEC60598_2_4I_II
Attachment Originator .....:	IMQ S.p.A.
Master Attachment .....:	Dated 2022-07-01
Copyright © 2022 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.	

	CENELEC COMMON MODIFICATIONS (EN)		**P**
4.6 (3)	MARKING		**N/A**
(3.2.12)	Delete the note 4		N/A
4.7 (4)	CONSTRUCTION		**P**
4.7 (4.11.6)	Electro-mechanical contact systems: electric strength test at 1 500 V		N/A
4.11 (5)	EXTERNAL AND INTERNAL WIRING		**N/A**
4.11 (5.2.2)	Cables equal to EN 50525		N/A
4.11 (5.2.2)	Delete paragraph 2		N/A
	Replace table 5.1 – Supply cord		N/A
4.11.4 (-)	For class I and class II portable luminaires for outdoor use, non-detachable flexible cables or cords not lighter than type H05RN-F		N/A

IEC60598_2_4H ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
4.13 (12)	ENDURANCE TESTS AND THERMAL TESTS		N/A
4.13 (12.4.2c)	Thermal test (normal operation) see footnote c to table 12.2 relating to unsleeved fixed wiring		N/A
ZB	ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)		**N/A**
(3.3)	DK: power supply cords of class I luminaires with label		N/A
(5.2.18)	DK: socket-outlets		N/A
(5.2.1)	CY, DK, FI, GB: type of plug		N/A
4.4.4 (-)	DK: luminaires for outdoor use classified as class II or class III		N/A
ZC	ANNEX ZC, NATIONAL DEVIATIONS (EN)		N/A
(4 & 5)	FR: Shuttered socket-outlets 10/16A		N/A
	FR: Safety requirements for high buildings (Arrêté du 30 décembre 2011 portant règlement de sécurité pour la construction des immeubles de grande hauteur et leur protection contre les risques d'incendie et de panique; Section VIII; Article GH 48, Eclairage) Glow-wire test for outer parts of luminaires:		N/A
	- 850°C for luminaires in stairways and horizontal travel paths		N/A
	- 650°C for indoor luminaires		N/A
	GB: Requirements according to United Kingdom Building Regulation		N/A

EN IEC 62031			
Clause	Requirement + Test	Result - Remark	Verdict
12 (14)	**FAULT CONDITIONS**		**P**
- (14.1)	**WHEN OPERATED UNDER FAULT CONDITIONS THE CONTROLGEAR:**		**P**
	- does not emit flames or molten material		P
	- does not produce flammable gases		P
	- protection against accidental contact not impaired		P
	Thermally protected controlgear does not exceed the marked temperature value		N/A
	Fault conditions: capacitors, resistors or inductors without proof of compliance with relevant specifications have been short-circuited or disconnected	(see appended table)	P
- (14.2)	Short-circuit of creepage distances and clearances if less than specified in clause 16 in Part 1 (after any reduction in 14.2 - 14.5)	(see appended table)	N/A
- (14.3)	Short-circuit or interruption of semiconductor devices	(see appended table)	N/A
- (14.4)	Short-circuit across insulation consisting of lacquer, enamel or textile	(see appended table)	P
- (14.5)	Short-circuit across electrolytic capacitors	(see appended table)	P
	Short-circuit or interruption of SPDs	(see appended table)	P
- (14.6)	After the tests has been carried out on three samples:		P
	The insulation resistance ≥ 1 MΩ .....:	>500MΩ	P
	No flammable gases		P
	No accessible parts have become live		P
	During the tests, a five-layer tissue paper, where the test specimen is wrapped, does not ignite		P
- (14.7)	Relevant fault condition tests with high-power a.c. supply and in turn to a d.c. supply		—
12.2	**Overpower condition**		**P**
	Module withstands overpower condition >15 min.		P
	Module with automatic protective device or power limiter, test performed 15 min. at limit.		P
	No fire, smoke or flammable gas is produced		P
	Molten material does not ignite tissue paper, spread below the module		P

IEC TR 62778			
Clause	Requirement + Test	Result - Remark	Verdict

7	**MEASUREMENT INFORMATION FLOW**		**P**
7.1	**Basic flow**		**P**
	'Law of conservation of luminance' applied		P
	Use of only true luminance/radiance values		P
	In case of luminaire: The light source is operated in the luminaire under similar conditions as when tested as a component		N/A
	In case E_{thr} value for RG2 was established the peak value was derived from angular light distribution		N/A
7.2	**Conditions for the radiance measurement**		**P**
	Standard condition applied (200mm distance, 0,011rad field of view)	Tested at 200mm	P
	Non-standard condition applied		N/A
7.3	**Special cases (I): Replacement by a lamp or LED module of another type**		**N/A**
	Light source is a white light source		N/A
	Evaluation done based on highest luminance		N/A
	Evaluation done based on CCT value		N/A
7.4	**Special cases (II): Arrays and clusters of primary light sources**		**N/A**
	LED package is evaluated as .....:		N/A
	E_{thr} of LED package applies to array		N/A
8	**RISC GROUP CLASSIFICATION**		**P**
	Risk group achieved:		P
	-.. Risk Group 0 unlimited		P
	-.. Risk Group 1 unlimited		N/A
	- E_{thr} ..... (lx) : Distance to reach RG1..... (m) :	RG0	N/A

IEC TR 62778			
Clause	Requirement + Test	Result - Remark	Verdict

	TABLE: Spectroradiometric measurement		**P**
	Measurement performed on:	☐ **LED package** ☐ **LED module** ☐ **Lamp** ☒ **Luminaire**	**P**
	Model number.....:	G-001	
	Test voltage (V).....:	--	—
	Test current (mA).....:	--	—
	Test frequency (Hz).....:	--	—
	Ambient, t (°C).....:	24,3	—
	Measurement distance.....:	☒ 20 cm ☐ ... cm	—
	Source size .....:	☒ Non-small ☐ Small : .... mm	—
	Field of view .....:	☒ 100 mrad ☐ 11 mrad ☐ 1,7 mrad (for small sources)	—

Item	Symbol	Units	Result	Remark
Correlated colour temperature	CCT	K	N/A	
x/y colour coordinates			/	
Blue light hazard radiance	L_B	$W/(m^2 \cdot sr^1)$	0,1539	RG0
Blue light hazard irradiance	E_B	W/m^2	N/A	--
Luminance	L	cd/m^2	294400	$K_{B,V}= L_B/L= 0,0000005$
Illuminance	E	lx	N/A	--
Supplementary information: N/A				

IEC TR 62778			
Clause	Requirement + Test	Result - Remark	Verdict

	TABLE: Angular light distribution	N/A

Prüfbericht-Nr.: *Test report no.*:	**Attachment 1 of CN23RCT9 001**	**Auftrags-Nr.:** *Order no.*:	180270222	
Kunden-Referenz-Nr.: *Client reference no.*:	N/A	**Auftragsdatum:** *Order date:*	2023-08-28	
Auftraggeber: *Client*:	Huizhou Duran Creative Technology CO.,LTD. 7 Floor, Innovation Building, Science and Technology Zone, Shihua Avenue, Dayawan District, Huizhou city, Guangdong P.R.China.			
Prüfgegenstand: *Test item*:	Control gear for Portable Light			
Bezeichnung / Typ-Nr.: *Identification / Type no.*:	227668G_Y138			
Auftrags-Inhalt: *Order content*:	Acceptance test			
Prüfgrundlage: *Test specification*:	EN 61347-1:2015+A1 EN 61347-2-11:2001+A1:2019			

Wareneingangsdatum: *Date of sample receipt*:	2023-08-28
Prüfmuster-Nr.: *Test sample no:*	A003548920
Prüfzeitraum: *Testing period*:	2023-08-28 - 2023-11-21
Ort der Prüfung: *Place of testing*:	TÜV Rheinland/CCIC (Ningbo)Co.,Ltd.
Prüflaboratorium: *Testing laboratory:*	TÜV Rheinland/CCIC (Ningbo)Co.,Ltd.
Prüfergebnis*: *Test result**:	Pass



geprüft von: tested by:	X Zeen Xu	**genehmigt von:** *authorized by*:	X ChengChao Huang
Datum: *Date:*	2023-11-27	**Ausstellungsdatum:** *Issue date:*	2023-11-27
Stellung / Position:	Project Engineer	**Stellung** / Position:	Reviewer

Sonstiges / *Other*: Acceptance test for control gear.

Zustand des Prüfgegenstandes bei Anlieferung: *Condition of the test item at delivery*: Prüfmuster vollständig und unbeschädigt *Test item complete and undamaged*

* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* *Legend:*	*P(ass) = passed a.m. test specification(s)*	*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.
V05

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. *The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.*
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. *As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.*
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. *Test clauses with remark of * are subcontracted to qualified subcontractors and descripted under the respective test clause in the report.* *Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.*
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnisen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezueglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the “Zero Guard Band Rule” and “Simple Acceptance” in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.

Test Report issued under the responsibility of:

www.tuv.com

TÜVRheinland®

TEST REPORT
EN 61347-2-11
Part 2: Particular requirements:
Section 11: Miscellaneous electronic circuits used with luminaires

Report Number..... :	Attachment 1 of CN23RCT9 001
Date of issue..... :	See cover page
Total number of pages.....	See cover page
Name of Testing Laboratory preparing the Report..... :	TÜV Rheinland / CCIC (Ningbo) Co., Ltd. 3F, Building C13, R&D Park, No.32 Lane 299 Guanghua Road, National Hi-Tech Zone, Ningbo 315048, P.R. China
Applicant's name..... :	Huizhou Duran Creative Technology CO.,LTD.
Address..... :	7 Floor, Innovation Building, Science and Technology Zone, Shihua Avenue, Dayawan District, Huizhou city, Guangdong P.R.China.
Test specification:	
Standard..... :	IEC 61347-2-11:2001, AMD1:2017 used in conjunction with IEC 61347-1:2015, AMD1:2017
Test procedure..... :	Acceptance test
Non-standard test method.....:	N/A
Test Report Form No..... :	IEC61347_2_11F
Test Report Form(s) Originator ... :	Intertek Semko AB
Master TRF..... :	Dated 2018-11-09

Copyright © 2015 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

General disclaimer:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.

Test item description..... :	Control gear for Portable Light
Trade Mark ..... :	N/A
Manufacturer ..... :	Huizhou Duran Creative Technology CO.,LTD. 7 Floor, Innovation Building, Science and Technology Zone, Shihua Avenue, Dayawan District, Huizhou city, Guangdong P.R.China.
Model/Type reference..... :	227668G_Y138
Ratings..... :	Input: DC 9V; Built-in controlgear; See "General product information"

Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):			
☒	**Testing Laboratory:**	TÜV Rheinland / CCIC (Ningbo) Co., Ltd.	
Testing location/ address..... :		3F, Building C13, R&D Park, No.32 Lane 299 Guanghua Road, National Hi-Tech Zone, Ningbo 315048, P.R.China.	
☐	**Associated Testing Laboratory:**	N/A	
Testing location/ address..... :		N/A	
Tested by (name, function, signature) .... :		N/A	
Approved by (name, function, signature) :		N/A	
☐	**Testing procedure: CTF Stage 1:**	N/A	
Testing location/ address..... :		N/A	
Tested by (name, function, signature) .... :		N/A	
Approved by (name, function, signature) :		N/A	
☐	**Testing procedure: CTF Stage 2:**	N/A	
Testing location/ address..... :		N/A	
Tested by (name + signature) ..... :		N/A	
Witnessed by (name, function, signature):		N/A	
Approved by (name, function, signature) :		N/A	
☐	**Testing procedure: CTF Stage 3:**	N/A	
☐	**Testing procedure: CTF Stage 4:**	N/A	
Testing location/ address..... :		N/A	

Tested by (name, function, signature) .... :	N/A	
Witnessed by (name, function, signature):	N/A	
Approved by (name, function, signature):	N/A	
Supervised by (name, function, signature):	N/A	

List of Attachments (including a total number of pages in each attachment):

N/A

Summary of testing:

Tests performed (name of test and test clause):	**Testing location:**
- All tests performed within the appliance. - Endurance test according to Cl.17 of EN 61058-1:2002/A2:2008 is also performed. **Test result: P**	TÜV Rheinland / CCIC (Ningbo) Co., Ltd. 3F, Building C13, R&D Park, No.32 Lane 299 Guanghua Road, National Hi-Tech Zone, Ningbo 315048, P.R.China.

Summary of compliance with National Differences:

List of countries addressed

N/A

Copy of marking plate

N/A

Test item particulars..... :	Control gear for Portable Light
Classification of installation and use..... :	Built-in control gear
Supply Connection..... :	Fixing wire
..... :	
Possible test case verdicts:	
- test case does not apply to the test object..... :	N/A
- test object does meet the requirement..... :	P (Pass)
- test object does not meet the requirement..... :	F (Fail)
Testing..... :	
Date of receipt of test item..... :	See cover page
Date (s) of performance of tests..... :	See cover page

General remarks:

"(See Enclosure #)" refers to additional information appended to the report.
"(See appended table)" refers to a table appended to the report.

Throughout this report a ☒ comma / ☐ point is used as the decimal separator.

Clause numbers between brackets refer to clauses in IEC 61347-1

Manufacturer's Declaration per sub-clause 4.2.5 of IECEE 02:

The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided..... :	☐ **Yes** ☒ **Not applicable**

When differences exist; they shall be identified in the General product information section.

Name and address of factory (ies) ..... :	**HUIZHOU LIDAFENG TECHNOLOGY CO., LTD.** **Workshop Building II, Shunju Industry Zone Chayuan Village, Qiuchang Town, Huiyang District 516221, Huizhou, Guangdong P.R.China.**

General product information:

The DUT is built-in control gear for Portable Light, used together with Class III product.

Details see below table:

Desk lamp name	Control gear name	Input voltage	Wattage
G-001	227668G_Y138	Input: DC 9V	1W

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

4 (4)	GENERAL REQUIREMENTS		P
- (4)	Insulation materials for double or reinforced insulation according requirements in Annex N of IEC 61347-1	(see Annex N)	N/A
- (4)	Compliance of independent controlgear enclosure with IEC 60598-1		P
- (4)	Built-in magnetic ballast with double or reinforced insulation comply with Annex I of IEC 61347-1		N/A
- (4)	Built-in electronic controlgear with double or reinforced insulation comply with Annex O of IEC 61347-1	(see Annex O)	N/A
- (4)	SELV controlgear comply with Annex L of IEC 61347-1	(see Annex L)	N/A

6 (6)	CLASSIFICATION		P
	Built-in controlgear .....:	Yes ☒ No ☐	—
	Independent controlgear.....:	Yes ☐ No ☒	—
	Integral controlgear .....:	Yes ☐ No ☒	—

7 (7)	MARKING		N/A
7.1 (7.1)	Mandatory markings		N/A
	a) mark of origin		N/A
	b) model number or type reference		N/A
	d) correlation between interchangeable parts and controlgear marked		N/A
	e) rated supply voltage (V)		N/A
	supply frequency (Hz)		N/A
	supply current (A)		N/A
	f) earthing symbol, if applicable		N/A
	k) wiring diagram		N/A
	l) value of tc alternative ta		N/A
	s) SELV symbol		N/A
7.1 (-)	control terminals identified		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	classification of insulation between live parts and control circuits		N/A
7.1 (7.2)	Marking durable and legible		N/A
	Rubbing 15 s water, 15 s petroleum; marking legible		N/A
7.2 (7.1)	**Information to be provided, if applicable**		N/A
	h) declaration of protection against accidental contact		N/A
	i) cross-section of conductors (mm^2)		N/A
	j) number, type and wattage of lamp(s)		N/A
7.1 (7.2)	Marking durable and legible		N/A
	Rubbing 15 s water, 15 s petroleum; marking legible		N/A

8 (10)	**PROTECTION AGAINST ACCIDENTAL CONTACT WITH LIVE PARTS**		**P**
- (10.1)	Controlgear protected against accidental contact with live parts	Rely upon enclosure	P
- (A2)	Voltage measured with 50 kΩ	(see Annex A)	N/A
- (A3)	Voltage > 35 V peak or > 60 V d.c. or protective impendance device	(see Annex A)	N/A
- (10.1)	Lacquer or enamel not used for protection or insulation		N/A
	Adequate mechanical strength on parts providing protection		N/A
- (10.2)	Capacitors > 0,5 µF: voltage after 1 min (V): < 50 V .....:		N/A
- (10.3)	**Controlgear providing SELV**		**N/A**
	Accessible conductive parts are insulated from live parts by double or reinforced insulation in SELV controlgear		N/A
	No connection between output circuit and the body or protective earthing circuit		N/A
	No possibility of connection between output circuit and the body or protective earthing circuit through other conductive parts		N/A
	SELV outputs separated by at least basic insulation		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	ELV conductive parts insulated as live parts		N/A
	Tests according Annex L of IEC 61347-1		N/A
- (10.4)	**Accessible conductive parts in SELV circuits**		N/A
	Output voltage under load ≤ 25 V r.m.s. or ≤ 60 V d.c.		N/A
	If output voltage > 25 V r.m.s. or > 60 V d.c.; No load output ≤ 35 V peak or ≤ 60 V d.c and touch current does not exceed 0,7 mA (peak) or 2 mA d.c. .....:		N/A
	One conductive part is insulated if output voltage or current exceeding the values above and withstand test voltage 500 V		N/A
	Double or reinforced insulation bridged by appropriate and at least two resistors or two Y2 capacitors or one Y1 capacitor		N/A
	Y1 or Y2 capacitors comply with IEC 60384-14		N/A
	Resistors comply with test (a) in 14.1 of IEC 60065		N/A
9 (8)	**TERMINALS**		N/A
- (8.1)	**Integral terminals**		N/A
	Screw terminals according section 14 of IEC 60598-1	(see Annex 2)	N/A
	Screwless terminals according section 15 of IEC 60598-1	(see Annex 3)	N/A
- (8.2)	**Terminals other than integral terminals**		N/A
	Comply with relevant IEC standard	(see Annex 1)	N/A
	Suit the conditions		N/A
	Satisfy additional relevant requirements of this standard		N/A
10 (9)	**PROVISION FOR PROTECTIVE EARTHING**		N/A
- (9.1)	**Provisions for protective earthing**		N/A
	Terminal complying with clause 8		N/A
	Locked against loosening and not possible to loosen by hand		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Not possible to loosen clamping means unintentionally on screwless terminals		N/A
	All parts of material minimizing the danger of electrolytic corrosion		N/A
	Made of brass or equivalent material		N/A
	Contact surface bare metal		N/A
	Test according 7.2.3 of IEC 60598-1		N/A
- (9.2)	**Provision for functional earthing**		N/A
	Comply with clause 8 and 9.1		N/A
	Functional earth insulated from live parts by double or reinforced insulation		N/A
- (9.3)	**Lamp controlgear with conductors for protective earthing by tracks on printed circuit board**		N/A
	Test with a current of 25 A between earthing terminal or earthing contact and each of the accessible metal parts; measured resistance (Ω) at ≥ 10 A according 7.2.3 of IEC 60598-1: < 0,5 Ω .....:		N/A
- (9.4)	**Earthing of built-in lamp controlgear**		N/A
	Earth by means of fixing to earthed metal of luminaire in compliance of 7.2 of IEC 60598-1		N/A
	Earthing terminal only for earthing the built-in controlgear		N/A
- (9.5)	**Earthing via independent controlgear**		N/A
- (9.5.1)	Earth connection to other equipment		N/A
	Looping or through connection, conductor min. 1,5 mm² and of copper or equivalent		N/A
	Protective earthing wires in line with 5.3.1.1 and clause 7 of IEC 60598-1		N/A
- (9.5.2)	Earthing of the lamp compartments powered via the independent lamp controlgear		N/A
	Test with a current of 25 A between input and output earth terminals; measured resistance (Ω) between earthing terminal or earthing contact and each of the accessible metal parts at ≥ 10 A according 7.2.3 of IEC 60598-1: < 0,5 Ω .....:		N/A
	Output earthing terminal marked as in 7.1 t) of IEC 61347-1		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

11 (11)	MOISTURE RESISTANCE AND INSULATION		P
	After storage 48 h at 91-95% relative humidity and 20-30 °C measuring of insulation resistance:		P
	For basic insulation ≥ 2 MΩ .....:	>500 MΩ	P
	For double or reinforced insulation ≥ 4 MΩ .....:		N/A
	Between primary and secondary circuits in controlgear providing SELV, values in Annex L in IEC 61347-1		N/A

12 (12)	ELECTRIC STRENGTH		P
	Immediately after clause 11 electric strength test for 1 min		P
	Basic insulation for SELV, test voltage 500 V	500V	P
	Working voltage ≤ 50 V, test voltage 500 V		P
	Working voltage > 50 V ≤ 1000 V, test voltage (V):		N/A
	Basic insulation, 2U + 1000 V		N/A
	Supplementary insulation, 2U + 1000 V		N/A
	Double or reinforced insulation, 4U + 2000 V		N/A
	No flashover or breakdown		P
	Solid or thin sheet insulation for double or reinforced insulation fulfil the requirements in Annex N in IEC 61347-1		N/A

14 (14)	FAULT CONDITIONS		P
- (14.1)	When operated under fault conditions the controlgear:		P
	- does not emit flames or molten material		P
	- does not produce flammable gases		P
	- protection against accidental contact not impaired		P
	Thermally protected controlgear does not exceed the marked temperature value		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Fault conditions: capacitors, resistors or inductors without proof of compliance with relevant specifications have been short-circuited or disconnected	(see appended table)	P
- (14.2)	Short-circuit of creepage distances and clearances if less than specified in clause 16 in Part 1 (after any reduction in 14.2 - 14.5)	(see appended table)	N/A
- (14.3)	Short-circuit or interruption of semiconductor devices	(see appended table)	P
- (14.4)	Short-circuit across insulation consisting of lacquer, enamel or textile	(see appended table)	N/A
- (14.5)	Short-circuit across electrolytic capacitors	(see appended table)	P
- (14.6)	After the tests has been carried out on three samples:		P
	The insulation resistance ≥ 1 MΩ .....:	> 500 MΩ	P
	No flammable gases		P
	No accessible parts have become live		P
	During the tests, a five-layer tissue paper, where the test specimen is wrapped, does not ignite		P
- (14.7)	Relevant fault condition tests with high-power a.c. supply		—

15 (15)	**CONSTRUCTION**		**P**
- (15.1)	**Wood, cotton, silk, paper and similar fibrous material**		**P**
	Wood, cotton, silk, paper and similar fibrous material not used as insulation		P
- (15.2)	**Printed circuits**		**P**
	Printed circuits used as internal connections complies with clause 14		P
- (15.3)	**Plugs and socket-outlets used in SELV or ELV circuits**		**N/A**
	No dangerous compatibility between output socket-outlet and a plug for socket-outlets for input circuit in relation to installation rules, voltages and frequencies		N/A
	Plugs and socket-outlets for SELV comply with IEC 60906-3 and IEC 60884-2-4		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Plugs and socket-outlets for SELV ≤ 3 A, ≤ 25 V r.m.s. or ≤ 60 V d.c. and ≤ 72 W comply with IEC 60906-3 and IEC 60884-2-4 or:		N/A
	- plugs not able to enter socket-outlets of other standardised system		N/A
	- socket-outlets not admit plugs of other standardised system		N/A
	- socket-outlets without protective earth		N/A
- (15.4)	**Insulation between circuits and accessible parts**		**N/A**
- (15.4.2)	SELV circuits		N/A
	Source used to supply SELV circuits:		N/A
	- safety isolating transformer in accordance with relevant part 2 of IEC 61558		N/A
	- controlgear providing SELV in accordance with relevant part 2 of IEC 61347		N/A
	- another source		N/A
	Voltage in the circuit not higher than ELV		N/A
	SELV circuits insulated from LV by double or reinforced insulation		N/A
	SELV circuits insulated from non SELV circuits by double or reinforced insulation		N/A
	SELV circuits insulated from FELV circuits by supplementary insulation		N/A
	SELV circuits insulated from other SELV circuits by basic insulation		N/A
	SELV circuits insulated from accessible conductive parts according Table 6 in 15.4.5		N/A
- (15.4.3)	FELV circuits		N/A
	Source used to supply FELV circuits:		N/A
	- separating transformer in accordance with relevant part 2 of IEC 61558		N/A
	- separating controlgear providing basic insulation between input and output circuits in accordance with relevant part 2 of IEC 61347		N/A
	- another source		N/A
	- source in circuits separated by the LV supply by basic insulation		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Voltage in the circuit not higher than ELV		N/A
	FELV circuits insulated from LV supply by at least basic insulation		N/A
	FELV circuits insulated from other FELV circuits if functional purpose		N/A
	FELV circuits insulated from accessible conductive parts according Table 6 in 15.4.5		N/A
	Plugs and socket-outlets for FELV system comply with:		N/A
	- plugs not able to enter socket-outlets of other voltage systems		N/A
	- socket-outlets not admit plugs of other voltage systems		N/A
	- socket-outlets have a protective conductor contact		N/A
- (15.4.4)	Other circuits		N/A
	Insulation between circuits other than SELV or FELV and accessible conductive parts in according Table 6 in 15.4.5.		N/A
- (15.4.5)	Insulation between circuits and accessible conductive parts		N/A
	Accessible conductive parts insulated from active parts of electric circuits by insulating according Table 6		N/A
	Requirements for Class II construction with equipotential bonding for protection against indirect contact with live parts:		N/A
	- all conductive parts are connected together		N/A
	- conductive parts are reliably connected together according test of IEC 60598-1 cl. 7.2.3		N/A
	- conductive parts comply with requirements of Annex A in case of insulation fault		N/A

16 (16)	**CREEPAGE DISTANCES AND CLEARANCES** **The working voltage is bellow 60Vd.c., no values for creepage distances and clearances**		**N/A**
- (16)	Creepage distances and clearances according to 16.2 and 16.3		N/A
	Controlgears providing SELV comply with additional requirements in Annex L		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Insulating lining of metallic enclosures		N/A
	Controlgear protected against pollution comply with Annex P		N/A
- (16.2)	**Creepage distances**		N/A
- (16.2.2)	Minimum creepage distances for working voltages		N/A
	Creepage distances according to Table 7	(see appended table)	N/A
- (16.2.3)	Creepage distances for working voltages with frequencies above 30 kHz		N/A
	Creepage distances according to Table 8	(see appended table)	N/A
- (16.3)	**Clearances**		N/A
- (16.3.2)	Clearances for working voltages		N/A
	Clearances distances according to Table 9	(see appended table)	N/A
- (16.3.3)	Clearances for ignition voltages and working voltages with higher frequencies		N/A
	Clearances distances for basic or supplementary insulation according to Table 10	(see appended table)	N/A
	Clearances distances for reinforced insulation according to Table 11	(see appended table)	N/A
17 (17)	**SCREWS, CURRENT-CARRYING PARTS AND CONNECTIONS**		**N/A**
	Screws, current-carrying parts and connections in compliance with IEC 60598-1 (clause numbers between parentheses refer to IEC 60598-1)		N/A
(4.11)	**Electrical connections**		**N/A**
(4.11.1)	Contact pressure		N/A
(4.11.2)	Screws:		N/A
	- self-tapping screws		N/A
	- thread-cutting screws		N/A
(4.11.3)	Screw locking:		N/A
	- spring washer		N/A
	- rivets		N/A
(4.11.4)	Material of current-carrying parts		N/A
(4.11.5)	No contact to wood or mounting surface		N/A
(4.11.6)	Electro-mechanical contact systems		N/A
(4.12)	**Mechanical connections and glands**		N/A
(4.12.1)	Screws not made of soft metal		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Screws of insulating material		N/A
	Torque test: torque (Nm); part..... :		N/A
	Torque test: torque (Nm); part..... :		N/A
	Torque test: torque (Nm); part..... :		N/A
(4.12.2)	Screws with diameter < 3 mm screwed into metal		N/A
(4.12.4)	Locked connections:		N/A
	- fixed arms; torque (Nm)..... :		N/A
	- lampholder; torque (Nm)..... :		N/A
	- push-button switches; torque 0,8 Nm..... :		N/A
(4.12.5)	Screwed glands; force (Nm)..... :		N/A
18 (18)	**RESISTANCE TO HEAT, FIRE AND TRACKING (Refer to main report)**		**P**
- (18.1)	Ball-pressure test:		N/A
	- part tested; temperature (°C)..... :		N/A
	- part tested; temperature (°C)..... :		N/A
	- part tested; temperature (°C)..... :		N/A
- (18.2)	Test of printed boards:		N/A
	- part tested..... :		N/A
	- part tested..... :		N/A
- (18.3)	Glow-wire test (650°C):		N/A
	- part tested..... :		N/A
	- part tested..... :		N/A
- (18.4)	Needle flame test (10 s):		N/A
	- part tested..... :		N/A
	- part tested..... :		N/A
- (18.5)	Tracking test:		N/A
	- part tested..... :		N/A
	- part tested..... :		N/A
19 (19)	**RESISTANCE TO CORROSION**		N/A
	- test according 4.18.1 of IEC 60598-1		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	- adequate varnish on the outer surface		N/A
20 (-)	**ANNEXES**		P
	Comply with appropriate annexes of IEC 61347-1	(see Annexes)	P

14	**TABLE: tests of fault conditions**	**P**
Part	Simulated fault	Hazard
SL9911-B		
Output	SC, no operation	~~YES/~~NO
One LED	SC, no operation	~~YES/~~NO
One LED	OC, no operation	~~YES/~~NO

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

16 (16)	TABLE: creepage distance and clearance (mm) The working voltage is bellow 60Vd.c., no values for creepage distances and clearances						N/A
Applicable part of IEC 61347-1 Table 7 – 11*							
Distances	Insulation type **	Measured clearance	Required		Measured creepage	Required	
			clearance	*Table		creepage	*Table
Distance 1:	--	--	--	--	--	--	--
Working voltage (V)..... :					--		—
Frequency if applicable (kHz)..... :					--		—
PTI..... :					< 600 ☐	≥ 600 ☐	—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV) .....:					--		—
Pulse voltage if applicable (kV) ..... :					--		—
Supplementary information: --							
Distance 2:	--	--	--	--	--	--	--
Working voltage (V)..... :					--		—
Frequency if applicable (kHz)..... :					--		—
PTI..... :					< 600 ☐	≥ 600 ☐	—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV) .....:					--		—
Pulse voltage if applicable (kV) ..... :					--		—
Supplementary information: --							
Distance 3:	--	--	--	--	--	--	--
Working voltage (V)..... :					--		—
Frequency if applicable (kHz)..... :					--		—
PTI..... :					< 600 ☐	≥ 600 ☐	—
Peak value of the working voltage $\hat{U}_{out}$ if applicable (kV) .....:					--		—
Pulse voltage if applicable (kV) ..... :					--		—
Supplementary information: --							

** Insulation type: B – Basic; S – Supplementary; R – Reinforced

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

18 (18.1)	TABLE: Ball Pressure Test			N/A
Allowed impression diameter (mm).....:		2		—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	
--	--	--	--	
--	--	--	--	
--	--	--	--	
Supplementary information:				

18 (18.2)	TABLE: Test of printed boards				N/A
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (s)	Ignition of specified layer Yes/No	Duration of burning (s)	Verdict
--	--	--	--	--	--
--	--	--	--	--	--
--	--	--	--	--	--
Supplementary information: --					

18 (18.3)	TABLE: Glow-wire test			N/A
Glow wire temperature .....:		650°C		—
Object/ Part No./ Material	Manufacturer/ trademark	Ignition of specified layer Yes/No	Duration of burning (s)	Verdict
--	--	--	--	--
--	--	--	--	--
--	--	--	--	--
Supplementary information: --				

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

18 (18.4)	TABLE: Needle-flame test				N/A
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (s)	Ignition of specified layer Yes/No	Duration of burning (s)	Verdict
--	--	--	--	--	--
--	--	--	--	--	--
--	--	--	--	--	--
Supplementary information: --					

18 (18.5)	TABLE: Proof tracking test				N/A
Test voltage PTI .....:		175 V			—
Object/ Part No./ Material	Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
--	--	--	--	--	--
--	--	--	--	--	--
--	--	--	--	--	--
Supplementary information: --					

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

(A)	**ANNEX A - TEST TO ESTABLISH WHETHER A CONDUCTIVE PART IS A LIVE PART WHICH MAY CAUSE AN ELECTRIC SHOCK**		N/A
(A.1)	Comply with A.2 or A.3		N/A
(A.2)	Voltage ≤ 35 V peak or ≤ 60 V d.c .....:		N/A
(A.3)	If voltage measured according Clause A.2 exceeds the limit value; touch current does not exceed 0,7 mA (peak) or 2 mA d.c. .....:		N/A
	Comply with Annex G.2 of IEC 60598-1		N/A

(C)	**ANNEX C – PARTICULAR REQUIREMENTS FOR ELECTRONIC LAMP CONTROLGEAR WITH MEANS OF PROTECTION AGAINST OVERHEATING**		N/A
(C3)	**GENERAL REQUIREMENTS**		**N/A**
(C3.1)	Thermal protection means integral with the convertor, protected against mechanical damage		N/A
	Renewable only by means of a tool		N/A
	If function depending on polarity, for cord-connected equipment protection means in both leads		N/A
	Thermal links comply with IEC 60691		N/A
	Electrical controls comply with IEC 60730-2-3		N/A
(C3.2)	No risk of fire by breaking (clause C7)		N/A
(C5)	**CLASSIFICATION**		N/A
	a) automatic resetting type		—
	b) manual resetting type		—
	c) non-renewable, non-resetting type		—
	d) renewable, non-resetting type		—
	e) other type of thermal protection; description :		—
(C6)	**MARKING**		N/A
(C6.1)	Symbol for temperature declared thermally protected ballasts		N/A
(C6.2)	Declaration of the type of protection provided		N/A
(C7)	**LIMITATION OF HEATING**		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

(C7.1)	**Preselection test:**		N/A
	Test sample placed for at least 12 h in an oven having temperature (t_c - 5) K		N/A
	No operation of the protection device		N/A
(C7.2)	**Functioning of protection means:**		N/A
	Normal operation of the sample in a test enclosure according to Annex D at an ambient temperature such that (t_c +0; -5) °C is obtained		N/A
	No operation of the protection device		N/A
	Introducing of the most onerous test condition determined during test of clause 14.2 to 14.5		N/A
	Output of windings connected to the mains supply short-circuited, and other part of the controlgear operated under normal conditions		N/A
	Increasing of the current through the windings continuously until operation of the protection means		N/A
	Continuous measuring of the highest surface temperature		N/A
	Ballasts according to C5 a) or C5 e) operated until stable conditions are achieved		N/A
	Automatic-resetting thermal protectors working 3 times		N/A
	Ballasts according to C5 b) working 6 times		N/A
	Ballasts according to C5 c) and C5) d) working once		N/A
	Highest temperature does not exceed the marked value		N/A
	Any overshoot of 10% over the marked value within 15 min		N/A
	After 15 min value not exceed marked value		N/A

(D)	**ANNEX D – REQUIREMENTS FOR CARRY OUT THE HEATING TESTS OF THERMALLY PROTECTED LAMP CONTROLGEAR**		N/A
	Tests in C7 performed in accordance with Annex D, if applicable		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

(F)	**ANNEX F - DRAUGHT-PROOF ENCLOSURE**		N/A
	Draught-proof enclosure in accordance with the description		N/A
	Dimensions of the enclosure		N/A
	Other design; description		N/A

(H)	**ANNEX H - TESTS**		N/A
	All tests performed in accordance with the advice given in Annex H, if applicable		N/A

(I)	**ANNEX I – ADDITIONAL REQUIREMENTS FOR BUILT-IN MAGNETIC BALLASTS WITH DOUBLE OR REINFORCED INSULATION**		N/A
(I.6)	Symbol on ballasts with double or reinforced insulation		N/A
	Symbol explained in manufacturers catalogue		N/A
(I.9)	No protective earthing terminal		N/A
(I.12)	Devices for limiting the temperature bridged		—
	After the test according clause 13		N/A
	At least six of seven ballast start the lamp and the current not exceed 115%		N/A
	Insulation resistance not less than 4 MΩ between winding and case for all ballasts		N/A
	All ballasts withstand electric strength test reduced to 35% of values in Table 1 of IEC 61347-1		N/A
(I.15)	Built-in ballasts with double or reinforced insulation comply with corresponding values of creepage and clearances in IEC 60598-1		N/A

(L)	**ANNEX L: PARTICULAR ADDITIONAL REQUIREMENTS FOR CONTROLGEARS PROVIDING SELV**		N/A
(L.3)	**Classification**		N/A
	Class I	Yes ☐ No ☒	—
	Class II	Yes ☐ No ☒	—
	Class III	Yes ☐ No ☒	—

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	non-inherently short circuit proof controlgear	Yes ☐ No ☒	—
	inherently short circuit proof controlgear	Yes ☐ No ☒	—
	fail safe controlgear	Yes ☐ No ☒	—
	non-short-circuit proof controlgear	Yes ☐ No ☒	—
(L.4)	**Marking**		N/A
	Adequate symbols are used		N/A
(L.5)	**Protection against electric shock**		N/A
	Comply with clause 9.2 of IEC 61558-1		N/A
(L.6)	**Heating**		N/A
	No excessive temperatures in normal use		N/A
	Value if capacitor t_c marked .....:		—
	Winding insulation classified as Class .....:		—
	Comply with tests of clause 14 of IEC 61558-1 with adjustments		N/A
(L.7)	**Short-circuit and overload protection**		N/A
	Comply with tests of clause 15 of IEC 61558-1 with adjustments		N/A
(L.8)	**Insulation resistance and electric strength**		N/A
(L.8.1)	Conditioned 48 h between 91 % and 95 %		N/A
(L.8.2)	Insulation resistance		N/A
	Between input- and output circuits not less than 5 MΩ .....:		N/A
	Between metal parts of class II convertors which are separated from live parts by basic insulation only and the body not less than 5 MΩ .....:		N/A
	Between metal foil in contact with the inner and outer surfaces of enclosures of insulating material not less than 2 MΩ .....:		N/A
(L.8.3)	Electric strength		N/A
	1) Between live parts of input circuits and live parts of output circuits .....:		N/A
	2) Over basic or supplementary insulation between:		N/A
	a) live parts having different polarity .....:		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	b) live parts and body if intended to be connected to protective earth .....:		N/A
	c) accessible metal parts and a metal rod of the same diameter as the flexible cable or cord ..:		N/A
	d) live parts and an intermediate metal part ...:		N/A
	e) intermediate metal parts and the body .....:		N/A
	f) each input circuit and all other input circuits :		N/A
	3) Over reinforced insulation between the body and live parts .....:		N/A
(L.9)	**Construction**		N/A
(L.9.1)	Transformer comply with 19.12 of IEC 61558-1 and 19 of IEC 61558-2-6		N/A
	HF transformer comply with 19 of IEC 61558-2-16		N/A
(L.10)	**Components**		**N/A**
	Protective devices comply with 20.6 – 20.11 of IEC 61558-1		N/A
(L.11)	**Creepage distances, clearances and distances through insulation**		N/A
	Creepage distances and clearances not less than in Clause 16		N/A
	Distance through insulation according Table L.5 in IEC 61347-1		N/A
	1) Basic distance through insulation		N/A
	Required distance (mm) .....:		—
	Measured (mm) .....:		N/A
	Supplementary information		—
	2) Supplementary distance through insulation		N/A
	Required distance (mm) .....:		—
	Measured (mm) .....:		N/A
	Supplementary information		—
	3) Reinforced distance through insulation		N/A
	Required distance (mm) .....:		—
	Measured (mm) .....:		N/A
	Supplementary information		—

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
(N)	**ANNEX N: REQUIREMENTS FOR INSULATION MATERIALS USED FOR DOUBLE OR REINFORCED INSULATION**		N/A
(N.4)	**General requirements**		N/A
(N.4.1)	Material comply with IEC 60085 and IEC 60216 series		N/A
(N.4.2)	**Solid insulation**		N/A
	Electric strength test at least 5 kV or 1,35 x test voltage in Table N.1		N/A
	If not classified according IEC 60085 and IEC 60216 series: Electric strength test increased 10 % of 5,5 kV or 1,5 x test voltage in Table N.1		N/A
(N.4.3)	**Thin sheet insulation**		N/A
(N.4.3.1)	Thickness and composition of thin sheet insulation		N/A
	- Inside the ballast and not subjected to handling or abrasion during the production and during maintenance		N/A
	- Non-separated layers: Min. 3 layers and fulfil mandrel test of 150N		N/A
	- Separated layers: Min. 2 layers and each layer fulfil mandrel test of 50N		N/A
	- Separated layers (alternative): Min. 3 layers and 2/3 of the layers fulfil mandrel test of 100N		N/A
(N.4.3.2)	Mandrel test (electric strength test during mechanical stress)		N/A
	Electric strength test after mandrel test:		N/A
	- Non-separated layers: min. 5 kV or 1,35 x test voltage in Table N.1		N/A
	- 2/3 of min. 3 separated layers: min. 5 kV or 1,25 x test voltage in Table N.1		N/A
	- one of 2 separated layers: min. 5 kV or 1,25 x test voltage in Table N.1		N/A
	No flashover or breakdown occurred		N/A

(O)	**ANNEX O: ADDITIONAL REQUIREMENTS FOR BUILT-IN ELECTRONIC CONTROLGEAR WITH DOUBLE OR REINFORCED INSULATION**		N/A
(O.6)	**Marking**		**N/A**
	Marking according clause 7 (7)	See clause 7	N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Special symbol		N/A
	Meaning of the special symbol explained in catalogue		N/A
(O.7)	**Protection against accidental contact with live parts**		N/A
	Requirements of clause 8 (10)	See clause 8	N/A
	Test finger not possible to make contact with basic insulated metal parts		N/A
(O.8)	**Terminals**		N/A
	Clause 9 (8)	See clause 9	N/A
(O.9)	**Provision for earthing**		N/A
	Functional earthing terminals comply with clause 9 of part 1		N/A
	No protective earthing terminal		N/A
(O.10)	**Moisture resistance and insulation**		N/A
	Clause 11 (11)	See clause 11	N/A
(O.11)	**Electric strength**		N/A
	Clause 12 (12)	See clause 12	N/A
(O.13)	**Fault conditions**		N/A
	Clause 14 (14)	See clause 14	N/A
	End of test, between live part and accessible metal parts or external parts of insulating material in contact with the supporting surface comply with dielectric strength test reduced to 35 % of values according Table 1 in part 1		N/A
	Insulation resistance according to O.10 between live part and accessible metal parts or external parts of insulating material in contact with the supporting surface not less than 4 MΩ		N/A
(O.14)	**Construction**		N/A
	Clause 17 (15)	See clause 17	N/A
	Accessible metal parts insulated from live parts by double or reinforced insulation		N/A
	Live part insulated from supporting surface in contact with external faces by double or reinforced insulation		N/A
(O.15)	**Creepage distances and clearances**		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Clause 18 (16)	See clause 18	N/A
	Comply with corresponding values for luminaries in IEC 60598-1		N/A
(O.16)	**Screws, current-carrying parts and connections**		N/A
	Clause 19 (17)	See clause 19	N/A
(O.17)	**Resistance to heat and fire**		N/A
	Clause 20 (18)	See clause 20	N/A
(O.18)	**Resistance to corrosion**		N/A
	Clause 21 (19)	See clause 21	N/A
(P)	**Creepage distances and clearances and distance through isolation (DTI) for lamp controlgear which are protected against pollution by the use of coating or potting**		N/A
(P.1)	**General**		N/A
	P.2 applies if creepage distances less than the minimum in Table 7 and 8		N/A
	P.3 applies if clearance less than the minimum in Table 9, 10 and 11		N/A
(P.2)	**Creepage distances**		N/A
(P.2.2)	Minimum creepage distances for working voltages and rated voltages with frequencies up to 30 kHz (Table P.1)		N/A
	Basic or supplementary insulation:		N/A
	Required creepage.....:		—
	Measured .....:		N/A
	Supplementary information		—
	Reinforced insulation:		N/A
	Required creepage.....:		—
	Measured .....:		N/A
	Supplementary information		—
(P.2.3)	Creepage distances for working voltages with frequencies above 30 kHz (Table P.2)		N/A
	Voltage $\hat{U}_{out}$ kV .....:		—
	Frequency .....:		—
	Required distance.....:		—

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict
	Measured .....:		N/A
	Supplementary information		—
(P.2.4)	Compliance with the required creepage distances		N/A
(P.2.4.1)	Compliance in accordance with 16.3.3 and test according P.2.4.2		N/A
(P.2.4.3)	Electrical tests after conditioning		N/A
(P.2.4.3.1)	Insulation resistance and electric strength according Clause 11 and 12		N/A
(P.3)	**Distance through isolation**		N/A
(P.3.4)	Electrical tests after conditioning		N/A
(P.3.4.1)	Insulation resistance and electric strength according Clause 11 and 12		N/A
(P.3.4.2)	Impulse voltage dielectrical test		N/A
	Basic or supplementary insulation:		N/A
	Working/rated voltage .....:		—
	Impulse voltage .....:		N/A
	Supplementary information		—
	Reinforced insulation:		N/A
	Working/rated voltage .....:		—
	Impulse voltage .....:		N/A
	Supplementary information		—

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 1	TABLE: Critical components information			Refer to main report		P
Object / part No.	**Code**	**Manufacturer/ trademark**	**Type / model**	**Technical data**	**Standard**	**Mark(s) of conformity[1)]**
--	--	--	--	--	--	--
Description:						
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--
Description:						
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--
Description:						
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--

Supplementary information:

[1)] Provided evidence ensures the agreed level of compliance. See OD-CB2039.

The codes above have the following meaning:

A - The component is replaceable with another one, also certified, with equivalent characteristics

B - The component is replaceable if authorised by the test house

C - Integrated component tested together with the appliance

D - Alternative component

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	**Screw terminals (part of the luminaire)**		N/A
(14)	**SCREW TERMINALS**		N/A
(14.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(14.3.2.1)	One or more conductors		N/A
(14.3.2.2)	Special preparation		N/A
(14.3.2.3)	Terminal size		N/A
	Cross-sectional area (mm²) ..... :		—
(14.3.3)	Conductor space (mm) ..... :		N/A
(14.4)	Mechanical tests		N/A
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread)..... :	M	N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm) ..... :		N/A
	Torque (Nm) ..... :		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N) ..... :		N/A
(14.4.8)	Without undue damage		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 3	**Screwless terminals (part of the luminaire)**		N/A
(15)	**SCREWLESS TERMINALS**		N/A
(15.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A
(15.3.3)	Stop		N/A
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5)	Terminals and connections for internal wiring		N/A
(15.5.1)	Mechanical tests		N/A
(15.5.1.1.1)	Pull test spring-type terminals (4 N, 4 samples)..... :		N/A
(15.5.1.1.2)	Pull test pin or tab terminals (4 N, 4 samples)..... :		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N/A
(15.5.2)	Electrical tests		N/A
	Voltage drop (mV) after 1 h (4 samples)..... :		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples)..... :		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples)..... :		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples)..... :		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples)..... :		N/A

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

(15.6)	Terminals and connections for external wiring		N/A
(15.6.1)	Conductors		N/A
	Terminal size and rating		N/A
15.6.2	Mechanical tests		N/A
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N) .....:		N/A
(15.6.2.2)	Pull test pin or tab terminals (4 samples); pull (N) .....:		N/A
(15.6.3)	Electrical tests		N/A
	Tests according 15.6.3.1 + 15.6.3.2 in IEC 60598-1		N/A

(15.6.3.1) (15.6.3.2)	**TABLE: Contact resistance test / Heating tests**									N/A
	Voltage drop (mV) after 1 h									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										
	Voltage drop of two inseparable joints									N/A
	Voltage drop after 10th alt. 25th cycle									N/A
	Max. allowed voltage drop (mV) .....:									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										
	Voltage drop after 50th alt. 100th cycle									N/A
	Max. allowed voltage drop (mV) .....:									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										
	Continued ageing: voltage drop after 10th alt. 25th cycle									N/A
	Max. allowed voltage drop (mV) .....:									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										
	Continued ageing: voltage drop after 50th alt. 100th cycle									N/A
	Max. allowed voltage drop (mV) .....:									—
terminal	1	2	3	4	5	6	7	8	9	10
voltage drop (mV)										

EN 61347-2-11			
Clause	Requirement + Test	Result - Remark	Verdict

Supplementary information:										

P H O T O D O C U M E N T A T I O N

Attachment 2 of CN23RCT9 001

for

Portable Light


G-001

Huizhou Duran Creative Technology CO.,LTD.

This documentation consists of 13 pages (excluding this cover page)




G-001



G-001


ON / OFF
Instaflash® Designed in Barcelona (SPAIN)
made in China
(PATENTED)
RoHS


G-001



G-001




G-001




G-001




G-001




G-001




G-001




G-001


FS-0089
AQLXIAOBAI V02

G-001


QUECTEL
DBG_TXD
DBG_RTX
AUX_TXD
AUX_RTX


G-001




G-001




G-001



G-001



G-001




G-001



G-001



G-001




G-001



G-001




G-001


R1 R2
D1
DL1
C1
C4
C2 C3
T1
R8
R5
DL18
U1
R9
R4
R7
DL7
R10
R3 R6
T2
AQL-DSLEDV2.6
2022.1.03

G-001



G-001



G-001