

MOMINA ALI 30579

```
momina@DESKTOP-C65VW8A: ~/xv6-labs
momina@DESKTOP-C65VW8A:~$ cd ~/xv6-labs
momina@DESKTOP-C65VW8A:~/xv6-labs$ git branch
* assignment1
  problemSet1
  util
momina@DESKTOP-C65VW8A:~/xv6-labs$ make grade
make clean
make[1]: Entering directory '/home/momina/xv6-labs'
rm -rf *.tex *.dvi *.idx *.aux *.log *.ind *.ilg *.dSYM *.zip *.pcap \
  /*.o /*.d /*.asm /*.sym \
  kernel/kernel.fs.img \
  mkfs/mkfs.gdbinit \
  user/users.S
user/_find user/_cat user/_sixfive user/_echo user/_forktest user/_grep user/_init user/_kill user/_ln user/_ls user/_mkdir user/_rm user/_sh user/_stressfs user/_usertests
user/_grind user/_wc user/_zombie user/_logstress user/_forphan user/_dorphan user/_sync user/_sleep user/_uptime user/_mempdump
make[1]: Leaving directory '/home/momina/xv6-labs'
./grade-lab-util -v
make[1]: Entering directory '/home/momina/xv6-labs'
riscv64-linux-gnu-gcc -marchrv64gc -g -ffile-prefix-map=/home/momina/xv6-labs=. -c -o kernel/entry.o kernel/entry.S
riscv64-linux-gnu-gcc -Wall -Werror -Wno-unknown-attributes -O -fno-omit-frame-pointer -ggdb -gdwarf-2 -ffile-prefix-map=/home/momina/xv6-labs=. -DSOL_UTIL -DLAB_UTIL -marc
herv64gc -std=gnu99 -MD -mcmmodel=medany -ffreestanding -fno-common -nostdlib -fno-builtin-strncpy -fno-builtin-strncmp -fno-builtin-strlen -fno-builtin-memset -fno-builtin-
memmove -fno-builtin-memcmp -fno-builtin-log -fno-builtin-bzero -fno-builtin-strchr -fno-builtin-exit -fno-builtin-malloc -fno-builtin-putc -fno-builtin-free -fno-builtin-m
empcy -Wno-main -fno-builtin-printf -fno-builtin-fprintf -fno-builtin-vprintf -fno-builtin-protector -fno-pie -no-pie -c -o kernel/kalloc.o kernel/kalloc.c
riscv64-linux-gnu-gcc -Wall -Werror -Wno-unknown-attributes -O -fno-omit-frame-pointer -ggdb -gdwarf-2 -ffile-prefix-map=/home/momina/xv6-labs=. -DSOL_UTIL -DLAB_UTIL -marc
herv64gc -std=gnu99 -MD -mcmmodel=medany -ffreestanding -fno-common -nostdlib -fno-builtin-strncpy -fno-builtin-strncmp -fno-builtin-strlen -fno-builtin-memset -fno-builtin-
memmove -fno-builtin-memcmp -fno-builtin-log -fno-builtin-bzero -fno-builtin-strchr -fno-builtin-exit -fno-builtin-malloc -fno-builtin-putc -fno-builtin-free -fno-builtin-m
empcy -Wno-main -fno-builtin-printf -fno-builtin-fprintf -fno-builtin-vprintf -fno-builtin-protector -fno-pie -no-pie -c -o kernel/string.o kernel/string.c
riscv64-linux-gnu-gcc -Wall -Werror -Wno-unknown-attributes -O -fno-omit-frame-pointer -ggdb -gdwarf-2 -ffile-prefix-map=/home/momina/xv6-labs=. -DSOL_UTIL -DLAB_UTIL -marc
herv64gc -std=gnu99 -MD -mcmmodel=medany -ffreestanding -fno-common -nostdlib -fno-builtin-strncpy -fno-builtin-strncmp -fno-builtin-strlen -fno-builtin-memset -fno-builtin-
memmove -fno-builtin-memcmp -fno-builtin-log -fno-builtin-bzero -fno-builtin-strchr -fno-builtin-exit -fno-builtin-malloc -fno-builtin-putc -fno-builtin-free -fno-builtin-m
empcy -Wno-main -fno-builtin-printf -fno-builtin-fprintf -fno-builtin-vprintf -fno-builtin-protector -fno-pie -no-pie -c -o kernel/main.o kernel/main.c
riscv64-linux-gnu-gcc -Wall -Werror -Wno-unknown-attributes -O -fno-omit-frame-pointer -ggdb -gdwarf-2 -ffile-prefix-map=/home/momina/xv6-labs=. -DSOL_UTIL -DLAB_UTIL -marc
herv64gc -std=gnu99 -MD -mcmmodel=medany -ffreestanding -fno-common -nostdlib -fno-builtin-strncpy -fno-builtin-strncmp -fno-builtin-strlen -fno-builtin-memset -fno-builtin-
memmove -fno-builtin-memcmp -fno-builtin-log -fno-builtin-bzero -fno-builtin-strchr -fno-builtin-exit -fno-builtin-malloc -fno-builtin-putc -fno-builtin-free -fno-builtin-m
empcy -Wno-main -fno-builtin-printf -fno-builtin-fprintf -fno-builtin-vprintf -fno-builtin-protector -fno-pie -no-pie -c -o kernel/vm.o kernel/vm.c
riscv64-linux-gnu-gcc -Wall -Werror -Wno-unknown-attributes -O -fno-omit-frame-pointer -ggdb -gdwarf-2 -ffile-prefix-map=/home/momina/xv6-labs=. -DSOL_UTIL -DLAB_UTIL -marc
herv64gc -std=gnu99 -MD -mcmmodel=medany -ffreestanding -fno-common -nostdlib -fno-builtin-strncpy -fno-builtin-strncmp -fno-builtin-strlen -fno-builtin-memset -fno-builtin-
memmove -fno-builtin-memcmp -fno-builtin-log -fno-builtin-bzero -fno-builtin-strchr -fno-builtin-exit -fno-builtin-malloc -fno-builtin-putc -fno-builtin-free -fno-builtin-m
empcy -Wno-main -fno-builtin-printf -fno-builtin-fprintf -fno-builtin-vprintf -fno-builtin-protector -fno-pie -no-pie -c -o kernel/proc.o kernel/proc.c
riscv64-linux-gnu-gcc -marchrv64gc -g -ffile-prefix-map=/home/momina/xv6-labs=. -c -o kernel/switch.o kernel/switch.S
riscv64-linux-gnu-gcc -marchrv64gc -g -ffile-prefix-map=/home/momina/xv6-labs=. -c -o kernel/trampoline.o kernel/trampoline.S
```

```
momina@DESKTOP-C65VW8A: ~/xv6-labs
make[1]: Leaving directory '/home/momina/xv6-labs'
== Test sleep, no arguments ==
$ make qemu-gdb
sleep, no arguments: OK (3.6s)
== Test sleep, returns ==
$ make qemu-gdb
sleep, returns: OK (1.3s)
== Test sleep, makes syscall ==
$ make qemu-gdb
sleep, makes syscall: OK (1.4s)
== Test sixfive_test ==
$ make qemu-gdb
sixfive_test: OK (1.1s)
== Test sixfive_readme ==
$ make qemu-gdb
sixfive_readme: OK (1.5s)
== Test sixfive_all ==
$ make qemu-gdb
sixfive_all: OK (1.4s)
== Test memdump, examples ==
$ make qemu-gdb
memdump, examples: OK (1.1s)
== Test memdump, format ii, S, p ==
$ make qemu-gdb
memdump, format ii, S, p: OK (1.0s)
== Test find, in current directory ==
$ make qemu-gdb
find, in current directory: OK (1.1s)
== Test find, in sub-directory ==
$ make qemu-gdb
find, in sub-directory: OK (1.1s)
== Test find, recursive ==
$ make qemu-gdb
find, recursive: OK (1.4s)
== Test exec ==
$ make qemu-gdb
exec: OK (0.9s)
== Test exec, multiple args ==
$ make qemu-gdb
exec, multiple args: OK (1.4s)
== Test exec via sh script ==
```

30579: Command not found

momina@DESKTOP-C65VW8A:~/xv6-labs\$ make qemu

mv -f fs.img fs.img.bk

mkfs/mkfs fs.img README user/findtest.sh user/sixfive.txt user/_find user/_cat user/_sixf
er/_mkdir user/_rm user/_sh user/_stressfs user/_usertests user/_grind user/_wc user/_zom
user/_memdump

nmata 47 (boot, super, log blocks 31, inode blocks 13, bitmap blocks 1) blocks 1953 total

ballocc: first 1147 blocks have been allocated

ballocc: write bitmap block at sector 46

qemu-system-riscv64 -machine virt -bios none -kernel kernel/kernel -m 128M -smp 3 -nographic
=x0 -device virtio-blk-device,drive=x0,bus=virtio-mmio-bus.0

xv6 kernel is booting

hart 2 starting

hart 1 starting

init: starting sh

\$ uptime

131

\$ uptime

151

\$ uptime

174

\$ momina ali 30579

exec momina failed

\$ uptime

297

\$ uptime

333

\$ uptime

357

\$ uptime

443

\$

momina@DESKTOP-C65VW8A: ~/xv6-labs

```
no-stack-protector -fno-pie -no-pie -c -o user/uptime.o user/uptime.c
riscv64-linux-gnu-ld -z max-page-size=4096 -T user/user.ld -o user/_uptime user/uptime.o user/ulib.o user/umalloc.o
riscv64-linux-gnu-objdump -S user/_uptime > user/uptime.asm
riscv64-linux-gnu-objdump -t user/_uptime | sed '1,/SYMBOL TABLE/d; s/ .* / /; /^$/d' > user/uptime.sym
mkfs/mkfs fs.img README user/findtest.sh user/sixfive.txt user/_find user/_cat user/_sixfive user/_grep user/_init user/_kill user/_ln user/_ls user/_mkdir user/_rm user/_sh user/_stressfs user/_sync user/_sleep user/_wait user/_write user/_zombie user/_logstress user/_forphan user/_dorphan user/_sync user/_sleep user/_wait user/_write user/_zombie
nmeta 47 (boot, super, log blocks 31, inode blocks 13, bitmap blocks 1) blocks 1953 total 2000
ballocc: first 1150 blocks have been allocated
ballocc: write bitmap block at sector 46
qemu-system-riscv64 -machine virt -bios none -kernel kernel/kernel -m 128M -smp 3 -nographic -glc
egacy=false -drive file=fs.img,if=none,format=raw,id=x0 -device virtio-blk-device,drive=x0,bus=virtio-b
xv6 kernel is booting

hart 2 starting
hart 1 starting
init: starting sh
$
$ echo "echo hello" > test.sh
sh < test.sh$
exec "echo failed"
$ echo "echo hello" > test.sh
sh < test.sh$
exec "echo failed"
$ echo echo hello > test.sh
sh < test.sh$
hello
$
```

```
momina@DESKTOP-C65VV8A: ~/xv6-labs
hello
$
$ momina 30579
exec momina failed
$ git add .
git commit -m "Challenge: shell no prompt from file"
git push
exec git failed
$ exec git failed
$
exec git failed
$ q
exec q failed
$
$ QEMU: Terminated
momina@DESKTOP-C65VV8A:~/xv6-labs$ git add .
commit -m "Challenge: shell no prompt from file"
git push
momina@DESKTOP-C65VV8A:~/xv6-labs$ git commit -m "Challenge: shell no prompt from file"
[assignment1 36ddb7] Challenge: shell no prompt from file
1 file changed, 4 insertions(+), 2 deletions(-)
momina@DESKTOP-C65VV8A:~/xv6-labs$ git push
Enumerating objects: 7, done.
Counting objects: 100% (7/7), done.
Delta compression using up to 4 threads
Compressing objects: 100% (4/4), done.
Writing objects: 100% (4/4), 455 bytes | 455.00 KiB/s, done.
Total 4 (delta 3), reused 0 (delta 0), pack-reused 0
remote: Resolving deltas: 100% (3/3), completed with 3 local objects.
To https://github.com/MominaAli1/xv6-labs
ab7ca53..36ddb7 assignment1 -> assignment1
```

```
❏ momina@DESKTOP-C65VV8A: ~/xv6-labs
== Test find, in sub-directory ==
$ make qemu-gdb
find, in sub-directory: OK (1.1s)
== Test find, recursive ==
$ make qemu-gdb
find, recursive: OK (1.4s)
== Test exec ==
$ make qemu-gdb
exec: OK (0.9s)
== Test exec, multiple args ==
$ make qemu-gdb
exec, multiple args: OK (1.4s)
== Test exec via sh script ==
$ make qemu-gdb
exec via sh script: OK (3.0s)
== Test sleep, zero and non-numeric args return ==
$ make qemu-gdb
sleep, zero and non-numeric args return: OK (1.4s)
== Test sixfive, stdin and missing file ==
$ make qemu-gdb
sixfive, stdin and missing file: OK (2.7s)
== Test memdump, formats h c, bounds checking, usage ==
$ make qemu-gdb
memdump, formats h c, bounds checking, usage: OK (1.3s)
== Test find, missing target, no duplicates, directory match ==
$ make qemu-gdb
find, missing target, no duplicates, directory match: OK (1.9s)
== Test time ==
time: OK
Score: 156/156
momina@DESKTOP-C65VV8A:~/xv6-labs$ 30579 momina ali
30579: command not found
momina@DESKTOP-C65VV8A:~/xv6-labs$ ~;5~;5~
```