

NORTHEASTERN UNIVERSITY, KHOURY COLLEGE OF COMPUTER SCIENCE

CS 6220 Data Mining — Assignment 2

Due: January 25, 2023 (100 points)

Xinwan Wang wang.xinwa@northeastern.edu

1 Map Reduce in Spark

Write a Spark program that implements a simple "People You Might Know" social network friendship recommendation algorithm. The key idea is that if two people have a lot of mutual friends, then the system should recommend that they connect with each other.

1.1 Data

- Associated data file is soc-LiveJournal1Adj.txt in ./data/.
- The file contains the adjacency list and has multiple lines in the following format:
 User><TAB><Friends>
- Here, <User> is a unique integer ID corresponding to a unique user and <Friends> is a
 comma separated list of unique IDs corresponding to the friends of the user with the
 unique ID <User>. Note that the friendships are mutual (i.e., edges are undirected): if A
 is friend with B then B is also friend with A. The data provided is consistent with that
 rule as there is an explicit entry for each side of each edge.

1.2 Algorithm

Let us use a simple algorithm such that, for each user U, the algorithm recommends N = 10 users who are not already friends with U, but have the most number of mutual friends in common with U.

1.3 Output

 The output (call it output.txt) should contain one line per user in the following format: <User><TAB><Recommendations>

- Here, <User> is a unique ID corresponding to a user and <Recommendations> is a comma separated list of unique IDs corresponding to the algorithm's recommendation of people that <User> might know, ordered in decreasing number of mutual friends.
- Note: The exact number of recommendations per user could be less than 10. If a user has less than 10 second-degree friends, output all of them in decreasing order of the number of mutual friends. If a user has no friends, you can provide an empty list of recommendations. If there are recommended users with the same number of mutual friends, then output those user IDs in numerically ascending order.

1.4 Pipeline sketch

Please provide a description of how you used Spark to solve this problem. Don't write more than 3 to 4 sentences for this: we only want a very high-level description of your strategy to tackle this problem.

I used sc.textFile() to read txt file. Split(), map and flatMap to transit original data into readable data pairs as needed. After that, I set pairs of users who are already friends as 0, and pairs of users who have mutual friends to 1. Then I count the number of mutual friends each pair have and reduce map by key and filter out those pair who are already friends.

1.5 Tips

Use Google Colab to use Spark seamlessly, e.g., copy and adapt the setup cells from Colab 2-1, done in class in the second lecture.

- Before submitting a complete application to Spark, you may go line by line, checking the outputs of each step. Command .take(X) should be helpful, if you want to check the first X elements in the RDD.
- For sanity check, your top 10 recommendations for user ID 11 should be: 27552, 7785, 27573, 27574, 27589, 27590, 27600, 27617, 27620, 27667.
- The execution may take a while. Our implementations took around 10 minutes.

2 Submission Instructions

- Submit your Colab URL, single output file (call it output.txt) and PDF write-up only once at this Google Forms before 5pm Wednesday, January 25, 2023.
- Colab has an extensive Markdown capability, so make sure you document your code
 while writing it. Code's legibility is part of our grading criterion, so please make sure it's
 readable.
- Include a diagram of your pipeline description in your PDF writeup.
- Include in your writeup the recommendations for the users with following user IDs: 924, 8941, 8942, 9019, 9020, 9021, 9022, 9990, 9992, 9993.