counter-reset
cursor
direction
display
empty-cells
filter
flex
flex-basis
flex-direction
flex-flow
flex-grow
flex-shrink
flex-wrap
float
font
@font-face
font-family
font-kerning
font-size
font-size-adjust
font-stretch
font-style
font-variant
font-weight
hanging-punctuation
height
justify-content
@keyframes
left
letter-spacing
line-height
list-style
list-style-image
list-style-position
list-style-type
margin

CSS font-style Property

❮ Previous Complete CSS Reference Next ❯

Example

Set different font styles for three paragraphs:

```
p.normal {
    font-style: normal;
}

p.italic {
    font-style: italic;
}

p.oblique {
    font-style: oblique;
}
```

Try it Yourself »

Definition and Usage

The font-style property specifies the font style for a text.

COLOR PICKER

HOW TO

Tabs
Dropdowns

counter-reset
cursor
direction
display
empty-cells
filter
flex
flex-basis
flex-direction
flex-flow
flex-grow
flex-shrink
flex-wrap
float
font
@font-face
font-family
font-kerning
font-size
font-size-adjust
font-stretch
font-style
font-variant
font-weight
hanging-punctuation
height
justify-content
@keyframes
left
letter-spacing
line-height
list-style
list-style-image
list-style-position
list-style-type
margin

Inherited:	yes
Animatable:	no. Read about *animatable*
Version:	CSS1
JavaScript syntax:	*object*.style.fontStyle="italic" Try it

Browser Support

The numbers in the table specify the first browser version that fully supports the property.

Property					
font-style	1.0	4.0	1.0	1.0	7.0

CSS Syntax

```
font-style: normal|italic|oblique|initial|inherit;
```

Property Values

Value	Description	Play it
normal	The browser displays a normal font style. This is default	Play it »
italic	The browser displays an italic font style	Play it »
oblique	The browser displays an oblique font style	Play it »

Animated Buttons
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE

CERTIFICATES

HTML, CSS, JavaScript, PHP, jQuery, Bootstrap and XML.

Read More »

inherit	Inherits this property from its parent element. Read about *inherit*

counter-reset
cursor
direction
display
empty-cells
filter
flex
flex-basis
flex-direction
flex-flow
flex-grow
flex-shrink
flex-wrap
float
font
@font-face
font-family
font-kerning
font-size
font-size-adjust
font-stretch
font-style
font-variant
font-weight
hanging-punctuation
height
justify-content
@keyframes
left
letter-spacing
line-height
list-style
list-style-image
list-style-position
list-style-type
margin

Related Pages

CSS tutorial: CSS Font

CSS reference: font property

HTML DOM reference: fontStyle property

❮ Previous | Complete CSS Reference | Next ❯

Top 10 Tutorials
HTML Tutorial
CSS Tutorial
JavaScript Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
SQL Tutorial

Top 10 References
HTML Reference
CSS Reference
JavaScript Reference
W3.CSS Reference
Browser Statistics
PHP Reference

Top 10 Examples
HTML Examples
CSS Examples
JavaScript Examples
W3.CSS Examples
HTML DOM Examples
PHP Examples

Web Certificates
HTML Certificate
CSS Certificate
JavaScript Certificate
jQuery Certificate
PHP Certificate

counter-reset
cursor
direction
display
empty-cells
filter
flex
flex-basis
flex-direction
flex-flow
flex-grow
flex-shrink
flex-wrap
float
font
@font-face
font-family
font-kerning
font-size
font-size-adjust
font-stretch
font-style
font-variant
font-weight
hanging-punctuation
height
justify-content
@keyframes
left
letter-spacing
line-height
list-style
list-style-image
list-style-position
list-style-type
margin
margin-bottom

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2017 by Refsnes Data. All Rights Reserved.
Powered by W3.CSS.