



[ARCH LINUX](#) / [DATABASE](#) / [FAQ](#) / [MYSQL](#)

Install Apache MariaDB PHP

[Backup tools](#)
[Cloud](#)
[Database](#)
[Directory servers](#)
[Mobile](#)
[Reviews](#)
[Security](#)
[Tips and Tricks](#)
[Trouble shooting](#)
[Virtualization](#)

(LAMP) stack on Arch Linux 2016.


As you probably know, **LAMP** is the the acronym of **L**inux, **A**pache, **M**ySQL/**M**ariaDB, **P**HP/**P**erl/**P**ython. For the purpose of this article, I will be using the following test machine.

- **Operating system:** Arch Linux 2016 64 bit server
- **IP Address:** 192.168.1.102/24
- **Hostname:** server

TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W



1. Update your Arch system

FOLLOW:



Run the following command as root user to update your Arch Linux:

```
pacman -Syu
```

2. Install Apache

After updating the system, install Apache web server using command:

```
pacman -S apache
```

Edit **/etc/httpd/conf/httpd.conf** file,

```
nano /etc/httpd/conf/httpd.conf
```

Search and comment out the following line if it is not already:

```
[...]
#LoadModule unique_id_module modules/mod_unique_id.so
[...]
```

Save and close the file.

Enable Apache service to start at boot and restart Apache service using commands:

```
systemctl enable httpd
systemctl restart httpd
```

You can verify whether Apache is running or not with command:

TO SEARCH, TYPE AND

FREE EBOOK OF THE W



```
systemctl status httpd
```

FOLLOW:

**Sample output:**

```
● httpd.service - Apache Web Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; vendor preset: enabled)
   Active: active (running) since Tue 2016-02-16 13:00:18 IST; 1min 1s ago
     Main PID: 1067 (httpd)
    Tasks: 82 (limit: 512)
   CGroup: /system.slice/httpd.service
           └─1067 /usr/bin/httpd -k start -DFOREGROUND
           └─1070 /usr/bin/httpd -k start -DFOREGROUND
           └─1071 /usr/bin/httpd -k start -DFOREGROUND
           └─1072 /usr/bin/httpd -k start -DFOREGROUND

Feb 16 13:00:18 server systemd[1]: Started Apache Web Server.
Feb 16 13:00:18 server httpd[1067]: AH00558: httpd: Could not spawn a new child, please see the error log for more details.
Hint: Some lines were ellipsized, use -l to show in full.
```

Apache server is ready to use.

Test Apache

Let us create a sample page in the Apache root directory , i.e **/srv/http**.

```
nano /srv/http/index.html
```


Add the following line:

```
<html>
<title>Welcome</title>
<body>
  <h2>Welcome to OSTechNix test page</h2>
</body>
</html>
```

TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W




```
</body>  
</html>
```

FOLLOW:



Now, open your web browser and navigate to **http://localhost** or **http://IP-address**. You will be pleased with Apache server Test page.



Welcome to OSTechNix test page

3. Install MariaDB

Run the following command to install MariaDB:

```
pacman -S mysql
```

As you may know, MariaDB is now officially the default implementation of MySQL in Arch Linux since 2013. So, you will be asked whether to install MariaDB or Percona server, just hit enter and then type "Y" and press enter again. The default selection i.e MariaDB will be installed on your Arch Linux.

```
resolving dependencies...  
looking for conflicting packages...  
  
Packages (7) boost-libs-1.60.0-2 icu-56.1-2 jemalloc-4.0.4-1  
libmariadbclient-10.1.11-1 libxml2-2.9.3-1  
mariadb-clients-10.1.11-1 mariadb-10.1.11-1  
  
Total Download Size: 30.68 MiB  
Total Installed Size: 218.10 MiB  
  
:: Proceed with installation? [Y/n] n  
[root@server ~]# pacman -S mysql  
:: There are 2 providers available for mysql:
```

TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W



FOLLOW:



```
:: Repository extra
 1) mariadb
:: Repository community
 2) percona-server

Enter a number (default=1): ## Press Enter

resolving dependencies...
looking for conflicting packages...

Packages (7) boost-libs-1.60.0-2 icu-56.1-2 jemalloc-4.0.4-1
libmariadbclient-10.1.11-1 libxml2-2.9.3-1
mariadb-clients-10.1.11-1 mariadb-10.1.11-1

Total Download Size: 30.68 MiB
Total Installed Size: 218.10 MiB

:: Proceed with installation? [Y/n] y
```

You need to initialize the MariaDB data directory prior to starting the service. To do so, run:

```
mysql_install_db --user=mysql --basedir=/usr --datadir=/var/
```

Then issue the following command to enable and start MariaDB service.

```
systemctl enable mysqld
systemctl start mysqld
```

You can verify whether MariaDb is running or not using command:

```
systemctl status mysqld
```

TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W



Sample output:

FOLLOW:



```
● mysqld.service - MariaDB database server
   Loaded: loaded (/usr/lib/systemd/system/mysqld.service; disabled; vendor preset: enabled)
   Active: active (running) since Tue 2016-02-16 13:19:50 IST; 1min 1s ago
     Process: 1406 ExecStartPost=/usr/bin/mysqld-post (code=exit status; PID=1405)
    Main PID: 1405 (mysqld)
      Tasks: 26 (limit: 512)
   CGroup: /system.slice/mysqld.service
           └─1405 /usr/bin/mysqld --pid-file=/run/mysqld/mysqld.pid

Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: 2016-02-16 13:19:49 139
Feb 16 13:19:49 server mysqld[1405]: Version: '10.1.11-MariaDB'
Feb 16 13:19:50 server systemd[1]: Started MariaDB database server.
Hint: Some lines were ellipsized, use -l to show in full.
```

Setup MySQL/MariaDB root user password

As you may know, It is recommended to setup a password for database root user.

Run the following command to setup MariaDB root user password:

```
mysql_secure_installation
```

Sample output:

TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W





NOTE: RUNNING ALL PARTS OF THIS SCRIPT IS RECOMMENDED FOR ALL
SERVERS IN PRODUCTION USE! PLEASE READ EACH STEP CAREFULLY!

In order to log into MariaDB to secure it, we'll need the current
password for the root user. If you've just installed MariaDB
you haven't set the root password yet, the password will be empty,
so you should just press enter here.

Enter current password for root (enter for none): **## Press Enter**
OK, successfully used password, moving on...

Setting the root password ensures that nobody can log into the
root user without the proper authorisation.

Set root password? [Y/n] **## Press Enter**
New password: **## Enter password**
Re-enter new password: **## Re-enter password**
Password updated successfully!
Reloading privilege tables..
... Success!

By default, a MariaDB installation has an anonymous user, allowing
anybody to log into MariaDB without having to have a user account or
password. This is intended only for testing, and to make the install
go a bit smoother. You should remove them before moving into
production environment.

Remove anonymous users? [Y/n] **## Press Enter**
... Success!


Normally, root should only be allowed to connect from 'localhost'. This
ensures that someone cannot guess at the root password from the
network.

Disallow root login remotely? [Y/n] **## Press Enter**

TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W





```
... Success!
```

```
By default, MariaDB comes with a database named 'test' that
access. This is also intended only for testing, and should be
before moving into a production environment.
```

```
Remove test database and access to it? [Y/n]## Press Enter
```

```
- Dropping test database...
```

```
... Success!
```

```
- Removing privileges on test database...
```

```
... Success!
```

```
Reloading the privilege tables will ensure that all changes
will take effect immediately.
```

```
Reload privilege tables now? [Y/n]## Press Enter
```

```
... Success!
```

```
Cleaning up...
```

```
All done! If you've completed all of the above steps, your M
installation should now be secure.
```

```
Thanks for using MariaDB!
```

MariaDB has been installed and ready to use.

4. Install PHP

To install PHP in Arch Linux, run:

```
pacman -S php php-apache
```

After PHP is installed, we need to configure Apache PHP module.

To do so, edit **/etc/httpd/conf/httpd.conf** file,

TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W




```
nano /etc/httpd/conf/httpd.conf
```

FOLLOW:



Find the following line and comment it out:

```
[...]
#LoadModule mpm_event_module modules/mod_mpm_event.so
[...]
```

Then, add the following lines at the bottom:

```
[...]
LoadModule mpm_prefork_module modules/mod_mpm_prefork.so
LoadModule php7_module modules/libphp7.so
AddHandler php7-script php
Include conf/extra/php7_module.conf
```

Save and close the file.

Test PHP

Now create a **test.php** file in the Apache root directory.

```
nano /srv/http/test.php
```

Add the following lines:

```
<?php
phpinfo();
?>
```

Restart httpd service.

TO SEARCH, TYPE AND

FREE EBOOK OF THE W



```
systemctl restart httpd
```

Open up your web browser and navigate to **http://ip-address/test.php**. You should see the screen like below.

FOLLOW:



5. Install phpMyAdmin

phpMyAdmin is a graphical MySQL/MariaDB administration tool that can be used to create, edit and delete databases.

To install it, run:

TO SEARCH, TYPE AND

FREE EBOOK OF THE W



```
pacman -S phpmyadmin php-mcrypt
```

FOLLOW:



After installing, edit **php.ini** file,

```
nano /etc/php/php.ini
```

Make sure the following lines are uncommented.

```
[...]  
extension=bz2.so  
extension=mcrypt.so  
extension=mysqli.so  
[...]
```

Save and close the file.

Next, create configuration file for phpMyAdmin,

```
nano /etc/httpd/conf/extra/phpmyadmin.conf
```

Add the following lines:

```
Alias /phpmyadmin "/usr/share/webapps/phpMyAdmin"  
<Directory "/usr/share/webapps/phpMyAdmin">  
    DirectoryIndex index.php  
    AllowOverride All  
    Options FollowSymlinks  
    Require all granted  
</Directory>
```

Then, open Apache configuration file,

TO SEARCH, TYPE AND

FREE EBOOK OF THE W



```
nano /etc/httpd/conf/httpd.conf
```

Add the following line at the end:

```
Include conf/extra/phpmyadmin.conf
```

Save and close the file. Restart httpd service.

```
systemctl restart httpd
```

Test phpMyAdmin

Open your browser and navigate to **http://IP-Address/phpmyadmin**. You should see the following like screen. Enter the MySQL/MariaDB root username and it's password.


FOLLOW:



TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W



FOLLOW:



Here it is how my phpMyAdmin web console looks like.

TO SEARCH, TYPE AND

FREE EBOOK OF THE W





You might see an error that says **“The configuration file now needs a secret passphrase (blowfish_secret)”** at the bottom of phpMyAdmin dashboard.

TO SEARCH, TYPE AND

FREE EBOOK OF THE W






To get rid of this error, edit **/etc/webapps/phpmyadmin/config.inc.php** file,

```
nano /etc/webapps/phpmyadmin/config.inc.php
```

Find the following line and specify bluefish secret passphrase:

```
$cfg['blowfish_secret'] = 'Welc0me1'; /* YOU MUST FILL IN TH
```

```
/* *
```



Here **Welc0me1** is my secret passphrase. Save and close the file. Restart Apache service.

```
systemctl restart httpd
```

The error will be gone now.

That's all for now. At this stage, you have a working LAMP stack, and is ready to host your websites.

If you want to use Nginx instead of Apache web server, refer the following article.

- **Installing and configuring Nginx, MySQL, PHP (LEMP) stack on Arch Linux 2016**

If you find this tutorial helpful, please share it on your social networks and support us.

Thanks for reading!

Cheers!!

FOLLOW:



TO SEARCH, TYPE AND

Custom Search


FREE EBOOK OF THE W



FOLLOW:



Share this:

Tags: [Apache](#) [Apache HTTP Server](#) [Arch Linux 2016](#) [LAMP Stack](#) [MariaDB](#) [PHP](#)

PREVIOUS STORY



How to fix "unable to lock
database" error in Arch linux

NEXT STORY




Install MATE Desktop in FreeBSD
10.2

YOU MAY ALSO LIKE...

TO SEARCH, TYPE AND

FREE EBOOK OF THE W



How to install PXE
Server on Ubuntu 16.04

AUGUST 8, 2016

Arch Linux 2016 post
installation

FEBRUARY 6, 2016

FOLLOW:



How To Reset Root
User Password In Linux

FEBRUARY 18, 2016

Sponsored



Report ad

13 Comments ostechnix

Login

Recommend 5 Share

Sort by Best



Join the discussion...

LOG IN WITH

OR SIGN UP WITH DISQUS ?

Name



Jess Maya • a year ago

Thank you! Very easy and usefull.

TO SEARCH, TYPE AND

Custom Search

FREE EBOOK OF THE W





2 ^ | v • Reply • Share ›

**Pranav Nutalapati** • a year ago

Super easy and completely accurate! Thank you very much!

1 ^ | v • Reply • Share ›

**Aimeric Oni** • 2 years ago

Thank you A LOT !

1 ^ | v • Reply • Share ›

Comments continue after advertisement

Best Defense Against Attacker Is NOT Pepper Spray

Safety experts say this tiny device (not pepper spray) is the most effective way to protect yourself against an attacker.

[Learn More](#)

Sponsored by Safesound Personal Alarm

[Report ad](#)**Kershing Flores** • 2 years ago

You are big man... Thanks

1 ^ | v • Reply • Share ›

**Chamuth Chamandana** • 7 days ago

Thank you very very much!!!! Best tutorial / walkthrough of LAMP stack installation :D

^ | v • Reply • Share ›

**Rizky Aidil Adha** • a month ago

Thanks is work for manjaro too

^ | v • Reply • Share ›

**Paulo Grian** • 3 months ago

thankyou. this is working until now. other tutorials are outdated.

^ | v • Reply • Share ›

**Luc** • 3 months ago

Very useful, a very detailed guide. Thanks a lot.

^ | v • Reply • Share ›

**Soenke Dohrn** • 5 months ago

great tutorial! Thank you, very helpful indeed.

^ | v • Reply • Share ›


FOLLOW:



TO SEARCH, TYPE AND

[Custom Search](#)

FREE EBOOK OF THE W



Comments continue after advertisement

FOLLOW:



Get Hit with Ransomware? Why Forego the Ransom

There are a variety of different ransomware variants that encrypt your data with no intention of ever decrypting it.

[Learn More](#)

Sponsored by Comcast

[Report ad](#)**Andrew Mott** • 7 months ago

Best LAMP setup walk-through EVER.

[^](#) | [v](#) • [Reply](#) • [Share](#) ›**Santiago Molina** • 9 months ago

thanks, very easy ;)

[^](#) | [v](#) • [Reply](#) • [Share](#) ›**Rahul Sharma** • 9 months ago

Super-awesome tutorial!! Thanks a ton!

[^](#) | [v](#) • [Reply](#) • [Share](#) ›**Madman** • 10 months ago

Thank you very much!

[^](#) | [v](#) • [Reply](#) • [Share](#) ›[✉ Subscribe](#) [⚙ Add Disqus to your siteAdd DisqusAdd](#) [🔒 Privacy](#)

Millions Of Americans Pay Nothing For Cable TV

Millions of Americans are getting FREE TV in HD thanks to the newly released ClearView HDTV Antenna.

[Learn More](#)

Sponsored by ClearView Antenna

[Report ad](#)

TO SEARCH, TYPE AND

[Custom Search](#)

FREE EBOOK OF THE W



EMAIL NEWSLETTER

Subscribe to our mailing list**Sign Up Now****We respect your privacy**

TODAY'S MOST READ

How To Find The Size Of A Directory In Linux
3 Good Alternatives To Man Pages Every Linux User
Should Know
How To Install Arch Linux Latest Version
How to clear Command line history in Linux
Install and configure DNS server in Ubuntu 16.04 LTS
How To Install Yaourt In Arch Linux
Configure GRUB2 Boot Loader Settings In Ubuntu 16.04
Install VSFTPD server in Ubuntu 16.04 LTS
Install DHCP Server in Ubuntu 16.04
Install Microsoft Windows Fonts in Ubuntu

WHO WE ARE

- [About](#)
- [Contact Us](#)
- [Donate](#)
- [Privacy Policy](#)
- [Sitemap](#)
- [Terms and Conditions](#)

FOLLOW:



OSTechNix © 2017. All Rights Reserved.

This site is licensed under CC BY-NC 4.0.



TO SEARCH, TYPE AND

FREE EBOOK OF THE W

