

HTML5 Tutorial

[HTML HOME](#)[HTML Introduction](#)[HTML Editors](#)[HTML Basic](#)[HTML Elements](#)[HTML Attributes](#)[HTML Headings](#)[HTML Paragraphs](#)[HTML Styles](#)[HTML Formatting](#)[HTML Quotations](#)[HTML Comments](#)[HTML Colors](#)[HTML CSS](#)[HTML Links](#)[HTML Images](#)[HTML Tables](#)[HTML Lists](#)[HTML Blocks](#)[HTML Classes](#)[HTML Iframes](#)[HTML JavaScript](#)[HTML File Paths](#)[HTML Head](#)[HTML Layout](#)[HTML Responsive](#)[HTML Computercode](#)[HTML Entities](#)[HTML Symbols](#)

HTML Styles - CSS

[◀ Previous](#)[Next ▶](#)

CSS = Styles and
Colors

M a n i p u l a t e T e x t
C o l o r s , B o x e s

Styling HTML with CSS

CSS stands for **C**ascading **S**tyle **S**heets.

CSS describes **how HTML elements are to be displayed on screen, paper, or in other media.**

CSS **saves a lot of work.** It can control the layout of multiple web pages all at once.

CSS can be added to HTML elements in 3 ways:

- **Inline** - by using the style attribute in HTML elements
- **Internal** - by using a <style> element in the <head> section
- **External** - by using an external CSS file

COLOR PICKER



HOW TO

Tabs
Dropdowns

HTML Charset
HTML URL Encode
HTML XHTML

HTML Forms

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

The most common way to add CSS, is to keep the styles in separate CSS files. However, here we will use inline and internal styling, because this is easier to demonstrate, and easier for you to try it yourself.

Tip: You can learn much more about CSS in our [CSS Tutorial](#).

Inline CSS

An inline CSS is used to apply a unique style to a single HTML element.

An inline CSS uses the style attribute of an HTML element.

This example sets the text color of the <h1> element to blue:

Example

```
<h1 style="color:blue;">This is a Blue Heading</h1>
```

Try it Yourself »

Internal CSS

An internal CSS is used to define a style for a single HTML page.

An internal CSS is defined in the <head> section of an HTML page, within a <style> element:

Accordions
Convert Weights
Animated Buttons
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML, CSS,
JavaScript, PHP,
jQuery, Bootstrap and
XML.

Read More »

HTML Charset
HTML URL Encode
HTML XHTML

HTML Forms

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

Example

```
<!DOCTYPE html>
<html>
<head>
<style>
  body {background-color: powderblue;}
  h1   {color: blue;}
  p    {color: red;}
</style>
</head>
<body>

<h1>This is a heading</h1>
<p>This is a paragraph.</p>

</body>
</html>
```

Try it Yourself »

External CSS

An external style sheet is used to define the style for many HTML pages.

With an external style sheet, you can change the look of an entire web site, by changing one file!

To use an external style sheet, add a link to it in the <head> section of the HTML page:

Example

```
<!DOCTYPE html>
<html>
<head>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
```

HTML Charset
HTML URL Encode
HTML XHTML
HTML Forms

```
<h1>This is a heading</h1>  
<p>This is a paragraph.</p>  
  
</body>  
</html>
```

Try it Yourself »

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

An external style sheet can be written in any text editor. The file must not contain any HTML code, and must be saved with a .css extension.

Here is how the "styles.css" looks:

```
body {  
    background-color: powderblue;  
}  
h1 {  
    color: blue;  
}  
p {  
    color: red;  
}
```

CSS Fonts

The CSS **color** property defines the text color to be used.

The CSS **font-family** property defines the font to be used.

The CSS **font-size** property defines the text size to be used.

Example

```
<!DOCTYPE html>  
<html>  
<head>  
<style>  
h1 {
```

HTML Charset
HTML URL Encode
HTML XHTML

HTML Forms

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

```
color: blue;
font-family: verdana;
font-size: 300%;
}
p {
color: red;
font-family: courier;
font-size: 160%;
}
</style>
</head>
<body>

<h1>This is a heading</h1>
<p>This is a paragraph.</p>

</body>
</html>
```

[Try it Yourself »](#)

CSS Border

The CSS **border** property defines a border around an HTML element:

Example

```
p {
border: 1px solid powderblue;
}
```

[Try it Yourself »](#)

CSS Padding

The CSS **padding** property defines a padding (space) between the text and the border:

HTML Charset
HTML URL Encode
HTML XHTML

HTML Forms

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

Example

```
p {  
    border: 1px solid powderblue;  
    padding: 30px;  
}
```

Try it Yourself »

CSS Margin

The CSS **margin** property defines a margin (space) outside the border:

Example

```
p {  
    border: 1px solid powderblue;  
    margin: 50px;  
}
```

Try it Yourself »

The id Attribute

To define a specific style for one special element, add an id attribute to the element:

```
<p id="p01">I am different</p>
```

then define a style for the element with the specific id:

Example

HTML Charset
HTML URL Encode
HTML XHTML

HTML Forms

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

```
#p01 {  
    color: blue;  
}
```

Try it Yourself »

Note: The id of an element should be unique within a page, so the id selector is used to select one unique element!

The class Attribute

To define a style for a special type of elements, add a class attribute to the element:

```
<p class="error">I am different</p>
```

then define a style for the elements with the specific class:

Example

```
p.error {  
    color: red;  
}
```

Try it Yourself »

External References

External style sheets can be referenced with a full URL or with a path relative to the current web page.

This example uses a full URL to link to a style sheet:

Example

HTML Charset
HTML URL Encode
HTML XHTML

HTML Forms

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

```
<link rel="stylesheet" href="https://www.w3schools.com/html/styles.css">
```

Try it Yourself »

This example links to a style sheet located in the html folder on the current web site:

Example

```
<link rel="stylesheet" href="/html/styles.css">
```

Try it Yourself »

This example links to a style sheet located in the same folder as the current page:

Example

```
<link rel="stylesheet" href="styles.css">
```

Try it Yourself »

You can read more about file paths in the chapter [HTML File Paths](#).

Chapter Summary

- Use the HTML **style** attribute for inline styling
- Use the HTML **<style>** element to define internal CSS
- Use the HTML **<link>** element to refer to an external CSS file
- Use the HTML **<head>** element to store <style> and <link> elements
- Use the CSS **color** property for text colors
- Use the CSS **font-family** property for text fonts
- Use the CSS **font-size** property for text sizes
- Use the CSS **border** property for borders
- Use the CSS **padding** property for space inside the border
- Use the CSS **margin** property for space outside the border

HTML Charset
HTML URL Encode
HTML XHTML
HTML Forms

Test Yourself with Exercises!

[Exercise 1 »](#)[Exercise 2 »](#)[Exercise 3 »](#)[Exercise 4 »](#)[Exercise 5 »](#)[Exercise 6 »](#)

HTML Style Tags

Tag	Description
<u><style></u>	Defines style information for an HTML document
<u><link></u>	Defines a link between a document and an external resource

[« Previous](#)[Next »](#)

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

HTML Charset
HTML URL Encode
HTML XHTML

HTML Forms

HTML5 Tutorial

HTML HOME
HTML Introduction
HTML Editors
HTML Basic
HTML Elements
HTML Attributes
HTML Headings
HTML Paragraphs
HTML Styles
HTML Formatting
HTML Quotations
HTML Comments
HTML Colors
HTML CSS
HTML Links
HTML Images
HTML Tables
HTML Lists
HTML Blocks
HTML Classes
HTML Iframes
HTML JavaScript
HTML File Paths
HTML Head
HTML Layout
HTML Responsive
HTML Computercode
HTML Entities
HTML Symbols

REPORT ERROR

PRINT PAGE

FORUM

ABOUT

Top 10 Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
SQL Tutorial
PHP Tutorial
jQuery Tutorial
Angular Tutorial
XML Tutorial

Top 10 References

HTML Reference
CSS Reference
JavaScript Reference
W3.CSS Reference
Browser Statistics
PHP Reference
HTML Colors
HTML Character Sets
jQuery Reference
AngularJS Reference

Top 10 Examples

HTML Examples
CSS Examples
JavaScript Examples
W3.CSS Examples
HTML DOM Examples
PHP Examples
ASP Examples
jQuery Examples
Angular Examples
XML Examples

Web Certificates

HTML Certificate
CSS Certificate
JavaScript Certificate
jQuery Certificate
PHP Certificate
Bootstrap Certificate
XML Certificate

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2017 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

