

# OS Project-1 Report

*Introduction to Linux Kernel Modules*

ZHOU YIYUAN

516021910270  
1025152261@qq.com

# 1 Module: simple

## 1.1 Requirements

- (a) Print out the value of GOLDEN\_RATIO\_PRIME in the simple init() function.
- (b) Print out the greatest common divisor of 3,300 and 24 in the simple exit() function.
- (c) Print out the values of jiffies and HZ in the simple init() function.
- (d) Print out the value of jiffies in the simple exit() function.

## 1.2 Code

---

```

#include <linux/init.h>
#include <linux/kernel.h>
#include <linux/module.h>
#include <linux/hash.h>
#include <linux/gcd.h>
#include <asm/param.h>
#include <linux/jiffies.h>

int simple_init(void)
{
    printk(KERN_INFO "Loading Kernel Module\n");
    printk(KERN_INFO "GOLDEN_RATIO_PRIME: %lu\n", GOLDEN_RATIO_PRIME);
    printk(KERN_INFO "HZ: %d\n", HZ);
    printk(KERN_INFO "jiffies: %lu\n", jiffies);

    return 0;
}

void simple_exit(void)
{
    printk(KERN_INFO "Removing Kernel Module\n");
    printk(KERN_INFO "%d\n", gcd(3300, 24));
    printk(KERN_INFO "jiffies: %lu\n", jiffies);
}

module_init(simple_init);
module_exit(simple_exit);

MODULE_LICENSE("GPL");
MODULE_DESCRIPTION("Simple Module");
MODULE_AUTHOR("ZYY");

```

---

## 1.3 Result

The result is shown as Figure 1.

```
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/simple$ sudo insmod simple.ko
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/simple$ dmesg
[10183.177194] Loading Kernel Module
[10183.177196] GOLDEN_RATIO_PRIME: 7046029254386353131
[10183.177197] HZ: 250
[10183.177198] jiffies: 4297438122
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/simple$ sudo rmmod simple
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/simple$ dmesg
[10183.177194] Loading Kernel Module
[10183.177196] GOLDEN_RATIO_PRIME: 7046029254386353131
[10183.177197] HZ: 250
[10183.177198] jiffies: 4297438122
[10201.051873] Removing Kernel Module
[10201.051876] 12
[10201.051877] jiffies: 4297442590
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/simple$
```

Figure 1: Result of simple module

## 2 Module: hello

### 2.1 Requirements

Print out "Hello World" when the command "cat /proc/hello" is entered.

### 2.2 Code

```
#include <linux/init.h>
#include <linux/kernel.h>
#include <linux/module.h>
#include <linux/proc_fs.h>
#include <linux/uaccess.h>

#define BUFFER_SIZE 128
#define PROC_NAME "hello"

ssize_t proc_read(struct file *file, char __user *usr_buf, size_t count, loff_t
↳ *pos);

static struct file_operations proc_ops = {
    .owner = THIS_MODULE,
    .read = proc_read,
};
```

```

int proc_init(void)
{
    proc_create(PROC_NAME, 0666, NULL, &proc_ops);

    return 0;
}

void proc_exit(void)
{
    remove_proc_entry(PROC_NAME, NULL);
}

ssize_t proc_read(struct file *file, char __user *usr_buf, size_t count, loff_t
↪ *pos)
{
    int rv = 0;
    char buffer[BUFFER_SIZE];
    static int completed = 0;

    if(completed){
        completed = 0;
        return 0;
    }

    completed = 1;

    rv = sprintf(buffer, "Hello World\n");

    copy_to_user(usr_buf, buffer, rv);

    return rv;
}
module_init(proc_init);
module_exit(proc_exit);

MODULE_LICENSE("GPL");
MODULE_DESCRIPTION("HELLO MODULE");
MODULE_AUTHOR("ZYY");

```

---

## 2.3 Result

The result is shown as Figure 2.

```

zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/hello$ sudo insmod hello.ko
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/hello$ cat /proc/hello
Hello World
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/hello$

```

Figure 2: Result of hello module

## 3 Module: jiffies

### 3.1 Requirements

Design a kernel module that creates a /proc file named /proc/jiffies that reports the current value of jiffies when the /proc/jiffies file is read, such as with the command

```
$ cat /proc/jiffies
```

Be sure to remove /proc/jiffies when the module is removed.

### 3.2 Code

```

#include <linux/init.h>
#include <linux/kernel.h>
#include <linux/module.h>
#include <linux/proc_fs.h>
#include <linux/uaccess.h>
#include <linux/jiffies.h>

#define BUFFER_SIZE 128
#define PROC_NAME "jiffies"

ssize_t proc_read(struct file *file, char __user *usr_buf, size_t count, loff_t
↳ *pos);

static struct file_operations proc_ops = {
    .owner = THIS_MODULE,
    .read = proc_read,
};

int proc_init(void)
{
    proc_create(PROC_NAME, 0666, NULL, &proc_ops);

    return 0;
}

void proc_exit(void)

```

```

{
    remove_proc_entry(PROC_NAME, NULL);
}

ssize_t proc_read(struct file *file, char __user *usr_buf, size_t count, loff_t
↪ *pos)
{
    int rv = 0;
    char buffer[BUFFER_SIZE];
    static int completed = 0;

    if(completed){
        completed = 0;
        return 0;
    }

    completed = 1;

    rv = sprintf(buffer, "jiffies: %lu\n", jiffies);

    copy_to_user(usr_buf, buffer, rv);

    return rv;
}
module_init(proc_init);
module_exit(proc_exit);

MODULE_LICENSE("GPL");
MODULE_DESCRIPTION("JIFFIES MODULE");
MODULE_AUTHOR("ZYY");

```

---

### 3.3 Result

The result is shown as Figure 3

## 4 Module: seconds

### 4.1 Requirements

Design a kernel module that creates a proc file named `/proc/seconds` that reports the number of elapsed seconds since the kernel module was loaded. This will involve using the value of `jiffies` as well as the `HZ` rate. When a user enters the command

```
$ cat /proc/seconds
```

your kernel module will report the number of seconds that have elapsed since the kernel module was first loaded. Be sure to remove `/proc/seconds` when the module is removed.

```

zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/jiffies$ sudo insmod jiffies.ko
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/jiffies$ cat /proc/jiffies
jiffies: 4299216301
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/jiffies$ cat /proc/jiffies
jiffies: 4299217489
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/jiffies$ cat /proc/jiffies
jiffies: 4299218543
zhouyiyuan@zhouyiyuan-CW65S:~/OS-Project/project1/jiffies$ █

```

Figure 3: Result of jiffies module

## 4.2 Code

```

#include <linux/init.h>
#include <linux/kernel.h>
#include <linux/module.h>
#include <linux/proc_fs.h>
#include <linux/uaccess.h>
#include <linux/jiffies.h>
#include <asm/param.h>

#define BUFFER_SIZE 128
#define PROC_NAME "seconds"

ssize_t proc_read(struct file *file, char __user *usr_buf, size_t count, loff_t
↳ *pos);

long unsigned init_jiffies = 0;

static struct file_operations proc_ops = {
    .owner = THIS_MODULE,
    .read = proc_read,
};

int proc_init(void)
{
    init_jiffies = jiffies;
    proc_create(PROC_NAME, 0666, NULL, &proc_ops);

    return 0;
}

void proc_exit(void)
{
    remove_proc_entry(PROC_NAME, NULL);
}

```

```

}

ssize_t proc_read(struct file *file, char __user *usr_buf, size_t count, loff_t
↳ *pos)
{
    int rv = 0;
    char buffer[BUFFER_SIZE];
    static int completed = 0;

    if(completed){
        completed = 0;
        return 0;
    }

    completed = 1;

    rv = sprintf(buffer, "seconds: %lu\n", (jiffies - init_jiffies) / HZ);

    copy_to_user(usr_buf, buffer, rv);

    return rv;
}
module_init(proc_init);
module_exit(proc_exit);

MODULE_LICENSE("GPL");
MODULE_DESCRIPTION("SECONDS MODULE");
MODULE_AUTHOR("ZYY");

```

### 4.3 Result

The result is shown as Figure 4

```

zhouiyuan@zhouiyuan-CW65S:~/OS-Project/project1/seconds$ sudo insmod seconds.ko
zhouiyuan@zhouiyuan-CW65S:~/OS-Project/project1/seconds$ cat /proc/seconds
seconds: 17
zhouiyuan@zhouiyuan-CW65S:~/OS-Project/project1/seconds$ cat /proc/seconds
seconds: 23
zhouiyuan@zhouiyuan-CW65S:~/OS-Project/project1/seconds$ cat /proc/seconds
seconds: 30
zhouiyuan@zhouiyuan-CW65S:~/OS-Project/project1/seconds$ sudo rmmod seconds
zhouiyuan@zhouiyuan-CW65S:~/OS-Project/project1/seconds$ █

```

Figure 4: Result of seconds module