



Análisis de resultados



+

•

○



$$S = \sqrt{\frac{\sum_{i=1}^n (X_i - \bar{X})^2}{n - 1}}$$

$$d = z_{\frac{\alpha}{2}} * \frac{S}{\sqrt{n}}$$

$$+ d = z_{\frac{\alpha}{2}} * \frac{S}{\sqrt{n}}$$

•

○

+
•
○

$n^{\circ} \text{corridas} = 30$

Sistema Base

$\bar{T} = 123,27 \text{ seg}$

Sistema Desfasado

$\bar{T} = 128,28 \text{ seg}$

Sistema Sincronizado

$\bar{T} = 129,818 \text{ seg}$



+
•
o

Sistema Base Sistema Desfasado Sistema Sincronizado

$$S = 2,06$$

$$d = 0,74 \text{ seg}$$



(122,53; 124,01)

$$S = 1,69$$

$$d = 0,605 \text{ seg}$$



(127,68; 128,88)

$$S = 1,75$$

$$d = 0,63 \text{ seg}$$



(129,19; 130,45)





Comparación de resultados





$$Z_{Base-Desfasado} = 123,27 - 128,28 = -5,01 < 0$$

$$Z_{Base-Sincronizado} = 123,27 - 129,818 = -6,548 < 0$$

$$Z_{Desfasado-Sincronizado} = 128,28 - 129,818 = -1,538 < 0$$





Conclusiones

