

eSal Backend Changes - Swift Integration Brief

2026-07-17 · covers every endpoint added or changed in this session

Summary: one field (transactionDate) was added across six existing endpoints - additive, nothing breaks if ignored. One existing endpoint's data went from hardcoded mock to real (/dashboard's smartOffers) - same shape, but now can return an empty array. Two brand-new endpoints exist but are backend-only for now - no UI needed yet, included here for reference.

1. Field added: transactionDate

Every affected endpoint gained one new field in its response. No other field changed. Type is always the same:

```
transactionDate: string | null    // ISO 8601 date-time, e.g. "2026-07-15T14:32:00.000Z"  
                                // null if the receipt's date wasn't printed/detected
```

Method & Path	Auth	Where the field appears
GET /receipts	Bearer JWT (customer)	each item in data[]
GET /receipts/:id	Bearer JWT (customer)	top-level object
GET /dashboard	Bearer JWT (customer)	each item in recentReceipts[]
GET /shop/receipts	Bearer JWT (shop)	each item in data[]
GET /shop/receipts/:id	Bearer JWT (shop)	top-level object
GET /shop/dashboard	Bearer JWT (shop)	each item in recentReceipts[]

2. Behavior change: GET /dashboard — smartOffers

Auth Bearer JWT (customer)

Request no body/query params

Shape is unchanged - still an array of the same object. What changed is where the data comes from:

	Before	Now
Contents	2 hardcoded mock entries, always present	0 or 1 real entries
Source	static array in code	a coupon matched to the customer's top all-time spending category

Action needed: confirm the offers section on-screen handles an **empty array** gracefully (e.g. hides itself) - it can no longer assume at least one offer is always present.

```
"smartOffers": [  
  {  
    "title": "5% Cashback on Electronics",  
    "description": "Get cashback on your next electronics purchase.",  
    "imageUrl": null  
  }  
]  
  
// or, for a customer with no purchase history yet:  
"smartOffers": []
```

3. New endpoints (backend-only for now, no UI required yet)

3.1 GET /insights/analysis

Auth Bearer JWT (customer)

Request no body/query params

Response 200 OK

```
{  
  "advice": "Your biggest spending category this month is Electronics at $180.00. Keeping an  
eye on this category could help you save more.",  
  "paymentPattern": "You paid with VISA in 75% of your purchases this month."  
}  
  
// with no purchases recorded this month:  
{  
  "advice": "You haven't recorded any spending yet this month.",  
  "paymentPattern": "No payment method data recorded yet this month."  
}
```

3.2 GET /shop/analysis

Auth Bearer JWT (shop account, must have a linked store)

Request no body/query params

Response 200 OK

```
{  
  "advice": "Revenue is up 12% compared to last month.",  
  "pattern": "Customers who buy Basmati Rice 5kg often also buy Cotton T-Shirt - they've  
appeared together in 4 receipts."  
}  
  
// with insufficient data:  
{  
  "advice": "You've made $0.00 in revenue this month so far.",  
  "pattern": "Not enough data yet to detect buying patterns."  
}
```