



---

## BE PAYMENT READY

Moneris Gateway API - Integration Guide -Java – Java

Version: 1.6.3

Copyright © Moneris Solutions, 2022

All rights reserved. No part of this publication may be reproduced, stored in retrieval systems, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of Moneris Solutions Corporation.

## Security and Compliance

Your solution may be required to demonstrate compliance with the card associations' PCI/CISP/PABP requirements. For more information on how to make your application PCI-DSS compliant, contact the Moneris Sales Center and visit <https://developer.moneris.com> to download the PCI\_DSS Implementation Guide.

All Merchants and Service Providers that store, process, or transmit cardholder data must comply with PCI DSS and the Card Association Compliance Programs. However, certification requirements vary by business and are contingent upon your "Merchant Level" or "Service Provider Level".

The card association has some data security standards that define specific requirements for all organizations that store, process, or transmit cardholder data. As a Moneris client or partner using this method of integration, your solution must demonstrate compliance to the Payment Card Industry Data Security Standard (PCI DSS) and/or the Payment Application Data Security Standard (PA DSS). These standards are designed to help the cardholders and merchants in such ways as they ensure credit card numbers are encrypted when transmitted/stored in a database and that merchants have strong access control measures.

Non-compliant solutions may prevent merchant boarding with Moneris. A non-compliant merchant can also be subject to fines, fees, assessments or termination of processing services.

For further information on PCI DSS & PA DSS requirements, visit <http://www.pcisecuritystandards.org>.

## Confidentiality

You have a responsibility to protect cardholder and merchant related confidential account information. Under no circumstances should ANY confidential information be sent via email while attempting to diagnose integration or production issues. When sending sample files or code for analysis by Moneris staff, all references to valid card numbers, merchant accounts and transaction tokens should be removed and or obscured. Under no circumstances should live cardholder accounts be used in the test environment.

## Changes in v1.6.3

- Added Merchant Advice Code in Purchase, Pre-Authorization, CAVV Purchase; CAVV Pre-Authorization responses samples
- Updated DS trans ID Type and Limits, and Description in B.1 Definition of Response Fields – 3-D Secure
- Removed the RequestType field from MPI 3DS Authentication Request - 3RI with recurring
- Updated the note for the fields RecurringFrequency and RecurringExpiry
- Added Set Methods in MPI 3DS Authentication Request
- Removed status check in MPI 3DS Authentication Request
- Removed ThreeDSCompletionInd in MPI 3DS Authentication Request - 3RI with recurring/no recurring
- Moved PriorAuthenticationInfo field to optional section for MPI 3DS Prior Authentication Info for MPI 3DS Authentication Request - 3RI with recurring
- Updated the note related to the Field Email
- Added Merchant Advice Code field in the Appendix B - Definitions of Response Fields

### Changes in v1.6.2

- Updated the 3-D version to 2.2
- Added the 3RI flow chart Transaction Flow for 3-D Secure - 3RI channel
- Updated the field Email moving from optional to required
- Added a note to the field Email
- Added the status “D” in the TransStatus Code
- Updated transaction status reason Decline Codes

- Removed the Visa Checkout section. Visa Checkout has been decommissioned in June 1st 2023
- Updated the note related to the Field DSTransID
- Updated the note related to the Field ThreedsServerTransId
- Updated the note related to the Field ThreedsServerTransId
- Added a comment to Visa Secure
- Updated the note related to the Field RlIndicator
- Added note to ds\_trans\_id on only submitting it in financial transactions if using a 3rd party 3DS Secure service
- Added new 3DS fields to 3DS Authentication to support 3RI such as MessageCategory, DeviceChannel, RlIndicator
- Added new 3DS fields to 3DS Authentication to support 3RI Decoupled Authentication such as DecoupledRequestIndicator, DecoupledRequestMaxTime, DecoupledRequestAsyncUrl
- Added new 3DS object prior\_request\_auth\_data to 3DS Authentication to support 3RI, including its fieldsPriorAuthenticationInfo , prior\_request\_auth\_method, prior\_request\_auth\_ref, prior\_request\_auth\_timestamp
- Added additional fields to 3DS responses ThreeDSVersion and AuthenticationType
- Added additional topics on 3DS Authentication for the 3RI scenarios with and without recurring features
- Retitled the existing 3DS Authentication scenario to specify it is intended for the browser channel only
- Added topic on 3RI channel authentication flow and retitled previous 3DS flow to specify it is intended for browser channel only
- Added topic on Handling 3RI Decoupled Authentication flow to explain the asynchronous response handling
- Added topic on Server To Server endpoints to cover the separate URL for 3DS Authentication

Changes in v1.6.1

- Added note to ds\_trans\_id on only submitting it in financial transactions if using a 3rd party 3DS Secure service

#### Changes in v1.6.0

- Added new foreign\_indicator field to Basic Transaction set: purchase and preauth
- Added new foreign\_indicator field to 3-D Secure Transaction set: cavvPurchase and cavvPreauth
- Added new foreign\_indicator values in Appendix A.2 Definition of Request Fields - Core Fields
- Updated sample code with new foreign\_indicator field
- Updated AVS Response Codes table

#### Changes in v1.5.0

- Added new definition for MPI 3DS Authentication Request transaction type
- Added new value V for request field **payment indicator** to reflect support for merchants who bill in recurring variable payments
- Amended allowable values for **e-commerce indicator** to reflect new **payment indicator** value and amended corresponding topic in Credential on File section
- Added note to the limit for request field **cardholder name** to indicate that accented characters are not allowable
- Added new section and topics about Installments by Visa
- Added topic about Vault and Installments in the Vault section

#### Changes in v1.4.4

- Added new topic to Vault section listing Vault transactions that support temporary tokens
- Convenience Fee response field **convenience fee status** limit has been corrected to 3-character alphanumeric
- Information added to About Convenience Fee and response field definitions to indicate convenience fee transactions do not support MCP or digital wallets

- Transaction type descriptions have been added or amended in Vault Add Token, Vault Delete, Vault Is Corporate Card, Vault Add Credit Card,

#### Changes in v1.4.3

- Added new MCP transaction topics MCP Purchase with 3-D Secure, MCP Purchase with 3-D Secure and Vault, MCP Pre-Authorization with 3-D Secure, and MCP Pre-Authorization with 3-D Secure
- Added transaction type topics for Purchase with 3-D Secure and Vault, Pre-Authorization with 3-D Secure and Vault, and Purchase with 3-D Secure and Recurring Billing in 3-D Secure 2.0 section
- Added new request field **DS transaction ID**
- Made billing-related request fields mandatory for 3DS Authentication Request transaction

#### Changes in v1.4.2

- Corrected the limits for the request field **start date**
- Corrected presentation of set methods for the request fields **browser language, browser java enabled, browser screen height, browser screen width**,

#### Changes in v1.4.1

- Added information about the request fields 3DS version and 3DS server indicator in the transaction topics for Purchase with 3-D Secure and Pre-Authorization with 3-D Secure
- corrected the variable name for the request field 3DS server indicator

#### Changes in v1.4.0

- 3-D Secure 2.0 section has replaced MPI section (which related to 3-D Secure 1.0)
- Added new fields for 3-D Secure 2.0 to the Purchase with 3-D Secure and Pre-Authorization with 3-D Secure transactions

- References related to 3-D Secure2.0 have been added, including CAVV Result Codes for Visa, Mastercard and American Express card brands, and 3-D Secure 2.0 TransStatus Codes
- Added Definition of Response Fields for 3-D Secure
- Added Definition of Request Fields – 3-D Secure 2.0 and removed the previous Definition of Request Fields – MPI

#### Changes in v1.3.1

- Amended response code 959 under "Other Response Codes" to 599

#### Changes in v1.3.0

- Removed wording about testing only with Visa cards in About Credential on File topic
- Removed differentiation between supported card brands in regards to AVS and CVD in Card Verification
- Added information about American Express support in Card Verification with AVS and CVD and Card Verification with Vault
- Removed the Re-Authorization transaction type and information related to it
- Removed the Mag Swipe transaction set section
- Added Response Codes reference
- Added new supported currencies to MCP Currency Codes
- Added transaction type definitions to Visa Checkout topics
- Added information about dynamic descriptor behaviour in Pre-Authorization transactions to all Pre-Authorization and Pre-Authorization Completion topics
- Added missing dynamic descriptor field information to Purchase with 3-D Secure transaction topic
- Added information about payment indicator and e-commerce indicator field values, including new topic Payment Indicator and E-Commerce Indicator Values
- Reorganized information for Convenience Fee, including new topics Supported Transactions for Convenience Fee and Convenience Fee Info Object

- Renamed Convenience Fee transaction type topics to emphasize that Purchase is the base transactions and Convenience Fee is an additional feature
- Reorganized Definition of Request Fields by feature sets; Mag Swipe request fields removed
- New request field definition topics for connection fields, core fields, Vault, MPI, and Convenience Fee

## **Previous version changes**

### Changes in v1.2.12

- Added warnings about 3-D Secure implementations using frames to MPI section and 3-D Secure related transaction type topics

### Changes in v1.2.11

- Added information about Google Pay™ and removed references to Android Pay
- Separated out transaction process flows into two separate topics for Apple Pay and Google Pay™, Apple Pay Transaction Process Overview and Google Pay™ Transaction Process Overview

### Changes in v1.2.10

- Added missing request fields in MCP Purchase with Vault

### Changes in v1.2.9

- Corrected sample code for some financial transactions (to remove old method of MCP processing)

### Changes in v1.2.8

- Added section about Multi-Currency Pricing (MCP) transactions
- Added new conceptual topics in Credential on File:
  - Merchant- vs. Cardholder-Initiated COF Transactions
  - COF With Previously Stored Credentials
- Discover test card number has been changed to 6011000992927602
- Amended electronic commerce indicator description in Definition of Response Fields to remove deprecated allowable values (8 and 9)

#### Changes in v1.2.7

Missing limits for request variables amount, completion amount and transaction amount were replaced

#### Changes in v1.2.6

Electronic commerce Indicator (crypt) request variable's value of '7' amended to reflect that it also represents an American ExpressSafeKey non-authenticated transaction

#### Changes in v1.2.5

Purchase transaction amended to include Customer ID variable

#### Changes in v1.2.4

Changes limits in Amount, Transaction Amount, Completion Amount request variables to reflect 10 decimals.

#### Changes in v1.2.3

This version adds information about passing Offlinx™ data for the Card Match pixel tag via Unified API transactions.

# Table of Contents

---

<b>Security and Compliance</b>	2
Confidentiality	2
<b>Changes in v1.6.3</b>	3
<b>Getting Help</b>	16
<b>1 About This Documentation</b>	17
1.1 Purpose	17
1.2 Who Is This Guide For?	17
<b>2 Basic Transaction Set</b>	18
2.1 Purchase	19
2.2 Pre-Authorization	24
2.3 Pre-Authorization Completion	30
2.4 Force Post	34
2.5 Purchase Correction	38
2.6 Refund	40
2.7 Independent Refund	43
2.8 Card Verification with AVS and CVD	46
2.9 Batch Close	50
2.10 Open Totals	52
<b>3 Credential on File</b>	55
3.1 About Credential on File	55
3.2 Credential on File Info Object and Variables	55
3.3 Credential on File Transaction Types	56
3.4 Merchant- vs. Cardholder-Initiated COF Transactions	57
3.5 Initial Transactions in Credential on File	57
3.6 COF With Previously Stored Credentials	58
3.7 Payment Indicator and E-Commerce Indicator Values	58
3.8 Vault Tokenize Credit Card and Credential on File	59
3.9 Credential on File and Converting Temporary Tokens	59
3.10 Card Verification and Credential on File Transactions	59
3.10.1 When to Use Card Verification With COF	60
3.10.2 Credential on File and Vault Add Token	60
3.10.3 Credential on File and Vault Update Credit Card	60
3.10.4 Credential on File and Vault Add Credit Card	61
3.10.5 Credential on File and Recurring Billing	61
<b>4 Vault</b>	63
4.1 About the Vault Transaction Set	63
4.2 Vault Transaction Types	63
4.2.1 Administrative Vault Transaction types	63
4.2.2 Financial Vault Transaction types	65
4.3 Vault Transactions That Support Temporary Tokens	65
4.4 Vault and Installments	66
4.5 Vault Administrative Transactions	66
4.5.1 Vault Add Credit Card – ResAddCC	66
4.5.1.1 Vault Data Key	70
4.5.1.2 Vault Encrypted Add Credit Card – EncResAddCC	70
4.5.2 Vault Temporary Token Add – ResTempAdd	73
4.5.3 Vault Update Credit Card – ResUpdateCC	75
4.5.3.1 Vault Encrypted Update CC – EncResUpdateCC	79
4.5.4 Vault Delete – ResDelete	82
4.5.5 Vault Lookup Full – ResLookupFull	84
4.5.6 Vault Lookup Masked – ResLookupMasked	86

---

4.5.7 Vault Get Expiring – ResGetExpiring .....	87
4.5.8 Vault Is Corporate Card - ResIsCorporateCard .....	90
4.5.9 Vault Add Token – ResAddToken .....	91
4.5.10 Vault Tokenize Credit Card – ResTokenizeCC .....	95
4.6 Vault Financial Transactions .....	99
4.6.1 Customer ID Changes .....	99
4.6.2 Purchase with Vault – ResPurchaseCC .....	100
4.6.3 Pre-Authorization with Vault – ResPreauthCC .....	105
4.6.4 Vault Independent Refund – ResIndRefundCC .....	111
4.6.5 Force Post with Vault – ResForcePostCC .....	115
4.6.6 Card Verification with Vault – ResCardVerificationCC .....	118
4.7 Hosted Tokenization .....	122
<b>5 INTERAC® Online Payment .....</b>	<b>124</b>
5.1 About INTERAC® Online Payment Transactions .....	124
5.2 Other Documents and References .....	124
5.3 Website and Certification Requirements .....	125
5.3.1 Things to provide to Moneris .....	125
5.3.2 Certification process .....	126
5.3.3 Client Requirements .....	126
5.3.4 Delays .....	127
5.4 Transaction Flow for INTERAC® Online Payment .....	127
5.5 Sending an INTERAC® Online Payment Purchase Transaction .....	129
5.5.1 Fund-Guarantee Request .....	129
5.5.2 Online Banking Response and Fund-Confirmation Request .....	129
5.6 INTERAC® Online Payment Purchase .....	130
5.7 INTERAC® Online Payment Refund .....	132
5.8 INTERAC® Online Payment Field Definitions .....	135
<b>6 Level 2/3 Transactions .....</b>	<b>138</b>
6.1 About Level 2/3 Transactions .....	138
6.2 Level 2/3 Visa Transactions .....	138
6.2.1 Level 2/3 Transaction Types for Visa .....	138
6.2.2 Level 2/3 Transaction Flow for Visa .....	141
6.2.3 VS Completion .....	143
6.2.4 VS Purchase Correction .....	148
6.2.5 VS Force Post .....	149
6.2.6 VS Refund .....	155
6.2.7 VS Independent Refund .....	160
6.2.8 VS Corpais .....	166
6.2.8.1 VS Purcha – Corporate Card Common Data .....	167
6.2.8.2 VS Purchl – Line Item Details .....	170
6.2.8.3 Sample Code for VS Corpais .....	173
6.3 Level 2/3 Mastercard Transactions .....	175
6.3.1 Level 2/3 Transaction Types for Mastercard .....	175
6.3.2 Level 2/3 Transaction Flow for Mastercard .....	178
6.3.3 MC Completion .....	180
6.3.4 MC Force Post .....	182
6.3.5 MC Purchase Correction .....	184
6.3.6 MC Refund .....	186
6.3.7 MC Independent Refund .....	188
6.3.8 MC Corpais - Corporate Card Common Data with Line Item Details .....	191
6.3.8.1 MC Corpac - Corporate Card Common Data .....	192
6.3.8.2 MC Corpals - Line Item Details .....	200
6.3.8.3 Tax Array Object - MC Corpais .....	204
6.3.8.4 Sample Code for MC Corpais .....	206
6.4 Level 2/3 American Express Transactions .....	208
6.4.1 Level 2/3 Transaction Types for Amex .....	208
6.4.2 Level 2/3 Transaction Flow for Amex .....	211

---

6.4.3 Level 2/3 Data Objects in Amex .....	212
6.4.3.1 About the Level 2/3 Data Objects for Amex .....	212
6.4.3.2 Definition of the AxLevel23 Object .....	212
Table 1 Object .....	213
Table 1 - Setting the N1Loop Object .....	214
Table 1 - Setting the AxRef Object .....	216
Table 2 Object .....	217
Table 2 - Setting the AxIt1Loop Object .....	218
Table 2 - Setting the AxIt106s Object .....	221
Table 2 - Setting the AxTxi Object .....	222
Table 3 Object .....	226
Table 3 - Setting the AxTxi Object .....	227
6.4.4 AX Completion .....	230
6.4.5 AX Force Post .....	234
6.4.6 AX Purchase Correction .....	238
6.4.7 AX Refund .....	240
6.4.8 AX Independent Refund .....	244
<b>7 3-D Secure 2.2 .....</b>	<b>250</b>
7.1 About 3-D Secure 2.2 .....	250
7.1.1 3-D Secure Implementations .....	251
7.1.2 Out of Scope/Not Supported Check .....	252
7.1.3 Version Compatibility .....	252
7.1.4 Upgrading from 3-D Secure 2.0 to 3-D Secure 2.2 Check .....	252
7.2 Building Your 3-D Secure 2.2 Integration .....	253
7.2.1 Activating 3-D Secure Functionality .....	253
7.2.2 Transaction Flow for 3-D Secure - Browser channel .....	253
7.2.3 Transaction Flow for 3-D Secure - 3RI channel .....	255
7.2.3.1 Decoupled Authentication .....	256
7.3 Implementing Card Lookup Request .....	256
7.3.1 Card Lookup Request – mpiCardLookup .....	256
7.4 Implementing MPI 3DS Authentication Request .....	258
7.4.1 MPI 3DS Authentication Request - Browser Channel .....	259
7.4.2 MPI 3DS Authentication Request - 3RI with recurring .....	268
7.4.3 MPI 3DS Authentication Request - 3RI, non-recurring .....	277
7.5 Handling the Challenge Flow .....	286
7.5.1 CAVV Lookup Request – mpiCavvLookup .....	286
7.6 Handling the Decoupled Authentication Flow .....	288
7.7 Performing the Authorization .....	292
7.7.1 Purchase with 3-D Secure – cavvPurchase .....	292
7.7.2 Pre-Authorization with 3-D Secure – cavvPreauth .....	301
7.7.3 Purchase with Vault and 3-D Secure .....	309
7.7.4 Pre-Authorization with Vault & 3-D Secure .....	313
7.7.5 Purchase with 3-D Secure and Recurring Billing .....	318
7.8 Testing Your 3-D Secure 2.2 Integration .....	319
7.9 Moving to Production With 3-D Secure 2.2 .....	320
7.10 3-D Secure 2.2 TransStatus Codes .....	320
7.11 3-D Secure 2.2 Commons TransStatusReason Decline Codes .....	321
7.12 CAVV Result Codes .....	322
7.12.1 Visa CAVV Result Codes .....	323
7.12.2 Mastercard CAVV Result Codes .....	324
7.12.3 American Express CAVV Result Codes .....	324
<b>8 Multi-Currency Pricing (MCP) .....</b>	<b>326</b>

---

8.1 About Multi-Currency Pricing (MCP) .....	326
8.2 Methods of Processing MCP Transactions .....	327
8.3 MCP Get Rate .....	327
8.4 MCP Purchase .....	329
8.5 MCP Purchase with 3-D Secure .....	334
8.6 MCP Purchase with 3-D Secure and Vault .....	339
8.7 MCP Pre-Authorization .....	344
8.8 MCP Pre-Authorization with 3-D Secure .....	349
8.9 MCP Pre-Authorization with 3-D Secure and Vault .....	354
8.10 MCP Pre-Authorization Completion .....	359
8.11 MCP Purchase Correction .....	363
8.12 MCP Refund .....	365
8.13 MCP Independent Refund .....	369
8.14 MCP Purchase with Vault .....	373
8.15 MCP Pre-Authorization with Vault .....	377
8.16 MCP Independent Refund with Vault .....	381
8.17 MCP Currency Codes .....	385
8.18 MCP Error Codes .....	391
<b>9 Installments by Visa .....</b>	<b>392</b>
9.1 About Installments by Visa .....	392
9.2 Installments by Visa Transaction Types .....	392
9.3 Sending Transactions with Installments by Visa .....	393
9.4 Installment Plan Lookup .....	393
9.5 Vault Installment Plan Lookup .....	396
9.6 Installment Info Object .....	399
<b>10 e-Fraud Tools .....</b>	<b>401</b>
10.1 Address Verification Service .....	403
10.1.1 About Address Verification Service (AVS) .....	403
10.1.2 AVS Info Object .....	404
10.1.3 AVS Response Codes .....	405
10.1.4 AVS Sample Code .....	406
10.2 Card Validation Digits (CVD) .....	408
10.2.1 About Card Validation Digits (CVD) .....	408
10.2.2 Transactions Where CVD Is Required .....	408
10.2.3 CVD Information Object .....	409
10.2.4 CVD Result Codes .....	410
10.2.5 Sample Purchase with CVD Info Object .....	411
10.3 Transaction Risk Management Tool .....	412
10.3.1 About the Transaction Risk Management Tool .....	412
10.3.2 Introduction to Queries .....	412
10.3.3 Session Query .....	413
10.3.3.1 Session Query Transaction Flow .....	420
10.3.3.4 Attribute Query .....	420
10.3.4.1 Attribute Query Transaction Flow .....	424
10.3.5 Handling Response Information .....	424
10.3.5.1 TRMT Response Fields .....	425
10.3.5.2 Understanding the Risk Score .....	428
10.3.5.3 Understanding the Rule Codes, Rule Names and Rule Messages .....	429
10.3.5.4 Examples of Risk Response .....	437
Session Query .....	437
Attribute Query .....	437
10.3.6 Inserting the Profiling Tags Into Your Website .....	438
10.4 Incorporating All Available Fraud Tools .....	440
10.4.1 Implementation Options for TRMT .....	440
10.4.2 Implementation Checklist .....	441
10.4.3 Making a Decision .....	442
<b>11 Apple Pay and Google Pay™ Integrations .....</b>	<b>443</b>

---

11.1 About Apple Pay and Google Pay™ Integration .....	443
11.2 Apple Pay Transaction Process Overview .....	443
11.3 Google Pay™ Transaction Process Overview .....	445
11.4 About API Integration of Apple Pay and Google Pay™ .....	446
11.4.1 Transaction Types Used for Apple Pay and Google Pay™ .....	446
11.5 Cavv Purchase – Apple Pay and Google Pay™ .....	447
11.6 Cavv Pre-Authorization – Apple Pay & Google Pay™ .....	451
<b>12 Offlinx™ .....</b>	<b>457</b>
12.1 What Is a Pixel Tag? .....	457
12.2 Offlinx™ and API Transactions .....	457
<b>13 Convenience Fee .....</b>	<b>459</b>
13.1 About Convenience Fee .....	459
13.2 Convenience Fee Information Object .....	459
13.3 Purchase with Convenience Fee .....	460
13.4 Purchase with Customer Info and Convenience Fee .....	463
13.5 Purchase with 3-D Secure and Convenience Fee .....	468
<b>14 Recurring Billing .....</b>	<b>473</b>
14.1 About Recurring Billing .....	473
14.2 Purchase with Recurring Billing .....	473
14.3 Recurring Billing Update .....	476
14.4 Recurring Billing Response Fields and Codes .....	480
14.5 Credential on File and Recurring Billing .....	481
<b>15 Customer Information .....</b>	<b>483</b>
15.1 Using the Customer Information Object .....	483
15.1.1 Customer Info Object – Miscellaneous Properties .....	484
15.1.2 Customer Info Object – Billing/Shipping Information .....	484
15.1.2.1 Set Methods for Billing and Shipping Info .....	485
15.1.2.2 Using Hash Tables for Billing and Shipping Info .....	486
15.1.3 Customer Info Object – Item Information .....	486
15.1.3.1 Set Methods for Item Information .....	487
15.1.3.2 Using Hash Tables for Item Information .....	487
15.2 Customer Information Sample Code .....	487
<b>16 Status Check .....</b>	<b>491</b>
16.1 About Status Check .....	491
16.2 Using Status Check Response Fields .....	491
16.3 Sample Purchase with Status Check .....	493
<b>17 Testing a Solution .....</b>	<b>495</b>
17.1 About the Merchant Resource Center .....	495
17.2 Logging In to the QA Merchant Resource Center .....	495
17.3 Test Credentials for Merchant Resource Center .....	496
17.4 Getting a Unique Test Store ID and API Token .....	497
17.5 Processing a Transaction .....	499
17.5.1 Overview .....	499
17.5.2 HttpsPostRequest Object .....	500
17.5.3 Receipt Object .....	502
17.6 Testing INTERAC® Online Payment Solutions .....	502
17.7 Testing MPI Solutions .....	503
17.8 Test Card Numbers .....	505
17.8.1 Test Card Numbers for Level 2/3 .....	505
17.8.2 Test Cards for Visa Checkout .....	506
17.9 Simulator Host .....	506
<b>18 Moving to Production .....</b>	<b>507</b>
18.1 Activating a Production Store Account .....	507
18.2 Configuring a Store for Production .....	507
18.2.1 Configuring an INTERAC® Online Payment Store for Production .....	508

---

18.2.1.1 Completing the Certification Registration - Merchants .....	509
18.2.1.2 Third-Party Service/Shopping Cart Provider .....	509
18.3 Receipt Requirements .....	510
18.3.1 Certification Requirements .....	511
<b>Appendix A Definition of Request Fields .....</b>	<b>512</b>
A.1 Definition of Request Fields – Connection Fields .....	512
A.2 Definition of Request Fields – Core Fields .....	513
A.3 Definition of Request Fields – Credential on File .....	517
A.4 Definition of Request Fields – Vault .....	519
A.5 Definition of Request Fields for Level 2/3 - Visa .....	520
A.6 Definition of Request Fields for Level 2/3 - Mastercard .....	530
A.7 Definition of Request Fields for Level 2/3 - Amex .....	541
A.8 Definition of Request Fields – 3-D Secure 2.2 .....	551
A.9 Definition of Request Fields – PBB Info Object .....	556
A.10 Definition of Request Fields – Pay By Bank .....	557
A.11 Definition of Request Fields – MCP .....	558
A.12 Definition of Request Fields – Offlinx™ .....	559
A.13 Definition of Request Fields – Convenience Fee .....	560
A.14 Definition of Request Fields – Recurring .....	560
A.15 Definition of Request Fields – Installments by Visa .....	561
<b>Appendix B Definitions of Response Fields .....</b>	<b>563</b>
B.1 Definition of Response Fields – 3-D Secure .....	578
B.2 Definition of Response Fields – MCP .....	582
B.3 Definition of Response Fields –Installments by Visa .....	584
<b>Appendix C Response Codes .....</b>	<b>590</b>
<b>Appendix D Error Messages .....</b>	<b>603</b>
<b>Appendix E Merchant Checklists for INTERAC® Online Payment Certification Testing .....</b>	<b>605</b>
<b>Appendix F Third-Party Service Provider Checklists for INTERAC® Online Payment Certification Testing .....</b>	<b>609</b>
<b>Appendix G Merchant Checklists for INTERAC® Online Payment Certification .....</b>	<b>614</b>
<b>Appendix H INTERAC® Online Payment Certification Test Case Detail .....</b>	<b>617</b>
H.1 Common Validations .....	617
H.2 Test Cases .....	617
H.3 Merchant front-end test case values .....	622
<b>Copyright Notice .....</b>	<b>627</b>
<b>Trademarks .....</b>	<b>627</b>

# Getting Help

Moneris has help for you at every stage of the integration process.

Getting Started	During Development	Production
Contact our Client Integration Specialists:  clientintegrations@moneris.com	If you are already working with an integration specialist and need technical development assistance, contact our eProducts Technical Consultants:  1-866-319-7450  eproducts@moneris.com	If your application is already live and you need production support, contact Moneris Customer Service:  onlinepayments@moneris.com  1-866-319-7450  Available 24/7

For additional support resources, you can also make use of our community forums at

<http://community.monteris.com/product-forums/>

# 1 About This Documentation

## 1.1 Purpose

This document describes the transaction information for using the Moneris Java API for sending credit card transactions. In particular, it describes the format for sending transactions and the corresponding responses you will receive.

## 1.2 Who Is This Guide For?

The Moneris Gateway API - Integration Guide -Java is intended for developers integrating with the Moneris Gateway.

This guide assumes that the system you are trying to integrate meets the requirements outlined below and that you have some familiarity with the Java programming language.

### System Requirements

- Java
- Port 443 open for bi-directional communication
- Web server with a SSL certificate

## 2 Basic Transaction Set

- 2.1 Purchase
- 2.2 Pre-Authorization
- 2.3 Pre-Authorization Completion
- 2.4 Force Post
- 2.5 Purchase Correction
- 2.6 Refund
- 2.7 Independent Refund
- 2.8 Card Verification with AVS and CVD
- 2.9 Batch Close
- 2.10 Open Totals

## 2.1 Purchase

Verifies funds on the customer's card, removes the funds and prepares them for deposit into the merchant's account.

```
Purchase purchase = new Purchase();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(purchase);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Purchase transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric	purchase.setOrderId(order_id);
amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	purchase.setAmount(amount);
<b>EXAMPLE:</b> 1234567.89		
credit card number	<i>String</i> 20-character alphanumeric	purchase.setPan(pan);
expiry date	<i>String</i>	purchase.setExpDate(expiry_date);

Variable Name	Type and Limits	
	4-character alphanumeric (YYMM format)	
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>purchase.setCryptType(crypt);</code>

### Purchase transaction request fields – Optional

Variable Name	Type and Limits	
customer ID	<i>String</i> 50-character alphanumeric	<code>purchase.setCustId(cust_id);</code>
card match ID	<i>String</i> 50-character alphanumeric	<code>purchase.setCmId(transaction_id);</code>
	<b>NOTE:</b> Applies to Offlinx™ only; must be unique value for each transaction	
Customer Information	<i>Object</i> N/A	<code>purchase.setCustInfo(customer);</code>
AVS Information	<i>Object</i> N/A	<code>purchase.setAvsInfo(avcCheck);</code>
CVD Information	<i>Object</i> N/A	<code>purchase.setCvdInfo(cvdCheck);</code>
	<b>NOTE:</b> When storing credentials on the initial transaction, the CVD object must be sent; for subsequent transactions using stored credentials, CVD can be sent with cardholder-initiated transactions only— <b>merchants must not store CVD information.</b>	
Convenience Fee Information	<i>Object</i> N/A	<code>purchase.setConvenienceFee(convFeeInfo);</code>

Variable Name	Type and Limits	
<b>NOTE:</b> This variable does not apply to Credential on File transactions.		
Recurring Billing	<i>Object</i> N/A	<code>purchase.setRecurInfo(recurInfo);</code>
dynamic descriptor	<i>String</i> 20-character alphanumeric	<code>purchase.setDynamicDescriptor(dynamic_descriptor);</code>
foreign indicator	<i>Boolean</i> true or false	<code>purchase.setForeignIndicator(foreign_indicator);</code>
wallet indicator	<i>String</i> 3-character alphanumeric	<code>purchase.setWalletIndicator(wallet_indicator);</code>
Credential on File Info  cof	<i>Object</i> N/A	<code>purchase.setCofInfo(cof);</code>
<b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.		
Installment Info  For fields in this object, see 9.6 Installment Info Object	<i>Object</i> N/A	<code>purchase.setInstallmentInfo(installmentInfo);</code>
<b>NOTE:</b> Do not send the Installment Info object on any transaction that is not intended to offer Installments by Visa functionality; doing so may		

Variable Name	Type and Limits
cause the transaction to fail.	

### Credential on File Info object request fields

Variable Name	Type and Limits	
issuer ID	<p><i>String</i></p> <p>15-character alphanumeric variable length</p> <p><b>NOTE:</b> This variable is required for all merchant-initiated transactions following the first one; upon sending the first transaction, the issuer ID value is received in the transaction response and then used in subsequent transaction requests.</p>	<pre>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
payment indicator	<p><i>String</i></p> <p>1-character alphabetic</p> <p><b>NOTE:</b> In Credential on File transactions where the request field e-commerce indicator is also being sent, the acceptable values for e-commerce indicator are dependent on the value sent for payment indicator; see request field definitions for more information.</p>	<pre>cof.setPaymentIndicator("PAYMENT_INDICATOR_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
payment information	<p><i>String</i></p> <p>1-character numeric</p>	<pre>cof.setPaymentInformation("PAYMENT_INFO_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>

### Sample Purchase

```
public class TestCanadaPurchase
{
    public static void main(String[] args)
    {
```

```

java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String store_id = "monca03650";
String api_token = "7Yw0MPTlhjBRcZiE6837";
String amount = "6000.0";
String pan = "4622943127023886";
String expdate = "2212"; //YYMM
String crypt = "7";
String processing_country_code = "CA";
boolean foreign_indicator= true; //New Foreign Indicator field
boolean status_check = false;

Purchase purchase = new Purchase();
purchase.setOrderId(order_id);
purchase.setAmount(amount);
purchase.setPan(pan);
purchase.setExpdate(expdate);
purchase.setCryptType(crypt);
purchase.setForeignIndicator(foreign_indicator);
//purchase.setDynamicDescriptor("123456");
//purchase.setWalletIndicator(""); //Refer documentation for possible values
//purchase.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique max 50
alphanumeric characters transaction id generated by merchant

// TrId and TokenCryptogram are optional, refer documentation for more details.
//purchase.setTrId("50189815682");
//purchase.setTokenCryptogram("APmbM/41le0uAAH+s6xMAAADFA==");

//optional - Installment Info
InstallmentInfo installmentInfo = new InstallmentInfo();
installmentInfo.setPlanId("ae859ef1-eb91-b708-8b80-1dd481746401");
installmentInfo.setPlanIdRef("0000000065");
installmentInfo.setTacVersion("2");
purchase.setInstallmentInfo(installmentInfo);

//optional - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("168451306048014");
purchase.setCofInfo(cof);

//Optional - Pay By bank details
PbbInfo pbbInfo = new PbbInfo();
pbbInfo.setConsentId("c3fef81c-0e12-4311-be7e-c1d102c2a7c9");
pbbInfo.setPaymentMethod("VISA_CREDIT");
purchase.setPbbInfo(pbbInfo);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(purchase);
mpgReq.setStatusCheck(status_check);

//Optional - Proxy
mpgReq.setProxy(false); //true to use proxy
mpgReq.setProxyHost("proxyURL");
mpgReq.setProxyPort("proxyPort");
mpgReq.setProxyUser("proxyUser"); //optional - domainName\user
mpgReq.setProxyPassword("proxyPassword"); //optional
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
}

```

```

System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("HostId = " + receipt.getHostId());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());
System.out.println("Advice Code= "+ receipt.getAdviceCode());

// InstallmentResults installmentResults = receipt.getInstallmentResults();
// System.out.println("\nPlanId = " + installmentResults.getPlanId() +"\n");
// System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
// System.out.println("TacVersion = " + installmentResults.getTacVersion());
// System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
// System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
// System.out.println("PlanResponse = " + installmentResults.getPlanResponse());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 2.2 Pre-Authorization

Verifies and locks funds on the customer's credit card. The funds are locked for a specified amount of time based on the card issuer.

To retrieve the funds that have been locked by a Pre-Authorization transaction so that they may be settled in the merchant's account, a Pre-Authorization Completion transaction must be performed. A Pre-Authorization transaction may only be "completed" once.

### Things to Consider:

- If a Pre-Authorization transaction is not followed by a Pre-Authorization Completion transaction, it must be reversed via a Pre-Authorization Completion transaction for 0.00. See 2.3 Pre-Authorization Completion
- A Pre-Authorization transaction may only be "completed" once

```
PreAuth preauth = new PreAuth();
```

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(preauth);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

**NOTE:**

### Pre-Authorization transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	preauth.setOrderId(order_id);
amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	preauth.setAmount(amount);
<b>EXAMPLE: 1234567.89</b>		
credit card number	<i>String</i> max 20-character alpha- numeric	preauth.setPan(pan);
expiry date	<i>String</i>	preauth.setExpDate(expiry_date);

Variable Name	Type and Limits	
	4-character alphanumeric YYMM	
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>preauth.setCryptType(crypt);</code>

### Pre-Authorization transaction request fields – Optional

Variable Name	Type and Limits	
dynamic descriptor	<i>String</i> 20-character alphanumeric total of 22 characters including your merchant name and separator  <b>NOTE:</b> Some special characters are not allowed: <> \$ % = ? ^ { } [ ] \	<code>preauth.setDynamicDescriptor(dynamic_descriptor);</code>
foreign indicator	<i>Boolean</i> true or false	<code>preauth.setForeignIndicator(foreign_indicator);</code>
card match ID	<i>String</i> 50-character alphanumeric  <b>NOTE:</b> Applies to Offlinx™ only; must be unique value for each transaction	<code>preauth.setCmId(transaction_id);</code>
Customer Information	<i>Object</i> N/A	<code>preauth.setCustInfo(customer);</code>
AVS Information	<i>Object</i> N/A	<code>preauth.setAvsInfo(avscCheck);</code>
CVD Information	<i>Object</i>	<code>preauth.setCvdInfo(cvdCheck);</code>

Variable Name	Type and Limits	
<p><b>NOTE:</b> When storing credentials on the initial transaction, the CVD object must be sent; for subsequent transactions using stored credentials, CVD can be sent with cardholder-initiated transactions only—<b>merchants must not store CVD information.</b></p>	N/A	
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p>	preauth.setCustId(cust_id);
<p><b>NOTE:</b> For basic Purchase and Preauthorization, the wallet indicator applies to Visa Checkout and MasterCard MasterPass only. For more, see Definition of Request Fields.</p>	<p><i>String</i></p> <p>3-character alphanumeric</p>	preauth.setWalletIndicator(wallet_indicator);
<p><b>NOTE:</b> Applies to Mastercard transactions only</p>	<p><i>String</i></p> <p>true/false</p>	preauth.setFinalAuth("true");
<p>Credential on File Info</p> <p><b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential</p>	<p><i>Object</i></p> <p>N/A</p>	cof.setCofInfo(cof);

Variable Name	Type and Limits	
<p>on File Info object, see Credential on File Info Object and Variables.</p>		

### Credential on File Info object request fields

Variable Name	Type and Limits	
<p>issuer ID</p> <p><b>NOTE:</b> This variable is required for all merchant-initiated transactions following the first one; upon sending the first transaction, the issuer ID value is received in the transaction response and then used in subsequent transaction requests.</p>	<p><i>String</i></p> <p>15-character alphanumeric variable length</p>	<pre>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
<p>payment indicator</p> <p><b>NOTE:</b> In Credential on File transactions where the request field e-commerce indicator is also being sent, the acceptable values for e-commerce indicator are dependent on the value sent for payment indicator; see request field definitions for more information.</p>	<p><i>String</i></p> <p>1-character alphabetic</p>	<pre>cof.setPaymentIndicator("PAYMENT_INDICATOR_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>

Variable Name	Type and Limits	
payment information	<p><i>String</i></p> <p>1-character numeric</p>	<pre>cof.setPaymentInformation("PAYMENT_INFO_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see <a href="#">Definition of Request Fields – Credential on File</a></p>

## Sample Pre-Authorization

```

package Canada;
import JavaAPI.*;
public class TestCanadaPreauth
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String amount = "5.00";
        String pan = "4242424242424242";
        String expdate = "1902";
        String crypt = "7";
        String processing_country_code = "CA";
        boolean foreign_indicator= true;
        boolean status_check = false;

        PreAuth preauth = new PreAuth();
        preauth.setOrderId(order_id);
        preauth.setAmount(amount);
        preauth.setPan(pan);
        preauth.setExpdate(expdate);
        preauth.setCryptType(crypt);
        preauth.setForeignIndicator(foreign_indicator);
        //preauth.setWalletIndicator(""); //Refer documentation for possible values
        //preauth.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique max 50 alphanumeric characters transaction id generated by merchant
        //preauth.setFinalAuth("true");

        // TrId and TokenCryptogram are optional, refer documentation for more details.
        preauth.setTrId("50189815682");
        preauth.setTokenCryptogram("APmbM/411e0uAAH+s6xMAAADFA==");

        //optional - Installment Info
        InstallmentInfo installmentInfo = new InstallmentInfo();
        installmentInfo.setPlanId("ae859ef1-eb91-b708-8b80-1dd481746401");
        installmentInfo.setPlanIdRef("0000000065");
        installmentInfo.setTacVersion("2");
        //preauth.setInstallmentInfo(installmentInfo);

        //optional - Credential on File details
        CofInfo cof = new CofInfo();
        cof.setPaymentIndicator("U");
        cof.setPaymentInformation("2");
        cof.setIssuerId("139X3130ASCXAS9");
    }
}

```

```

preauth.setCofInfo(cof);

//Optional - Pay By bank details
PbbInfo pbbInfo = new PbbInfo();
pbbInfo.setConsentId("c3fef81c-0e12-4311-be7e-c1d102c2a7c9");
pbbInfo.setPaymentMethod("VISA_CREDIT");
preauth.setPbbInfo(pbbInfo);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(preauth);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
//System.out.println("StatusCode = " + receipt.getStatusCode());
//System.out.println("StatusMessage = " + receipt.getStatusMessage());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());
System.out.println("Advice Code= "+ receipt.getAdviceCode());

InstallmentResults installmentResults = receipt.getInstallmentResults();
System.out.println("\nPlanId = " + installmentResults.getPlanId() +"\\n");
System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
System.out.println("TacVersion = " + installmentResults.getTacVersion());
System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
System.out.println("PlanResponse = " + installmentResults.getPlanResponse());

}
catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

## 2.3 Pre-Authorization Completion

Retrieves funds that have been locked (by a Pre-Authorization transaction), and prepares them for settlement into the merchant's account.

**Things to Consider:**

- A Pre-Authorization transaction can only be completed once
- To reverse the full amount of a Pre-Authorization transaction, use the Pre-Authorization Completion transaction with the amount set to 0.00
- To process this transaction, you need the order ID and transaction number from the original Pre-Authorization transaction

```
Completion completion = new Completion();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(completion);
```

**Core connection object fields (all API transactions)**

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	<code>mpgReq.setstoreId(store_id);</code> Unique identifier provided by Moneris upon merchant account setup
API token	<i>String</i> N/A	<code>mpgReq.setApiToken(api_token);</code> Unique alphanumeric string assigned by Moneris upon merchant account activation To find your API token, refer to your test or production store's Admin settings in the Merchant Resource Center, at the following URLs: Testing: <a href="https://esqa-monteris.com/mpg/">https://esqa-monteris.com/mpg/</a> Production: <a href="https://www3-monteris.com/mpg/">https://www3-monteris.com/mpg/</a>

**Pre-Authorization Completion transaction request fields – Required**

Variable Name	Type and Limits	
order ID	<i>String</i>	<code>completion.setOrderId(order_</code>

Variable Name	Type and Limits	
	50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	id) ;
completion amountamount	<i>String</i>  10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	completion.setCompAmount (comp_amount) ;
	<b>EXAMPLE:</b> 1234567.89	
transaction number	<i>String</i>  255-character, alpha-numeric, hyphens or underscores  variable length	completion.setTxnNumber (txn_number) ;
electronic commerce indicator	<i>String</i>  1-character alphanumeric	completion.setCryptType (crypt) ;

#### Pre-Authorization Completion transaction request fields – Optional

Variable Name	Type and Limits	Description
customer ID	<i>String</i>  50-character alphanumeric	completion.setCustId (cust_id) ;
	<b>NOTE:</b> Some special characters are not allowed: < > \$ % = ? ^ { } [ ] \	
dynamic descriptor	<i>String</i>  20-character alphanumeric  total of 22 characters includ-	completion.setDynamicDescriptor (dynamic_descriptor) ;
	<b>NOTE: For Pre-Authorization</b>	

Variable Name	Type and Limits	Description
<b>transactions</b> : the value in the dynamic descriptor field will only be carried over to a Pre-Authorization Completion when executing the latter via the Merchant Resource Center; otherwise, the value for dynamic descriptor must be sent again in the Pre-Authorization Completion	ing your merchant name and separator  <b>NOTE:</b> Some special characters are not allowed: <>\$%=?^{}[]\	
shipping indicator	<i>String</i> 1-character alphanumeric	<code>completion.setShipIndicator(ship_indicator);</code>

## Sample Pre-Authorization Completion

```

package Canada;
import JavaAPI.*;
public class TestCanadaPreauth
{
public static void main(String[] args)
{
String store_id = "store5";
String api_token = "yesguy";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String amount = "5.00";
String pan = "4242424242424242";
String expdate = "1902";
String crypt = "7";
String processing_country_code = "CA";
boolean status_check = false;
PreAuth preauth = new PreAuth();
preauth.setOrderId(order_id);
preauth.setAmount(amount);
preauth.setPan(pan);
preauth.setExpdate(expdate);
preauth.setCryptType(crypt);
//preauth.setWalletIndicator(""); //Refer documentation for possible values
//preauth.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique max 50
alphanumeric characters transaction id generated by merchant
//optional - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

preauth.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(preauth);
}

```

```

mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
//System.out.println("StatusCode = " + receipt.getStatusCode());
//System.out.println("StatusMessage = " + receipt.getStatusMessage());
System.out.println("IssuerId = " + receipt.getIssuerId());

InstallmentResults installmentResults = receipt.getInstallmentResults();
System.out.println("\nPlanId = " + installmentResults.getPlanId() +"\n");
System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
System.out.println("TacVersion = " + installmentResults.getTacVersion());
System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
System.out.println("PlanResponse = " + installmentResults.getPlanResponse());

}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 2.4 Force Post

Retrieves the locked funds and prepares them for settlement into the merchant's account.

Used when a merchant obtains the authorization number directly from the issuer by a third-party authorization method (such as by phone).

### Things to Consider:

- This transaction is an independent completion where the original Pre-Authorization transaction was not processed via the same Moneris Gateway merchant account.

- It is not required for the transaction that you are submitting to have been processed via the Moneris Gateway. However, a credit card number, expiry date and original authorization number are required.
- Force Post transactions are not supported for UnionPay

```
ForcePost forcepost = new ForcePost();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(forcepost);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Force Post transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	forcepost.setorderId(order_id);
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	forcepost.setAmount(amount);

**EXAMPLE: 1234567.89**

Variable Name	Type and Limits	
credit card number	<p><i>String</i></p> <p>max 20-character alpha-numeric</p>	<code>forcepost.setPan(pan);</code>
expiry date	<p><i>String</i></p> <p>4-character alphanumeric</p> <p>YYMM</p>	<code>forcepost.setExpDate(expiry_date);</code>
authorization code	<p><i>String</i></p> <p>8-character alphanumeric</p>	<code>forcepost.setAuthCode(auth_code);</code>
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	<code>forcepost.setCryptType(crypt);</code>

### Force Post transaction request fields – Optional

Variable Name	Type and Limits	
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid black; padding: 5px;"> <b>NOTE:</b>            Some special characters are not allowed:  <code>&lt;&gt;\$%=?^{}[]\</code> </div>	<code>forcepost.setCustId(cust_id);</code>
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid black; padding: 5px;"> <b>NOTE:</b>            Some special characters are not allowed:  <code>&lt;&gt;\$%=?^{}[]\</code> </div>	<code>forcepost.setDynamicDescriptor(dynamic_descriptor);</code>

## Sample Force Post

```

package Canada;
import JavaAPI.*;
public class TestCanadaForcePost
{
public static void main(String[] args)
{
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String cust_id = "my customer id";
String store_id = "moneris";
String api_token = "hurgle";
String amount = "1.00";
String pan = "4242424242424242";
String expdate = "1901"; //YYMM format
String auth_code = "88864";
String crypt = "7";
String dynamic_descriptor = "my descriptor";
String processing_country_code = "CA";
boolean status_check = false;
ForcePost forcepost = new ForcePost();
forcepost.setOrderId(order_id);
forcepost.setCustId(cust_id);
forcepost.setAmount(amount);
forcepost.setPan(pan);
forcepost.setExpdate(expdate);
forcepost.setAuthCode(auth_code);
forcepost.setCryptType(crypt);
forcepost.setDynamicDescriptor(dynamic_descriptor);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(forcepost);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CorporateCard = " + receipt.getCorporateCard());
//System.out.println("MessageId = " + receipt.getMessageId());
System.out.println("IssuerId = " + receipt.getIssuerId());
}
catch (Exception e)
{
e.printStackTrace();
}
}

```

```
}
```

## 2.5 Purchase Correction

Restores the full amount of a previous Purchase, Pre-Authorization Completion or Force Post transaction to the cardholder's card, and removes any record of it from the cardholder's statement.

This transaction can be used against a Purchase or Pre-Authorization Completion transaction that occurred same day provided that the batch containing the original transaction remains open.

### Things to Consider:

- To process this transaction, you need the order ID and the transaction number from the original Completion, Purchase or Force Post transaction.

```
PurchaseCorrection purchasecorrection = new PurchaseCorrection();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(purchasecorrection);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Purchase Correction transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	purchasecorrection.setorderId(order_id);
transaction number	<i>String</i>	purchasecorrection.setTxnNumber(txn_number);

Variable Name	Type and Limits	
	255-character, alpha-numeric, hyphens or underscores  variable length	
electronic commerce indicator	<i>String</i>  1-character alphanumeric	<code>purchasecorrection.setCryptType(crypt);</code>

### Purchase Correction transaction request fields – Optional

Variable Name	Type and Limits	
customer ID	<i>String</i>  50-character alphanumeric	<code>purchasecorrection.setCustId(cust_id);</code>
dynamic descriptor	<i>String</i>  20-character alphanumeric  total of 22 characters including your merchant name and separator	<code>purchasecorrection.setDynamicDescriptor(dynamic_descriptor);</code>

### Sample Purchase Correction

```
package Canada;
import JavaAPI.*;
public class TestCanadaPurchaseCorrection
{
public static void main(String[] args)
{
String store_id = "store5";
String api_token = "yesguy";
String order_id = "Test1432065003686";
String txn_number = "42014-0_10";
String crypt = "7";
String dynamic_descriptor = "123456";
```

```

String processing_country_code = "CA";
boolean status_check = false;
PurchaseCorrection purchasecorrection = new PurchaseCorrection();
purchasecorrection.setOrderId(order_id);
purchasecorrection.setTxnNumber(txn_number);
purchasecorrection.setCryptType(crypt);
purchasecorrection.setDynamicDescriptor(dynamic_descriptor);
purchasecorrection.setCustId("my customer id");
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(purchasecorrection);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());

InstallmentResults installmentResults = receipt.getInstallmentResults();
System.out.println("\nPlanId = " + installmentResults.getPlanId() + "\n");
System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
System.out.println("TacVersion = " + installmentResults.getTacVersion());
System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
System.out.println("PlanResponse = " + installmentResults.getPlanResponse());
}
catch (Exception e)
{
e.printStackTrace();
}
}

```

## 2.6 Refund

Restores all or part of the funds from a Purchase, Pre-Authorization Completion or Force Post transaction to the cardholder's card.

Unlike a Purchase Correction, there is a record of both the initial charge and the refund on the cardholder's statement.

For processing refunds on a different card than the one used in the original transaction, the Independent Refund transaction should be used instead.

To process this transaction, you need the order ID and transaction number from the original Completion, Purchase or Force Post transaction.

```
Refund refund = new Refund();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(refund);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Refund transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	refund.setOrderId(order_id);
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	refund.setAmount(amount);
<b>EXAMPLE: 1234567.89</b>		
transaction number	<i>String</i>	refund.setTxnNumber(txn_

Variable Name	Type and Limits	
	255-character, alpha-numeric, hyphens or underscores  variable length	number);
electronic commerce indicator	<i>String</i>  1-character alphanumeric	refund.setCryptType(crypt);

## Sample Refund

```

package Canada;
import JavaAPI.*;
public class TestCanadaRefund
{
    public static void main(String[] args)
    {
        String store_id = "store1";
        String api_token = "yesguy";
        String amount = "1.00";
        String crypt = "7";
        String dynamic_descriptor = "123456";
        String custid = "mycust9";
        String order_id = "mvt2713618548";
        String txn_number = "911464-0_10";
        String processing_country_code = "CA";
        boolean status_check = false;
        Refund refund = new Refund();
        refund.setTxnNumber(txn_number);
        refund.setOrderId(order_id);
        refund.setAmount(amount);
        refund.setCryptType(crypt);
        refund.setCustId(custid);
        refund.setDynamicDescriptor(dynamic_descriptor);
        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(refund);
        mpgReq.setStatusCheck(status_check);
        mpgReq.send();
        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("CardType = " + receipt.getCardType());
            System.out.println("TransAmount = " + receipt.getTransAmount());
            System.out.println("TxnNumber = " + receipt.getTxnNumber());
            System.out.println("ReceiptId = " + receipt.getReceiptId());
            System.out.println("TransType = " + receipt.getTransType());
            System.out.println("ReferenceNum = " + receipt.getReferenceNum());
            System.out.println("ResponseCode = " + receipt.getResponseCode());
            System.out.println("ISO = " + receipt.getISO());
            System.out.println("BankTotals = " + receipt.getBankTotals());
            System.out.println("Message = " + receipt.getMessage());
            System.out.println("AuthCode = " + receipt.getAuthCode());
            System.out.println("Complete = " + receipt.getComplete());
            System.out.println("TransDate = " + receipt.getTransDate());
        }
    }
}

```

```

System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());

InstallmentResults installmentResults = receipt.getInstallmentResults();
System.out.println("\nPlanId = " + installmentResults.getPlanId() +"\n");
System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
System.out.println("TacVersion = " + installmentResults.getTacVersion());
System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
System.out.println("PlanResponse = " + installmentResults.getPlanResponse());

}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 2.7 Independent Refund

Credits a specified amount to the cardholder's credit card. The credit card number and expiry date are mandatory.

It is not necessary for the transaction that you are refunding to have been processed via the Moneris Gateway.

### Things to Consider:

- Because of the potential for fraud, permission for this transaction is not granted to all accounts by default. If it is required for your business, it must be requested via your account manager.

**NOTE:** Independent Refund transactions do not support Installments

```

IndependentRefund indrefund = new IndependentRefund();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(indrefund);

```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i>	mpgReq.setStoreId(store_id);

Variable Name	Type and Limits	
	N/A	
API token	<i>String</i> N/A	<code>mpgReq.setApiToken(api_token);</code>

### Independent Refund transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	<code>indrefund.setOrderId(order_id);</code>
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	<code>indrefund.setAmount(amount);</code>
<b>EXAMPLE: 1234567.89</b>		
credit card number	<i>String</i> max 20-character alpha- numeric	<code>indrefund.setPan(pan);</code>
expiry date	<i>String</i> 4-character alphanumeric YYMM	<code>indrefund.setExpDate(expiry_date);</code>
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>indrefund.setCryptType(crypt);</code>

## Independent Refund transaction request fields – Optional

Variable Name	Type and Limits	
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid black; padding: 5px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt;\$%=?^{}[]\         </div>	indrefund.setCustId(cust_id);
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid black; padding: 5px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt;\$%=?^{}[]\         </div>	indrefund.setDynamicDescriptor(dynamic_descriptor);

## Sample Independent Refund

```

package Canada;
import JavaAPI.*;
public class TestCanadaIndependentRefund
{
  public static void main(String[] args)
  {
    java.util.Date createDate = new java.util.Date();
    String order_id = "Test"+createDate.getTime();
    String store_id = "store5";
    String api_token = "yesguy";
    String cust_id = "my customer id";
    String amount = "20.00";
    String pan = "4242424242424242";
    String expdate = "1901"; //YYMM
    String crypt = "7";
    String processing_country_code = "CA";
    boolean status_check = false;
    IndependentRefund indrefund = new IndependentRefund();
    indrefund.setOrderId(order_id);
    indrefund.setCustId(cust_id);
    indrefund.setAmount(amount);
    indrefund.setPan(pan);
    indrefund.setExpdate(expdate);
    indrefund.setCryptType(crypt);
    indrefund.setDynamicDescriptor("123456");
    HttpsPostRequest mpgReq = new HttpsPostRequest();
    mpgReq.setProcCountryCode(processing_country_code);
    mpgReq.setTestMode(true); //false for production transactions
    mpgReq.setstoreId(store_id);
  }
}

```

```

mpgReq.setApiToken(api_token);
mpgReq.setTransaction(indrefund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 2.8 Card Verification with AVS and CVD

Verifies the validity of the credit card, expiry date and any additional details (such as the Card Verification Digits or Address Verification details). It does not verify the available amount or lock any funds on the credit card.

### Things to Consider:

- The Card Verification transaction is only supported by Visa, Mastercard, Discover and American Express
- For some Credential on File transactions, Card Verification with AVS and CVD is used as a prior step to get the Issuer ID used in the subsequent transaction
- When testing Card Verification, please use the Visa and MasterCard test card numbers provided in the MasterCard Card Verification and Visa Card Verification tables available in CVD & AVS (E-Fraud) Simulator.

- For a full list of possible AVS & CVD result codes refer to the CVD and AVS Result Code tables.

```
CardVerification cardVerification = new CardVerification();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(cardVerification );
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Card Verification transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	cardVerification.setOrderId(order_id);
credit card number	<i>String</i> max 20-character alphanumeric	cardVerification.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric YYMM	cardVerification.setExpDate(expiry_date);
electronic commerce indicator	<i>String</i> 1-character alphanumeric	cardVerification.setCryptType(crypt);

Variable Name	Type and Limits	
AVS Information	<i>Object</i> N/A	<code>cardVerification.setAvsInfo(avsCheck);</code>
CVD Information	<i>Object</i> N/A	<code>cardVerification.setCvdInfo(cvdCheck);</code>

### Credential on File Info object request fields

Variable Name	Type and Limits	
issuer ID	<i>String</i> 15-character alphanumeric variable length	<code>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</code>  <b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File
payment indicator	<i>String</i> 1-character alphabetic	<code>cof.setPaymentIndicator("PAYMENT_INDICATOR_VALUE");</code>  <b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File

Variable Name	Type and Limits	
payment information	<i>String</i> 1-character numeric	<pre>cof.setPaymentInformation("PAYMENT_INFO_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see <a href="#">Definition of Request Fields – Credential on File</a></p>

## Sample Card Verification

```

package Canada;
import JavaAPI.*;
public class TestCanadaCardVerification
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String pan = "4242424242424242";
        String expdate = "1901"; //YYMM format
        String crypt = "7";
        String processing_country_code = "CA";
        boolean status_check = false;

        AvsInfo avsCheck = new AvsInfo();
        avsCheck.setAvsStreetNumber("212");
        avsCheck.setAvsStreetName("Payton Street");
        avsCheck.setAvsZipCode("M1M1M1");
        CvdInfo cvdCheck = new CvdInfo();
        cvdCheck.setCvdIndicator("1");
        cvdCheck.setCvdValue("099");
        CardVerification cardVerification = new CardVerification();
        cardVerification.setOrderId(order_id);
        cardVerification.setPan(pan);
        cardVerification.setExpdate(expdate);
        cardVerification.setCryptType(crypt);
        cardVerification.setAvsInfo(avsCheck);
        cardVerification.setCvdInfo(cvdCheck);

        // TrId and TokenCryptogram are optional, refer documentation for more details.
        cardVerification.setTrId("50189815682");
        cardVerification.setTokenCryptogram("APmbM/411e0uAAH+s6xMAAADFA==");

        //optional - Credential on File details
        CofInfo cof = new CofInfo();
        cof.setPaymentIndicator("U");
        cof.setPaymentInformation("2");
        cof.setIssuerId("139X3130ASCXAS9");

        cardVerification.setCofInfo(cof);

        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
    }
}

```

```

mpgReq.setTransaction(cardVerification);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 2.9 Batch Close

Takes the funds from all Purchase, Completion, Refund and Force Post transactions so that they will be deposited or debited the following business day.

For funds to be deposited the following business day, the batch must close before 11 pm Eastern Time.

```

BatchClose batchclose = new BatchClose();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(batchclose);

```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

## Batch Close transaction request fields – Required

Variable Name	Type and Limits	
ECR (electronic cash register) number	<i>String</i> No limit (value provided by Moneris)	batchclose.setEcrno(ecr_no);

## Sample Batch Close

```

package Canada;
import JavaAPI.*;
public class TestCanadaBatchClose
{
  public static void main(String[] args)
  {
    String store_id = "store5";
    String api_token = "yesguy";
    String ecr_no = "66013455"; //ecr within store
    String processing_country_code = "CA";
    boolean status_check = false;
    BatchClose batchclose = new BatchClose();
    batchclose.setEcrno(ecr_no);
    HttpsPostRequest mpgReq = new HttpsPostRequest();
    mpgReq.setProcCountryCode(processing_country_code);
    mpgReq.setTestMode(true); //false for production transactions
    mpgReq.setstoreId(store_id);
    mpgReq.setApiToken(api_token);
    mpgReq.setTransaction(batchclose);
    mpgReq.setStatusCheck(status_check);
    mpgReq.send();
    try
    {
      Receipt receipt = mpgReq.getReceipt();
      if ((receipt.getReceiptId()).equals("Global Error Receipt") ||
          receipt.getReceiptId().equals("null") ||
          receipt.getReceiptId().equals(""))
      {
        System.out.println("CardType = " + receipt.getCardType());
        System.out.println("TransAmount = " + receipt.getTransAmount());
        System.out.println("TxnNumber = " + receipt.getTxnNumber());
        System.out.println("ReceiptId = " + receipt.getReceiptId());
        System.out.println("TransType = " + receipt.getTransType());
        System.out.println("ReferenceNum = " + receipt.getReferenceNum());
        System.out.println("ResponseCode = " + receipt.getResponseCode());
        System.out.println("ISO = " + receipt.getISO());
        System.out.println("BankTotals = null");
        System.out.println("Message = " + receipt.getMessage());
        System.out.println("AuthCode = " + receipt.getAuthCode());
        System.out.println("Complete = " + receipt.getComplete());
        System.out.println("TransDate = " + receipt.getTransDate());
        System.out.println("TransTime = " + receipt.getTransTime());
        System.out.println("Ticket = " + receipt.getTicket());
        System.out.println("TimedOut = " + receipt.getTimedOut());
      }
      else
      {
        for (String ecr : receipt.getTerminalIDs())
        {
          System.out.println("ECR: " + ecr);
          for(String cardType : receipt.getCreditCards(ecr))
        }
      }
    }
  }
}

```

## 2.10 Open Totals

Returns the details about the currently open batch.

Similar to the Batch Close; the difference is that it does not close the batch for settlement.

```
OpenTotals opentotals = new OpenTotals();  
  
HttpsPostRequest mpgReq = new HttpsPostRequest();  
  
mpgReq.setTransaction(opentotals);
```

## Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

## **Open Totals transaction request fields – Required**

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	
ECR (electronic cash register) number	No limit (value provided by Moneris)	opentotals.setEcrno(ecr_no);

## Sample Open Totals

```

package Canada;
import JavaAPI.*;
public class TestCanadaOpenTotals
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        String ecr_no = "66013455";
        //String ecr_no = "66011091";
        String processing_country_code = "CA";
        OpenTotals opentotals = new OpenTotals();
        opentotals.setEcrno(ecr_no);
        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(opentotals);
        mpgReq.send();

        try
        {
            Receipt receipt = mpgReq.getReceipt();
            if ((receipt.getReceiptId()).equals("Global Error Receipt") ||
                receipt.getReceiptId().equals("null") ||
                receipt.getReceiptId().equals(""))
            {
                System.out.println("CardType = null");
                System.out.println("TransAmount = " + receipt.getTransAmount());
                System.out.println("TxnNumber = " + receipt.getTxnNumber());
                System.out.println("ReceiptId = " + receipt.getReceiptId());
                System.out.println("TransType = " + receipt.getTransType());
                System.out.println("ReferenceNum = " + receipt.getReferenceNum());
                System.out.println("ResponseCode = " + receipt.getResponseCode());
                System.out.println("ISO = " + receipt.getISO());
                System.out.println("BankTotals = null");
                System.out.println("Message = " + receipt.getMessage());
                System.out.println("AuthCode = " + receipt.getAuthCode());
                System.out.println("Complete = " + receipt.getComplete());
                System.out.println("TransDate = " + receipt.getTransDate());
                System.out.println("TransTime = " + receipt.getTransTime());
                System.out.println("Ticket = " + receipt.getTicket());
                System.out.println("TimedOut = " + receipt.getTimedOut());
            }
            else
            {
                for (String ecr : receipt.getTerminalIDs())
                {
                    System.out.println("ECR: " + ecr);

                    for (String cardType : receipt.getCreditCards(ecr))
                    {
                        System.out.println("\tCard Type: " + cardType);
                        System.out.println("\t\tPurchase Count = "
                            + receipt.getPurchaseCount(ecr, cardType));
                }
            }
        }
    }
}

```

```
+ " Amount = "
+ receipt.getPurchaseAmount(ecr,
cardType));
System.out.println("\t\tRefund: Count = "
+ receipt.getRefundCount(ecr, cardType)
+ " Amount = "
+ receipt.getRefundAmount(ecr, cardType));
System.out.println("\t\tCorrection: Count = "
+ receipt.getCorrectionCount(ecr, cardType)
+ " Amount = "
+ receipt.getCorrectionAmount(ecr,
cardType));
}
}
}
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
```

## 3 Credential on File

- 3.1 About Credential on File
- 3.2 Credential on File Info Object and Variables
- 3.3 Credential on File Transaction Types
- 3.5 Initial Transactions in Credential on File
- 3.9 Credential on File and Converting Temporary Tokens
- 3.8 Vault Tokenize Credit Card and Credential on File
- 3.10 Card Verification and Credential on File Transactions

### 3.1 About Credential on File

When storing customers' credit card credentials for use in future authorizations, or when using these credentials in subsequent transactions, card brands now require merchants to indicate this in the transaction request.

In the Moneris API, this is handled by the Moneris Gateway via the inclusion of the Credential on File info object and its variables in the transaction request.

While the requirements for handling Credential on File transactions relate to Visa, Mastercard and Discover only, in order to avoid confusion and prevent error, please implement these changes for all card types and the Moneris system will then correctly flow the relevant card data values as appropriate.

**NOTE:** If either the first transaction or a Card Verification authorization is declined when attempting to store cardholder credentials, those credentials cannot be stored —therefore the merchant must not use the credential for any subsequent transactions.

### 3.2 Credential on File Info Object and Variables

The Credential on File Info object is nested within the request for the applicable transaction types.

Credential on File Info Object:

cof

Variables in the cof object:

Payment Indicator

Payment Information

#### Issuer ID

For more information, see [Definition of Request Fields – Credential on File](#).

### 3.3 Credential on File Transaction Types

The Credential on File Info object applies to the following transaction types:

- Purchase
- Pre-Authorization
- Purchase with 3-D Secure – cavvPurchase
- Purchase with 3-D Secure and Recurring Billing
- Pre-Authorization with 3-D Secure – cavvPreauth
- Purchase with Vault – ResPurchaseCC
- Pre-Authorization with Vault – ResPreauthCC
- Card Verification with AVS and CVD
- Card Verification with Vault – ResCardVerificationCC
- Vault Add Credit Card – ResAddCC
- Vault Update Credit Card – ResUpdateCC
- Vault Add Token – ResAddToken
- Vault Tokenize Credit Card – ResTokenizeCC
- Recurring Billing
- MCP Purchase
- MCP Pre-Authorization
- MCP Pre-Authorization Completion

- MCP Purchase with Vault
- MCP Pre-Authorization with Vault

## 3.4 Merchant- vs. Cardholder-Initiated COF Transactions

Transactions defined as Credential on File (COF) can be initiated one of two ways: by a merchant or by a cardholder. The initiator of a transaction is important because it determines which Credential on File indicator fields need to be sent in the transaction request.

**Merchant-initiated Credential on File transactions:** transactions in which the merchant intends to store cardholder credentials or use credentials that have already been stored. This includes sending the Credential on File Info object in the transaction request, and including all three of its fields: **issuer ID**, **payment indicator** and **payment information**.

**Cardholder-initiated Credential on File transactions:** transactions which are triggered by some action by the cardholder. For cardholder-initiated transactions, only the **payment indicator** and **payment information** fields are required.

For simplicity in developing your integration, the Moneris Gateway also allows cardholder-initiated transactions to be processed according to the same Credential on File rules as apply to merchant-initiated transactions. Technically, the **issuer ID** indicator is not required for cardholder-initiated transactions, but for convenience, if it is included in the transaction request, the Moneris Gateway will just ignore it when forwarding the request to the host.

## 3.5 Initial Transactions in Credential on File

When sending an *initial* transaction with the Credential on File Info object, i.e., a transaction request where the cardholder's credentials are being stored for the *first* time, it is important to understand the following:

- You must send the cardholder's Card Verification Digits (CVD)
- **Issuer ID** will be sent without a value on the initial transaction, because it is received in the response to that initial transaction; for all *subsequent* merchant-initiated transactions and all administrative transactions you send this **Issuer ID**
- The **payment information** field should always be set to a value of 0 on the first transaction
- The **payment indicator** field should be set to the value that is appropriate for the transaction

## 3.6 COF With Previously Stored Credentials

When processing a transaction with cardholder information that was already stored **prior to** the implementation of Credential on File requirements, you must:

- Include the Credential on File Info object in the transaction request, and
- Send the **payment information** value as 2, and
- Store the **issuer ID** returned in the transaction and associate it with the cardholder credentials for future use

Once the **issuer ID** has been stored and associated with the cardholder credentials, send it in all subsequent transactions going forward. **Issuer ID** is only required when sending merchant-initiated transactions.

## 3.7 Payment Indicator and E-Commerce Indicator Values

When sending Credential on File information in transaction requests that also include the **e-commerce indicator** request field (in code, referred to as `crypt`), acceptable values for the e-commerce indicator are dependent upon the value being sent for the **payment indicator**.

If Payment Indicator Value is:	Allowable e-commerce indicator values are:
R	2 – Mail Order / Telephone Order—Recurring 5 – Authenticated e-commerce transaction (3-D Secure) 6 – Non-authenticated e-commerce transaction (3-D Secure)
V	2 – Mail Order / Telephone Order—Recurring (Variable) 5 – Authenticated e-commerce transaction (3-D Secure) 6 – Non-authenticated e-commerce transaction (3-D Secure)
C	1 – Mail Order / Telephone Order—Single 5 – Authenticated e-commerce transaction (3-D Secure) 6 – Non-authenticated e-commerce transaction (3-D Secure) 7 – SSL-enabled merchant
U	1 – Mail Order / Telephone Order—Single 7 – SSL-enabled merchant

If Payment Indicator Value is:	Allowable e-commerce indicator values are:
Z	1 – Mail Order / Telephone Order—Single 5 – Authenticated e-commerce transaction (3-D Secure) 6 – Non-authenticated e-commerce transaction (3-D Secure) 7 – SSL-enabled merchant

## 3.8 Vault Tokenize Credit Card and Credential on File

When you want to store cardholder credentials from previous transactions into the Vault, you use the Vault Tokenize Credit Card transaction request. Credential on File rules require that only previous transactions with the Credential on File Info object can be tokenized to the Vault.

For more information about this transaction, see 4.5.10 Vault Tokenize Credit Card – ResTokenizeCC.

## 3.9 Credential on File and Converting Temporary Tokens

In the event you decide to convert a temporary token representing cardholder credentials into a permanent token, these credentials become stored credentials, and therefore it is necessary to send Credential on File information.

For Vault Temporary Token Add transactions where you subsequently decide to convert the temporary token into a permanent token (stored credentials):

1. Send a transaction request that includes the Credential on File Info object to get the Issuer ID; this can be a Card Verification, Purchase or Pre-Authorization request
2. After completing the transaction, send the Vault Add Token request with the Credential on File object (Issuer ID only) in order to convert the temporary token to a permanent one.

## 3.10 Card Verification and Credential on File Transactions

In the absence of a Purchase or Pre-Authorization, a Card Verification transaction is used to get the unique issuer ID value (**issuerId**) that is used in subsequent Credential on File transactions. Issuer ID is a variable included in the nested Credential on File object.

For all first-time transactions, including Card Verification transactions, you must also request the cardholder's Card Verification Details (CVD). For more on CVD, see 10.2 Card Validation Digits (CVD).

For a complete list of these variables, see each transaction type or Definition of Request Fields – Credential on File

The Card Verification request, including the Credential on File Info object, must be sent immediately prior to storing cardholder credentials.

For information about Card Verification, see 2.8 Card Verification with AVS and CVD.

### **3.10.1 When to Use Card Verification With COF**

If you are not sending a Purchase or Pre-Authorization transaction (i.e., you are not charging the customer immediately), you must use Card Verification (or in the case of Vault Add Token, Card Verification with Vault) first before running the transaction in order to get the Issuer ID.

Transactions this applies to:

Vault Add Credit Card – ResAddCC

Vault Update Credit Card – ResUpdateCC

Vault Add Token – ResAddToken

Recurring Billing transactions, if:

- the first transaction is set to start on a future date

### **3.10.2 Credential on File and Vault Add Token**

For Vault Add Token transactions:

1. Send Card Verification with Vault transaction request including the Credential on File object to get the Issuer ID
2. Send the Vault Add Token request including the Credential on File object (with Issuer ID only; other fields are not applicable)

For more on this transaction type, see 4.5.9 Vault Add Token – ResAddToken.

### **3.10.3 Credential on File and Vault Update Credit Card**

For Vault Update Credit Card transactions where you are updating the credit card number:

1. Send Card Verification transaction request including the Credential on File object to get the Issuer ID

2. Send the Vault Update Credit Card request including the Credential on File Info object (Issuer ID only).

For more on this transaction type, see 4.5.3 Vault Update Credit Card – ResUpdateCC.

#### 3.10.4 Credential on File and Vault Add Credit Card

For Vault Add Credit Card transactions:

1. Send Card Verification transaction request including the Credential on File object to get the Issuer ID
2. Send the Vault Add Credit Card request including the Credential on File Info object (Issuer ID only)

For more on this transaction type, see 4.5.1 Vault Add Credit Card – ResAddCC.

#### 3.10.5 Credential on File and Recurring Billing

**NOTE:** The value of the **payment indicator** field must be **R** when sending Recurring Billing transactions.

For Recurring Billing transactions which are set to start **immediately**:

1. Send a Purchase transaction request with both the Recurring Billing and Credential on File info objects (with Recurring Billing object field **start now** = true)

For Recurring Billing transactions which are set to start on a **future** date:

1. Send Card Verification transaction request including the Credential on File info object to get the Issuer ID
2. Send Purchase transaction request with the Recur and Credential on File info objects included

For updating a Recurring Billing series where you are updating the card number (does not apply if you are only modifying the schedule or amount in a recurring series):

1. Send Card Verification request including the Credential on File info object to get the Issuer ID
2. Send a Recurring Billing Update transaction

For more information about the Recurring Billing object, see [Definition of Request Fields – Recurring](#).

## 4 Vault

- 4.1 About the Vault Transaction Set
- 4.2 Vault Transaction Types
- 4.3 Vault Transactions That Support Temporary Tokens
- 4.5 Vault Administrative Transactions
- 4.6 Vault Financial Transactions
- 4.7 Hosted Tokenization

### 4.1 About the Vault Transaction Set

The Vault feature allows merchants to create customer profiles, edit those profiles, and use them to process transactions without having to enter financial information each time. Customer profiles store customer data essential to processing transactions, including credit and signature debit.

The Vault is a complement to the Recurring Billing module. It securely stores customer account information on Moneris secure servers. This allows merchants to bill customers for routine products or services when an invoice is due.

### 4.2 Vault Transaction Types

The Vault API supports both administrative and financial transactions.

#### 4.2.1 Administrative Vault Transaction types

##### **ResAddCC**

Creates a new credit card profile, and generates a unique data key which can be obtained from the Receipt object.

This data key is the profile identifier that all future financial Vault transactions will use to associate with the saved information.

##### **EncResAddCC**

Creates a new credit card profile, but requires the card data to be either swiped or manually keyed in via a Moneris-provided encrypted mag swipe reader.

##### **ResTempAdd**

Creates a new temporary token credit card profile. This transaction requires a duration to be set to indicate how long the temporary token is to be stored for.

During the lifetime of this temporary token, it may be used for any other vault transaction before it is permanently deleted from the system.

##### **ResUpdateCC**

Updates a Vault profile (based on the data key) to contain credit card information.

All information contained within a credit card profile is updated as indicated by the submitted fields.

**EncResUpdateCC**

Updates a profile (based on the data key) to contain credit card information. The encrypted version of this transaction requires the card data to either be swiped or manually keyed in via a Moneris-provided encrypted mag swipe reader.

**ResDelete**

Deletes an existing Vault profile of any type using the unique data key that was assigned when the profile was added.

It is important to note that after a profile is deleted, the information which was saved within can no longer be retrieved.

**ResLookupFull**

Verifies what is currently saved under the Vault profile associated with the given data key. The response to this transaction returns the latest active data for that profile.

Unlike ResLookupMasked (which returns the masked credit card number), this transaction returns both the masked and the unmasked credit card numbers.

**ResLookupMasked**

Verifies what is currently saved under the Vault profile associated with the given data key. The response to this transaction returns the latest active data for that profile.

Unlike ResLookupFull (which only returns both the masked and the unmasked credit card numbers), this transaction only returns the masked credit card number.

**ResGetExpiring**

Verifies which profiles have credit cards that are expiring during the current and next calendar month. For example, if you are processing this transaction on September 30, then it will return all cards that expire(d) in September and October of this year.

When generating a list of profiles with expiring credit cards, only the **masked** credit card numbers are returned.

This transaction can be performed no more than 2 times on any given calendar day, and it only applies to credit card profiles.

**ResIsCorporateCard**

Determines whether a profile has a corporate card registered within it.

After sending the transaction, the response field to the Receipt object's getCorporateCard method is either `true` or `false` depending on whether the associated card is a corporate card.

**ResAddToken**

Converts a Hosted Tokenization temporary token to a permanent Vault token.

A temporary token is valid for 15 minutes after it is created.

**ResTokenizeCC**

Creates a new credit card profile using the credit card number, expiry date and e-commerce indicator that were submitted in a previous financial transaction. A transaction that was previously done in Moneris Gateway is taken, and the card data from that transaction is stored in the Moneris Vault.

As with ResAddCC, a unique data key is generated and returned to the merchant via the Receipt object. This is the profile identifier that all future financial Vault transactions will use to associate with the saved information.

## 4.2.2 Financial Vault Transaction types

**ResPurchaseCC**

Uses the data key to identify a previously registered credit card profile. The details saved within the profile are then submitted to perform a Purchase transaction.

**ResPreauthCC**

Uses the data key to identify a previously registered credit card profile. The details within the profile are submitted to perform a Pre-Authorization transaction.

**ResIndRefundCC**

Uses the unique data key to identify a previously registered credit card profile, and credits a specified amount to that credit card.

**ResMpiTxn**

Uses the data key (as opposed to a credit card number) in a VBV/SecureCode Txn MPI transaction. The merchant uses the data key with ResMpiTxn request, and then reads the response fields to verify whether the card is enrolled in Verified by Visa or MasterCard SecureCode. Retrieves the vault transaction value to pass on to Visa or MasterCard.

After it has been validated that the data key is enrolled in 3-D Secure, a window appears in which the customer can enter the 3-D Secure password. The merchant may initiate the forming of the validation form `getMpiInLineForm()`.

For more information on integrating with MonerisMPI, refer to 1 MPI.

## 4.3 Vault Transactions That Support Temporary Tokens

The following transactions support temporary as well as permanent tokens:

- Purchase with Vault – ResPurchaseCC
- Pre-Authorization with Vault – ResPreauthCC
- Card Verification with Vault – ResCardVerificationCC
- Purchase with Vault and 3-D Secure

- Pre-Authorization with Vault & 3-D Secure
- Force Post with Vault – ResForcePostCC
- Vault Independent Refund – ResIndRefundCC
- Vault Is Corporate Card - ResIsCorporateCard

## 4.4 Vault and Installments

Installments functionality is also available on transactions using cardholder credentials stored in the Moneris Vault. To offer this feature to the customer, send the Vault Installment Plan Lookup transaction prior to running a Purchase with Vault or Pre-Authorization with Vault.

For more about Installments, see [9 Installments by Visa](#)

## 4.5 Vault Administrative Transactions

Administrative transactions allow you to perform such tasks as creating new Vault profiles, deleting existing Vault profiles and updating profile information.

Some Vault Administrative Transactions require the Credential on File object to be sent with the **issuer ID** field only.

### 4.5.1 Vault Add Credit Card – ResAddCC

Creates a new credit card profile, and generates a unique data key which can be obtained from the Receipt object.

This data key is the profile identifier that all future financial Vault transactions will use to associate with the saved information.

#### Vault Add Credit Card transaction object definition

```
ResAddCC resaddcc = new ResAddCC();
```

#### HttpsPostRequest object for Vault Add Credit Card transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();  
mpgReq.setTransaction(resaddcc);
```

#### Vault Add Credit Card transaction request fields – Required

For a full description of mandatory and optional values, see [Appendix A Definition of Request Fields](#).

Variable Name	Type and Limits	Set Method
credit card number	<i>String</i> max 20-character alphanumeric	<code>resaddcc.setPan(pan);</code>
expiry date	<i>String</i> 4-character alphanumeric YYMM	<code>resaddcc.setExpDate(expiry_date);</code>
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>resaddcc.setCryptType(crypt);</code>
Credential on File Info	<i>Object</i>	<code>resaddcc.setCofInfo(cof);</code>
cof	N/A	
<b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.		

### Vault Add Credit Card transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<i>String</i> 50-character alphanumeric	<code>resaddcc.setCustId(cust_id);</code>
<b>NOTE:</b> Some special characters are not allowed: <code>&lt; &gt; \$ % = ? ^ { } [ ] \</code>		
email address	<i>String</i> 30-character alphanumeric	<code>resaddcc.setEmail(email);</code>

Variable Name	Type and Limits	Set Method
phone number	<i>String</i> 30-character alphanumeric	<code>resaddcc.setPhone(phone);</code>
note	<i>String</i> 30-character alphanumeric	<code>resaddcc.setNote(note);</code>
data key format	<i>String</i> 2-character alphanumeric	<code>resaddcc.setDataKeyFormat(data_key_format);</code>
AVS Information	<i>Object</i> N/A	<code>resaddcc.setAvsInfo(avscCheck);</code>

### Credential on File Info object request fields

Variable Name	Type and Limits	Set Method
issuer ID	<i>String</i> 15-character alphanumeric variable length	<code>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</code>  <b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File

### Sample Vault Add Credit Card

```
package Canada;
import JavaAPI.*;
public class TestCanadaResAddCC
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        String pan = "4242424242424242";
        String expdate = "1912";
        String phone = "0000000000";
```

### Sample Vault Add Credit Card

```

String email = "bob@smith.com";
String note = "my note";
String cust_id = "customer1";
String crypt_type = "7";
String data_key_format = "0";
String processing_country_code = "CA";
boolean status_check = false;
AvsInfo avsCheck = new AvsInfo();
avsCheck.setAvsStreetNumber("212");
avsCheck.setAvsStreetName("Payton Street");
avsCheck.setAvsZipCode("M1M1M1");
ResAddCC resaddcc = new ResAddCC();
resaddcc.setPan(pan);
resaddcc.setExpdate(expdate);
resaddcc.setCryptType(crypt_type);
resaddcc.setCustId(cust_id);
resaddcc.setPhone(phone);
resaddcc.setEmail(email);
resaddcc.setNote(note);
resaddcc.setAvsInfo(avsCheck);
//resaddcc.setDataKeyFormat(data_key_format); //optional
//Mandatory - Credential on File details
CofInfo cof = new CofInfo();
cof.setIssuerId("139X3130ASCXAS9"); //can be obtained by performing card verification

resaddcc.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resaddcc);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("MaskedPan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("IssuerId = " + receipt.getIssuerId());
}

```

## Sample Vault Add Credit Card

```
        catch (Exception e)
        {
e.printStackTrace();
        }
    }
}
```

## Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see [Definitions of Response Fields](#) (page 563).

#### 4.5.1.1 Vault Data Key

The ResAddCC sample code includes the following instruction from the Receipt object:

```
System.out.println("DataKey = " + receipt.getDataKey());
```

The data key response field is populated when you send a Vault Add Credit Card – ResAddCC (page 66), Vault Encrypted Add Credit Card – EncResAddCC (page 70), Vault Tokenize Credit Card – ResTokenizeCC (page 95), Vault Temporary Token Add – ResTempAdd (page 73) or Vault Add Token – ResAddToken (page 91) transaction. It is the profile identifier that all future financial Vault transactions will use to associate with the saved information.

The data key is a maximum 28-character alphanumeric string.

#### 4.5.1.2 Vault Encrypted Add Credit Card – EncResAddCC

## Vault Encrypted Add Credit Card transaction object definition

```
EncResAddCC encresaddcc = new EncResAddCC();
```

## **HttpsPostRequest object for Vault Encrypted Add Credit Card transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
```

```
mpgReq.setTransaction(encrestadcc);
```

#### **Vault Encrypted Add Credit Card transaction request fields – Required**

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
encrypted track 2 data	<i>String</i> 40-character numeric	<code>encresaddcc.setEncTrack2(enc_track2);</code>

Variable Name	Type and Limits	Set Method
device type	<p><i>String</i></p> <p>30-character alphanumeric</p> <p>case sensitive</p>	encresaddcc.setDeviceType(device_type);
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	encresaddcc.setCryptType(crypt);

#### Vault Encrypted Add Credit Card transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt; \$ % = ? ^ { } [ ] \          </div>	encresaddcc.setCustId(cust_id);
AVS Information	<p><i>Object</i></p> <p>N/A</p>	encresaddcc.setAvsInfo(avscCheck);
email address	<p><i>String</i></p> <p>30-character alphanumeric</p>	encresaddcc.setEmail(email);
phone number	<p><i>String</i></p> <p>30-character alphanumeric</p>	encresaddcc.setPhone(phone);
note	<p><i>String</i></p> <p>30-character alphanumeric</p>	encresaddcc.setNote(note);
data key format	<p><i>String</i></p> <p>2-character alphanumeric</p>	encresaddcc.setDataKeyFormat(data_key_format);

**Sample Vault Encrypted Add Credit Card**

```

package Canada;
import JavaAPI.*;
public class TestCanadaEncResAddCC
{
    public static void main(String args[])
    {
        String store_id = "moneris";
        String api_token = "hurgle";
        String enc_track2 = "ENCRYPTEDTRACK2DATA";
        String device_type = "idtech_bdk";
        String phone = "55555555555";
        String email = "test.user@moneris.com";
        String note = "my note";
        String cust_id = "customer2";
        String crypt = "7";
        String processing_country_code = "CA";

        AvsInfo avsCheck = new AvsInfo();
        avsCheck.setAvsStreetNumber("212");
        avsCheck.setAvsStreetName("Payton Street");
        avsCheck.setAvsZipcode("M1M1M1");
        EncResAddCC enc_res_add_cc = new EncResAddCC ();
        enc_res_add_cc.setEncTrack2(enc_track2);
        enc_res_add_cc.setDeviceType(device_type);
        enc_res_add_cc.setCryptType(crypt);
        enc_res_add_cc.setCustId(cust_id);
        enc_res_add_cc.setPhone(phone);
        enc_res_add_cc.setEmail(email);
        enc_res_add_cc.setNote(note);
        //enc_res_add_cc.setAvsInfo(avsCheck);
        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(enc_res_add_cc);
        mpgReq.send();

        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("DataKey = " + receipt.getDataKey());
            System.out.println("ResponseCode = " + receipt.getResponseCode());
            System.out.println("Message = " + receipt.getMessage());
            System.out.println("TransDate = " + receipt.getTransDate());
            System.out.println("TransTime = " + receipt.getTransTime());
            System.out.println("Complete = " + receipt.getComplete());
            System.out.println("TimedOut = " + receipt.getTimedOut());
            System.out.println("ResSuccess = " + receipt.getResSuccess());
            System.out.println("PaymentType = " + receipt.getPaymentType() + "\n");
            //Contents of ResolveData
            System.out.println("Cust ID = " + receipt.getResCustomerId());
            System.out.println("Phone = " + receipt.getResPhone());
            System.out.println("Email = " + receipt.getResEmail());
            System.out.println("Note = " + receipt.getResNote());
            System.out.println("MaskedPan = " + receipt.getResMaskedPan());
            System.out.println("Exp Date = " + receipt.getResExpDate());
            System.out.println("Crypt Type = " + receipt.getResCryptType());
            System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
        }
    }
}

```

### Sample Vault Encrypted Add Credit Card

```

System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

#### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

### 4.5.2 Vault Temporary Token Add – ResTempAdd

Creates a new temporary token credit card profile. This transaction requires a duration to be set to indicate how long the temporary token is to be stored for.

During the lifetime of this temporary token, it may be used for any other Vault transaction before it is permanently deleted from the system.

#### Things to Consider:

- The duration, or lifetime, of the temporary token can be set to be a maximum of 15 minutes.

#### Vault Temporary Token Add transaction object definition

```
ResTempAdd resTempAdd = new ResTempAdd();
```

#### HttpsPostRequest object for Vault Temporary Token Add transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resTempAdd);
```

#### Vault Temporary Token Add transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
credit card number	<p><i>String</i></p> <p>max 20-character alpha-numeric</p>	resTempAdd.setPan(pan);
expiry date	<p><i>String</i></p> <p>4-character alphanumeric</p> <p>YYMM</p>	resTempAdd.setExpDate(expiry_date);
duration	<p><i>String</i></p> <p>3-character numeric</p> <p>maximum 900 seconds</p>	resTempAdd.setDuration(duration);
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	resTempAdd.setCryptType(crypt);

### Vault Temporary Token Add transaction request fields – Optional

Variable Name	Type and Limits	Set Method
data key format	<p><i>String</i></p> <p>2-character alphanumeric</p>	resTempAdd.setDataKeyFormat(data_key_format);

#### Sample Vault Temporary Token Add

```

package Canada;
import JavaAPI.*;
public class TestCanadaResTempAdd
{
public static void main(String[] args)
{
String store_id = "store1";
String api_token = "yesguy";
String pan = "5454545454545454";
String expdate = "1901"; //YYMM format
String crypt_type = "7";
String duration = "900";
String processing_country_code = "CA";
boolean status_check = false;
ResTempAdd resTempAdd = new ResTempAdd();
resTempAdd.setPan(pan);
resTempAdd.setExpdate(expdate);
resTempAdd.setDuration(duration);
resTempAdd.setCryptType(crypt_type);
}

```

### Sample Vault Temporary Token Add

```
// resTempAdd.setDataKeyFormat("0U");

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resTempAdd);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("MaskedPan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
}
catch (Exception e)
{
e.printStackTrace();
}
}
```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

#### 4.5.3 Vault Update Credit Card – ResUpdateCC

Updates an existing Vault profile (referencing the profile's unique **data key**) with cardholder information.

Information contained within a credit card profile is updated as indicated by the submitted fields; if any field representing an item of cardholder information is not sent in this request, that item will remain unchanged in the profile.

If the Vault profile is being updated with a new credit card number, then you first need to send a Purchase, Pre-Authorization or Card Verification transaction, with the Credential on File Info object included, before performing Vault Update Credit Card. If the credit card number is not one of the profile items being updated, this step is not required.

**Things to Consider:**

- To update a specific element in the profile, set that element using the corresponding set method
- When updating a credit card number, first send a Purchase, Pre-Authorization, or Card Verification with the Credential on File Info object before sending this transaction; send the issuer ID received in the response in the subsequent Vault Update Credit Card request
- If the credit card number is not one of the profile items being updated, the Credential on File info object is not required

**Vault Update Credit Card transaction object definition**

```
ResUpdateCC resUpdateCC = new ResUpdateCC();
```

**HttpsPostRequest object for Vault Update Credit Card transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resUpdateCC);
```

**Vault Update Credit Card transaction request fields – Required**

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	resUpdateCC.setData (data_key) ;

Optional values that are submitted to the ResUpdateCC object are updated. Unsubmitted optional values (with one exception) remain unchanged. This allows you to change only the fields you want.

If a profile contains AVS information, but a Vault Update Credit Card transaction is submitted without an AVS Info object, the existing AVS Info details are deactivated and the new credit card information is registered without AVS.

**Vault Update Credit Card transaction request fields – Optional**

Variable Name	Type and Limits	Set Method
credit card number	<i>String</i> 20-character alphanumeric	resUpdateCC.setPan (pan) ;

Variable Name	Type and Limits	Set Method
expiry date	<p><i>String</i></p> <p>4-character alphanumeric</p> <p>YYMM</p>	resUpdateCC.setExpDate(expiry_date);
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	resUpdateCC.setCryptType(crypt);
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p>	resUpdateCC.setCustId(cust_id);
	<p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p>	
email address	<p><i>String</i></p> <p>30-character alphanumeric</p>	resUpdateCC.setEmail(email);
phone number	<p><i>String</i></p> <p>30-character alphanumeric</p>	resUpdateCC.setPhone(phone);
note	<p><i>String</i></p> <p>30-character alphanumeric</p>	resUpdateCC.setNote(note);
AVS Information	<p><i>Object</i></p> <p>N/A</p>	resUpdateCC.setAvsInfo(avscCheck);
Credential on File Info cof	<p><i>Object</i></p> <p>N/A</p> <p><b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object</p>	resUpdateCC.setCofInfo(cof);

Variable Name	Type and Limits	Set Method
and Variables.		

### Credential on File Info object request fields

Variable Name	Type and Limits	Set Method
issuer ID	<p><i>String</i></p> <p>15-character alphanumeric variable length</p> <p><b>NOTE:</b> This variable is required for all merchant-initiated transactions following the first one; upon sending the first transaction, the issuer ID value is received in the transaction response and then used in subsequent transaction requests.</p>	<pre>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>

### Sample Vault Update Credit Card

```

package Canada;
import JavaAPI.*;
public class TestCanadaResUpdateCC
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hungle";
String data_key = "vthBJyN1BicbRkdWFZ9flyDP2";
String pan = "4242424242424242";
String expdate = "1901";
String phone = "0000000000";
String email = "bob@smith.com";
String note = "my note";
String cust_id = "customer1";
String crypt_type = "7";
String processing_country_code = "CA";
boolean status_check = false;
AvsInfo avsCheck = new AvsInfo();
avsCheck.setAvsStreetNumber("212");
avsCheck.setAvsStreetName("Payton Street");
avsCheck.setAvsZipCode("M1M1M1");
//Credential on File details
CofInfo cof = new CofInfo();
cof.setIssuerId("139X3130ASCXAS9");

ResUpdateCC resUpdateCC = new ResUpdateCC();
resUpdateCC.setData(data_key);
resUpdateCC.setAvsInfo(avsCheck);
resUpdateCC.setCustId(cust_id);
}

```

### Sample Vault Update Credit Card

```

resUpdateCC.setPan(pan);
resUpdateCC.setExpdate(expdate);
resUpdateCC.setPhone(phone);
resUpdateCC.setEmail(email);
resUpdateCC.setNote(note);
resUpdateCC.setCryptType(crypt_type);
resUpdateCC.setCofInfo(cof);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resUpdateCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("MaskedPan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

#### 4.5.3.1 Vault Encrypted Update CC – EncResUpdateCC

##### Vault Encrypted Update CC transaction object definition

```
EncResUpdateCC enc_res_update_cc = new EncResUpdateCC ();
```

## HttpsPostRequest object for Vault Encrypted Update CC transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(enc_res_update_cc);
```

### Vault Encrypted Update CC transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	enc_res_update_cc.setData(data_key);
encrypted track 2 data	<i>String</i> 40-character numeric	enc_res_update_cc.setEncTrack2(enc_track2);
device type	<i>String</i> 30-character alphanumeric case sensitive	enc_res_update_cc.setDeviceType(device_type);

Optional values that are submitted to the ResUpdateCC object are updated, while unsubmitted optional values (with one exception) remain unchanged. This allows you to change only the fields you want.

The exception is that if you are making changes to the payment type, **all** of the variables in the optional values table below must be submitted.

If you update a profile to a different payment type, it is automatically deactivated and a new credit card profile is created and assigned to the data key. The only values from the prior profile that will remain unchanged are the customer ID, phone number, email address, and note.

**EXAMPLE:** If a profile contains AVS information, but a ResUpdateCC transaction is submitted without an AVSInfo object, the existing AVSInfo details are deactivated and the new credit card information is registered without AVS.

### Vault Encrypted Update CC transaction request fields – Optional

Variable Name	Type and Limits	Set Method
electronic commerce indicator	<i>String</i> 1-character alphanumeric	enc_res_update_cc.setCryptType(crypt);

Variable Name	Type and Limits	Set Method
customer ID	<i>String</i> 50-character alphanumeric	<code>enc_res_update_cc.setCustId(cust_id);</code>
	<b>NOTE:</b> Some special characters are not allowed: <code>&lt;&gt;\$%=?^{}[]\</code>	
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>enc_res_update_cc.setCryptType(crypt);</code>
email address	<i>String</i> 30-character alphanumeric	<code>enc_res_update_cc.setEmail(email);</code>
phone number	<i>String</i> 30-character alphanumeric	<code>enc_res_update_cc.setPhone(phone);</code>
note	<i>String</i> 30-character alphanumeric	<code>enc_res_update_cc.setNote(note);</code>

#### Sample Vault Encrypted Update CC

```

package Canada;
import JavaAPI.*;
public class TestCanadaEncResUpdateCC
{
  public static void main(String args[])
  {
    String store_id = "store1";
    String api_token = "yesguy";
    String data_key = "PHTM1pun7VOaSCFM2xdeP2Sim";
    String enc_track2 = "ENCRYPTEDTRACK2DATA";
    String device_type = "idtech_bdk";
    String phone = "55555555555";
    String email = "test.user@moneris.com";
    String note = "my note";
    String cust_id = "customer2";
    String crypt = "7";
    String processing_country_code = "CA";
    AvsInfo avsinfo = new AvsInfo();
    avsinfo.setAvsStreetNumber("212");
    avsinfo.setAvsStreetName("Smith Street");
    avsinfo.setAvsZipcode("M1M1M1");
    EncResUpdateCC enc_res_update_cc = new EncResUpdateCC ();
    enc_res_update_cc.setDataKey(data_key);
    enc_res_update_cc.setAvsInfo(avsinfo);
  }
}

```

### Sample Vault Encrypted Update CC

```

enc_res_update_cc.setCustId(cust_id);
enc_res_update_cc.setEncTrack2(enc_track2);
enc_res_update_cc.setDeviceType(device_type);
enc_res_update_cc.setPhone(phone);
enc_res_update_cc.setEmail(email);
enc_res_update_cc.setNote(note);
enc_res_update_cc.setCryptType(crypt);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(enc_res_update_cc);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType() + "\n");
//Contents of ResolveData
System.out.println("Cust ID = " + receipt.getResCustId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("MaskedPan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpDate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

#### 4.5.4 Vault Delete – ResDelete

Deletes an existing Vault profile of any type using the unique data key that was assigned when the profile was added.

**NOTE:** Once a profile is deleted, the information that was saved within can no longer be retrieved.

### Vault Delete transaction object definition

```
ResDelete resDelete = new ResDelete (data_key);
```

### HttpsPostRequest object for Vault Delete transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resDelete);
```

### Vault Delete transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	resDelete.setData(data_key);

### Sample Vault Delete

```
package Canada;
import JavaAPI.*;
public class TestCanadaResDelete
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String data_key = "DxwdemrvfnoXO1HhmRikfw3gA";
String processing_country_code = "CA";
boolean status_check = false;
ResDelete resDelete = new ResDelete(data_key);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resDelete);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Complete = " + receipt.getComplete());
}
}
```

### Sample Vault Delete

```

System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
//ResolveData
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("MaskedPan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

## 4.5.5 Vault Lookup Full – ResLookupFull

Verifies what is currently saved under the Vault profile associated with the given data key. The response to this transaction returns the latest active data for that profile.

Unlike Vault Lookup Masked (which returns a masked credit card number), this transaction returns both the masked and unmasked credit card number.

### Vault Lookup Full transaction object definition

```
ResLookupFull resLookupFull = new ResLookupFull(data_key);
```

### HttpsPostRequest object for Vault Lookup Full transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resLookupFull);
```

### Vault Lookup Full transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	resLookupFull.setData(data_key);

### Sample Vault Lookup Full

```

package Canada;
import JavaAPI.*;
public class TestCanadaResLookupFull
{
    public static void main(String[] args)
    {
        String store_id = "store1";
        String api_token = "yesguy";
        String data_key = "pi3ZMZoTTM8pLM9wuwws2KBxw";
        String processing_country_code = "CA";
        boolean status_check = false;
        ResLookupFull resLookupFull = new ResLookupFull(data_key);
        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(resLookupFull);
        mpgReq.setStatusCheck(status_check);
        mpgReq.send();
        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("DataKey = " + receipt.getDataKey());
            System.out.println("ResponseCode = " + receipt.getResponseCode());
            System.out.println("Message = " + receipt.getMessage());
            System.out.println("TransDate = " + receipt.getTransDate());
            System.out.println("TransTime = " + receipt.getTransTime());
            System.out.println("Complete = " + receipt.getComplete());
            System.out.println("TimedOut = " + receipt.getTimedOut());
            System.out.println("ResSuccess = " + receipt.getResSuccess());
            System.out.println("PaymentType = " + receipt.getPaymentType());
            System.out.println("Cust ID = " + receipt.getResCustomerId());
            System.out.println("Phone = " + receipt.getResPhone());
            System.out.println("Email = " + receipt.getResEmail());
            System.out.println("Note = " + receipt.getResNote());
            System.out.println("Pan = " + receipt.getResPan());
            System.out.println("MaskedPan = " + receipt.getResMaskedPan());
            System.out.println("Exp Date = " + receipt.getResExpdate());
            System.out.println("Crypt Type = " + receipt.getResCryptType());
            System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
            System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
            System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
        }
        catch (Exception e)
        {
            e.printStackTrace();
        }
    }
}

```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see [Definitions of Response Fields \(page 563\)](#).

## 4.5.6 Vault Lookup Masked – ResLookupMasked

Verifies what is currently saved under the Vault profile associated with the given data key. The response to this transaction returns the latest active data for that profile.

Unlike Vault Lookup Full (which returns both the masked and the unmasked credit card numbers), this transaction only returns the masked credit card number.

### Vault Lookup Masked transaction object definition

```
ResLookupMasked resLookupMasked = new ResLookupMasked();
```

### HttpsPostRequest object for Vault Lookup Masked transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
```

```
mpgReq.setTransaction(resLookupMasked);
```

### Vault Lookup Masked transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	resLookupMasked.setData(data_key);

### Sample Vault Lookup Masked

```
package Canada;
import JavaAPI.*;
public class TestCanadaResLookupMasked
{
public static void main(String[] args)
{
String store_id = "store1";
String api_token = "yesguy";
String data_key = "pi3ZMZoTTM8pLM9wuwws2KBxw";
String processing_country_code = "CA";
boolean status_check = false;
ResLookupMasked resLookupMasked = new ResLookupMasked();
resLookupMasked.setData(data_key);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resLookupMasked);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
}
}
```

### Sample Vault Lookup Masked

```

System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("MaskedPan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

#### 4.5.7 Vault Get Expiring – ResGetExpiring

Verifies which profiles have credit cards that are expiring during the current and next calendar month.

**EXAMPLE:** if you are processing this transaction on September 30, then it will return all cards that expire(d) in September and October of this year.

When generating a list of profiles with expiring credit cards, only the masked credit card numbers are returned. Can be performed no more than 2 times on any given calendar day.

### Vault Get Expiring transaction object definition

```
ResGetExpiring resGetExpiring = new ResGetExpiring();
```

### HttpsPostRequest object for Vault Get Expiring transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resGetExpiring);
```

### **Vault Get Expiring transaction request fields – Required**

This transaction has no required request fields.

### Sample Vault Get Expiring

```

package Canada;
import JavaAPI.*;
public class TestCanadaResGetExpiring
{
    public static void main(String[] args)
    {
        String store_id = "store1";
        String api_token = "yesguy";
        String processing_country_code = "CA";
        boolean status_check = false;
        ResGetExpiring resGetExpiring = new ResGetExpiring();
        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(resGetExpiring);
        mpgReq.setStatusCheck(status_check);
        mpgReq.send();
        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("DataKey = " + receipt.getDataKey());
            System.out.println("ResponseCode = " + receipt.getResponseCode());
            System.out.println("Message = " + receipt.getMessage());
            System.out.println("TransDate = " + receipt.getTransDate());
            System.out.println("TransTime = " + receipt.getTransTime());
            System.out.println("Complete = " + receipt.getComplete());
            System.out.println("TimedOut = " + receipt.getTimedOut());
            System.out.println("ResSuccess = " + receipt.getResSuccess());
            System.out.println("PaymentType = " + receipt.getPaymentType());
            //ResolveData
            for (int index =0; index < receipt.getExpiredCardCount(); index++)
            {
                System.out.println("\nDataKey = " + index);
                System.out.println("Payment Type = " + receipt.getExpPaymentType(index));
                System.out.println("Cust ID = " + receipt.getExpCustomerId(index));
                System.out.println("Phone = " + receipt.getExpPhone(index));
                System.out.println("Email = " + receipt.getExpEmail(index));
                System.out.println("Note = " + receipt.getExpNote(index));
                System.out.println("Masked Pan = " + receipt.getExpMaskedPan(index));
                System.out.println("Exp Date = " + receipt.getExpExdate(index));
                System.out.println("Crypt Type = " + receipt.getExpCryptType(index));
                System.out.println("Avs Street Number = " + receipt.getExpAvsStreetNumber(index));
                System.out.println("Avs Street Name = " + receipt.getExpAvsStreetName(index));
                System.out.println("Avs Zipcode = " + receipt.getExpAvsZipCode(index));
            }
        }
        catch (Exception e)
        {
            e.printStackTrace();
        }
    }
}

```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

#### 4.5.8 Vault Is Corporate Card - ResIsCorporateCard

Determines whether a profile has a corporate card registered within it.

After sending the transaction, the response field to the Receipt object's `getCorporateCard` method is either true or false depending on whether the associated card is a corporate card.

**NOTE:** This transaction supports both temporary and permanent tokens.

#### Vault Is Corporate Card transaction object definition

```
ResIsCorporatecard resIsCorporatecard = new ResIsCorporatecard();
```

#### HttpsPostRequest object for Vault Is Corporate Card transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resIsCorporateCard);
```

#### Vault Is Corporate Card transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	<code>resIsCorporatecard.setData(data_key);</code>

#### Sample Vault Is Corporate Card

```
package Canada;
import JavaAPI.*;
public class TestCanadaResIsCorporatecard
{
public static void main(String[] args)
{
String store_id = "store1";
String api_token = "yesguy";
String data_key = "eLqsADfwqHDxIpJG9vLnELx01";
String processing_country_code = "CA";
boolean status_check = false;
ResIsCorporatecard resIsCorporatecard = new ResIsCorporatecard();
resIsCorporatecard.setData(data_key);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resIsCorporatecard);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
```

### Sample Vault Is Corporate Card

```

{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("CorporateCard = " + receipt.getCorporateCard());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

#### 4.5.9 Vault Add Token – ResAddToken

Converts a Hosted Tokenization temporary token to a permanent Vault token.

A temporary token is valid for 15 minutes after it is created. This transaction must be performed within that time frame if the token is to be changed to a permanent one for future use.

Using the temporary token, send either a Purchase with Vault, Pre-Authorization with Vault or Card Verification with Vault transaction request including the Credential on File object to get the issuer ID.

#### Vault Add Token transaction object definition

```
ResAddToken resAddToken = new ResAddToken();
```

#### HttpsPostRequest object for Vault Add Token transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(resAddToken);
```

#### Vault Add Token transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
data key	<i>String</i>	resAddToken.setData(data_key);

Variable Name	Type and Limits	Set Method
	25-character alphanumeric	
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>resAddToken.setCryptType(crypt);</code>
Credential on File Info  cof	<i>Object</i> N/A	<code>cof.setCofInfo(cof);</code>
<p><b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.</p>		

### Vault Add Token transaction request fields – Optional

**Table 1: Vault Add Token transaction optional values**

Variable Name	Type and Limits	Set Method
customer ID	<i>String</i> 50-character alphanumeric	<code>resAddToken.setCustId(cust_id);</code>
<p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p>		
AVS Information	<i>Object</i> N/A	<code>resAddToken.setAvsInfo(avscCheck);</code>
email address	<i>String</i> 30-character alphanumeric	<code>resAddToken.setEmail(email);</code>
phone number	<i>String</i> 30-character alphanumeric	<code>resAddToken.setPhone(phone);</code>

Variable Name	Type and Limits	Set Method
note	<i>String</i> 30-character alphanumeric	<code>resAddToken.setNote(note);</code>

data key format	<i>String</i> 2-character alphanumeric	<code>resAddToken.setDataKeyFormat(data_key_format);</code>
-----------------	---	---

### Credential on File Info object request fields

Variable Name	Type and Limits	Set Method
issuer ID	<i>String</i> 15-character alphanumeric variable length	<code>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</code>  <b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File

### Sample Vault Add Token

```
package Canada;
import JavaAPI.*;
public class TestCanadaResAddToken
{
    public static void main(String[] args)
    {
        String store_id = "store1";
        String api_token = "yesguy";
        String data_key = "ot-545454ucx87A5454";
        String expdate = "2001";
        String phone = "0000000000";
        String email = "bob@smith.com";
        String note = "my note";
        String cust_id = "customer1";
        String crypt_type = "7";
        String data_key_format = "0";
        String processing_country_code = "CA";
        boolean status_check = false;
        AvsInfo avsCheck = new AvsInfo();
        avsCheck.setAvsStreetNumber("212");
        avsCheck.setAvsStreetName("Payton Street");
        avsCheck.setAvsZipCode("M1M1M1");

        //Credential on File details
    }
}
```

### Sample Vault Add Token

```

CofInfo cof = new CofInfo();
cof.setIssuerId("139X3130ASCXAS9");
ResAddToken resAddToken = new ResAddToken();
resAddToken.setDataKey(data_key);
resAddToken.setCryptType(crypt_type);
resAddToken.setExpdate(expdate);
resAddToken.setCustId(cust_id);
resAddToken.setPhone(phone);
resAddToken.setEmail(email);
resAddToken.setNote(note);
resAddToken.setAvsInfo(avsc);
resAddToken.setCofInfo(cof);
//resAddToken.setDataKeyFormat(data_key_format); //optional
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resAddToken);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("MaskedPan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

#### 4.5.10 Vault Tokenize Credit Card – ResTokenizeCC


Creates a new credit card profile using the credit card number, expiry date and e-commerce indicator that were submitted in a previous financial transaction. Previous transactions to be tokenized must have included the Credential on File Info object.

The Issuer ID received in the previous transaction response is sent in the Vault Tokenize Credit Card request to reference that this is a stored credential.

Basic transactions that can be tokenized are:

- Purchase
- Pre-Authorization
- Card Verification

The tokenization process is outlined below :



**Figure 1: Tokenize process diagram**

#### Vault Tokenize Credit Card transaction object definition

```
ResTokenizeCC resTokenizeCC = new ResTokenizeCC();
```

#### HttpsPostRequest object for Vault Tokenize Credit Card transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resTokenizeCC);
```

#### Vault Tokenize Credit Card transaction request fields – Required

These mandatory values reference a previously processed credit card financial transaction. The credit card number, expiry date, and e-commerce indicator from the original transaction are registered in the Vault for future financial Vault transactions.

Variable Name	Type and Limits	Set Method
order ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <p>a-Z A-Z 0-9 _ - : . @ spaces</p>	resTokenizeCC.setOrderId(order_id);
transaction number	<p><i>String</i></p> <p>255-character, alpha-numeric, hyphens or underscores</p> <p>variable length</p>	resTokenizeCC.setTxnNumber(txn_number);

### Vault Tokenize Credit Card transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt; &gt; \$ % = ? ^ { } [ ] \          </div>	resTokenizeCC.setCustId(cust_id);
email address	<p><i>String</i></p> <p>30-character alphanumeric</p>	resTokenizeCC.setEmail(email);
phone number	<p><i>String</i></p> <p>30-character alphanumeric</p>	resTokenizeCC.setPhone(phone);
note	<p><i>String</i></p> <p>30-character alphanumeric</p>	resTokenizeCC.setNote(note);
AVS Information	<p><i>Object</i></p> <p>N/A</p>	resTokenizeCC.setAvsInfo(avscCheck);
data key format	<p><i>String</i></p> <p>2-character alphanumeric</p>	resTokenizeCC.setDataKeyFormat(data_key_format);

Variable Name	Type and Limits	Set Method
Credential on File Info cof	<i>Object</i> N/A	cof.setCofInfo(cof);

**NOTE:** This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.

### Credential on File Info object request fields

Variable Name	Type and Limits	Set Method
issuer ID	<i>String</i> 15-character alphanumeric variable length	cof.setIssuerId("VALUE_FOR_ISSUER_ID");  <b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File

Any field that is not set in the tokenize request is not stored with the transaction. That is, Moneris Gateway does not automatically take the optional information that was part of the original transaction.

The ResolveData that is returned in the response fields indicates what values were registered for this profile.

#### Sample Vault Tokenize Credit Card

```
package Canada;
import JavaAPI.*;
public class TestCanadaResTokenizeCC
{
    public static void main(String[] args)
```

**Sample Vault Tokenize Credit Card**

```

{
    String store_id = "moneris";
    String api_token = "hurgle";
    String order_id = "mvt3212954335";
    String txn_number = "199999-0_10";
    String phone = "0000000000";
    String email = "bob@smith.com";
    String note = "my note";
    String cust_id = "customer1";
    String data_key_format = "0";
    String processing_country_code = "CA";
    boolean status_check = false;
    AvsInfo avsCheck = new AvsInfo();
    avsCheck.setAvsStreetNumber("212");
    avsCheck.setAvsStreetName("Payton Street");
    avsCheck.setAvsZipCode("M1M1M1");

    //Credential on File details
    CofInfo cof = new CofInfo();
    cof.setIssuerId("139X3130ASCXAS9");
    ResTokenizeCC resTokenizeCC = new ResTokenizeCC();
    resTokenizeCC.setOrderId(order_id);
    resTokenizeCC.setTxnNumber(txn_number);
    resTokenizeCC.setCustId(cust_id);
    resTokenizeCC.setPhone(phone);
    resTokenizeCC.setEmail(email);
    resTokenizeCC.setNote(note);
    resTokenizeCC.setAvsInfo(avsCheck);
    resTokenizeCC.setCofInfo(cof);
    //resTokenizeCC.setDataKeyFormat(data_key_format); //optional

    HttpsPostRequest mpgReq = new HttpsPostRequest();
    mpgReq.setProcCountryCode(processing_country_code);
    mpgReq.setTestMode(true); //false for production transactions
    mpgReq.setstoreId(store_id);
    mpgReq.setApiToken(api_token);
    mpgReq.setTransaction(resTokenizeCC);
    mpgReq.setStatusCheck(status_check);
    mpgReq.send();
    try
    {
        Receipt receipt = mpgReq.getReceipt();
        System.out.println("DataKey = " + receipt.getDataKey());
        System.out.println("ResponseCode = " + receipt.getResponseCode());
        System.out.println("Message = " + receipt.getMessage());
        System.out.println("TransDate = " + receipt.getTransDate());
        System.out.println("TransTime = " + receipt.getTransTime());
        System.out.println("Complete = " + receipt.getComplete());
        System.out.println("TimedOut = " + receipt.getTimedOut());
        System.out.println("ResSuccess = " + receipt.getResSuccess());
        System.out.println("PaymentType = " + receipt.getPaymentType());
        //ResolveData
        System.out.println("Cust ID = " + receipt.getResCustId());
        System.out.println("Phone = " + receipt.getResPhone());
        System.out.println("Email = " + receipt.getResEmail());
        System.out.println("Note = " + receipt.getResNote());
        System.out.println("MaskedPan = " + receipt.getResMaskedPan());
        System.out.println("Exp Date = " + receipt.getResExpdate());
        System.out.println("Crypt Type = " + receipt.getResCryptType());
    }
}

```

### Sample Vault Tokenize Credit Card

```

System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

#### Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

## 4.6 Vault Financial Transactions

After a financial transaction is complete, the response fields indicate all the values that are currently saved under the profile that was used.

### 4.6.1 Customer ID Changes

Some financial transactions take the customer ID as an optional value. The customer ID may or may not already be in the Vault profile when the transaction is sent. Therefore, it is possible to change the value of the customer ID by performing a financial transaction.

The table below shows what the customer ID will be in the response field after a financial transaction is performed.

**Table 2: Customer ID use in response fields**

Already in profile?	Passed in?	Version used in response
No	No	Customer ID not used in transaction
No	Yes	Passed in
Yes	No	Profile
Yes	Yes	Passed in

## 4.6.2 Purchase with Vault – ResPurchaseCC

**NOTE:** This transaction supports both temporary and permanent tokens.

### Purchase with Vault transaction object definition

```
ResPurchaseCC resPurchaseCC = new ResPurchaseCC();
```

### HttpsPostRequest object for Purchase with Vault transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resPurchaseCC);
```

### Purchase with Vault transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	resPurchaseCC.setData_key();
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	resPurchaseCC.setOrderId(order_id);
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	resPurchaseCC.setAmount(amount);
<b>EXAMPLE: 1234567.89</b>		
electronic commerce indicator	<i>String</i> 1-character alphanumeric	resPurchaseCC.setCryptType(crypt);
Credential on File Info	<i>Object</i>	cof.setCofInfo(cof);

Variable Name	Type and Limits	Set Method
cof	N/A	

**NOTE:** This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.

### Purchase with Vault transaction request fields – Optional

Variable Name	Type and Limits	Set Method
status check	<i>Boolean</i> true/false	mpgReq.setStatusCheck(status_check);
expiry date	<i>String</i> 4-character numeric YYMM format.  (Note that this is reversed from the date displayed on the card, which is MMYY)	resPurchaseCC.setExpDate(expiry_date);
customer ID	<i>String</i> 50-character alphanumeric  <b>NOTE:</b> Some special characters are not allowed: < > \$ % = ? ^ { } [ ] \	resPurchaseCC.setCustId(cust_id);
dynamic descriptor	<i>String</i> 20-character alphanumeric  total of 22 characters including your merchant name and separator	resPurchaseCC.setDynamicDescriptor(dynamic_descriptor);

Variable Name	Type and Limits	Set Method
	<p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p>	
Customer Information	<i>Object</i> N/A	resPurchaseCC.setCustInfo(customer);
AVS Information	<i>Object</i> N/A	resPurchaseCC.setAvsInfo(avsCheck);
CVD Information	<i>Object</i> N/A  <p><b>NOTE:</b> When storing credentials on the initial transaction, the CVD object must be sent; for subsequent transactions using stored credentials, CVD can be sent with cardholder-initiated transactions only—<b>merchants must not store CVD information.</b></p>	resPurchaseCC.setCvdInfo(cvdCheck);
Recurring Billing	<i>Object</i> N/A	resPurchaseCC.setRecurInfo(recurInfo);
Installment Info  For fields in this object, see 9.6 Installment Info Object  <p><b>NOTE:</b> Do not send the Installment Info object on any transaction that is not intended to offer Installments by Visa functionality; doing so may cause the transaction to fail.</p>	<i>Object</i> N/A	resPurchaseCC.setInstallmentInfo(installmentInfo);

## Credential on File Info object request fields

Variable Name	Type and Limits	
issuer ID	<p><i>String</i></p> <p>15-character alphanumeric variable length</p> <p><b>NOTE:</b> This variable is required for all merchant-initiated transactions following the first one; upon sending the first transaction, the issuer ID value is received in the transaction response and then used in subsequent transaction requests.</p>	<pre>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
payment indicator	<p><i>String</i></p> <p>1-character alphabetic</p> <p><b>NOTE:</b> In Credential on File transactions where the request field e-commerce indicator is also being sent, the acceptable values for e-commerce indicator are dependent on the value sent for payment indicator; see request field definitions for more information.</p>	<pre>cof.setPaymentIndicator("PAYMENT_INDICATOR_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
payment information	<p><i>String</i></p> <p>1-character numeric</p>	<pre>cof.setPaymentInformation("PAYMENT_INFO_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>

### Sample Purchase with Vault

```
package Canada;
import JavaAPI.*;
public class TestCanadaResPurchaseCC
{
public static void main(String[] args)
{
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String store_id = "store5";
```

### Sample Purchase with Vault

```

String api_token = "yesguy";
String data_key = "800XGiwxgvfbZngigVFeld9d2";
String amount = "1.00";
String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile
will be used
String crypt_type = "1";
String descriptor = "my descriptor";
String processing_country_code = "CA";
String expdate = "1512"; //For Temp Token
boolean status_check = false;

ResPurchaseCC resPurchaseCC = new ResPurchaseCC();
resPurchaseCC.setDataKey(data_key);
resPurchaseCC.setOrderId(order_id);
resPurchaseCC.setCustId(cust_id);
resPurchaseCC.setAmount(amount);
resPurchaseCC.setCryptType(crypt_type);
//resPurchaseCC.setDynamicDescriptor(descriptor);
resPurchaseCC.setExpDate(expdate); //Temp Tokens only

//NT Response Option
boolean get_nt_response = true;
resPurchaseCC.setGetNtResponse(get_nt_response);

//optional - Installment Info
// InstallmentInfo installmentInfo = new InstallmentInfo();
// installmentInfo.setPlanId("ae859ef1-eb91-b708-8b80-1dd481746401");
// installmentInfo.setPlanIdRef("0000000065");
// installmentInfo.setTacVersion("2");
// resPurchaseCC.setInstallmentInfo(installmentInfo);

//Mandatory - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");
resPurchaseCC.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resPurchaseCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
}

```

## Sample Purchase with Vault

```

System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("Cust ID = " + receipt.getResCustId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());

if(get_nt_response) {
System.out.println("\nNTResponseCode = " + receipt.getNTResponseCode());
System.out.println("NTMessage = " + receipt.getNTMessage());
System.out.println("NTUsed = " + receipt.getNTUsed());
System.out.println("NTTokenBin = " + receipt.getNTTokenBin());
System.out.println("NTTokenLast4 = " + receipt.getNTTokenLast4());
System.out.println("NTTokenExpDate = " + receipt.getNTTokenExpDate());
}

// InstallmentResults installmentResults = receipt.getInstallmentResults();
// System.out.println("\nPlanId = " + installmentResults.getPlanId() +"\\n");
// System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
// System.out.println("TacVersion = " + installmentResults.getTacVersion());
// System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
// System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
// System.out.println("PlanResponse = " + installmentResults.getPlanResponse());
}

catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

## Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see [Definitions of Response Fields](#) (page 563).

#### 4.6.3 Pre-Authorization with Vault – ResPreauthCC

**NOTE:** This transaction supports both temporary and permanent tokens.

## Pre-Authorization with Vault transaction object definition

```
ResPreauthCC resPreauthCC = new ResPreauthCC();
```

## HttpsPostRequest object for Pre-Authorization with Vault transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resPreauthCC);
```

## Pre-Authorization with Vault transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<p><i>String</i></p> <p>25-character alphanumeric</p>	resPreauthCC.setData(data_key);
order ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <p>a-Z A-Z 0-9 _ - : @ spaces</p>	resPreauthCC.setOrderId(order_id);
amount	<p><i>String</i></p> <p>10-character decimal</p> <p>Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point</p> <p><b>EXAMPLE: 1234567.89</b></p>	resPreauthCC.setAmount(amount);
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	resPreauthCC.setCryptType(crypt);
Credential on File Info cof	<p><i>Object</i></p> <p>N/A</p> <p><b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Cre-</p>	resPreauthCC.setCofInfo(cof);

Variable Name	Type and Limits	Set Method
Pre-Authorization on File Info Object and Variables.		

### Pre-Authorization with Vault transaction request fields – Optional

Value	Limits	Set method
status check	<i>Boolean</i> true/false	<code>mpgReq.setStatusCheck(status_check);</code>
dynamic descriptor	<p><i>String</i> 20-character alphanumeric total of 22 characters including your merchant name and separator</p> <p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p>	<code>resPreauthCC.setDynamicDescriptor(dynamic_descriptor);</code>
expiry date	<p><i>String</i> 4-character alphanumeric YYMM</p> <p><b>NOTE:</b> This field is required if referencing a temporary token in Installments by Visa</p>	<code>resPreauthCC.setExpDate(expiry_date);</code>
customer ID	<p><i>String</i> 50-character alphanumeric</p> <p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p>	<code>resPreauthCC.setCustId(cust_id);</code>
final authorization	<p><i>String</i> true/false</p> <p><b>NOTE:</b> Applies to Mastercard</p>	<code>resPreauthCC.setFinalAuth("true");</code>

Value	Limits	Set method
transactions only		
Customer Information	<i>Object</i> N/A	<code>resPreauthCC.setCustInfo(customer);</code>
AVS Information	<i>Object</i> N/A	<code>resPreauthCC.setAvsInfo(avsCheck);</code>
CVD Information  <b>NOTE:</b> When storing credentials on the initial transaction, the CVD object must be sent; for subsequent transactions using stored credentials, CVD can be sent with cardholder-initiated transactions only—merchants must not store CVD information.	<i>Object</i> N/A	<code>resPreauthCC.setCvdInfo(cvdCheck);</code>
Installment Info  For fields in this object, see 9.6 Installment Info Object  <b>NOTE:</b> Do not send the Installment Info object on any transaction that is not intended to offer Installments by Visa functionality; doing so may cause the transaction to fail.	<i>Object</i> N/A	<code>resPreauthCC.setInstallmentInfo(installmentInfo);</code>

### Credential on File Info object request fields

Variable Name	Type and Limits	
issuer ID  <b>NOTE:</b> This variable is required for all merchant-initiated transactions.	<i>String</i> 15-character alphanumeric variable length	<code>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</code> <b>NOTE:</b> For a list and explanation of the pos-

Variable Name	Type and Limits	
<p>tiated transactions following the first one; upon sending the first transaction, the issuer ID value is received in the transaction response and then used in subsequent transaction requests.</p>		<p>sible values to send for this variable, see <a href="#">Definition of Request Fields – Credential on File</a></p>
<p><b>payment indicator</b></p> <p><b>NOTE:</b> In Credential on File transactions where the request field e-commerce indicator is also being sent, the acceptable values for e-commerce indicator are dependent on the value sent for payment indicator; see request field definitions for more information.</p>	<p><i>String</i> 1-character alphabetic</p>	<pre>cof.setPaymentIndicator("PAYMENT_INDICATOR_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see <a href="#">Definition of Request Fields – Credential on File</a></p>
<p><b>payment information</b></p>	<p><i>String</i> 1-character numeric</p>	<pre>cof.setPaymentInformation("PAYMENT_INFO_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see <a href="#">Definition of Request Fields – Credential on File</a></p>

### Sample Pre-Authorization with Vault

```
package Canada;
import JavaAPI.*;
public class TestCanadaResPreauthCC
{
public static void main(String[] args)
{
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String store_id = "store5";
String api_token = "yesguy";
String data_key = "rS7DbroQHJmJxdBfxFXiauQc4";
String amount = "1.00";
String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile will be used
String crypt_type = "1";
String dynamic_descriptor = "my descriptor";
```

### Sample Pre-Authorization with Vault

```

String processing_country_code = "CA";
String expdate = "1712"; //For Temp Token
boolean status_check = false;

ResPreauthCC resPreauthCC = new ResPreauthCC();
resPreauthCC.setDataKey(data_key);
resPreauthCC.setOrderId(order_id);
resPreauthCC.setCustId(cust_id);
resPreauthCC.setAmount(amount);
resPreauthCC.setCryptType(crypt_type);
resPreauthCC.setInstallmentInfo(installmentInfo);
//resPreauthCC.setDynamicDescriptor(dynamic_descriptor);
//resPreauthCC.setExpDate(expdate); //Temp Tokens only

//NT Response Option
boolean get_nt_response = true;
resPreauthCC.setGetNtResponse(get_nt_response);

//optional - Installment Info
// InstallmentInfo installmentInfo = new InstallmentInfo();
// installmentInfo.setPlanId("ae859ef1-eb91-b708-8b80-1dd481746401");
// installmentInfo.setPlanIdRef("0000000065");
// installmentInfo.setTacVersion("2");
// resPreauthCC.setInstallmentInfo(installmentInfo);

//Mandatory - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

resPreauthCC.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resPreauthCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
}

```

## Sample Pre-Authorization with Vault

```
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("IsCorporate = " + receipt.getCorporateCard());
System.out.println("Cust ID = " + receipt.getResCustId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());

if(get_nt_response) {
    System.out.println("\nNTResponseCode = " + receipt.getNTResponseCode());
    System.out.println("NTMessage = " + receipt.getNTMessage());
    System.out.println("NTUsed = " + receipt.getNTUsed());
    System.out.println("NTTokenBin = " + receipt.getNTTokenBin());
    System.out.println("NTTokenLast4 = " + receipt.getNTTokenLast4());
    System.out.println("NTTokenExpDate = " + receipt.getNTTokenExpDate());
}

// InstallmentResults installmentResults = receipt.getInstallmentResults();
// System.out.println("\nPlanId = " + installmentResults.getPlanId());
// System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
// System.out.println("TacVersion = " + installmentResults.getTacVersion());
// System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
// System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
// System.out.println("PlanResponse = " + installmentResults.getPlanResponse());
}

catch (Exception e)
{
e.printStackTrace();
}
}
}
```

## Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see [Definitions of Response Fields](#) (page 563).

#### 4.6.4 Vault Independent Refund – ResIndRefundCC

**NOTE:** This transaction supports both temporary and permanent tokens.

## Vault Independent Refund transaction object definition

```
ResIndRefundCC resIndRefundCC = new ResIndRefundCC();
```

### **HttpsPostRequest object for Vault Independent Refund transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resIndRefundCC);
```

#### **Vault Independent Refund transaction values**

For a full description of mandatory and optional values, see [Appendix A Definition of Request Fields](#).

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	resIndRefundCC.setData(data_key);
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	resIndRefundCC.setOrderId(order_id);
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	resIndRefundCC.setAmount(amount);
	<b>EXAMPLE:</b> 1234567.89	
electronic commerce indicator	<i>String</i> 1-character alphanumeric	resIndRefundCC.setCryptType(crypt);

#### **Vault Independent Refund transaction request fields – Optional**

Value	Limits	Set method
customer ID	<i>String</i> 50-character alphanumeric	resIndRefundCC.setCustId(cust_id);

**NOTE:**  
 Some special characters are not allowed:  
 < > \$ % = ? ^ { } [ ] \

Value	Limits	Set method
expiry date	<i>String</i> 4-character alphanumeric YYMM	<code>resIndRefundCC.setExpDate(expiry_date);</code>
status check	<i>Boolean</i> true/false	<code>mpgReq.setStatusCheck(status_check);</code>
dynamic descriptor	<i>String</i> 20-character alphanumeric total of 22 characters including your merchant name and separator	<code>resIndRefundCC.setDynamicDescriptor(dynamic_descriptor);</code>

**NOTE:**  
 Some special characters are not allowed:  
 <>\$%=?^{}[]\

### Sample Vault Independent Refund

```

package Canada;
import JavaAPI.*;
public class TestCanadaResIndRefundCC
{
  public static void main(String[] args)
  {
    java.util.Date createDate = new java.util.Date();
    String order_id = "Test"+createDate.getTime();
    String store_id = "moneris";
    String api_token = "hurgle";
    String data_key = "eRNR6lU1RD6jmgS9OPqmmBVrk";
    String amount = "1.00";
    String cust_id = "customer1";
    String crypt_type = "1";
    String processing_country_code = "CA";
    boolean status_check = false;

    ResIndRefundCC resIndRefundCC = new ResIndRefundCC();
    resIndRefundCC.setOrderId(order_id);
    resIndRefundCC.setCustId(cust_id);
    resIndRefundCC.setAmount(amount);
    resIndRefundCC.setCryptType(crypt_type);
    resIndRefundCC.setData(data_key);
  }
}

```

## **Sample Vault Independent Refund**

```

//NT Response Option
boolean get_nt_response = true;
resIndRefundCC.setGetNtResponse(get_nt_response

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resIndRefundCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("Cust ID = " + receipt.getResCustId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExppdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());

if(get_nt_response) {
System.out.println("\nNTResponseCode = " + receipt.getNTResponseCode());
System.out.println("NTMessage = " + receipt.getNTMessage());
System.out.println("NTUsed = " + receipt.getNTUsed());
System.out.println("NTTokenBin = " + receipt.getNTTokenBin());
System.out.println("NTTokenLast4 = " + receipt.getNTTokenLast4());
System.out.println("NTTokenExpDate = " + receipt.getNTTokenExpDate());
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## Vault response fields

For a list and explanation of (Receipt object) response fields that are available after sending this Vault transaction, see Definitions of Response Fields (page 563).

### 4.6.5 Force Post with Vault – ResForcePostCC

**NOTE:** This transaction supports both temporary and permanent tokens.

#### Force Post with Vault transaction object definition

```
ResForcePostCC resForcePostCC = new ResForcePostCC();
```

#### HttpsPostRequest object for Force Post with Vault transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resForcePostCC);
```

#### Force Post with Vault transaction request fields – Required

Variable Name	Type and Limits	Set Method
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	resForcePostCC.setAmount(amount);
	<b>EXAMPLE: 1234567.89</b>	
data key	<i>String</i> 25-character alphanumeric	resForcePostCC.setData(data_key);
authorization code	<i>String</i> 8-character alphanumeric	resForcePostCC.setAuthCode(auth_code);
electronic commerce indicator	<i>String</i> 1-character alphanumeric	resForcePostCC.setCryptType(crypt);

## Force Post with Vault transaction object definition

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:  <code>&lt;&gt;\$%=?^{}[]\</code> </div>	<code>resForcePostCC.setCustId(cust_id);</code>
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:  <code>&lt;&gt;\$%=?^{}[]\</code> </div>	<code>resForcePostCC.setDynamicDescriptor(dynamic_descriptor);</code>
status check	<p><i>Boolean</i></p> <p>true/false</p>	<code>mpgReq.setStatusCheck(status_check);</code>

### Sample Force Post with Vault

```

package Canada;
import JavaAPI.*;
public class TestCanadaResForcePostCC
{
public static void main(String[] args)
{
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String store_id = "store5";
String api_token = "yesguy";
String data_key = "uroyVNSxzjk5hHoT0kpQDBCw4";
String amount = "1.00";
String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile
will be used
String crypt_type = "7";

```

### Sample Force Post with Vault

```

String auth_code = "124424";
String descriptor = "my descriptor";
String processing_country_code = "CA";
boolean status_check = false;

ResForcePostCC resForcePostCC = new ResForcePostCC();
resForcePostCC.setOrderId(order_id);
resForcePostCC.setCustId(cust_id);
resForcePostCC.setAmount(amount);
resForcePostCC.setDataKey(data_key);
resForcePostCC.setAuthCode(auth_code);
resForcePostCC.setCryptType(crypt_type);
resForcePostCC.setDynamicDescriptor(descriptor);

//NT Response Option
boolean get_nt_response = true;
resForcePostCC.setGetNtResponse(get_nt_response);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resForcePostCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("Cust ID = " + receipt.getResCustId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());

if(get_nt_response) {
}
}

```

### Sample Force Post with Vault

```

System.out.println("\nNTResponseCode = " + receipt.getNTResponseCode());
System.out.println("NTMessage = " + receipt.getNTMessage());
System.out.println("NTUsed = " + receipt.getNTUsed());
System.out.println("NTTokenBin = " + receipt.getNTTokenBin());
System.out.println("NTTokenLast4 = " + receipt.getNTTokenLast4());
System.out.println("NTTokenExpDate = " + receipt.getNTTokenExpDate());
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 4.6.6 Card Verification with Vault – ResCardVerificationCC

**NOTE:** This transaction supports both temporary and permanent tokens.

### Things to Consider:

- This transaction type only applies to Visa, Mastercard, American Express and Discover transactions
- The card number and expiry date for this transaction are passed using a token, as represented by the data key value
- When using a temporary token (e.g., such as with Hosted Tokenization) **and** you intend to store the cardholder credentials, this transaction must be run prior to running the Vault Add Token transaction

### Card Verification with Vault object definition

```
ResCardVerificationCC resCardVerificationCC = new ResCardVerificationCC();
```

### HttpsPostRequest object for Card Verification with Vault transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resCardVerificationCC);
```

### Card Verification with Vault transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	<code>resCardVerificationCC .setOrderId(order_id);</code>
data key	<i>String</i> 25-character alphanumeric	<code>resCardVerificationCC .setDataKeyFormat(data_key_format);</code>
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>resCardVerificationCC .setCryptType(crypt);</code>
AVS Information	<i>Object</i> N/A	<code>resCardVerificationCC .setAvsInfo(avscCheck);</code>
CVD Information	<i>Object</i> N/A	<code>resCardVerificationCC . setCvdInfo(cvdCheck);</code>
Credential on File Info	<i>Object</i>	<code>resCardVerificationCC .setCofInfo(cof);</code>
cof	N/A	
	<b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.	

## Credential on File Info object request fields

Variable Name	Type and Limits	
issuer ID	<p><i>String</i></p> <p>15-character alphanumeric variable length</p> <p><b>NOTE:</b> This variable is required for all merchant-initiated transactions following the first one; upon sending the first transaction, the issuer ID value is received in the transaction response and then used in subsequent transaction requests.</p>	<pre>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
payment indicator	<p><i>String</i></p> <p>1-character alphabetic</p> <p><b>NOTE:</b> In Credential on File transactions where the request field e-commerce indicator is also being sent, the acceptable values for e-commerce indicator are dependent on the value sent for payment indicator; see request field definitions for more information.</p>	<pre>cof.setPaymentIndicator("PAYMENT_INDICATOR_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
payment information	<p><i>String</i></p> <p>1-character numeric</p>	<pre>cof.setPaymentInformation("PAYMENT_INFO_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>

### Sample Card Verification with Vault

```
package Canada;
import java.io.*;
import JavaAPI.*;
public class TestCanadaResCardVerificationCC
{
public static void main(String args[]) throws IOException
{
String store_id = "store5";
String api_token = "yesguy";
```

### Sample Card Verification with Vault

```

String data_key = "AoG4zAFzlFFFxcVmzWAZVQuhj";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String crypt_type = "7";
String processing_country_code = "CA";
boolean status_check = false;

//***** Efraud Variables *****/
AvsInfo avs = new AvsInfo ();
avs.setAvsStreetName("test ave");
avs.setAvsStreetNumber("123");
avs.setAvsZipcode("123456");
CvdInfo cvd = new CvdInfo ("1", "099");
//***** Transaction Object *****/
ResCardVerificationCC resCardVerificationCC = new ResCardVerificationCC();
resCardVerificationCC.setDataKey(data_key);
resCardVerificationCC.setOrderId(order_id);
resCardVerificationCC.setCryptType(crypt_type);
resCardVerificationCC.setAvsInfo(avs);
resCardVerificationCC.setCvdInfo(cvd);

//NT Response Option
boolean get_nt_response = true;
resCardVerificationCC.setGetNtResponse(get_nt_response);

//resCardVerificationCC.setExdate("1412"); //For Temp Tokens only

//Mandatory - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

resCardVerificationCC.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resCardVerificationCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
//***** Receipt Object *****/
try
{
Receipt resreceipt = mpgReq.getReceipt();
System.out.println("DataKey = " + resreceipt.getDataKey());
System.out.println("ReceiptId = " + resreceipt.getReceiptId());
System.out.println("ReferenceNum = " + resreceipt.getReferenceNum());
System.out.println("ResponseCode = " + resreceipt.getResponseCode());
System.out.println("AuthCode = " + resreceipt.getAuthCode());
System.out.println("ISO = " + resreceipt.getISO());
System.out.println("Message = " + resreceipt.getMessage());
System.out.println("TransDate = " + resreceipt.getTransDate());
System.out.println("TransTime = " + resreceipt.getTransTime());
System.out.println("TransType = " + resreceipt.getTransType());
System.out.println("Complete = " + resreceipt.getComplete());
System.out.println("TransAmount = " + resreceipt.getTransAmount());
}

```

### Sample Card Verification with Vault

```

System.out.println("CardType = " + resreceipt.getCardType());
System.out.println("TxnNumber = " + resreceipt.getTxnNumber());
System.out.println("TimedOut = " + resreceipt.getTimedOut());
System.out.println("ResSuccess = " + resreceipt.getResSuccess());
System.out.println("PaymentType = " + resreceipt.getPaymentType() + "\n");
System.out.println("IssuerId = " + resreceipt.getIssuerId());
System.out.println("SourcePanLast4 = " + resreceipt.getSourcePanLast4());
System.out.println();

//Contents of ResolveData
System.out.println("Cust ID = " + resreceipt.getResCustomerId());
System.out.println("Phone = " + resreceipt.getResPhone());
System.out.println("Email = " + resreceipt.getResEmail());
System.out.println("Note = " + resreceipt.getResNote());
System.out.println("Masked Pan = " + resreceipt.getResMaskedPan());
System.out.println("Exp Date = " + resreceipt.getResExpdate());
System.out.println("Crypt Type = " + resreceipt.getResCryptType());
System.out.println("Avs Street Number = " + resreceipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + resreceipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + resreceipt.getResAvsZipcode());

if(get_nt_response) {
    System.out.println("\nNTResponseCode = " + resreceipt.getNTResponseCode());
    System.out.println("NTMessage = " + resreceipt.getNTMessage());
    System.out.println("NTUsed = " + resreceipt.getNTUsed());
    System.out.println("NTTokenBin = " + resreceipt.getNTTokenBin());
    System.out.println("NTTokenLast4 = " + resreceipt.getNTTokenLast4());
    System.out.println("NTTokenExpDate = " + resreceipt.getNTTokenExpDate());
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
} // end TestResCardVerificationCC

```

## 4.7 Hosted Tokenization

Moneris Hosted Tokenization is a solution for online e-commerce merchants who do not want to handle credit card numbers directly on their websites, yet want the ability to fully customize their check-out web page appearance.

When an hosted tokenization transaction is initiated, the Moneris Gateway displays (on the merchant's behalf) a single text box on the merchant's checkout page. The cardholder can then securely enter the credit card information into the text box. Upon submission of the payment information on the checkout page, Moneris Gateway returns a temporary token representing the credit card number to the merchant. This is then used in an API call to process a financial transaction directly with Moneris to charge the card. After receiving a response to the financial transaction, the merchant generates a receipt and allows the cardholder to continue with online shopping.

For more details on how to implement the Moneris Hosted Tokenization feature, see the Hosted Solutions Integration Guide. The guide can be downloaded from the Moneris Developer Portal at

[developer.moneris.com](https://developer.moneris.com)

# 5 INTERAC® Online Payment

- 5.1 About INTERAC® Online Payment Transactions
- 5.2 Other Documents and References
- 5.3 Website and Certification Requirements
- 5.4 Transaction Flow for INTERAC® Online Payment
- 5.5 Sending an INTERAC® Online Payment Purchase Transaction
- 5.6 INTERAC® Online Payment Purchase
- 5.7 INTERAC® Online Payment Refund
- 5.8 INTERAC® Online Payment Field Definitions

## 5.1 About INTERAC® Online Payment Transactions

The INTERAC® Online Payment method offers cardholders the ability to pay using online banking. This payment method can be combined with the Moneris GatewayJava API solution to allow online payments using credit and debit cards.

INTERAC® Online Payment transactions via the Java API require two steps:

1. The cardholder guarantees the funds for the purchase amount using their online banking process.
2. The merchant confirms the payment by sending an INTERAC® Online Payment purchase request to Moneris using the Java API.

Any of the transaction objects that are defined in this section can be passed to the `HttpsPostRequest` connection object defined in Section 17.5 Processing a Transaction.

INTERAC® Online Payment transactions are available to **Canadian integrations** only.

## 5.2 Other Documents and References

INTERAC® Online Payment is offered by Acxsys Corporation, which is also a licensed user of the *Interac* logo. Refer to the following documentation and websites for additional details.

### INTERAC® Online Payment Merchant Guideline

Visit the Moneris Developer Portal (<https://developer.moneris.com>) to access the latest documentation and downloads.

This details the requirements for each page consumers visit on a typical INTERAC® Online Payment merchant website. It also details the requirements that can be displayed on any page (that is, requirements that are not page-specific).

## Logos

Visit the Moneris Developer Portal (<https://developer.moneris.com>) to access the logos and downloads.

## 5.3 Website and Certification Requirements

### 5.3.1 Things to provide to Moneris

Refer to the Merchant Guidelines referenced in Section 5.2 for instructions on proper use of logos and the term "INTERAC® Online Payment". You need to provide Moneris with the following registration information:

- Merchant logo to be displayed on the INTERAC® Online Payment Gateway page
  - In both French and English
  - 120 × 30 pixels
  - Only PNG format is supported.
- Merchant business name
  - In both English and French
  - Maximum 30 characters.
- List of all referrer URLs. That is, URLs from which the customer may be redirected to the INTERAC® Online Payment gateway.
- List of all URLs that may appear in the IDEBIT\_FUNDEDURL field of the https form POST to the INTERAC® Online Payment Gateway.
- List of all URLs that may appear in the IDEBIT\_NOTFUNDEDURL field of the https form POST to the INTERAC® Online Payment Gateway.

Note that if your test and production environments are different, provide the above information for both environments.

### 5.3.2 Certification process

#### Test cases

All independent merchants and third-party service/shopping cart providers must pass the certification process by conducting all the test cases outlined in Appendix E (page 605) and "Third-Party Service Provider Checklists for INTERAC® Online Payment Certification Testing" on page 609 respectively. This is required after you have completed all of your testing.

Any major changes to your website after certification (with respect to the INTERAC® Online Payment functionality) require the site to be re-certified by completing the test cases again.

Appendix H (page 617) is the Certification Test Case Detail showing all the information and requirements for each test case.

#### Screenshots

You must provide Moneris with screenshots of your check-out process showing examples of approved and declined transactions using the INTERAC® Online Payment service.

#### Checklists

To consistently portray the INTERAC Online service as a secure payment option, you must complete the respective Merchant Requirement checklist in Appendix E (page 605) or Appendix F (page 609) accordingly. The detailed descriptions of the requirements in these checklists can be found in the INTERAC® Online Payment Merchant Guidelines document referred to in 5.2 (page 124). If any item does not apply, mark it as "N/A".

After completion, fax or email the results to the Moneris Integration Support help desk for review before implementing the change into the production environment.

### 5.3.3 Client Requirements

#### Checklists

As a merchant using an INTERAC® Online Payment-certified third-party solution, your clients must complete the Merchant Checklists for INTERAC® Online Payment Certification form (Appendix G, page 614). They will **not** be required to complete any of the test cases.

Your clients must also complete the Merchant Requirement checklist (Appendix G, page 614). Ensure that your product documentation properly instructs your clients to fax or email the results to the Moneris Integration Support helpdesk for registration purposes.

#### Screenshots

Your clients must provide Moneris with screenshots of their check-out process that show examples of approved and declined transactions using INTERAC® Online Payment.


### 5.3.4 Delays

Note that merchants that fall under the following category codes listed in Table 3 may experience delays in the certification or registration process of up to 7 days.

**Table 3: Category codes that might introduce certification/registration delays**

Category code	Merchant type/name
4812	Telecommunication equipment including telephone sales
4829	Money transfer—merchant
5045	Computers, computer peripheral equipment, software
5732	Electronic sales
6012	Financial institution—merchandise and services
6051	Quasi cash—merchant
6530	Remote stored value load—merchant
6531	Payment service provider—money transfer for a purchase
6533	Payment service provider—merchant—payment transaction

## 5.4 Transaction Flow for INTERAC® Online Payment



**Figure 2: INTERAC® Online Payment transaction flow diagram**

1. Customer selects the INTERAC® Online Payment option on the merchant's web store.
2. Merchant redirects the customer to the IOP gateway to select a financial institution (issuer) of choice. This step involves form-posting the following required variables over the HTTPS protocol:

- IDEBIT\_MERCHNUM
  - IDEBIT\_AMOUNT<sup>1</sup>
  - IDEBIT\_CURRENCY
  - IDEBIT\_FUNDEDURL
  - IDEBIT\_NOTFUNDEDURL
  - IDEBIT\_MERCHLANG
  - IDEBIT\_VERSIONIDEBIT\_TERMID - optional
  - IDEBIT\_INVOICE - optional
  - IDEBIT\_MERCHDATA - optional
3. Customer selects an issuer, and is directed to the online banking site. Customer completes the online banking process and guarantees the funds for the purchase.
4. Depending on the results of step 5.4, the issuer re-directs the customer through the IOP Gateway to either the merchant's non-funded URL (4a) or funded URL (4b). Both URLs can appear on the same page. The funded/non-funded URLs must validate the variables posted back according to 5.8 (page 135) before continuing.
- 5.4 shows the variables that are posted back in the re-direction.
- If the customer is directed to the non-funded URL, return to step 5.4 and ask for another means of payment.
- If the customer is directed to the funded URL, continue to the next step.
5. Merchant sends an INTERAC® Online Payment purchase request to Moneris Gateway while displaying the "Please wait...." message to the customer. This should be done within 30 minutes of receiving the response in step 5.4.
6. Moneris' processing host sends a request for payment confirmation to the issuer.
7. The issuer sends a response (either approved or declined) to Moneris host.
8. Moneris Gateway relays the response back to the merchant. If the payment was approved, the merchant fulfills the order.

**Table 4: Funded and non-funded URL variables**

To funded URL only	To funded and non-funded URL
IDEBIT_TRACK2	IDEBIT_VERSION
IDEBIT_ISSCONF	IDEBIT_ISSLANG
IDEBIT_ISSNAME	IDEBIT_TERMID (optional)
	IDEBIT_INVOICE (optional)

<sup>1</sup>This value is expressed in cents. Therefore, \$1 is input as 100

To funded URL only	To funded and non-funded URL
	IDEBIT_MERCHDATA (optional)

## 5.5 Sending an INTERAC® Online Payment Purchase Transaction

### 5.5.1 Fund-Guarantee Request

After choosing to pay by INTERAC® Online Payment, the customer is redirected using an HTML form post to the INTERAC® Online PaymentGateway page. Below is a sample code that is used to post the request to the Gateway.

```
<form action='from Section 9' method='post'>
<input type='text' name='IDEBIT_INVOICE' value='your unique invoice number'>
    <input type='text' name='IDEBIT_AMOUNT' value='100'> <!-- ($1.00) use cent values instead
        of dollar.cent format -->
<input type='text' name='IDEBIT_MERCHNUM' value='from Moneris Solutions'>
<input type='text' name='IDEBIT_CURRENCY' value='CA'>
<input type='text' name='IDEBIT_FUNDEDURL' value='your funded url'>
<input type='text' name='IDEBIT_NOTFUNDEDURL' value='your not funded url'>
<input type='text' name='IDEBIT_ISSLANG' value='en'>
<input type='text' name='IDEBIT_VERSION' value='1'>
<input type="submit" name="Submit" value="Submit to Gateway">
</form>
```

### 5.5.2 Online Banking Response and Fund-Confirmation Request

The response variables are posted back in an HTML form to either the funded or non-funded URL that was provided to INTERAC®.

The following variables must be validated (5.8, page 135):

- IDEBIT\_TRACK2
- IDEBIT\_ISSCONF
- IDEBIT\_ISSNAME
- IDEBIT\_VERSION
- IDEBIT\_ISSLANG
- IDEBIT\_INVOICE

Note that IDEBIT\_ISSCONF and IDEBIT\_ISSNAME must be displayed on the client's receipt that is generated by the merchant.

After validation, IDEBIT\_TRACK2 is used to form an IDebitPurchase transaction that is sent to Moneris Gateway to confirm the fund.

If the validation fails, redirect the client to the main page and ask for a different means of payment.

If the validation passes, an IDebitPurchase transaction can be sent to Moneris Gateway.

## 5.6 INTERAC® Online Payment Purchase

### INTERAC® Online Payment Purchase transaction object definition

```
IDebitPurchase IOP_Txn = new IDebitPurchase();
```

### HttpsPostRequest object for INTERAC® Online Payment Purchase transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(IOP_Txn);
```

### INTERAC® Online Payment Purchase transaction values

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

**Table 5: INTERAC® Online Payment transaction object mandatory values**

Value	Type	Limits	Set method
Order ID	String	50-character alpha-numeric	IOP_Txn.setOrderId(order_id);
Amount	String	10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point <div style="border: 1px solid black; padding: 5px; background-color: #e0f2e0; margin-top: 10px;"> <b>EXAMPLE:</b> 1234567.89         </div>	IOP_Txn.setAmount(amount);
Track2 data	String	40-character alpha-numeric	IOP_Txn.setTrack2(track2);

**Table 6: INTERAC® Online Payment Purchase transaction optional values**

Value	Type	Limits	Set method
Customer ID	String	50-character alphanumeric	IOP_Txn.setCustId(cust_id);
Dynamic descriptor	String	20-character alphanumeric	IOP_Txn.setDynamicDescriptor(dynamic_descriptor);
Customer information	Object	Not applicable. Click <a href="#">here</a> See Section 15 (page 483).	IOP_Txn.setCustInfo(customer);

**Sample INTERAC® Online Payment Purchase**

```

package Canada;
import JavaAPI.*;
public class TestCanadaIDebitPurchase
{
public static void main(String[] args)
{
String store_id = "store5";
String api_token = "yesguy";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String cust_id = "Lance_Briggs_55";
String amount = "5.00";
String track2 = "526805111999326=0609AAAAAAAAAAAA000";
String processing_country_code = "CA";
boolean status_check = false;
/********************* Billing/Shipping Variables *****/
String first_name = "Bob";
String last_name = "Smith";
String company_name = "ProLine Inc.";
String address = "623 Bears Ave";
String city = "Chicago";
String province = "Illinois";
String postal_code = "M1M2M1";
String country = "Canada";
String phone = "777-999-7777";
String fax = "777-999-7778";
String tax1 = "10.00";
String tax2 = "5.78";
String tax3 = "4.56";
String shipping_cost = "10.00";
/********************* Order Line Item Variables *****/
String[] item_description = new String[] { "Chicago Bears Helmet", "Soldier Field Poster" };
String[] item_quantity = new String[] { "1", "1" };
String[] item_product_code = new String[] { "CB3450", "SF998S" };
String[] item_extended_amount = new String[] { "150.00", "19.79" };
/********************* Customer Information Object *****/
CustInfo customer = new CustInfo();
/********************* Set Customer Billing Information *****/
customer.setBilling(first_name, last_name, company_name, address, city,
province, postal_code, country, phone, fax, tax1, tax2,
tax3, shipping_cost);
/********************* Set Customer Shipping Information *****/
customer.setShipping(first_name, last_name, company_name, address, city,

```

### Sample INTERAC® Online Payment Purchase

```

province, postal_code, country, phone, fax, tax1, tax2,
tax3, shipping_cost);
***** Order Line Items *****
customer.setItem(item_description[0], item_quantity[0],
item_product_code[0], item_extended_amount[0]);
customer.setItem(item_description[1], item_quantity[1],
item_product_code[1], item_extended_amount[1]);
***** Request *****
IDebitPurchase IOP_Txn = new IDebitPurchase();
IOP_Txn.setOrderId(order_id);
IOP_Txn.setCustId(cust_id);
IOP_Txn.setAmount(amount);
IOP_Txn.setIdebitTrack2(track2);
IOP_Txn.setCustInfo(customer);
//IOP_Txn.setDynamicDescriptor("dynamicdescriptor1");
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setStoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(IOP_Txn);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 5.7 INTERAC® Online Payment Refund

To process this transaction, you need the order ID and transaction number from the original INTERAC® Online Payment Purchase transaction.

### **INTERAC® Online Payment Refund transaction object definition**

```
IDebitRefund refund = new IDebitRefund();
```

### **HttpsPostRequest object for INTERAC® Online Payment Refund transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(refund);
```

### **INTERAC® Online Payment Refund transaction object values**

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

**Table 7: INTERAC® Online Payment Refund transaction object mandatory variables**

Value	Type	Limits	Set method
Order ID	String	50-character alpha-numeric	refund.setOrderId(order_id);
Amount	String	10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point  <b>EXAMPLE:</b> 1234567.89	refund.setAmount(amount);
Transaction number	String	255-character alpha-numeric	refund.setTxnNumber(txn_number);

**Table 8: INTERAC® Online Payment Refund transaction optional values**

Value	Type	Limits	Set method
Customer ID	String	50-character alphanumeric	refund.setCustId(cust_id);
Status Check	Boolean	true/false	mpgReq.setStatusCheck(status_check);

### **Sample code**

#### **Sample INTERAC® Online Payment Refund**

```
package Canada;
```

**Sample INTERAC® Online Payment Refund**

```
import JavaAPI.*;
public class TestCanadaIDebitRefund
{
public static void main(String[] args)
{
String store_id = "store5";
String api_token = "yesguy";
String order_id = "Test1435508096214";
String amount = "5.00";
String txn_number = "116181-0_10";
String processing_country_code = "CA";
String cust_id = "my customer id";
boolean status_check = false;
IDebitRefund refund = new IDebitRefund();
refund.setOrderId(order_id);
refund.setAmount(amount);
refund.setTxnNumber(txn_number);
refund.setCustId(cust_id);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(refund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
```

## 5.8 INTERAC® Online Payment Field Definitions

Table 9: Field Definitions

Value	Characters		Limits
	Description		
IDEBIT_MERCHNUM	5-14	Numbers and uppercase letters	This field is provided by Moneris. For example, 0003MONMPGXXXX.
IDEBIT_TERMID	8	Numbers and uppercase letters	Optional field
IDEBIT_AMOUNT	1-12	Numbers	Amount expressed in cents (for example, 1245 for \$12.45) to charge to the card.
IDEBIT_CURRENCY	3	"CAD" or "USD"	National currency of the transaction.
IDEBIT_INVOICE	1-20	ISO-8859-1 encoded characters restricted to: <ul style="list-style-type: none"> <li>• Uppercase and lowercase</li> <li>• Numbers</li> <li>• À Á Â Ã È É Ë Ì Í Ò Ú Ü Ç à á â ã è é ê ë ì í ô ù ú ü ý ç</li> <li>• Spaces</li> <li>• # \$ . , - / = ? @ '</li> </ul>	Optional field Can be the Order ID when used with Moneris Gateway fund confirmation transactions.

**Table 9: Field Definitions (continued)**

Value	Characters		Limits
	Description		
IDEBIT_MERCHDATA	1024	<p>ISO-8859-1 restricted to single-byte codes, hex 20 to 7E (consistent with US-ASCII and ISO-8859-1 Latin-1).</p> <p>Note that the following character combinations may not be accepted in the IDEBIT_MERCHDATA field:</p> <ul style="list-style-type: none"> <li>• "/..", "%2E.", ".%2E", "%2E%2E", "\\%2E%2E", "\%2E.", "\.%2E", "\%2E%2E", "&amp;#", "&lt;", "%3C", "&gt;", "%3E"</li> </ul>	
	<p>Free form data provided by the merchant that will be passed back unchanged to the merchant once the payment has been guaranteed in online banking.</p> <p>This may be used to identify the customer, session or both.</p>		
IDEBIT_FUNDEDURL	1024	<p>ISO-8859-1 restricted to single-byte codes, restricted to:</p> <ul style="list-style-type: none"> <li>• Uppercase and lowercase letters</li> <li>• Numbers</li> <li>• ; / ? : @ &amp; = + \$ , - _ . ! ~ * ' ( ) %</li> </ul>	
	<p>Https address to which the issuer will redirect cardholders after guaranteeing the fund through online banking.</p>		
IDEBIT_NOTFUNDEDURL	1024	<p>ISO-8859-1, restricted to single-byte codes, restricted to:</p> <ul style="list-style-type: none"> <li>• Uppercase and lowercase letters</li> <li>• Numbers</li> <li>• ; / ? : @ &amp; = + \$ , - _ . ! ~ * ' ( ) %</li> </ul>	
	<p>Https address to which the issuer redirects cardholders after failing or canceling the online banking process.</p>		
IDEBIT_MERCHLANG	2	<p>“en” or “fr”</p>	
	<p>Customer's current language at merchant.</p>		
IDEBIT_VERSION	3	<p>Numbers</p>	
	<p>Initially, the value is 1.</p>		
IDEBIT_ISSLANG	2	<p>“en” or “fr”</p>	
	<p>Customer's current language at issuer.</p>		

**Table 9: Field Definitions (continued)**

Value	Characters		Limits
	Description		
IDEBIT_TRACK2	37	ISO-8859-1 (restricted to single-byte codes), hex 20 to 7E (consistent with US-ASCII and ISO-8859-1 Latin-1)	
		Value returned by the issuer. It includes the PAN, expiry date, and transaction ID.	
IDEBIT_ISSCONF	15	ISO-8859-1 encoded characters restricted to: <ul style="list-style-type: none"> <li>• Uppercase and lowercase letters</li> <li>• Numbers</li> <li>• À Á Â Ã È É Ê Ë Ì Õ Ù Ú Ü Ç à á â ã è é ê ë ì õ ù ú ü ý ç</li> <li>• Spaces</li> <li>• # \$ . , - / = ? @ ' </li> </ul>	Confirmation number returned from the issuer to be displayed on the merchant's confirmation page and on the receipt.
IDEBIT_ISSNAME	30	ISO-8859-1 encoded characters restricted to: <ul style="list-style-type: none"> <li>• Uppercase and lowercase letters</li> <li>• Numbers</li> <li>• À Á Â Ã È É Ê Ë Ì Õ Ù Ú Ü Ç à á â ã è é ê ë ì õ ù ú ü ý ç</li> <li>• Spaces</li> <li>• # \$ . , - / = ? @ • ' </li> </ul>	Issuer name to be displayed on the merchant's confirmation page and on the receipt.

# 6 Level 2/3 Transactions

- 6.1 About Level 2/3 Transactions
- 6.2 Level 2/3 Visa Transactions
- 6.3 Level 2/3 Mastercard Transactions
- 6.4 Level 2/3 American Express Transactions

## 6.1 About Level 2/3 Transactions

The Moneris Gateway API supports passing Level 2/3 purchasing card transaction data for Visa, MasterCard and American Express corporate cards.

All Level 2/3 transactions use the same Pre-Authorization transaction as described in the topic Pre-Authorization (page 24).

## 6.2 Level 2/3 Visa Transactions

- 6.2.1 Level 2/3 Transaction Types for Visa
- 6.2.2 Level 2/3 Transaction Flow for Visa
- 6.2.3 VS Completion
- 6.2.5 VS Force Post
- 6.2.4 VS Purchase Correction
- 6.2.6 VS Refund
- 6.2.7 VS Independent Refund
- 6.2.8 VS Corpais
- 1 VS Corpais Invoice
- 1 VS Corpais – Passenger Itinerary

### 6.2.1 Level 2/3 Transaction Types for Visa

This transaction set includes a suite of corporate card financial transactions as well as a transaction that allows for the passing of Level 2/3 data. Please ensure that Visa Level 2/3 support is enabled on your

merchant account. Batch Close, Open Totals and Pre-authorization are identical to the transactions outlined in the section Basic Transaction Set (page 18).

- When the Pre-authorization response contains CorporateCard equal to true then you can submit the Visa transactions.
- If CorporateCard is false then the card does not support Level 2/3 data and non Level 2/3 transaction are to be used. If the card is not a corporate card, please refer to the section 2 Basic Transaction Set for the appropriate non-corporate card transactions.

**NOTE:** This transaction set is intended for transactions where Corporate Card is true and Level 2/3 data will be submitted. If the credit card is found to be a corporate card but you do not wish to send any Level 2/3 data then you may submit Visa transactions using the basic transaction set outlined in 2 Basic Transaction Set.

#### **Pre-authorization– (authorization/pre-authorization)**

Pre-authorization verifies and locks funds on the customer's credit card. The funds are locked for a specified amount of time, based on the card issuer. To retrieve the funds from a preauth so that they may be settled in the merchant account a capture must be performed. CorporateCard will return as true if the card supports Level 2/3.

#### **VS Completion – (Capture/Pre-authorization Completion)**

Once a Pre-authorization is obtained the funds that are locked need to be retrieved from the customer's credit card. The capture retrieves the locked funds and readies them for settlement into the merchant account. Prior to performing a VS Completion, a Pre-authorization must be performed. Once the transaction is completed, VS Corpais must be used to process the Level 2/3 data.

#### **VS Force Post – (Force Capture/Pre-authorization Completion)**

This transaction is an alternative to VS Completion to obtain the funds locked on Pre-auth obtained from IVR or equivalent terminal. The VS Force Post retrieves the locked funds and readies them for settlement in to the merchant account. Once the transaction is completed, VS Corpais must be used to process the Level 2/3 data.

#### **VS Purchase Correction (Void, Correction)**

VS Completion and VS Force Post can be voided the same day\* that they occur. A VS Purchase Correction must be for the full amount of the transaction and will remove any record of it from the cardholder statement.

#### **VS Refund – (Credit)**

A VS Refund can be performed against a VS Completion to refund any part or all of the transaction. Once the transaction is completed, VS Corpais must be used to process the Level 2/3 data.

**VS Independent Refund – (Credit)**

A VS Independent Refund can be performed against a purchase or a capture to refund any part, or all of the transaction. Independent refund is used when the originating transaction was not performed through Moneris Gateway. Once the transaction is completed, VS Corpais must be used to process the Level 2/3 data.

**NOTE:** the Independent Refund transaction may or may not be supported on your account. If you receive a transaction not allowed error when attempting an independent refund, it may mean the transaction is not supported on your account. If you wish to have the Independent Refund transaction type temporarily enabled (or re-enabled), please contact the Service Centre at 1-866-319-7450.


**VS Corpais – (Level 2/3 Data)**

VS Corpais will contain all the required and optional data fields for Level 2/3 Business to Business data. VS Corpais data can be sent when the card has been identified in the Pre-authorization transaction request as being a corporate card.


\* A VS Purchase Correction can be performed against a transaction as long as the batch that contains the original transaction remains open. When using the automated closing feature, the batch close occurs daily between 10 – 11 pm EST.

## 6.2.2 Level 2/3 Transaction Flow for Visa

### Pre-authorization/Completion Transaction Flow



## Purchase Correction Transaction Flow



### 6.2.3 VS Completion

Once a Pre-authorization is obtained, the funds that are locked need to be retrieved from the customer's credit card. This VS Completion transaction is used to secure the funds locked by a pre-authorization transaction and readies them for settlement into the merchant account.

**NOTE:** Once you have completed this transaction successfully, to submit the complete supplemental level 2/3 data, please proceed to VS Corpais.

#### VS Completion transaction object definition

```
VsCompletion vsCompletion = new VsCompletion();
```

#### HttpsPostRequest object for VS Completion transaction object

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(vsCompletion);
```

#### VS Completion transaction request fields – Required

Variable Name	Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	vsCompletion.setOrderId(order_id);
Completion amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	vsCompletion.setCompAmount(comp_amount);
<b>EXAMPLE:</b> 1234567.89		
Transaction number	<i>String</i> 255-character alphanumeric	vsCompletion.setTxnNumber(txn_number);
E-Commerce Indicator	<i>String</i> 1-character alphanumeric	vsCompletion.setCryptType(crypt);

**Table 1 Visa - Corporate Card Common Data - Level 2 Request Fields**

<b>Req*</b>	<b>Value</b>	<b>Limits</b>	<b>Set Method</b>	<b>Description</b>
Y	National Tax	12-character decimal	vsCompletion .setNationalTax(national_tax);	Must reflect the amount of National Tax (GST or HST) appearing on the invoice.  Minimum - 0.01 Maximum - 999999.99. Must have 2 decimal places.
Y	Merchant VAT Registration/Single Business Reference	20-character alphanumeric	vsCompletion .setMerchantVatNo(merchant_vat_no);	Merchant's Tax Registration Number  must be provided if tax is included on the invoice  <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2f1;"><b>NOTE:</b> Must not be all spaces or all zeroes</div>
C	Local Tax	12-character decimal	vsCompletion .setLocalTax(local_tax);	Must reflect the amount of Local Tax (PST or QST) appearing on the invoice  If Local Tax included then must not be all spaces or all

Req*	Value	Limits	Set Method	Description
				<p>zeroes; Must be provided if Local Tax (PST or QST) applies</p> <p>Minimum = 0.01</p> <p>Maximum = 999999.99</p> <p>Must have 2 decimal places</p>
C	Local Tax (PST or QST) Registration Number	15-character alphanumeric	<pre>vsCompletion .setLocalTaxNo (local_tax_no);</pre>	<p>Merchant's Local Tax (PST/QST) Registration Number</p> <p>Must be provided if tax is included on the invoice; If Local Tax included then must not be all spaces or all zeroes</p> <p>Must be provided if Local Tax (PST or QST) applies</p>
C	Customer VAT Registration Number	13-character alphanumeric	<pre>vsCompletion .setCustomerVatNo (customer_vat_no);</pre>	If the Customer's Tax Registration Number appears on the invoice to support tax exempt transactions it must be provided

Req*	Value	Limits	Set Method	Description
				here
C	Customer Code/Customer Reference Identifier (CRI)	16-character alphanumeric	vsCompletion .setCri(cri);	Value which the customer may choose to provide to the supplier at the point of sale – must be provided if given by the customer
N	Customer Code	17-character alphanumeric	vsCompletion .setCustomerCode(customer_code);	Optional customer code field that will not be passed along to Visa, but will be included on Moneris reporting
N	Invoice Number	17-character alphanumeric	vsCompletion .setInvoiceNumber(invoice_number);	Optional invoice number field that will not be passed along to Visa, but will be included on Moneris reporting

\*Y = Required, N = Optional, C = Conditional

#### Sample VS Completion

```
package Level23;
import JavaAPI.*;
public class TestVsCompletion
{
    public static void main(String[] args)
    {
        String store_id = "moneris";
        String api_token = "hurgle";
        String processing_country_code = "CA";
        boolean status_check = false;
```

### Sample VS Completion

```

String order_id="ord-210916-15:14:46";
String comp_amount="5.00";
String txn_number = "19002-0_11";
String crypt="7";
String national_tax = "1.23";
String merchant_vat_no = "gstno111";
String local_tax = "2.34";
String customer_vat_no = "gstno999";
String cri = "CUST-REF-002";
String customer_code="ccvsfp";
String invoice_number="invsfp";
String local_tax_no="ltaxno";
VsCompletion vsCompletion = new VsCompletion();
vsCompletion.setOrderId(order_id);
vsCompletion.setCompAmount(comp_amount);
vsCompletion.setTxnNumber(txn_number);
vsCompletion.setCryptType(crypt);
vsCompletion.setNationalTax(national_tax);
vsCompletion.setMerchantVatNo(merchant_vat_no);
vsCompletion.setLocalTax(local_tax);
vsCompletion.setCustomerVatNo(customer_vat_no);
vsCompletion.setCri(cri);
vsCompletion.setCustomerCode(customer_code);
vsCompletion.setInvoiceNumber(invoice_number);
vsCompletion.setLocalTaxNo(local_tax_no);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(vsCompletion);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}
}

```

## 6.2.4 VS Purchase Correction

The VS Purchase Correction (also known as a "void") transaction is used to cancel a transaction that was performed in the current batch. No amount is required because a void is always for 100% of the original transaction. The only transaction that can be voided using VS Purchase Correction is a VS Completion or VS Force Post. To send a void the `order_id` and `txn_number` from the VS Completion/VS Force Post are required.

### VS Purchase Correction transaction object definition

```
VsPurchaseCorrection vsPurchaseCorrection = new VsPurchaseCorrection();
```

### HttpsPostRequest object for VS Purchase Correction transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(vsPurchaseCorrection);
```

### VS Purchase Correction transaction request fields – Required

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	<code>vsPurchaseCorrection.setOrderId(order_id);</code>
Transaction number	<i>String</i> 255-character alpha-numeric	<code>vsPurchaseCorrection.setTxnNumber(txn_number);</code>
E-Commerce Indicator	<i>String</i> 1-character alphanumeric	<code>vsPurchaseCorrection.setCryptType(crypt);</code>

#### Sample VS Purchase Correction

```
package Level123;
import JavaAPI.*;

public class TestVsPurchaseCorrection
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;
```

### Sample VS Purchase Correction

```

String order_id="Test1485208113189";
String txn_number = "39793-0_11";
String crypt="7";
VsPurchaseCorrection vsPurchaseCorrection = new VsPurchaseCorrection();
vsPurchaseCorrection.setOrderId(order_id);
vsPurchaseCorrection.setTxnNumber(txn_number);
vsPurchaseCorrection.setCryptType(crypt);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(vsPurchaseCorrection);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}

```

## 6.2.5 VS Force Post

The VS Force Post transaction is used to secure the funds locked by a pre-authorization transaction performed over IVR or equivalent terminal. When sending a force post request, you will need Order ID, Amount, Credit Card Number, Expiry Date, E-commerce Indicator and the Authorization Code received in the pre-authorization response.

**NOTE:** Once you have completed this transaction successfully, to submit the complete supplemental level 2/3 data, please proceed to VS Corpais.

## VS Force Post transaction object definition

```
VsForcePost vsForcePost = new VsForcePost();
```

## HttpsPostRequest object for VS Force Post transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(vsForcePost);
```

## VS Force Post transaction request fields – Required

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	vsForcePost.setOrderId(order_id);
Amount	<i>String</i>  10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	vsForcePost.setAmount(amount);
<b>EXAMPLE:</b> 1234567.89		
Credit card number	<i>String</i> 20-character numeric	vsForcePost.setPan(pan);
Expiry Date	<i>String</i> 4-character numeric  YYMM format	vsForcePost.setExpDate(expiry_date);
Authorization code	<i>String</i> 8-character alphanumeric	vsForcePost.setAuthCode(auth_code);
E-commerce Indicator	<i>String</i> 1-character alphanumeric	vsForcePost.setCryptType(crypt);

**VS Force Post transaction request fields – Optional**

Variable Name	Type and Limits	Set Method
Customer ID	<i>String</i> 50-character alphanumeric	<code>vsForcePost.setCustId(cust_id);</code>

**Table 1 Visa - Corporate Card Common Data - Level 2 Request Fields**

Req*	Value	Limits	Set Method	Description
Y	National Tax	12-character decimal	<code>vsForcePost.setNationalTax(national_tax);</code>	Must reflect the amount of National Tax (GST or HST) appearing on the invoice.  Minimum - 0.01 Maximum - 999999.99. Must have 2 decimal places.
Y	Merchant VAT Registration/Single Business Reference	20-character alphanumeric	<code>vsForcePost.setMerchantVatNo(merchant_vat_no);</code>	Merchant's Tax Registration Number  must be provided if tax is included on the invoice  <div style="border: 1px solid #0070C0; padding: 5px; background-color: #E0F2FD;"><b>NOTE:</b> Must not be all spaces or all zeroes</div>
C	Local Tax	12-character decimal	<code>vsForcePost.setLocalTax(local_</code>	Must reflect the amount of

Req*	Value	Limits	Set Method	Description
			tax) ;	<p>Local Tax (PST or QST) appearing on the invoice</p> <p>If Local Tax included then must not be all spaces or all zeroes; Must be provided if Local Tax (PST or QST) applies</p> <p>Minimum = 0.01</p> <p>Maximum = 999999.99</p> <p>Must have 2 decimal places</p>
C	Local Tax (PST or QST) Registration Number	15-character alphanumeric	vsForcePost .setLocalTaxNo (local_tax_no) ;	<p>Merchant's Local Tax (PST/QST) Registration Number</p> <p>Must be provided if tax is included on the invoice; If Local Tax included then must not be all spaces or all zeroes</p> <p>Must be provided if Local Tax (PST or QST) applies</p>

Req*	Value	Limits	Set Method	Description
C	Customer VAT Registration Number	13-character alphanumeric	vsForcePost .setCustomerVatNo (customer_vat_no);	If the Customer's Tax Registration Number appears on the invoice to support tax exempt transactions it must be provided here
C	Customer Code/Customer Reference Identifier (CRI)	16-character alphanumeric	vsForcePost .setCri(cri);	Value which the customer may choose to provide to the supplier at the point of sale – must be provided if given by the customer
N	Customer Code	17-character alphanumeric	vsForcePost .setCustomerCode (customer_code);	Optional customer code field that will not be passed along to Visa, but will be included on Moneris reporting
N	Invoice Number	17-character alphanumeric	vsForcePost .setInvoiceNumber (invoice_number);	Optional invoice number field that will not be passed along to Visa, but will be included on Moneris reporting

\*Y = Required, N = Optional, C = Conditional

### Sample VS Force Post

```

package Level123;
import JavaAPI.*;

public class TestVsForcePost
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

java.util.Date createDate = new java.util.Date();
String order_id="Test"+createDate.getTime();
String cust_id="CUST13343";
String amount="5.00";
String pan="4242424254545454";
String expiry_date="2012"; //YYMM
String auth_code="123456";
String crypt="7";
String national_tax = "1.23";
String merchant_vat_no = "gstno111";
String local_tax = "2.34";
String customer_vat_no = "gstno999";
String cri = "CUST-REF-002";
String customer_code="ccvsfp";
String invoice_number="invsfp";
String local_tax_no="ltaxno";
VsForcePost vsForcePost = new VsForcePost();
vsForcePost.setOrderId(order_id);
vsForcePost.setCustId(cust_id);
vsForcePost.setAmount(amount);
vsForcePost.setPan(pan);
vsForcePost.setExpDate(expiry_date);
vsForcePost.setAuthCode(auth_code);
vsForcePost.setCryptType(crypt);
vsForcePost.setNationalTax(national_tax);
vsForcePost.setMerchantVatNo(merchant_vat_no);
vsForcePost.setLocalTax(local_tax);
vsForcePost.setCustomerVatNo(customer_vat_no);
vsForcePost.setCri(cri);
vsForcePost.setCustomerCode(customer_code);
vsForcePost.setInvoiceNumber(invoice_number);
vsForcePost.setLocalTaxNo(local_tax_no);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(vsForcePost);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
}
}

```

### Sample VS Force Post

```

System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}

```

## 6.2.6 VS Refund

VS Refund will credit a specified amount to the cardholder's credit card. A refund can be sent up to the full value of the original VS Completion or VS Force Post. To send a VS Refund you will require the Order ID and Transaction Number from the original VS Completion or VS Force Post.

**NOTE:** Once you have completed this transaction successfully, to submit the complete supplemental level 2/3 data, please proceed to VS Corpais.

### VS Refund transaction object definition

```
VsRefund vsRefund = new VsRefund();
```

### HttpsPostRequest object for VS Refund transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(vsRefund);
```

### VS Refund transaction object values

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	vsRefund.setOrderId(order_id);

Variable Name	Type and Limits	Set Method
Transaction number	<p><i>String</i></p> <p>255-character alpha-numeric</p>	<code>vsRefund.setTxnNumber(txn_number);</code>
Amount	<p><i>String</i></p> <p>10-character decimal</p> <p>Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point</p>	<code>vsRefund.setAmount(amount);</code>
E-Commerce Indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	<code>vsRefund.setCryptType(crypt);</code>

**Table 1 Visa - Corporate Card Common Data - Level 2 Request Fields**

Req*	Value	Limits	Set Method	Description
Y	National Tax	12-character decimal	<code>vsRefund.setNationalTax(national_tax);</code>	<p>Must reflect the amount of National Tax (GST or HST) appearing on the invoice.</p> <p>Minimum - 0.01 Maximum - 999999.99.</p> <p>Must have 2 decimal places.</p>
Y	Merchant VAT Registration/Single Business Reference	20-character alphanumeric	<code>vsRefund.setMerchantVatNo(merchant_vat_no);</code>	Merchant's Tax Registration Num-

Req*	Value	Limits	Set Method	Description
				<p>ber must be provided if tax is included on the invoice</p> <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2fd;"> <b>NOTE:</b> Must not be all spaces or all zeroes       </div>
C	Local Tax	12-character decimal	<pre>vsRefund .setLocalTax(local_ tax);</pre>	<p>Must reflect the amount of Local Tax (PST or QST) appearing on the invoice</p> <p>If Local Tax included then must not be all spaces or all zeroes; Must be provided if Local Tax (PST or QST) applies</p> <p>Minimum = 0.01</p> <p>Maximum = 999999.99</p> <p>Must have 2 decimal places</p>
C	Local Tax (PST or QST) Registration Number	15-character alphanumeric	<pre>vsRefund .setLocalTaxNo( local_tax_no);</pre>	Merchant's Local Tax (PST/QST) Registration Number

Req*	Value	Limits	Set Method	Description
				Must be provided if tax is included on the invoice; If Local Tax included then must not be all spaces or all zeroes  Must be provided if Local Tax (PST or QST) applies
C	Customer VAT Registration Number	13-character alphanumeric	vsRefund.setCustomerVatNo(customer_vat_no);	If the Customer's Tax Registration Number appears on the invoice to support tax exempt transactions it must be provided here
C	Customer Code/Customer Reference Identifier (CRI)	16-character alphanumeric	vsRefund.setCri(cri);	Value which the customer may choose to provide to the supplier at the point of sale – must be provided if given by the customer
N	Customer Code	17-character alphanumeric	vsRefund.setCustomerCode(customer_code);	Optional customer code field that will not be passed along to Visa, but will be included on Moneris

Req*	Value	Limits	Set Method	Description
				reporting
N	Invoice Number	17-character alphanumeric	vsRefund .setInvoiceNumber (invoice_number);	Optional invoice number field that will not be passed along to Visa, but will be included on Moneris reporting

\*Y = Required, N = Optional, C = Conditional

#### Sample VS Refund

```

package Level23;
import JavaAPI.*;
public class TestVsRefund
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

String order_id="Test1485208133961";
String amount="5.00";
String txn_number = "39795-0_11";
String crypt="7";
String national_tax = "1.23";
String merchant_vat_no = "gstno111";
String local_tax = "2.34";
String customer_vat_no = "gstno999";
String cri = "CUST-REF-002";
String customer_code="ccvsfp";
String invoice_number="invsfp";
String local_tax_no="ltaxno";
VsRefund vsRefund = new VsRefund();
vsRefund.setOrderId(order_id);
vsRefund.setAmount(amount);
vsRefund.setTxnNumber(txn_number);
vsRefund.setCryptType(crypt);
vsRefund.setNationalTax(national_tax);
vsRefund.setMerchantVatNo(merchant_vat_no);
vsRefund.setLocalTax(local_tax);
vsRefund.setCustomerVatNo(customer_vat_no);
vsRefund.setCri(cri);
vsRefund.setCustomerCode(customer_code);
vsRefund.setInvoiceNumber(invoice_number);
vsRefund.setLocalTaxNo(local_tax_no);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
}

```

### Sample VS Refund

```

mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(vsRefund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}

```

### 6.2.7 VS Independent Refund

VS Independent Refund will credit a specified amount to the cardholder's credit card. The independent refund does not require an existing order to be logged in the Moneris Gateway; however, the credit card number and expiry date will need to be passed. The transaction format is almost identical to a pre-authorization.

**NOTE:** Once you have completed this transaction successfully, to submit the complete supplemental level 2/3 data, please proceed to VS Corpais.

#### VS Independent Refund transaction object definition

```
VsIndependentRefund vsIndependentRefund = new VsIndependentRefund();
```

#### HttpsPostRequest object for VS Independent Refund transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
```

```
mpgReq.setTransaction(vsIndependentRefund);
```

### VS Independent Refund transaction request fields – Required

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	vsIndependentRefund.setOrderId(order_id);
Amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	vsIndependentRefund.setAmount(amount);
<b>EXAMPLE:</b> 1234567.89		
Credit card number	<i>String</i> 20-character numeric	vsIndependentRefund.setPan(pan);
Expiry date	<i>String</i> 4-character numeric  YYMM format	vsIndependentRefund.setExpDate(expiry_date);
E-commerce indicator	<i>String</i> 1-character alphanumeric	vsIndependentRefund.setCryptType(crypt);

### VS Independent Refund transaction request fields – Optional

Variable Name	Type and Limits	Set Method
Customer ID	50-character alphanumeric	vsIndependentRefund.setCustId(cust_id);

**Table 1 Visa - Corporate Card Common Data - Level 2 Request Fields**

<b>Req*</b>	<b>Value</b>	<b>Limits</b>	<b>Set Method</b>	<b>Description</b>
Y	National Tax	12-character decimal	<code>vsIndependentRefund.setNationalTax(national_tax);</code>	<p>Must reflect the amount of National Tax (GST or HST) appearing on the invoice.</p> <p>Minimum - 0.01 Maximum - 999999.99. Must have 2 decimal places.</p>
Y	Merchant VAT Registration/Single Business Reference	20-character alphanumeric	<code>vsIndependentRefund.setMerchantVatNo(merchant_vat_no);</code>	<p>Merchant's Tax Registration Number</p> <p>must be provided if tax is included on the invoice</p> <div style="border: 1px solid #ccc; padding: 5px; width: fit-content;"> <b>NOTE:</b> Must not be all spaces or all zeroes       </div>
C	Local Tax	12-character decimal	<code>vsIndependentRefund.setLocalTax(local_tax);</code>	<p>Must reflect the amount of Local Tax (PST or QST) appearing on the invoice</p> <p>If Local Tax included then must not be all spaces or all</p>

Req*	Value	Limits	Set Method	Description
				<p>zeroes; Must be provided if Local Tax (PST or QST) applies</p> <p>Minimum = 0.01</p> <p>Maximum = 999999.99</p> <p>Must have 2 decimal places</p>
C	Local Tax (PST or QST) Registration Number	15-character alphanumeric	<pre>vsIndependentRefund .setLocalTaxNo (local_tax_no);</pre>	<p>Merchant's Local Tax (PST/QST) Registration Number</p> <p>Must be provided if tax is included on the invoice; If Local Tax included then must not be all spaces or all zeroes</p> <p>Must be provided if Local Tax (PST or QST) applies</p>
C	Customer VAT Registration Number	13-character alphanumeric	<pre>vsIndependentRefund .setCustomerVatNo (customer_vat_no);</pre>	If the Customer's Tax Registration Number appears on the invoice to support tax exempt transactions it must be provided

Req*	Value	Limits	Set Method	Description
				here
C	Customer Code/Customer Reference Identifier (CRI)	16-character alphanumeric	vsIndependentRefund.setCri(cri);	Value which the customer may choose to provide to the supplier at the point of sale – must be provided if given by the customer
N	Customer Code	17-character alphanumeric	vsIndependentRefund.setCustomerCode(customer_code);	Optional customer code field that will not be passed along to Visa, but will be included on Moneris reporting
N	Invoice Number	17-character alphanumeric	vsIndependentRefund.setInvoiceNumber(invoice_number);	Optional invoice number field that will not be passed along to Visa, but will be included on Moneris reporting

\*Y = Required, N = Optional, C = Conditional

#### Sample VS Independent Refund

```
package Level23;
import JavaAPI.*;
public class TestVsIndependentRefund
{
    public static void main(String[] args)
    {
        String store_id = "moneris";
        String api_token = "hurgle";
        String processing_country_code = "CA";
        boolean status_check = false;
```

### Sample VS Independent Refund

```

java.util.Date createDate = new java.util.Date();
String order_id="Test"+createDate.getTime();
String cust_id="CUST13343";
String amount="5.00";
String pan="4242424254545454";
String expiry_date="2012"; //YYMM
String crypt="7";
String national_tax = "1.23";
String merchant_vat_no = "gstno111";
String local_tax = "2.34";
String customer_vat_no = "gstno999";
String cri = "CUST-REF-002";
String customer_code="ccvsfp";
String invoice_number="invsfp";
String local_tax_no="ltaxno";
VsIndependentRefund vsIndependentRefund = new VsIndependentRefund();
vsIndependentRefund.setOrderId(order_id);
vsIndependentRefund.setCustId(cust_id);
vsIndependentRefund.setAmount(amount);
vsIndependentRefund.setPan(pan);
vsIndependentRefund.setExpDate(expiry_date);
vsIndependentRefund.setCryptType(crypt);
vsIndependentRefund.setNationalTax(national_tax);
vsIndependentRefund.setMerchantVatNo(merchant_vat_no);
vsIndependentRefund.setLocalTax(local_tax);
vsIndependentRefund.setCustomerVatNo(customer_vat_no);
vsIndependentRefund.setCri(cri);
vsIndependentRefund.setCustomerCode(customer_code);
vsIndependentRefund.setInvoiceNumber(invoice_number);
vsIndependentRefund.setLocalTaxNo(local_tax_no);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(vsIndependentRefund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}

```

## Sample VS Independent Refund

```
}  
catch (Exception e)  
{  
    System.out.println(e);  
}  
}
```

## 6.2.8 VS Corpais

VS Corpais will contain all the required and optional data fields for Level 2/3 Purchasing Card Addendum data. VS Corpais data can be sent when the card has been identified in the Pre-authorization transaction request as being a corporate card.

In addition to the order ID and transaction number, this transaction also contains two objects:

- VS Purcha – Corporate Card Common Data
  - VS Purchl – Line Item Details

VS Corpais request must be preceded by a financial transaction (VS Completion, VS Force Post, VS Refund, VS Independent Refund) and the Corporate Card flag must be set to "true" in the Pre-authorization response.

## VS Corpais transaction object definition

```
VsCorpais vsCorpais = new VsCorpais();
```

## **HttpsPostRequest object for VS Corpais transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();  
mpgReq.setTransaction(vsCorpais);
```

## **VS Corpais transaction request fields – Required**

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	<code>vsCorpais.setOrderId(order_id);</code>
Transaction number	<i>String</i> 255-character alphanumeric	<code>vsCorpais.setTxnNumber(txn_number);</code>
vsPurcha	<i>String</i>	<code>VsPurcha vsPurcha = new</code>

Variable Name	Type and Limits	Set Method
For a list of the variables that appear in this object, see the table below	n/a	VsPurcha(); vsCorpais.setVsPurch(vnPurcha, vnPurchl);

vsPurchl	<i>String</i>	VsPurchl vsPurchl = new VsPurchl(); vsCorpais.setVsPurch(vnPurcha, vnPurchl);
----------	---------------	--

\*Y = Required, N = Optional, C = Conditional

### 6.2.8.1 VS Purcha – Corporate Card Common Data

VS Corpais transactions use the VS Purcha object to contain Level 2 data.

Variable Name	Type and Limits	Description
Buyer Name	<i>String</i> 30-character alphanumeric	Buyer/Recipient Name  <b>NOTE:</b> Name required by CRA on transactions >\$150
Local Tax Rate	<i>String</i> 4-character decimal	Indicates the detailed tax rate applied in relationship to a local tax amount  <b>EXAMPLE:</b> 8% PST should be 8.0  Minimum = 0.01 Maximum = 99.99  <b>NOTE:</b> Must be provided if Local Tax (PST or QST) applies.
Duty Amount	<i>String</i> 9-character decimal	Duty on total purchase amount A minus sign means 'amount is a credit', plus sign or no sign means

Variable Name	Type and Limits	Description
		'amount is a debit' maximum without sign is 999999.99
Invoice Discount Treatment	<i>String</i> 1-character numeric	Indicates how the merchant is managing discounts  Must be one of the following values:  0 - if no invoice level discounts apply for this invoice  1 - if Tax was calculated on Post-Discount totals  2 - if Tax was calculated on Pre-Discount totals
Invoice Level Discount Amount	<i>String</i> 9-character decimal	Amount of discount (if provided at the invoice level according to the Invoice Discount Treatment)  Must be non-zero if Invoice Discount Treatment is 1 or 2  Minimum amount is 0.00 and maximum is 999999.99
Ship To Postal Code / Zip Code	<i>String</i> 10-character alphanumeric	The postal code or zip code for the destination where goods will be delivered <div style="border: 1px solid #00AEEF; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> Required if shipment is involved           </div>
Ship From Postal Code / Zip Code	<i>String</i> 10-character alphanumeric	The postal code or zip code from which items were shipped  For Canadian addresses, requires full alpha postal code for the merchant with Valid ANA<space>NAN format
Destination Country Code	2-character alphanumeric	Code of country where purchased goods will be delivered

Variable Name	Type and Limits	Description
		Use ISO 3166-1 alpha-2 format  <b>NOTE:</b> Required if it appears on the invoice for an international transaction
Unique VAT Invoice Reference Number	<i>String</i> 25-character alphanumeric	Unique Value Added Tax Invoice Reference Number  Must be populated with the invoice number and this cannot be all spaces or zeroes
Tax Treatment	<i>String</i> 1-character alphanumeric	Must be one of the following values:  0 = Net Prices with tax calculated at line item level;  1 = Net Prices with tax calculated at invoice level;  2 = Gross prices given with tax information provided at line item level;  3 = Gross prices given with tax information provided at invoice level;  4 = No tax applies (small merchant) on the invoice for the transaction
Freight/Shipping Amount (Ship Amount)	<i>String</i> 9-character decimal	Freight charges on total purchase  If shipping is not provided as a line item it must be provided here, if applicable  Signed monetary amount:  Minus (-) sign means 'amount is a credit',  Plus (+) sign or no sign means 'amount is a debit'  Maximum without sign is 999999.99
GST HST Freight Rate	<i>String</i> 4-character decimal	Rate of GST (excludes PST) or HST charged on the shipping amount (in accordance with the Tax Treatment)

Variable Name	Type and Limits	Description
		If Freight/Shipping Amount is provided then this (National GST or HST) tax rate must be provided.
GST HST Freight Amount	<i>String</i> 9-character decimal	Monetary amount, maximum is 99.99. Such as 13% HST is 13.00  Amount of GST (excludes PST) or HST charged on the shipping amount  If Freight/Shipping Amount is provided then this (National GST or HST) tax amount must be provided if taxTreatment is 0 or 2  Signed monetary amount: maximum without sign is 999999.99.

### 6.2.8.2 VS Purchl – Line Item Details

VS Corpais transactions use the VS Purchl object to contain Level 3 data.

#### Line Item Details for VS Purchl

```
String[] item_com_code = {"X3101", "X84802"};
String[] product_code = {"CHR123", "DDSK200"};
String[] item_description = {"Office Chair", "Disk Drive"};
String[] item_quantity = {"3", "1"};
String[] item_uom = {"EA", "EA"};
String[] unit_cost = {"0.20", "0.40"};
String[] vat_tax_amt = {"0.00", "0.00"};
String[] vat_tax_rate = {"13.00", "13.00"};
String[] discount_treatmentL = {"0", "0"};
String[] discount_amtl = {"0.00", "0.00"};
```

#### Setting VS Purchl Line Item Details

```
vsPurchl.setVsPurchl(item_com_code[0], product_code[0], item_description[0],
item_quantity[0], item_uom[0], unit_cost[0], vat_tax_amt[0], vat_tax_rate[0],
discount_treatmentL[0], discount_amtl[0]);
```

```
vsPurch1.setVsPurch1(item_com_code[1], product_code[1], item_description[1],
item_quantity[1], item_uom[1], unit_cost[1], vat_tax_amt[1], vat_tax_rate[1],
discount_treatmentL[1], discount_amtl[1]);
```

**Table 1 Corporate Card Common Data - Level 3 Request Fields - VSPurch1**

Req*	Value	Limits	Variable/Field	Description
C	Item Commodity Code	12-character alpha-numeric	item_com_code	Line item Commodity Code (if this field is not sent, then Product Code must be sent)
Y	Product Code	12-character alpha-numeric	product_code	<p>Product code for this line item – merchant's product code, manufacturer's product code or buyer's product code</p> <p>Typically this will be the SKU or identifier by which the merchant tracks and prices the item or service</p> <p>This should always be provided for every line item</p>
Y	Item Description	35-character alpha-numeric	item_description	Line item description
Y	Item Quantity	12-character decimal	item_quantity	<p>Quantity invoiced for this line item</p> <p>Up to 4 decimal places supported, whole numbers are accepted</p> <p>Minimum = 0.0001</p> <p>Maximum = 999999999999</p>

Req*	Value	Limits	Variable/Field	Description
Y	Item Unit of Measure	2-character alpha-numeric	item_uom	Unit of measure Use ANSI X-12 EDI Allowable Units of Measure and Codes
Y	Item Unit Cost	12-character decimal	unit_cost	Line item cost per unit 2-4 decimal places accepted Minimum = 0.0001 Maximum = 999999.9999
N	VAT Tax Amount	12-character decimal	vat_tax_amt	Any value-added tax or other sales tax amount Must have 2 decimal places Minimum = 0.01 Maximum = 999999.99
N	VAT Tax Rate	4-character decimal	vat_tax_rate	Sales tax rate  <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2e0;"><b>EXAMPLE:</b> 8% PST should be 8.0</div> maximum 99.99
Y	Discount Treatment	1-character numeric	discount_treatmentL	Must be one of the following values:  0 if no invoice level discounts apply for this invoice  1 if Tax was calculated on Post-Discount totals  2 if Tax was calculated

Req*	Value	Limits	Variable/Field	Description
				on Pre-Discount totals
C	Discount Amount	12-character decimal	discount_amtL	<p>Amount of discount, if provided for this line item according to the Line Item Discount Treatment</p> <p>Must be non-zero if Line Item Discount Treatment is 1 or 2</p> <p>Must have 2 decimal places</p> <p>Minimum = 0.01</p> <p>Maximum = 999999.99</p>

### 6.2.8.3 Sample Code for VS Corpais

#### Sample VS Corpais

```

package Level23;
import JavaAPI.*;

public class TestVsCorpais
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

String order_id="Test1485208069127";
String txn_number="39791-0_11";
String buyer_name = "Buyer Manager";
String local_tax_rate = "13.00";
String duty_amount = "0.00";
String discount_treatment = "0";
String discount_amt = "0.00";
String freight_amount = "0.20";
String ship_to_pos_code = "M8X 2W8";
String ship_from_pos_code = "M1K 2Y7";
String des_cou_code = "CAN";
String vat_ref_num = "VAT12345";
String tax_treatment = "3";//3 = Gross prices given with tax information provided at
}

```

### Sample VS Corpais

```

invoice level
String gst_hst_freight_amount = "0.00";
String gst_hst_freight_rate = "13.00";
String[] item_com_code = {"X3101", "X84802"};
String[] product_code = {"CHR123", "DDSK200"};
String[] item_description = {"Office Chair", "Disk Drive"};
String[] item_quantity = {"3", "1"};
String[] item_uom = {"EA", "EA"};
String[] unit_cost = {"0.20", "0.40"};
String[] vat_tax_amt = {"0.00", "0.00"};
String[] vat_tax_rate = {"13.00", "13.00"};
String[] discount_treatmentL = {"0", "0"};
String[] discount_amtl = {"0.00", "0.00"};
//Create and set VsPurcha
VsPurcha vsPurcha = new VsPurcha();
vsPurcha.setBuyerName(buyer_name);
vsPurcha.setLocalTaxRate(local_tax_rate);
vsPurcha.setDutyAmount(duty_amount);
vsPurcha.setDiscountTreatment(discount_treatment);
vsPurcha.setDiscountAmt(discount_amt);
vsPurcha.setFreightAmount(freight_amount);
vsPurcha.setShipToPostalCode(ship_to_pos_code);
vsPurcha.setShipFromPostalCode(ship_from_pos_code);
vsPurcha.setDesCouCode(des_cou_code);
vsPurcha.setVatRefNum(vat_ref_num);
vsPurcha.setTaxTreatment(tax_treatment);
vsPurcha.setGstHstFreightAmount(gst_hst_freight_amount);
vsPurcha.setGstHstFreightRate(gst_hst_freight_rate);
//Create and set VsPurchl
VsPurchl vsPurchl = new VsPurchl();
vsPurchl.setVsPurchl(item_com_code[0], product_code[0], item_description[0], item_quantity[0], item_uom[0], unit_cost[0], vat_tax_amt[0], vat_tax_rate[0], discount_treatmentL[0], discount_amtl[0]);
vsPurchl.setVsPurchl(item_com_code[1], product_code[1], item_description[1], item_quantity[1], item_uom[1], unit_cost[1], vat_tax_amt[1], vat_tax_rate[1], discount_treatmentL[1], discount_amtl[1]);

VsCorpais vsCorpais = new VsCorpais();
vsCorpais.setOrderId(order_id);
vsCorpais.setTxnNumber(txn_number);
vsCorpais.setVsPurch(vsPurcha, vsPurchl);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(vsCorpais);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
}

```

**Sample VS Corpais**

```
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}
```

## 6.3 Level 2/3 Mastercard Transactions

- 6.3.1 Level 2/3 Transaction Types for Mastercard
- 6.3.2 Level 2/3 Transaction Flow for Mastercard
- 6.3.3 MC Completion
- 6.3.4 MC Force Post
- 6.3.5 MC Purchase Correction
- 6.3.6 MC Refund
- 6.3.7 MC Independent Refund
- 1 MC Corpais – Level 2/3 Transactions

### 6.3.1 Level 2/3 Transaction Types for Mastercard

This transaction set includes a suite of corporate card financial transactions as well as a transaction that allows for the passing of Level 2/3 data. Please ensure MC Level 2/3 processing support is enabled on your merchant account. Batch Close, Open Totals and Pre-authorization are identical to the transactions outlined in the section Basic Transaction Set (page 18).

When the Preauth response contains CorporateCard equal to true then you can submit the MC transactions.

If CorporateCard is false then the card does not support Level 2/3 data and non Level 2/3 transaction are to be used. If the card is not a corporate card, please refer to section 4 for the appropriate non-corporate card transactions.

**NOTE:** This transaction set is intended for transactions where Corporate Card is true and Level 2/3 data will be submitted. If the credit card is found to be a corporate card but you do not wish to send any Level 2/3 data then you may submit MC transactions using the transaction set outlined in Basic Transaction Set (page 18).

#### **Pre-auth – (authorization/pre-authorization)**

The pre-auth verifies and locks funds on the customer's credit card. The funds are locked for a specified amount of time, based on the card issuer. To retrieve the funds from a pre-auth so that they may be settled in the merchant account a capture must be performed. Level 2/3 data submission is not supported as part of a pre-auth as a pre-auth is not settled. When CorporateCard is returned true then Level 2/3 data may be submitted.

#### **MC Completion – (Capture/Preauth Completion)**

Once a Pre-authorization is obtained the funds that are locked need to be retrieved from the customer's credit card. The capture retrieves the locked funds and readies them for settlement in to the merchant account. Prior to performing an MCCompletion a Pre-auth must be performed.

#### **MC Force Post – (Force Capture/Preauth Completion)**

This transaction is an alternative to MC Completion to obtain the funds locked on Preauth obtained from IVR or equivalent terminal. The MC Force Post requires that the original Pre-authorization's auth code is provided and it retrieves the locked funds and readies them for settlement in to the merchant account.

#### **MC Purchase Correction – (Void, Correction)**

MC Completions can be voided the same day\* that they occur. A void must be for the full amount of the transaction and will remove any record of it from the cardholder statement. \* An MC Purchase Correction can be performed against a transaction as long as the batch that contains the original transaction remains open. When using the automated closing feature batch close occurs daily between 10 – 11 pm EST.

#### **MC Refund – (Credit)**

A MC Refund can be performed against an MC Completion or MC Force Post to refund an amount less than or equal to the amount of the original transaction.

### **MC Independent Refund – (Credit)**

A MC Indpendent Refund can be performed against an completion to refund any part, or all of the transaction. Independent refund is used when the originating transaction was not performed through Moneris Gateway. Please note, the MC Independent Refund transaction may or may not be supported on your account. If you receive a transaction not allowed error when attempting an MC Independent Refund, it may mean the transaction is not supported on your account. If you wish to have the MC Independent Refund transaction type temporarily enabled (or re-enabled), please contact the Service Centre at 1-866-319-7450.


### **MC Corpais Common Line Item – (Level 2/3 Data)**

MC Corpais Common Line Item will contain the entire required and optional data field for Level 2/3 data. MCCorpais Common Line Item data can be sent when the card has been identified in the transaction request as being a corporate card. This transaction supports multiple data types and combinations:


- Purchasing Card Data:
  - Corporate card common data with Line Item Details

### 6.3.2 Level 2/3 Transaction Flow for Mastercard

#### Pre-Authorization/Completion Transaction Flow



## Purchase Correction Transaction Flow



### 6.3.3 MC Completion

The MC Completion transaction is used to secure the funds locked by a Pre-Authorization transaction. When sending a capture request you will need two pieces of information from the original pre-authorization—the order ID and the transaction number from the returned response.

---

Once you have completed this transaction successfully, to submit the complete supplemental level 2/3 data, please proceed to MC Corpais.

---

#### MC Completion transaction object definition

```
McCompletion mcCompletion = new McCompletion();
```

#### HttpsPostRequest object for MC Completion transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcCompletion);
```

#### MC Completion transaction request fields – Required

Variable Name	Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	mcCompletion.setOrderId(order_id);
Completion amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	mcCompletion.setCompAmount(comp_amount);
<b>EXAMPLE:</b> 1234567.89		
Transaction number	<i>String</i> 255-character alpha-numeric	mcCompletion.setTxnNumber(txn_number);
Merchant reference number	<i>String</i> 19-character alphanumeric	mcCompletion.setMerchantRefNo(merchant_ref_no);

Variable Name	Limits	Set Method
E-commerce indicator	<i>String</i> 1-character alphanumeric	mcCompletion.setCryptType(crypt);

### Sample MC Completion

```

package Level123;
import JavaAPI.*;

public class TestMcCompletion
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

String order_id="Test1485206444761";
String comp_amount="1.00";
String txn_number="39777-0_11";
String crypt="7";
String merchant_ref_no = "319038";
McCompletion mcCompletion = new McCompletion();
mcCompletion.setOrderId(order_id);
mcCompletion.setCompAmount(comp_amount);
mcCompletion.setTxnNumber(txn_number);
mcCompletion.setCryptType(crypt);
mcCompletion.setMerchantRefNo(merchant_ref_no);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcCompletion);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
}
}

```

## Sample MC Completion

```
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}
```

### 6.3.4 MC Force Post

MC Force Post transaction is used to secure the funds locked by a Pre-Authorization transaction performed over IVR or equivalent terminal. When sending a Force Post request, you will need order\_id, amount, pan (card number), expiry date, crypt type and the authorization code received in the Pre-Authorization response.

## MC Force Post transaction object definition

```
McForcePost mcforcepost= new McForcePost();
```

## **HttpsPostRequest object for MC Force Post transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();  
mpgReq.setTransaction(mcforcepost);
```

## MC Force Post transaction request fields – Required

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	<code>mcforcepost.setOrderId(order_id);</code>
Amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	<code>mcforcepost.setAmount(amount);</code>

Variable Name	Type and Limits	Set Method
Credit card number	<i>String</i> 20-character alphanumeric	<code>mcforcepost.setPan(pan);</code>
Expiry date	<i>String</i> 4-character alphanumeric (YYMM format)	<code>mcforcepost.setExpDate(expiry_date);</code>
Authorization code	<i>String</i> 8-character alphanumeric	<code>mcforcepost.setAuthCode(auth_code);</code>
E-commerce indicator	<i>String</i> 1-character alphanumeric	<code>mcforcepost.setCryptType(crypt);</code>
Merchant reference number	<i>String</i> 19-character alphanumeric	<code>mcforcepost.setMerchantRefNo(merchant_ref_no);</code>

### MC Force Post transaction request fields – Optional

Variable Name	Type and Limits	Set Method
Customer ID	<i>String</i> 50-character alphanumeric	<code>mcforcepost.setCustId(cust_id);</code>

### Sample MC Force Post

```

package Level123;
import JavaAPI.*;

public class TestMcForcePost
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

java.util.Date createDate = new java.util.Date();
String order_id="Test"+createDate.getTime();
String cust_id = "CUST13343";

```

### Sample MC Force Post

```

String amount = "5.00";
String pan = "5454545442424242";
String expiry_date = "1912"; //YYMM
String auth_code = "123456";
String crypt = "7";
String merchant_ref_no = "319038";
McForcePost mcforcepost = new McForcePost();
mcforcepost.setOrderId(order_id);
mcforcepost.setCustId(cust_id);
mcforcepost.setAmount(amount);
mcforcepost.setPan(pan);
mcforcepost.setExpDate(expiry_date);
mcforcepost.setAuthCode(auth_code);
mcforcepost.setCryptType(crypt);
mcforcepost.setMerchantRefNo(merchant_ref_no);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setStoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcforcepost);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}
}

```

### 6.3.5 MC Purchase Correction

The MC Purchase Correction (void) transaction is used to cancel a transaction that was performed in the current batch. No amount is required because a void is always for 100% of the original transaction. The

only transaction that can be voided is completion. To send a void, the order ID and transaction number from the MC Completion or MC Force Post are required.

### MC Purchase Correction transaction object definition

```
McPurchaseCorrection mcpurchasecorrection = new McPurchaseCorrection();
```

### HttpsPostRequest object for MC Purchase Correction transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpurchasecorrection);
```

### MC Purchase Correction transaction request fields – Required

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	mcpurchasecorrection.setOrderId(order_id);
Transaction number	<i>String</i> 255-character alpha- numeric	mcpurchasecorrection.setTxnNumber(txn_number);
E-commerce indicator	<i>String</i> 1-character alphanumeric	mcpurchasecorrection.setCryptType(crypt);

### Sample MC Purchase Correction

```
package Level123;
import JavaAPI.*;

public class TestMcPurchaseCorrection
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

String order_id="Test1485207871499";
String txn_number="660117311902017023164431860-0_11";
String crypt="7";
McPurchaseCorrection mcpurchasecorrection = new McPurchaseCorrection();
mcpurchasecorrection.setOrderId(order_id);
mcpurchasecorrection.setTxnNumber(txn_number);
mcpurchasecorrection.setCryptType(crypt);
```

### Sample MC Purchase Correction

```

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpurchasecorrection);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}

```

### 6.3.6 MC Refund

The MC Refund will credit a specified amount to the cardholder's credit card. A refund can be sent up to the full value of the original capture. To send a refund you will require the Order ID and Transaction Number from the original MC Completion or MC Force Post.

#### **MC Refund transaction object definition**

```
McRefund mcRefund = new McRefund();
```

#### **HttpsPostRequest object for MC Refund transaction**

```

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(mcRefund);

```

## MC Refund transaction request fields – Required

Variable Name	Type and Limits	Set Method
Order ID	50-character alphanumeric	mcRefund.setOrderId(order_id);
Amount	10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	mcRefund.setAmount(amount);
<b>EXAMPLE:</b> 1234567.89		
Transaction number	255-character alpha- numeric	mcRefund.setTxnNumber(txn_ number);
E-commerce indicator	1-character alphanumeric	mcRefund.setCryptType(crypt);
Merchant reference num- ber	19-character alphanumeric	mcRefund.setMerchantRefNo (merchant_ref_no);

### Sample MC Refund

```

package Level23;
import JavaAPI.*;
public class TestMcRefund
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

String order_id="Test1485207913048";
String amount="5.00";
String txn_number="660117311902017023164513403-0_11";
String crypt="7";
String merchant_ref_no = "319038";
McRefund mcRefund = new McRefund();
mcRefund.setOrderId(order_id);
mcRefund.setAmount(amount);
mcRefund.setTxnNumber(txn_number);
mcRefund.setCryptType(crypt);
mcRefund.setMerchantRefNo(merchant_ref_no);
HttpsPostRequest mpgReq = new HttpsPostRequest();
}
}

```

### Sample MC Refund

```

mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcRefund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}
}

```

### 6.3.7 MC Independent Refund

MC Independent Refund is used when the originating transaction was not performed through Moneris Gateway and does not require an existing order to be logged in the Moneris Gateway; however, the credit card number and the expiry date will need to be passed. The transaction format is almost identical to a purchase or a pre-authorization.

**NOTE:** Independent refund transactions are not supported on all accounts. If you receive a transaction not allowed error when attempting an independent refund transaction, it may mean the feature is not supported on your account. To have Independent Refund transaction functionality temporarily enabled (or re-enabled), please contact the MonerisCustomer Service Centre at 1-866-319-7450.

Once you have completed this transaction successfully, to submit the complete supplemental level 2/3 data, please proceed to MC Corpais.

### **MC Independent Refund transaction object definition**

```
McIndependentRefund mcindrefund = new McIndependentRefund();
```

### **HttpsPostRequest object for MC Independent Refund transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcindrefund);
```

### **MC Independent Refund transaction request fields – Required**

Variable Name	Type and Limits	Set Method
Order ID	50-character alphanumeric	mcindrefund.setOrderId(order_id);
Amount	10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	mcindrefund.setAmount(amount);
<b>EXAMPLE: 1234567.89</b>		
E-commerce indicator	1-character alphanumeric	mcindrefund.setCryptType(crypt);
Credit card number	20-character numeric	mcindrefund.setPan(pan);
Expiry date	4-character numeric (YYMM format)	mcindrefund.setExpDate(expiry_date);
Merchant reference number	19-character alphanumeric	mcindrefund.setMerchantRefNo(merchant_ref_no);

## MC Independent Refund transaction request fields – Optional

**Table 1 MC Independent Refund transaction object optional values**

Variable Name	Type and Limits	Set Method
Customer ID	<i>String</i> 50-character alphanumeric	mcindrefund.setCustId(cust_id);

### Sample MC Independent Refund

```

package Level23;
import JavaAPI.*;
public class TestMcIndependentRefund
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

java.util.Date createDate = new java.util.Date();
String order_id="Test"+createDate.getTime();
String cust_id = "CUST13343";
String amount = "5.00";
String pan = "5454545442424242";
String expiry_date = "1912"; //YYMM
String crypt = "7";
String merchant_ref_no = "319038";
McIndependentRefund mcindrefund = new McIndependentRefund();
mcindrefund.setOrderId(order_id);
mcindrefund.setCustId(cust_id);
mcindrefund.setAmount(amount);
mcindrefund.setPan(pan);
mcindrefund.setExpDate(expiry_date);
mcindrefund.setCryptType(crypt);
mcindrefund.setMerchantRefNo(merchant_ref_no);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcindrefund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
}
}

```

### Sample MC Independent Refund

```
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
```

#### 6.3.8 MC Corpais - Corporate Card Common Data with Line Item Details

This transaction example includes the following elements for Level 2 and 3 purchasing card corporate card data processing:

- Corporate Card Common Data (MC Corpac)
  - only 1 set of MC Corpac fields can be submitted
  - this data set includes data elements that apply to the overall order, e.g., the total overall taxes
- Line Item Details (MC Corpal)
  - 1-998 counts of MC Corpal line items can be submitted
  - This data set includes the details about each individual item or service purchased

The MC Corpais request must be preceded by a financial transaction (MC Completion, MC Force Post, MC Refund, MC Independent Refund) and the Corporate Card flag must be set to “true” in the Preauthorization response. The MC Corpais request will need to contain the Order ID of the financial transaction as well as the Transaction Number.

In addition, MC Corpais has a tax array object that can be sent via the Tax fields in MC Corpac and MC Corpal. For more about the tax array object, see 6.3.8.3 Tax Array Object - MC Corpais.

For descriptions of the Level 2/3 fields, please see Definition of Request Fields for Level 2/3 - Mastercard (page 530).

### MC Corpais transaction object definition

```
McCorpais mcCorpais = new McCorpais();
```

### HttpsPostRequest object for MC Corpais transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcCorpais);
```

### MC Corpais transaction object values

**Table 1 MC Corpais transaction object mandatory values**

Value	Type	Limits	Set Method
Order ID	String	50-character alpha-numeric	mcCorpais.setOrderId(order_id);
Transaction number	String	255-character alpha-numeric	mcCorpais.setTxnNumber(txn_number);
MCCorpac	Object	n/a	mcCorpac.setMCCorpac(mcCorpac);
MC Corpal	Object	n/a	mcCorpais.setMcCorpal(mcCorpal);

\*Y = Required, N = Optional, C = Conditional

#### 6.3.8.1 MC Corpac - Corporate Card Common Data

**Table 1 Corporate Card Common Data - Level 2 Request Fields - MCCorpac**

Re-q*	Value	Limits	Set Method	Description
N	Austin-Tetra Number	15-character alpha-numeric	mcCorpac.setAustinTetraNumber(austin_tetra_number);	The Austin-Tetra Number assigned to the card acceptor
N	NAICS Code	15-character alpha-numeric	mcCorpac.setNaicsCode(naics_code);	North American Industry Classification System (NAICS) code assigned to the card acceptor
N	Customer	25-character	mcCorpac.setCustomerCode1	A control number, such

Re-q*	Value	Limits	Set Method	Description
	Code	alpha-numeric	(customer_code1_c) ;	as purchase order number, project number, department allocation number or name that the purchaser supplied the merchant  Left-justified; may be spaces
N	Unique Invoice Number	17-character alpha-numeric	mcCorpac.setUniqueInvoiceNumber(unique_invoice_number_c) ;	Unique number associated with the individual transaction provided by the merchant
N	Commodity Code	15-character alpha-numeric	mcCorpac.setCommodityCode(commodity_code) ;	Code assigned by the merchant that best categorizes the item(s) being purchased
N	Order Date	6-character numeric YYMMDD format	mcCorpac.setOrderDate(order_date_c) ;	The date the item was ordered  <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2f1;"><b>NOTE:</b> If present, must contain a valid date</div>
N	Corporation VAT Number	20-character alpha-numeric	mcCorpac.setCorporationVatNumber(corporation_vat_number_c) ;	Contains a corporation's value added tax (VAT) number
N	Customer VAT Number	20-character alpha-numeric	mcCorpac.setCustomerVatNumber(customer_vat_number_c) ;	Contains the VAT number for the customer / cardholder used to identify the customer when purchasing goods and services from the merchant
N	Freight Amount	12-character decimal	mcCorpac.setFreightAmount1(freight_amount_c) ;	The freight on the total

Re-q*	Value	Limits	Set Method	Description
				<p>purchase</p> <p>Must have 2 decimals</p> <p>Minimum = 0.00 Maximum = 999999.99</p>
N	Duty Amount	12-character decimal	mcCorpac.setDutyAmount1(duty_amount_c);	<p>The duty on the total purchase</p> <p>Must have 2 decimals</p> <p>Minimum = 0.00</p> <p>Maximum = 999999.99</p>
N	Destination State / Province Code	3-character alpha-numeric	mcCorpac.setDestinationProvinceCode(destination_province_code);	<p>State or Province of the country where the goods will be delivered</p> <p>Left justified with trailing spaces</p> <div style="background-color: #e0f2e0; padding: 5px;"> <b>EXAMPLE:</b> ONT = Ontario         </div>
N	Destination Country Code	3-character alpha-numeric ISO 3166-1 alpha-3 format	mcCorpac.setDestinationCountryCode(destination_country_code);	<p>The country code where goods will be delivered</p> <p>Left justified with trailing spaces</p> <p>ISO 3166-1 alpha-3 format</p> <div style="background-color: #e0f2e0; padding: 5px;"> <b>EXAMPLE:</b> CAN = Canada         </div>
N	Ship From Postal Code	10-character alpha-numeric	mcCorpac.setShipFromPosCode(ship_from_pos_code);	The postal code or zip code from which items were shipped

Re-q*	Value	Limits	Set Method	Description
		ANA NAN format		Full alpha postal code - Valid ANA<space>NAN format
N	Destination Postal Code	10-character alpha-numeric	mcCorpac.setShipToPosCode (ship_to_pos_code_c);	The postal code or zip code where goods will be delivered  Full alpha postal code - Valid ANA<space>NAN format if shipping to an address within Canada
N	Authorized Contact Name	36-character alpha-numeric	mcCorpac.setAuthorizedContactName (authorized_contact_name_c);	Name of an individual or company contacted for company authorized purchases
N	Authorized Contact Phone	17-character alpha-numeric	mcCorpac.setAuthorizedContactPhone (authorized_contact_phone);	Phone number of an individual or company contacted for company authorized purchases
N	Additional Card Acceptor Data	40-character alpha-numeric	mcCorpac.setAdditionalCardAcceptorData (additional_card_acceptor_data);	Information pertaining to the card acceptor
N	Card Acceptor Type	8-character alpha-numeric	mcCorpac.setCardAcceptorType (card_acceptor_type);	Various classifications of business ownership characteristics  This field takes 8 characters. Each character represents a different component, as follows:  1st character represents 'Business Type' and contains a code to identify the specific classification or type of business:  Corporation

Re-q*	Value	Limits	Set Method	Description
				<p>Not known</p> <p>Individual/Sole Proprietorship</p> <p>Partnership</p> <p>Association/Estate/Trust</p> <p>Tax Exempt Organizations (501C)</p> <p>International Organization</p> <p>Limited Liability Company (LLC)</p> <p>Government Agency</p> <p>2nd character represents 'Business Owner Type'. Contains a code to identify specific characteristics about the business owner.</p> <ul style="list-style-type: none"> <li>1 - No application classification</li> <li>2 - Female business owner</li> <li>3 - Physically handicapped female business owner</li> <li>4 - Physically handicapped male business owner</li> <li>0 - Unknown</li> </ul> <p>3rd character represents 'Business Certification Type'. Contains a code to identify specific characteristics about the business certification type, such as small business, disadvantaged, or other certification type:</p>

Re-q*	Value	Limits	Set Method	Description
				<p>1 - Not certified</p> <p>2 - Small Business Administration (SBA) certification small business</p> <p>3 - SBA certification as small disadvantaged business</p> <p>4 - Other government or agency-recognized certification (such as Minority Supplier Development Council)</p> <p>5 - Self-certified small business</p> <p>6 - SBA certification as small and other government or agency-recognized certification</p> <p>7 - SBA certification as small disadvantaged business and other government or agency-recognized certification</p> <p>8 - Other government or agency-recognized certification and self-certified small business</p> <p>A - SBA certification as 8(a)</p> <p>B - Self-certified small disadvantaged business (SDB)</p>

Re-q*	Value	Limits	Set Method	Description
				<p>C - SBA certification as HUBZone 0 - Unknown</p> <p>4th character represents 'Business Racial/Ethnic Type'. Contains a code identifying the racial or ethnic type of the majority owner of the business.</p> <p>1 - African American 2 - Asian Pacific American 3 - Subcontinent Asian American 4 - Hispanic American 5 - Native American Indian 6 - Native Hawaiian 7 - Native Alaskan 8 - Caucasian 9 - Other 0 - Unknown</p> <p>5th character represents 'Business Type Provided Code'</p> <p>Y - Business type is provided. N - Business type was not provided. R - Card acceptor refused to provide business type</p>

Re-q*	Value	Limits	Set Method	Description
				<p>6th character represents 'Business Owner Type Provided Code'</p> <p>Y - Business owner type is provided.</p> <p>N - Business owner type was not provided.</p> <p>R - Card acceptor refused to provide business type</p> <p>7th character represents 'Business Certification Type Provided Code'</p> <p>Y - Business certification type is provided.</p> <p>N - Business certification type was not provided.</p> <p>R - Card acceptor refused to provide business type</p> <p>8th character represents 'Business Racial/Ethnic Type'</p> <p>Y - Business racial/ethnic type is provided.</p> <p>N - Business racial/ethnic type was not provided.</p> <p>R - Card acceptor refused to provide business racial/ethnic type</p>

Re-q*	Value	Limits	Set Method	Description
N	Card Acceptor Tax ID	20-character alpha-numeric	mcCorpac.setCardAcceptorTaxTd(card_acceptor_tax_id_c);	US federal tax ID number or value-added tax (VAT) ID
N	Card Acceptor Reference Number	25-character alpha-numeric	mcCorpac.setCardAcceptorReferenceNumber(card_acceptor_reference_number);	Code that facilitates card acceptor/corporation communication and record keeping
N	Card Acceptor VAT Number	20-character alpha-numeric	mcCorpac.setCardAcceptorVatNumber(card_acceptor_vat_number_c);	Value added tax (VAT) number for the card acceptor location  Used to identify the card acceptor when collecting and reporting taxes
C	Tax	Up to 6 arrays	mcCorpac.setTax(tax_c);	Can have up to 6 arrays containing different tax details  <div style="border: 1px solid #ccc; padding: 5px;"> <b>NOTE:</b> If you use this variable, you must fill in all the fields of tax array mentioned below.         </div>

### 6.3.8.2 MC Corpal - Line Item Details

#### MC Corpal Object - Line Item Details

```
mcCorpal.setMcCorpal(customer_code1_1[0], line_item_date_1[0], ship_date_1[0],
order_date1_1[0], medical_services_ship_to_health_industry_number_1[0],
contract_number_1[0], medical_services_adjustment_1[0], medical_services_
product_number_qualifier_1[0], product_code1_1[0], item_description_1[0],
item_quantity_1[0], unit_cost_1[0], item_unit_measure_1[0], ext_item_amount_1
[0], discount_amount_1[0], commodity_code_1[0], type_of_supply_1[0], vat_ref_
num_1[0], tax_1[0]);
```

**Table 1 Line Item Details - Level 3 Request Fields - MC CorpA**

<b>Req*</b>	<b>Value</b>	<b>Limits</b>	<b>Variable</b>	<b>Description</b>
N	Customer Code	25-character alpha-numeric	customer_code1_I	A control number, such as purchase order number, project number, department allocation number or name that the purchaser supplied the merchant
N	Line Item Date	6-character numeric YYMMDD format	line_item_date_I	The purchase date of the line item referenced in the associated Corporate Card Line Item Detail  Fixed length 6 Numeric, in YYMMDD format
N	Ship Date	6-character numeric YYMMDD format	ship_date_I	The date the merchandise was shipped to the destination  Fixed length 6 Numeric, in YYMMDD format
N	Order Date	6-character numeric YYMMDD format	order_date1_I	The date the item was ordered  Fixed length 6-character numeric, in YYMMDD format
Y	Product Code	12-character alpha-numeric	product_code1_I	Line item Product Code

Req*	Value	Limits	Variable	Description
				Contains the non-fuel related product code of the individual item purchased
Y	Item Description	35-character alpha-numeric	item_description_I	<p>Line Item description</p> <p>Contains the description of the individual item purchased</p>
Y	Item Quantity	12-character alpha-numeric	item_quantity_I	<p>Quantity of line item</p> <p>Up to 5 decimal places supported</p> <p>Minimum amount is 0.0 and maximum is 9999999.99999</p>
Y	Unit Cost	12-character decimal	unit_cost_I	<p>Line item cost per unit.</p> <p>Must contain a minimum of 2 decimal places, up to 5 decimal places supported.</p> <p>Minimum amount is 0.00001 and maximum is 999999.99999</p>
Y	Item Unit Measure	12-character alpha-numeric	item_unit_measure_I	<p>The line item unit of measurement code</p> <p>ANSI X-12 EDI Allowable Units of</p>

Req*	Value	Limits	Variable	Description
				Measure and Codes
Y	Extended Item Amount	9-character decimal	ext_item_amount_I	<p>Contains the individual item amount that is normally calculated as price multiplied by quantity</p> <p>Must contain 2 decimal places</p> <p>Minimum amount is 0.00 and maximum is 999999.99</p>
N	Discount Amount	9-character decimal	discount_amount_I	<p>Contains the item discount amount</p> <p>Must contain 2 decimal places</p> <p>Minimum amount is 0.00 and maximum is 999999.99</p>
N	Commodity Code	15-character alpha-numeric	commodity_code_I	Code assigned to the merchant that best categorizes the item(s) being purchased
C	Tax	Up to 6 arrays	tax_I	<p>Can have up to 6 arrays containing different tax details –see Tax Array Request Fields table below for each field description</p> <div style="border: 1px solid #00AEEF; padding: 5px; background-color: #E0F2F1; margin-top: 10px;"> <b>NOTE:</b> If you use this variable, you must fill in all the         </div>

Req*	Value	Limits	Variable	Description
				fields of tax array mentioned below.

### 6.3.8.3 Tax Array Object - MC Corpais

The tax array object is used when you use the Tax field of both MC Corpac and MC Corpal. If you use the tax array object, all of the array fields must be sent.

Setting the tax array differs slightly between the two objects.

#### Setting tax array for MC Corpac

```
//Tax Details

String[] tax_amount_c = { "1.19", "1.29"};

String[] tax_rate_c = { "6.0", "7.0"};

String[] tax_type_c = { "GST", "PST"};

String[] tax_id_c = { "gst1298", "pst1298"};

String[] tax_included_in_sales_c = { "Y", "N"};

McTax tax_c = new McTax();

tax_c.setTax(tax_amount_c[0], tax_rate_c[0], tax_type_c[0], tax_id_c[0], tax_included_in_sales_c[0]);
```

#### Setting tax array for MC Corpal

```
//Tax Details for Items

String[] tax_amount_l = {"0.52", "1.48"};

String[] tax_rate_l = {"13.0", "13.0"};

String[] tax_type_l = {"HST", "HST"};

String[] tax_id_l = {"hst1298", "hst1298"};

String[] tax_included_in_sales_l = {"Y", "Y"};

McTax[] tax_l = new McTax[2];

tax_l[1].setTax(tax_amount_l[1], tax_rate_l[1], tax_type_l[1], tax_id_l[1], tax_included_in_sales_l[1]);
```

**Table 1 MC Corpais Tax Array Request Fields**

Req*	Value	Limits	Variable	Description
Y	Tax Amount	12-character decimal	tax_amount_c/tax_amount_l	<p>Contains detail tax amount for purchase of goods or services</p> <p>Must be 2 decimal places. Minimum amount is 0.00 and maximum is 999999.99</p>
Y	Tax Rate	5-character decimal	tax_rate_c/tax_rate_l	<p>Contains the detailed tax rate applied in relationship to a specific tax amount</p> <p><b>EXAMPLE:</b> 5% GST should be '5.0' or 9.975% QST should be '9.975'</p> <p>May contain up to 3 decimals, minimum 0.001, maximum up to 9999.9</p>
Y	Tax Type	4-character alpha-numeric	tax_type_c/tax_type_l	Contains tax type, such as GST,QST,PST,HST
Y	Tax ID	20-character alpha-numeric	tax_id_c/tax_id_l	Provides an identification number used by the card acceptor with the tax authority in relationship to a specific tax amount, such as GST/HST number
Y	Tax included in sales indicator	1-character alpha-numeric	tax_included_in_sales_c/tax_included_in_sales_l	This is the indicator used to reflect addi-

Req*	Value	Limits	Variable	Description
				tional tax capture and reporting  Valid values are:  Y = Tax included in total purchase amount  N = Tax not included in total purchase amount

### 6.3.8.4 Sample Code for MC Corpais

#### Sample MC Corpais - Corporate Card Common Data with Line Item Details

```

package Level23;
import JavaAPI.*;
public class TestMcCorpaisCommonLineItem
{
    public static void main(String[] args)
    {
        String store_id = "moneris";
        String api_token = "hurgle";
        String processing_country_code = "CA";
        boolean status_check = false;

        String order_id="Test1485206444761";
        String txn_number="39777-1_11";
        String customer_code1_c ="CustomerCode123";
        String card_acceptor_tax_id_c ="UrTaxId";//Merchant tax id which is mandatory
        String corporation_vat_number_c ="cvn123";
        String freight_amount_c ="1.23";
        String duty_amount_c ="2.34";
        String ship_to_pos_code_c ="M1R 1W5";
        String order_date_c ="141211";
        String customer_vat_number_c ="customervn231";
        String unique_invoice_number_c ="uin567";
        String authorized_contact_name_c ="John Walker";
        //Tax Details
        String[] tax_amount_c = { "1.19", "1.29"};
        String[] tax_rate_c = { "6.0", "7.0"};
        String[] tax_type_c = { "GST", "PST"};
        String[] tax_id_c = { "gst1298", "pst1298"};
        String[] tax_included_in_sales_c = { "Y", "N"};
        //Item Details
        String[] customer_code1_l = {"customer code", "customer code2"};
        String[] line_item_date_l = {"150114", "150114"};
        String[] ship_date_l = {"150120", "150122"};
        String[] order_date1_l = {"150114", "150114"};
        String[] medical_services_ship_to_health_industry_number_l = {"", ""};
        String[] contract_number_l = {"", ""};
        String[] medical_services_adjustment_l = {"", ""};
        String[] medical_services_product_number_qualifier_l = {"", ""};
        String[] product_code1_l = {"pc11", "pc12"};
        String[] item_description_l = {"Good item", "Better item"};
    }
}

```

**Sample MC Corpais - Corporate Card Common Data with Line Item Details**

```

String[] item_quantity_l = {"4", "5"};
String[] unit_cost_l = {"1.25", "10.00"};
String[] item_unit_measure_l = {"EA", "EA"};
String[] ext_item_amount_l = {"5.00", "50.00"};
String[] discount_amount_l = {"1.00", "50.00"};
String[] commodity_code_l = {"cCode11", "cCode12"};
String[] type_of_supply_l = {"", ""};
String[] vat_ref_num_l = {"", ""};
//Tax Details for Items
String[] tax_amount_l = {"0.52", "1.48"};
String[] tax_rate_l = {"13.0", "13.0"};
String[] tax_type_l = {"HST", "HST"};
String[] tax_id_l = {"hst1298", "hst1298"};
String[] tax_included_in_sales_l = {"Y", "Y"};
//Create and set Tax for McCorpac
McTax tax_c = new McTax();
tax_c.setTax(tax_amount_c[0], tax_rate_c[0], tax_type_c[0], tax_id_c[0], tax_included_in_sales_c[0]);
tax_c.setTax(tax_amount_c[1], tax_rate_c[1], tax_type_c[1], tax_id_c[1], tax_included_in_sales_c[1]);
//Create and set McCorpac for common data - only set values that you know
McCorpac mcCorpac = new McCorpac();
mcCorpac.setCustomerCode1(customer_code1_c);
mcCorpac.setCardAcceptorTaxTd(card_acceptor_tax_id_c);
mcCorpac.setCorporationVatNumber(corporation_vat_number_c);
mcCorpac.setFreightAmount1(freight_amount_c);
mcCorpac.setDutyAmount1(duty_amount_c);
mcCorpac.setShipToPosCode(ship_to_pos_code_c);
mcCorpac.setOrderDate(order_date_c);
mcCorpac.setCustomerVatNumber(customer_vat_number_c);
mcCorpac.setUniqueInvoiceNumber(unique_invoice_number_c);
mcCorpac.setAuthorizedContactName(authorized_contact_name_c);
mcCorpac.setTax(tax_c);
//Create and set Tax for McCorpal
McTax[] tax_l = new McTax[2];
tax_l[0] = new McTax();
tax_l[0].setTax(tax_amount_l[0], tax_rate_l[0], tax_type_l[0], tax_id_l[0], tax_included_in_sales_l[0]);
tax_l[1] = new McTax();
tax_l[1].setTax(tax_amount_l[1], tax_rate_l[1], tax_type_l[1], tax_id_l[1], tax_included_in_sales_l[1]);
//Create and set McCorpal for each item
McCorpal mcCorpal = new McCorpal();
mcCorpal.setMcCorpal(customer_code1_l[0], line_item_date_l[0], ship_date_l[0], order_date1_l[0], medical_services_ship_to_health_industry_number_l[0], contract_number_l[0], medical_services_adjustment_l[0], medical_services_product_number_qualifier_l[0], product_code1_l[0], item_description_l[0], item_quantity_l[0], unit_cost_l[0], item_unit_measure_l[0], ext_item_amount_l[0], discount_amount_l[0], commodity_code_l[0], type_of_supply_l[0], vat_ref_num_l[0], tax_l[0]);
mcCorpal.setMcCorpal(customer_code1_l[1], line_item_date_l[1], ship_date_l[1], order_date1_l[1], medical_services_ship_to_health_industry_number_l[1], contract_number_l[1], medical_services_adjustment_l[1], medical_services_product_number_qualifier_l[1], product_code1_l[1], item_description_l[1], item_quantity_l[1], unit_cost_l[1], item_unit_measure_l[1], ext_item_amount_l[1], discount_amount_l[1], commodity_code_l[1], type_of_supply_l[1], vat_ref_num_l[1], tax_l[1]);
McCorpais mcCorpais = new McCorpais();
mcCorpais.setOrderId(order_id);
mcCorpais.setTxnNumber(txn_number);
mcCorpais.setMcCorpac(mcCorpac);

```

### Sample MC Corpais - Corporate Card Common Data with Line Item Details

```

mcCorpais.setMcCorpal(mccorpal);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mccorpais);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}

```

## 6.4 Level 2/3 American Express Transactions

- 1 American Express Level 2/3 Standard Transactions
- 1 American Express L23 Air and Rail Transactions

### 6.4.1 Level 2/3 Transaction Types for Amex

This transaction set includes a suite of corporate card financial transactions as well as a transaction that allows for the passing of Level 2/3 data. Please ensure American Express Level 2/3 processing support is enabled on your merchant account. Batch Close, Open Totals and Pre-authorization are identical to the transactions outlined in the section Basic Transaction Set (page 18).

- When the Pre-authorization response contains CorporateCard equal to true then you can submit the AX transactions.
- If CorporateCard is false then the card does not support Level 2/3 data and non Level 2/3 transaction are to be used. If the card is not a corporate card, please refer to 2 Basic Transaction Set for the appropriate non-corporate card transactions.

**NOTE:** This transaction set is intended for transactions where Corporate Card is true and Level 2/3 data will be submitted. If the credit card is found to be a corporate card but you do not wish to send any Level 2/3 data then you may submit AX transactions using the transaction set outlined in the section Basic Transaction Set (page 18).

#### **Pre-authorization – (authorization)**

The preauth verifies and locks funds on the customer's credit card. The funds are locked for a specified amount of time, based on the card issuer. To retrieve the funds from a pre-auth so that they may be settled in the merchant account a capture must be performed. CorporateCard will return as true if the card supports Level 2/3.

#### **AX Completion – (Capture/Pre-authorization Completion)**

Once a Pre-authorization is obtained the funds that are locked need to be retrieved from the customer's credit card. The capture retrieves the locked funds and readies them for settlement in to the merchant account. Prior to performing an AXCompletion a Preauth must be performed.

#### **AX Force Post – (Force Capture/Pre-authorization Completion)**

This transaction is an alternative to AX Completion to obtain the funds locked on a Pre-authorization obtained from IVR or equivalent terminal. The capture retrieves the locked funds and readies them for settlement in to the merchant account.

#### **AX Purchase Correction – (Void, Correction)**

AX Completion and AX Force Post can be voided the same day\* that they occur. A void must be for the full amount of the transaction and will remove any record of it from the cardholder statement. \* An AX Purchase Correction can be performed against a transaction as long as the batch that contains the original transaction remains open. When using the automated closing feature, the batch close occurs daily between 10 – 11 pm EST.


#### **AX Refund – (Credit)**

An AX Refund can be performed against an AX Completion and AX Force Post to refund any part, or all of the transaction.

**AX Independent Refund – (Credit)**

An AX Independent Refund can be performed against a purchase or a capture to refund any part, or all of the transaction. Independent refund is used when the originating transaction was not performed through Moneris Gateway. Please note, the Independent Refund transaction may or may not be supported on your account. If you receive a transaction not allowed error when attempting an independent refund, it may mean the transaction is not supported on your account. If you wish to have the AX Independent Refund transaction type temporarily enabled (or re-enabled), please contact the Service Centre at 1-866-319-7450.

## 6.4.2 Level 2/3 Transaction Flow for Amex



### 6.4.3 Level 2/3 Data Objects in Amex

- 6.4.3.1 About the Level 2/3 Data Objects for Amex
- 6.4.3.2 Definition of the AxLevel23 Object
- Table 1 Object
- Table 2 Object
- Table 3 Object

#### 6.4.3.1 About the Level 2/3 Data Objects for Amex

Many of the Level 2/3 transaction requests using American Express also include a mandatory data object called AxLevel23. AxLevel23 is also comprised of other objects, also described in this section.

The Level 2/3 data objects within this section apply to all of the following transactions and are passed as part of the transaction request for:

- AX Completion
- AX Force Post
- AX Refund
- AX Independent Refund

**Things to Consider:**

- Please ensure the addendum data below is complete and accurate.
- Please ensure the math on quantities calculations, amounts, discounts, taxes, etc. properly adds up to the overall transaction amount. Incorrect amounts will cause the transaction to be rejected.

#### 6.4.3.2 Definition of the AxLevel23 Object

##### AxLevel23 object definition

```
AxLevel23 level23 = new AxLevel23();
```

The AxLevel23 object itself has three objects, Table1, Table2 and Table3, all of which are mandatory.

**Table 1 AxLevel23 Object**

Variable Name	Type and Limits	Description	Set Method
Table1	Object	Refer below for further breakdown and definition of table1	AxTable1 table1 = new AxTable1();  level23.setTable1(table1);
Table2	Object	Refer below for further breakdown and definition of table2	AxTable2 table2 = new AxTable2();  level23.setTable2(table2);
Table3	Object	Refer below for further breakdown and definition of table3	AxTable3 table3 = new AxTable3();  level23.setTable3(table3);

**Table 1 Object**

Table 1 contains the addendum data heading information. Contains information such as identification elements that uniquely identify an invoice (transaction), the customer name and shipping address.

**Table 1 object definition**

```
AxTable1 table1 = new AxTable1();
```

**Table 1 AxLevel23 object - Table 1 object fields**

Req*	Value	Limits	Set Method	Description
C	Purchase Order Number	22-character alpha-numeric	table1.setBig04(big04);	The cardholder supplied Purchase Order Number, which is entered by the merchant at the point-of-sale  This entry is used in the Statement/Reporting process and may include accounting information specific to the client

Req*	Value	Limits	Set Method	Description
				<b>NOTE:</b> This element is mandatory, if the merchant's customer provides a Purchase Order Number.
N	Release Number	30-character alpha-numeric	table1.setBig05 (big05);	A number that identifies a release against a Purchase Order previously placed by the parties involved in the transaction
N	Invoice Number	8-character alpha-numeric	table1.setBig10 (big10);	Contains the Amex invoice/reference number
N	N1Loop	Object	table1.setN1Loop (n1Loop)	Refer below for further breakdown and definition of N1Loop object

\*Y = Required, N = Optional, C = Conditional

Table 1 also has its own objects:

- N1Loop object
- AxRef object

#### Table 1 - Setting the N1Loop Object

The N1Loop data set contains the Requester names. It can also optionally contain the buying group, ship from, ship to and receiver details.

A minimum of at least 1 n1Loop must be set. Up to 5 n1Loop can be set.

#### N1Loop object definition

```
n1Loop.setN1Loop(n101, n102, n301, n401, n402, n403, axRef1);
```

**Table 1 AxLevel23 object - Table 1 object - N1Loop object fields**

Req*	Value	Limits	Variable or Set Method	Description
Y	Entity Identifier Code	2-character alpha-numeric	n101	Supported values:

Req*	Value	Limits	Variable or Set Method	Description												
				R6 - Requester (required) BG - Buying Group (optional) SF - Ship From (optional) ST - Ship To (optional) 40 - Receiver (optional)												
Y	Name	40-character alpha-numeric	n102	<table> <thead> <tr> <th>n101 code</th> <th>n102 meaning</th> </tr> </thead> <tbody> <tr> <td>R6</td> <td>Requester Name</td> </tr> <tr> <td>BG</td> <td>Buying Group Name</td> </tr> <tr> <td>SF</td> <td>Ship From Name</td> </tr> <tr> <td>ST</td> <td>Ship To Name</td> </tr> <tr> <td>40</td> <td>Receiver Name</td> </tr> </tbody> </table>	n101 code	n102 meaning	R6	Requester Name	BG	Buying Group Name	SF	Ship From Name	ST	Ship To Name	40	Receiver Name
n101 code	n102 meaning															
R6	Requester Name															
BG	Buying Group Name															
SF	Ship From Name															
ST	Ship To Name															
40	Receiver Name															
N	Address	40-character alpha-numeric	n301	Address												
N	City	30-character alpha-numeric	n401	City												
N	State or Province	2-character alpha-numeric	n402	State or province												
N	Postal Code	15-character alpha-numeric	n403	Postal Code												
N	AxRef	Object	<pre>AxRef axRef1 = new AxRef();</pre>	<p>Refer below for further breakdown and definition of AxRef object.</p> <p>This object contains the customer postal code (mandatory) and customer reference number (optional)</p> <p>A minimum of 1 axRef1 must be set; maximum of 2 axRef1's may be set</p>												

\*Y = Required, N = Optional, C = Conditional

**Table 1 - Setting the AxRef Object****Setting AXRef object**

```
AxRef axRef1 = new AxRef();

String[] ref01 = {"4C", "CR"}; //Reference ID Qualifier

String[] ref02 = {"M5T3A5", "16802309004"}; //Reference ID

axRef1.setRef(ref01[0], ref02[0]);

axRef1.setRef(ref01[1], ref02[1]);
```

**Table 1 AxLevel23 object - Table 1 object - AxRef object fields**

Req*	Value	Limits	Variable	Description												
Y	Reference Identification Qualifier	2-character alphanumeric	ref01	<p>This element may contain the following qualifiers for the corresponding occurrences of the N1Loop:</p> <table> <thead> <tr> <th>n101 value</th> <th>ref01 denotation</th> </tr> </thead> <tbody> <tr> <td>R6</td> <td>Supported values: 4C - Shipment Destination Code (mandatory) CR - Customer Reference Number (conditional)</td> </tr> <tr> <td>BG</td> <td>n/a</td> </tr> <tr> <td>SF</td> <td>n/a</td> </tr> <tr> <td>ST</td> <td>n/a</td> </tr> <tr> <td>40</td> <td>n/a</td> </tr> </tbody> </table>	n101 value	ref01 denotation	R6	Supported values: 4C - Shipment Destination Code (mandatory) CR - Customer Reference Number (conditional)	BG	n/a	SF	n/a	ST	n/a	40	n/a
n101 value	ref01 denotation															
R6	Supported values: 4C - Shipment Destination Code (mandatory) CR - Customer Reference Number (conditional)															
BG	n/a															
SF	n/a															
ST	n/a															
40	n/a															
Y	Reference Identification	15-character alphanumeric	ref02	This field must be populated for each ref01 provided												

Req*	Value	Limits	Variable	Description
				<p style="text-align: center;"><b>ref01 value</b>      <b>ref02 denotation</b></p> <hr/> <p>4C (n101 value = R6) This element must contain the Amex Ship-to Postal Code of the destination where the commodity was shipped. If the Ship-to Postal Code is unavailable, the postal code of the merchant location where the transaction took place may be substituted.</p> <hr/> <p>CR (n101 value = R6): This element must contain the Amex Card member Reference Number (e.g., purchase order, cost center, project number, etc.) that corresponds to this transaction, if provided by the Cardholder.</p> <p>This information may be displayed in the statement/reporting process and may include client-specific accounting information.</p>

\*Y = Required, N = Optional, C = Conditional

#### Table 2 Object

Table 2 includes the transaction's addendum detail. It contains transaction data including reference codes, debit or credit and tax amounts, line item detail descriptions, shipping information and much more. All transaction data in an invoice relate to a single transaction and cardholder account number.

#### Table 2 object definition

```
AxTable2 table2 = new AxTable2();
```

**Table 1 AxLevel23 object - Table 2 object fields**

Req*	Value	Limits	Set Method	Description
N	It1loop	Object	table2.setIt1Loop(it1Loop);	Refer below for further break-down and definition of object details.

\*Y = Required, N = Optional, C = Conditional

**Table 2 - Setting the AxIt1Loop Object**

The AxIt1Loop data defines the baseline item data for the invoice. This data is defined for each item/service purchased and included within this invoice. This data set contains basic transaction data, including quantity, unit of measure, unit price and goods/services reference information.

- A minimum of 1 it1Loop required
- A maximum of 999 it1Loop's supported

### AxIt1Loop object definition

```
AxIt1Loop it1Loop = new AxIt1Loop();

it1Loop.setIt1Loop(it102[0], it103[0], it104[0], it105[0], it106s[0], txi[0],
pam05[0], pid05[0]);

it1Loop.setIt1Loop(it102[1], it103[1], it104[1], it105[1], it106s[1], txi[1],
pam05[1], pid05[1]);
```

**Table 1 AxLevel23 object - Table 2 object - AxIt1Loop object fields**

Req*	Value	Limits	Variable	Description
Y	Line Item Quantity Invoiced	10-character decimal	it102	Quantity of line item Up to 2 decimal places supported Minimum amount is 0.0 and maximum is 9999999999

Req*	Value	Limits	Variable	Description
Y	Unit or Basis for Measurement Code	2-character alpha-numeric	it103	<p>The line item unit of measurement code</p> <p>Must contain a code that specifies the units in which the value is expressed or the manner in which a measurement is taken</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> EA = each, E5=inches         </div> <p>See <a href="#">ANSI X-12 EDI Allowable Units of Measure and Codes</a> for the list of codes</p>
Y	Unit Price	15-character decimal	it104	<p>Line item cost per unit</p> <p>Must contain 2 decimal places</p> <p>Minimum amount is 0.00 and maximum is 999999.99</p>
N	Basis or Unit Price Code	2-character alpha-numeric	it105	<p>Code identifying the type of unit price for an item</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> DR = dealer, AP = advise price         </div> <p>See <a href="#">ASC X12 004010 Element</a></p>

Req*	Value	Limits	Variable	Description
				<a href="#">639</a> for list of codes
N	AxIt106s	object	it106s	Refer below for further break-down and definition of object details.
N	AxTxi	object	txi	Refer below for further break-down and definition of object details  A maximum of 12 AxTxi (tax information data sets) may be defined
<p><b>NOTE:</b> that if line item level tax information is populated in AxTxi in Table2, then tax totals for the entire invoice (transaction) must be entered in Table3.</p>				
Y	Line Item Extended Amount	8-character decimal	pam05	Contains the individual item amount that is normally calculated as price multiplied by quantity  Must contain 2 decimal places  Minimum amount is 0.00 and max-

Req*	Value	Limits	Variable	Description
				imum is 99999.99
Y	Line Item Description	80-character alphanumeric	pid05	<p>Line Item description</p> <p>Contains the description of the individual item purchased</p> <p>This field pertain to each line item in the transaction</p>

\*Y = Required, N = Optional, C = Conditional

**Table 2 - Setting the AxIt106s Object**

```
AxIt106s[] it106s = {new AxIt106s(), new AxIt106s(), new AxIt106s(), new AxIt106s(), new AxIt106s()};

String[] it10618 = {"MG", "MG", "MG", "MG", "MG"}; //Product/Service ID
qualifier

String[] it10719 = {"DJFR4", "JFJ49", "FEF33", "FEE43", "DISCOUNT"};
//Product/Service ID (corresponds to it10618)
```

**Table 1 AxLevel23 object - Table 2 object - AxIt106s object fields**

Req*	Value	Limits	Set Method	Description
N	Product/Service ID Qualifier	2-character alphanumeric	<pre>it106s [0].setIt10618 (it10618[0]);</pre> <pre>it106s [1].setIt10618 (it10618[1]);</pre>	<p>Supported values:</p> <p>MG - Manufacturer's Part Number</p> <p>VC - Supplier Catalog Number</p> <p>SK - Supplier Stock Keeping Unit Number</p> <p>UP - Universal Product Code</p> <p>VP – Vendor Part Number</p> <p>PO – Purchase Order Number</p>

Req*	Value	Limits	Set Method	Description
				AN – Client Defined Asset Code
N	Product/Service ID	<b>it10618</b> <b>it10719 - size/type</b> <hr/> VC                  20-character alphanumeric <hr/> PO                  22-character alphanumeric <hr/> Other                30-character alphanumeric	it106s [0].setIt10719 (it10719[0]);  it106s [1].setIt10719 (it10719[1]);	Product/Service ID corresponds to the preceding qualifier defined by it10618  The maximum length depends on the qualifier defined in it10618

\*Y = Required, N = Optional, C = Conditional

Table 2 - Setting the AxTxi Object

### Table 2 AxiTxi object definition

```
//Create Table 2 with details

String[] txi01_GST = {"GS", "GS", "GS", "GS", "GS"}; //Tax type code
String[] txi02_GST = {"0.70", "1.75", "1.00", "0.80", "0.00"}; //Monetary amount

String[] txi03_GST = {"5.0", "5.0", "5.0", "5.0", "5.0"}; //Percent

String[] txi06_GST = {"2", "2", "2", "2", "2"}; //Tax exempt code

String[] txi01_PST = {"PG", "PG", "PG", "PG", "PG"}; //Tax type code
String[] txi02_PST = {"0.80", "2.00", "1.00", "0.80", "0.00"}; //Monetary amount

String[] txi03_PST = {"7.0", "7.0", "7.0", "7.0", "7.0"}; //Percent

String[] txi06_PST = {"2", "2", "2", "2", "2"}; //Tax exempt code


AxTxi[] txi = {new AxTxi(), new AxTxi(), new AxTxi(), new AxTxi(), new AxTxi()};

txi[0].setTxi(txi01_GST[0], txi02_GST[0], txi03_GST[0], txi06_GST[0]);
txi[0].setTxi(txi01_PST[0], txi02_PST[0], txi03_PST[0], txi06_PST[0]);
txi[1].setTxi(txi01_GST[1], txi02_GST[1], txi03_GST[1], txi06_GST[1]);
txi[1].setTxi(txi01_PST[1], txi02_PST[1], txi03_PST[1], txi06_PST[1]);
```

```

txi[2].setTxi(txio1_GST[2], txio2_GST[2], txio3_GST[2], txio6_GST[2]);
txi[2].setTxi(txio1_PST[2], txio2_PST[2], txio3_PST[2], txio6_PST[2]);
txi[3].setTxi(txio1_GST[3], txio2_GST[3], txio3_GST[3], txio6_GST[3]);
txi[3].setTxi(txio1_PST[3], txio2_PST[3], txio3_PST[3], txio6_PST[3]);
txi[4].setTxi(txio1_GST[4], txio2_GST[4], txio3_GST[4], txio6_GST[4]);
txi[4].setTxi(txio1_PST[4], txio2_PST[4], txio3_PST[4], txio6_PST[4]);

```

**Table 1 AxLevel23 object - Table 2 object - AxiTxi object fields**

Req*	Value	Limits	Variable	Description
C	Tax Type code	txi01	2-character alpha-numeric	<p>Tax type code applicable to Canada and US only</p> <p>For Canada, this field must contain a code that specifies the type of tax</p> <p>If txi01 is used, then txi02, txi03 or txi06 must be populated</p> <p>Valid codes include the following:</p> <ul style="list-style-type: none"> <li>CT – County/Tax (optional)</li> <li>CA – City Tax (optional)</li> <li>EV – Environmental Tax (optional)</li> <li>GS – Good and Services Tax (GST) (optional)</li> <li>LS – State and Local Sales Tax (optional)</li> <li>LT – Local Sales Tax</li> </ul>

Req*	Value	Limits	Variable	Description
				<p>(optional)</p> <p>PG – Provincial Sales Tax (PST) (optional)</p> <p>SP – State/Provincial Tax a.k.a. Quebec Sales Tax (QST) (optional)</p> <p>ST – State Sales Tax (optional)</p> <p>TX – All Taxes (required)</p> <p>VA – Value-Added Tax a.k.a. Canadian Harmonized Sales Tax (HST) (optional)</p>
C	Monetary Amount	txi02	6-character decimal	<p>This element may contain the monetary tax amount that corresponds to the Tax Type Code in txi01</p> <div data-bbox="1199 1172 1411 1573" style="border: 1px solid #ccc; padding: 10px;"> <p><b>NOTE:</b> If txi02 is used in mandatory occurrence txi01=TX, txi02 must contain the total tax amount applicable to the entire invoice (transaction) If taxes are not applicable for the entire invoice (transaction), txi02 must be 0.00.</p> </div> <p>The maximum value that can be entered in this field is “9999.99”, which is \$9,999.99 (CAD)</p> <p>A debit is entered</p>

Req*	Value	Limits	Variable	Description
				as: 9999.99  A credit is entered as: – 9999.99
C	Percent	txi03	10-character decimal	Contains the tax percentage (in decimal format) that corresponds to the tax type code defined in txi01  Up to 2 decimal places supported
C	Tax Exempt Code	txi06	1-character alpha-numeric	This element may contain the Tax Exempt Code that identifies the exemption status from sales and tax that corresponds to the Tax Type Code in txi01  Supported values:  1 – Yes (Tax Exempt) 2 – No (Not Tax Exempt) 4 – Not Exempt/For Resale A – Labor Taxable, Material Exempt B – Material Taxable, Labor Exempt C – Not Taxable F – Exempt (Goods /

Req*	Value	Limits	Variable	Description
				Services Tax) G – Exempt (Provincial Sales Tax) L – Exempt Local Service R – Recurring Exempt U – Usage Exempt

\*Y = Required, N = Optional, C = Conditional

### Table 3 Object

Table 3 includes the transaction addendum summary. It contains the total invoice (transaction) amount, sales tax, freight and/or handling charges and invoice summary information, including total line items, number of segments in the invoice, and the transaction set control number (a.k.a., batch number).

### Table 3 object definition

```
AxTable3 table3 = new AxTable3();
```

**Table 1 AxLevel23 object - Table 3 object fields**

Req*	Value	Limits	Set Method	Description
C	AxTaxi	Object	table3.setTaxi(taxTbl3);	Refer below for further breakdown and definition of object details. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> if line item level tax information is populated in AxTaxi in Table2, then tax totals for the entire invoice (transaction) must be entered in Table3. A maximum of 10         </div>

Req*	Value	Limits	Set Method	Description
				AxTxi's may be set in Table3.

\*Y = Required, N = Optional, C = Conditional

[Table 3 - Setting the AxTxi Object](#)

The mandatory tax information data set must contain the total tax amount applicable to the entire invoice (transaction) which includes all line items identified in Table2. If taxes are not applicable for the entire invoice (transaction), then txi02 must be set to 0.00.

Tax totals must be entered in this mandatory tax information segment in Table 3, even if line item detail level tax data is reported in Table 2.

At least one occurrence of txi02, txi03 or txi06 is required.

### Table 3 AxiTxi object definition

```
AxTxi taxTbl3 = new AxTxi();

taxTbl3.setTxi("GS", "4.25","",""); //sum of GST taxes
taxTbl3.setTxi("PG", "4.60","",""); //sum of PST taxes
taxTbl3.setTxi("TX", "8.85","",""); //sum of all taxes
```

[Table 1 AxLevel23 object - Table 3 object - AxiTxi object fields](#)

Req*	Value	Limits	Variable	Description
C	Tax Type code	txi01	2-character alpha-numeric	<p>Tax type code applicable to Canada and US only</p> <p>For Canada, this field must contain a code that specifies the type of tax</p> <p>If txi01 is used, then txi02, txi03 or txi06 must be populated</p> <p>Valid codes</p>

Req*	Value	Limits	Variable	Description
				<p>include the following:</p> <p>CT – County/Tax (optional)</p> <p>CA – City Tax (optional)</p> <p>EV – Environmental Tax (optional)</p> <p>GS – Good and Services Tax (GST) (optional)</p> <p>LS – State and Local Sales Tax (optional)</p> <p>LT – Local Sales Tax (optional)</p> <p>PG – Provincial Sales Tax (PST) (optional)</p> <p>SP – State/Provincial Tax a.k.a. Quebec Sales Tax (QST) (optional)</p> <p>ST – State Sales Tax (optional)</p> <p>TX – All Taxes (required)</p> <p>VA – Value-Added Tax a.k.a. Canadian Harmonized Sales Tax (HST) (optional)</p>
C	Monetary Amount	txi02	6-character decimal	<p>This element may contain the monetary tax amount that corresponds to the Tax Type Code in txi01</p> <div data-bbox="1199 1763 1411 1879" style="border: 1px solid #0070C0; padding: 5px; background-color: #E0F2F1;"> <b>NOTE:</b>            If txi02 is used in mandatory occur-         </div>

Req*	Value	Limits	Variable	Description
				<p>rence txi01=TX, txi02 must contain the total tax amount applicable to the entire invoice (transaction)</p> <p>If taxes are not applicable for the entire invoice (transaction), txi02 must be 0.00.</p> <p>The maximum value that can be entered in this field is "9999.99", which is \$9,999.99 (CAD)</p> <p>A debit is entered as: 9999.99</p> <p>A credit is entered as: -9999.99</p>
C	Percent	txi03	10-character decimal	<p>Contains the tax percentage (in decimal format) that corresponds to the tax type code defined in txi01</p> <p>Up to 2 decimal places supported</p>
C	Tax Exempt Code	txi06	1-character alpha-numeric	<p>This element may contain the Tax Exempt Code that identifies the exemption status from sales and tax that corresponds to the Tax Type Code in</p>

Req*	Value	Limits	Variable	Description
				txi01 Supported values: 1 – Yes (Tax Exempt) 2 – No (Not Tax Exempt) 4 – Not Exempt/For Resale A – Labor Taxable, Material Exempt B – Material Taxable, Labor Exempt C – Not Taxable F – Exempt (Goods / Services Tax) G – Exempt (Provincial Sales Tax) L – Exempt Local Service R – Recurring Exempt U – Usage Exempt

\*Y = Required, N = Optional, C = Conditional

#### 6.4.4 AX Completion

The AX Completion transaction is used to secure the funds locked by a pre-authorization transaction. When sending a capture request you will need two pieces of information from the original pre-authorization – the Order ID and the transaction number from the returned response.

##### AX Completion transaction object definition

```
AxCompletion axCompletion = new AxCompletion()
```

##### HttpsPostRequest object for AX Completion

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
```

```
mpgReq.setTransaction(axCompletion);
```

### AX Completion transaction request fields – Required

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	<code>axCompletion.setOrderId(order_id);</code>
Completion amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	<code>axCompletion.setCompAmount(comp_amount);</code>
<b>EXAMPLE:</b> 1234567.89		
Transaction number	<i>String</i> 255-character alpha- numeric	<code>axCompletion.setTxnNumber(txn_number);</code>
E-commerce indicator	<i>String</i>  1-character alphanumeric	<code>axCompletion.setCryptType(crypt);</code>
Level 2/3 Data	<i>Object</i> n/a	<code>axCompletion.setAxLevel23(level23);</code>

#### Sample AX Completion

```
package Level23;
import JavaAPI.*;

public class TestAxCompletion
{
  public static void main(String[] args)
  {
    String store_id = "moneris";
    String api_token = "hurgle";
    String processing_country_code = "CA";
    boolean status_check = false;
```

### Sample AX Completion

```

String order_id="ord-210916-12:06:38";
String comp_amount="62.37";
String txn_number = "18924-0_11";
String crypt="7";

//Create Table 1 with details
String n101 = "R6"; //Entity ID Code
String n102 = "Retailing Inc. International"; //Name
String n301 = "919 Oriole Rd."; //Address Line 1
String n401 = "Toronto"; //City
String n402 = "On"; //State or Province
String n403 = "H1T6W3"; //Postal Code
String[] ref01 = {"4C", "CR"}; //Reference ID Qualifier
String[] ref02 = {"M5T3A5", "16802309004"}; //Reference ID
String big04 = "PO7758545"; //Purchase Order Number
String big05 = "RN0049858"; //Release Number
String big10 = "INV99870E"; //Invoice Number
AxRef axRef1 = new AxRef();
axRef1.setRef(ref01[0], ref02[0]);
axRef1.setRef(ref01[1], ref02[1]);
AxN1Loop n1Loop = new AxN1Loop();
n1Loop.setN1Loop(n101, n102, n301, n401, n402, n403, axRef1);
AxTable1 table1 = new AxTable1();
table1.setBig04(big04);
table1.setBig05(big05);
table1.setBig10(big10);
table1.setN1Loop(n1Loop);

//Create Table 2 with details
//the sum of the extended amount field (pam05) must equal the level 1 amount field
String[] it102 = {"1", "1", "1", "1", "1"}; //Line item quantity invoiced
String[] it103 = {"EA", "EA", "EA", "EA", "EA"}; //Line item unit or basis of measurement
code
String[] it104 = {"10.00", "25.00", "8.62", "10.00", "-10.00"}; //Line item unit price
String[] it105 = {"", "", "", "", ""}; //Line item basis of unit price code

String[] it10618 = {"MG", "MG", "MG", "MG"}; //Product/Service ID qualifier
String[] it10719 = {"DJFR4", "JFJ49", "FEF33", "FEE43", "DISCOUNT"}; //Product/Service ID
(corresponds to it10618)

String[] txi01_GST = {"GS", "GS", "GS", "GS"}; //Tax type code
String[] txi02_GST = {"0.70", "1.75", "1.00", "0.80", "0.00"}; //Monetary amount
String[] txi03_GST = {"", "", "", "", ""}; //Percent
String[] txi06_GST = {"", "", "", "", ""}; //Tax exempt code

String[] txi01_PST = {"PG", "PG", "PG", "PG"}; //Tax type code
String[] txi02_PST = {"0.80", "2.00", "1.00", "0.80", "0.00"}; //Monetary amount
String[] txi03_PST = {"", "", "", "", ""}; //Percent
String[] txi06_PST = {"", "", "", "", ""}; //Tax exempt code
String[] pam05 = {"11.50", "28.75", "10.62", "11.50", "-10.00"}; //Extended line-item
amount
String[] pid05 = {"Stapler", "Lamp", "Bottled Water", "Fountain Pen", "DISCOUNT"}; //Line
item description
AxIt106s[] it106s = {new AxIt106s(), new AxIt106s(), new AxIt106s(), new AxIt106s(), new
AxIt106s()};

it106s[0].setIt10618(it10618[0]);
it106s[0].setIt10719(it10719[0]);

```

### Sample AX Completion

```

it106s[1].setIt10618(it10618[1]);
it106s[1].setIt10719(it10719[1]);

it106s[2].setIt10618(it10618[2]);
it106s[2].setIt10719(it10719[2]);

it106s[3].setIt10618(it10618[3]);
it106s[3].setIt10719(it10719[3]);

it106s[4].setIt10618(it10618[4]);
it106s[4].setIt10719(it10719[4]);
AxTxi[] txi = {new AxTxi(), new AxTxi(), new AxTxi(), new AxTxi(), new AxTxi()};
txi[0].setTxi(txio1_GST[0], txio2_GST[0], txio3_GST[0], txio6_GST[0]);
txi[0].setTxi(txio1_PST[0], txio2_PST[0], txio3_PST[0], txio6_PST[0]);
txi[1].setTxi(txio1_GST[1], txio2_GST[1], txio3_GST[1], txio6_GST[1]);
txi[1].setTxi(txio1_PST[1], txio2_PST[1], txio3_PST[1], txio6_PST[1]);
txi[2].setTxi(txio1_GST[2], txio2_GST[2], txio3_GST[2], txio6_GST[2]);
txi[2].setTxi(txio1_PST[2], txio2_PST[2], txio3_PST[2], txio6_PST[2]);
txi[3].setTxi(txio1_GST[3], txio2_GST[3], txio3_GST[3], txio6_GST[3]);
txi[3].setTxi(txio1_PST[3], txio2_PST[3], txio3_PST[3], txio6_PST[3]);
txi[4].setTxi(txio1_GST[4], txio2_GST[4], txio3_GST[4], txio6_GST[4]);
txi[4].setTxi(txio1_PST[4], txio2_PST[4], txio3_PST[4], txio6_PST[4]);
AxIt1Loop it1Loop = new AxIt1Loop();
it1Loop.setIt1Loop(it102[0], it103[0], it104[0], it105[0], it106s[0], txi[0], pam05[0],
pid05[0]);
it1Loop.setIt1Loop(it102[1], it103[1], it104[1], it105[1], it106s[1], txi[1], pam05[1],
pid05[1]);
it1Loop.setIt1Loop(it102[2], it103[2], it104[2], it105[2], it106s[2], txi[2], pam05[2],
pid05[2]);
it1Loop.setIt1Loop(it102[3], it103[3], it104[3], it105[3], it106s[3], txi[3], pam05[3],
pid05[3]);
it1Loop.setIt1Loop(it102[4], it103[4], it104[4], it105[4], it106s[4], txi[4], pam05[4],
pid05[4]);
AxTable2 table2 = new AxTable2();
table2.setIt1Loop(it1Loop);
//Create Table 3 with details
AxTxi taxTbl3 = new AxTxi();
taxTbl3.setTxi("GS", "4.25","",""); //sum of GST taxes
taxTbl3.setTxi("PG", "4.60","",""); //sum of PST taxes
taxTbl3.setTxi("TX", "8.85","",""); //sum of all taxes
AxTable3 table3 = new AxTable3();
table3.setTxi(taxTbl3);

//Create and set Level23 Object
AxLevel23 level23 = new AxLevel23();
level23.setTable1(table1);
level23.setTable2(table2);
level23.setTable3(table3);
AxCompletion axCompletion = new AxCompletion();
axCompletion.setOrderId(order_id);
axCompletion.setCompAmount(comp_amount);
axCompletion.setTxnNumber(txn_number);
axCompletion.setCryptType(crypt);
axCompletion.setAxLevel23(level23);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);

```

### Sample AX Completion

```

mpgReq.setTransaction(axCompletion);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
    Receipt receipt = mpgReq.getReceipt();
    System.out.println("CardType = " + receipt.getCardType());
    System.out.println("TransAmount = " + receipt.getTransAmount());
    System.out.println("TxnNumber = " + receipt.getTxnNumber());
    System.out.println("ReceiptId = " + receipt.getReceiptId());
    System.out.println("TransType = " + receipt.getTransType());
    System.out.println("ReferenceNum = " + receipt.getReferenceNum());
    System.out.println("ResponseCode = " + receipt.getResponseCode());
    System.out.println("ISO = " + receipt.getISO());
    System.out.println("BankTotals = " + receipt.getBankTotals());
    System.out.println("Message = " + receipt.getMessage());
    System.out.println("AuthCode = " + receipt.getAuthCode());
    System.out.println("Complete = " + receipt.getComplete());
    System.out.println("TransDate = " + receipt.getTransDate());
    System.out.println("TransTime = " + receipt.getTransTime());
    System.out.println("Ticket = " + receipt.getTicket());
    System.out.println("TimedOut = " + receipt.getTimedOut());
    System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
    System.out.println(e);
}
}
}

```

## 6.4.5 AX Force Post

The AX Force Post transaction is used to secure the funds locked by a pre-authorization transaction performed over IVR or equivalent terminal. When sending an AX Force Post request, you will need the order ID, amount, credit card number, expiry date, authorization code and e-commerce indicator.

### AX Force Post transaction object definition

```
AxForcePost axForcePost = new AxForcePost();
```

### HttpsPostRequest object for AX Force Post transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(axForcePost);
```

### AX Force Post transaction request fields – Required

Value	Limits	Set Method
Order ID	<i>String</i>	axForcePost.setOrderId(order_id);

Value	Limits	Set Method
	50-character alphanumeric	
Amount	<p><i>String</i></p> <p>10-character decimal</p> <p>Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point</p>	<pre>axForcePost.setAmount(amount);</pre>
	<b>EXAMPLE:</b> 1234567.89	
Credit card number	<p><i>String</i></p> <p>20-character alphanumeric</p>	<pre>axForcePost.setPan(pan);</pre>
Expiry date	<p><i>String</i></p> <p>4-character alphanumeric (YYMM format)</p>	<pre>axForcePost.setExpDate(expiry_date);</pre>
Authorization code	<p><i>String</i></p> <p>8-character alphanumeric</p>	<pre>axForcePost.setAuthCode(auth_code);</pre>
E-commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	<pre>axForcePost.setCryptType(crypt);</pre>
Level 2/3 Data	<p><i>Object</i></p> <p>n/a</p>	<pre>axForcePost.setAxLevel23(level23);</pre>

### AX Force Post transaction request fields – Optional

Variable Name	Type and Limits	Set Method
Customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p>	<pre>axForcePost.setCustId(cust_id);</pre>

### Sample AX Force Post

```

package Level23;
import JavaAPI.*;

public class TestAxForcePost
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

java.util.Date createDate = new java.util.Date();
String order_id="Test"+createDate.getTime();
String cust_id="CUST13343";
String amount="62.37";
String pan="373269005095005";
String expiry_date="2012"; //YYMM
String auth_code="123456";
String crypt="7";

//Create Table 1 with details
String n101 = "R6"; //Entity ID Code
String n102 = "Retailing Inc. International"; //Name
String n301 = "919 Oriole Rd."; //Address Line 1
String n401 = "Toronto"; //City
String n402 = "On"; //State or Province
String n403 = "H1T6W3"; //Postal Code
String[] ref01 = {"4C", "CR"}; //Reference ID Qualifier
String[] ref02 = {"M5T3A5", "16802309004"}; //Reference ID
String big04 = "PO7758545"; //Purchase Order Number
String big05 = "RN0049858"; //Release Number
String big10 = "INV99870E"; //Invoice Number
AxRef axRef1 = new AxRef();
axRef1.setRef(ref01[0], ref02[0]);
axRef1.setRef(ref01[1], ref02[1]);
AxN1Loop n1Loop = new AxN1Loop();
n1Loop.setN1Loop(n101, n102, n301, n401, n402, n403, axRef1);
AxTable1 table1 = new AxTable1();
table1.setBig04(big04);
table1.setBig05(big05);
table1.setBig10(big10);
table1.setN1Loop(n1Loop);

//Create Table 2 with details
//the sum of the extended amount field (pam05) must equal the level 1 amount field

String[] it102 = {"1", "1", "1", "1", "1"}; //Line item quantity invoiced
String[] it103 = {"EA", "EA", "EA", "EA", "EA"}; //Line item unit or basis of measurement
code
String[] it104 = {"10.00", "25.00", "8.62", "10.00", "-10.00"}; //Line item unit price
String[] it105 = {"", "", "", "", ""}; //Line item basis of unit price code

String[] it10618 = {"MG", "MG", "MG", "MG", "MG"}; //Product/Service ID qualifier
String[] it10719 = {"DJF4R4", "JFJ49", "FEF33", "FEE43", "DISCOUNT"}; //Product/Service ID
(corresponds to it10618)

String[] txi01_GST = {"GS", "GS", "GS", "GS", "GS"}; //Tax type code
String[] txi02_GST = {"0.70", "1.75", "1.00", "0.80","0.00"}; //Monetary amount

```

**Sample AX Force Post**

```

String[] txi03_GST = {"", "", "", "", ""}; //Percent
String[] txi06_GST = {"", "", "", "", ""}; //Tax exempt code

String[] txi01_PST = {"PG", "PG", "PG", "PG"}; //Tax type code
String[] txi02_PST = {"0.80", "2.00", "1.00", "0.80", "0.00"}; //Monetary amount
String[] txi03_PST = {"", "", "", "", ""}; //Percent
String[] txi06_PST = {"", "", "", "", ""}; //Tax exempt code
String[] pam05 = {"11.50", "28.75", "10.62", "11.50", "-10.00"}; //Extended line-item
amount
String[] pid05 = {"Stapler", "Lamp", "Bottled Water", "Fountain Pen", "DISCOUNT"}; //Line
item description
AxIt106s[] it106s = {new AxIt106s(), new AxIt106s(), new AxIt106s(), new AxIt106s(), new
AxIt106s()};

it106s[0].setIt10618(it10618[0]);
it106s[0].setIt10719(it10719[0]);

it106s[1].setIt10618(it10618[1]);
it106s[1].setIt10719(it10719[1]);

it106s[2].setIt10618(it10618[2]);
it106s[2].setIt10719(it10719[2]);

it106s[3].setIt10618(it10618[3]);
it106s[3].setIt10719(it10719[3]);

it106s[4].setIt10618(it10618[4]);
it106s[4].setIt10719(it10719[4]);
AxTxi[] txi = {new AxTxi(), new AxTxi(), new AxTxi(), new AxTxi(), new AxTxi()};
txi[0].setTxi(txi01_GST[0], txi02_GST[0], txi03_GST[0], txi06_GST[0]);
txi[0].setTxi(txi01_PST[0], txi02_PST[0], txi03_PST[0], txi06_PST[0]);
txi[1].setTxi(txi01_GST[1], txi02_GST[1], txi03_GST[1], txi06_GST[1]);
txi[1].setTxi(txi01_PST[1], txi02_PST[1], txi03_PST[1], txi06_PST[1]);
txi[2].setTxi(txi01_GST[2], txi02_GST[2], txi03_GST[2], txi06_GST[2]);
txi[2].setTxi(txi01_PST[2], txi02_PST[2], txi03_PST[2], txi06_PST[2]);
txi[3].setTxi(txi01_GST[3], txi02_GST[3], txi03_GST[3], txi06_GST[3]);
txi[3].setTxi(txi01_PST[3], txi02_PST[3], txi03_PST[3], txi06_PST[3]);
txi[4].setTxi(txi01_GST[4], txi02_GST[4], txi03_GST[4], txi06_GST[4]);
txi[4].setTxi(txi01_PST[4], txi02_PST[4], txi03_PST[4], txi06_PST[4]);
AxIt1Loop it1Loop = new AxIt1Loop();
it1Loop.setIt1Loop(it102[0], it103[0], it104[0], it105[0], it106s[0], txi[0], pam05[0],
pid05[0]);
it1Loop.setIt1Loop(it102[1], it103[1], it104[1], it105[1], it106s[1], txi[1], pam05[1],
pid05[1]);
it1Loop.setIt1Loop(it102[2], it103[2], it104[2], it105[2], it106s[2], txi[2], pam05[2],
pid05[2]);
it1Loop.setIt1Loop(it102[3], it103[3], it104[3], it105[3], it106s[3], txi[3], pam05[3],
pid05[3]);
it1Loop.setIt1Loop(it102[4], it103[4], it104[4], it105[4], it106s[4], txi[4], pam05[4],
pid05[4]);
AxTable2 table2 = new AxTable2();
table2.setIt1Loop(it1Loop);
//Create Table 3 with details
AxTxi taxTbl3 = new AxTxi();
taxTbl3.setTxi("GS", "4.25", "", ""); //sum of GST taxes
taxTbl3.setTxi("PG", "4.60", "", ""); //sum of PST taxes
taxTbl3.setTxi("TX", "8.85", "", ""); //sum of all taxes
AxTable3 table3 = new AxTable3();
table3.setTxi(taxTbl3);

```

### Sample AX Force Post

```

AxLevel23 level23 = new AxLevel23();
level23.setTable1(table1);
level23.setTable2(table2);
level23.setTable3(table3);
AxForcePost axForcePost = new AxForcePost();
axForcePost.setOrderId(order_id);
axForcePost.setCustId(cust_id);
axForcePost.setAmount(amount);
axForcePost.setPan(pan);
axForcePost.setExpDate(expiry_date);
axForcePost.setAuthCode(auth_code);
axForcePost.setCryptType(crypt);
axForcePost.setAxLevel23(level23);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(axForcePost);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();

System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}

```

#### 6.4.6 AX Purchase Correction

The AX Purchase Correction (Void) transaction is used to cancel a transaction that was performed in the current batch. No amount is required because a void is always for 100% of the original transaction. The

only transaction that can be voided using AX Purchase Correction is AX Completion and AX Force Post. To send an AX Purchase Correction the Order ID and transaction number from the AX Completion or AX Force Post are required.

### **AX Purchase Correction transaction object definition**

```
AxPurchaseCorrection axPurchaseCorrection = new AxPurchaseCorrection();
```

### **HttpsPostRequest object for AX Purchase Correction transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(axPurchaseCorrection);
```

### **AX Purchase Correction transaction request fields – Required**

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	axPurchaseCorrection.setOrderId(order_id);
Transaction number	<i>String</i> 255-character alphanumeric	axPurchaseCorrection.setTxnNumber(txn_number);
E-commerce indicator	<i>String</i> 1-character alphanumeric	axPurchaseCorrection.setCryptType(crypt);

### **AX Purchase Correction**

```
package Level23;
import JavaAPI.*;

public class TestAxPurchaseCorrection
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

String order_id="Test1485206180427";
String txn_number = "660117311902017023161620759-0_11";
String crypt="7";
AxPurchaseCorrection axPurchaseCorrection = new AxPurchaseCorrection();
axPurchaseCorrection.setOrderId(order_id);
axPurchaseCorrection.setTxnNumber(txn_number);
```

### AX Purchase Correction

```

axPurchaseCorrection.setCryptType(crypt);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(axPurchaseCorrection);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}

```

## 6.4.7 AX Refund

The AX Refund will credit a specified amount to the cardholder's credit card. A refund can be sent up to the full value of the original AX Completion or AX Force Post. To send an AX Refund you will require the order ID and transaction number from the original AX Completion or AX Force Post.

### **AX Refund transaction object definition**

```
AxRefund axRefund = new AxRefund();
```

### **HttpsPostRequest object for AX Refund transaction**

```

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(axRefund);

```

## AX Refund transaction request fields – Required

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	<code>axRefund.setOrderId(order_id);</code>
Transaction number	<i>String</i> 255-character alpha-numeric	<code>axRefund.setTxnNumber(txn_number);</code>
Amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	<code>axRefund.setAmount(amount);</code>
<b>EXAMPLE:</b> 1234567.89		
E-commerce indicator	<i>String</i> 1-character alphanumeric	<code>axRefund.setCryptType(crypt);</code>
Level 2/3 Data	<i>Object</i> n/a	<code>axRefund.setAxLevel23(level23);</code>

### Sample AX Refund

```

package Level23;
import JavaAPI.*;
public class TestAxRefund
{
  public static void main(String[] args)
  {
    String store_id = "moneris";
    String api_token = "hurgle";
    String processing_country_code = "CA";
    boolean status_check = false;

    String order_id="Test1485206231878";
    String amount="62.37";
    String txn_number = "660117311902017023161712265-0_11";
  }
}

```

### Sample AX Refund

```

String crypt="7";

//Create Table 1 with details
String n101 = "R6"; //Entity ID Code
String n102 = "Retailing Inc. International"; //Name
String n301 = "919 Oriole Rd."; //Address Line 1
String n401 = "Toronto"; //City
String n402 = "On"; //State or Province
String n403 = "H1T6W3"; //Postal Code
String[] ref01 = {"4C", "CR"}; //Reference ID Qualifier
String[] ref02 = {"M5T3A5", "16802309004"}; //Reference ID
String big04 = "PO7758545"; //Purchase Order Number
String big05 = "RN0049858"; //Release Number
String big10 = "INV99870E"; //Invoice Number
AxRef axRef1 = new AxRef();
axRef1.setRef(ref01[0], ref02[0]);
axRef1.setRef(ref01[1], ref02[1]);
AxN1Loop n1Loop = new AxN1Loop();
n1Loop.setN1Loop(n101, n102, n301, n401, n402, n403, axRef1);
AxTable1 table1 = new AxTable1();
table1.setBig04(big04);
table1.setBig05(big05);
table1.setBig10(big10);
table1.setN1Loop(n1Loop);

//Create Table 2 with details
//the sum of the extended amount field (pam05) must equal the level 1 amount field
String[] it102 = {"1", "1", "1", "1", "1"}; //Line item quantity invoiced
String[] it103 = {"EA", "EA", "EA", "EA", "EA"}; //Line item unit or basis of measurement
code
String[] it104 = {"10.00", "25.00", "8.62", "10.00", "-10.00"}; //Line item unit price
String[] it105 = {"", "", "", "", ""}; //Line item basis of unit price code

String[] it10618 = {"MG", "MG", "MG", "MG", "MG"}; //Product/Service ID qualifier
String[] it10719 = {"DJFR4", "JFJ49", "FEF33", "FEE43", "DISCOUNT"}; //Product/Service ID
(corresponds to it10618)

String[] txi01_GST = {"GS", "GS", "GS", "GS"}; //Tax type code
String[] txi02_GST = {"0.70", "1.75", "1.00", "0.80", "0.00"}; //Monetary amount
String[] txi03_GST = {"", "", "", "", ""}; //Percent
String[] txi06_GST = {"", "", "", "", ""}; //Tax exempt code

String[] txi01_PST = {"PG", "PG", "PG", "PG"}; //Tax type code
String[] txi02_PST = {"0.80", "2.00", "1.00", "0.80", "0.00"}; //Monetary amount
String[] txi03_PST = {"", "", "", "", ""}; //Percent
String[] txi06_PST = {"", "", "", "", ""}; //Tax exempt code
String[] pam05 = {"11.50", "28.75", "10.62", "11.50", "-10.00"}; //Extended line-item
amount
String[] pid05 = {"Stapler", "Lamp", "Bottled Water", "Fountain Pen", "DISCOUNT"}; //Line
item description
AxIt106s[] it106s = {new AxIt106s(), new AxIt106s(), new AxIt106s(), new AxIt106s(), new
AxIt106s()};

it106s[0].setIt10618(it10618[0]);
it106s[0].setIt10719(it10719[0]);

it106s[1].setIt10618(it10618[1]);
it106s[1].setIt10719(it10719[1]);

```

**Sample AX Refund**

```

it106s[2].setIt10618(it10618[2]);
it106s[2].setIt10719(it10719[2]);

it106s[3].setIt10618(it10618[3]);
it106s[3].setIt10719(it10719[3]);

it106s[4].setIt10618(it10618[4]);
it106s[4].setIt10719(it10719[4]);
AxTxi[] txi = {new AxTxi(), new AxTxi(), new AxTxi(), new AxTxi()};
txi[0].setTxi(txio1_GST[0], txio2_GST[0], txio3_GST[0], txio6_GST[0]);
txi[0].setTxi(txio1_PST[0], txio2_PST[0], txio3_PST[0], txio6_PST[0]);
txi[1].setTxi(txio1_GST[1], txio2_GST[1], txio3_GST[1], txio6_GST[1]);
txi[1].setTxi(txio1_PST[1], txio2_PST[1], txio3_PST[1], txio6_PST[1]);
txi[2].setTxi(txio1_GST[2], txio2_GST[2], txio3_GST[2], txio6_GST[2]);
txi[2].setTxi(txio1_PST[2], txio2_PST[2], txio3_PST[2], txio6_PST[2]);
txi[3].setTxi(txio1_GST[3], txio2_GST[3], txio3_GST[3], txio6_GST[3]);
txi[3].setTxi(txio1_PST[3], txio2_PST[3], txio3_PST[3], txio6_PST[3]);
txi[4].setTxi(txio1_GST[4], txio2_GST[4], txio3_GST[4], txio6_GST[4]);
txi[4].setTxi(txio1_PST[4], txio2_PST[4], txio3_PST[4], txio6_PST[4]);
AxIt1Loop it1Loop = new AxIt1Loop();
it1Loop.setIt1Loop(it102[0], it103[0], it104[0], it105[0], it106s[0], txi[0], pam05[0],
pid05[0]);
it1Loop.setIt1Loop(it102[1], it103[1], it104[1], it105[1], it106s[1], txi[1], pam05[1],
pid05[1]);
it1Loop.setIt1Loop(it102[2], it103[2], it104[2], it105[2], it106s[2], txi[2], pam05[2],
pid05[2]);
it1Loop.setIt1Loop(it102[3], it103[3], it104[3], it105[3], it106s[3], txi[3], pam05[3],
pid05[3]);
it1Loop.setIt1Loop(it102[4], it103[4], it104[4], it105[4], it106s[4], txi[4], pam05[4],
pid05[4]);
AxTable2 table2 = new AxTable2();
table2.setIt1Loop(it1Loop);
//Create Table 3 with details
AxTxi taxTbl3 = new AxTxi();
taxTbl3.setTxi("GS", "4.25","","","");
taxTbl3.setTxi("PG", "4.60","","","");
taxTbl3.setTxi("TX", "8.85","","","");
AxTable3 table3 = new AxTable3();
table3.setTxi(taxTbl3);

//Create and set Level23 Object
AxLevel23 level23 = new AxLevel23();
level23.setTable1(table1);
level23.setTable2(table2);
level23.setTable3(table3);
AxRefund axRefund = new AxRefund();
axRefund.setOrderId(order_id);
axRefund.setAmount(amount);
axRefund.setTxnNumber(txn_number);
axRefund.setCryptType(crypt);
axRefund.setAxLevel23(level23);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(axRefund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();

```

### Sample AX Refund

```

try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
}

```

## 6.4.8 AX Independent Refund

The AX Independent Refund will credit a specified amount to the cardholder's credit card. The independent refund does not require an existing order to be logged in the Moneris Gateway; however, the credit card number and expiry date will need to be passed.

### **AX Independent Refund transaction object definition**

```
AxIndependentRefund axIndependentRefund = new AxIndependentRefund();
```

### **HttpsPostRequest object for AX Independent Refund transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(axIndependentRefund);
```

### **AX Independent Refund transaction request fields – Required**

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i> 50-character alphanumeric	axIndependentRefund.setOrderId( order_id);
Amount	<i>String</i>	axIndependentRefund.setAmount

Variable Name	Type and Limits	Set Method
	10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	(amount) ;
	<b>EXAMPLE:</b> 1234567.89	
Credit card number	<i>String</i>  20-character alphanumeric	axIndependentRefund.setPan(pan) ;
Expiry date	<i>String</i>  4-character alphanumeric  (YYMM format)	axIndependentRefund.setExpDate(expiry_date) ;
E-commerce indicator	<i>String</i>  1-character alphanumeric	axIndependentRefund.setCryptType(crypt) ;

### AX Independent Refund transaction request fields – Optional

Variable Name	Type and Limits	Set Method
Customer ID	<i>String</i>  50-character alphanumeric	axIndependentRefund.setCustId(cust_id) ;

### Sample AX Independent Refund

```
package Level23;
import JavaAPI.*;
public class TestAxIndependentRefund
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";
boolean status_check = false;

java.util.Date createDate = new java.util.Date();
```

### Sample AX Independent Refund

```

String order_id="Test"+createDate.getTime();
String cust_id="CUST13343";
String amount="62.37";
String pan="373269005095005";
String expiry_date="2012"; //YYMM
String crypt="7";

//Create Table 1 with details
String n101 = "R6"; //Entity ID Code
String n102 = "Retailing Inc. International"; //Name
String n301 = "919 Oriole Rd."; //Address Line 1
String n401 = "Toronto"; //City
String n402 = "On"; //State or Province
String n403 = "H1T6W3"; //Postal Code
String[] ref01 = {"4C", "CR"}; //Reference ID Qualifier
String[] ref02 = {"M5T3A5", "16802309004"}; //Reference ID
String big04 = "PO7758545"; //Purchase Order Number
String big05 = "RN0049858"; //Release Number
String big10 = "INV99870E"; //Invoice Number
AxRef axRef1 = new AxRef();
axRef1.setRef(ref01[0], ref02[0]);
axRef1.setRef(ref01[1], ref02[1]);
AxN1Loop n1Loop = new AxN1Loop();
n1Loop.setN1Loop(n101, n102, n301, n401, n402, n403, axRef1);
AxTable1 table1 = new AxTable1();
table1.setBig04(big04);
table1.setBig05(big05);
table1.setBig10(big10);
table1.setN1Loop(n1Loop);

//Create Table 2 with details
//the sum of the extended amount field (pam05) must equal the level 1 amount field
String[] it102 = {"1", "1", "1", "1", "1"}; //Line item quantity invoiced
String[] it103 = {"EA", "EA", "EA", "EA", "EA"}; //Line item unit or basis of measurement
code
String[] it104 = {"10.00", "25.00", "8.62", "10.00", "-10.00"}; //Line item unit price
String[] it105 = {"", "", "", "", ""}; //Line item basis of unit price code

String[] it10618 = {"MG", "MG", "MG", "MG", "MG"}; //Product/Service ID qualifier
String[] it10719 = {"DJFR4", "JFJ49", "FEF33", "FEE43", "DISCOUNT"}; //Product/Service ID
(corresponds to it10618)

String[] txi01_GST = {"GS", "GS", "GS", "GS", "GS"}; //Tax type code
String[] txi02_GST = {"0.70", "1.75", "1.00", "0.80", "0.00"}; //Monetary amount
String[] txi03_GST = {"", "", "", "", ""}; //Percent
String[] txi06_GST = {"", "", "", "", ""}; //Tax exempt code

String[] txi01_PST = {"PG", "PG", "PG", "PG", "PG"}; //Tax type code
String[] txi02_PST = {"0.80", "2.00", "1.00", "0.80", "0.00"}; //Monetary amount
String[] txi03_PST = {"", "", "", "", ""}; //Percent
String[] txi06_PST = {"", "", "", "", ""}; //Tax exempt code
String[] pam05 = {"11.50", "28.75", "10.62", "11.50", "-10.00"}; //Extended line-item
amount
String[] pid05 = {"Stapler", "Lamp", "Bottled Water", "Fountain Pen", "DISCOUNT"}; //Line
item description
AxIt106s[] it106s = {new AxIt106s(), new AxIt106s(), new AxIt106s(), new AxIt106s(), new
AxIt106s()};

it106s[0].setIt10618(it10618[0]);

```

### Sample AX Independent Refund

```

it106s[0].setIt10719(it10719[0]);

it106s[1].setIt10618(it10618[1]);
it106s[1].setIt10719(it10719[1]);

it106s[2].setIt10618(it10618[2]);
it106s[2].setIt10719(it10719[2]);

it106s[3].setIt10618(it10618[3]);
it106s[3].setIt10719(it10719[3]);

it106s[4].setIt10618(it10618[4]);
it106s[4].setIt10719(it10719[4]);
AxTxi[] txi = {new AxTxi(), new AxTxi(), new AxTxi(), new AxTxi()};
txi[0].setTxi(txio1_GST[0], txio2_GST[0], txio3_GST[0], txio6_GST[0]);
txi[0].setTxi(txio1_PST[0], txio2_PST[0], txio3_PST[0], txio6_PST[0]);
txi[1].setTxi(txio1_GST[1], txio2_GST[1], txio3_GST[1], txio6_GST[1]);
txi[1].setTxi(txio1_PST[1], txio2_PST[1], txio3_PST[1], txio6_PST[1]);
txi[2].setTxi(txio1_GST[2], txio2_GST[2], txio3_GST[2], txio6_GST[2]);
txi[2].setTxi(txio1_PST[2], txio2_PST[2], txio3_PST[2], txio6_PST[2]);
txi[3].setTxi(txio1_GST[3], txio2_GST[3], txio3_GST[3], txio6_GST[3]);
txi[3].setTxi(txio1_PST[3], txio2_PST[3], txio3_PST[3], txio6_PST[3]);
txi[4].setTxi(txio1_GST[4], txio2_GST[4], txio3_GST[4], txio6_GST[4]);
txi[4].setTxi(txio1_PST[4], txio2_PST[4], txio3_PST[4], txio6_PST[4]);
AxIt1Loop it1Loop = new AxIt1Loop();
it1Loop.setIt1Loop(it102[0], it103[0], it104[0], it105[0], it106s[0], txi[0], pam05[0],
pid05[0]);
it1Loop.setIt1Loop(it102[1], it103[1], it104[1], it105[1], it106s[1], txi[1], pam05[1],
pid05[1]);
it1Loop.setIt1Loop(it102[2], it103[2], it104[2], it105[2], it106s[2], txi[2], pam05[2],
pid05[2]);
it1Loop.setIt1Loop(it102[3], it103[3], it104[3], it105[3], it106s[3], txi[3], pam05[3],
pid05[3]);
it1Loop.setIt1Loop(it102[4], it103[4], it104[4], it105[4], it106s[4], txi[4], pam05[4],
pid05[4]);
AxTable2 table2 = new AxTable2();
table2.setIt1Loop(it1Loop);
//Create Table 3 with details
AxTxi taxTbl3 = new AxTxi();
taxTbl3.setTxi("GS", "4.25","",""); //sum of GST taxes
taxTbl3.setTxi("PG", "4.60","",""); //sum of PST taxes
taxTbl3.setTxi("TX", "8.85","",""); //sum of all taxes
AxTable3 table3 = new AxTable3();
table3.setTxi(taxTbl3);

//Create and set Level23 Object
AxLevel23 level23 = new AxLevel23();
level23.setTable1(table1);
level23.setTable2(table2);
level23.setTable3(table3);
AxIndependentRefund axIndependentRefund = new AxIndependentRefund();
axIndependentRefund.setOrderId(order_id);
axIndependentRefund.setCustId(cust_id);
axIndependentRefund.setAmount(amount);
axIndependentRefund.setPan(pan);
axIndependentRefund.setExpDate(expiry_date);
axIndependentRefund.setCryptType(crypt);
axIndependentRefund.setAxLevel23(level23);
HttpsPostRequest mpgReq = new HttpsPostRequest();

```

### Sample AX Independent Refund

```
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(axIndependentRefund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}
catch (Exception e)
{
System.out.println(e);
}
}
```



## 7 3-D Secure 2.2

- 7.1 About 3-D Secure 2.2
- 7.2 Building Your 3-D Secure 2.2 Integration
- 7.3 Implementing Card Lookup Request
- 7.4 Implementing MPI 3DS Authentication Request
- 7.5 Handling the Challenge Flow
- 7.7 Performing the Authorization
- 7.8 Testing Your 3-D Secure 2.2 Integration
- 7.9 Moving to Production With 3-D Secure 2.2
- 7.10 3-D Secure 2.2 TransStatus Codes
- 7.11 3-D Secure 2.2 Commons TransStatusReason Decline Codes
- 7.12 CAVV Result Codes

### 7.1 About 3-D Secure 2.2

3-D Secure 2.2 is an EMVCo payment authentication protocol designed to reduce card not present fraud by making a risk assessment based on transaction and device data, while also supporting further risk minimization measures, such as a challenge to the cardholder. In some cases, a liability shift takes effect for certain card-not-present fraud-related chargebacks enabling the merchant to provide goods and services with confidence.

The Moneris Gateway can enable transactions using the 3-D Secure protocol via Moneris 3DS Server and Access Control Server (ACS).

Moneris Gateway supports the following 3-D Secure implementations:

- Visa Secure (please note: Visa Secure does not support all the RI Indicators available in the 3D Secure 2.2. Check the RI Indicators status field to confirm the status Visa Secure support.)
- Mastercard Identity Check
- American Express SafeKey (please note: American Express only supports authentication requests for merchants who have an Amex OFI merchant account)

### 7.1.1 3-D Secure Implementations

Visa Secure, Mastercard Identity Check and American Express SafeKey are programs based on the 3-D Secure Protocol to improve the security of online transactions.

These programs involve authentication of the cardholder during an online e-commerce transaction.

Authentication is based on the issuer's selected method of authentication.

The following are examples of authentication methods:

- Risk-based authentication
- Dynamic passwords
- Static passwords

Some benefits of these programs are reduced risk of fraudulent transactions and protection against chargebacks for certain fraudulent transactions.

The Java 3DS 2.2 API supports two message categories and two device channels from the 3-D Secure authentication protocol:

#### 1. Message Categories:

- **Payment Authentication** – Cardholder authentication prior to an eCommerce transaction. After a successful 3DS authentication, you proceed with a purchase or pre-authorization.
- **Non-Payment Authentication (NPA)**– Identity verification and account confirmation performed without an accompanying financial transaction. After a successful 3DS authentication, you might proceed with:
  - Tokenizing the card for future payments
  - Allowing log-in for client portals
  - Any other activity relying on identity or account confirmation

#### 2. Device Channels:

- **Browser** – The transaction originates from a website utilized via a browser on the cardholder's device.

- For example, an eCommerce transaction originating on the merchant’s website with a check-out process that the cardholder is using via their personal computer or mobile phone’s web browser (Chrome, Edge, Safari, etc.).
- **3DS Requestor Initiated** – Account confirmations and cardholder authentication with no direct cardholder originating the transaction.
  - 3RI can be used for authenticating Mail-Telephone Order (MOTO) transactions.
  - 3RI can be used to authenticate follow-on transactions as part of a subscription, such as recurring transactions. The first cardholder payment might use a browser-based authentication, with subsequent payments utilizing a 3RI authentication linking to the previous.
  - In situations where a merchant business model accommodates waiting before processing their payment, they can utilize Decoupled Authentication to allow the cardholder to authenticate directly with their issuer via a non-3DS challenge, such as a push notification to a banking app.

### 7.1.2 Out of Scope/Not Supported Check

- In-app

### 7.1.3 Version Compatibility

All development to the Moneris API must be able to support the addition of new fields in the response and new error conditions in the response. Otherwise any changes that affect backwards compatibility will be communicated by Moneris Solutions with an appropriate period of notice. When developing to the solution it is recommended to validate for success state of the request and then handle errors states separately and ensure there is a final catch for any unexpected/undocumented errors that are returned.

### 7.1.4 Upgrading from 3-D Secure 2.0 to 3-D Secure 2.2 Check

The 3DS 2.2 API is different from the 3DS 2.0 API therefore developers will have to complete the steps described in the section 7.2 Building Your 3-D Secure 2.2 Integration.


## 7.2 Building Your 3-D Secure 2.2 Integration

- 7.2.1 Activating 3-D Secure Functionality
- 7.2.2 Transaction Flow for 3-D Secure - Browser channel
- 7.2.3 Transaction Flow for 3-D Secure - 3RI channel

### 7.2.1 Activating 3-D Secure Functionality

To activate Visa Secure, Mastercard Identity Check and/or American Express SafeKey transaction functionality, call Moneris Sales Support at 1-855-465-4980 to have Moneris enroll you in the program(s) and enable the functionality on your account.

### 7.2.2 Transaction Flow for 3-D Secure - Browser channel



The 3DS 2.2 API is called when the customer wishes to checkout. An optional card lookup request can be performed to initiate cardholder browser fingerprinting. Once the fingerprint is complete, or as a first step if not performing a fingerprint, the transactional information can then be transmitted to the 3DS 2.2 service so a risk assessment may be initiated.

The flow can then proceed in one of two ways. The two different flows are referred to as “frictionless” and “challenge”.

The “frictionless” flow is invisible to a cardholder. If the issuing financial institution has enough information to make a risk assessment and assume liability, this will manifest itself as with an authentication attempt or success with an accompanying CAVV value. No cardholder challenge is presented.

In the “challenge” flow the issuing financial institution may wish to take a further step and issue a challenge to the cardholder. In this case the cardholder’s browser gets re-directed to the issuer’s 3DS platform for authentication. Once this challenge is complete, the cardholder browser is again re-directed back to the merchant’s site. The merchant’s server then issues a server-to-server request in order to obtain the CAVV value from Moneris.

### **Steps 1 – 2 (Optional)**

An optional card lookup request can be performed to initiate cardholder browser fingerprinting. The merchant website collects device information and provides them to Moneris via the card\_lookup request (1.1). Moneris submits this data to the 3DS Directory Server and returns with the card\_lookup response containing the card’s supported 3DS version, an ACS URL, and 3DS Method Data representing the fingerprint (2.2). The merchant browser then submits an HTTP POST to the ACS URL with the method data. (2.3)

Once the fingerprint is complete, or as a first step if not performing a fingerprint, the transactional information can then be transmitted to the 3DS 2.2 service so a risk assessment may be initiated.

### **Steps 3 – 4 (Required)**

The 3DS authentication request threeDSAuthentication is performed by the merchant website to initiate validating the cardholder identity. Moneris communicates with the 3DS Directory and the ACS system for that issuer to provide an initial risk assessment (3.2-4.2). Moneris returns a threeDSAuthentication response to the merchant with a TransStatus indicating the action for the website to perform:

- A TransStatus = “Y” or “A” means the website can proceed immediately to the financial transaction with the CAVV value provided. This is a frictionless transaction flow without presenting a challenge.
- A TransStatus = “C” indicates that the cardholder must be presented a challenge. To present the challenge, you must POST a <form> with a “creq” field, which contains the ChallengeData, to the URL defined in the ChallengeURL field.
- A TransStatus = “D” indicates that the cardholder must be presented a challenge via Decoupled Authentication. See Decoupled Authentication.


### **Steps 5 – 10 (Challenge Only)**

In scenarios where a challenge is required, the merchant website sends an HTTP POST to the Challenge URL with the ChallengeData sent as a “CREQ” value (5). The ACS system will present a challenge to the cardholder, who will supply whatever credentials their issuer requires. The merchant website receives a

“CRES” value from the ACS via the HTTP POST response (6). Meanwhile, the ACS supplies the results to the 3DS Directory, which then forwards it to Moneris (7-8).

The merchant’s website then sends a CAVV Lookup to Moneris via a cavv\_lookup request and includes their “CRES” (9). Moneris responds with the cavv\_lookup response with the necessary ECI and CAVV values. With the 3DS authentication complete, you can proceed to the financial transaction.

### 7.2.3 Transaction Flow for 3-D Secure - 3RI channel



In a 3DS Requestor Initiated flow, the cardholder is not directly triggering the transaction flow via a browser experience as above. It is possible they are initiating the transaction outside the 3DS protocol, such as mailing or phoning the merchant (Mail-Telephone Order, aka MOTO), or it is possible the merchant is processing a recurring or installment plan on behalf of the cardholder’s subscription. It is also possible the merchant requires a non-payment authentication as part of tokenizing the card for later use.

3RI flows do not have direct cardholder interaction. The merchant sends their <threeDSAuthentication> request per steps 3-4 above but include additional fields to describe their 3RI usage scenario.

- If this is a Mail or Telephone (MOTO) payment authentication, the ACS may trigger a Decoupled Authentication between the issuer and cardholder (see Decoupled Authentication)
- If this is a follow-on payment from a previous 3DS authenticated transaction, you can include PriorAuthenticationInfo to link to the previous authentication and improve the likelihood of a successful result

Your server can utilize the fields DeviceChannel , RlIndicator and MessageCategory to inform Moneris if your merchant server is attempting to use the 3DS Requestor Initiated process.

### 7.2.3.1 Decoupled Authentication

For scenarios where a 3RI authentication requires challenge, instead of utilizing the standard challenge request and response the ACS authenticates the cardholder outside of the 3-D Secure protocol such as a banking app or mobile phone text to the cardholder. The Moneris 3DS Server waits for the ACS to authenticate the cardholder; this authentication can take up to 7 days. As this process relies on a cardholder action outside the 3DS flow, it occurs asynchronously to transaction processing.

Your server can utilize the fields DecoupledRequestIndicator and DecoupledRequestAsyncUrl to inform Moneris that you are opting in to accept a Decoupled Authentication attempt and where you want Moneris to POST the results asynchronously.

## 7.3 Implementing Card Lookup Request

The CardLookup request verifies the applicability of 3DS 2.2 on the card and returns the 3DS Method URL used for device fingerprinting if the card supports this feature. This request is optional, it may increase the chance of a frictionless flow.

The threeDSMethodURL & threeDSMethodData are returned to the merchant server on the CardLookup response, if supported.

- If you receive the threeDSMethodURL, you may send the threeDSMethodData to the threeDSMethodURL via a browser post in order to supplement the authentication request with device data pertaining to the cardholder's browser.
- If you do not receive the threeDSMethodURL, you may still proceed with 3DS Authentication.

The threeDSMethodData must be sent via HTTP POST to the threeDSMethodURL in a hidden iFrame.

In your implementation, use the following URLs as Host, depending on the development stage:

Testing:

esqa.moneris.com

Production:

www3.moneris.com

### 7.3.1 Card Lookup Request – mpiCardLookup

#### Card Lookup Request transaction object definition

```
MpiCardLookup mpiCardLookup = new MpiCardLookup();
```

### **HttpsPostRequest object for Card Lookup Request transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mpiCardLookup);
```

### **Core connection object fields (all API transactions)**

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### **Card Lookup Request transaction request fields – Required**

**NOTE:** Either a pan or a data\_key must be passed in the request

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric-Z A-Z 0-9 _ - : . @ spaces	mpiCardLookup.setOrderId(order_id);
credit card number	<i>String</i> max 20-character alphanumeric	mpiCardLookup.setPan(pan);
data key	<i>String</i> 25-character alphanumeric	mpiCardLookup.setData(data_key);
notification URL	<i>String</i> 256-character alphanumeric	mpiCardLookup.setNotificationURL("https://yournotificationurl.com");

## Sample Card Lookup Request

```

package Canada;
import JavaAPI.*;
public class TestCanadaMpiCardLookup
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String pan = "347668693641199";

String processing_country_code = "CA";
MpiCardLookup mpiCardLookup = new MpiCardLookup();
mpiCardLookup.setOrderId(order_id);
mpiCardLookup.setPan(pan);
//mpiCardLookup.setDataKey("800XGiwxgvfbZngigVFeld9d2"); //Optional - For Moneris Vault and
Hosted Tokenization tokens in place of setPan
mpiCardLookup.setNotificationUrl("https://yournotificationurl.com"); //(Website URL that will
receive 3DS Method Completion response from ACS)
//*****OPTIONAL VARIABLES*****
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false or comment out this line for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mpiCardLookup);
mpgReq.send();
/************* REQUEST *****/
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("Message = " + receipt.getMessage());
System.out.println("MessageType = " + receipt.getMpiMessageType());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());
System.out.println("ThreeDSMethodURL = " + receipt.getMpiThreeDSMethodURL());
System.out.println("ThreeDSMethodData = " + receipt.getMpiThreeDSMethodData());
System.out.println("ThreeDSServerTransId = " + receipt.getMpiThreeDSServerTransId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
} // end TestResMpiTxn

```

## 7.4 Implementing MPI 3DS Authentication Request

The MPI 3DS Authentication Request is used to start the validation process of the card. The result of this request determines whether 3DS 2.2 is supported by the card and what type of authentication is required.

In your implementation, use the following URLs as Host, depending on the development stage:

### Testing URLs:

<https://mpg1t.moneris.io/mpi2/servlet/MpiServlet>

**Production URLs:**

<https://mpg1.monteris.io/mpi2/servlet/MpiServlet>

Below we detail three different scenarios for utilizing Moneris MPI 3DS Authentication. Each scenario has conditions for which fields are required or optional for the endpoint.

### 7.4.1 MPI 3DS Authentication Request - Browser Channel

The authentication request is used to start the validation process of the card.

The result of this request determines whether 3-D Secure 2.2 is supported by the card and what type of authentication is required.

In your implementation, use the following URLs as Host, depending on the development stage:

testing: mpg1t.monteris.io

production: mpg1.monteris.io

**NOTE:** Billing-related request fields are required to be sent for this transaction, or else the authentication process may fail

#### MPI 3DS Authentication Request transaction object definition

```
MpiThreeDSAuthentication mpiThreeDSAuthentication = new  
MpiThreeDSAuthentication();
```

#### HttpsPostRequest object for MPI 3DS Authentication Request transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();  
  
mpgReq.setTransaction(mpiThreeDSAuthentication);
```

**WARNING:** Do not send fields related to 3RI on browser-based authentications.

#### Core connection object fields (all API transactions)

Variable Name	Type and Limits	Description
store ID <store_id>	<i>String</i> N/A	mpgReq.setStoreId(store_id); Unique identifier provided by Moneris upon merchant account setup

Variable Name	Type and Limits	Description
API token <api_token>	<i>String</i> N/A	<pre>mpgReq.setApiToken(api_token);</pre> <p>Unique alphanumeric string assigned by Moneris upon merchant account activation</p> <p>To find your API token, refer to your test or production store's Admin settings in the Merchant Resource Center, at the following URLs:</p> <p>Testing: <a href="https://esqa-monteris.com/mpg/">https://esqa-monteris.com/mpg/</a></p> <p>Production: <a href="https://www3-monteris.com/mpg/">https://www3-monteris.com/mpg/</a></p>

### MPI 3DS Authentication Request transaction request fields – Required

Variable Name	Type and Lim-its	Description
message category <MessageCategory>	<i>String</i> 2-character numeric	<pre>mpiThreeDSAuthentication.setMessageCategory("02");</pre> <p>Whether the authentication request is for a payment or non-payment use:</p> <p>01 = payment authentication (PA)</p> <p>02 = non-payment authentication (NPA)</p>
device channel <DeviceChannel>	<i>String</i> 2-character numeric	<pre>mpiThreeDSAuthentication.setDeviceChannel("02");</pre> <p>The interface used to initiate the authentication:</p> <p>02 = Browser (BRW)</p> <p>03 = 3DS Requestor Initiated (3RI)</p>
request type <RequestType>	<i>String</i> 2-character	<pre>mpiThreeDSAuthentication.setRequestType("REQUEST_TYPE_VALUE");</pre>

Variable Name	Type and Limits	Description
	alphanumeric	<p>Indicates the type of browser-based authentication request:</p> <p>01 = cardholder initiated payment</p> <p>02 = recurring transaction</p> <p>Conditional. Required if device_channel = 02</p>
order ID <order_id>	<p><i>String</i></p> <p>50-character alphanumeric</p> <p>a-Z A-Z 0-9 _ - : . @ spaces</p>	<pre>mpiThreeDSAuthentication.setOrderId(order_id);</pre> <p>Merchant-defined transaction identifier that must be unique for every Purchase, Pre-Authorization and Independent Refund transaction. No two transactions of these types may have the same order ID.</p> <p>For Refund, Completion and Purchase Correction transactions, the order ID must be the same as that of the original transaction.</p>
<p>data key &lt;data_key&gt;</p> <p>OR</p> <p>credit card number &lt;pan&gt;</p>	<p><i>String</i></p> <p>data key limits:</p> <p>25-character alphanumeric</p> <p>credit card number limits:</p> <p>max 20-character alphanumeric</p>	<pre>mpiThreeDSAuthentication.setData(data_key);</pre> <p><b>data key description:</b></p> <p>Unique identifier for a Vault profile, and used in future Vault financial transactions to associate a transaction with that profile</p> <p>Data key is generated by Moneris and returned to you in the Receipt object when the profile is first registered</p> <pre>mpiThreeDSAuthentication.SetPan(pan);</pre> <p><b>credit card number description:</b></p> <p>Credit card number, usually 16 digits —field can be maximum 20 digits in support of future expansion of card number ranges.</p> <p>Carries the token for network tokenization transactions.</p>
expiry date <expiry_date>	<p><i>String</i></p> <p>4-character alphanumeric</p>	<pre>mpiThreeDSAuthentication.setExpDate(expiry_date);</pre> <p>Expiry date of the credit card, in YYMM format.</p>

Variable Name	Type and Limits	Description
	YYMM	<p><b>NOTE:</b> This is the reverse of the MMYY date format that is presented on the card.</p>
<b>amount</b> <amount>	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	<pre>mpiThreeDSAuthentication.setAmount(amount);</pre> <p>Transaction dollar amount</p> <p>This must contain at least 3 digits, two of which are penny values</p> <p>Minimum allowable value = \$0.01, maximum allowable value = \$9999999.99</p> <div data-bbox="496 910 670 1009" style="border: 1px solid #ccc; padding: 5px; width: fit-content;"> <b>EXAMPLE:</b> 1234567.89 </div>
<b>cardholder name</b> <CardholderName>	<i>String</i> 45-character alphanumeric	<pre>mpiThreeDSAuthentication.setCardholderName("CARDHOLDER_NAME_VALUE");</pre> <p>Name of the cardholder</p> <div data-bbox="496 1205 670 1410" style="border: 1px solid #ccc; padding: 5px; width: fit-content;"> <b>NOTE:</b> Accented characters are not allowable </div>
<b>3DS completion indicator</b> <ThreeDSCompletionInd>	<i>String</i> 1-character alphabetic	<pre>mpiThreeDSAuthentication.setThreeDSCompletionInd(THREEDSCOMPLETION_VALUE);</pre> <p>indicates whether 3ds method MpiCardLookup was successfully completed</p> <p>Allowable values:</p> <p>Y = Successfully completed</p> <p>N = Did not successfully complete</p> <p>U = Unavailable</p>

Variable Name	Type and Limits	Description
		Conditional. Required if card_lookup is used.
billing address <BillAddress1>	<i>String</i> 50-character alphanumeric	<code>mpiThreeDSAuthentication.setBillAddress1 ("BILL_STREET_ADDRESS_VALUE");</code> Cardholder billing address
billing province <BillProvince>	<i>String</i> 3-character alphanumeric	<code>mpiThreeDSAuthentication.setBillProvince ("BILL_PROV_VALUE");</code> Cardholder province or state Defined in country subdivision ISO 3166-2
billing city <BillCity>	<i>String</i> 50-character alphanumeric	<code>mpiThreeDSAuthentication.setBillCity ("BILL_CITY_VALUE");</code> Cardholder billing city
billing postal code <BillPostalCode>	<i>String</i> 16-character alphanumeric	<code>mpiThreeDSAuthentication.setBillPostalCode ("BILL_POSTAL_CODE_VALUE");</code> Cardholder billing postal code
billing country <BillCountry>	<i>String</i> 3-character alphanumeric	<code>mpiThreeDSAuthentication.setBillCountry ("BILL_COUNTRY_VALUE");</code> Cardholder billing country Defined as 3 digit country code ISO 3166-1
shipping address <ShipAddress1>	<i>String</i> 50-character alphanumeric	<code>mpiThreeDSAuthentication.setShipAddress1 ("SHIP_STREET_ADDRESS_VALUE");</code> Shipping destination address
shipping province <ShipProvince>	<i>String</i> 3-character alphanumeric	<code>mpiThreeDSAuthentication.setShipProvince ("SHIP_PROV_VALUE");</code> Shipping destination province or state Defined in country subdivision ISO 3166-2
shipping city <ShipCity>	<i>String</i> 50-character	<code>mpiThreeDSAuthentication.setShipCity ("SHIP_CITY_VALUE");</code> Shipping destination city

Variable Name	Type and Limits	Description
	alphanumeric	
shipping postal code <ShipPostalCode>	<i>String</i> 16-character alphanumeric	<pre>mpiThreeDSAuthentication.setShipPostalCode ("SHIP_POSTAL_CODE_VALUE");</pre> Shipping destination postal or ZIP code
shipping country <ShipCountry>	<i>String</i> 3-character alphanumeric	<pre>mpiThreeDSAuthentication.setShipCountry ("SHIP_COUNTRY_VALUE");</pre> Shipping destination country  Defined as 3-digit country code in ISO 3166-1
notification URL <NotificationURL>	<i>String</i> 256-character alphanumeric	<pre>mpiThreeDSAuthentication.setNotificationURL ("HTTPS://YOURURL.COM");</pre> Notification URL for receiving the 3DS Method POST response from the issuer ACS.  Conditional. Required if device_channel = 02
challenge window size <ChallengeWindowSize>	<i>String</i> 2-character alphanumeric	<pre>mpiThreeDSAuthentication.setChallengeWindowSize("CWS_VALUE");</pre> Relates to the rendering of the ACS challenge within the browser.  Allowable values:  01 = 250 x 400 02 = 390 x 400 03 = 500 x 600 04 = 600 x 400 05 = Full screen  Conditional. Required if device_channel = 02
browser user agent <BrowserUserAgent>	<i>String</i> 2048-character alphanumeric	<pre>mpiThreeDSAuthentication.setBrowserUserAgent ("BROWSER_USER_AGENT_VALUE");</pre> Browser User Agent  Conditional. Required if device_channel = 02

Variable Name	Type and Limits	Description
browser java enabled <BrowserJavaEnabled>	String 1-character alphabetic	<pre>mpiThreeDSAuthentication.setBrowserJavaEnabled(BROWSER_JAVA_VALUE);</pre> <p>Indicates whether Java is enabled in the browser</p> <p>Allowable values:</p> <ul style="list-style-type: none"> <li>T = True</li> <li>F = False</li> </ul> <p>Conditional. Required if device_channel = 02</p>
browser screen height <BrowserScreenHeight>	String 6-character numeric	<pre>mpiThreeDSAuthentication.setBrowserScreenHeight(BROWSER_SCREEN_HEIGHT_VALUE);</pre> <p>Pixel height of cardholder screen</p> <p>Conditional. Required if device_channel = 02</p>
browser screen width <BrowserScreenWidth>	String 6-character numeric	<pre>mpiThreeDSAuthentication.setBrowserScreenWidth(BROWSER_SCREEN_WIDTH_VALUE);</pre> <p>Pixel width of cardholder screen</p> <p>Conditional. Required if device_channel = 02</p>
browser language <BrowserLanguage>	String 8-character alphanumeric	<pre>mpiThreeDSAuthentication.setBrowserLanguage(BROWSER_LANGUAGE_VALUE);</pre> <p>As defined in IETF BCP47</p> <p>Conditional. Required if device_channel = 02</p>
email <Email>	String 254-character alphanumeric	<pre>mpiThreeDSAuthentication.setEmail("EMAIL_VALUE");</pre> <p>Cardholder email address</p> <div data-bbox="709 1552 1411 1721" style="border: 1px solid #ccc; padding: 10px; background-color: #e0f2e0;"> <p><b>NOTE:</b> This field is not mandatory, but it is required. It is highly recommended to provide the cardholder's email address. Lack of providing the cardholder's address, might increase the risk of rejects.</p> </div>

## MPI 3DS Authentication Request transaction request fields – Optional

Variable Name	Type and Limits	Description
currency <Currency>	<i>String</i> 3-character numeric	<pre>mpiThreeDSAuthentication.setCurrency("CURRENCY_VALUE");</pre> <p>ISO 4217 3 digit currency code</p> <p>CAD = 124</p> <p>USD = 840</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> This field should not be sent unless Multi Currency Pricing is enabled on your merchant account       </div>
request challenge <RequestChallenge>	<i>String</i> 2-character numeric	<pre>mpiThreeDSAuthentication.setRequestChallenge("CHALLENGE_VALUE");</pre> <p>Indicates whether a browser-based challenge is requested for this transaction. Standard is "01"</p> <ul style="list-style-type: none"> <li>• 01 = No preference</li> <li>• 02 = No challenge requested</li> <li>• 03 = Challenge requested: 3DS Requestor Preference</li> <li>• 04 = Challenge requested: Mandate</li> </ul> <p>Conditional. Required if device_channel = 02</p>

## Sample MPI 3DS Authentication Request - Browser Channel

```
package Canada;
import JavaAPI.*;
public class TestCanadaMpThreeDSAuthentication
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String prior_request_ref="d7clee99-9478-44a6-b1f2-391e29c6b340";
String prior_request_auth_data="abc";
String prior_request_auth_method = "01";
String prior_request_auth_timestamp = "201710282113";
String processing_country_code = "CA";
MpThreeDSAuthentication mpiThreeDSAuthentication = new MpThreeDSAuthentication();
mpiThreeDSAuthentication.setOrderId("Test159787ssa3215193"); //must be the same one that was
used in MpCardLookup call
mpiThreeDSAuthentication.setCardholderName("Moneris Test");
```

```

mpiThreeDSAuthentication.setPan("347668693641199");
// mpiThreeDSAuthentication.setDataKey("xRl904FgrZUYdGkmqHTqiEw97"); //Optional - For Moneris
Vault and Hosted Tokenization tokens in place of setPan
mpiThreeDSAuthentication.setExpdate("2310");
mpiThreeDSAuthentication.setAmount("1.00");
mpiThreeDSAuthentication.setThreeDSCompletionInd("Y"); // (Y|N|U) indicates whether 3ds method
MpICardLookup was successfully completed
mpiThreeDSAuthentication.setRequestType("01"); // (01=payment|02=recur)
mpiThreeDSAuthentication.setPurchaseDate("20200819035249"); // (YYYYMMDDHHMMSS)
mpiThreeDSAuthentication.setNotificationURL("https://yournotificationurl.com"); // (Website
where response from RRes or CRes after challenge will go)
mpiThreeDSAuthentication.setChallengeWindowSize("03"); // (01 = 250 x 400, 02 = 390 x 400, 03
= 500 x 600, 04 = 600 x 400, 05 = Full screen)
mpiThreeDSAuthentication.setEmail("test@email.com");
mpiThreeDSAuthentication.setBrowserUserAgent("Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/80.0.3987.132 Safari/537.36\\");
mpiThreeDSAuthentication.setBrowserJavaEnabled("true"); // (true|false)
mpiThreeDSAuthentication.setBrowserScreenHeight("1000"); // (pixel height of cardholder
screen)
mpiThreeDSAuthentication.setBrowserScreenWidth("1920"); // (pixel width of cardholder screen)
mpiThreeDSAuthentication.setBrowserLanguage("en-GB"); // (defined by IETF BCP47)

//Optional Methods
mpiThreeDSAuthentication.setBillAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setBillProvince("ON");
mpiThreeDSAuthentication.setBillCity("Toronto");
mpiThreeDSAuthentication.setBillPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setBillCountry("124");

mpiThreeDSAuthentication.setShipAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setShipProvince("ON");
mpiThreeDSAuthentication.setShipCity("Toronto");
mpiThreeDSAuthentication.setShipPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setShipCountry("124");

mpiThreeDSAuthentication.setRequestChallenge("Y"); // (Y|N Requesting challenge regardless of
outcome)
*****3DS2.2*****
mpiThreeDSAuthentication.setMessageCategory("01");
mpiThreeDSAuthentication.setDeviceChannel("02");
// mpiThreeDSAuthentication.setDecoupledRequestIndicator("Y");
// mpiThreeDSAuthentication.setDecoupledRequestMaxTime("000010");
// mpiThreeDSAuthentication.setDecoupledRequestAsyncUrl("localhost:8080/googlepay");

// mpiThreeDSAuthentication.setRiIndicator("01");
// PriorAuthenticationInfo priorAuthenticationInfo= new PriorAuthenticationInfo();
// priorAuthenticationInfo.setPriorParams(prior_request_auth_data,prior_request_ref,
// prior_request_auth_method,prior_request_auth_timestamp);
// mpiThreeDSAuthentication.setRecurringExpiry("20221230");
// mpiThreeDSAuthentication.setRecurringFrequency("031");
*****OPTIONAL VARIABLES*****
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false or comment out this line for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mpiThreeDSAuthentication);
System.out.println(mpiThreeDSAuthentication.toXML());
mpgReq.send();
***** REQUEST *****/
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ReceiptId = " + receipt.getReceiptId());
}

```

```

System.out.println("Message = " + receipt.getMessage());
System.out.println("MessageType = " + receipt.getMpiMessageType());
System.out.println("TransStatus = " + receipt.getMpiTransStatus());
System.out.println("TransStatusReason = " + receipt.getMpiTransStatusReason());
System.out.println("ChallengeURL = " + receipt.getMpiChallengeURL());
System.out.println("ChallengeData = " + receipt.getMpiChallengeData());
System.out.println("ThreeDServerTransId = " + receipt.getMpiThreeDSserverTransId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());
System.out.println("ThreeDSAcstransID = " + receipt.getMpiThreeDSAcstransID());
System.out.println("DSTransID = " + receipt.getMpiDSTransId());
System.out.println("ThreeDSAuthTimeStamp = " + receipt.getMpiThreeDSAuthTimeStamp());
System.out.println("AuthenticationType = " + receipt.getMpiAuthenticationType());
//In Frictionless flow, you may receive TransStatus as "Y",
//in which case you can then proceed directly to Cavv Purchase/Preauth with values below
if(receipt.getMpiTransStatus().equals("Y"))
{
    System.out.println("Cavv = " + receipt.getMpiCavv());
    System.out.println("ECI = " + receipt.getMpiEci());
}
}
catch (Exception e)
{
    e.printStackTrace();
}
}
} // end TestResMpiTxn

```

## 7.4.2 MPI 3DS Authentication Request - 3RI with recurring

**NOTE:** Billing address request fields are recommended to be sent for this transaction, or else the authentication process may fail

### MPI 3DS Authentication Request transaction object definition

```
MpiThreeDSAuthentication mpiThreeDSAuthentication = new
MpiThreeDSAuthentication();
```

### HttpsPostRequest object for MPI 3DS Authentication Request transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mpiThreeDSAuthentication);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	Description
store ID <store_id>	<i>String</i> N/A	mpgReq.setstoreId(store_id); Unique identifier provided by Moneris upon merchant account setup
API token	<i>String</i>	mpgReq.setApiToken(api_

Variable Name	Type and Limits	Description
<api_token>	N/A	<p>token);</p> <p>Unique alphanumeric string assigned by Moneris upon merchant account activation</p> <p>To find your API token, refer to your test or production store's Admin settings in the Merchant Resource Center, at the following URLs:</p> <p>Testing: <a href="https://esqa-monteris.com/mpg/">https://esqa-monteris.com/mpg/</a></p> <p>Production: <a href="https://www3-monteris.com/mpg/">https://www3-monteris.com/mpg/</a></p>

### MPI 3DS Authentication Request transaction request fields – Required

Variable Name	Type and Limits	Description
message category <MessageCategory>	<i>String</i> 2-character numeric	<pre>mpiThreeDSAuthentication.setMessageCategory("02");</pre> <p>Whether the authentication request is for a payment or non-payment use:</p> <p>01 = payment authentication (PA)</p> <p>02 = non-payment authentication (NPA)</p>
device channel <DeviceChannel>	<i>String</i> 2-character numeric	<pre>mpiThreeDSAuthentication.setDeviceChannel("02");</pre> <p>The interface used to initiate the authentication:</p> <p>02 = Browser (BRW)</p> <p>03 = 3DS Requestor Initiated (3RI)</p>
recurring frequency <RecurringFrequency>	<i>String</i> 4-character numeric	<pre>mpiThreeDSAuthentication.setRecurringFrequency("031");</pre> <p>The minimum number of days between recurring transactions. Numeric values between 1 and 9999, leading zero required.</p>

Variable Name	Type and Limits	Description
		oes accepted. Conditional. Required if ri indicator = 01
recurring expiry <RecurringExpiry>	String 8-character numeric	mpiThreeDSAuthentication.setRecurringExpiry ("20221230"); End date after which no further recurring transactions shall be performed. Format is YYYYMMDD. Conditional. Required if ri indicator = 01
ri indicator <RiIndicator>  <b>NOTE:</b> Visa Secure only support ri_ Indicator = 6 or 11 for Payment Transaction and ri Indicator = 3, 4, 5 and 10 for Non Payment Transaction	String 2-character numeric	mpiThreeDSAuthentication.setRiIndicator ("03"); The type of 3DS Requestor Initiated (3RI) request: 01 = Recurring 02 = Installment 03 = Add Card 04 = Maintain Card Information 05 = Account verification 06 = Split/Delayed Shipment 07 = Top-up 08 = Mail Order 09 = Telephone Order 10 = Whitelist 11 = Other Payment Conditional. Required if device_channel = 03
order ID <order_id>	String 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	mpiThreeDSAuthentication.setOrderId(order_id); Merchant-defined transaction identifier that must be unique for every Purchase, Pre-Authorization and Independent Refund transaction. No two transactions of these types may have the same order ID. For Refund, Completion and Purchase Correction trans-

Variable Name	Type and Limits	Description
		<p>actions, the order ID must be the same as that of the original transaction.</p>
data key <data_key> OR credit card number <pan>	<i>String</i> data key limits: 25-character alphanumeric credit card number limits: max 20-character alphanumeric	<pre>mpiThreeDSAuthentication.setData(data_key);</pre> <p><b>data key description:</b></p> <p>Unique identifier for a Vault profile, and used in future Vault financial transactions to associate a transaction with that profile</p> <p>Data key is generated by Moneris and returned to you in the Receipt object when the profile is first registered</p> <pre>mpiThreeDSAuthentication.SetPan(pan);</pre> <p><b>credit card number description:</b></p> <p>Credit card number, usually 16 digits —field can be maximum 20 digits in support of future expansion of card number ranges.</p> <p>Carries the token for network tokenization transactions.</p>
expiry date <expiry_date>	<i>String</i> 4-character alphanumeric YYMM	<pre>mpiThreeDSAuthentication.setExpDate(expiry_date);</pre> <p>Expiry date of the credit card, in YYMM format.</p> <p><b>NOTE:</b> This is the reverse of the MMYY date format that is presented on the card.</p>
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	<pre>mpiThreeDSAuthentication.setAmount(amount);</pre> <p>Transaction dollar amount</p> <p>This must contain at least 3 digits, two of which are penny values</p> <p>Minimum allowable value = \$0.01, maximum allowable value = \$9999999.99</p>

Variable Name	Type and Limits	Description
	<b>EXAMPLE:</b> 1234567.89	
cardholder name <CardholderName>	<i>String</i> 45-character alphanumeric	<pre>mpiThreeDSAuthentication.setCardholderName("CARDHOLDER_NAME_VALUE");</pre> Name of the cardholder <div style="background-color: #e0f2e0; padding: 10px; margin-top: 10px;"> <b>NOTE:</b> Accented characters are not allowable         </div>
billing address <BillAddress1>	<i>String</i> 50-character alphanumeric	<pre>mpiThreeDSAuthentication.setBillAddress1("BILL_STREET_ADDRESS_VALUE");</pre> Cardholder billing address
billing province <BillProvince>	<i>String</i> 3-character alphanumeric	<pre>mpiThreeDSAuthentication.setBillProvince("BILL_PROV_VALUE");</pre> Cardholder province or state <div style="margin-top: 10px;">             Defined in country subdivision ISO 3166-2           </div>
billing city <BillCity>	<i>String</i> 50-character alphanumeric	<pre>mpiThreeDSAuthentication.SetBillCity("BILL_CITY_VALUE");</pre> Cardholder billing city
billing postal code <BillPostalCode>	<i>String</i> 16-character alphanumeric	<pre>mpiThreeDSAuthentication.setBillPostalCode("BILL_POSTAL_CODE_VALUE");</pre> Cardholder billing postal code
billing country <BillCountry>	<i>String</i> 3-character alphanumeric	<pre>mpiThreeDSAuthentication.setBillCountry("BILL_COUNTRY_VALUE");</pre> Cardholder billing country <div style="margin-top: 10px;">             Defined as 3 digit country code ISO 3166-1           </div>
shipping address <ShipAddress1>	<i>String</i> 50-character	<pre>mpiThreeDSAuthentication.setShipAddress1("SHIP_STREET_ADDRESS_VALUE");</pre> Shipping destination address

Variable Name	Type and Limits	Description
		alphanumeric
shipping province <ShipProvince>	<i>String</i> 3-character alphanumeric	<code>mpiThreeDSAuthentication.setShipProvince ("SHIP_PROV_VALUE");</code> Shipping destination province or state Defined in country subdivision ISO 3166-2
shipping city <ShipCity>	<i>String</i> 50-character alphanumeric	<code>mpiThreeDSAuthentication.setShipCity ("SHIP_CITY_VALUE");</code> Shipping destination city
shipping postal code <ShipPostalCode>	<i>String</i> 16-character alphanumeric	<code>mpiThreeDSAuthentication.setShipPostalCode ("SHIP_POSTAL_CODE_VALUE");</code> Shipping destination postal or ZIP code
shipping country <ShipCountry>	<i>String</i> 3-character alphanumeric	<code>mpiThreeDSAuthentication.setShipCountry ("SHIP_COUNTRY_VALUE");</code> Shipping destination country Defined as 3-digit country code in ISO 3166-1
email <Email>	<i>String</i> 254-character alphanumeric	<code>mpiThreeDSAuthentication.setEmail ("EMAIL_VALUE");</code> Cardholder email address
		<p><b>NOTE:</b> This field is not mandatory, but it is required. It is highly recommended to provide the cardholder's email address. Lack of providing the cardholder's address, might increase the risk of rejects.</p>

### MPI 3DS Authentication Request transaction request fields – Optional

Variable Name	Type and Lim-its	Description
currency <Currency>	<i>String</i> 3-character numeric	<code>mpiThreeDSAuthentication.setCurrency ("CURRENCY_VALUE");</code> ISO 4217 3 digit currency code CAD = 124

Variable Name	Type and Lim-its	Description
		<p>USD = 840</p> <p><b>NOTE:</b> This field should not be sent unless Multi Currency Pricing is enabled on your merchant account</p>
decoupled request indicator < DecoupledRequestIndicator>	<i>String</i> 1-character alphabetic	<pre>mpiThreeDSAuthentication.setDecoupledRequestIndicator("Y");</pre> <p>Whether the request utilizes Decoupled Authentication or not, if the ACS confirms its use.</p> <p>Y = Decoupled Authentication is supported and preferred if challenge is necessary</p> <p>N = Do not use Decoupled Authentication (Default)</p> <p>Defaults to N if unused.</p>
decoupled request max time < DecoupledRequestMaxTime>	<i>String</i> 5-character numeric	<pre>mpiThreeDSAuthentication.setDecoupledRequestMaxTime("00010");</pre> <p>The maximum minutes that Moneris waits for an ACS to provide results.</p> <p>Numeric values between 1 and 10080. The max is equivalent to 7 days.</p> <p>Conditional. Required if device_channel = 03 and decoupled_request_indicator = Y</p>
decoupled request async URL < DecoupledRequestAsyncUrl>	<i>String</i> 256-character alphanumeric	<pre>mpiThreeDSAuthentication.setDecoupledRequestAsyncUrl("https://yourasyncnotificationurl.com");</pre> <p>Your URL where Moneris will POST the response back from ACS. Moneris reattempts 3 times to POST the response.</p> <p>Conditional. Only sent if decoupled_request_indicator = Y</p>
prior request auth info < PriorAuthenticationInfo>	<i>Object</i> N/A	<pre>mpiThreeDSAuthentication.setPriorRequestAuthInfo(pai);</pre> <p>Object containing details for a prior 3DS authentication for this series of transactions. This is a nested object within the authentication transaction, and required when storing or using the information about the prior authentication for that card. For information about fields in the Prior</p>

Variable Name	Type and Limits	Description
		Authentication Info object, see MPI 3DS Prior Authentication Info Object and Variables.

**MPI 3DS Prior Authentication Info**

Variable Name	Type and Limits	Description
prior request auth data  <prior_request_auth_data>	<i>String</i>  36-character alphanumeric	prior_request_auth_data="abc";  Refers to the DSTransID in the response of the previous 3DS authentication.
prior request ref  <prior_request_auth_ref>	<i>String</i>  36-character alphanumeric	prior_request_ref="d7c1ee99-9478-44a6-b1f2-391e29c6b340";  Refers to the 3DS ACS Transaction ID in the response of the previous 3DS authentication.
prior request auth method  <prior_request_auth_method>	<i>String</i>  2-character numeric	prior_request_auth_method = "01";  Mechanism used by the cardholder to authenticate in the previous 3DS authentication:  01 = Frictionless authentication  02 = Challenge authentication  03 = AVS verified  04 = Other issuer methods
prior request auth timestamp  <prior_request_auth_timestamp>	<i>String</i>  12-character numeric	prior_request_auth_timestamp = "201710282113";  Date and time in UTC of the prior cardholder authentication. Found in the previous 3DS authentication response as 3DS AuthTimeStamp.  Format is YYYYMMDDHHMM.

## Sample MPI 3DS Authentication Request - 3RI with recurring

```

package Canada;
import JavaAPI.*;
public class TestCanadaMpiThreeDSAuthentication
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String prior_request_ref="d7c1ee99-9478-44a6-b1f2-391e29c6b340";
String prior_request_auth_data="abc";
String prior_request_auth_method = "01";
String prior_request_auth_timestamp = "201710282113";
String processing_country_code = "CA";
MpiThreeDSAuthentication mpiThreeDSAuthentication = new MpiThreeDSAuthentication();
mpiThreeDSAuthentication.setOrderId("Test159787ssa3215193"); //must be the same one that was
used in MpiCardLookup call
mpiThreeDSAuthentication.setCardholderName("Moneris Test");
mpiThreeDSAuthentication.setPan("343427006265962");
// mpiThreeDSAuthentication.setDataKey("xR1904FgrZUYdGkmqHTqiEw97"); //Optional - For Moneris
Vault and Hosted Tokenization tokens in place of setPan
mpiThreeDSAuthentication.setExdate("2310");
mpiThreeDSAuthentication.setAmount("1.00");
mpiThreeDSAuthentication.setThreeDSCompletionInd("Y"); // (Y|N|U) indicates whether 3ds method
MpiCardLookup was successfully completed
mpiThreeDSAuthentication.setRequestType("02"); //(01=payment|02=recur)
mpiThreeDSAuthentication.setPurchaseDate("20200819035249"); //(YYYYMMDDHHMMSS)
mpiThreeDSAuthentication.setNotificationURL("https://yournotificationurl.com"); // (Website
where response from RRes or CRes after challenge will go)
mpiThreeDSAuthentication.setChallengeWindowSize("03"); //(01 = 250 x 400, 02 = 390 x 400, 03
= 500 x 600, 04 = 600 x 400, 05 = Full screen)
mpiThreeDSAuthentication.setEmail("test@email.com");
mpiThreeDSAuthentication.setBrowserUserAgent("Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/80.0.3987.132 Safari/537.36\\");
mpiThreeDSAuthentication.setBrowserJavaEnabled("true"); //(true|false)
mpiThreeDSAuthentication.setBrowserScreenHeight("1000"); //(pixel height of cardholder
screen)
mpiThreeDSAuthentication.setBrowserScreenWidth("1920"); //(pixel width of cardholder screen)
mpiThreeDSAuthentication.setBrowserLanguage("en-GB"); //(defined by IETF BCP47)
//Optional Methods
mpiThreeDSAuthentication.setBillAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setBillProvince("ON");
mpiThreeDSAuthentication.setBillCity("Toronto");
mpiThreeDSAuthentication.setBillPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setBillCountry("124");
mpiThreeDSAuthentication.setShipAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setShipProvince("ON");
mpiThreeDSAuthentication.setShipCity("Toronto");
mpiThreeDSAuthentication.setShipPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setShipCountry("124");
mpiThreeDSAuthentication.setRequestChallenge("Y"); // (Y|N Requesting challenge regardless of
outcome)
*****3DS2.2*****
mpiThreeDSAuthentication.setMessageCategory("01");
mpiThreeDSAuthentication.setDeviceChannel("03");
// mpiThreeDSAuthentication.setDecoupledRequestIndicator("Y");
// mpiThreeDSAuthentication.setDecoupledRequestMaxTime("000010");
// mpiThreeDSAuthentication.setDecoupledRequestAsyncUrl("localhost:8080/googlepay");
mpiThreeDSAuthentication.setRiIndicator("01");
PriorAuthenticationInfo priorAuthenticationInfo= new PriorAuthenticationInfo();
// priorAuthenticationInfo.setPriorParams(prior_request_auth_data,prior_request_ref,prior_
request_auth_method,prior_request_auth_timestamp);
mpiThreeDSAuthentication.setRecurringExpiry("20221230");
mpiThreeDSAuthentication.setRecurringFrequency("031");

```

```

//*****OPTIONAL VARIABLES*****
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false or comment out this line for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mpiThreeDSAuthentication);
System.out.println(mpiThreeDSAuthentication.toXML());
mpgReq.send();
/************* REQUEST *****/
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("Message = " + receipt.getMessage());
System.out.println("MessageType = " + receipt.getMpiMessageType());
System.out.println("TransStatus = " + receipt.getMpiTransStatus());
System.out.println("TransStatusReason = " + receipt.getMpiTransStatusReason());
System.out.println("ChallengeURL = " + receipt.getMpiChallengeURL());
System.out.println("ChallengeData = " + receipt.getMpiChallengeData());
System.out.println("ThreeDServerTransId = " + receipt.getMpiThreeDServerTransId());
System.out.println("ThreeDSVersion = " + receipt.getMpiThreeDSVersion());
System.out.println("ThreeDSAcctsTransID = " + receipt.getMpiThreeDSAcctsTransID());
System.out.println("DSTransID = " + receipt.getMpiDSTransId());
System.out.println("ThreeDSAuthTimeStamp = " + receipt.getMpiThreeDSAuthTimeStamp());
System.out.println("AuthenticationType = " + receipt.getMpiAuthenticationType());
System.out.println("CardHolderInfo = " + receipt.getMpiCardholderInfo());
//In Frictionless flow, you may receive TransStatus as "Y",
//in which case you can then proceed directly to Cavv Purchase/Preauth with values below
if(receipt.getMpiTransStatus().equals("Y"))
{
System.out.println("Cavv = " + receipt.getMpiCavv());
System.out.println("ECI = " + receipt.getMpiEci());
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
} // end TestResMpiTxn

```

#### 7.4.3 MPI 3DS Authentication Request - 3RI, non-recurring

**NOTE:** Billing address request fields are recommended to be sent for this transaction, or else the authentication process may fail

#### MPI 3DS Authentication Request transaction object definition

```

MpiThreeDSAuthentication mpiThreeDSAuthentication = new
MpiThreeDSAuthentication();

```

### HttpsPostRequest object for MPI 3DS Authentication Request transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mpiThreeDSAuthentication);
```

**WARNING:** Do not send fields related to 3RI on browser-based authentications.

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	Description
store ID <store_id>	<i>String</i> N/A	mpgReq.setstoreId(store_id); Unique identifier provided by Moneris upon merchant account setup
API token <api_token>	<i>String</i> N/A	mpgReq.setApiToken(api_token); Unique alphanumeric string assigned by Moneris upon merchant account activation
		To find your API token, refer to your test or production store's Admin settings in the Merchant Resource Center, at the following URLs:  Testing: <a href="https://esqa-moneris.com/mpg/">https://esqa-moneris.com/mpg/</a>  Production: <a href="https://www3-moneris.com/mpg/">https://www3-moneris.com/mpg/</a>

### MPI 3DS Authentication Request transaction request fields – Required

Variable Name	Type and Limits	Description
message category <MessageCategory>	<i>String</i> 2-character numeric	mpiThreeDSAuthentication.setMessageCategory("02"); Whether the authentication request is for a payment or non-payment use:

Variable Name	Type and Limits	Description
		01 = payment authentication (PA) 02 = non-payment authentication (NPA)
device channel <DeviceChannel>	<i>String</i>  2-character numeric	mpiThreeDSAuthentication.setDeviceChannel ("02");  The interface used to initiate the authentication:  02 = Browser (BRW)  03 = 3DS Requestor Initiated (3RI)
ri indicator <RiIndicator>  <b>NOTE:</b> Visa Secure only support ri_ Indicator = 6 or 11 for Payment Transaction and ri Indicator = 3, 4, 5 and 10 for Non Payment Transaction	<i>String</i>  2-character numeric	mpiThreeDSAuthentication.setRiIndicator ("03");  The type of 3DS Requestor Initiated (3RI) request:  01 = Recurring 02 = Installment 03 = Add Card 04 = Maintain Card Information 05 = Account verification 06 = Split/Delayed Shipment 07 = Top-up 08 = Mail Order 09 = Telephone Order 10 = Whitelist 11 = Other Payment
order ID <order_id>	<i>String</i>  50-character alphanumeric  a-Z A-Z 0-9 _ - : .  @ spaces	mpiThreeDSAuthentication.setOrderId(order_id);  Merchant-defined transaction identifier that must be unique for every Purchase, Pre-Authorization and Independent Refund transaction. No two transactions of these types may have the same order ID.  For Refund, Completion and Purchase Correction transactions, the order ID must be the same as that of the ori-

Variable Name	Type and Limits	Description
		ginal transaction.
data key  <data_key>  OR  credit card number  <pan>	<i>String</i>  data key limits:  25-character alphanumeric  credit card number limits:  max 20-character alphanumeric	mpiThreeDSAuthentication.setData (data_key);  <b>data key description:</b>  Unique identifier for a Vault profile, and used in future Vault financial transactions to associate a transaction with that profile  Data key is generated by Moneris and returned to you in the Receipt object when the profile is first registered  mpiThreeDSAuthentication.SetPan (pan);  <b>credit card number description:</b>  Credit card number, usually 16 digits —field can be maximum 20 digits in support of future expansion of card number ranges.  Carries the token for network tokenization transactions.
expiry date  <expiry_date>	<i>String</i>  4-character alphanumeric  YYMM	mpiThreeDSAuthentication.setExpDate (expiry_date);  Expiry date of the credit card, in YYMM format.  <b>NOTE:</b> This is the reverse of the MMYY date format that is presented on the card.
amount  <amount>	<i>String</i>  10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	mpiThreeDSAuthentication.setAmount (amount);  Transaction dollar amount  This must contain at least 3 digits, two of which are penny values  Minimum allowable value = \$0.01, maximum allowable value = \$9999999.99
	<b>EXAMPLE:</b>	

Variable Name	Type and Limits	Description
	1234567.89	
cardholder name <CardholderName>	<p><i>String</i></p> <p>45-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; width: fit-content;"> <b>NOTE:</b> Accented characters are not allowable       </div>	<pre>mpiThreeDSAuthentication.setCardholderName("CARDHOLDER_NAME_VALUE");</pre> <p>Name of the cardholder</p>
billing address <BillAddress1>	<p><i>String</i></p> <p>50-character alphanumeric</p>	<pre>mpiThreeDSAuthentication.setBillAddress1("BILL_STREET_ADDRESS_VALUE");</pre> <p>Cardholder billing address</p>
billing province <BillProvince>	<p><i>String</i></p> <p>3-character alphanumeric</p>	<pre>mpiThreeDSAuthentication.setBillProvince("BILL_PROV_VALUE");</pre> <p>Cardholder province or state</p> <p>Defined in country subdivision ISO 3166-2</p>
billing city <BillCity>	<p><i>String</i></p> <p>50-character alphanumeric</p>	<pre>mpiThreeDSAuthentication.SetBillCity("BILL_CITY_VALUE");</pre> <p>Cardholder billing city</p>
billing postal code <BillPostalCode>	<p><i>String</i></p> <p>16-character alphanumeric</p>	<pre>mpiThreeDSAuthentication.setBillPostalCode("BILL_POSTAL_CODE_VALUE");</pre> <p>Cardholder billing postal code</p>
billing country <BillCountry>	<p><i>String</i></p> <p>3-character alphanumeric</p>	<pre>mpiThreeDSAuthentication.setBillCountry("BILL_COUNTRY_VALUE");</pre> <p>Cardholder billing country</p> <p>Defined as 3 digit country code ISO 3166-1</p>
shipping address <ShipAddress1>	<p><i>String</i></p> <p>50-character alphanumeric</p>	<pre>mpiThreeDSAuthentication.setShipAddress1("SHIP_STREET_ADDRESS_VALUE");</pre> <p>Shipping destination address</p>

Variable Name	Type and Limits	Description
shipping province <ShipProvince>	<i>String</i> 3-character alphanumeric	mpiThreeDSAuthentication.setShipProvince ("SHIP_PROV_VALUE");  Shipping destination province or state  Defined in country subdivision ISO 3166-2
shipping city <ShipCity>	<i>String</i> 50-character alphanumeric	mpiThreeDSAuthentication.setShipCity ("SHIP_CITY_VALUE");  Shipping destination city
shipping postal code <ShipPostalCode>	<i>String</i> 16-character alphanumeric	mpiThreeDSAuthentication.setShipPostalCode ("SHIP_POSTAL_CODE_VALUE");  Shipping destination postal or ZIP code
shipping country <ShipCountry>	<i>String</i> 3-character alphanumeric	mpiThreeDSAuthentication.setShipCountry ("SHIP_COUNTRY_VALUE");  Shipping destination country  Defined as 3-digit country code in ISO 3166-1
email <Email>	<i>String</i> 254-character alphanumeric	mpiThreeDSAuthentication.setEmail ("EMAIL_VALUE");  Cardholder email address
<p><b>NOTE:</b> This field is not mandatory, but it is required. It is highly recommended to provide the cardholder's email address. Lack of providing the cardholder's address, might increase the risk of rejects.</p>		

### MPI 3DS Authentication Request transaction request fields – Optional

Variable Name	Type and Lim-its	Description
currency <Currency>	<i>String</i> 3-character numeric	mpiThreeDSAuthentication.setCurrency ("CURRENCY_VALUE");  ISO 4217 3 digit currency code  CAD = 124  USD = 840

Variable Name	Type and Lim-its	Description
		<p><b>NOTE:</b> This field should not be sent unless Multi Currency Pricing is enabled on your merchant account</p>
decoupled request indicator < DecoupledRequestIndicator>	<i>String</i> 1-character alphabetic	<pre>mpiThreeDSAuthentication.setDecoupledRequestIndicator("Y");</pre> <p>Whether the request utilizes Decoupled Authentication or not, if the ACS confirms its use.</p> <p>Y = Decoupled Authentication is supported and preferred if challenge is necessary</p> <p>N = Do not use Decoupled Authentication (Default)</p> <p>Defaults to N if unused.</p>
decoupled request max time < DecoupledRequestMaxTime>	<i>String</i> 5-character numeric	<pre>mpiThreeDSAuthentication.setDecoupledRequestMaxTime("00010");</pre> <p>The maximum minutes that Moneris waits for an ACS to provide results.</p> <p>Numeric values between 1 and 10080. The max is equivalent to 7 days.</p> <p>Conditional. Required if device_channel = 03 and decoupled_request_indicator = Y</p>
decoupled request async URL < DecoupledRequestAsyncUrl>	<i>String</i> 256-character alphanumeric	<pre>mpiThreeDSAuthentication.setDecoupledRequestAsyncUrl("https://yourasyncnotificationurl.com");</pre> <p>Your URL where Moneris will POST the response back from ACS. Moneris reattempts 3 times to POST the response.</p> <p>Conditional. Only sent if decoupled_request_indicator = Y</p>
prior request auth info < PriorAuthenticationInfo>	<i>Object</i> N/A	<pre>mpiThreeDSAuthentication.setPriorRequestAuthInfo(pai);</pre> <p>Object containing details for a prior 3DS authentication for this series of transactions. This is a nested object within the authentication transaction, and required when storing or using the information about the prior authentication for that card. For information about fields in the Prior Authentication Info object, see MPI 3DS Prior Authentication Info Object and Variables.</p>

## MPI 3DS Prior Authentication Info

Variable Name	Type and Limits	Description
prior request auth data <prior_request_auth_data>	<i>String</i> 36-character alphanumeric	prior_request_auth_data="abc"; Refers to the DSTransID in the response of the previous 3DS authentication.
prior request ref <prior_request_auth_ref>	<i>String</i> 36-character alphanumeric	prior_request_ref="d7c1ee99-9478-44a6-b1f2-391e29c6b340"; Refers to the 3DS ACS Transaction ID in the response of the previous 3DS authentication.
prior request auth method <prior_request_auth_method>	<i>String</i> 2-character numeric	prior_request_auth_method = "01"; Mechanism used by the cardholder to authenticate in the previous 3DS authentication:  01 = Frictionless authentication 02 = Challenge authentication 03 = AVS verified 04 = Other issuer methods
prior request auth timestamp <prior_request_auth_timestamp>	<i>String</i> 12-character numeric	prior_request_auth_timestamp = "201710282113"; Date and time in UTC of the prior cardholder authentication. Found in the previous 3DS authentication response as 3DS AuthTimeStamp.  Format is YYYYMMDDHHMM.

## Sample MPI 3DS Authentication Request - 3RI without recurring

```
package Canada;
import JavaAPI.*;
public class TestCanadaMpithreeDSAuthentication
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String prior_request_ref="d7c1ee99-9478-44a6-b1f2-391e29c6b340";
```

```

String prior_request_auth_data="abc";
String prior_request_auth_method = "01";
String prior_request_auth_timestamp = "201710282113";
String processing_country_code = "CA";
MpThreeDSAuthentication mpiThreeDSAuthentication = new MpThreeDSAuthentication();
mpiThreeDSAuthentication.setOrderId("Test159787ssa3215193"); //must be the same one that was
used in MpCardLookup call
mpiThreeDSAuthentication.setCardholderName("Moneris Test");
mpiThreeDSAuthentication.setPan("347668693641199");
// mpiThreeDSAuthentication.setaDataKey("xRl904FgrZUYdGkmqHTqiEw97"); //Optional - For Moneris
Vault and Hosted Tokenization tokens in place of setPan
mpiThreeDSAuthentication.setExppdate("2310");
mpiThreeDSAuthentication.setAmount("1.00");
mpiThreeDSAuthentication.setThreeDSCompletionInd("Y"); // (Y|N|U) indicates whether 3ds method
MpCardLookup was successfully completed
mpiThreeDSAuthentication.setRequestType("01"); //(01=payment|02=recur)
mpiThreeDSAuthentication.setPurchaseDate("20200819035249"); //(YYYYMMDDHHMMSS)
mpiThreeDSAuthentication.setNotificationURL("https://yournotificationurl.com"); //(Website
where response from RRes or CRes after challenge will go)
mpiThreeDSAuthentication.setChallengeWindowSize("03"); //(01 = 250 x 400, 02 = 390 x 400, 03
= 500 x 600, 04 = 600 x 400, 05 = Full screen)
mpiThreeDSAuthentication.setEmail("test@email.com");
mpiThreeDSAuthentication.setBrowserUserAgent("Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/80.0.3987.132 Safari/537.36\\\"");
mpiThreeDSAuthentication.setBrowserJavaEnabled("true"); //(true|false)
mpiThreeDSAuthentication.setBrowserScreenHeight("1000"); //(pixel height of cardholder
screen)
mpiThreeDSAuthentication.setBrowserScreenWidth("1920"); //(pixel width of cardholder screen)
mpiThreeDSAuthentication.setBrowserLanguage("en-GB"); //(defined by IETF BCP47)

//Optional Methods
mpiThreeDSAuthentication.setBillAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setBillProvince("ON");
mpiThreeDSAuthentication.setBillCity("Toronto");
mpiThreeDSAuthentication.setBillPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setBillCountry("124");

mpiThreeDSAuthentication.setShipAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setShipProvince("ON");
mpiThreeDSAuthentication.setShipCity("Toronto");
mpiThreeDSAuthentication.setShipPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setShipCountry("124");

mpiThreeDSAuthentication.setRequestChallenge("Y"); //(Y|N Requesting challenge regardless of
outcome)
*****3DS2.2*****
mpiThreeDSAuthentication.setMessageCategory("01");
mpiThreeDSAuthentication.setDeviceChannel("03");
// mpiThreeDSAuthentication.setDecoupledRequestIndicator("Y");
// mpiThreeDSAuthentication.setDecoupledRequestMaxTime("000010");
// mpiThreeDSAuthentication.setDecoupledRequestAsyncUrl("localhost:8080/googlepay");
mpiThreeDSAuthentication.setRiIndicator("01");
PriorAuthenticationInfo priorAuthenticationInfo= new PriorAuthenticationInfo();
priorAuthenticationInfo.setPriorParams(prior_request_auth_data,prior_request_ref,
prior_request_auth_method,prior_request_auth_timestamp);
// mpiThreeDSAuthentication.setRecurringExpiry("20221230");
// mpiThreeDSAuthentication.setRecurringFrequency("031");
*****OPTIONAL VARIABLES*****
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false or comment out this line for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mpiThreeDSAuthentication);
System.out.println(mpiThreeDSAuthentication.toXML());

```

```

mpgReq.send();
/********************* REQUEST *****/
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("Message = " + receipt.getMessage());
System.out.println("MessageType = " + receipt.getMpiMessageType());
System.out.println("TransStatus = " + receipt.getMpiTransStatus());
System.out.println("TransStatusReason = " + receipt.getMpiTransStatusReason());
System.out.println("ChallengeURL = " + receipt.getMpiChallengeURL());
System.out.println("ChallengeData = " + receipt.getMpiChallengeData());
System.out.println("ThreeDServerTransId = " + receipt.getMpiThreeDServerTransId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());
System.out.println("ThreeDSAcstTransID = " + receipt.getMpiThreeDSAcstTransID());
System.out.println("DSTransID = " + receipt.getMpiDSTransId());
System.out.println("ThreeDSAuthTimeStamp = " + receipt.getMpiThreeDSAuthTimeStamp());
System.out.println("AuthenticationType = " + receipt.getMpiAuthenticationType());
//In Frictionless flow, you may receive TransStatus as "Y",
//in which case you can then proceed directly to Cavv Purchase/Preauth with values below
if(receipt.getMpiTransStatus().equals("Y"))
{
System.out.println("Cavv = " + receipt.getMpiCavv());
System.out.println("ECI = " + receipt.getMpiEci());
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
} // end TestResMpiTxn

```

## 7.5 Handling the Challenge Flow

If you get a TransStatus = “C” in your threeDSAuthentication Response, then a form must be built and POSTed to the URL provided.

The form can be dynamically generated and added to the DOM and submitted or created and submitted in a manner that suits your environment. This can be built as a full page redirect or presented as an inline iframe or as a lightbox.

If you wish for this to be loaded inside a defined space it must conform to the size specified in the ChallengeWindowSize from the request. The “action” is retrieved from the ChallengeURL and the “[creq](#)” field is retrieved from the ChallengeData.

Below is a sample of a basic static form to help visualize the data and fields that need to be submitted.

### 7.5.1 Cavv Lookup Request – [mpiCavvLookup](#)

(Challenge Flow Only)

In the challenge flow, the 3DS server will POST a [cres](#) value back to the notificationURL provided in the threeDSAuthentication request once the cardholder has completed the challenge. The “cres” is then pos-

ted to the Moneris 3DS server in the CavvLookup request, the response to this request will include the result of the challenge, which will include the eci and the cavv if the challenge was successful.

### Cavv Lookup Request transaction object definition

```
MpiCavvLookup mpiCavvLookup = new MpiCavvLookup();
```

### HttpsPostRequest object for Cavv Lookup Request transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mpiCavvLookup);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Cavv Lookup Request transaction request fields – Required

Variable Name	Type and Limits	
cres	<i>String</i> 200-character alpha-numeric	mpiCavvLookup.setCRes(cres);

### Sample Cavv Lookup Request

```
package Canada;
import JavaAPI.*;
public class TestCanadaMpiCavvLookup
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String processing_country_code = "CA";

//BASE64 Encoded CRes value returned from response at completion of challenge flow.
String cres =
"eyJhY3NUcmFuc01EIjoiNzQ0ZDI2NjUtNjU2Yy00ZGNiLTg3MWUtYTByYmMwODA0OTYzIiwibWVzc2FnZVR5cGUioiJD
UmVzIiwiY2hhbGx1bmdlQ29tcGx1dGlvbkluZCI6IlkiLCJtZXNzYWdlVmVyc21vbiI6IjIuMS4wIiwidHJhbnNTdGF0d
XMiOijZIiwidGhyZWVEU1NlcnZlclRyYW5zSUQiOijlMTFkNDk4NS04ZDI1LTQwZWQtOTlkNi1jMzgwM2Z1NWU2OGYifQ
==";

MpiCavvLookup mpiCavvLookup = new MpiCavvLookup();
mpiCavvLookup.setCRes(cres);
```

```

*****OPTIONAL VARIABLES*****
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false or comment out this line for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mpiCavvLookup);
mpgReq.send();
***** REQUEST *****/
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("Message = " + receipt.getMessage());
System.out.println("MessageType = " + receipt.getMpiMessageType());
System.out.println("ThreeDSserverTransId = " + receipt.getMpiThreeDSserverTransId());
System.out.println("TransStatus = " + receipt.getMpiTransStatus());
System.out.println("ChallengeCompletionIndicator = " +
receipt.getMpiChallengeCompletionIndicator());
System.out.println("Cavv = " + receipt.getMpiCavv());
System.out.println("ECI = " + receipt.getMpiEci());
}
catch (Exception e)
{
e.printStackTrace();
}
}
} // end TestResMpiTxn

```

## 7.6 Handling the Decoupled Authentication Flow

If you get a TransStatus = “D” in your threeDSAuthentication Response, then your server must be prepared to accept a second asynchronous response from Moneris.

The cardholder will be engaged by their issuer for cardholder authentication outside the 3DS protocol. This may involve alternate authentication applications or SMS prompts to the cardholder to confirm.

The cardholder is given up to 7 days to complete this decoupled challenge. Once completed, the issuer will communicate to Moneris and our MPI system sends a second 3DS Authentication Response to the address you define in <decoupled\_request\_async\_url>

### Sample Authentication Request – 3RI With Decoupled Authentication for MOTO

```

package Canada;
import JavaAPI.*;
public class TestCanadaMpiThreeDSAuthentication
{
public static void main(String[] args)
{
String store_id = "moneris";
String api_token = "hurgle";
String prior_request_ref="d7c1ee99-9478-44a6-b1f2-391e29c6b340";
String prior_request_auth_data="abc";
String prior_request_auth_method = "01";
String prior_request_auth_timestamp = "201710282113";
String processing_country_code = "CA";
MpiThreeDSAuthentication mpiThreeDSAuthentication = new MpiThreeDSAuthentication();
mpiThreeDSAuthentication.setOrderId("Test159787ssa3215193"); //must be the same one that was
used in MpiCardLookup call
mpiThreeDSAuthentication.setCardholderName("Moneris Test");
}
}

```

```

mpiThreeDSAuthentication.setPan("347668693641199");
// mpiThreeDSAuthentication.setDataKey("xRl904FgrZUYdGkmqHTqiEw97"); //Optional - For Moneris
Vault and Hosted Tokenization tokens in place of setPan
mpiThreeDSAuthentication.setExpdate("2310");
mpiThreeDSAuthentication.setAmount("1.00");
mpiThreeDSAuthentication.setThreeDSCompletionInd("Y"); // (Y|N|U) indicates whether 3ds method
MpICardLookup was successfully completed
mpiThreeDSAuthentication.setRequestType("01"); // (01=payment|02=recur)
mpiThreeDSAuthentication.setPurchaseDate("20200819035249"); // (YYYYMMDDHHMMSS)
mpiThreeDSAuthentication.setNotificationURL("https://yournotificationurl.com"); // (Website
where response from RRes or CRes after challenge will go)
mpiThreeDSAuthentication.setChallengeWindowSize("03"); // (01 = 250 x 400, 02 = 390 x 400, 03
= 500 x 600, 04 = 600 x 400, 05 = Full screen)
mpiThreeDSAuthentication.setEmail("test@email.com");
mpiThreeDSAuthentication.setBrowserUserAgent("Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/80.0.3987.132 Safari/537.36\\");
mpiThreeDSAuthentication.setBrowserJavaEnabled("true"); // (true|false)
mpiThreeDSAuthentication.setBrowserScreenHeight("1000"); // (pixel height of cardholder
screen)
mpiThreeDSAuthentication.setBrowserScreenWidth("1920"); // (pixel width of cardholder screen)
mpiThreeDSAuthentication.setBrowserLanguage("en-GB"); // (defined by IETF BCP47)

//Optional Methods
mpiThreeDSAuthentication.setBillAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setBillProvince("ON");
mpiThreeDSAuthentication.setBillCity("Toronto");
mpiThreeDSAuthentication.setBillPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setBillCountry("124");

mpiThreeDSAuthentication.setShipAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setShipProvince("ON");
mpiThreeDSAuthentication.setShipCity("Toronto");
mpiThreeDSAuthentication.setShipPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setShipCountry("124");

mpiThreeDSAuthentication.setRequestChallenge("Y"); // (Y|N Requesting challenge regardless of
outcome)
//*****3DS2.2*****
mpiThreeDSAuthentication.setMessageCategory("01");
mpiThreeDSAuthentication.setDeviceChannel("03");
mpiThreeDSAuthentication.setDecoupledRequestIndicator("Y");
mpiThreeDSAuthentication.setDecoupledRequestMaxTime("000010");
mpiThreeDSAuthentication.setDecoupledRequestAsyncUrl("localhost:8080/googlepay");
mpiThreeDSAuthentication.setRiIndicator("08");
// PriorAuthenticationInfo priorAuthenticationInfo= new PriorAuthenticationInfo();
// priorAuthenticationInfo.setPriorParams(prior_request_auth_data,prior_request_ref,
// prior_request_auth_method,prior_request_auth_timestamp);
// mpiThreeDSAuthentication.setRecurringExpiry("20221230");
// mpiThreeDSAuthentication.setRecurringFrequency("031");
//*****OPTIONAL VARIABLES*****
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false or comment out this line for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mpiThreeDSAuthentication);
System.out.println(mpiThreeDSAuthentication.toXML());
mpgReq.send();
***** REQUEST *****/
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("Message = " + receipt.getMessage());
}

```

```

System.out.println("MessageType = " + receipt.getMpiMessageType());
System.out.println("TransStatus = " + receipt.getMpiTransStatus());
System.out.println("TransStatusReason = " + receipt.getMpiTransStatusReason());
System.out.println("ChallengeURL = " + receipt.getMpiChallengeURL());
System.out.println("ChallengeData = " + receipt.getMpiChallengeData());
System.out.println("ThreeDServerTransId = " + receipt.getMpiThreeDSserverTransId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());
System.out.println("ThreeDSAcstransID = " + receipt.getMpiThreeDSAcstransID());
System.out.println("DSTransID = " + receipt.getMpiDSTransID());
System.out.println("ThreeDSAuthTimeStamp = " + receipt.getMpiThreeDSAuthTimeStamp());
System.out.println("AuthenticationType = " + receipt.getMpiAuthenticationType());
//In Frictionless flow, you may receive TransStatus as "Y",
//in which case you can then proceed directly to Cavv Purchase/Preauth with values below
if(receipt.getMpiTransStatus().equals("Y"))
{
    System.out.println("Cavv = " + receipt.getMpiCavv());
    System.out.println("ECI = " + receipt.getMpiEci());
}
}
catch (Exception e)
{
    e.printStackTrace();
}
}
} // end TestResMpiTxn

```

## Sample Authentication Request – 3RI With Prior Authentication and Decoupled Authentication

```

package Canada;
import JavaAPI.*;
public class TestCanadaMpiThreeDSAuthentication
{
    public static void main(String[] args)
    {
        String store_id = "moneris";
        String api_token = "hurgle";
        String prior_request_ref="d7clee99-9478-44a6-b1f2-391e29c6b340";
        String prior_request_auth_data="abc";
        String prior_request_auth_method = "01";
        String prior_request_auth_timestamp = "201710282113";
        String processing_country_code = "CA";
        MpiThreeDSAuthentication mpiThreeDSAuthentication = new MpiThreeDSAuthentication();
        mpiThreeDSAuthentication.setOrderId("Test159787ssa3215193"); //must be the same one that was
        used in MpiCardLookup call
        mpiThreeDSAuthentication.setCardholderName("Moneris Test");
        mpiThreeDSAuthentication.setPan("347668693641199");
        // mpiThreeDSAuthentication.setDataKey("xR1904FgrZUYdGkmqHTqiEw97"); //Optional - For Moneris
        Vault and Hosted Tokenization tokens in place of setPan
        mpiThreeDSAuthentication.setExppdate("2310");
        mpiThreeDSAuthentication.setAmount("1.00");
        mpiThreeDSAuthentication.setThreeDSCompletionInd("Y"); // (Y|N|U) indicates whether 3ds method
        MpiCardLookup was successfully completed
        mpiThreeDSAuthentication.setRequestType("01"); //(01=payment|02=recur)
        mpiThreeDSAuthentication.setPurchaseDate("20200819035249"); //(YYYYMMDDHHMMSS)
        mpiThreeDSAuthentication.setNotificationURL("https://yournotificationurl.com"); // (Website
        where response from RRes or CRes after challenge will go)
        mpiThreeDSAuthentication.setChallengeWindowSize("03"); //(01 = 250 x 400, 02 = 390 x 400, 03
        = 500 x 600, 04 = 600 x 400, 05 = Full screen)
        mpiThreeDSAuthentication.setEmail("test@email.com");
        mpiThreeDSAuthentication.setBrowserUserAgent("Mozilla/5.0 (Windows NT 10.0; Win64; x64)
        AppleWebKit/537.36 (KHTML, like Gecko) Chrome/80.0.3987.132 Safari/537.36\\\"");
        mpiThreeDSAuthentication.setBrowserJavaEnabled("true"); //(true|false)
    }
}

```

```

mpiThreeDSAuthentication.setBrowserScreenHeight("1000"); // (pixel height of cardholder screen)
mpiThreeDSAuthentication.setBrowserScreenWidth("1920"); // (pixel width of cardholder screen)
mpiThreeDSAuthentication.setBrowserLanguage("en-GB"); // (defined by IETF BCP47)

//Optional Methods
mpiThreeDSAuthentication.setBillAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setBillProvince("ON");
mpiThreeDSAuthentication.setBillCity("Toronto");
mpiThreeDSAuthentication.setBillPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setBillCountry("124");

mpiThreeDSAuthentication.setShipAddress1("3300 Bloor St W");
mpiThreeDSAuthentication.setShipProvince("ON");
mpiThreeDSAuthentication.setShipCity("Toronto");
mpiThreeDSAuthentication.setShipPostalCode("M8X 2X2");
mpiThreeDSAuthentication.setShipCountry("124");

mpiThreeDSAuthentication.setRequestChallenge("Y"); // (Y|N Requesting challenge regardless of outcome)
//*****3DS2.2*****
mpiThreeDSAuthentication.setMessageCategory("01");
mpiThreeDSAuthentication.setDeviceChannel("03");
mpiThreeDSAuthentication.setDecoupledRequestIndicator("Y");
mpiThreeDSAuthentication.setDecoupledRequestMaxTime("000010");
mpiThreeDSAuthentication.setDecoupledRequestAsyncUrl("localhost:8080/googlepay");
mpiThreeDSAuthentication.setRiIndicator("08");
PriorAuthenticationInfo priorAuthenticationInfo= new PriorAuthenticationInfo();
priorAuthenticationInfo.setPriorParams(prior_request_auth_data,prior_request_ref,
prior_request_auth_method,prior_request_auth_timestamp);
// mpiThreeDSAuthentication.setRecurringExpiry("20221230");
// mpiThreeDSAuthentication.setRecurringFrequency("031");
//*****OPTIONAL VARIABLES*****
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false or comment out this line for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mpiThreeDSAuthentication);
System.out.println(mpiThreeDSAuthentication.toXML());
mpgReq.send();
***** REQUEST *****/
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("Message = " + receipt.getMessage());
System.out.println("MessageType = " + receipt.getMpiMessageType());
System.out.println("TransStatus = " + receipt.getMpiTransStatus());
System.out.println("TransStatusReason = " + receipt.getMpiTransStatusReason());
System.out.println("ChallengeURL = " + receipt.getMpiChallengeURL());
System.out.println("ChallengeData = " + receipt.getMpiChallengeData());
System.out.println("ThreeDServerTransId = " + receipt.getMpiThreeDSserverTransId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());
System.out.println("ThreeDSacsTransID = " + receipt.getMpiThreeDSacsTransID());
System.out.println("DSTransID = " + receipt.getMpiDSTransId());
System.out.println("ThreeDSAuthTimeStamp = " + receipt.getMpiThreeDSAuthTimeStamp());
System.out.println("AuthenticationType = " + receipt.getMpiAuthenticationType());
//In Frictionless flow, you may receive TransStatus as "Y",
//in which case you can then proceed directly to Cavv Purchase/Preauth with values below
if(receipt.getMpiTransStatus().equals("Y"))
{
System.out.println("Cavv = " + receipt.getMpiCavv());
System.out.println("ECI = " + receipt.getMpiEci());
}
}

```

```

    }
    catch (Exception e)
    {
        e.printStackTrace();
    }
}
} // end TestResMpiTxn

```

## 7.7 Performing the Authorization

Once the authentication is complete and a CAVV and ECI value are retrieved, these values can be sent to Moneris using the transactions Purchase with 3-D Secure – cavvPurchase or Pre-Authorization with 3-D Secure – cavvPreauth.

### 7.7.1 Purchase with 3-D Secure – cavvPurchase

The Purchase with 3-D Secure transaction follows a 3-D Secure MPI authentication. After receiving confirmation from the MPI ACS transaction, this Purchase verifies funds on the customer's card, removes the funds and prepares them for deposit into the merchant's account.

To perform the 3-D Secure authentication, the Moneris MPI or any third-party MPI may be used.

In addition to 3-D Secure transactions, this transaction can also be used to process Apple Pay and Google Pay™ transactions. This transaction is applicable only if choosing to integrate directly to Apple Wallet or Google Wallet (if not using the Moneris Apple Pay or Google Pay™ SDKs).

Refer to Apple or Google developer portals for details on integrating directly to their wallets to retrieve the payload data.

**WARNING:** Moneris strongly discourages the use of frames as part of a 3-D Secure implementation, and cannot guarantee their reliability when processing transactions in the production environment.

```

CavvPurchase cavvPurchase = new CavvPurchase();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(cavvPurchase);

```

#### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);

Variable Name	Type and Limits	
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

**Purchase with 3-D Secure transaction request fields – Required**

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	cavvPurchase.setOrderId(order_id);
amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	cavvPurchase.setAmount(amount);
<b>EXAMPLE: 1234567.89</b>		
credit card number	<i>String</i> max 20-character alpha- numeric	cavvPurchase.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric  YYMM	cavvPurchase.setExpDate(expiry_date);
Cardholder Authentication Verification Value (CAVV)	<i>String</i> 50-character alphanumeric	cavvPurchase.setCavv(cavv);
<b>NOTE:</b> For Apple Pay and Google Pay™ Cavv Purchase and Cavv Pre-Authorization transactions, CAVV field contains the decrypted cryptogram. For more, see		

Variable Name	Type and Limits	
Appendix A Definition of Request Fields.		
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p> <p><b>NOTE:</b> For Apple Pay and Google Pay™ Cavv Purchase and Cavv Pre-Authorization transactions, the e-commerce indicator is a mandatory field containing the value received from the decrypted payload or a default value of 5. If you get a 2-character value (e.g., 05 or 07) from the payload, remove the initial 0 and just send us the 2nd character. For more, see Appendix A Definition of Request Fields.</p>	<pre>cavvPurchase.setCryptType(crypt);</pre>

### 3-D Secure 2.2 -specific fields – Required

Variable Name	Type and Limits	
3DS version	<p><i>String</i></p> <p>10-character numeric</p> <p><b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services.</p>	<pre>cavvPurchase.setThreeDSVersion("ThreeDSVersion");</pre> <p>Acceptable values:</p> <ul style="list-style-type: none"> <li>2.0.0 = 3DS protocol 2.0.0</li> <li>2.1.0 = 3DS protocol 2.1.0</li> <li>2.2.0 = 3DS protocol 2.2.0</li> <li>2.3.0 = 3DS protocol 2.3.0</li> </ul>
3DS server transaction ID	<p><i>String</i></p> <p>36-character numeric</p> <p><b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from the Cavv Lookup request or MPI 3DS</p>	<pre>cavvPurchase.setThreeDSServerTransId("ThreeDSServerTransId");</pre>

Variable Name	Type and Limits
Authentication request	

Following fields are required for Apple Pay and Google Pay only:

Variable Name	Type and Limits	
network	<i>String</i> alphabetic	<code>cavvPurchase.setNetwork(network);</code>
data type	<i>String</i> 3-character alphanumeric	<code>cavvPurchase.setDataType(data_type);</code>

### Purchase with 3-D Secure transaction request fields – Optional

Variable Name	Type and Limits	
customer ID	<i>String</i> 50-character alphanumeric	<code>cavvPurchase.setCustId(cust_id);</code>
	<b>NOTE:</b> Some special characters are not allowed: <code>&lt; &gt; \$ % = ? ^ { } [ ] \</code>	
dynamic descriptor	<i>String</i> 20-character alphanumeric total of 22 characters including your merchant name and separator	<code>cavvPurchase.setDynamicDescriptor(dynamic_descriptor);</code>
	<b>NOTE:</b> Some special characters are not allowed: <code>&lt; &gt; \$ % = ? ^ { } [ ] \</code>	
foreign indicator	<i>Boolean</i> true or false	<code>cavvPurchase.setForeignIndicator(foreign_indicator);</code>
card match ID	<i>String</i>	<code>cavvPurchase.setCmId(transaction_</code>

Variable Name	Type and Limits	
<b>NOTE:</b> Applies to Off-linx™ only; must be unique value for each transaction	50-character alphanumeric	<code>id);</code>
Customer Information	<i>Object</i> N/A	<code>cavvPurchase.setCustInfo(customer);</code>
AVS Information	<i>Object</i> N/A	<code>cavvPurchase.setAvsInfo(avsCheck);</code>
CVD Information	<i>Object</i> <b>NOTE:</b> When storing credentials on the initial transaction, the CVD object must be sent; for subsequent transactions using stored credentials, CVD can be sent with cardholder-initiated transactions only— <b>merchants must not store CVD information.</b>	<code>cavvPurchase.setCvdInfo(cvdCheck);</code>
Convenience Fee Information	<i>Object</i> N/A <b>NOTE:</b> Not applicable when processing Apple Pay or Google Pay transactions.	<code>ConvFeeInfo convFeeInfo = new ConvFeeInfo();</code>  <code>cavvPurchase.setConvenienceFee(convFeeInfo);</code>
Recurring Billing recur	<i>Object</i> N/A <b>NOTE:</b> For sample code for a Purchase with 3-D Secure including the Recurring Billing Info	<code>cavvPurchase.setRecurInfo(recurInfo);</code>

Variable Name	Type and Limits	
Object, see 7.7.5 Purchase with 3-D Secure and Recurring Billing.		
wallet indicator	<p><i>String</i></p> <p>3-character alphanumeric</p> <p><b>NOTE:</b> For Cavv Purchase and Cavv Pre-Authorization, wallet indicator applies to Apple Pay or Google Pay™ only. For more, see Appendix A Definition of Request Fields.</p>	<pre>cavvPurchase.setWalletIndicator(wallet_indicator);</pre>
Credential on File Info	<i>Object</i>	<pre>cavvPurchase.setCofInfo(cof);</pre>
cof	N/A	

### Credential on File Info object request fields

Variable Name	Type and Limits	
issuer ID	<p><i>String</i></p> <p>15-character alphanumeric</p> <p><b>NOTE:</b> This variable is required for all merchant-initiated transactions following the first one; upon sending the first transaction, the</p>	<pre>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>

Variable Name	Type and Limits	
<p>issuer ID value is received in the transaction response and then used in subsequent transaction requests.</p>		
<p>payment indicator</p> <p><b>NOTE:</b> In Credential on File transactions where the request field e-commerce indicator is also being sent, the acceptable values for e-commerce indicator are dependent on the value sent for payment indicator; see request field definitions for more information.</p>	<i>String</i> 1-character alphabetic	<pre>cof.setPaymentIndicator("PAYMENT_INDICATOR_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>

### 3-D Secure 2.2 -specific fields – Optional

Variable Name	Type and Limits	
<p>DS transaction ID</p> <p><b>NOTE:</b> Only used in financial transactions using 3rd Party 3-D Secure services.</p>	<i>String</i> 36-character alphanumeric	<pre>cavvPurchase.setDsTransId("DsTransId");</pre>

### Recurring Billing Info Object Request Fields

Variable Name	Type and Limits	Description
number of recurs	<i>String</i> numeric	The number of times that the transaction must recur

Variable Name	Type and Limits	Description
	1-999	
period	<i>String</i> numeric 1-999	Number of recur unit intervals that must pass between recurring billings
start date	<i>String</i> YYYYMMDD format	Date of the first future recurring billing transaction; this must be a date in the future  If an additional charge will be made immediately, the start now variable must be set to true
start now	<i>String</i> true/false	Set to true if a charge will be made against the card immediately; otherwise set to false  When set to false, use Card Verification prior to sending the Purchase with Recurring Billing and Credential on File objects
		<b>NOTE:</b> Amount to be billed immediately can differ from the subsequent recurring amounts
recurring amount	<i>String</i> 10-character decimal, minimum three digits Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	Dollar amount of the recurring transaction  This amount will be billed on the start date, and then billed repeatedly based on the interval defined by period and recur unit
<b>EXAMPLE:</b> 1234567.89		
recur unit	<i>String</i> day, week, month or eom	Unit to be used as a basis for the interval

Variable Name	Type and Limits	Description
		Works in conjunction with the period variable to define the billing frequency

**Sample Purchase with 3-D Secure – cavvPurchase**

```

package Canada;
import JavaAPI.*;
public class TestCanadaCavvPurchase
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String cust_id = "CUS887H67";
        String amount = "10.42";
        String pan = "4740611374762707";
        String expdate = "1901"; //YYMM
        String cavv = "BwABApFSYyd4l2eQQFJjAAAAAAA=";
        String dynamic_descriptor = "123456";
        String processing_country_code = "CA";
        String crypt_type = "5";
        boolean status_check = false;
        boolean foreign_indicator= true; //New Foreign Indicator field

        CavvPurchase cavvPurchase = new CavvPurchase();
        cavvPurchase.setOrderId(order_id);
        cavvPurchase.setCustomerId(cust_id);
        cavvPurchase.setAmount(amount);
        cavvPurchase.setPan(pan);
        cavvPurchase.setExpdate(expdate);
        cavvPurchase.setCavv(cavv);
        cavvPurchase.setCryptType(crypt_type); //Mandatory for AMEX only
        cavvPurchase.setDynamicDescriptor(dynamic_descriptor);
        //cavvPurchase.setWalletIndicator("APP"); //set only for wallet transactions. e.g APPLE PAY
        //cavvPurchase.setNetwork("Interac"); //set only for Interac e-commerce
        //cavvPurchase.setData_type("3DSecure"); //set only for Interac e-commerce
        //cavvPurchase.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique max
        //50 alphanumeric characters transaction id generated by merchant

        cavvPurchase.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using 3rd
        //Party 3-D Secure services.
        cavvPurchase.setThreeDSServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f"); //Mandatory for
        //financial transactions using 3rd Party 3-D Secure services - obtained from MpICavvLookup or
        MpThreeDSAuthentication
        //cavvPurchase.setDsTransId("12345");//Optional - to be used only if you are using 3rd party
        //3ds service
        cavvPurchase.setForeignIndicator(foreign_indicator);

        // TrId and TokenCryptogram are optional, refer documentation for more details.
        cavvPurchase.setTrId("50189815682");
        cavvPurchase.setTokenCryptogram("APmbM/411e0uAAH+s6xMAAADFA==");

        //optional - Credential on File details
        CofInfo cof = new CofInfo();
        cof.setPaymentIndicator("U");
        cof.setPaymentInformation("2");
        cof.setIssuerId("139X3130ASCXAS9");
    }
}

```

```
cavvPurchase.setCofInfo(cof);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(cavvPurchase);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());
System.out.println("Advice Code= "+ receipt.getAdviceCode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
```

### 7.7.2 Pre-Authorization with 3-D Secure – cavvPreauth

The Pre-Authorization with 3-D Secure transaction follows a 3-D Secure MPI authentication. After receiving confirmation from the MPI ACS Request transaction, this Pre-Authorization verifies funds on the customer's card, removes the funds and prepares them for deposit into the merchant's account.

To perform the 3-D Secure authentication, the Moneris MPI or any third-party MPI may be used.

In addition to 3-D Secure transactions, this transaction can also be used to process Apple Pay and Google Pay™ transactions. This transaction is applicable only if choosing to integrate directly to Apple Wallet or Google Wallet (if not using the Moneris Apple Pay or Google Pay™ SDKs).

Refer to Apple or Google developer portals for details on integrating directly to their wallets to retrieve the payload data.

**WARNING:** Moneris strongly discourages the use of frames as part of a 3-D Secure implementation, and cannot guarantee their reliability when processing transactions in the production environment.

```
CavvPreAuth cavvPreauth = new CavvPreAuth();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(cavvPreauth);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Pre-Authorization with 3-D Secure transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	cavvPreauth.setOrderId(order_id);
amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	cavvPreauth.setAmount(amount);
credit card number	<i>String</i> max 20-character alpha-	cavvPreauth.setPan(pan);

**EXAMPLE:** 1234567.89

Variable Name	Type and Limits	
	numeric	
Cardholder Authentication Verification Value (CAVV)	<p><i>String</i></p> <p>50-character alphanumeric</p>	<pre>cavvPreauth.setCavv(cavv);</pre>
	<p><b>NOTE:</b> For Apple Pay and Google Pay™ Cavv Purchase and Cavv Pre-Authorization transactions, CAVV field contains the decrypted cryptogram. For more, see Appendix A Definition of Request Fields.</p>	
expiry date	<p><i>String</i></p> <p>4-character alphanumeric</p> <p>YYMM</p>	<pre>cavvPreauth.setExpDate(expiry_date);</pre>
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	<pre>cavvPreauth.setCryptType(crypt);</pre>
	<p><b>NOTE:</b> For Apple Pay and Google Pay™ Cavv Purchase and Cavv Pre-Authorization transactions, the e-commerce indicator is a mandatory field containing the value received from the decrypted payload or a default value of 5. If you get a 2-character value (e.g., 05 or 07) from the payload, remove the initial 0 and just send us the 2nd character. For more, see Appendix A Definition of Request Fields.</p>	

### 3-D Secure 2.2 -specific fields – Required

Variable Name	Type and Limits	
3DS version	<p><i>String</i></p> <p>10-character numeric</p>	<pre>cavvPreauth.setThreeDSVersion("ThreeDSVersion");</pre> <p>Acceptable values:</p>

Variable Name	Type and Limits	
<b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services.		2.0.0 = 3DS protocol 2.0.0 2.1.0 = 3DS protocol 2.1.0 2.2.0 = 3DS protocol 2.2.0 2.3.0 = 3DS protocol 2.3.0
3DS server transaction ID	<i>String</i>  <b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from the Cavv Lookup request or MPI 3DS Authentication request	36-character numeric  cavvPreauth .setThreeDSServerTransId ( "ThreeDSServerTransId" );

### Pre-Authorization with 3-D Secure transaction request fields – Optional

Variable Name	Type and Limits	
status check	<i>Boolean</i>  true/false	mpgReq.setStatusCheck (status_check);
customer ID	<i>String</i>  50-character alphanumeric	cavvPreauth.setCustId(cust_id);
dynamic descriptor	<i>String</i>  <b>NOTE:</b> Some special characters are not allowed: < > \$ % = ? ^ { } [ ] \	cavvPreauth .setDynamicDescriptor(dynamic_descriptor);

Variable Name	Type and Limits	
Authorization Completion		
foreign indicator	<i>Boolean</i> true or false	<code>cavvPreauth.setForeignIndicator(foreign_indicator);</code>
card match ID  <b>NOTE:</b> Applies to Offlinx™ only; must be unique value for each transaction	<i>String</i> 50-character alphanumeric	<code>cavvPreauth.setCmId(transaction_id);</code>
AVS Information	<i>Object</i> N/A	<code>cavvPreauth.setAvsInfo(avsCheck);</code>
CVD Information  <b>NOTE:</b> When storing credentials on the initial transaction, the CVD object must be sent; for subsequent transactions using stored credentials, CVD can be sent with cardholder-initiated transactions only—merchants must not store CVD information.	<i>Object</i> N/A	<code>cavvPreauth.setCvdInfo(cvdCheck);</code>
wallet indicator  <b>NOTE:</b> For Cavv Purchase and Cavv Pre-Authorization, wallet indicator applies to Apple Pay or Google Pay™ only. For more, see Appendix A Definition of Request Fields.	<i>String</i> 3-character alphanumeric	<code>cavvPreauth.setWalletIndicator(wallet_indicator);</code>
final authorization  <b>NOTE:</b> Applies to Mastercard transactions only	<i>String</i> true/false	<code>cavvPreauth.setFinalAuth("true");</code>

Variable Name	Type and Limits	
Credential on File Info	<i>Object</i>	cavvPreauth.setCofInfo(cof);
cof	N/A	<p><b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.</p>

### Credential on File Info object request fields

Variable Name	Type and Limits	
issuer ID	<i>String</i> 15-character alphanumeric variable length	<pre>cof.setIssuerId("VALUE_FOR_ISSUER_ID");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
payment indicator	<i>String</i> 1-character alphabetic	<pre>cof.setPaymentIndicator("PAYMENT_INDICATOR_VALUE");</pre> <p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see Definition of Request Fields – Credential on File</p>
payment information	<i>String</i>	<pre>cof.setPaymentInformation("PAYMENT_INFO_VALUE");</pre>

Variable Name	Type and Limits	
	1-character numeric	<p><b>NOTE:</b> For a list and explanation of the possible values to send for this variable, see <a href="#">Definition of Request Fields – Credential on File</a></p>

### 3-D Secure 2.2 -specific fields – Optional

Variable Name	Type and Limits	
DS transaction ID	<p><i>String</i></p> <p><b>NOTE:</b> Only used in financial transactions using 3rd Party 3-D Secure services.</p>	cavvPreauth.setDsTransId("DsTransId");

### Sample Pre-Authorization with 3-D Secure – cavvPreauth

```

package Canada;
import JavaAPI.*;
public class TestCanadaCavvPreauth
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String cust_id = "CUS887H67";
        String amount = "10.42";
        String pan = "4242424242424242";
        String expdate = "1911"; //YYMM format
        String cavv = "AAABBJg0VhI0VniQEjRWAAAAAAA=";
        String dynamic_descriptor = "123456";
        String processing_country_code = "CA";
        String crypt_type = "5";
        String ds_trans_id = "12345";
        boolean status_check = false;
        boolean foreign_indicator= true; //New Foreign Indicator field

        CavvPreAuth cavvPreauth = new CavvPreAuth();
        cavvPreauth.setOrderId(order_id);
        cavvPreauth.setCustomerId(cust_id);
        cavvPreauth.setAmount(amount);
        cavvPreauth.setPan(pan);
        cavvPreauth.setExpdate(expdate);
        cavvPreauth.setCavv(cavv);
        cavvPreauth.setCryptType(crypt_type); //Mandatory for AMEX only
        cavvPreauth.setDynamicDescriptor(dynamic_descriptor);
        //cavvPreauth.setWalletIndicator("APP"); //set only for wallet transactions. e.g APPLE PAY
        //cavvPreauth.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique max 50 alphanumeric characters transaction id generated by merchant
        cavvPreauth.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using 3rd Party 3-D Secure services
    }
}

```



### 7.7.3 Purchase with Vault and 3-D Secure

**NOTE:** This transaction supports both temporary and permanent tokens.

**WARNING:** Moneris strongly discourages the use of frames as part of a 3-D Secure implementation, and cannot guarantee their reliability when processing transactions in the production environment.

```
ResCavvPurchaseCC resCavvPurchaseCC = new ResCavvPurchaseCC();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(resCavvPurchaseCC);
```

#### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

#### Purchase with Vault and 3-D Secure transaction request fields – Required

Variable Name	Type and Limits	
data key	<i>String</i> 25-character alphanumeric	resCavvPurchaseCC.setData(data_key);
order ID	<i>String</i> 50-character alphanumeric  a-Z A-Z 0-9 _ - : . @ spaces	resCavvPurchaseCC.setOrderId(order_id);
amount	<i>String</i> 10-character decimal	resCavvPurchaseCC.setAmount(amount);

Variable Name	Type and Limits	
	Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point  EXAMPLE: 1234567.89	
Cardholder Authentication Verification Value (CAVV)	<i>String</i>  50-character alphanumeric	resCavvPurchaseCC.setCavv(cavv);
electronic commerce indicator	<i>String</i>  1-character alphanumeric	resCavvPurchaseCC.setCryptType(crypt);

### 3-D Secure 2.2 -specific fields – Required

Variable Name	Type and Limits	
3DS version	<i>String</i>  10-character numeric  NOTE: Mandatory for financial transactions using 3rd Party 3-D Secure services.	resCavvPurchaseCC.setThreeDSVersion("ThreeDSVersion");  Acceptable values:  2.0.0 = 3DS protocol 2.0.0  2.1.0 = 3DS protocol 2.1.0  2.2.0 = 3DS protocol 2.2.0  2.3.0 = 3DS protocol 2.3.0
3DS server transaction ID	<i>String</i>  36-character numeric  NOTE: Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from the Cavv Lookup request or MPI 3DS Authentication request	resCavvPurchaseCC.setThreeDSServerTransId("ThreeDSServerTransId");

## Purchase with Vault and 3-D Secure transaction request fields – Optional

Variable Name	Type and Limits	
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt;\$%=?^{}[]\         </div>	resCavvPurchaseCC.setCustId(cust_id);
expiry date	<p><i>String</i></p> <p>4-character alphanumeric</p> <p>YYMM</p>	resCavvPurchaseCC.setExpDate(expiry_date);
final authorization	<p><i>String</i></p> <p>true/false</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> Applies to Mastercard transactions only         </div>	resCavvPurchaseCC.setFinalAuth("true");

## 3-D Secure 2.2 -specific fields – Optional

Variable Name	Type and Limits	
DS transaction ID	<p><i>String</i></p> <p>36-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> Only used in financial transactions using 3rd Party 3-D Secure services.         </div>	resCavvPurchaseCC.setDsTransId("DsTransId");

## Sample Purchase with Vault and 3-D Secure

```

package Canada;
import JavaAPI.*;
public class TestCanadaResCavvPurchaseCC
{
  public static void main(String[] args)
  {
    String store_id = "store1";
    String api_token = "yesguy1";
    String data_key = "4INQR1A8ocxD0oafSz50LADXY";
    java.util.Date createDate = new java.util.Date();
    String order_id = "Test"+createDate.getTime();
    String amount = "1.00";
    String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile will be used
    String cavv = "AAABBBJg0VhI0VniQEjRWAAAAAAA";
  }
}
  
```

```

String processing_country_code = "CA";
String exp_date = "1901";
String ds_trans_id = "12345";
boolean status_check = false;

ResCavvPurchaseCC resCavvPurchaseCC = new ResCavvPurchaseCC();
resCavvPurchaseCC.setOrderId(order_id);
resCavvPurchaseCC.setDataKey(data_key);
resCavvPurchaseCC.setCustomerId(cust_id);
resCavvPurchaseCC.setAmount(amount);
resCavvPurchaseCC.setCavv(cavv);
resCavvPurchaseCC.setExpDate(exp_date);

//NT Response Option
boolean get_nt_response = true;
resCavvPurchaseCC.setGetNtResponse(get_nt_response);

//optional - Installment Info
// InstallmentInfo installmentInfo = new InstallmentInfo();
// installmentInfo.setPlanId("ae859ef1-eb91-b708-8b80-1dd481746401");
// installmentInfo.setPlanIdRef("0000000065");
// installmentInfo.setTacVersion("2");
// resCavvPurchaseCC.setInstallmentInfo(installmentInfo);

resCavvPurchaseCC.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using
3rd Party 3-D Secure services
resCavvPurchaseCC.setThreeDSServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f");
//Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from
MpICavyLookup or MpIThreeDSAAuthentication
//resCavvPurchaseCC.setDsTransId("12345");//Optional - to be used only if you are using 3rd
party 3ds 2.0 service

//Mandatory - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

resCavvPurchaseCC.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resCavvPurchaseCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
}

```

```

System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());
//ResolveData
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());

if(get_nt_response) {
    System.out.println("\nNTResponseCode = " + receipt.getNTResponseCode());
    System.out.println("NTMessage = " + receipt.getNTMessage());
    System.out.println("NTUsed = " + receipt.getNTUsed());
    System.out.println("NTTokenBin = " + receipt.getNTTokenBin());
    System.out.println("NTTokenLast4 = " + receipt.getNTTokenLast4());
    System.out.println("NTTokenExpDate = " + receipt.getNTTokenExpDate());
}
// InstallmentResults installmentResults = receipt.getInstallmentResults();
// System.out.println("\nPlanId = " + installmentResults.getPlanId() +"\n");
// System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
// System.out.println("TacVersion = " + installmentResults.getTacVersion());
// System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
// System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
// System.out.println("PlanResponse = " + installmentResults.getPlanResponse());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

#### 7.7.4 Pre-Authorization with Vault & 3-D Secure

**NOTE:** This transaction supports both temporary and permanent tokens.

**WARNING:** Moneris strongly discourages the use of frames as part of a 3-D Secure implementation, and cannot guarantee their reliability when processing transactions in the production environment.

#### Pre-Authorization with Vault & 3-D Secure transaction object definition

```
ResCavvPreAuthCC resCavvPreauthCC = new ResCavvPreAuthCC();
```

### HttpsPostRequest object for Pre-Authorization with Vault & 3-D Secure

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(resCavvPreauthCC);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Pre-Authorization with Vault & 3-D Secure transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	resCavvPreauthCC.setData(data_key);
order ID	<i>String</i> 50-character alphanumeric  a-Z A-Z 0-9 _ - : . @ spaces	resCavvPreauthCC.setOrderId(order_id);
amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	resCavvPreauthCC.setAmount(amount);
	<b>EXAMPLE:</b> 1234567.89	
Cardholder Authentication Verification Value (CAVV)	<i>String</i> 50-character alphanumeric	resCavvPreauthCC.setCavv(cavv);
electronic commerce indicator	<i>String</i>	resCavvPreauthCC.setCryptType(crypt);

Variable Name	Type and Limits	Set Method
	1-character alphanumeric	

### Pre-Authorization with Vault & 3-D Secure transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt; &gt; \$ % = ? ^ { } [ ] \          </div>	<pre>resCavvPreauthCC.setCustId(cust_id);</pre>
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt; &gt; \$ % = ? ^ { } [ ] \          </div>	<pre>resCavvPreauthCC.setDynamicDescriptor(dynamic_descriptor);</pre>
expiry date	<p><i>String</i></p> <p>4-character alphanumeric</p> <p>YYMM</p>	<pre>resCavvPreauthCC.setExpDate(expiry_date);</pre>
DS transaction ID	<p><i>String</i></p> <p>36-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> Only used in financial transactions using 3rd Party 3-D Secure services.         </div>	<pre>resCavvPreauthCC.setDsTransId("DsTransId");</pre>
final authorization	<p><i>String</i></p> <p>true/false</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> Applies to Mastercard         </div>	<pre>resCavvPreauthCC.setFinalAuth("true");</pre>

Variable Name	Type and Limits	Set Method
transactions only		

## Sample Pre-Authorization with Vault & 3-D Secure

```

package Canada;
import JavaAPI.*;
public class TestCanadaResCavvPreauthCC
{
    public static void main(String[] args)
    {
        String store_id = "store1";
        String api_token = "yesguy1";
        String data_key = "4INQR1A8ocxD0oafSz50LADXY";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String amount = "1.00";
        String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile
        will be used
        String cavv = "AAABBJg0VhI0VniQEjRWAAAAAA";
        String processing_country_code = "CA";
        String expdate = "1901";
        boolean status_check = false;

        ResCavvPreauthCC resCavvPreauthCC = new ResCavvPreauthCC();
        resCavvPreauthCC.setOrderId(order_id);
        resCavvPreauthCC.setDataKey(data_key);
        resCavvPreauthCC.setCustomerId(cust_id);
        resCavvPreauthCC.setAmount(amount);
        resCavvPreauthCC.setCavv(cavv);
        resCavvPreauthCC.setExpDate(expdate);

        //NT Response Option
        boolean get_nt_response = true;
        resCavvPreauthCC.setGetNtResponse(get_nt_response);

        //optional - Installment Info
        // InstallmentInfo installmentInfo = new InstallmentInfo();
        // installmentInfo.setPlanId("ae859ef1-eb91-b708-8b80-1dd481746401");
        // installmentInfo.setPlanIdRef("0000000065");
        // installmentInfo.setTacVersion("2");
        // resCavvPreauthCC.setInstallmentInfo(installmentInfo);

        resCavvPreauthCC.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using 3rd
        Party 3-D Secure services.
        resCavvPreauthCC.setThreeDSServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f"); //Mandatory
        for financial transactions using 3rd Party 3-D Secure services - obtained from MpiCavvLookup
        or MpiThreeDSAuthentication
        //resCavvPreauthCC.setDsTransId("12345");//Optional - to be used only if you are using 3rd
        party 3ds 2.0 service

        //Mandatory - Credential on File details
        CofInfo cof = new CofInfo();
        cof.setPaymentIndicator("U");
        cof.setPaymentInformation("2");
        cof.setIssuerId("139X3130ASCXAS9");

        resCavvPreauthCC.setCofInfo(cof);

        HttpsPostRequest mpgReq = new HttpsPostRequest();
    }
}

```

```

mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(resCavvPreauthCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());

//ResolveData
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());

if(get_nt_response) {
System.out.println("\nNTResponseCode = " + receipt.getNTResponseCode());
System.out.println("NTMessage = " + receipt.getNTMessage());
System.out.println("NTUsed = " + receipt.getNTUsed());
System.out.println("NTTokenBin = " + receipt.getNTTokenBin());
System.out.println("NTTokenLast4 = " + receipt.getNTTokenLast4());
System.out.println("NTTokenExpDate = " + receipt.getNTTokenExpDate());
}
// InstallmentResults installmentResults = receipt.getInstallmentResults();
// System.out.println("\nPlanId = " + installmentResults.getPlanId() +"\n");
// System.out.println("PlanIDRef = " + installmentResults.getPlanIDRef());
// System.out.println("TacVersion = " + installmentResults.getTacVersion());
// System.out.println("PlanAcceptanceId = " + installmentResults.getPlanAcceptanceId());
// System.out.println("PlanStatus = " + installmentResults.getPlanStatus());
// System.out.println("PlanResponse = " + installmentResults.getPlanResponse());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 7.7.5 Purchase with 3-D Secure and Recurring Billing

**WARNING:** Moneris strongly discourages the use of frames as part of a 3-D Secure implementation, and cannot guarantee their reliability when processing transactions in the production environment.

The example below illustrates the Purchase with 3-D Secure when also sending the Recurring Billing Info object in the transaction.

### Purchase with 3-D Secure and Recurring Billing

```

package Canada;
import JavaAPI.*;
public class TestCanadaCavvPurchaseRecur
{
public static void main(String[] args)
{
String store_id = "store5";
String api_token = "yesguy";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String cust_id = "CUS887H67";
String amount = "10.42";
String pan = "4242424242424242";
String expdate = "1901"; //YYMM
String cavv = "AAABBGg0VhI0VniQEjRWAAAAAA=";
String dynamic_descriptor = "123456";
String processing_country_code = "CA";
String crypt_type = "5";
boolean status_check = false;

***** Recur Variables *****/
String recur_unit = "month"; //eom = end of month
String start_now = "true";
String start_date = "2022/02/09";
String num_recur = "12";
String period = "1";
String recur_amount = "5.00";
***** Recur Object Option1 *****/
Recur recurring_cycle = new Recur(recur_unit, start_now, start_date,
num_recur, period, recur_amount);
CavvPurchase cavvPurchase = new CavvPurchase();
cavvPurchase.setOrderId(order_id);
cavvPurchase.setCustomerId(cust_id);
cavvPurchase.setAmount(amount);
cavvPurchase.setPan(pan);
cavvPurchase.setExpdate(expdate);
cavvPurchase.setCavv(cavv);
cavvPurchase.setCryptType(crypt_type); //Mandatory for AMEX only
cavvPurchase.setDynamicDescriptor(dynamic_descriptor);
cavvPurchase.setRecur(recurring_cycle);
//cavvPurchase.setWalletIndicator("APP"); //set only for wallet transactions. e.g APPLE PAY
//cavvPurchase.setNetwork("Interac"); //set only for Interac e-commerce
//cavvPurchase.setDataType("3DSecure"); //set only for Interac e-commerce
cavvPurchase.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using 3rd
Party 3-D Secure services.
cavvPurchase.setThreeDSServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f"); Mandatory

```

```
for financial transactions using 3rd Party 3-D Secure services - obtained from MpiCavvLookup
or MpiThreeDSAuthentication
cavvPurchase.setDsTransId("12345");

//Mandatory on Recurs - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("R");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

cavvPurchase.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setStoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(cavvPurchase);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
System.out.println("IssuerId = " + receipt.getIssuerId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
```

## 7.8 Testing Your 3-D Secure 2.2 Integration

In the testing stage of development:

1. Use the testing URL as Host for your requests:  
[esqa.moneris.com](http://esqa.moneris.com)
  
2. In all Card Lookup Request transactions, make sure that you are using the testing version of your credentials for store ID and API token

3. In all MPI 3DS Authentication Request transactions, make sure that you are using the testing version of your credentials for store ID and API token
4. In all Cavv Lookup Request transactions, make sure that you are using the testing version of your credentials for store ID and API token

## 7.9 Moving to Production With 3-D Secure 2.2

Once you have finished testing your 3D Secure 2.2 integration, do the following to move the integration into production:

1. Use the production URL as Host for your requests:  
[www3.moneris.com](http://www3.moneris.com)
2. In all Card Lookup Request transactions, make sure that you are using the production version of your credentials for store ID and API token
3. In all MPI 3DS Authentication Request transactions, make sure that you are using the production version of your credentials for store ID and API token
4. In all Cavv Lookup Request transactions, make sure that you are using the production version of your credentials for store ID and API token

## 7.10 3-D Secure 2.2 TransStatus Codes

Value	Description	Comments
Y	Authenticated	Cardholder has been fully authenticated
D	Challenge Required (Decoupled)	Cardholder requires a challenge using Decoupled Authentication
A	Authentication Attempt	A proof of authentication attempt was generated
C	Challenge Required	Cardholder requires a challenge to complete authentication
U	Not Authenticated	Authentication could not be performed due to technical or other issue

Value	Description	Comments
N	Not Authenticated	Not authenticated
R	Not Authenticated	Not authenticated because the Issuer is rejecting authentication and requesting that authorisation not be attempted

## 7.11 3-D Secure 2.2 Commons TransStatusReason Decline Codes

The following codes are returned by the 3-D Secure service in order to provide additional information about the 3-D Secure transaction status.

TransStatusReason Code	Description
01	Card authentication failed
02	Unknown Device
03	Unsupported Device
04	Exceeds authentication frequency limit
05	Expired card
06	Invalid card number
07	Invalid transaction
08	No Card record
09	Security failure
10	Stolen card
11	Suspected fraud
12	Transaction not permitted to cardholder
13	Cardholder not enrolled in service
14	Transaction timed out at the ACS

TransStatusReason Code	Description
15	Low confidence
16	Medium confidence
17	High confidence
18	Very High confidence
19	Exceeds ACS maximum challenges
20	Non-Payment transaction not supported
21	3RI transaction not supported
22	ACS technical issue
23	Decoupled Authentication required by ACS but not requested by 3DS Requestor
24	3DS Requestor Decoupled Max Expiry Time exceeded
25	Decoupled Authentication was provided insufficient time to authenticate cardholder. ACS will not make attempt
26	Authentication attempted but not performed by the cardholder

**NOTE:** For a list of all TransStatus Decline Codes, please see Reference section of 3D Secure 2.2 at <https://developer.moneris.com>.

## 7.12 CAVV Result Codes

The Cardholder Authentication Verification Value (CAVV), the Accountholder Authentication Value (AAV), and the American Express Verification Value (AEVV), are the values that allow Visa, Mastercard and American Express to validate the integrity of the Visa Secure, Mastercard Identity Check and American Express SafeKey transaction data. These values are passed back from the issuer to the merchant after the authentication has taken place. The merchant then integrates the CAVV/AAV/AEVV value into the authorization request using the Purchase or Pre-Authorization with 3-D Secure transaction type.

To summarize this process:

1. Merchant conducts 3-D Secure authentication request and receives CAVV/AAV/AEVV value in response
2. Merchant sends the CAVV/AAV/AEVV value to Moneris using the Purchase or Pre-Authorization with 3-D Secure transaction type and receives the CAVV result code in the response

The following tables describe the contents of the CAVV data response and what it means to the merchant.

### 7.12.1 Visa CAVV Result Codes

#### Visa CAVV result codes

Result Code	Message	Significance to Merchants
Blank	CAVV not present or not verified	Not a Visa Secure transaction. No liability shift and merchant is not protected from chargebacks
0	CAVV authentication results invalid	Not a Visa Secure transaction. No liability shift and merchant is not protected from chargebacks
1	CAVV failed validation (authentication)	Provided that you have implemented the Visa Secureprocess correctly, the liability for this transaction should remain with the Issuer for chargeback reason codes covered by Visa Secure.
2	CAVV passed validation (authentication)	Fully authenticated transaction. There is a liability shift and the merchant is protected from chargebacks.
3, 8, A	CAVV passed validation (attempt)	Visa Secure has been attempted. There is a liability shift and the merchant is protected from certain card fraud-related chargebacks.
4, 7, 9	CAVV failed validation (attempt)	Visa Secure has been attempted. There is a liability shift and the merchant is protected from certain card fraud-related chargebacks.
6	CAVV not validated - Issuer not participating	Visa Secure has been attempted. There is a liability shift and the merchant is protected from certain card fraud-related chargebacks.

Result Code	Message	Significance to Merchants
B	CAVV passed validation; information only	Not a Visa Secure transaction. No liability shift and merchant is not protected from chargebacks
C	CAVV was not validated (attempt)	Visa Secure has been attempted. There is a liability shift and the merchant is protected from certain card fraud-related chargebacks.
D	CAVV was not validated (authentication)	Visa Secure has been attempted. There is a liability shift and the merchant is protected from certain card fraud-related chargebacks.

## 7.12.2 Mastercard CAVV Result Codes

### Mastercard CAVV result codes

Result Code	Message	Significance to Merchants
0	Authentication failed	Not a Mastercard Identity Check transaction. No liability shift and merchant is not protected from chargebacks
1	Authentication attempted	Mastercard Identity Check has been attempted. There is a liability shift and the merchant is protected from certain card fraud-related chargebacks (international commercial cards excluded).
2	Authentication successful	Fully authenticated transaction. There is a liability shift and the merchant is protected from chargebacks.

## 7.12.3 American Express CAVV Result Codes

### American Express CAVV result codes

**NOTE:** American Express SafeKey is only available to American Express direct acquired merchants (i.e., not OptBlue merchants). Any questions pertaining to chargebacks, liability and

disputes should be addressed to your American Express representative given that American Express is the acquirer of record for these merchants.

Result Code	Description
1	AEVV Failed - Authentication, Issuer Key
2	AEVV Passed - Authentication, Issuer Key
3	AEVV Passed - Attempt, Issuer Key
4	AEVV Failed - Attempt, Issuer Key
7	AEVV Failed - Attempt, Issuer not participating, Network Key
8	AEVV Passed - Attempt, Issuer not participating, Network Key
9	AEVV Failed - Attempt, Participating, Access Control Server (ACS) not available, Network Key
A	AEVV Passed - Attempt, Participating, Access Control Server (ACS) not available, Network Key
U	AEVV Unchecked

## 8 Multi-Currency Pricing (MCP)

- 8.1 About Multi-Currency Pricing (MCP)
- 8.2 Methods of Processing MCP Transactions
- 8.3 MCP Get Rate
- 8.4 MCP Purchase
- 8.5 MCP Purchase with 3-D Secure
- 8.6 MCP Purchase with 3-D Secure and Vault
- 8.7 MCP Pre-Authorization
- 8.8 MCP Pre-Authorization with 3-D Secure
- 8.9 MCP Pre-Authorization with 3-D Secure and Vault
- 8.10 MCP Pre-Authorization Completion
- 8.11 MCP Purchase Correction
- 8.12 MCP Refund
- 8.13 MCP Independent Refund
- 8.14 MCP Purchase with Vault
- 8.15 MCP Pre-Authorization with Vault
- 8.16 MCP Independent Refund with Vault
- 8.17 MCP Currency Codes
- 8.18 MCP Error Codes

### 8.1 About Multi-Currency Pricing (MCP)

Multi-currency pricing (MCP) is a financial service which allows businesses to price goods and services in a variety of foreign currencies, while continuing to receive settlement and reporting in Canadian dollars. MCP allows cardholders to shop, view prices and pay in the currency of their choice.

MCP is only available when processing Visa and Mastercard transactions.

**NOTE:** Use MCP only when processing transactions that involve foreign currency exchange; for transactions strictly in Canadian dollars, use the basic financial transaction requests

## 8.2 Methods of Processing MCP Transactions

There are two methods of processing multi-currency pricing transactions via the Moneris Gateway:

1. **Using the MCP Get Rate transaction** – this method is used to obtain a foreign exchange rate and locks that specific rate in for a limited time, and is applied in a subsequent transaction
2. **Without using MCP Get Rate** – this method sends a MCP transaction without performing the Get Rate request, and the foreign exchange rate is obtained at processing time

## 8.3 MCP Get Rate

Performs a foreign currency exchange rate look-up, and secures that exchange rate for use in a subsequent MCP financial transaction.

The exchange rate retrieved by this transaction request is represented in the response as the **RateToken**, and the underlying exchange rate is locked in for a limited time period.

### MCP Get Rate transaction object definition

```
MCPGetRate getRate = new MCPGetRate();
```

### HttpsPostRequest object for MCP Get Rate transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();  
mpgReq.setTransaction(getRate);
```

### MCP Get Rate transaction request fields – Required

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i> numeric current version is 1.0	getRate.setMCPVersion ("MCP_VERSION_NUM");
rate transaction type	<i>String</i> 1-character alphabetic	getRate.setRateTxnType ("TRANSACTION_TYPE_VALUE");
MCP Rate Info	<i>Object</i> N/A	getRate.setMCPRateInfo (rate);

### MCP Rate Info object request fields

At least one of the following variables must be sent:

Variable Name	Type and Limits	Set Method
add cardholder amount	<p><i>String array</i></p> <p>12-character numeric, 3-character numeric (smallest discrete unit of foreign currency, currency code)</p>	rate.addCardholderAmount("FOREIGN_AMT", "FOREIGN_CURRENCY_CODE");
add merchant settlement amount	<p><i>String array</i></p> <p>12-character numeric, 3-character numeric (amount in CAD pennies, currency code)</p>	rate.addMerchantSettlementAmount("CAD_AMOUNT", "FOREIGN_CURRENCY_CODE");

## Sample MCP Get Rate

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPGetRate
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        String processing_country_code = "CA";

        MCPGetRate getRate = new MCPGetRate();
        getRate.setMCPVersion("1.0"); //MCP Version number. Should always be 1.0
        getRate.setRateTxnType("P"); //P or R are valid values (Purchase or Refund)

        MCPRate rate = new MCPRate();
        rate.addCardholderAmount("500", "840"); //penny value amount 1.25 = 125. Foreign amount and SO-4217 country currency number
        //rate.addMerchantSettlementAmount("200", "826"); //penny value amount 1.25 = 125. Domestic (CAD) amount and SO-4217 country currency number
        //rate.addMerchantSettlementAmount("300", "036"); //penny value amount 1.25 = 125. Domestic (CAD) amount and SO-4217 country currency number

        getRate.setMCPRateInfo(rate);

        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(getRate);
        mpgReq.send();

        try
        {
    
```

```
Receipt receipt = mpgReq.getReceipt();

System.out.println("RateTxnType = " + receipt.getRateTxnType());
System.out.println("MCPRateToken = " + receipt.getMCPRateToken());

System.out.println("RateInqStartTime = " + receipt.getRateInqStartTime()); //The time (unix UTC) of when the rate is requested
System.out.println("RateInqEndTime = " + receipt.getRateInqEndTime()); //The time (unix UTC) of when the rate is returned
System.out.println("RateValidityStartTime = " + receipt.getRateValidityStartTime()); //The time (unix UTC) of when the rate is valid from
System.out.println("RateValidityEndTime = " + receipt.getRateValidityEndTime()); //The time (unix UTC) of when the rate is valid until
System.out.println("RateValidityPeriod = " + receipt.getRateValidityPeriod()); //The time in minutes this rate is valid for

System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TimedOut = " + receipt.getTimedOut());

//RateData
for (int index = 0; index < receipt.getRatesCount(); index++)
{
    System.out.println("MCPRate = " + receipt.getMCPRate(index));
    System.out.println("MerchantSettlementCurrency = " + receipt.getMerchantSettlementCurrency(index));
    System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount(index)); //Domestic(CAD) amount
    System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode(index));
    System.out.println("CardholderAmount = " + receipt.getCardholderAmount(index)); //Foreign amount

    System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode(index));
    System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage(index));
}

}
catch (Exception e)
{
    e.printStackTrace();
}
}
```

## 8.4 MCP Purchase

Verifies funds on the customer's card, removes the funds and prepares them for deposit into the merchant's account.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

### MCP Purchase transaction object definition

```
MCPPurchase mcpPurchase = new MCPPurchase();
```

### HttpsPostRequest object for MCP Purchase transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpPurchase);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	Set Method
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Purchase transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	mcpPurchase.setOrderId(order_id);
credit card number	<i>String</i> max 20-character alphanumeric	mcpPurchase.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric YYMM	mcpPurchase.setExpDate(expiry_date);
electronic commerce indicator	<i>String</i> 1-character alphanumeric	mcpPurchase.setCryptType(crypt);

### MCP-specific request fields – Required

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i> numeric	mcpPurchase.setMCVersion("MCP_VERSION_NUM");

Variable Name	Type and Limits	Set Method
	current version is 1.0	
cardholder amount	<p><i>String</i></p> <p>12-character numeric</p> <p>smallest discrete unit of foreign currency</p>	<pre>mcpPurchase .setCardholderAmount ("CARDHOLDER_AMOUNT");</pre>
cardholder currency code	<p><i>String</i></p> <p>3-character numeric</p>	<pre>mcpPurchase .setCardholderCurrencyCode ("CARDHOLDER_CURRENCY_CODE");</pre>

### MCP Purchase transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt; \$ % = ? ^ { } [ ] \          </div>	<pre>mcpPurchase.setCustId(cust_id);</pre>
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt; \$ % = ? ^ { } [ ] \          </div>	<pre>mcpPurchase .setDynamicDescriptor(dynamic_ descriptor);</pre>
wallet indicator	<p><i>String</i></p> <p>3-character alphanumeric</p>	<pre>mcpPurchase.setWalletIndicator (wallet_indicator);</pre>
Credential on File Info	<i>Object</i>	<pre>mcpPurchase.setCofInfo(cof);</pre>
cof	N/A	

Variable Name	Type and Limits	Set Method
<b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.		
AVS Information	<i>Object</i> N/A	mcpPurchase.setAvsInfo(avsCheck);
CVD Information	<i>Object</i> N/A	mcpPurchase.setCvdInfo(cvdCheck);

### MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i> N/A	mcpPurchase.setMCPRateToken("MCP_RATE_TOKEN");

### Sample MCP Purchase

```
package Canada;
import JavaAPI.*;
public class TestCanadaMCPPurchase
{
    public static void main(String[] args)
    {
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String store_id = "store5";
        String api_token = "yesguy";
        String amount = "5.00";
        String pan = "4242424242424242";
        String expdate = "1901"; //YYMM format
        String crypt = "7";
        String processing_country_code = "CA";
        boolean status_check = false;
        MCPPurchase mcpPurchase = new MCPPurchase();
        mcpPurchase.setOrderId(order_id);
        mcpPurchase.setAmount(amount);
        mcpPurchase.setPan(pan);
        mcpPurchase.setExpdate(expdate);
        mcpPurchase.setCryptType(crypt);
        mcpPurchase.setDynamicDescriptor("123456");
        //mcpPurchase.setWalletIndicator(""); //Refer documentation for possible values
    }
}
```

```

//optional - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

//mcpPurchase.setCofInfo(cof);

//MCP Fields
mcpPurchase.setMCPVersion("1.0");
mcpPurchase.setCardholderAmount("500");
mcpPurchase.setCardholderCurrencyCode("840");
mcpPurchase.setMCPRateToken("P1538681661706745");

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpPurchase);
mpgReq.setStatusCheck(status_check);

//Optional - Proxy
mpgReq.setProxy(false); //true to use proxy
mpgReq.setProxyHost("proxyURL");
mpgReq.setProxyPort("proxyPort");
mpgReq.setProxyUser("proxyUser"); //optional - domainName\User
mpgReq.setProxyPassword("proxyPassword"); //optional
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("HostId = " + receipt.getHostId());
System.out.println("IssuerId = " + receipt.getIssuerId());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 8.5 MCP Purchase with 3-D Secure

### MCP Purchase with 3-D Secure transaction object definition

```
MCP CavvPurchase mcpCavvPurchase = new MCP CavvPurchase();
```

### HttpsPostRequest object for MCP Purchase with 3-D Secure transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpCavvPurchase);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Purchase with 3-D Secure transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	mcpCavvPurchase.setOrderId(order_id);
credit card number	<i>String</i> max 20-character alpha- numeric	mcpCavvPurchase.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric YYMM	mcpCavvPurchase.setExpDate(expiry_date);
Cardholder Authentication Verification Value (CAVV)	<i>String</i> 50-character alphanumeric	mcpCavvPurchase.setCavv(cavv);
electronic commerce indic-	<i>String</i>	mcpCavvPurchase.setCryptType

Variable Name	Type and Limits	Set Method
ator	1-character alphanumeric	(crypt) ;

**MCP-specific request fields – Required**

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i> numeric current version is 1.0	mcpCavvPurchase.setMCPVersion ("MCP_VERSION_NUM");
cardholder amount	<i>String</i> 12-character numeric smallest discrete unit of foreign currency	mcpCavvPurchase.setCardholderAmount ("CARDHOLDER_AMOUNT");
cardholder currency code	<i>String</i> 3-character numeric	mcpCavvPurchase.setCardholderCurrencyCode ("CARDHOLDER_CURRENCY_CODE");

**3-D Secure 2.2 -specific fields – Required**

Variable Name	Type and Limits	Set Method
3DS version	<i>String</i> 10-character numeric	mcpCavvPurchase.setThreeDSVersion ("ThreeDSVersion"); Acceptable values: 2.0.0 = 3DS protocol 2.0.0 2.1.0 = 3DS protocol 2.1.0 2.2.0 = 3DS protocol 2.2.0 2.3.0 = 3DS protocol 2.3.0
3DS server transaction ID	<i>String</i> 36-character numeric	mcpCavvPurchase.setThreeDSServerTransId ("ThreeDSServerTransId"); <b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services -

Variable Name	Type and Limits	Set Method
obtained from the Cavv Lookup request or MPI 3DS Authentication request		

### MCP Purchase with 3-D Secure transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<i>String</i> 50-character alphanumeric	<code>mcpCavvPurchase.setCustId(cust_id);</code>
	<b>NOTE:</b> Some special characters are not allowed: <code>&lt;&gt;\$%=?^{}[]\</code>	
dynamic descriptor	<i>String</i> 20-character alphanumeric total of 22 characters including your merchant name and separator	<code>mcpCavvPurchase.setDynamicDescriptor(dynamic_descriptor);</code>
	<b>NOTE:</b> Some special characters are not allowed: <code>&lt;&gt;\$%=?^{}[]\</code>	
wallet indicator	<i>String</i> 3-character alphanumeric	<code>mcpCavvPurchase.setWalletIndicator(wallet_indicator);</code>
Credential on File Info	<i>Object</i>	<code>mcpCavvPurchase.setCofInfo(cof);</code>
cof	N/A	
	<b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Create Transaction Request.	

Variable Name	Type and Limits	Set Method
<b>Note:</b> This section applies to the AVS and CVD fields.		
AVS Information	<i>Object</i> N/A	<code>mcpCavvPurchase.setAvsInfo(avsCheck);</code>
CVD Information	<i>Object</i> N/A	<code>mcpCavvPurchase.setCvdInfo(cvdCheck);</code>

### MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i> N/A	<code>mcpCavvPurchase.setMCPRateToken("MCP_RATE_TOKEN");</code>

### 3-D Secure 2.2 -specific fields – Optional

Variable Name	Type and Limits	Set Method
DS transaction ID	<i>String</i> 36-character alphanumeric  <b>NOTE:</b> Only used in financial transactions using 3rd Party 3-D Secure services.	<code>mcpCavvPurchase.setDsTransId("DsTransId");</code>

### Sample MCP Purchase with 3-D Secure

```
package Canada;
import JavaAPI.*;
public class TestCanadaMCPCavvPurchase
{
    public static void main(String[] args)
    {
        String store_id = "store1";
        String api_token = "yesguy1";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String cust_id = "CUS887H67";
        String amount = "10.42";
        String pan = "4740611374762707";
        String expdate = "2201"; //YYMM
        String cavv = "BwABApFSYyd412eQQFJjAAAAAA=";
        String dynamic_descriptor = "123456";
        String processing_country_code = "CA";
        String crypt_type = "5";
    }
}
```

```

boolean status_check = false;
MCP_CavvPurchase mcpCavvPurchase = new MCP_CavvPurchase();
mcpCavvPurchase.setOrderId(order_id);
mcpCavvPurchase.setCustId(cust_id);
mcpCavvPurchase.setAmount(amount);
mcpCavvPurchase.setPan(pan);
mcpCavvPurchase.setExpdate(expdate);
mcpCavvPurchase.setCavv(cavv);
mcpCavvPurchase.setCryptType(crypt_type); //Mandatory for AMEX only
mcpCavvPurchase.setDynamicDescriptor(dynamic_descriptor);
//mcpCavvPurchase.setWalletIndicator("APP"); //set only for wallet transactions. e.g APPLE
PAY
//mcpCavvPurchase.setNetwork("Interac"); //set only for Interac e-commerce
//mcpCavvPurchase.setDataType("3DSecure"); //set only for Interac e-commerce
//mcpCavvPurchase.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique
max 50 alphanumeric characters transaction id generated by merchant

mcpCavvPurchase.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using 3rd
Party 3-D Secure services.
mcpCavvPurchase.setThreeDSServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f"); //Mandatory
for financial transactions using 3rd Party 3-D Secure services - obtained from MpiCavvLookup
or MpiThreeDSAuthentication
//mcpCavvPurchase.setDsTransId("12345"); //Optional - to be used only if you are using 3rd
party 3ds 2.0 service

//MCP Fields
mcpCavvPurchase.setMCPVersion("1.0");
mcpCavvPurchase.setCardholderAmount("500");
mcpCavvPurchase.setCardholderCurrencyCode("840");
mcpCavvPurchase.setMCPRateToken("P1623162875163626");

//optional - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

mcpCavvPurchase.setCofInfo(cof);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpCavvPurchase);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
}

```

```

System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

## 8.6 MCP Purchase with 3-D Secure and Vault

### MCP Purchase with 3-D Secure and Vault transaction object definition

```
MCPResCavvPurchaseCC mcpResCavvPurchaseCC = new MCPResCavvPurchaseCC();
```

### HttpsPostRequest object for MCP Purchase with 3-D Secure and Vault transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(mcpResCavvPurchaseCC);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Purchase with 3-D Secure and Vault transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	mcpResCavvPurchaseCC.setData(data_key);
order ID	<i>String</i> 50-character alphanumeric	mcpResCavvPurchaseCC.setOrderId(order_id);

Variable Name	Type and Limits	Set Method
a-Z A-Z 0-9 _ - : . @ spaces		
credit card number	<i>String</i> max 20-character alpha-numeric	<code>mcpResCavvPurchaseCC.setPan(pan);</code>
expiry date	<i>String</i> 4-character alphanumeric YYMM	<code>mcpResCavvPurchaseCC.setExpDate(expiry_date);</code>
Cardholder Authentication Verification Value (CAVV)	<i>String</i> 50-character alphanumeric	<code>mcpResCavvPurchaseCC.setCavv(cavv);</code>
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>mcpResCavvPurchaseCC.setCryptType(crypt);</code>

#### MCP-specific request fields – Required

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i> numeric current version is 1.0	<code>mcpResCavvPurchaseCC.setMCVersion("MCP_VERSION_NUM");</code>
cardholder amount	<i>String</i> 12-character numeric smallest discrete unit of foreign currency	<code>mcpResCavvPurchaseCC.setCardholderAmount("CARDHOLDER_AMOUNT");</code>
cardholder currency code	<i>String</i> 3-character numeric	<code>mcpResCavvPurchaseCC.setCardholderCurrencyCode("CARDHOLDER_CURRENCY_CODE");</code>

### 3-D Secure 2.2 -specific fields – Required

Variable Name	Type and Limits	Set Method
3DS version	<p><i>String</i></p> <p><b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services.</p>	<pre>mcpResCavvPurchaseCC .setThreeDSVersion ("ThreeDSVersion");</pre> <p>Acceptable values:</p> <ul style="list-style-type: none"> <li>2.0.0 = 3DS protocol 2.0.0</li> <li>2.1.0 = 3DS protocol 2.1.0</li> <li>2.2.0 = 3DS protocol 2.2.0</li> <li>2.3.0 = 3DS protocol 2.3.0</li> </ul>
3DS server transaction ID	<p><i>String</i></p> <p><b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from the Cavv Lookup request or MPI 3DS Authentication request</p>	<pre>mcpResCavvPurchaseCC .setThreeDSServerTransId ("ThreeDSServerTransId");</pre>

### MCP Purchase with 3-D Secure and Vault transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <p><b>NOTE:</b> Some special characters are not allowed: &lt;&gt; \$ % = ? ^ { } [ ] \</p>	<pre>mcpResCavvPurchaseCC.setCustId (cust_id);</pre>
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p>	<pre>mcpResCavvPurchaseCC .setDynamicDescriptor(dynamic_ descriptor);</pre>

Variable Name	Type and Limits	Set Method
<b>NOTE:</b> Some special characters are not allowed: < > \$ % = ? ^ { } [ ] \		
wallet indicator	<i>String</i> 3-character alphanumeric	<code>mcpResCavvPurchaseCC.setWalletIndicator(wallet_indicator);</code>
Credential on File Info	<i>Object</i>	<code>mcpResCavvPurchaseCC.setCofInfo(cof);</code>
cof	N/A	
<b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.		
AVS Information	<i>Object</i> N/A	<code>mcpResCavvPurchaseCC.setAvsInfo(avsCheck);</code>
CVD Information	<i>Object</i> N/A	<code>mcpResCavvPurchaseCC.setCvdInfo(cvdCheck);</code>
<b>3-D Secure 2.2 -specific fields – Optional</b>		
Variable Name	Type and Limits	Set Method
DS transaction ID	<i>String</i> 36-character alphanumeric	<code>mcpResCavvPurchaseCC.setDsTransId("DsTransId");</code>
<b>NOTE:</b> Only used in financial transactions using 3rd Party 3-D Secure services.		

### Sample MCP Purchase with 3-D Secure and Vault

```
package Canada;
import JavaAPI.*;
public class TestCanadaMCPResCavvPurchaseCC
```

```

{
public static void main(String[] args)
{
String store_id = "monca02932";
String api_token = "CG8kYzGgzVU5z23irgMx";
String data_key = "xRl9O4FgrZUYdGkmqHTqiEw97";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String amount = "1.00";
String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile
will be used
String cavv = "AAABBJg0VhI0VniQEjRWAAAAAAA";
String processing_country_code = "CA";
String exp_date = "1901";
String crypt_type = "7";
boolean status_check = false;
MCPResCavvPurchaseCC mcpResCavvPurchaseCC = new MCPResCavvPurchaseCC();
mcpResCavvPurchaseCC.setOrderId(order_id);
mcpResCavvPurchaseCC.setDataKey(data_key);
mcpResCavvPurchaseCC.setCustomerId(cust_id);
mcpResCavvPurchaseCC.setAmount(amount);
mcpResCavvPurchaseCC.setCavv(cavv);
mcpResCavvPurchaseCC.setCryptType(crypt_type);
mcpResCavvPurchaseCC.setExpDate(exp_date);
mcpResCavvPurchaseCC.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using
3rd Party 3-D Secure services.
mcpResCavvPurchaseCC.setThreeDServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f");
//Mandatory for financial transactions using 3rd Party 3-D Secure services" - obtained from
MpiCavvLookup or MpiThreeDSAAuthentication
//MCP Fields
mcpResCavvPurchaseCC.setMCPVersion("1.0");
mcpResCavvPurchaseCC.setCardholderAmount("500");
mcpResCavvPurchaseCC.setCardholderCurrencyCode("840");
mcpResCavvPurchaseCC.setMCPRateToken("P1623439175449463");

//Mandatory - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

mcpResCavvPurchaseCC.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpResCavvPurchaseCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
}
}

```

```

System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
//ResolveData
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 8.7 MCP Pre-Authorization

Verifies and locks funds on the customer's credit card. The funds are locked for a specified amount of time based on the card issuer. For situations where the merchant does not know the precise amount when the transaction begins, a Pre-Authorization transaction may use an estimated amount instead. If the cardholder incurs additional charges during the transaction period, the merchant is able to increase the total amount authorized via Incremental Pre-Authorization; these increments are added to the previously authorized amount. To retrieve the funds that have been locked by a Pre-Authorization transaction so that they may be settled in the merchant's account, a Pre-Authorization Completion transaction must be performed. A Pre-Authorization transaction may only be "completed" once. If the Pre-Authorization is not completed within the allowable chargeback protection period then a new authorization should be obtained. For Mastercard, the merchant can instead submit an Incremental Pre-Authorization with a \$0 amount field associated to the original Pre-Authorization transaction; if approved, this extends the protection period.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

### MCP Pre-Authorization transaction object definition

```
MCPPreAuth mcpPreauth = new MCPPreAuth();
```

### **HttpsPostRequest object for MCP Pre-Authorization transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpPreauth);
```

### **Core connection object fields (all API transactions)**

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### **MCP Pre-Authorization transaction request fields – Required**

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	mcpPreauth.setOrderId(order_id);
credit card number	<i>String</i> max 20-character alphanumeric	mcpPreauth.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric YYMM	mcpPreauth.setExpDate(expiry_date);
electronic commerce indicator	<i>String</i> 1-character alphanumeric	mcpPreauth.setCryptType(crypt);

### **MCP-specific request fields – Required**

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i> numeric	mcpPreauth.setMCPVersion("MCP_VERSION_NUM");

Variable Name	Type and Limits	Set Method
	current version is 1.0	
cardholder amount	<p><i>String</i></p> <p>12-character numeric</p> <p>smallest discrete unit of foreign currency</p>	<code>mcpPreauth.setCardholderAmount("CARDHOLDER_AMOUNT");</code>
cardholder currency code	<p><i>String</i></p> <p>3-character numeric</p>	<code>mcpPreauth.setCardholderCurrencyCode("CARDHOLDER_CURRENCY_CODE");</code>

### MCP Pre-Authorization transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <p><b>NOTE:</b> Some special characters are not allowed: &lt;&gt; \$ % = ? ^ { } [ ] \</p>	<code>mcpPreauth.setCustId(cust_id);</code>
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <p><b>NOTE:</b> Some special characters are not allowed: &lt;&gt; \$ % = ? ^ { } [ ] \</p>	<code>mcpPreauth.setDynamicDescriptor(dynamic_descriptor);</code>
wallet indicator	<p><i>String</i></p> <p>3-character alphanumeric</p>	<code>mcpPreauth.setWalletIndicator(wallet_indicator);</code>
final authorization	<i>String</i>	<code>mcpPreauth.setFinalAuth("true");</code>

Variable Name	Type and Limits	Set Method
<b>NOTE:</b> Applies to Mastercard transactions only	true/false	
Credential on File Info  cof	<i>Object</i>  N/A	<code>mcpPreauth.setCofInfo(cof);</code>
	<b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.	
AVS Information	<i>Object</i>  N/A	<code>mcpPreauth.setAvsInfo(avscCheck);</code>
CVD Information	<i>Object</i>  N/A	<code>mcpPreauth.setCvdInfo(cvdCheck);</code>

### MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i>  N/A	<code>mcpPreauth.setMCPRateToken("MCP_RATE_TOKEN");</code>

### Sample MCP Pre-Authorization

```
package Canada;
import JavaAPI.*;
public class TestCanadaCPPreauth
{
public static void main(String[] args)
{
String store_id = "store5";
String api_token = "yesguy";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String amount = "5.00";
String pan = "4242424242424242";
String expdate = "1902";
String crypt = "7";
```

```

String processing_country_code = "CA";
boolean status_check = false;
MCPPreAuth mcpPreauth = new MCPPreAuth();
mcpPreauth.setOrderId(order_id);
mcpPreauth.setAmount(amount);
mcpPreauth.setPan(pan);
mcpPreauth.setExpdate(expdate);
mcpPreauth.setCryptType(crypt);
//mcpPreauth.setWalletIndicator(""); //Refer documentation for possible values
//mcpPreauth.setFinalAuth("true");
//optional - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

//mcpPreauth.setCofInfo(cof);

//MCP Fields
mcpPreauth.setMCPVersion("1.0");
mcpPreauth.setCardholderAmount("500");
mcpPreauth.setCardholderCurrencyCode("840");
mcpPreauth.setMCPRateToken("P1538681661706745");

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpPreauth);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
//System.out.println("StatusCode = " + receipt.getStatusCode());
//System.out.println("StatusMessage = " + receipt.getStatusMessage());
System.out.println("IssuerId = " + receipt.getIssuerId());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
}
catch (Exception e)
{

```

```

        e.printStackTrace();
    }
}
}
}

```

## 8.8 MCP Pre-Authorization with 3-D Secure

### MCP Pre-Authorization with 3-D Secure transaction object definition

```
MCP CavvPreAuth mcpCavvPreauth = new MCP CavvPreAuth();
```

### HttpsPostRequest object for MCP Pre-Authorization with 3-D Secure transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(mcpCavvPreauth);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Pre-Authorization with 3-D Secure transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	mcpCavvPreauth.setOrderId(order_id);
credit card number	<i>String</i> max 20-character alpha-numeric	mcpCavvPreauth.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric YYMM	mcpCavvPreauth.setExpDate(expiry_date);

Variable Name	Type and Limits	Set Method
Cardholder Authentication Verification Value (CAVV)	<i>String</i> 50-character alphanumeric	<code>mcpCavvPreauth.setCavv(cavv);</code>
electronic commerce indicator	<i>String</i> 1-character alphanumeric	<code>mcpCavvPreauth.setCryptType(crypt);</code>

**MCP-specific request fields – Required**

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i> numeric current version is 1.0	<code>mcpCavvPreauth.setMCPVersion("MCP_VERSION_NUM");</code>
cardholder amount	<i>String</i> 12-character numeric smallest discrete unit of foreign currency	<code>mcpCavvPreauth.setCardholderAmount("CARDHOLDER_AMOUNT");</code>
cardholder currency code	<i>String</i> 3-character numeric	<code>mcpCavvPreauth.setCardholderCurrencyCode("CARDHOLDER_CURRENCY_CODE");</code>

**3-D Secure 2.2 -specific fields – Required**

Variable Name	Type and Limits	Set Method
3DS version	<i>String</i> 10-character numeric	<code>mcpCavvPreauth.setThreeDSVersion("ThreeDSVersion");</code>  Acceptable values:  2.0.0 = 3DS protocol 2.0.0 2.1.0 = 3DS protocol 2.1.0 2.2.0 = 3DS protocol 2.2.0 2.3.0 = 3DS protocol 2.3.0

Variable Name	Type and Limits	Set Method
3DS server transaction ID  <b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from the Cavv Lookup request or MPI 3DS Authentication request	<i>String</i> 36-character numeric	<code>mcpCavvPreauth.setThreeDSServerTransId("ThreeDSServerTransId");</code>

**MCP Pre-Authorization with 3-D Secure transaction request fields – Optional**

Variable Name	Type and Limits	Set Method
customer ID  <b>NOTE:</b> Some special characters are not allowed: <> \$ % = ? ^ { } [ ] \	<i>String</i> 50-character alphanumeric	<code>mcpCavvPreauth.setCustId(cust_id);</code>
dynamic descriptor  <b>NOTE:</b> Some special characters are not allowed: <> \$ % = ? ^ { } [ ] \	<i>String</i> 20-character alphanumeric  total of 22 characters including your merchant name and separator	<code>mcpCavvPreauth.setDynamicDescriptor(dynamic_descriptor);</code>
wallet indicator  <b>NOTE:</b> Some special characters are not allowed: <> \$ % = ? ^ { } [ ] \	<i>String</i> 3-character alphanumeric	<code>mcpCavvPreauth.setWalletIndicator(wallet_indicator);</code>
Credential on File Info  <b>NOTE:</b> This is a nested object within the transaction, and cof N/A	<i>Object</i> N/A	<code>mcpCavvPreauth.setCofInfo(cof);</code>

Variable Name	Type and Limits	Set Method
<p>required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.</p>		
AVS Information	<i>Object</i> N/A	<code>mcpCavvPreauth.setAvsInfo(avsCheck);</code>
CVD Information	<i>Object</i> N/A	<code>mcpCavvPreauth.setCvdInfo(cvdCheck);</code>

### MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i> N/A	<code>mcpCavvPreauth.setMCPRateToken("MCP_RATE_TOKEN");</code>

### 3-D Secure 2.2 -specific fields – Optional

Variable Name	Type and Limits	Set Method
DS transaction ID	<i>String</i> 36-character alphanumeric  <b>NOTE:</b> Only used in financial transactions using 3rd Party 3-D Secure services.	<code>mcpCavvPreauth.setDsTransId("DsTransId");</code>

### Sample MCP Pre-Authorization with 3-D Secure

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPCavvPurchase
{
  public static void main(String[] args)
  {
    String store_id = "store1";
    String api_token = "yesguy1";
    java.util.Date createDate = new java.util.Date();
    String order_id = "Test"+createDate.getTime();
    String cust_id = "CUS887H67";
    String amount = "10.42";
  }
}

```

```

String pan = "4740611374762707";
String expdate = "2201"; //YYMM
String cavv = "BwABApFSYyd4l2eQQFJjAAAAAA=";
String dynamic_descriptor = "123456";
String processing_country_code = "CA";
String crypt_type = "5";
boolean status_check = false;
MCP CavvPurchase mcpCavvPurchase = new MCP CavvPurchase();
mcpCavvPurchase.setOrderId(order_id);
mcpCavvPurchase.setCustId(cust_id);
mcpCavvPurchase.setAmount(amount);
mcpCavvPurchase.setPan(pan);
mcpCavvPurchase.setExpdate(expdate);
mcpCavvPurchase.setCavv(cavv);
mcpCavvPurchase.setCryptType(crypt_type); //Mandatory for AMEX only
mcpCavvPurchase.setDynamicDescriptor(dynamic_descriptor);
//mcpCavvPurchase.setWalletIndicator("APP"); //set only for wallet transactions. e.g APPLE PAY
//mcpCavvPurchase.setNetwork("Interac"); //set only for Interac e-commerce
//mcpCavvPurchase.setDataType("3DSecure"); //set only for Interac e-commerce
//mcpCavvPurchase.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique max 50 alphanumeric characters transaction id generated by merchant

mcpCavvPurchase.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using 3rd Party 3-D Secure services
mcpCavvPurchase.setThreeDSServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f"); Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from MpiCavvLookup or MpiThreeDSAAuthentication
//mcpCavvPurchase.setDsTransId("12345"); //Optional - to be used only if you are using 3rd party 3ds 2.0 service

//MCP Fields
mcpCavvPurchase.setMCPVersion("1.0");
mcpCavvPurchase.setCardholderAmount("500");
mcpCavvPurchase.setCardholderCurrencyCode("840");
mcpCavvPurchase.setMCPRateToken("P1623162875163626");

//optional - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

mcpCavvPurchase.setCofInfo(cof);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpCavvPurchase);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
}

```

```

System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 8.9 MCP Pre-Authorization with 3-D Secure and Vault

### MCP Pre-Authorization with 3-D Secure and Vault transaction object definition

```
MCPResCavvPreauthCC mcpResCavvPreauthCC = new MCPResCavvPreauthCC();
```

### HttpsPostRequest object for MCP Pre-Authorization with 3-D Secure and Vault transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpResCavvPreauthCC);
```

#### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

#### MCP Pre-Authorization with 3-D Secure and Vault transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	mcpResCavvPreauthCC.setData(data_key);

Variable Name	Type and Limits	Set Method
order ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <p>a-Z A-Z 0-9 _ - : . @ spaces</p>	<code>mcpResCavvPreauthCC.setOrderId(order_id);</code>
credit card number	<p><i>String</i></p> <p>max 20-character alpha-numeric</p>	<code>mcpResCavvPreauthCC.setPan(pan);</code>
expiry date	<p><i>String</i></p> <p>4-character alphanumeric</p> <p>YYMM</p>	<code>mcpResCavvPreauthCC.setExpDate(expiry_date);</code>
Cardholder Authentication Verification Value (CAVV)	<p><i>String</i></p> <p>50-character alphanumeric</p>	<code>mcpResCavvPreauthCC.setCavv(cavv);</code>
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	<code>mcpResCavvPreauthCC.setCryptType(crypt);</code>

### MCP-specific request fields – Required

Variable Name	Type and Limits	Set Method
MCP version number	<p><i>String</i></p> <p>numeric</p> <p>current version is 1.0</p>	<code>mcpResCavvPreauthCC.setMCPVersion("MCP_VERSION_NUM");</code>
cardholder amount	<p><i>String</i></p> <p>12-character numeric</p> <p>smallest discrete unit of foreign currency</p>	<code>mcpResCavvPreauthCC.setCardholderAmount("CARDHOLDER_AMOUNT");</code>
cardholder currency code	<p><i>String</i></p> <p>3-character numeric</p>	<code>mcpResCavvPreauthCC.setCardholderCurrencyCode("CARDHOLDER_CURRENCY_CODE");</code>

### 3-D Secure 2.2 -specific fields – Required

Variable Name	Type and Limits	Set Method
3DS version	<p><i>String</i></p> <p>10-character numeric</p> <p><b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services.</p>	<pre>mcpResCavvPreauthCC .setThreeDSVersion ("ThreeDSVersion");</pre> <p>Acceptable values:</p> <ul style="list-style-type: none"> <li>2.0.0 = 3DS protocol 2.0.0</li> <li>2.1.0 = 3DS protocol 2.1.0</li> <li>2.2.0 = 3DS protocol 2.2.0</li> <li>2.3.0 = 3DS protocol 2.3.0</li> </ul>
3DS server transaction ID	<p><i>String</i></p> <p>36-character numeric</p> <p><b>NOTE:</b> Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from the Cavv Lookup request or MPI 3DS Authentication request</p>	<pre>mcpResCavvPreauthCC .setThreeDSServerTransId ("ThreeDSServerTransId");</pre>

### MCP Pre-Authorization with 3-D Secure and Vault transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <p><b>NOTE:</b> Some special characters are not allowed: &lt;&gt; \$ % = ? ^ { } [ ] \</p>	<pre>mcpResCavvPreauthCC.setCustId (cust_id);</pre>
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p>	<pre>mcpResCavvPreauthCC .setDynamicDescriptor(dynamic_ descriptor);</pre>

Variable Name	Type and Limits	Set Method
<b>NOTE:</b> Some special characters are not allowed: < > \$ % = ? ^ { } [ ] \		
wallet indicator	<i>String</i> 3-character alphanumeric	<code>mcpResCavvPreauthCC.setWalletIndicator(wallet_indicator);</code>
Credential on File Info  cof	<i>Object</i> N/A	<code>mcpResCavvPreauthCC.setCofInfo(cof);</code>
<b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.		
AVS Information	<i>Object</i> N/A	<code>mcpResCavvPreauthCC.setAvsInfo(avsCheck);</code>
CVD Information	<i>Object</i> N/A	<code>mcpResCavvPreauthCC.setCvdInfo(cvdCheck);</code>

**MCP-specific request fields – Optional**

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i> N/A	<code>mcpResCavvPreauthCC.setMCPRateToken("MCP_RATE_TOKEN");</code>

**3-D Secure 2.2 -specific fields – Optional**

Variable Name	Type and Limits	Set Method
DS transaction ID	<i>String</i>	<code>mcpResCavvPreauthCC.setDsTransId("DsTransId");</code>

Variable Name	Type and Limits	Set Method
<b>NOTE:</b> Only used in financial transactions using 3rd Party 3-D Secure services.	36-character alphanumeric	

## Sample MCP Pre-Authorization with 3-D Secure and Vault

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPResCavvPreauthCC
{
    public static void main(String[] args)
    {
        String store_id = "store1";
        String api_token = "yesguy1";
        String data_key = "4INQR1A8ocxD0oafSz50LADXY";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String amount = "1.00";
        String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile
        will be used
        String cavv = "AAABBJg0VhI0VniQEjRWAAAAAA";
        String processing_country_code = "CA";
        String expdate = "1901";
        String crypt_type = "7";
        boolean status_check = false;
        MCPResCavvPreauthCC mcpResCavvPreauthCC = new MCPResCavvPreauthCC();
        mcpResCavvPreauthCC.setOrderId(order_id);
        mcpResCavvPreauthCC.setDataKey(data_key);
        mcpResCavvPreauthCC.setCustomerId(cust_id);
        mcpResCavvPreauthCC.setAmount(amount);
        mcpResCavvPreauthCC.setCavv(cavv);
        mcpResCavvPreauthCC.setExpDate(expdate);
        mcpResCavvPreauthCC.setCryptType(crypt_type);

        mcpResCavvPreauthCC.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using
        3rd Party 3-D Secure services
        mcpResCavvPreauthCC.setThreeDSServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f");
        Mandatory for financial transactions using 3rd Party 3-D Secure services - obtained from
        MpiCavvLookup or MpiThreeDSAuthentication
        //MCP Fields
        mcpResCavvPreauthCC.setMCPVersion("1.0");
        mcpResCavvPreauthCC.setCardholderAmount("500");
        mcpResCavvPreauthCC.setCardholderCurrencyCode("840");
        mcpResCavvPreauthCC.setMCPRateToken("P1623165281389116");

        //Mandatory - Credential on File details
        CofInfo cof = new CofInfo();
        cof.setPaymentIndicator("U");
        cof.setPaymentInformation("2");
        cof.setIssuerId("139X3130ASCXAS9");

        mcpResCavvPreauthCC.setCofInfo(cof);

        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(mcpResCavvPreauthCC);
    }
}

```

```

mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());

//ResolveData
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpiryDate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 8.10 MCP Pre-Authorization Completion

Retrieves funds that have been locked by an MCP Pre-Authorization transaction, and prepares them for settlement into the merchant's account.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

### MCP Pre-Authorization Completion transaction object definition

```
MCPCompletion mcpCompletion = new MCPCompletion();
```

### HttpsPostRequest object for MCP Pre-Authorization Completion transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpCompletion);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Pre-Authorization Completion transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	mcpCompletion.setOrderId(order_id);
transaction number	<i>String</i> 255-character, alpha- numeric, hyphens or under- scores  variable length	mcpCompletion.setTxnNumber(txn_number);
electronic commerce indicator	<i>String</i> 1-character alphanumeric	mcpCompletion.setCryptType(crypt);

### MCP-specific request fields – Required

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i>	mcpCompletion.setMCPVersion("MCP_VERSION_NUM");

Variable Name	Type and Limits	Set Method
	numeric current version is 1.0	
cardholder amount	<i>String</i> 12-character numeric  smallest discrete unit of foreign currency	mcpCompletion .setCardholderAmount ("CARDHOLDER_AMOUNT");
cardholder currency code	<i>String</i> 3-character numeric	mcpCompletion .setCardholderCurrencyCode ("CARDHOLDER_CURRENCY_CODE");

**MCP Pre-Authorization Completion transaction request fields – Optional**

Variable Name	Type and Limits	Set Method
customer ID	<i>String</i> 50-character alphanumeric  <b>NOTE:</b> Some special characters are not allowed: < > \$ % = ? ^ { } [ ] \	mcpCompletion.setCustId(cust_id);
dynamic descriptor	<i>String</i> 20-character alphanumeric  total of 22 characters including your merchant name and separator  <b>NOTE:</b> Some special characters are not allowed: < > \$ % = ? ^ { } [ ] \	mcpCompletion .setDynamicDescriptor(dynamic_descriptor);

## MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i> N/A	<code>mcpCompletion.setMCPRateToken("MCP_RATE_TOKEN");</code>

## Sample MCP Pre-Authorization Completion

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPCompletion
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        String order_id = "Test1538681966167";
        String txn_number = "696294-0_11";
        String crypt = "7";
        String cust_id = "my customer id";
        String dynamic_descriptor = "my descriptor";
        String ship_indicator = "F" ;
        String processing_country_code = "CA";
        boolean status_check = false;
        MCPCompletion mcpCompletion = new MCPCompletion();
        mcpCompletion.setOrderId(order_id);
        mcpCompletion.setTxnNumber(txn_number);
        mcpCompletion.setCryptType(crypt);
        mcpCompletion.setCustId(cust_id);
        mcpCompletion.setDynamicDescriptor(dynamic_descriptor);
        //mcpCompletion.setShipIndicator(ship_indicator); //optional
        //MCP Fields
        mcpCompletion.setMCVersion("1.0");
        mcpCompletion.setCardholderAmount("500");
        mcpCompletion.setCardholderCurrencyCode("840");
        //mcpCompletion.setMCPRateToken("P1538681661706745"); //optional

        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(mcpCompletion);
        mpgReq.setStatusCheck(status_check);
        mpgReq.send();
        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("CardType = " + receipt.getCardType());
            System.out.println("TransAmount = " + receipt.getTransAmount());
            System.out.println("TxnNumber = " + receipt.getTxnNumber());
            System.out.println("ReceiptId = " + receipt.getReceiptId());
            System.out.println("TransType = " + receipt.getTransType());
            System.out.println("ReferenceNum = " + receipt.getReferenceNum());
            System.out.println("ResponseCode = " + receipt.getResponseCode());
            System.out.println("ISO = " + receipt.getISO());
            System.out.println("BankTotals = " + receipt.getBankTotals());
            System.out.println("Message = " + receipt.getMessage());
            System.out.println("AuthCode = " + receipt.getAuthCode());
            System.out.println("Complete = " + receipt.getComplete());
            System.out.println("TransDate = " + receipt.getTransDate());
        }
    }
}

```

```

System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 8.11 MCP Purchase Correction

Restores the full amount of a previous MCP Purchase or MCP Pre-Authorization Completion transaction to the cardholder's card, and removes any record of it from the cardholder's statement.

This transaction can be used against a Purchase or Pre-Authorization Completion transaction that occurred same day provided that the batch containing the original transaction remains open.

MCP processing uses the automated closing feature, and Batch Close occurs daily between 10 and 11 pm Eastern Time.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

### **MCP Purchase Correction transaction object definition**

```
MCPPurchaseCorrection mcpPurchasecorrection = new MCPPurchaseCorrection();
```

### **HttpsPostRequest object for MCP Purchase Correction transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(mcpPurchasecorrection);
```

### **Core connection object fields (all API transactions)**

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Purchase Correction transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<p><i>String</i></p> <p>50-character alpha-numeric-a-Z A-Z 0-9 _ - : . @ spaces</p>	<code>mcpPurchasecorrection.setOrderId(order_id);</code>
transaction number	<p><i>String</i></p> <p>255-character, alpha-numeric, hyphens or underscores</p> <p>variable length</p>	<code>mcpPurchasecorrection.setTxnNumber(txn_number);</code>
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	<code>mcpPurchasecorrection.setCryptType(crypt);</code>

### MCP Purchase Correction transaction request fields – Optional

Variable Name	Type and Limits	Description
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt; &gt; \$ % = ? ^ { } [ ] \          </div>	<code>mcpPurchasecorrection.setDynamicDescriptor(dynamic_descriptor);</code>
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt; &gt; \$ % = ? ^ { } [ ] \          </div>	<code>mcpPurchasecorrection.setCustId(cust_id);</code>

## Sample MCP Purchase Correction

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPPurchaseCorrection
{
public static void main(String[] args)
{
String store_id = "store5";
String api_token = "yesguy";
String order_id = "Test1538682314339";
String txn_number = "696314-0_11";
String crypt = "7";
String dynamic_descriptor = "123456";
String processing_country_code = "CA";
boolean status_check = false;
MCPPurchaseCorrection mcpPurchasecorrection = new MCPPurchaseCorrection();
mcpPurchasecorrection.setOrderId(order_id);
mcpPurchasecorrection.setTxnNumber(txn_number);
mcpPurchasecorrection.setCryptType(crypt);
mcpPurchasecorrection.setDynamicDescriptor(dynamic_descriptor);
mcpPurchasecorrection.setCustId("my customer id");
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpPurchasecorrection);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

## 8.12 MCP Refund

Restores all or part of the funds from a MCP Purchase or MCP Pre-Authorization Completion transaction to the cardholder's card.

Unlike a MCP Purchase Correction, there is a record of both the initial charge and the refund on the card-holder's statement.

For processing refunds on a different card than the one used in the original transaction, the MCP Independent Refund transaction should be used instead.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

### MCP Refund transaction object definition

```
MCPRefund mcpRefund = new MCPRefund();
```

### HttpsPostRequest object for MCP Refund transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpRefund);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Refund transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alpha-numerica-Z A-Z 0-9 _ - : . @ spaces	mcpRefund.setOrderId(order_id);
transaction number	<i>String</i> 255-character, alpha-numeric, hyphens or under-scores variable length	mcpRefund.setTxnNumber(txn_number);
electronic commerce indic-	<i>String</i>	mcpRefund.setCryptType(crypt);

Variable Name	Type and Limits	Set Method
ator	1-character alphanumeric	

**MCP-specific request fields – Required**

Variable Name	Type and Limits	Set Method
MCP version number	<p><i>String</i></p> <p>numeric</p> <p>current version is 1.0</p>	<code>mcpRefund.setMCPVersion("MCP_VERSION_NUM");</code>
cardholder amount	<p><i>String</i></p> <p>12-character numeric</p> <p>smallest discrete unit of foreign currency</p>	<code>mcpRefund.setCardholderAmount("CARDHOLDER_AMOUNT");</code>
cardholder currency code	<p><i>String</i></p> <p>3-character numeric</p>	<code>mcpRefund.setCardholderCurrencyCode("CARDHOLDER_CURRENCY_CODE");</code>

**MCP Refund transaction request fields – Optional**

Variable Name	Type and Limits	Description
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt; &gt; \$ % = ? ^ { } [ ] \          </div>	<code>mcpRefund.setDynamicDescriptor(dynamic_descriptor);</code>
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt; &gt; \$ % = ? ^ { } [ ] \          </div>	<code>mcpRefund.setCustId(cust_id);</code>

Variable Name	Type and Limits	Description
allowed: <>\$%=?^{}[]\		

### MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i> N/A	mcpRefund.setMCPRateToken("MCP_RATE_TOKEN");

### Sample MCP Refund

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPRefund
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        String amount = "2.00";
        String crypt = "7";
        String dynamic_descriptor = "123456";
        String custid = "mycust9";
        String order_id = "Test1534871380572";
        String txn_number = "332654-0_11";
        String processing_country_code = "CA";
        boolean status_check = false;
        MCPRefund mcpRefund = new MCPRefund();
        mcpRefund.setTxnNumber(txn_number);
        mcpRefund.setOrderId(order_id);
        mcpRefund.setCryptType(crypt);
        mcpRefund.setCustId(custid);
        mcpRefund.setDynamicDescriptor(dynamic_descriptor);

        //MCP Fields
        mcpRefund.setMCPVersion("1.0");
        mcpRefund.setCardholderAmount("200");
        mcpRefund.setCardholderCurrencyCode("840");
        mcpRefund.setMCPRateToken("P1534873994652426");
        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(mcpRefund);
        mpgReq.setStatusCheck(status_check);
        mpgReq.send();
        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("CardType = " + receipt.getCardType());
            System.out.println("TransAmount = " + receipt.getTransAmount());
            System.out.println("TxnNumber = " + receipt.getTxnNumber());
            System.out.println("ReceiptId = " + receipt.getReceiptId());
            System.out.println("TransType = " + receipt.getTransType());
        }
    }
}

```

```

System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 8.13 MCP Independent Refund

Credits a specified amount to the cardholder's credit card. The credit card number and expiry date are mandatory.

It is not necessary for the transaction that you are refunding to have been processed via the Moneris Gateway.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

### Things to Consider:

- Because of the potential for fraud, permission for this transaction is not granted to all accounts by default. If it is required for your business, it must be requested via your account manager.

### MCP Independent Refund transaction object definition

```
MCPIndependentRefund mcpIndrefund = new MCPIndependentRefund();
```

### HttpsPostRequest object for MCP Independent Refund transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(mcpIndrefund);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Independent Refund transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alpha-numeric-A-Z 0-9 _ - : . @ spaces	mcplndrefund.setOrderId(order_id);
credit card number	<i>String</i> max 20-character alpha-numeric	mcplndrefund.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric YYMM	mcplndrefund.setExpDate(expiry_date);
electronic commerce indicator	<i>String</i> 1-character alphanumeric	mcplndrefund.setCryptType(crypt);

### MCP-specific request fields – Required

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i> numeric current version is 1.0	mcplndrefund.setMCPVersion("MCP_VERSION_NUM");
cardholder amount	<i>String</i>	mcplndrefund.setCardholderAmount

Variable Name	Type and Limits	Set Method
	12-character numeric smallest discrete unit of foreign currency	( "CARDHOLDER_AMOUNT" );
cardholder currency code	<i>String</i> 3-character numeric	mcplndrefund .setCardholderCurrencyCode ( "CARDHOLDER_CURRENCY_CODE" );

**MCP Independent Refund transaction request fields – Optional**

Variable Name	Type and Limits	Set Method
customer ID	<i>String</i> 50-character alphanumeric	mcplndrefund.setCustId (cust_id);
	<p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p>	
dynamic descriptor	<i>String</i> 20-character alphanumeric total of 22 characters including your merchant name and separator	mcplndrefund .setDynamicDescriptor (dynamic_descriptor);
	<p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p>	

**MCP-specific request fields – Optional**

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i> N/A	mcplndrefund.setMCPRateToken ( "MCP_RATE_TOKEN" );

## Sample MCP Independent Refund

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPIndependentRefund
{
public static void main(String[] args)
{
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String store_id = "store5";
String api_token = "yesguy";
String cust_id = "my customer id";
String amount = "20.00";
String pan = "4242424242424242";
String expdate = "1901"; //YYMM
String crypt = "7";
String processing_country_code = "CA";
boolean status_check = false;
MCPIndependentRefund mcpIndrefund = new MCPIndependentRefund();
mcpIndrefund.setOrderId(order_id);
mcpIndrefund.setCustId(cust_id);
mcpIndrefund.setAmount(amount);
mcpIndrefund.setPan(pan);
mcpIndrefund.setExpdate(expdate);
mcpIndrefund.setCryptType(crypt);
mcpIndrefund.setDynamicDescriptor("123456");

//MCP Fields
mcpIndrefund.setMCPVersion("1.0");
mcpIndrefund.setCardholderAmount("500");
mcpIndrefund.setCardholderCurrencyCode("840");
mcpIndrefund.setMCPRateToken("R1538679861330690");
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpIndrefund);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
}
}

```

```

        System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
        System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
        System.out.println("HostId = " + receipt.getHostId());
    }
    catch (Exception e)
    {
        e.printStackTrace();
    }
}
}

```

## 8.14 MCP Purchase with Vault

This transaction uses the data key to identify a previously registered credit card profile in Vault. The details saved within the profile are then submitted to perform a Purchase transaction.

The data key may be a temporary one generated used Hosted Tokenization, or may be a permanent one from the Vault.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

### MCP Purchase with Vault transaction object definition

```
MCPResPurchaseCC mcpResPurchaseCC = new MCPResPurchaseCC();
```

### HttpsPostRequest object for MCP Purchase with Vault transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpResPurchaseCC);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Purchase with Vault transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<i>String</i>	mcpResPurchaseCC.setData(data_key);

Variable Name	Type and Limits	Set Method
	25-character alphanumeric	
order ID	<p><i>String</i></p> <p>50-character alpha- numerica-Z A-Z 0-9 _ - : . @ spaces</p>	<code>mcpResPurchaseCC.setOrderId (order_id);</code>
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	<code>mcpResPurchaseCC.setCryptType (crypt);</code>

#### MCP-specific request fields – Required

Variable Name	Type and Limits	Set Method
MCP version number	<p><i>String</i></p> <p>numeric</p> <p>current version is 1.0</p>	<code>mcpResPurchaseCC.setMCPVersion ("MCP_VERSION_NUM");</code>
cardholder amount	<p><i>String</i></p> <p>12-character numeric</p> <p>smallest discrete unit of for- eign currency</p>	<code>mcpResPurchaseCC .setCardholderAmount ("CARDHOLDER_AMOUNT");</code>
cardholder currency code	<p><i>String</i></p> <p>3-character numeric</p>	<code>mcpResPurchaseCC .setCardholderCurrencyCode ("CARDHOLDER_CURRENCY_CODE");</code>

#### MCP Purchase with Vault transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt; &gt; \$ % = ? ^ { } [ ] \          </div>	<code>mcpResPurchaseCC.setCustId(cust_id);</code>

Variable Name	Type and Limits	Set Method
Credential on File Info  cof	<i>Object</i>  N/A	<code>mcpResPurchaseCC.setCofInfo(cof);</code>
<p><b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.</p>		
AVS Information	<i>Object</i>  N/A	<code>mcpResPurchaseCC.setAvsInfo(avscCheck);</code>
CVD Information	<i>Object</i>  N/A	<code>mcpResPurchaseCC.setCvdInfo(cvdCheck);</code>

### MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i>  N/A	<code>mcpResPurchaseCC.setMCPRateToken("MCP_RATE_TOKEN");</code>

### Sample MCP Purchase with Vault

```
package Canada;
import JavaAPI.*;
public class TestCanadaMCPResPurchaseCC
{
public static void main(String[] args)
{
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String store_id = "store5";
String api_token = "yesguy";
String data_key = "800XGiwxgvfbZngigVFeld9d2";
String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile
will be used
String crypt_type = "1";
String descriptor = "my descriptor";
String processing_country_code = "CA";
String expdate = "1512"; //For Temp Token
boolean status_check = false;
MCPResPurchaseCC mcpResPurchaseCC = new MCPResPurchaseCC();
```

```

mcpResPurchaseCC.setDataKey(data_key);
mcpResPurchaseCC.setOrderId(order_id);
mcpResPurchaseCC.setCustId(cust_id);
mcpResPurchaseCC.setCryptType(crypt_type);
//resPurchaseCC.setDynamicDescriptor(descriptor);
//resPurchaseCC.setExpDate(expdate); //Temp Tokens only

//MCP Fields
mcpResPurchaseCC.setMCPVersion("1.0");
mcpResPurchaseCC.setCardholderAmount("500");
mcpResPurchaseCC.setCardholderCurrencyCode("840");
mcpResPurchaseCC.setMCPRateToken("P1538679861174342");
//Mandatory - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");

mcpResPurchaseCC.setCofInfo(cof);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpResPurchaseCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("Cust ID = " + receipt.getResCustId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("IssuerId = " + receipt.getIssuerId());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());

```

```
    }
    catch (Exception e)
    {
        e.printStackTrace();
    }
}
```

## 8.15 MCP Pre-Authorization with Vault

This transaction uses the data key to identify a previously registered credit card profile in Vault. The details saved within the profile are then submitted to perform a Pre-Authorization transaction.

The data key may be a temporary one generated using Hosted Tokenization, or may be a permanent one from the Vault.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

## MCP Pre-Authorization with Vault transaction object definition

```
MCPResPreauthCC mcpResPreauthCC = new MCPResPreauthCC();
```

## **HttpsPostRequest object for MCP Pre-Authorization with Vault transaction**

```
HttpsPostRequest mpgReq = new HttpsPostRequest();  
mpgReq.setTransaction(mcpResPreauthCC);
```

## Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

## MCP Pre-Authorization with Vault transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	<code>mcpResPreauthCC.setDataKey(data_key);</code>
order ID	<i>String</i>	<code>mcpResPreauthCC.setOrderId(order_id);</code>

Variable Name	Type and Limits	Set Method
electronic commerce indicator	String 50-character alpha-numeric-Z A-Z 0-9 _ - : . @ spaces 1-character alphanumeric	mcpResPreauthCC.setCryptType(crypt);

**MCP-specific request fields – Required**

Variable Name	Type and Limits	Set Method
MCP version number	String numeric current version is 1.0	mcpResPreauthCC.setMCPVersion("MCP_VERSION_NUM");
cardholder amount	String 12-character numeric smallest discrete unit of foreign currency	mcpResPreauthCC.setCardholderAmount("CARDHOLDER_AMOUNT");
cardholder currency code	String 3-character numeric	mcpResPreauthCC.setCardholderCurrencyCode("CARDHOLDER_CURRENCY_CODE");

**MCP Pre-Authorization with Vault transaction request fields – Optional**

Variable Name	Type and Limits	Set Method
customer ID	String 50-character alphanumeric <b>NOTE:</b> Some special characters are not allowed: < > \$ % = ? ^ { } [ ] \	mcpResPreauthCC.setCustId(cust_id);
dynamic descriptor	String 20-character alphanumeric	mcpResPreauthCC.setDynamicDescriptor(dynamic_descriptor);

Variable Name	Type and Limits	Set Method
<p><b>NOTE:</b> For Pre-Authorization transactions: the value in the dynamic descriptor field will only be carried over to a Pre-Authorization Completion when executing the latter via the Merchant Resource Center; otherwise, the value for dynamic descriptor must be sent again in the Pre-Authorization Completion</p>	<p>total of 22 characters including your merchant name and separator</p> <p><b>NOTE:</b> Some special characters are not allowed: &lt;&gt;\$%=?^{}[]\</p>	
final authorization	<p><i>String</i></p> <p>true/false</p> <p><b>NOTE:</b> Applies to Mastercard transactions only</p>	mcpResPreauthCC.setFinalAuth ("true");
Credential on File Info	<i>Object</i>	mcpResPreauthCC.setCofInfo (cof) ;
cof	N/A	
	<p><b>NOTE:</b> This is a nested object within the transaction, and required when storing or using the customer's stored credentials. For information about fields in the Credential on File Info object, see Credential on File Info Object and Variables.</p>	
AVS Information	<p><i>Object</i></p> <p>N/A</p>	mcpResPreauthCC.setAvsInfo (avsCheck);
CVD Information	<p><i>Object</i></p> <p>N/A</p>	mcpResPreauthCC.setCvdInfo (cvdCheck);

### MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<i>String</i>	mcpResPreauthCC.setMCPRateToken ("MCP_RATE_TOKEN");

Variable Name	Type and Limits	Set Method
	N/A	

## Sample MCP Pre-Authorization with Vault

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPResPreauthCC
{
    public static void main(String[] args)
    {
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String store_id = "store5";
        String api_token = "yesguy";
        String data_key = "rS7DbroQHJmJxdBfXFXiauQc4";
        String amount = "1.00";
        String cust_id = "customer1"; //if sent will be submitted, otherwise cust_id from profile
        will be used
        String crypt_type = "1";
        String dynamic_descriptor = "my descriptor";
        String processing_country_code = "CA";
        String expdate = "1712"; //For Temp Token
        boolean status_check = false;
        MCPResPreauthCC mcpResPreauthCC = new MCPResPreauthCC();
        mcpResPreauthCC.setDataKey(data_key);
        mcpResPreauthCC.setOrderId(order_id);
        mcpResPreauthCC.setCustId(cust_id);
        mcpResPreauthCC.setAmount(amount);
        mcpResPreauthCC.setCryptType(crypt_type);
        mcpResPreauthCC.setDynamicDescriptor(dynamic_descriptor);
        //mcpResPreauthCC.setExpDate(expdate); //Temp Tokens only
        //mcpResPreauthCC.setFinalAuth("true");

        //MCP Fields
        mcpResPreauthCC.setMCPVersion("1.0");
        mcpResPreauthCC.setCardholderAmount("500");
        mcpResPreauthCC.setCardholderCurrencyCode("840");
        mcpResPreauthCC.setMCPRateToken("P1538681661706745");

        //Mandatory - Credential on File details
        CofInfo cof = new CofInfo();
        cof.setPaymentIndicator("U");
        cof.setPaymentInformation("2");
        cof.setIssuerId("139X3130ASCXAS9");

        mcpResPreauthCC.setCofInfo(cof);
        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(mcpResPreauthCC);
        mpgReq.setStatusCheck(status_check);
        mpgReq.send();
        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("DataKey = " + receipt.getDataKey());
            System.out.println("ReceiptId = " + receipt.getReceiptId());
            System.out.println("ReferenceNum = " + receipt.getReferenceNum());
            System.out.println("ResponseCode = " + receipt.getResponseCode());
        }
    }
}

```

```

System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("IsCorporate = " + receipt.getCorporateCard());
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExpdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());
System.out.println("IssuerId = " + receipt.getIssuerId());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 8.16 MCP Independent Refund with Vault

This transaction uses the data key to identify a previously registered credit card profile in Vault. The details saved within the profile are then submitted to perform an Independent Refund transaction.

This transaction request is the multi-currency pricing (MCP) enabled version of the equivalent financial transaction.

### Things to Consider:

- Because of the potential for fraud, permission for this transaction is not granted to all accounts by default. If it is required for your business, it must be requested via your account manager.

### MCP Independent Refund with Vault transaction object definition

```
MCPResIndRefundCC mcpResIndRefundCC = new MCPResIndRefundCC();
```

### HttpsPostRequest object for MCP Independent Refund with Vault transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(mcpResIndRefundCC);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### MCP Independent Refund with Vault transaction request fields – Required

Variable Name	Type and Limits	Set Method
data key	<i>String</i> 25-character alphanumeric	mcpResIndRefundCC.setData(data_key);
order ID	<i>String</i> 50-character alpha-numerica-Z A-Z 0-9 _ - : . @ spaces	mcpResIndRefundCC.setOrderId(order_id);
electronic commerce indicator	<i>String</i> 1-character alphanumeric	mcpIndrefund.setCryptType(crypt);

### MCP-specific request fields – Required

Variable Name	Type and Limits	Set Method
MCP version number	<i>String</i> numeric current version is 1.0	mcpResIndRefundCC.setMCPVersion("MCP_VERSION_NUM");

Variable Name	Type and Limits	Set Method
cardholder amount	<p><i>String</i></p> <p>12-character numeric</p> <p>smallest discrete unit of foreign currency</p>	mcpResIndRefundCC .setCardholderAmount ("CARDHOLDER_AMOUNT");
cardholder currency code	<p><i>String</i></p> <p>3-character numeric</p>	mcpResIndRefundCC .setCardholderCurrencyCode ("CARDHOLDER_CURRENCY_CODE");

### MCP Independent Refund with Vault transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt;\$%=?^{}[]\         </div>	mcpResIndRefundCC.setCustId(cust_id);

### MCP-specific request fields – Optional

Variable Name	Type and Limits	Set Method
MCP rate token	<p><i>String</i></p> <p>N/A</p>	mcpResIndRefundCC .setMCPRateToken("MCP_RATE_TOKEN");

### Sample MCP Independent Refund with Vault

```

package Canada;
import JavaAPI.*;
public class TestCanadaMCPResIndRefundCC
{
  public static void main(String[] args)
  {
    java.util.Date createDate = new java.util.Date();
    String order_id = "Test"+createDate.getTime();
    String store_id = "store5";
    String api_token = "yesguy";
    String data_key = "rS7DbroQHJmJxdBfXFXiauQc4";
    String amount = "1.00";
    String cust_id = "customer1";
    String crypt_type = "1";
    String processing_country_code = "CA";
    boolean status_check = false;
    MCPResIndRefundCC mcpResIndRefundCC = new MCPResIndRefundCC();
  }
}
  
```

```

mcpResIndRefundCC.setDataKey(data_key);
mcpResIndRefundCC.setOrderId(order_id);
mcpResIndRefundCC.setCustomerId(cust_id);
mcpResIndRefundCC.setAmount(amount);
mcpResIndRefundCC.setCryptType(crypt_type);

//MCP Fields
mcpResIndRefundCC.setMCPVersion("1.0");
mcpResIndRefundCC.setCardholderAmount("500");
mcpResIndRefundCC.setCardholderCurrencyCode("840");
mcpResIndRefundCC.setMCPRateToken("R1538679861330690");
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(mcpResIndRefundCC);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("DataKey = " + receipt.getDataKey());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("ResSuccess = " + receipt.getResSuccess());
System.out.println("PaymentType = " + receipt.getPaymentType());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("Cust ID = " + receipt.getResCustomerId());
System.out.println("Phone = " + receipt.getResPhone());
System.out.println("Email = " + receipt.getResEmail());
System.out.println("Note = " + receipt.getResNote());
System.out.println("Masked Pan = " + receipt.getResMaskedPan());
System.out.println("Exp Date = " + receipt.getResExdate());
System.out.println("Crypt Type = " + receipt.getResCryptType());
System.out.println("Avs Street Number = " + receipt.getResAvsStreetNumber());
System.out.println("Avs Street Name = " + receipt.getResAvsStreetName());
System.out.println("Avs Zipcode = " + receipt.getResAvsZipcode());

System.out.println("MerchantSettlementAmount = " + receipt.getMerchantSettlementAmount());
System.out.println("CardholderAmount = " + receipt.getCardholderAmount());
System.out.println("CardholderCurrencyCode = " + receipt.getCardholderCurrencyCode());
System.out.println("MCPRate = " + receipt.getMCPRate());
System.out.println("MCPErrorStatusCode = " + receipt.getMCPErrorStatusCode());
System.out.println("MCPErrorMessage = " + receipt.getMCPErrorMessage());
System.out.println("HostId = " + receipt.getHostId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 8.17 MCP Currency Codes

For currency symbols, see <https://justforex.com/education/currencies>

**NOTE:** This documentation contains links to websites owned and operated by third parties. If you use these links, you leave our website. These links are provided for your information and convenience only and are not an endorsement by Moneris Solutions of the content of such linked websites or third parties. Moneris Solutions has no control over the contents of any linked website and is not responsible for these websites or their content or availability. If you decide to access any third party websites and make use of the information contained on them, you do so entirely at your own risk.

Numeric Currency Code (ISO)	Currency Name/Acronym
008	Albanian Lek (ALL)
012	Algerian Dinar (DZD)
032	Argentine Peso (ARS)
036	Australian Dollar (AUD)
048	Bahraini Dinar (BHD)
050	Bangladeshi Taka (BDT)
052	Barbados Dollar (BBD)
060	Bermudian Dollar (BMD)
064	Bhutan Ngultrum (BTN)
068	Bolivia Boliviano (BOB)
084	Belize Dollar (BZD)
090	Solomon Islands Dollar (SBD)
096	Brunei Dollar (BND)
108	Burundi Franc (BIF)
132	Cabo Verde Escudo (CVE)

Numeric Currency Code (ISO)	Currency Name/Acronym
136	Cayman Islands Dollar (KYD)
144	Sri Lanka Rupee (LKR)
152	Chilean Peso (CLP)
156	Chinese Yuan (CNY)
170	Colombian Peso (COP)
174	Comorian Franc (KMF)
188	Costa Rican Colon (CRC)
191	Croatian Kuna (HRK)
192	Cuban Peso (CUP)
203	Czech Koruna (CZK)
208	Danish Krone (DKK)
214	Dominican Republic Peso
222	Salvadoran Colon (SVC)
242	Fijian Dollar (FJD)
262	Djiboutian Franc (DJF)
270	Gambian Dalasi (GMD)
292	Gibraltar Pound (GIP)
320	Guatemala Quetzal (GTQ)
324	Guinean Franc (GNF)
328	Guyanese Dollar (GYD)
332	Haitian Gourde (HTG)
340	Honduran Lempira (HNL)

Numeric Currency Code (ISO)	Currency Name/Acronym
344	Hong Kong Dollar (HKD)
348	Hungarian Forint (HUF)
352	Iceland Krona (ISK)
356	Indian Rupee (INR)
360	Indonesian Rupiah (IDR)
376	Israeli Shekel (ILS)
388	Jamaican Dollar (JMD)
392	Japanese Yen (JPY)
398	Kazakh Tenge (KZT)
400	Jordanian Dinar (JOD)
404	Kenyan Shilling (KES)
410	South Korean Won (KRW)
414	Kuwaiti Dinar (KWD)
418	Laotian Kip (LAK)
426	Lesotho Loti (LSL)
430	Liberian Dollar (LRD)
446	Macanese Pataca (MOP)
454	Malawian Kwacha (MWK)
458	Malaysian Ringgit (MYR)
462	Maldivian Rufiyaa (MVR)
480	Mauritius Rupee (MUR)
484	Mexican Peso (MXN)

Numeric Currency Code (ISO)	Currency Name/Acronym
498	Moldovan Leu (MDL)
504	Moroccan Dirham (MAD)
512	Omani Rial (OMR)
516	Namibian Dollar (NAD)
524	Nepalese Rupee (NPR)
532	Netherlands Antillean Guilder (ANG)
533	Aruban Guilder (AWG)
548	Vanuatu Vatu (VUV)
554	New Zealand Dollar (NZD)
558	Nicaraguan Cordoba (NIO)
566	Nigerian Naira (NGN)
578	Norwegian Krone (NOK)
586	Pakistan Rupee (PKR)
598	Papua New Guinean Kina (PGK)
600	Paraguayan Guarani (PYG)
604	Peruvian Nuevo Sol (PEN)
608	Philippine Peso (PHP)
634	Qatari Rial (QAR)
643	Russian Ruble (RUB)
646	Rwandan Franc (RWF)
654	Saint Helena Pound (SHP)
682	Saudi Riyal (SAR)

Numeric Currency Code (ISO)	Currency Name/Acronym
690	Seychelles Rupee (SCR)
694	Sierra Leonean Leone (SLL)
702	Singapore Dollar (SGD)
704	Vietnamese Dong (VND)
710	South African Rand (ZAR)
748	Swaziland Lilangeni (SZL)
752	Swedish Krona (SEK)
756	Swiss Franc (CHF)
764	Thai Baht (THB)
780	Trinidad & Tobago Dollar (TTD)
784	UAE Dirham (AED)
788	Tunisian Dinar (TND)
800	Ugandan Shilling (UGX)
807	Macedonian Denar (MKD)
818	Egyptian Pound (EGP)
826	UK Pound Sterling (GBP)
834	Tanzanian Shilling (TZS)
840	US Dollar (USD)
858	Uruguayan Peso (UYU)
860	Uzbekistani Sum (UZS)
882	Samoan Tala (WST)
901	New Taiwan Dollar (TWD)

Numeric Currency Code (ISO)	Currency Name/Acronym
929	Mauritanian Ouguiya (MRU)
933	Belarusian Ruble (BYN)
934	Turkmenistan Manat (TMT)
941	Serbian Dinar (RSD)
943	Mozambique Metical (MZN)
944	Azerbaijani Manat (AZN)
946	Romanian New Leu (RON)
949	New Turkish Lira (TRY)
951	East Caribbean Dollar (XCD)
952	West African CFA Franc BCEAO (XOF)
953	CFP Franc (XPF)
967	Zambian Kwacha (ZMW)
968	Surinamese Dollar (SRD)
969	Malagasy Ariary (MGA)
971	Afghan Afghani (AFN)
972	Tajikistan Somoni (TJS)
973	Angola Kwanza (AOA)
975	Bulgarian Lev (BGN)
977	Bosnia and Herzegovina Convertible Mark (BAM)
978	Euro (EUR)
981	Georgian Lari (GEL)
985	Polish New Zloty (PLN)

Numeric Currency Code (ISO)	Currency Name/Acronym
986	Brazilian Real (BRL)

## 8.18 MCP Error Codes

Error Code	Description
200	OK (there will be no value returned in the MCP error message)
500	Upstream error
1000	Invalid JSON format
1003	Invalid txnType detected: <invalid txnType> please enter PURCHASE or REFUND
1005	Invalid rateInquiryId-txnType combination.
1007	Warning: at least one of cardHolderCurrency or merchantSettlementCurrency must be non-zero.
1008	Card-holder amount must be non-zero.
1009	Negative amounts detected
1010	Unsupported cardholder currency detected: <unsupported currency>
1015	invalid rateInquiryId
1016	Unsupported merchant id

## 9 Installments by Visa

- 9.1 About Installments by Visa
- 9.2 Installments by Visa Transaction Types
- 9.3 Sending Transactions with Installments by Visa
- 9.4 Installment Plan Lookup
- 9.5 Vault Installment Plan Lookup
- 9.6 Installment Info Object

### 9.1 About Installments by Visa

Installments by Visa enables issuers the ability to offer cardholders installment payment plans at the time of purchase. When a cardholder accepts an installment plan option, the merchant receives the payment in full, and the cardholder pays the issuer according to the plan.

For a full list of definitions of the request and response fields see B.3 Definition of Response Fields – Installments by Visa

### 9.2 Installments by Visa Transaction Types

Financial transactions that support Installments by Visa include the following:

- Purchase
- Pre-Authorization
- Pre-Authorization Completion
- Purchase Correction
- Refund

- Purchase with Vault – ResPurchaseCC
- Pre-Authorization with Vault – ResPreauthCC

**NOTE:** Independent Refund transactions do not support Installments by Visa

**WARNING:** Do not send the Installment Info object on any transaction that is not intended to offer Installments by Visa functionality; doing so may cause the transaction to fail.

## 9.3 Sending Transactions with Installments by Visa

Sending transactions with Installments by Visa functionality involves the following steps:

1. Send the Installment Plan Lookup or Vault Installment Plan Lookup (for Vault transactions) transaction request to obtain the **installment plan ID**, **installment plan reference** and **terms and conditions version** data in the response
2. Using the data obtained in the response above, send the Installment Info object in the Purchase or Pre-Authorization; for Vault transactions, use Purchase with Vault or Pre-Authorization with Vault

When completing the transaction with a Pre-Authorization Completion, or when doing a Purchase Correction or Refund, as in the rest of the Unified API, the previous transactions are referenced using the **order ID** and **transaction number**, or for Vault transactions, using the **data key**.

**NOTE:** Independent Refund transactions do not support Installments by Visa

## 9.4 Installment Plan Lookup

Used to obtain information required to do financial transactions with Installments by Visa.

### Installment Plan Lookup transaction object definition

```
InstallmentLookup installmentLookup = new InstallmentLookup();
```

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(installmentLookup);
```

### Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setStoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

### Installment Plan Lookup transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	installmentLookup.setOrderId(order_id);
amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	installmentLookup.setAmount(amount);
<b>EXAMPLE: 1234567.89</b>		
credit card number	<i>String</i> max 20-character alpha- numeric	installmentLookup.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric  YYMM	installmentLookup.setExpDate(expiry_date);
<pre>package Canada; import JavaAPI.*;</pre>		

```

public class TestCanadaInstallmentLookup
{
    public static void main(String[] args)
    {
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String store_id = "monca03650";
        String api_token = "7Yw0MPTlhbRcZiE6837";
        String amount = "600.00";
        String pan = "4761270070000310";
        String expdate = "2212"; //YYMM format

        InstallmentLookup InstallmentLookup = new InstallmentLookup();
        InstallmentLookup.setOrderId(order_id);
        InstallmentLookup.setAmount(amount);
        InstallmentLookup.setPan(pan);
        InstallmentLookup.setExpdate(expdate);

        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
        mpgReq.setApiToken(api_token);
        mpgReq.setTransaction(InstallmentLookup);

        //Optional - Proxy
        mpgReq.setProxy(false); //true to use proxy
        mpgReq.setProxyHost("proxyURL");
        mpgReq.setProxyPort("proxyPort");
        mpgReq.setProxyUser("proxyUser"); //optional - domainName\user
        mpgReq.setProxyPassword("proxyPassword"); //optional
        mpgReq.send();

        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("CardType = " + receipt.getCardType());
            System.out.println("TransAmount = " + receipt.getTransAmount());
            System.out.println("TxnNumber = " + receipt.getTxnNumber());
            System.out.println("ReceiptId = " + receipt.getReceiptId());
            System.out.println("TransType = " + receipt.getTransType());
            System.out.println("ReferenceNum = " + receipt.getReferenceNum());
            System.out.println("ResponseCode = " + receipt.getResponseCode());
            System.out.println("ISO = " + receipt.getISO());
            System.out.println("BankTotals = " + receipt.getBankTotals());
            System.out.println("Message = " + receipt.getMessage());
            System.out.println("AuthCode = " + receipt.getAuthCode());
            System.out.println("Complete = " + receipt.getComplete());
            System.out.println("TransDate = " + receipt.getTransDate());
            System.out.println("TransTime = " + receipt.getTransTime());
            System.out.println("Ticket = " + receipt.getTicket());
            System.out.println("TimedOut = " + receipt.getTimedOut());
            System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
        }

        EligibleInstallmentPlans eligibleInstallmentPlans = receipt.getEligibleInstallmentPlans();

        int planCount = eligibleInstallmentPlans.getPlanCount();
        PlanDetails [] installmentPlans = eligibleInstallmentPlans.getInstallmentPlans();

        for (int i = 0; i < planCount; i++)
        {
            System.out.println("\nPlanId = " + installmentPlans[i].getPlanId() + "\n");
            System.out.println("PlanIdRef = " + installmentPlans[i].getPlanIdRef());
            System.out.println("Name = " + installmentPlans[i].getName());
            System.out.println("Type = " + installmentPlans[i].getType());
            System.out.println("NumInstallments = " + installmentPlans[i].getNumInstallments());
        }
    }
}

```

```

System.out.println("InstallmentFrequency = " + installmentPlans[i].getInstallmentFrequency
());
TAC tac = installmentPlans[i].getTac();
TACDetails [] tacDetailsList = tac.getTacDetailsList();
int tacCount = tac.getTacCount();

for (int j = 0; j < tacCount; j++)
{
TACDetails tacDetails = tacDetailsList[j];

System.out.println("\nText = " + tacDetails.getText() +"\n");
System.out.println("Url = " + tacDetails.getUrl());
System.out.println("Version = " + tacDetails.getVersion());
System.out.println("LanguageCode = " + tacDetails.getLanguageCode());
}

PromotionInfo promotionInfo = installmentPlans[i].getPromotionInfo();

System.out.println("\nPromotionCode = " + promotionInfo.getPromotionCode() +"\n");
System.out.println("PromotionId = " + promotionInfo.getPromotionId());

FirstInstallment firstInstallment = installmentPlans[i].getFirstInstallment();

System.out.println("\nUpfrontFee = " + firstInstallment.getUpfrontFee() +"\n");
System.out.println("InstallmentFee = " + firstInstallment.getInstallmentFee());
System.out.println("Amount = " + firstInstallment.getAmount());

LastInstallment lastInstallment = installmentPlans[i].getLastInstallment();

System.out.println("\nInstallmentFee = " + lastInstallment.getInstallmentFee());
System.out.println("Amount = " + lastInstallment.getAmount());

System.out.println("\nAPR = " + installmentPlans[i].getAPR());
System.out.println("\nTotalFees = " + installmentPlans[i].getTotalFees());
System.out.println("\nTotalPlanCost = " + installmentPlans[i].getTotalPlanCost());
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 9.5 Vault Installment Plan Lookup

Used to obtain information required to do financial transactions with installments when using a token stored in the Moneris Vault.

### Vault Installment Plan Lookup transaction object definition

```

ResInstallmentLookup resInstallmentLookup= new ResInstallmentLookup();

HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(resInstallmentLookup);

```

## Core connection object fields (all API transactions)

Variable Name	Type and Limits	
store ID	<i>String</i> N/A	mpgReq.setstoreId(store_id);
API token	<i>String</i> N/A	mpgReq.setApiToken(api_token);

## Vault Installment Plan Lookup transaction request fields – Required

Variable Name	Type and Limits	
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	resInstallmentLookup.setOrderId(order_id);
amount	<i>String</i> 10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	resInstallmentLookup.setAmount(amount);
	<b>EXAMPLE:</b> 1234567.89	
data key	<i>String</i> 25-character alphanumeric	resInstallmentLookup.setData(data_key);
expiry date	<i>String</i> 4-character alphanumeric YYMM	resInstallmentLookup.setExpDate(expiry_date);
	<b>NOTE:</b> Only send this field if using a temporary token; if not, omit this field	
	<pre>package Canada; import JavaAPI.*; public class TestCanadaInstallmentLookup {     public static void main(String[] args)     {</pre>	

```

java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String store_id = "monca03650";
String api_token = "7Yw0MPTlhjBRcZiE6837";
String amount = "600.00";
String expdate = "2212"; //YYMM format

InstallmentLookup InstallmentLookup = new InstallmentLookup();
InstallmentLookup.setOrderId(order_id);
InstallmentLookup.setAmount(amount);
InstallmentLookup.setExpdate(expdate);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(InstallmentLookup);

//Optional - Proxy
mpgReq.setProxy(false); //true to use proxy
mpgReq.setProxyHost("proxyURL");
mpgReq.setProxyPort("proxyPort");
mpgReq.setProxyUser("proxyUser"); //optional - domainName\User
mpgReq.setProxyPassword("proxyPassword"); //optional
mpgReq.send();

try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());

EligibleInstallmentPlans eligibleInstallmentPlans = receipt.getEligibleInstallmentPlans();

int planCount = eligibleInstallmentPlans.getPlanCount();
PlanDetails [] installmentPlans = eligibleInstallmentPlans.getInstallmentPlans();

for (int i = 0; i < planCount; i++)
{
System.out.println("\nPlanId = " + installmentPlans[i].getPlanId() + "\n");
System.out.println("PlanIdRef = " + installmentPlans[i].getPlanIdRef());
System.out.println("Name = " + installmentPlans[i].getName());
System.out.println("Type = " + installmentPlans[i].getType());
System.out.println("NumInstallments = " + installmentPlans[i].getNumInstallments());
System.out.println("InstallmentFrequency = " + installmentPlans[i].getInstallmentFrequency());
}

TAC tac = installmentPlans[i].getTac();
}

```

```
TACDetails [] tacDetailsList = tac.getTacDetailsList();
int tacCount = tac.getTacCount();

for (int j = 0; j < tacCount; j++)
{
TACDetails tacDetails = tacDetailsList[j];

System.out.println("\nText = " + tacDetails.getText() +"\n");
System.out.println("Url = " + tacDetails.getUrl());
System.out.println("Version = " + tacDetails.getVersion());
System.out.println("LanguageCode = " + tacDetails.getLanguageCode());
}

PromotionInfo promotionInfo = installmentPlans[i].getPromotionInfo();

System.out.println("\nPromotionCode = " + promotionInfo.getPromotionCode() +"\n");
System.out.println("PromotionId = " + promotionInfo.getPromotionId());

FirstInstallment firstInstallment = installmentPlans[i].getFirstInstallment();

System.out.println("\nUpfrontFee = " + firstInstallment.getUpfrontFee() +"\n");
System.out.println("InstallmentFee = " + firstInstallment.getInstallmentFee());
System.out.println("Amount = " + firstInstallment.getAmount());

LastInstallment lastInstallment = installmentPlans[i].getLastInstallment();

System.out.println("\nInstallmentFee = " + lastInstallment.getInstallmentFee());
System.out.println("Amount = " + lastInstallment.getAmount());

System.out.println("\nAPR = " + installmentPlans[i].getAPR());
System.out.println("\nTotalFees = " + installmentPlans[i].getTotalFees());
System.out.println("\nTotalPlanCost = " + installmentPlans[i].getTotalPlanCost());
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
```

## 9.6 Installment Info Object

When sending Purchase or Pre-Authorization transactions with Installments by Visa, the Installment Info object is included in the request. The Installment Info object uses information received in the response to the Installment Plan Lookup transaction.

For a full list of definitions of the request and response fields see B.3 Definition of Response Fields – Installments by Visa

## Installment Info object request fields

Variable Name	Type and Limits	
installment plan ID	<i>String</i> 36-character alphanumeric	installmentLookup.setPlanId ("VALUE");

Variable Name	Type and Limits	
	fixed length	
installment plan reference	<p><i>String</i></p> <p>10-character alphanumeric</p>	<pre>installmentLookup.setPlanIdRef("VALUE");</pre>
terms and conditions version	<p><i>String</i></p> <p>10-character alphanumeric</p> <p>variable length (1-10 characters)</p>	<pre>installmentLookup.setTacVersion("VALUE");</pre>

**WARNING:** Do not send the Installment Info object on any transaction that is not intended to offer Installments by Visa functionality; doing so may cause the transaction to fail.

## 10 e-Fraud Tools

- 10.1 Address Verification Service
- 10.2 Card Validation Digits (CVD)
- 10.3 Transaction Risk Management Tool



## 10.1 Address Verification Service

- 10.1.1 About Address Verification Service (AVS)
- 10.1.2 AVS Info Object
- 10.1.3 AVS Response Codes
- 10.1.4 AVS Sample Code

### 10.1.1 About Address Verification Service (AVS)

Address Verification Service (AVS) is an optional fraud-prevention tool offered by issuing banks whereby a cardholder's address is submitted as part of the transaction authorization. The AVS address is then compared to the address kept on file at the issuing bank. AVS checks whether the street number, street name and zip/postal code match. The issuing bank returns an AVS result code indicating whether the data was matched successfully. Regardless of the AVS result code returned, the credit card is authorized by the issuing bank.

The response that is received from AVS verification is intended to provide added security and fraud prevention, but the response itself does not affect the completion of a transaction. Upon receiving a response, the choice to proceed with a transaction is left entirely to the merchant. The responses is **not** a strict guideline of whether a transaction will be approved or declined.

The following transactions support AVS:

- Purchase (Basic and Mag Swipe)
- Pre-Authorization (Basic)
- Re-Authorization (Basic)
- ResAddCC (Vault)
- ResUpdateCC (Vault)

#### Things to Consider:

- AVS is supported by Visa, MasterCard, American Express, Discover and JCB.
- When testing AVS, you must **only** use the Visa test card numbers 4242424242424242 or 400555444444403, and the amounts described in the Simulator eFraud Response Codes document available at the Moneris developer portal (<https://developer.monteris.com>).
- Store ID “store5” is set up to support AVS testing.

## 10.1.2 AVS Info Object

### AVSInfo object definition

```
AvsInfo avsCheck = new AvsInfo();
```

### Transaction object set method

```
<transaction>.setAvsInfo(avsCheck);
```

Variable Name	Type and Limits	Set Method	Description
AVS street number	<p><i>String</i></p> <p>19-character alpha-numeric</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> this character limit is a combined total allowed for AVS street number and AVS street name       </div>	avscCheck.setAvsStreetNumber("212");	Cardholder street number
AVS street name	<p><i>String</i></p> <p>19-character alpha-numeric</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> this character limit is the combined total allowed for AVS street number and AVS street name       </div>	avscCheck.setAvsStreetName("Payton Street");	Cardholder street name
AVS zip/postal code	<p><i>String</i></p> <p>9-character alpha-numeric</p>	avscCheck.setAvsZipCode("M1M1M1");	Cardholder zip/- postal code

### 10.1.3 AVS Response Codes

Below is a full list of possible AVS response codes. These can be returned when you call the `receipt.-getAvsResultCode()` method .

Code	Visa	Mastercard/Discover	American Express/ JCB
A	AVS street address only (partial match)	Address matches, zip/ postal code does not	Billing address matches, zip/postal code does not
D	No longer applicable to Visa	N/A	Customer name incorrect; zip/postal code matches
E	N/A	N/A	Customer name incorrect, billing address and zip/postal code match
F	No longer applicable to Visa	N/A	Customer name incorrect; billing address matches
G	No longer applicable to Visa	Address information not verified for international transaction	N/A
K	N/A	N/A	Customer name matches
L	N/A	N/A	Customer name and zip/postal code match
M	No longer applicable to Visa	N/A	Customer name, billing address, and zip/postal code match
N	AVS non-match	Neither address nor zip/postal code matches	Billing address and zip-/postal code do not match
O	N/A	N/A	Customer name and billing address match

Code	Visa	Mastercard/Discover	American Express/ JCB
R	AVS indeterminate outcome (retry)	Retry; system unable to process	System unavailable; retry
S	No longer applicable to Visa	AVS currently not supported	AVS currently not supported
T	N/A	Nine-digit zip code matches; address does not match	N/A
U	AVS unable to verify	No data from issuer-/authorization system	Information is unavailable
W	No longer applicable to Visa	For U.S. addresses, nine-digit postal code matches, address does not  For addresses outside the U.S., postal code matches, address does not	Customer name, billing address, and zip/postal code are all correct matches
X	No longer applicable to Visa	For U.S. addresses, nine-digit postal code and address match  For addresses outside the U.S., postal code and address match	N/A
Y	AVS full match	Billing address and zip/postal code both match	Billing address and zip-/postal code both match
Z	AVS zip/postal code only (partial match)	For U.S. addresses, five-digit zip code matches, address does not match	Zip/postal code matches, billing address does not

#### 10.1.4 AVS Sample Code

This is a sample of Java code illustrating how AVS is implemented with a Purchase transaction. Purchase object information that is not relevant to AVS has been removed.

For more about Purchase transactions, see 2.1 Purchase.

### Sample Purchase with AVS information

```
AvsInfo avsCheck = new AvsInfo();
avsCheck.setAvsStreetNumber("212");
avsCheck.setAvsStreetName("Payton Street");
avsCheck.setAvsZipCode("M1M1M1");
avsCheck.setAvsEmail("test@host.com");
avsCheck.setAvsHostname("hostname");
avsCheck.setAvsBrowser("Mozilla");
avsCheck.setAvsShipToCountry("CAN");
avsCheck.setAvsShipMethod("G");
avsCheck.setAvsMerchProdSku("123456");
avsCheck.setAvsCustIp("192.168.0.1");
avsCheck.setAvsCustPhone("5556667777");

Purchase purchase = new Purchase();
purchase.setAvsInfo(avsCheck);
```

## 10.2 Card Validation Digits (CVD)

- 10.2.1 About Card Validation Digits (CVD)
- 10.2.3 CVD Information Object
- 10.2.4 CVD Result Codes
- 10.2.5 Sample Purchase with CVD Info Object

### 10.2.1 About Card Validation Digits (CVD)

The Card Validation Digits (CVD) value is an additional number printed on credit cards that is used as an additional check when verifying cardholder credentials during a transaction.

The response that is received from CVD verification is intended to provide added security and fraud prevention, but the response itself does not affect the completion of a transaction. Upon receiving a response, the choice whether to proceed with a transaction is left entirely to the merchant. The responses is **not** a strict guideline of which transaction will approve or decline.

The following transactions support CVD:

- Purchase (Basic, Vault and Mag Swipe)
- Pre-Authorization (Basic and Vault)
- Re-Authorization

#### Things to Consider:

- CVD is only supported by Visa, MasterCard, American Express, Discover, JCB and UnionPay.
- For UnionPay cards, the CVD response will not be returned; the issuer will approve or decline based on the CVD result.
- When testing CVD, you must **only** use the Visa test card numbers 4242424242424242 or 400555444444403, and the amounts described in the Simulator eFraud Response Codes document available at the Moneris developer portal (<https://developer.monteris.com>).
- Test store\_id “store5” is set up to support CVD testing.

### 10.2.2 Transactions Where CVD Is Required

The Card Validation Digits (CVD) object is required in transaction requests in the following scenarios:

- Initial transactions when storing cardholder credentials in Credential on File scenarios; subsequent follow-on transactions do not use CVD
- Any Purchase, Pre-Authorization or Card Verification where you are not storing cardholder credentials

### 10.2.3 CVD Information Object

**NOTE:** The CVD value must only be passed to the Moneris Gateway. Under **no** circumstances may it be stored for subsequent uses or displayed as part of the receipt information.

#### CvdInfo object definition

```
CvdInfo cvdCheck = new CvdInfo();

$cvdTemplate = array(
    'cvd_indicator' => $cvd_indicator,
    'cvd_value' => $cvd_value
);

$mpgCvdInfo = new mpgCvdInfo ($cvdTemplate);
```

#### Transaction object set method

```
transaction.setCvdInfo(cvdCheck);

$mpgTxn->setCvdInfo($mpgCvdInfo);
```

**Table 1 CVD Info Object – Required Fields**

Variable Name	Type and Limits	Set Method	Description
CVD indicator	<i>String</i> 1-character numeric	cvdCheck.setCvdIndicator("1");	<p>Indicates presence of CVD</p> <p>Possible values:</p> <p>0: CVD value is deliberately bypassed or is not provided by the merchant.</p> <p>1: CVD value is present.</p>

Variable Name	Type and Limits	Set Method	Description
			2: CVD value is on the card, but is illegible. 9: Cardholder states that the card has no CVD imprint.
CVD value	<i>String</i> 4-character numeric	<code>cvdCheck.setCvdValue("099");</code>	CVD value located on credit card <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> The CVD value must only be passed to the Moneris Gateway. Under <b>no</b> circumstances may it be stored for subsequent uses or displayed as part of the receipt information.         </div>

#### 10.2.4 CVD Result Codes

CVD verification is available for Visa, Mastercard, Discover, American Express, JCB and UnionPay transactions.

Code	Description
M	Match
N	No match
P	Not processed
S	CVD should be on the card, but Merchant has indicated that CVD is not present
U	Issuer is not a CVD participant
Y	Match for American Express/JCB only
D	Invalid security code for American Express or JCB only
Other	Invalid response code

## 10.2.5 Sample Purchase with CVD Info Object

This is a sample of Java code illustrating how CVD is implemented with a Purchase transaction. Purchase object information that is not relevant to CVD has been removed.

### Sample Purchase with CVD Information

```
CvdInfo cvdCheck = new CvdInfo();
cvdCheck.setCvdIndicator("1");
cvdCheck.setCvdValue("099");

Purchase purchase = new Purchase();
purchase.setCvdInfo(cvdCheck);
```

## 10.3 Transaction Risk Management Tool

- 10.3.1 About the Transaction Risk Management Tool
- 10.3.2 Introduction to Queries
- 10.3.3 Session Query
- 10.3.4 Attribute Query
- 10.3.6 Inserting the Profiling Tags Into Your Website
- 10.3.6 Inserting the Profiling Tags Into Your Website

The Transaction Risk Management Tool (TRMT) is available to **Canadian integrations** only.

### 10.3.1 About the Transaction Risk Management Tool

The Transaction Risk Management Tool provides additional information to assist in identifying fraudulent transactions. To maximize the benefits from the Transaction Risk Management Tool, it is highly recommended that you:

- Carefully consider the business logic and processes that you need to implement surrounding the handling of response information the Transaction Risk Management Tool provides.
- Implement the other fraud tools available through Moneris Gateway (such as AVS, CVD, Verified by Visa, MasterCard SecureCode and American Express SafeKey).

### 10.3.2 Introduction to Queries

There are two types of transactions associated with the Transaction Risk Management Tool (TRMT):

- Session Query (page 413)
- Attribute Query (page 420)

The Session Query and Attribute Query are used at the time of the transaction to obtain the risk assessment.

Moneris recommends that you use the Session Query as much as possible for obtaining your risk assessment because it uses the device fingerprint as well as other transaction information when providing the risk scores.

To use the Session Query, you must implement two components:

- Tags on your website to collect the device fingerprinting information
- Session Query transaction.

If you are not able to collect the necessary information for the Session Query (such as the device fingerprint), then use the Attribute Query.

### 10.3.3 Session Query

Once a device profiling session has been initiated upon a client device, the Session Query API is used at the time of the transaction or even to obtain a device identifier or ‘fingerprint’, attribute list and risk assessment for the client device.

#### Session Query transaction object definition

```
SessionQuery sq = new SessionQuery();
```

#### HttpsPostRequest object for Session Query transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(sq);
```

#### Session Query transaction values

**Table 10: Session Query transaction object mandatory values**

Value	Type	Limits	Set method
	Description		
Session ID	String	9-character decimal Permitted characters: [a-z], [A-Z], 0-9, _, -	sq.setSessionId(session_id);  Web server session identifier generated when device profiling was initiated.
Service type	String	9-character decimal	sq.setServiceType(service_type);  Which output fields are returned.  session -- returns IP and device related attributes.
Event type	String	payment	sq.setEventType(service_type);  Defines the type of transaction or event for reporting purposes.  payment - Purchasing of goods/services.

**Table 10: Session Query transaction object mandatory values (continued)**

Value	Type	Limits	Set method
	Description		
Credit card number (PAN)	String	20-character numeric No spaces or dashes	sq.setPan(pan);  Most credit card numbers today are 16 digits, but some 13-digit numbers are still accepted by some issuers. This field has been intentionally expanded to 20 digits in consideration for future expansion and potential support of private label card ranges.
Account address street 1	String	32-character alphanumeric	sq.setAccountAddressStreet1("3300 Bloor St W");  First portion of the street address component of the billing address.
Account Address street 2	String	32-character alphanumeric	sq.setAccountAddressStreet2("4th Flr West Tower");  Second portion of the street address component of the billing address.
Account address city	String	50-character alphanumeric	sq.setAccountAddressCity("Toronto");  The city component of the billing address.
Account address state/-province	String	64-character alphanumeric	sq.setAccountAddressState("Ontario");  The state/province component of the billing address.
Account address country	String	2-character alphanumeric	sq.setAccountAddressCountry("CA");  ISO2 country code of the billing addresses.
Account address ZIP/-postal code	String	8-character alphanumeric	sq.setAccountAddressZip("M8X2X2");  ZIP/postal code of the billing address.
Shipping address street 1	String	32-character alphanumeric	sq.setShippingAddressStreet1("3300 Bloor St W");  First portion of the street address component of the shipping address.
Shipping address street 2	String	32-character alphanumeric	sq.setShippingAddressStreet2("4th Flr West Tower");  Second portion of the street address component of the shipping address.

**Table 10: Session Query transaction object mandatory values (continued)**

Value	Type	Limits	Set method
	Description		
Shipping address city	String	50-character alphanumeric	<code>sq.setShippingAddressCity ("Toronto");</code>
		City component of the shipping address.	
Shipping address state/-province	String	64-character alphanumeric	<code>sq.setShippingAddressState ("Ontario");</code>
		The state/province component of the shipping address.	
Shipping address country	String	2-character alphanumeric	<code>sq.setShippingAddressCountry ("CA");</code>
		ISO2 country code of the account address country.	
Shipping address ZIP	String	8-character alphanumeric	<code>sq.setAccountAddressZip ("M8X2X2");</code>
		The ZIP/postal code component of the shipping address.	
Local attribute 1-5	String	255-character alphanumeric	<code>sq.setLocalAttrib1("a");</code>
		These five attributes can be used to pass custom attribute data. These are used if you wish to correlate some data with the returned device information.	
Transaction amount	String	255-character alphanumeric Must contain 2 decimal places	<code>sq.setTransactionAmount ("1.00");</code>
		The numeric currency amount.	
Transaction currency	String	10-character numeric	<code>sq.setTransactionCurrency ("CAN");</code>
		The currency type that the transaction was denominated in. If TransactionAmount is passed, the TransactionCurrency is required.	
		Values to be used are: <ul style="list-style-type: none"><li>• CAD – 124</li><li>• USD – 840</li></ul>	

**Table 11: Session Query transaction object optional values**

Value	Type	Limits	Set method
	Description		
Account login	String	255-character alphanumeric	sq.setAccountLogin("13195417-8CA0-46cd-960D-14C158E4DBB2");
The Account Login name.			
Password hash	String	40-character alphanumeric	sq.setPasswordHash ("489c830f10f7c601d30599a0deaf66e64d2aa50a");
The input must be a SHA-2 hash of the password in hexadecimal format. Used to check if it is on a watch list.			
Account number	String	255-character alphanumeric	sq.setAccountNumber ("3E17A905-AC8A-4c8d-A417-3DADA2A55220");
The account number for the account.			
Account name	String	255-character alphanumeric	sq.setAccountName ("4590FCC0-DF4A-44d9-A57B-AF9DE98B84DD");
Account name (or concatenation of first and last name of account holder).			
Account email	String	100-character alphanumeric	sq.setAccountEmail ("3CAE72EF-6B69-4a25-93FE-2674735E78E8@test.threatmetrix.com");
The email address entered into the form for this contact. Used to check if this is a high risk account email id.			
Account telephone	String	32-character alphanumeric	
Contact telephone number including country and city codes. All whitespace is removed.			
Must be in format: 0..9,<space>,(),[,] braces must be matched.			
Address street 1	String	32-character alphanumeric	
The first portion of the street address component of the account address.			
Address street 2	String	32-character alphanumeric	
The second portion of the street address component of the account address.			

**Table 11: Session Query transaction object optional values (continued)**

Value	Type	Limits	Set method
	Description		
Address city	String	50-character alphanumeric	
	The city component of the account address.		
Address state/-province	String	64-character alphanumeric	
	The state/province component of the account address		
Address country	String	2-character alphanumeric	
	The 2 character ISO2 country code of the account address country		
Address ZIP	String	8-character alphanumeric	
	The ZIP/postal code of the account address.		
Ship Address Street 1	String	32-character alphanumeric	
	The first portion of the street address component of the shipping address		
Ship Address Street 2	String	32-character alphanumeric	
	The second portion of the street address component of the shipping address		
Ship Address City	String	50-character alphanumeric	
	The city component of the shipping address		
Ship Address State/Province	String	64-character alphanumeric	
	The state/province component of the shipping address		
Ship Address Country	String	2-character alphanumeric	
	The 2 character ISO2 country code of the shipping address country		

**Table 11: Session Query transaction object optional values (continued)**

Value	Type	Limits	Set method
	Description		
Ship Address ZIP	String	8-character alphanumeric	
The ZIP/postal code of the shipping address			
CC Number Hash	String	255-character alphanumeric	
	This is a SHA-2 hash (in hexadecimal format) of the credit card number.		
Custom Attribute 1-8	String	255-character alphanumeric	
	These 8 attributes can be used to pass custom attribute data which can be used within the rules.		

#### **Sample Session Query - CA**

```

package Canada;
import java.util.Hashtable;
import java.util.Iterator;
import java.util.Map;
import JavaAPI.*;
public class TestCanadaRiskCheckSession
{
    public static void main(String[] args)
    {
        String store_id = "moneris";
        String api_token = "hurgle";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String session_id = "abc123";
        String service_type = "session";
        //String event_type = "LOGIN";
        String processing_country_code = "CA";
        boolean status_check = false;
        SessionQuery sq = new SessionQuery();
        sq.setOrderId(order_id);
        sq.setSessionId(session_id);
        sq.setServiceType(service_type);
        sq.setEventType(service_type);
        //sq.setPolicy("");
        //sq.setDeviceId("4EC40DE5-0770-4fa0-BE53-981C067C598D");
        sq.setAccountLogin("13195417-8CA0-46cd-960D-14C158E4DBB2");
        sq.setPasswordHash("489c830f10f7c601d30599a0deaf66e64d2aa50a");
        sq.setAccountNumber("3E17A905-AC8A-4c8d-A417-3DADA2A55220");
        sq.setAccountName("4590FCC0-DF4A-44d9-A57B-AF9DE98B84DD");
        sq.setAccountEmail("3CAE72EF-6B69-4a25-93FE-2674735E78E8@test.threatmetrix.com");

        //sq.setAccountTelephone("5556667777");
        sq.setPan("4242424242424242");
    }
}

```

**Sample Session Query - CA**

```

//sq.setAccountAddressStreet1("3300 Bloor St W");
//sq.setAccountAddressStreet2("4th Flr West Tower");
//sq.setAccountAddressCity("Toronto");
//sq.setAccountAddressState("Ontario");
//sq.setAccountAddressCountry("CA");
//sq.setAccountAddressZip("M8X2X2");
//sq.setShippingAddressStreet1("3300 Bloor St W");
//sq.setShippingAddressStreet2("4th Flr West Tower");
//sq.setShippingAddressCity("Toronto");
//sq.setShippingAddressState("Ontario");
//sq.setShippingAddressCountry("CA");
//sq.setShippingAddressZip("M8X2X2");
//sq.setLocalAttrib1("a");
//sq.setLocalAttrib2("b");
//sq.setLocalAttrib3("c");
//sq.setLocalAttrib4("d");
//sq.setLocalAttrib5("e");
//sq.setTransactionAmount("1.00");
//sq.setTransactionCurrency("840");
//set SessionAccountInfo
sq.setTransactionCurrency("CAN");
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(sq);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
String[] rules;
Hashtable<String, String> results = new Hashtable<String, String>();
Receipt receipt = mpgReq.getReceipt();
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
results = receipt.getRiskResult();
Iterator<Map.Entry<String, String>> response = results.entrySet().iterator();
while (response.hasNext())
{
Map.Entry<String, String> entry = response.next();
System.out.println(entry.getKey().toString() + " = " + entry.getValue().toString());
}
rules = receipt.getRiskRules();
for (int i = 0; i < rules.length; i++)
{
System.out.println("RuleName = " + rules[i]);
System.out.println("RuleCode = " + receipt.getRuleCode(rules[i]));
System.out.println("RuleMessageEn = " + receipt.getRuleMessageEn(rules[i]));
System.out.println("RuleMessageFr = " + receipt.getRuleMessageFr(rules[i]));
}
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

### 10.3.3.1 Session Query Transaction Flow




Figure 3: Session Query transaction flow

1. Cardholder logs onto the merchant website.
2. When the page has loaded in the cardholder's browser, special tags within the site allow information from the device to be gathered and sent to ThreatMetrix as the device fingerprint.  
The HTML tags should be placed where the cardholder is resident on the page for a couple of seconds to get the broadest data possible.
3. Customer submits a transaction.
4. Merchant's web application makes a Session Query transaction to the Moneris Gateway using the same session id that was included in the device fingerprint. This call must be made within 30 minutes of profiling (2).
5. Moneris Gateway submits the Session Query data to ThreatMetrix.
6. ThreatMetrix uses the Session Query data and the device fingerprint information to assess the transaction against the rules. A score is generated based on the rules.
7. The merchant uses the returned device information in its risk analysis to make a business decision. The merchant may wish to continue or cancel with the cardholder's payment transaction.

### 10.3.4 Attribute Query

The Attribute Query is used to obtain a risk assessment of transaction-related identifiers such as the email address and the card number. Unlike the Session Query, the Attribute Query does not require the device fingerprinting information to be provided.

#### AttributeQuery transaction object definition

```
AttributeQuery aq = new AttributeQuery();
```

#### HttpsPostRequest object for AttributeQuery transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();  
mpgReq.setTransaction(aq);
```

## Attribute Query transaction values

**Table 12: Attribute Query transaction object mandatory values**

Value	Type	Limits	Set method
	Description		
Service type	String	N/A	<code>aq.setServiceType(service_type);</code>
Which output fields are returned. session -- returns IP and device related attributes.			
Device ID	String	36-character alphanumeric	<code>aq.setDeviceId("");</code>
	Unique device identifier generated by a previous call to the ThreatMetrix session-query API.		
Credit card number	String	20-character numeric No spaces or dashes	<code>aq.setPan(pan);</code>
	Most credit card numbers today are 16 digits, but some 13-digit numbers are still accepted by some issuers. This field has been intentionally expanded to 20 digits in consideration for future expansion and potential support of private label card ranges.		
IP address	String	64-character alphanumeric	<code>aq.setIPAddress("192.168.0.1");</code>
	True IP address. Results will be returned as true_ip_geo, true_ip_score and so on.		
IP forwarded	String	64-character alphanumeric	<code>aq.setIPForwarded("192.168.1.0");</code>
	The IP address of the proxy. If the IPAddress is supplied, results will be returned as proxy_ip_geo and proxy_ip_score.  If the IP Address is not supplied, this IP address will be treated as the true IP address and results will be returned as true_ip_geo, true_ip_score and so on		
Account address street 1	String	32-character alphanumeric	<code>aq.setAccountAddressStreet1("3300 Bloor St W");</code>
	First portion of the street address component of the billing address.		
Account Address Street 2	String	32-character alphanumeric	<code>aq.setAccountAddressStreet2("4th Flr West Tower");</code>
	Second portion of the street address component of the billing address.		
Account address city	String	50-character alphanumeric	<code>aq.setAccountAddressCity("Toronto");</code>
	The city component of the billing address.		

**Table 12: Attribute Query transaction object mandatory values (continued)**

Value	Type	Limits	Set method
	Description		
Account address state/-province	String	64-character alphanumeric	aq.setAccountAddressState ("Ontario");
		The state component of the billing address.	
Account address country	String	2-character alphanumeric	aq.setAccountAddressCountry ("CA");
		ISO2 country code of the billing addresses.	
Account address zip/-postal code	String	8-character alphanumeric	aq.setAccountAddressZip ("M8X2X2");
		Zip/postal code of the billing address.	
Shipping address street 1	String	32-character alphanumeric	aq.setShippingAddressStreet1 ("3300 Bloor St W");
		Account address country	
Shipping Address Street 2	String	32-character alphanumeric	aq.setShippingAddressStreet2 ("4th Flr West Tower");
		Second portion of the street address component of the shipping address.	
Shipping Address City	String	50-character alphanumeric	aq.setShippingAddressCity ("Toronto");
		City component of the shipping address.	
Shipping Address State/Province	String	64-character alphanumeric	aq.setShippingAddressState ("Ontario");
		State/Province component of the shipping address.	
Shipping Address Country	String	2-character alphanumeric	aq.setShippingAddressCountry ("CA");
		ISO2 country code of the account address country.	
Shipping Address zip/-postal code	String	8-character alphanumeric	aq.setAccountAddressZip ("M8X2X2");
		The zip/postal code component of the shipping address.	

#### Sample Attribute Query

```

String store_id = "moneris";
String api_token = "hurgle";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();

```

### Sample Attribute Query

```

String service_type = "session";
String processing_country_code = "CA";
boolean status_check = false;

AttributeQuery aq = new AttributeQuery();
aq.setOrderId(order_id);
aq.setServiceType(service_type);
aq.setDeviceId("");
aq.setAccountLogin("13195417-8CA0-46cd-960D-14C158E4DBB2");
aq.setPasswordHash("489c830f10f7c601d30599a0deaf66e64d2aa50a");
aq.setAccountNumber("3E17A905-AC8A-4c8d-A417-3DADA2A55220");
aq.setAccountName("4590FCC0-DF4A-44d9-A57B-AF9DE98B84DD");
aq.setAccountEmail("3CAE72EF-6B69-4a25-93FE-2674735E78E8@test.threatmetrix.com");
//aq.setCCNumberHash("4242424242424242");
//aq.setIPAddress("192.168.0.1");
//aq.setIPForwarded("192.168.1.0");
aq.setAccountAddressStreet1("3300 Bloor St W");
aq.setAccountAddressStreet2("4th Flr West Tower");
aq.setAccountAddressCity("Toronto");
aq.setAccountAddressState("Ontario");
aq.setAccountAddressCountry("CA");
aq.setAccountAddressZip("M8X2X2");
aq.setShippingAddressStreet1("3300 Bloor St W");
aq.setShippingAddressStreet2("4th Flr West Tower");
aq.setShippingAddressCity("Toronto");
aq.setShippingAddressState("Ontario");
aq.setShippingAddressCountry("CA");
aq.setShippingAddressZip("M8X2X2");

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(aq);
mpgReq.send();

try
{
    String[] rules;
    Hashtable<String, String> results = new Hashtable<String, String>();
    Receipt receipt = mpgReq.getReceipt();
    System.out.println("ResponseCode = " + receipt.getResponseCode());
    System.out.println("Message = " + receipt.getMessage());
    System.out.println("TxnNumber = " + receipt.getTxnNumber());

    results = receipt.getRiskResult();
    Iterator<Map.Entry<String, String>> response = results.entrySet().iterator();
    while (response.hasNext())
    {
        Map.Entry<String, String> entry = response.next();
        System.out.println(entry.getKey().toString() + " = " + entry.getValue().toString());
    }
    rules = receipt.getRiskRules();
    for (int i = 0; i < rules.length; i++)
    {
        System.out.println("RuleName = " + rules[i]);
        System.out.println("RuleCode = " + receipt.getRuleCode(rules[i]));
        System.out.println("RuleMessageEn = " + receipt.getRuleMessageEn(rules[i]));
        System.out.println("RuleMessageFr = " + receipt.getRuleMessageFr(rules[i]));
    }
}
}

```

#### 10.3.4.1 Attribute Query Transaction Flow




Figure 4: Attribute query transaction flow

1. Cardholder logs onto merchant website and submits a transaction.
2. The merchant's web application makes an Attribute Query transaction that includes the session ID to the Moneris Gateway.
3. Moneris Gateway submits Attribute Query data to ThreatMetrix.
4. ThreatMetrix uses the Attribute Query data to assess the transaction against the rules. A score is generated based on the rules.
5. The merchant uses the returned device information in its risk analysis to make a business decision. The merchant may wish to continue or cancel with the cardholder's payment transaction.

#### 10.3.5 Handling Response Information

When reviewing the response information and determining how to handle the transaction, it is recommended that you (either manually or through automated logic on your site) use the following pieces of information:

- Risk score
- Rules triggered (such as Rule Codes, Rule Names, Rule Messages)
- Results obtained from Verified by Visa, MasterCard Secure Code, AVS, CVD and the financial transaction authorization
- Response codes for the Transaction Risk Management Transaction that are included by automated processes.

### 10.3.5.1 TRMT Response Fields

Table 13: Receipt object response values for TRMT

Value	Type	Limits	Get method
	Definition		
Response Code	String	3-character alpha-numeric	<code>receipt.getResponseCode();</code>
		001 – Success	
		981 – Data error	
		982 – Duplicate Order ID	
		983 – Invalid Transaction	
		984 – Previously asserted	
		985 – Invalid activity description	
		986 – Invalid impact description	
		987 – Invalid Confidence description	
		988 - Cannot find Previous	
Message	String	N/A	<code>receipt.getMessage();</code>
		Response message	
Event type	String	N/A	
		Type of transaction or event returned in the response.	
Org ID	String	N/A	
		ThreatMetrix-defined unique transaction identifier	
Policy	String	N/A	
		Policy used for the Session Query will be returned with the return request. If the Policy was not included, then the Policy name default is returned.	
Policy score	String	N/A	
		The sum of all the risks weights from triggered rules within the selected policy in the range [-100...100]	
Request duration	String	N/A	
		Length of time it takes for the transaction to be processed.	

**Table 13: Receipt object response values for TRMT (continued)**

Value	Type	Limits	Get method
	Definition		
Request ID	String	N/A	
	Unique number and will always be returned with the return request.		
Request result	String	N/A	<code>receipt.getRiskResult();</code>
	See 10.3.5.1 (page 425).		
Review status	String	N/A	
	The transaction status based on the assessments and risk scores.		
Risk rating	String	N/A	
	The rating based on the assessments and risk scores.		
Service type	String	N/A	
	The service type will be returned in the attribute query response.		
Session ID	String	N/A	
	Temporary identifier unique to the visitor will be returned in the return request.		
Summary risk score	String	N/A	
	Based on all of the returned values in the range [-100 ... 100]		
Transaction ID	String	N/A	
	This is the transaction identifier and will always be returned in the response when supplied as input.		
Unknown session	String	N/A	
	If present, the value is "yes". It indicates the session ID that was passed was not found.		

**Table 14: Response code descriptions**

Value	Definition
001	Success
981	Data error
982	Duplicate order ID
983	Invalid transaction
984	Previously asserted

Value	Definition
985	Invalid activity description
986	Invalid impact description
987	Invalid confidence description
988	Cannot find previous

**Table 15: Request result values and descriptions**

Value	Definition
fail_duplicate_entities_of_same_type	More than one entity of the same was specified, e.g. password_hash was specified twice.
fail_incomplete	ThreatMetrix was unable to process the request due to incomplete or incorrect input data
fail_invalid_account_number	The format of the supplied account number was invalid
fail_invalid_characters	Invalid characters submitted
fail_invalid_charset	The value of character set was invalid
fail_invalid_currency_code	The format of the currency_code was invalid
fail_invalid_currency_format	The format of the currency_format was invalid
fail_invalid_telephone_number	Format of the supplied telephone number was invalid
fail_access	ThreatMetrix was unable to process the request because of API verification failing
fail_internal_error	ThreatMetrix encountered an error while processing the request
fail_invalid_device_id	Format of the supplied device_id was invalid
fail_invalid_email_address	Format of the supplied email address was invalid
fail_invalid_fuzzy_device_id	The format of fuzzy_device_id was invalid
fail_invalid_ip_address_parameter	Format of a supplied ip_address parameter was invalid

Value	Definition
fail_invalid_parameter	The format of the parameter was invalid, or the value is out of boundary
fail_invalid_sha_hash	The format of a parameter specified as a sha hash was invalid, sha hash included sha1/2/3 hash
fail_invalid_submitter_id	The format of the submitter id was invalid or the value is out of boundary
fail_no_policy_configured	No policy was configured against the org_id
fail_not_enough_params	Not enough device attributes were collected during profiling to perform a fingerprint match
fail_parameter_overlength	The value of the parameter was overlength
fail_temporarily_unavailable	Request failed because the service is temporarily unavailable
fail_too_many_instances_of_same_parameter	Multiple values for some parameters which only allow one instance
fail_verification	API query limit reached
success	ThreatMetrix was able to process the request successfully

### 10.3.5.2 Understanding the Risk Score

For each Session Query or Attribute Query, a score with a value between -100 and +100 is returned based on the rules that were triggered for the transaction.

Table 16 defines the risk scores ranges.

**Table 16: Session Query and Attribute Query risk score definitions**

Risk score	Visa definition
-100 to -1	A lower score indicates a higher probability that the transaction is fraudulent.
0	Neutral transaction
1 to 100	A higher score indicates a lower probability that the transaction is fraudulent.

**Table 16: Session Query and Attribute Query risk score definitions (continued)**

Risk score	Visa definition
<b>Note:</b> All e-commerce transactions have some level of risk associated with them. Therefore, it is rare to see risk score in the high positive values.	

When evaluating the risk of a transaction, the risk score gives an initial indicator of the potential risk that the transaction is fraudulent. Because some of the rules that are evaluated on each transaction may not be relevant to your business scenario, review the rules that were triggered for the transaction before determining how to handle the transaction.

#### 10.3.5.3 Understanding the Rule Codes, Rule Names and Rule Messages

The rule codes, rule names and rule messages provide details about what rules were triggered during the assessment of the information provided in the Session or Attribute Query. Each rule code has a rule name and rule message. The rule name and rule message are typically similar. Table 17 provides additional information on each rule.

When evaluating the risk of a transaction, it is recommended that you review the rules that were triggered for the transaction and assess the relevance to your business. (That is, how does it relate to the typical buying habits of your customer base?)

If you are automating some or all of the decision-making processes related to handling the responses, you may want to use the rule codes. If you are documenting manual processes, you may want to refer to the more user-friendly rule name or rule message.

**Table 17: Rule names, numbers and messages**

Rule name	Rule number	Rule message
	Rule explanation	
White lists		
DeviceWhitelisted	WL001	Device White Listed  Device is on the white list. This indicates that the device has been flagged as always "ok".  <b>Note:</b> This rule is currently not in use.
IPWhitelisted	WL002	IP White Listed  IP address is on the white list. This indicates the device has been flagged as always "ok".  <b>Note:</b> This rule is currently not in use.

**Table 17: Rule names, numbers and messages (continued)**

Rule name	Rule number	Rule message
	Rule explanation	
EmailWhitelisted	WL003	Email White Listed
	Email address is on the white list. This indicates that the device has been flagged as always "ok".	
	<b>Note:</b> This rule is currently not in use.	
Event velocity		
2DevicePayment	EV003	2 Device Payment Velocity
	Multiple payments were detected from this device in the past 24 hours.	
2IPPaymentVelocity	EV006	2 IP Payment Velocity
	Multiple payments were detected from this IP within the past 24 hours.	
2ProxyPaymentVelocity	EV008	2 Proxy Payment Velocity
	The device has used 3 or more different proxies during a 24 hour period. This could be a risk or it could be someone using a legitimate corporate proxy.	
Email		
3EmailPerDeviceDay	EM001	3 Emails for the Device ID in 1 Day
	This device has presented 3 different email IDs within the past 24 hours.	
3EmailPerDeviceWeek	EM002	3 emails for the Device ID in 1 week
	This device has presented 3 different email IDs within the past week.	
3DevciePerEmailDay	EM003	3 Device Ids for email address in 1 day
	This email has been presented from three different devices in the past 24 hours.	
3DevciePerEmailWeek	EM004	3 Device Ids for email address in 1 week
	This email has been presented from three different devices in the past week.	
EmailDistanceTravelled	EM005	Email Distance Travelled
	This email address has been associated with different physical locations in a short period of time.	

**Table 17: Rule names, numbers and messages (continued)**

Rule name	Rule number	Rule message
	Rule explanation	
3EmailPerSmartIDHour	EM006	3 Emails for SmartID in 1 Hour  The SmartID for this device has been associated with 3 different email addresses in 1 hour.
GlobalEMailOverOneMonth	EM007	Global Email over 1 month  The e-mail address involved in the transaction over 30 days ago. This generally indicates that the transaction is less risky.  <b>Note:</b> This rule is set so that it does not impact the policy score or risk rating.
ComputerGeneratedEmailAddress	EM008	Computer Generated Email Address  This transaction used a computer-generated email address.
Account Number		
3AccountNumberPerDeviceDay	AN001	3 Account Numbers for device in 1 day  This device has presented 3 different user accounts within the past 24 hours.
3AccountNumberPerDeviceWeek	AN002	3 Account Numbers for device in 1 week  This device has presented 3 different user accounts within the past week.
3DevciePerAccountNumberDay	AN003	3 Device IDs for account number in 1 day  This user account been used from three different devices in the past 24 hours.
3DevciePerAccountNumberWeek	AN004	3 Device IDs for account number in 1 week  This card number has been used from three different devices in the past week.
AccountNumberDistanceTravelled	AN005	Account Number distance travelled  This card number has been used from a number of physically different locations in a short period of time.
Credit card/payments		

**Table 17: Rule names, numbers and messages (continued)**

Rule name	Rule number	Rule message
	Rule explanation	
3CreditCardPerDeviceDay	CP001	3 credit cards for device in 1 day This device has used three credit cards within 24 hours.
3CreditCardPerDeviceWeek	CP002	3 credit cards for device in 1 week This device has used three credit cards within 1 week.
	CP003	3 device ids for credit card in 1 day This credit card has been used on three different devices in 24 hours.
3DevicePerCreditCardWeek	CP004	3 device ids for credit card in 1 week This credit card has been used on three different devices in 1 week.
	CP005	Credit Card has travelled The credit card has been used at a number of physically different locations in a short period of time.
CreditCardShipAddressGeoMismatch	CP006	Credit Card and Ship Address do not match The credit card was issued in a region different from the Ship To Address information provided.
	CP007	Credit Card and Billing Address do not match The credit card was issued in a region different from the Billing Address information provided.
CreditCardDeviceGeoMismatch	CP008	Credit Card and device location do not match The device is located in a region different from where the card was issued.
	CP009	Credit Card issuing location and Shipping address do not match The credit card was issued in a region different from the Ship To Address information provided.
CreditCardBINShipAddressGeoMismatch	CP010	Credit Card issuing location and Billing address do not match The credit card was issued in a region different from the Billing Address information provided.

**Table 17: Rule names, numbers and messages (continued)**

Rule name	Rule number	Rule message
	Rule explanation	
CreditCardBINDeviceGeoMismatch	CP011	Credit Card issuing location and location of the device do not match
	The device is located in a region different from where the card was issued.	
TransactionValueDay	CP012	Daily Transaction Value Threshold
	The transaction value exceeds the daily threshold.	
TransactionValueWeek	CP013	Weekly Transaction Value Threshold
	The transaction value exceeds the weekly threshold.	
Proxy rules		
3ProxyPerDeviceDay	PX001	3 Proxy Ips in 1 day
	This device has used three different proxy servers in the past 24 hours.	
AnonymousProxy	PX002	Anonymous Proxy IP
	This device is using an anonymous proxy	
UnusualProxyAttributes	PX003	Unusual Proxy Attributes
	This transaction is coming from a source with unusual proxy attributes.	
AnonymousProxy	PX004	Anonymous Proxy
	This device is connecting through an anonymous proxy connection.	
HiddenProxy	PX005	Hidden Proxy
	This device is connecting via a hidden proxy server.	
OpenProxy	PX006	Open Proxy
	This transaction is coming from a source that is using an open proxy.	
TransparentProxy	PX007	Transparent Proxy
	This transaction is coming from a source that is using a transparent proxy.	
DeviceProxyGeoMismatch	PX008	Proxy and True GEO Match
	This device is connecting through a proxy server that didn't match the devices geo-location.	

**Table 17: Rule names, numbers and messages (continued)**

Rule name	Rule number	Rule message
	Rule explanation	
ProxyTrueISPMismatch	PX009	Proxy and True ISP Match
This device is connecting through a proxy server that doesn't match the true IP address of the device.		
ProxyTrueOrganizationMismatch	PX010	Proxy and True Org Match
The Proxy information and True ISP information for this source do not match.		
DeviceProxyRegionMismatch	PX011	Proxy and True Region Match
The proxy and device region location information do not match.		
ProxyNegativeReputation	PX012	Proxy IP Flagged Risky in Reputation Network
This device is connecting from a proxy server with a known negative reputation.		
SatelliteProxyISP	PX013	Satellite Proxy
This transaction is coming from a source that is using a satellite proxy.		
<b>GEO</b>		
DeviceCountriesNotAllowed	GE001	True GEO in Countries Not Allowed blacklist
This device is connecting from a high-risk geographic location.		
DeviceCountriesNotAllowed	GE002	True GEO in Countries Not Allowed (negative whitelist)
The device is from a region that is not on the whitelist of regions that are accepted.		
DeviceProxyGeoMismatch	GE003	True GEO different from Proxy GEO
The true geographical location of this device is different from the proxy geographical location.		
DeviceAccountGeoMismatch	GE004	Account Address different from True GEO
This device has presented an account billing address that doesn't match the devices geolocation.		

**Table 17: Rule names, numbers and messages (continued)**

Rule name	Rule number	Rule message
	Rule explanation	
DeviceShipGeoMismatch	GE005	Device and Ship Geo mismatch The location of the device and the shipping address do not match.
DeviceShipGeoMismatch	GE006	Device and Ship Geo mismatch The location of the device and the shipping address do not match.
Device		
SatelliteISP	DV001	Satellite ISP This transaction is from a source that is using a satellite ISP.
MidsessionChange	DV002	Session Changed Mid-session This device changed session details and identifiers in the middle of a session.
LanguageMismatch	DV003	Language Mismatch The language of the user does not match the primary language spoken in the location where the True IP is registered.
NoDeviceID	DV004	No Device ID No device ID was available for this transaction.
Dial-upConnection	DV005	Dial-up connection This device uses a less identifiable dial-up connection.
DeviceNegativeReputation	DV006	Device Blacklisted in Reputational Network This device has a known negative reputation as reported to the fraud network.
DeviceGlobalBlacklist	DV007	Device on the Global Black List This device has been flagged on the global blacklist of known problem devices.
DeviceCompromisedDay	DV008	Device compromised in last day This device has been reported as compromised in the last 24 hours.

---

**Table 17: Rule names, numbers and messages (continued)**

Rule name	Rule number	Rule message
	Rule explanation	
DeviceCompromisedHour	DV009	Device compromised in last hour
	This device has been reported as compromised in the last hour.	
FlashImagesCookiesDisabled	DV010	Flash Images Cookies Disabled
	Key browser functions/identifiers have been disabled on this device.	
FlashCookiesDisabled	DV011	Flash Cookies Disabled
	Key browser functions/identifiers have been disabled on this device.	
FlashDisabled	DV012	Flash Disabled
	Key browser functions/identifiers have been disabled on this device.	
ImagesDisabled	DV013	Images Disabled
	Key browser functions/identifiers have been disabled on this device.	
CookiesDisabled	DV014	Cookies Disabled
	Key browser functions/identifiers have been disabled on this device.	
DeviceDistanceTravelled	DV015	Device Distance Travelled
	The device has been used from multiple physical locations in a short period of time.	
PossibleCookieWiping	DV016	Cookie Wiping
	This device appears to be deleting cookies after each session.	
PossibleCookieCopying	DV017	Possible Cookie Copying
	This device appears to be copying cookies.	
PossibleVPNConnection	DV018	Possibly using a VPN Connection
	This device may be using a VPN connection	

#### 10.3.5.4 Examples of Risk Response

##### Session Query

###### Sample Risk Response - Session Query

```
<?xml version="1.0"?>
<response>
<receipt>
<ResponseCode>001</ResponseCode>
<Message>Success</Message>
<Result>
<session_id>abc123</session_id>
<unknown_session>yes</unknown_session>
<event_type>payment</event_type>
<service_type>session</service_type>
<policy_score>-25</policy_score>
<transaction_id>riskcheck42</transaction_id>
<org_id>11kue096</org_id>
<request_id>91C1879B-33D4-4D72-8FCB-B60A172B3CAC</request_id>
<risk_rating>medium</risk_rating>
<request_result>success</request_result>
<summary_risk_score>-25</summary_risk_score>
<Policy>default</policy>
<review_status>review</review_status>
</Result>
<Rule>
<RuleName>ComputerGeneratedEMail</RuleName>
<RuleCode>UN001</RuleCode>
<RuleMessageEn>Unknown Rule</RuleMessageEn>
<RuleMessageFr>Regle Inconnus</RuleMessageFr>
</Rule>
<Rule>
<RuleName>NoDeviceID</RuleName>
<RuleCode>DV004</RuleCode>
<RuleMessageEn>No Device ID</RuleMessageEn>
<RuleMessageFr>null</RuleMessageFr>
</Rule>
</receipt>
</response>
```

##### Attribute Query

###### Sample Risk Response - Attribute Query

```
<?xml version="1.0"?>
<response>
<receipt>
<ResponseCode>001</ResponseCode>
<Message = Success</Message>
<Result>
<org_id>11kue096</org_id>
<request_id>443D7FB5-CC5C-4917-A57E-27EAC824069C</request_id>
<service_type>session</service_type>
<risk_rating>medium</risk_rating>
<summary_risk_score>-25</summary_risk_score>
<request_result>success</request_result>
```

### Sample Risk Response - Attribute Query

```
<policy>default</policy>
<policy_score>-25</policy_score>
<transaction_id>riskcheck19</transaction_id>
<review_status>review</review_status>
</Result>
<Rule>
<RuleName>ComputerGeneratedEMail</RuleName>
<RuleCode>UN001</RuleCode>
<RuleMessageEn>Unknown Rule</RuleMessageEn>
<RuleMessageFr>Regle Inconnus</RuleMessageFr>
</Rule>
<Rule>
<RuleName>NoDeviceID</RuleName>
<RuleCode>DV004</RuleCode>
<RuleMessageEn>No Device ID</RuleMessageEn>
<RuleMessageFr>null</RuleMessageFr>
</Rule>
</receipt>
</response>
```

### 10.3.6 Inserting the Profiling Tags Into Your Website

Place the profiling tags on an HTML page served by your web application such that ThreatMetrix can collect device information from the customer's web browser. The tags must be placed on a page that a visitor would display in a browser window for 3-5 seconds (such as a page that requires a user to input data). After the device is profiled, a Session Query may be used to obtain the detail device information for risk assessment before submitting a financial payment transaction.

There are two profiling tags that require two variables. Those tags are `org_id` and `session_id`. `session_id` must match the session ID value that is to be passed in the Session Query transaction. The valid `org_id` values are:

**11kue096**

QA testing environment.

**lbhqgx47**

Production environment.

Below is an HTML sample of the profiling tags.

**NOTE:** Your site must replace `<my_session_id>` in the sample code with a unique alphanumeric value each time you fingerprint a new customer.

```
<p style="background:url(https://h.online-metrix.net/fp/clear.png?org_id=11kue096&session_id=<my_
session_id>&m=1)">
</p>


```

```
<script src="https://h.onlinemetrix.net/fp/check.js?org_id=11kue096&session_id=<my_session_id>" type="text/javascript">
</script>

<object type="application/x-shockwave-flash"
data="https://h.onlinemetrix.net/fp/fp.swf?org_id=11kue096&session_id=<my_session_id>"
width="1" height="1" id="obj_id">
<param name="movie"
value="https://h.onlinemetrix.net/fp/fp.swf?org_id=11kue096&session_id=<my_session_id>" />
<div></div>
</object>
```

## 10.4 Incorporating All Available Fraud Tools

- 10.4.1 Implementation Options for TRMT
- 10.4.2 Implementation Checklist
- 10.4.3 Making a Decision

To minimize fraudulent activity in online transactions, Moneris recommends that you implement all of the fraud tools available through the Moneris Gateway. These are explained below:

### **Address Verification Service (AVS)**

Vерifies the cardholder's billing address information.

### **Verified by Visa, MasterCard Secure Code and Amex SafeKey (VbV/MCSC/SafeKey)**

Authenticates the cardholder at the time of an online transaction.

### **Card Validation Digit (CVD)**

Validates that cardholder is in possession of a genuine credit card during the transaction.

Note that all responses that are returned from these verification methods are intended to provide added security and fraud prevention. The response itself does not affect the completion of a transaction. Upon receiving a response, the choice to proceed with a transaction is left entirely to the merchant.

### 10.4.1 Implementation Options for TRMT

#### **Option A**

Process a Transaction Risk Management Tool query and obtain the response. You can then decide whether to continue with the transaction, abort the transaction, or use additional eFraud features.

If you want to use additional eFraud features, perform one or both of the following to help make your decision about whether to continue with the transaction or abort it:

- Process a VbV/MCSC/SafeKey transaction and obtain the response. The merchant then makes the decision whether to continue with the transaction or to abort it.
- Process a financial transaction including AVS/CVD details and obtain the response. The merchant then makes a decision whether to continue with the transaction or to abort it.

#### **Option B**

1. Process a Transaction Risk Management Tool query and obtain the response.
2. Process a VbV/MCSC/SafeKey transaction and obtain the response.
3. Process a financial transaction including AVS/CVD details and obtain the response.
4. Merchant then makes a one-time decision based on the responses received from the eFraud tools.

## 10.4.2 Implementation Checklist

The following checklists provide high-level tasks that are required as part of your implementation of the Transaction Risk Management Tool. Because each organization has certain project requirements for implementing system and process changes, this list is only a guideline, and does not cover all aspects of your project.

### Download and review all of the applicable APIs and Integration Guides

Please review the sections outlined within this document that refers to the following feature

**Table 18: API documentation**

Document/API	Use the document if you are....
Transaction Risk Management Tool Integration Guide (Section #)	Implementing or updating your integration for the Transaction Risk Management Tool
Moneris MPI – Verified by Visa/MasterCard SecureCode/American Express SafeKey – Java API Integration Guide	Implementing or updating Verified by Visa, MasterCard SecureCode or American Express SafeKey
Basic transaction with VS and CVD (Section#)	Implementing or updating transaction processing, AVS or CVD

### Design your transaction flow and business processes

When designing your transaction flow, think about which scenarios you would like to have automated, and which scenarios you would like to have handled manually by your employees.

The “Understand Transaction Risk Management Transaction Flow” and Handling Response Information (page 424) sections can help you work through the design of your transaction and process flows.

Things to consider when designing your process flows:

- Processes for notifying people within your organization when there is scheduled maintenance for Moneris Gateway.
- Handling refunds, canceled orders and so on.
- Communicating with customers when you will not be shipping the goods because of suspected fraud, back-ordered goods and so on.

---

## Complete your development and testing

- The Moneris Gateway API - Integration Guide -Java provides the technical details required for the development and testing. Ensure that you follow the testing instructions and data provided.

### If you are an integrator

- Ensure that your solution meets the requirements for PCI-DSS/PA-DSS as applicable.
- Send an email to [eproducts@moneris.com](mailto:eproducts@moneris.com) with the subject line “Certification Request”.
- Develop material to set up your customers as quickly as possible with your solution and a Moneris account. Include information such as:
  - Steps they must take to enter their store ID or API token information into your solution.
  - Any optional services that you support via Moneris Gateway (such as TRMT, AVS, CVD, VBV/MCSC/SafeKey and so on) so that customers can request these features.

### 10.4.3 Making a Decision

Depending on your business policies and processes, the information obtained from the fraud tools (such as AVS, CVD, VBV/MCSC/SafeKey and TRMT) can help you make an informed decision about whether to accept a transaction or deny it because it is potentially fraudulent.

If you do not want to continue with a likely fraudulent transaction, you must inform the customer that you are not proceeding with their transaction.

If you are attempting to do further authentication by using the available fraud tools, but you have received an approval response instead, cancel the financial transaction by doing one of the following:

- If the original transaction is a Purchase, use a Purchase Correction or Refund transaction. You will need the original order ID and transaction number.
- If the original transaction is a Pre-Authorization, use a Completion transaction for \$0.00.

# 11 Apple Pay and Google Pay™ Integrations

- 11.1 About Apple Pay and Google Pay™ Integration
- 11.2 Apple Pay Transaction Process Overview
- 11.3 Google Pay™ Transaction Process Overview
- 11.4 About API Integration of Apple Pay and Google Pay™
- 11.5 Cvv Purchase – Apple Pay and Google Pay™
- 11.6 Cvv Pre-Authorization – Apple Pay & Google Pay™

## 11.1 About Apple Pay and Google Pay™ Integration

The Moneris Gateway enables merchants to process in-app transactions within applications running on iOS (Apple Pay) or Android (Google Pay™) mobile devices, and in-browser when using the Safari web browser (Apple Pay, using Apple devices only) or the Chrome web browser on (Google Pay™).

Moneris Solutions offers two integration methods for processing Apple Pay and Google Pay™ transactions. Merchants can choose to use one of two methods:


- Software Development Kit (SDK), or
- API method (where decryption of the transaction payload is handled by merchants)

While both methods provide the same basic payment features, there are differences in their implementations.

This guide only deals with the API method; for detailed information about the SDK method of integration, see the Moneris Developer Portal at <https://developer.moneris.com>.

## 11.2 Apple Pay Transaction Process Overview

For both API and SDK methods of mobile in-app integration, the merchant's iOS app uses Apple's PassKit Framework to request and receive encrypted payment details from Apple. When payment details are returned in their encrypted form, they can be decrypted and processed by the Moneris Gateway in one of two ways: SDK or API.



### Steps in the Apple Pay payment process

#### API

1. Merchant's mobile application or web page requests and receives the encrypted payload
2. Encrypted payload is sent to the merchant's server, where it is decrypted
3. Moneris Gateway receives the decrypted payload from the merchant's server, and processes the Cava Purchase – Apple Pay and Google Pay™ or "Cava Pre-Authorization – Apple Pay & Google Pay™" on page 451transaction
  - a. Please ensure the wallet indicator is properly populated with the correct value (APP for Apple Pay In-App or APW for Apple Pay on the Web)

#### SDK


1. Merchant's mobile application or web page requests and receives the encrypted payload
2. Encrypted payload is sent from the merchant's server to the Moneris Gateway, and the payload is decrypted and processed

This guide only deals with the API method; for detailed information about the SDK method of integration, see the Moneris Developer Portal at <https://developer.moneris.com>.

## 11.3 Google Pay™ Transaction Process Overview

For both API and SDK methods of integration, the merchant's app or website uses the Google Pay™ Framework to request and receive encrypted payment details from Google. When payment details are returned in their encrypted form, they can be decrypted and processed by the Moneris Gateway in one of two ways: SDK or API.

**NOTE:** In the API scenario where merchant's server is responsible for decrypting the payload, merchants must sign agreement with Google directly. Google can then provide you with the keys to decrypt the payload.



### Steps in the Google Pay™ payment process

#### API

1. Merchant's app or web page requests and receives the encrypted payload
2. Encrypted payload is sent to the merchant's server, where it is decrypted
3. Moneris Gateway receives the decrypted payload from the merchant's server, and processes the Cava Purchase – Apple Pay and Google Pay™ or "Cava Pre-Authorization – Apple Pay & Google Pay™" on page 451 transaction

- a. Please ensure the wallet indicator is properly populated with the correct value (GPP for Google Pay™ In-App or GPW for Google Pay™ Web)

## SDK

1. Merchant's mobile application or web page requests and receives the encrypted payload
2. Encrypted payload is sent from the merchant's server to the Moneris Gateway, and the payload is decrypted and processed

## 11.4 About API Integration of Apple Pay and Google Pay™

An API integration works to provide a communication link between your merchant server and Moneris' server. APIs are required to complete any transaction, and therefore the APIs for Apple Pay and Google Pay™ are also included in SDK integration.

If the merchant chooses to use the API-only integration method, the merchant must decrypt payload information themselves before sending the decrypted information to the Moneris Gateway to be processed. Because this process is complicated, Moneris recommends only businesses with expertise and a previously integrated payment processing system use the API integration method; all other merchants should use the Moneris Apple Pay or Google Pay™SDK as the integration method.

### 11.4.1 Transaction Types Used for Apple Pay and Google Pay™

In the Moneris Gateway API, there are two transaction types that allow you to process decrypted transaction payload information from Apple Pay and Google Pay™:

- 11.5 Cavv Purchase – Apple Pay and Google Pay™  
11.5 Cavv Purchase – Apple Pay and Google Pay™
- 11.6 Cavv Pre-Authorization – Apple Pay & Google Pay™

**NOTE:** INTERAC® e-Commerce functionality is currently available using the Cavv Purchase transaction type only.

Once you have processed the initial transaction using Cavv Purchase or Cavv Pre-Authorization, if required you can then process any of the following transactions:

- Refund
- Pre-Authorization Completion
- Purchase Correction

## 11.5 Cavv Purchase – Apple Pay and Google Pay™

The Cavv Purchase for Apple Pay and Google Pay™ transaction follows a 3-D Secure model but it does not require an MPI. Once the transaction payload has been decrypted, this transaction verifies funds on the customer's card, removes the funds and prepares them for deposit into the merchant's account.

To perform the 3-D Secure authentication, the Moneris MPI or any third-party MPI may be used.

In addition to 3-D Secure transactions, this transaction can also be used to process Apple Pay and Google Pay™ transactions. This transaction is applicable only if choosing to integrate directly to Apple Wallet or Google Wallet (if not using the Moneris Apple Pay or Google Pay™ SDKs).

Refer to Apple or Google developer portals for details on integrating directly to their wallets to retrieve the payload data.

**WARNING:** Moneris strongly discourages the use of frames as part of a 3-D Secure implementation, and cannot guarantee their reliability when processing transactions in the production environment.

### Cavv Purchase for Apple Pay & Google Pay™ transaction object definition

```
CavvPurchase cavvPurchase = new CavvPurchase();
```

### HttpsPostRequest object for Cavv Purchase for Apple Pay & Google Pay™ transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(cavvPurchase);
```

### Cavv Purchase for Apple Pay & Google Pay™ transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	cavvPurchase.setOrderId(order_id);

Variable Name	Type and Limits	Set Method
amount	<p><i>String</i></p> <p>10-character decimal</p> <p>Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point</p>	cavvPurchase.setAmount(amount);
	<b>EXAMPLE: 1234567.89</b>	
credit card number	<p><i>String</i></p> <p>max 20-character alpha-numeric</p>	cavvPurchase.setPan(pan);
expiry date	<p><i>String</i></p> <p>4-character alphanumeric</p> <p>YYMM</p>	cavvPurchase.setExpDate(expiry_date);
Cardholder Authentication Verification Value (CAVV)	<p><i>String</i></p> <p>50-character alphanumeric</p>	cavvPurchase.setCavv(cavv);
	<p><b>NOTE:</b> For Apple Pay and Google Pay™ Cavv Purchase and Cavv Pre-Authorization transactions, CAVV field contains the decrypted cryptogram. For more, see Appendix A Definition of Request Fields.</p>	
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	cavvPurchase.setCryptType(crypt);
	<p><b>NOTE:</b> For Apple Pay and Google Pay™ Cavv Purchase and Cavv Pre-Authorization transactions, the e-commerce indicator is a mandatory field containing the value received from the decrypted payload</p>	

Variable Name	Type and Limits	Set Method
<p>or a default value of 5. If you get a 2-character value (e.g., 05 or 07) from the payload, remove the initial 0 and just send us the 2nd character.</p> <p>For more, see Appendix A Definition of Request Fields.</p>		

Following fields are required for Apple Pay and Google Pay only:

Variable Name	Type and Limits	
network	<i>String</i> alphabetic	<code>cavvPurchase.setNetwork(network);</code>
data type	<i>String</i> 3-character alphanumeric	<code>cavvPurchase.setDataType(data_type);</code>

#### Cavv Purchase for Apple Pay & Google Pay™ transaction request fields – Optional

Variable Name	Type and Limits	Set Method
status check	<i>Boolean</i> true/false	<code>mpgReq.setStatusCheck(status_check);</code>
customer ID	<i>String</i> 50-character alphanumeric	<code>cavvPurchase.setCustId(cust_id);</code>
<b>NOTE:</b> Some special characters are not allowed: <>\$%=?^{}[]\		
dynamic descriptor	<i>String</i> 20-character alphanumeric total of 22 characters including your merchant name and separator	<code>cavvPurchase.setDynamicDescriptor(dynamic_descriptor);</code>

Variable Name	Type and Limits	Set Method
card match ID	<p><b>String</b></p> <p><b>NOTE:</b> Some special characters are not allowed: &lt; &gt; \$ % = ? ^ { } [ ] \</p> <p><b>NOTE:</b> Applies to Offlinx™ only; must be unique value for each transaction</p>	cavvPurchase.setCmId(transaction_id);
Customer Information	<p><b>Object</b></p> <p>N/A</p>	cavvPurchase.setCustInfo(customer);

### Sample Cavv Purchase for Apple Pay & Google Pay™

```

package Canada;
import JavaAPI.*;
public class TestCanadaCavvPurchase
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String cust_id = "CUS887H67";
        String amount = "10.42";
        String pan = "4740611374762707";
        String expdate = "1901"; //YYMM
        String cavv = "BwABApFSYyd4l2eQQFJjAAAAAAA=";
        String dynamic_descriptor = "123456";
        String processing_country_code = "CA";
        String crypt_type = "5";
        boolean status_check = false;
        boolean foreign_indicator= true; //New Foreign Indicator field

        CavvPurchase cavvPurchase = new CavvPurchase();
        cavvPurchase.setOrderId(order_id);
        cavvPurchase.setCustId(cust_id);
        cavvPurchase.setAmount(amount);
        cavvPurchase.setPan(pan);
        cavvPurchase.setExpdate(expdate);
        cavvPurchase.setCavv(cavv);
        cavvPurchase.setCryptType(crypt_type); //Mandatory for AMEX only
        cavvPurchase.setDynamicDescriptor(dynamic_descriptor);
        //cavvPurchase.setWalletIndicator("APP"); //set only for wallet transactions. e.g APPLE PAY
        //cavvPurchase.setNetwork("Interac"); //set only for Interac e-commerce
        //cavvPurchase.setData("3DSecure"); //set only for Interac e-commerce
        //cavvPurchase.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique max
        //50 alphanumeric characters transaction id generated by merchant

        cavvPurchase.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using 3rd
        Party 3-D Secure services.
    }
}

```

## 11.6 CAVV Pre-Authorization – Apple Pay & Google Pay™

The Cava Pre-Authorization for Apple Pay and Google Pay™ transaction follows a 3-D Secure model but it does not require an MPI. Once the transaction payload has been decrypted, this transaction verifies

funds on the customer's card, and holds the funds. To prepare the funds for deposit into the merchant's account please process a Pre-Authorization Completion transaction.

To perform the 3-D Secure authentication, the Moneris MPI or any third-party MPI may be used.

In addition to 3-D Secure transactions, this transaction can also be used to process Apple Pay and Google Pay™ transactions. This transaction is applicable only if choosing to integrate directly to Apple Wallet or Google Wallet (if not using the Moneris Apple Pay or Google Pay™ SDKs).

Refer to Apple or Google developer portals for details on integrating directly to their wallets to retrieve the payload data.

**NOTE:** INTERAC® e-Commerce functionality is currently available using the Cavv Purchase transaction type only.

**WARNING:** Moneris strongly discourages the use of frames as part of a 3-D Secure implementation, and cannot guarantee their reliability when processing transactions in the production environment.

### Cavv Pre-Authorization for Apple Pay & Google Pay™ transaction object definition

```
CavvPreAuth cavvPrauth = new CavvPreAuth();
```

### HttpsPostRequest object for Cavv Pre-Authorization for Apple Pay & Google Pay™ transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(cavvPrauth);
```

### Cavv Pre-Authorization for Apple Pay&Google Pay™ transaction request fields – Required

Variable Name	Type and Limits	Set Method
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	cavvPrauth.setOrderId(order_id);
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) +	cavvPrauth.setAmount(amount);

Variable Name	Type and Limits	Set Method
	decimal point (.) + 2 digits (cents) after the decimal point	
	<b>EXAMPLE:</b> 1234567.89	
credit card number	<i>String</i>  max 20-character alpha-numeric	<code>cavvPreauth.setPan(pan);</code>
Cardholder Authentication Verification Value (CAVV)	<i>String</i>  50-character alphanumeric	<code>cavvPreauth.setCavv(cavv);</code>
	<b>NOTE:</b> For Apple Pay and Google Pay™ Cavv Purchase and Cavv Pre-Authorization transactions, CAVV field contains the decrypted cryptogram. For more, see Appendix A Definition of Request Fields.	
expiry date	<i>String</i>  4-character alphanumeric  YYMM	<code>cavvPreauth.setExpDate(expiry_date);</code>
electronic commerce indicator	<i>String</i>  1-character alphanumeric	<code>cavvPreauth.setCryptType(crypt);</code>
	<b>NOTE:</b> For Apple Pay and Google Pay™ Cavv Purchase and Cavv Pre-Authorization transactions, the e-commerce indicator is a mandatory field containing the value received from the decrypted payload or a default value of 5. If you get a 2-character value (e.g., 05 or 07) from the payload, remove the initial 0 and just send us the 2nd character. For more, see Appendix A	

Variable Name	Type and Limits	Set Method
Definition of Request Fields.		

**Cavv Pre-Authorization for Apple Pay & Google Pay™ transaction request fields – Optional**

Variable Name	Type and Limits	Set Method
status check	<i>Boolean</i> true/false	<code>mpgReq.setStatusCheck(status_check);</code>
customer ID	<i>String</i>  50-character alphanumeric  <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"><b>NOTE:</b> Some special characters are not allowed: &lt;&gt;\$%=?^{}[]\</div>	<code>cavvPreauth.setCustId(cust_id);</code>
dynamic descriptor	<i>String</i>  20-character alphanumeric  total of 22 characters including your merchant name and separator  <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"><b>NOTE:</b> Some special characters are not allowed: &lt;&gt;\$%=?^{}[]\</div>	<code>cavvPreauth.setDynamicDescriptor(dynamic_descriptor);</code>
card match ID	<i>String</i>  50-character alphanumeric  <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"><b>NOTE:</b> Applies to Offlinx™ only; must be unique value for each transaction</div>	<code>cavvPreauth.setCmId(transaction_id);</code>
network	<i>String</i>  alphabetic  <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"><b>NOTE:</b> This request variable is mandatory for INTERAC® e-</div>	<code>cavvPurchase.setNetwork(network);</code>

Variable Name	Type and Limits	Set Method
<p>Commerce transactions conducted via Apple Pay or Google Pay™ only, and is not for use with credit card transactions.</p> <p><b>NOTE:</b> This request variable is mandatory for INTERAC® e-Commerce transactions conducted via Apple Pay or Google Pay™ only, and is not for use with credit card transactions.</p>	<p><i>String</i></p> <p>3-character alphanumeric</p>	<pre>cavvPurchase.setDataType(data_type);</pre>

### Sample Cavv Pre-Authorization for Apple Pay & Google Pay™

```

package Canada;
import JavaAPI.*;
public class TestCanadaCavvPreauth
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String cust_id = "CUS887H67";
        String amount = "10.42";
        String pan = "4242424242424242";
        String expdate = "1911"; //YYMM format
        String cavv = "AAABBjg0VhI0VniQEjRWAAAAAAA=";
        String dynamic_descriptor = "123456";
        String processing_country_code = "CA";
        String crypt_type = "5";
        String ds_trans_id = "12345";
        boolean status_check = false;
        boolean foreign_indicator= true; //New Foreign Indicator field

        CavvPreAuth cavvPreauth = new CavvPreAuth();
        cavvPreauth.setOrderId(order_id);
        cavvPreauth.setCustomerId(cust_id);
        cavvPreauth.setAmount(amount);
        cavvPreauth.setPan(pan);
        cavvPreauth.setExpdate(expdate);
        cavvPreauth.setCavv(cavv);
        cavvPreauth.setCryptType(crypt_type); //Mandatory for AMEX only
        cavvPreauth.setDynamicDescriptor(dynamic_descriptor);
        //cavvPreauth.setWalletIndicator("APP"); //set only for wallet transactions. e.g APPLE PAY
        //cavvPreauth.setCmId("8nAK8712sGaAkls56"); //set only for usage with Offlinx - Unique max 50
        alphanumeric characters transaction id generated by merchant
    }
}

```

```

cavvPreauth.setThreeDSVersion("2.2.0"); //Mandatory for financial transactions using 3rd
Party 3-D Secure services
cavvPreauth.setThreeDSServerTransId("e11d4985-8d25-40ed-99d6-c3803fe5e68f"); //Mandatory for
financial transactions using 3rd Party 3-D Secure services" - obtained from MpiCavvLookup or
MpiThreeDSAuthentication
//cavvPreauth.setDsTransId("12345");//Optional - to be used only if you are using 3rd party
3ds service

// TrId and TokenCryptogram are optional, refer documentation for more details.
cavvPreauth.setTrId("50189815682");
cavvPreauth.setTokenCryptogram("APmbM/411e0uAAH+s6xMAAADFA==");

//optional - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("U");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

cavvPreauth.setCofInfo(cof);
cavvPreauth.setForeignIndicator(foreign_indicator);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(cavvPreauth);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());
System.out.println("IssuerId = " + receipt.getIssuerId());
System.out.println("ThreeDSVersion = " + receipt.getThreeDSVersion());
System.out.println("SourcePanLast4 = " + receipt.getSourcePanLast4());
System.out.println("Advice Code= "+ receipt.getAdviceCode());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

## 12 Offlinx™

- What Is a Pixel Tag?
- Offlinx™ and API Transactions

### 12.1 What Is a Pixel Tag?

A pixel tag is a piece of code that goes on a web page and requests an image file (a tiny transparent image or pixel) when loaded, which, while not visible to the user, allows Offlinx™ to gather relevant information about the user.

The data collected by our pixel tag is:

- Anonymous (not personally identifiable) and compliant with privacy standards
- Secure — utilizes SSL communication to transmit the data securely
- Not shared with anyone

### 12.2 Offlinx™ and API Transactions

The Offlinx™ Card Match pixel tag feature can be implemented via the Unified API with the Card Match ID variable, which corresponds to the Transaction ID in Offlinx™. The Card Match ID must be a unique value for each transaction.

For more information about the Offlinx™ solution, consult the Offlinx™ Pixel Tag Setup Guide available from your account/service manager.

API transactions where this applies:

- Purchase
- Pre-Authorization
- Purchase with 3-D Secure – cavvPurchase
- Pre-Authorization with 3-D Secure – cavvPreauth

- Cvv Purchase – Apple Pay and Google Pay™
- Cvv Pre-Authorization – Apple Pay & Google Pay™

# 13 Convenience Fee

- 13.1 About Convenience Fee
- 13.3 Purchase with Convenience Fee
- 13.4 Purchase with Customer Info and Convenience Fee
- 13.5 Purchase with 3-D Secure and Convenience Fee

## 13.1 About Convenience Fee

The Convenience Fee program was designed to allow merchants to offer the convenience of an alternative payment channel to the cardholder at a charge. This applies only when providing a true "convenience" in the form of an alternative payment channel outside the merchant's customary face-to-face payment channels. The convenience fee will be a separate charge on top of what the consumer is paying for the goods and/or services they were given, and this charge will appear as a separate line item on the consumer's statement.

Convenience fee transactions do not support MCP or digital wallets.

**NOTE:** The Convenience Fee program is only offered to certain supported Merchant Category Codes (MCCs). Please speak to your account manager for further details.

## 13.2 Convenience Fee Information Object

Any transaction that supports Convenience Fee has an available set method for the Convenience Fee Information object.

The Convenience Fee Information object contains one request field, **convenience fee amount**.

### Convenience Fee Info object definition

```
ConvFeeInfo convFeeInfo = new ConvFeeInfo();
```

### Convenience Fee Info object set method

```
<transaction>.setConvenienceFee(convFeeInfo);
```

### Convenience Fee Information object request fields

Variable Name	Type and Limits	Description
Convenience Fee Information	<i>Object</i> N/A	Contains fields related to the Convenience Fee feature

Variable Name	Type and Limits	Description
convenience fee amount	<i>String</i> 9-character decimal	Dollar amount charged to the customer as a convenience fee

### 13.3 Purchase with Convenience Fee

Information below describes a Purchase transaction request that also includes the Convenience Fee Info object.

#### Purchase with Convenience Fee transaction object definition

```
Purchase purchase = new Purchase();
```

#### HttpsPostRequest object for Purchase with Convenience Fee transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(purchase);
```

#### Purchase with Convenience Fee transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
Convenience Fee Information	<i>Object</i> N/A	ConvFeeInfo convFeeInfo = new ConvFeeInfo(); purchase.setConvenienceFee(convFeeInfo);
order ID	<i>String</i> 50-character alphanumeric a-Z A-Z 0-9 _ - : . @ spaces	purchase.setOrderId(order_id);
amount	<i>String</i> 10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	purchase.setAmount(amount);

Variable Name	Type and Limits	Set Method
	<b>EXAMPLE:</b> 1234567.89	
credit card number	<i>String</i> max 20-character alpha-numeric YYMM	purchase.setPan(pan);
expiry date	<i>String</i> 4-character alphanumeric YYMM	purchase.setExpDate(expiry_date);
electronic commerce indicator	<i>String</i> 1-character alphanumeric	purchase.setCryptType(crypt);
	<b>NOTE:</b> In Credential on File transactions where the request field e-commerce indicator is also being sent, the acceptable values for e-commerce indicator are dependent on the value sent for payment indicator; see request field definitions for more information.	
convenience fee amount	<i>String</i> 9-character decimal	convFeeInfo.setConvenienceFee(convfee_amount);

### Purchase with Convenience Fee transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<i>String</i> 50-character alphanumeric	purchase.setCustId(cust_id);
	<b>NOTE:</b> Some special characters are not allowed: <> \$ % = ? ^ { } [ ] \	
dynamic descriptor	<i>String</i>	purchase.setDynamicDescriptor

Variable Name	Type and Limits	Set Method
	20-character alphanumeric total of 22 characters includ- ing your merchant name and separator	(dynamic_descriptor) ;
AVS Information	<p><b>Object</b></p> <p>N/A</p>	<pre>AvsInfo avsCheck = new AvsInfo(); purchase.setAvsInfo(avsCheck);</pre>
CVD Information	<p><b>Object</b></p> <p>N/A</p>	<pre>CvdInfo cvdCheck = new CvdInfo(); purchase.setCvdInfo(cvdCheck);</pre>

### Sample Purchase with Convenience Fee

```
package Canada;
import JavaAPI.*;
public class TestCanadaConvFeePurchase
{
public static void main(String args[])
{
String store_id = "monca00392";
String api_token = "qYdISUhHiOdfTr1CLNpN";
String processing_country_code = "CA";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String amount = "10.00";
String pan = "4242424242424242";
String expdate = "1911";
String crypt = "7";

ConvFeeInfo convFeeInfo = new ConvFeeInfo();
convFeeInfo.setConvenienceFee("1.00");

Purchase purchase = new Purchase();
purchase.setOrderId(order_id);
purchase.setAmount(amount);
purchase.setPan(pan);
purchase.setExpdate(expdate);
purchase.setCryptType(crypt);
purchase.setConvFeeInfo(convFeeInfo);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
```

### Sample Purchase with Convenience Fee

```

mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(purchase);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CfSuccess = " + receipt.getCfSuccess());
System.out.println("CfStatus = " + receipt.getCfStatus());
System.out.println("FeeAmount = " + receipt.getFeeAmount());
System.out.println("FeeRate = " + receipt.getFeeRate());
System.out.println("FeeType = " + receipt.getFeeType());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 13.4 Purchase with Customer Info and Convenience Fee

Information below is a Purchase transaction request that also includes the Convenience Fee Info and Customer Information objects.

### Purchase with Customer Info and Convenience Fee transaction object definition

```
Purchase purchase = new Purchase();
```

### HttpsPostRequest object for Purchase with Customer Info and Convenience Fee transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();

mpgReq.setTransaction(purchase);
```

### Purchase with Customer Info and Convenience Fee transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
Convenience Fee Information	<i>Object</i> N/A	<pre>ConvFeeInfo convFeeInfo = new ConvFeeInfo(); purchase.setConvenienceFee(convFeeInfo);</pre>
order ID	<i>String</i>  50-character alphanumeric  a-Z A-Z 0-9 _ - : . @ spaces	<pre>purchase.setOrderId(order_id);</pre>
amount	<i>String</i>  10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point  <b>EXAMPLE: 1234567.89</b>	<pre>purchase.setAmount(amount);</pre>
credit card number	<i>String</i>  max 20-character alphanumeric	<pre>purchase.setPan(pan);</pre>
expiry date	<i>String</i>  4-character alphanumeric  YYMM	<pre>purchase.setExpDate(expiry_date);</pre>
electronic commerce indicator	<i>String</i>  1-character alphanumeric	<pre>purchase.setCryptType(crypt);</pre>
convenience fee amount	<i>String</i>  9-character decimal	<pre>purchase convFeeInfo.setConvenienceFee(convfee_amount);</pre>

### Purchase with Customer Info and Convenience Fee transaction request fields – Optional

Variable Name	Type and Limits	Set Method
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt;\$%=?^{}[]\         </div>	<code>purchase.setCustId(cust_id);</code>
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt;\$%=?^{}[]\         </div>	<code>purchase.setDynamicDescriptor(dynamic_descriptor);</code>
Customer Information	<p><i>Object</i></p> <p>N/A</p>	<code>purchase.setCustInfo(customer);</code>
AVS Information	<p><i>Object</i></p> <p>N/A</p>	<code>purchase.setAvsInfo(avscCheck);</code>
CVD Information	<p><i>Object</i></p> <p>N/A</p> <div style="border: 1px solid #ccc; padding: 10px; margin-top: 10px;"> <b>NOTE:</b> When storing credentials on the initial transaction, the CVD object must be sent; for subsequent transactions using stored credentials, CVD can be sent with cardholder-initiated transactions only—merchants must not store CVD information.         </div>	<code>purchase.setCvdInfo(cvdCheck);</code>

### Sample Purchase with Customer Info and Convenience Fee

```

package Canada;

import java.util.*;
import JavaAPI.*;
public class TestCanadaConvFeePurchaseCustInfo
{
public static void main(String[] args)
{
String store_id = "monca00392";
String api_token = "qYdISUhHiOdfTr1CLNpN";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String amount = "10.00";
String pan = "4242424242424242";
String expdate = "1901"; //YYMM format
String crypt = "7";
String processing_country_code = "CA";
boolean status_check = false;
***** Billing/Shipping Variables *****/
String first_name = "Bob";
String last_name = "Smith";
String company_name = "ProLine Inc.";
String address = "623 Bears Ave";
String city = "Chicago";
String province = "Illinois";
String postal_code = "M1M2M1";
String country = "Canada";
String phone = "777-999-7777";
String fax = "777-999-7778";
String tax1 = "10.00";
String tax2 = "5.78";
String tax3 = "4.56";
String shipping_cost = "10.00";
***** Order Line Item Variables *****/
String[] item_description = new String[] { "Chicago Bears Helmet", "Soldier Field Poster" };
String[] item_quantity = new String[] { "1", "1" };
String[] item_product_code = new String[] { "CB3450", "SF998S" };
String[] item_extended_amount = new String[] { "150.00", "19.79" };
***** Customer Information Option 1 ****/
/*
 **** Customer Information Object ****/
CustInfo customer = new CustInfo();
***** Set Customer Billing Information ****/
customer.setBilling(first_name, last_name, company_name, address, city,
province, postal_code, country, phone, fax, tax1, tax2,
tax3, shipping_cost);
***** Set Customer Shipping Information ****/
customer.setShipping(first_name, last_name, company_name, address, city,
province, postal_code, country, phone, fax, tax1, tax2,
tax3, shipping_cost);
***** Order Line Items ****/
customer.setItem(item_description[0], item_quantity[0],
item_product_code[0], item_extended_amount[0]);
customer.setItem(item_description[1], item_quantity[1],
item_product_code[1], item_extended_amount[1]);
***** */

```

### Sample Purchase with Customer Info and Convenience Fee

```

/*
 * Customer Information Option 2 */
*/
***** ***** ***** ***** ***** ***** ***** *****
***** ***** ***** Customer Information Object ***** *****
CustInfo customer2 = new CustInfo();
***** ***** ***** Billing Hashtable *****
Hashtable<String, String> b = new Hashtable<String, String>(); //billing hashtable
b.put("first_name", first_name);
b.put("last_name", last_name);
b.put("company_name", company_name);
b.put("address", address);
b.put("city", city);
b.put("province", province);
b.put("postal_code", postal_code);
b.put("country", country);
b.put("phone", phone);
b.put("fax", fax);
b.put("tax1", tax1); //federal tax
b.put("tax2", tax2); //prov tax
b.put("tax3", tax3); //luxury tax
b.put("shipping_cost", shipping_cost); //shipping cost
customer2.setBilling(b);
***** ***** ***** Shipping Hashtable *****
Hashtable<String, String> s = new Hashtable<String, String>(); //shipping hashtable
s.put("first_name", first_name);
s.put("last_name", last_name);
s.put("company_name", company_name);
s.put("address", address);
s.put("city", city);
s.put("province", province);
s.put("postal_code", postal_code);
s.put("country", country);
s.put("phone", phone);
s.put("fax", fax);
s.put("tax1", tax1); //federal tax
s.put("tax2", tax2); //prov tax
s.put("tax3", tax3); //luxury tax
s.put("shipping_cost", shipping_cost); //shipping cost
customer2.setShipping(s);
***** ***** ***** Order Line Item1 Hashtable *****
Hashtable<String, String> i1 = new Hashtable<String, String>(); //item hashtable #1
i1.put("name", item_description[0]);
i1.put("quantity", item_quantity[0]);
i1.put("product_code", item_product_code[0]);
i1.put("extended_amount", item_extended_amount[0]);
customer2.setItem(i1);
***** ***** ***** Order Line Item2 Hashtable *****
Hashtable<String, String> i2 = new Hashtable<String, String>(); //item hashtable #2
i2.put("name", "item2's name");
i2.put("quantity", "7");
i2.put("product_code", "item2's product code");
i2.put("extended_amount", "5.01");
customer2.setItem(i2);
***** ***** ***** Miscellaneous Customer Information Methods *****
customer.setEmail("nick@widget.com");
customer.setInstructions("Make it fast!");

***** ***** ***** Convenience Fee *****
ConvFeeInfo convFeeInfo = new ConvFeeInfo();

```

### Sample Purchase with Customer Info and Convenience Fee

```

convFeeInfo.setConvenienceFee("1.00");
/********************* Transactional Request Object *****/
Purchase purchase = new Purchase();
purchase.setOrderId(order_id);
purchase.setAmount(amount);
purchase.setPan(pan);
purchase.setExpdate(expdate);
purchase.setCryptType(crypt);
purchase.setCustInfo(customer);
purchase.setConvFeeInfo(convFeeInfo);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(false); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(purchase);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());

System.out.println("CfSuccess = " + receipt.getCfSuccess());
System.out.println("CfStatus = " + receipt.getCfStatus());
System.out.println("FeeAmount = " + receipt.getFeeAmount());
System.out.println("FeeRate = " + receipt.getFeeRate());
System.out.println("FeeType = " + receipt.getFeeType());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}
}

```

## 13.5 Purchase with 3-D Secure and Convenience Fee

Information below describes a Purchase with 3-D Secure transaction request that also includes the Convenience Fee Info object.

### Convenience Fee Purchase with 3-D Secure transaction object definition

```
CavvPurchase cavvPurchase = new CavvPurchase();
```

### HttpsPostRequest object for Convenience Fee Purchase w/ 3-D Secure transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
```

### Convenience Fee Purchase with 3-D Secure transaction request fields – Required

For a full description of mandatory and optional values, see Appendix A Definition of Request Fields.

Variable Name	Type and Limits	Set Method
Convenience Fee Information	<i>Object</i> N/A	cavvPurchase.setConvenienceFee(convFeeInfo);
order ID	<i>String</i>  50-character alphanumeric  a-Z A-Z 0-9 _ - : . @ spaces	cavvPurchase.setOrderId(order_id);
amount	<i>String</i>  10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point  <b>EXAMPLE: 1234567.89</b>	cavvPurchase.setAmount(amount);
credit card number	<i>String</i>  max 20-character alphanumeric	cavvPurchase.setPan(pan);
expiry date	<i>String</i>  4-character alphanumeric  YYMM	cavvPurchase.setExpDate(expiry_date);
electronic commerce indic-	<i>String</i>	cavvPurchase.setCryptType(crypt);

Variable Name	Type and Limits	Set Method
ator	1-character alphanumeric	
Cardholder Authentication Verification Value (CAVV)	<p><i>String</i></p> <p>50-character alpha- numeric</p>	cavvPurchase.setCavv(cavv);
convenience fee amount	<p><i>String</i></p> <p>9-character decimal</p>	convFeeInfo.setConvenienceFee(convfee_amount);

### Purchase with 3-D Secure and Convenience Fee transaction request fields – Optional

Variable Name	Type and Limits	Set Method
status check	<p><i>Boolean</i></p> <p>true/false</p>	mpgReq.setStatusCheck(status_check);
customer ID	<p><i>String</i></p> <p>50-character alphanumeric</p>	cavvPurchase.setCustId(cust_id);
<div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt; \$ % = ? ^ { } [ ] \          </div>		
dynamic descriptor	<p><i>String</i></p> <p>20-character alphanumeric</p> <p>total of 22 characters including your merchant name and separator</p>	cavvPurchase.setDynamicDescriptor(dynamic_descriptor);
<div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt; \$ % = ? ^ { } [ ] \          </div>		
electronic commerce indicator	<p><i>String</i></p> <p>1-character alphanumeric</p>	cavvPurchase.setCryptType(crypt);
Customer Information	<i>Object</i>	cavvPurchase.setCustInfo

Variable Name	Type and Limits	Set Method
	N/A	(customer);
AVS Information	<i>Object</i> N/A	cavvPurchase.setAvsInfo(avsCheck);
CVD Information	<i>Object</i> N/A	cavvPurchase.setCvdInfo(cvdCheck);

#### Sample Purchase with 3-D Secure and Convenience Fee

```

package Canada;
import JavaAPI.*;
public class TestCanadaConvFeeCavvPurchase
{
    public static void main(String[] args)
    {
        String store_id = "monca00392";
        String api_token = "qYdISUhHiOdfTr1CLNpN";
        java.util.Date createDate = new java.util.Date();
        String order_id = "Test"+createDate.getTime();
        String cust_id = "CUS887H67";
        String amount = "10.42";
        String pan = "4242424242424242";
        String expdate = "1901"; //YYMM
        String cavv = "AAABBJg0VhI0VniQEjRWAAAAAA=";
        String dynamic_descriptor = "123456";
        String processing_country_code = "CA";
        String crypt_type = "5";
        boolean status_check = false;
        //***** Convenience Fee *****/
        ConvFeeInfo convFeeInfo = new ConvFeeInfo();
        convFeeInfo.setConvenienceFee("1.00");

        CavvPurchase cavvPurchase = new CavvPurchase();
        cavvPurchase.setOrderId(order_id);
        cavvPurchase.setCustomerId(cust_id);
        cavvPurchase.setAmount(amount);
        cavvPurchase.setPan(pan);
        cavvPurchase.setExpdate(expdate);
    }
}

```

**Sample Purchase with 3-D Secure and Convenience Fee**

```
cavvPurchase.setCavv(cavv);
cavvPurchase.setCryptType(crypt_type); //Mandatory for AMEX only
cavvPurchase.setDynamicDescriptor(dynamic_descriptor);
cavvPurchase.setConvFeeInfo(convFeeInfo);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(cavvPurchase);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("CavvResultCode = " + receipt.getCavvResultCode());

System.out.println("CfSuccess = " + receipt.getCfSuccess());
System.out.println("CfStatus = " + receipt.getCfStatus());
System.out.println("FeeAmount = " + receipt.getFeeAmount());
System.out.println("FeeRate = " + receipt.getFeeRate());
System.out.println("FeeType = " + receipt.getFeeType());
}
catch (Exception e)
{
e.printStackTrace();
}
}
```

# 14 Recurring Billing

- 14.1 About Recurring Billing
- 14.2 Purchase with Recurring Billing
- 14.3 Recurring Billing Update
- 14.4 Recurring Billing Response Fields and Codes
- 14.5 Credential on File and Recurring Billing

## 14.1 About Recurring Billing

Recurring Billing allows you to set up payments whereby Moneris automatically processes the transactions and bills customers on your behalf based on the billing cycle information you provide.

Recurring Billing series are created by sending the Recurring Billing object in these transactions:

- Purchase
- Purchase with Vault
- Purchase with 3-D Secure (cavvPurchase)

You can modify a Recurring Billing series after it has been created by sending the Recurring Billing Update administrative transaction.

**NOTE:** Alternatively, if you prefer to manage recurring series on your own merchant system, you can send the periodic payments as basic Purchase transactions with the e-commerce indicator (`crypt_type`) value = 2 and with the Credential on File info object included.

## 14.2 Purchase with Recurring Billing

### Recurring Billing Info Object Definition

```
Recur recurring_cycle = new Recur(recur_unit, start_now, start_date, num_
recurs, period, recur_amount);
```

### Transaction object set method

```
<transaction>.setRecur(recurring_cycle);
```

## Recurring Billing Info Object Request Fields

Variable Name	Type and Limits	Description
number of recurs	<i>String</i> numeric 1-999	The number of times that the transaction must recur
period	<i>String</i> numeric 1-999	Number of recur unit intervals that must pass between recurring billings
start date	<i>String</i> YYYYMMDD format	Date of the first future recurring billing transaction; this must be a date in the future  If an additional charge will be made immediately, the start now variable must be set to true
start now	<i>String</i> true/false	Set to true if a charge will be made against the card immediately; otherwise set to false  When set to false, use Card Verification prior to sending the Purchase with Recurring Billing and Credential on File objects
recurring amount	<i>String</i> 10-character decimal, minimum three digits  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	Dollar amount of the recurring transaction  This amount will be billed on the start date, and then billed repeatedly based on the interval defined by period and recur unit

**NOTE:** Amount to be billed immediately can differ from the subsequent recurring amounts

Variable Name	Type and Limits	Description
<b>EXAMPLE: 1234567.89</b>		
recur unit	<i>String</i> day, week, month or eom	Unit to be used as a basis for the interval Works in conjunction with the period variable to define the billing frequency

### Sample Purchase with Recurring Billing

```

package Canada;

import java.util.*;
import JavaAPI.*;
public class TestCanadaPurchaseRecur
{
public static void main(String[] args)
{
String store_id = "store5";
String api_token = "yesguy";
java.util.Date createDate = new java.util.Date();
String order_id = "Test"+createDate.getTime();
String amount = "10.00";
String pan = "4242424242424242";
String expiry_date = "1901"; //YYMM format
String crypt = "7";
***** Recur Variables *****/
String recur_unit = "month"; //eom = end of month
String start_now = "true";
String start_date = "2018/04/01";
String num_recurr = "12";
String period = "1";
String recur_amount = "30.00";
String processing_country_code = "CA";
boolean status_check = false;
***** Recur Object Option1 *****/
Recur recurring_cycle = new Recur(recur_unit, start_now, start_date,
num_recurr, period, recur_amount);
***** Recur Object Option2 *****/
Hashtable<String, String> recur_hash = new Hashtable<String, String>();
recur_hash.put("recur_unit", recur_unit);
recur_hash.put("start_now", start_now);
recur_hash.put("start_date", start_date);
recur_hash.put("num_recurr", num_recurr);
recur_hash.put("period", period);
recur_hash.put("recur_amount", recur_amount);
***** Transactional Object *****/
Purchase purchase = new Purchase();
purchase.setOrderId(order_id);
purchase.setAmount(amount);
purchase.setPan(pan);
purchase.setExdate(expiry_date);
purchase.setCryptType(crypt);
***** Set Recur *****/

```

### Sample Purchase with Recurring Billing

```

purchase.setRecur(recurring_cycle);
//Mandatory on Recurs - Credential on File details
CofInfo cof = new CofInfo();
cof.setPaymentIndicator("R");
cof.setPaymentInformation("2");
cof.setIssuerId("139X3130ASCXAS9");

purchase.setCofInfo(cof);

***** Https Post Request *****
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setProcCountryCode(processing_country_code);
mpgReq.setTestMode(true); //false for production transactions
mpgReq.setstoreId(store_id);
mpgReq.setApiToken(api_token);
mpgReq.setTransaction(purchase);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
***** Receipt *****
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("CardType = " + receipt.getCardType());
System.out.println("TransAmount = " + receipt.getTransAmount());
System.out.println("TxnNumber = " + receipt.getTxnNumber());
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("TransType = " + receipt.getTransType());
System.out.println("ReferenceNum = " + receipt.getReferenceNum());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("ISO = " + receipt.getISO());
System.out.println("BankTotals = " + receipt.getBankTotals());
System.out.println("Message = " + receipt.getMessage());
System.out.println("AuthCode = " + receipt.getAuthCode());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("Ticket = " + receipt.getTicket());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("Recur Success = " + receipt.getRecurSuccess());
System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit());
System.out.println("IssuerId = " + receipt.getIssuerId());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 14.3 Recurring Billing Update

After you have set up a Recurring Billing transaction series, you can change some of the details of the series as long as it has not yet completed the preset recurring duration (i.e., it hasn't terminated yet).

Before sending a Recurring Billing Update transaction that updates the credit card number, you must send a Card Verification request. This requirement does not apply if you are only updating the schedule or amount.

**Things to Consider:**

- When completing the update recurring billing portion please keep in mind that the recur bill dates cannot be changed to have an end date greater than 10 years from today and cannot be changed to have an end date end today or earlier.

### Recurring Billing Update transaction object definition

```
RecurUpdate recurUpdate = new RecurUpdate();
```

### HttpsPostRequest object for Recurring Billing Update transaction

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(recurUpdate);
```

### Recurring Billing Update transaction values

**Table 1 Recurring Billing Update – Basic Required Fields**

Variable Name	Type and Limits	Set Method
Order ID	<i>String</i>	recurUpdate.setOrderId(order_id);
order_id	50-character alphanumeric	

**Table 2 Recurring Billing Update – Basic Optional Fields**

Variable Name	Type and Limits	Set Method
Customer ID	<i>String</i>	recurUpdate.setCustId(cust_id);
cust_id	50-character alphanumeric	
Credit card number	<i>String</i>	recurUpdate.setPan(pan);
pan	20-character alphanumeric	
Expiry date	<i>String</i>	recurUpdate.setExpdate(expiry_date);

Variable Name	Type and Limits	Set Method
expiry_date	YYMM	

**Table 3 Recurring Billing Update – Recurring Billing Required Fields**

Variable Name	Type and Limits	Set Method	Description
Recurring amount recur_amount	<i>String</i>  numeric, 1-999	<code>recurUpdate.setRecurAmount(recur_amount);</code>	Changes the amount that is billed recurrently  The change takes effect on the next charge
Add number of recurs add_num	<i>String</i>  numeric, 1-999	<code>recurUpdate.setAddNumRecurs(add_num);</code>	<b>Adds</b> to the given number of recurring transactions to the current (remaining) number  This can be used if a customer decides to extend a membership or subscription  Cannot be used to decrease the current number of recurring transactions; use Change number of recurs instead
Change number of recurs total_num	<i>String</i>  numeric, 1-999	<code>recurUpdate.setTotalNumRecurs(total_num);</code>	<b>Replaces</b> the current (remaining) number of recurring transactions
Hold recurring billing hold	<i>String</i>  true/false	<code>recurUpdate.setHold(hold);</code>	Temporarily pauses recurring billing  While a transaction is on hold, it is not billed for the recurring amount; however, the number of remaining recurs continues to be decremented during that time

Variable Name	Type and Limits	Set Method	Description
Terminate recurring transaction terminate	<i>String</i> true/false	recurUpdate.setTerminate(terminate);	Terminates recurring billing  <b>NOTE:</b> After it has been terminated, a recurring transaction <b>cannot</b> be reactivated; a new purchase transaction with recurring billing must be submitted.

### Sample Recurring Billing Update

```

package Canada;
import JavaAPI.*;
public class TestCanadaRecurUpdate
{
    public static void main(String[] args)
    {
        String store_id = "store5";
        String api_token = "yesguy";
        String order_id = "Test155409282";
        String cust_id = "antonio";
        String recur_amount = "1.50";
        String pan = "4242424242424242";
        String expiry_date = "1902";
        //String add_num = "";
        //String total_num = "";
        //String hold = "";
        //String terminate = "";
        String processing_country_code = "CA";
        boolean status_check = false;
        //Credential on File details
        CofInfo cof = new CofInfo();
        cof.setIssuerId("139X3130ASCXAS9");

        RecurUpdate recurUpdate = new RecurUpdate();
        recurUpdate.setOrderId(order_id);
        recurUpdate.setCustId(cust_id);
        recurUpdate.setRecurAmount(recur_amount);
        recurUpdate.setPan(pan);
        recurUpdate.setExdate(expiry_date);
        //recurUpdate.setAddNumRecurs(add_num);
        //recurUpdate.setTotalNumRecurs(total_num);
        //recurUpdate.setHold(hold);
        //recurUpdate.setTerminate(terminate);
        recurUpdate.setCofInfo(cof);
        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode(processing_country_code);
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId(store_id);
    }
}

```

### Sample Recurring Billing Update

```

mpgReq.setApiToken(api_token);
mpgReq.setTransaction(recurUpdate);
mpgReq.setStatusCheck(status_check);
mpgReq.send();
try
{
Receipt receipt = mpgReq.getReceipt();
System.out.println("ReceiptId = " + receipt.getReceiptId());
System.out.println("ResponseCode = " + receipt.getResponseCode());
System.out.println("Message = " + receipt.getMessage());
System.out.println("Complete = " + receipt.getComplete());
System.out.println("TransDate = " + receipt.getTransDate());
System.out.println("TransTime = " + receipt.getTransTime());
System.out.println("TimedOut = " + receipt.getTimedOut());
System.out.println("RecurUpdateSuccess = " + receipt.getRecurUpdateSuccess());
System.out.println("NextRecurDate = " + receipt.getNextRecurDate());
System.out.println("RecurEndDate = " + receipt.getRecurEndDate());
}
catch (Exception e)
{
e.printStackTrace();
}
}
}

```

## 14.4 Recurring Billing Response Fields and Codes

Table 19 outlines the response fields that are part of recurring billing. Some are available when you set up recurring billing (such as with a Purchase transaction), and some are available when you update an existing transaction with the Recurring Billing transaction.

### Receipt object definition

```
Receipt receipt = mpgReq.getReceipt();
```

**Table 19: Recurring Billing response fields**

Value	Type	Limits	Get method
	Description		
<b>Transaction object with Recurring Billing response fields</b>			
Response code	String	3-character numeric	receipt.getResponseCode(); See Table 20: for a description of possible response codes.
Recur success	String	TBD	receipt.getRecurSuccess(); Indicates whether the transaction successfully registered
<b>Recur update object response fields</b>			

**Table 19: Recurring Billing response fields**

Value	Type	Limits	Get method
	Description		
Recur update success	String	true/false	receipt.getRecurUpdateSuccess();
	Indicates whether the transaction successfully updated.		
Next recur date	String	yyyy-mm-dd format	receipt.getNextRecurDate();
	Indicates when the transaction will be billed again.		
Recur end date	String	yyyy-mm-dd format	receipt.getRecurEndDate();
	Indicates when the Recurring Billing Transaction will end.		

The Recur Update response is a 3-digit numeric value. The following is a list of all possible responses after a Recur Update transaction has been sent.

**Table 20: Recur update response codes**

Request Value	Definition
001	Recurring transaction successfully updated (optional: terminated)
983	Cannot find the previous transaction
984	Data error: (optional: field name)
985	Invalid number of recurs
986	Incomplete: timed out
null	Error: Malformed XML

## 14.5 Credential on File and Recurring Billing

**NOTE:** The value of the **payment indicator** field must be **R** when sending Recurring Billing transactions.

For Recurring Billing transactions which are set to start **immediately**:

1. Send a Purchase transaction request with both the Recurring Billing and Credential on File info objects (with Recurring Billing object field **start now** = true)

For Recurring Billing transactions which are set to start on a **future** date:

1. Send Card Verification transaction request including the Credential on File info object to get the Issuer ID
2. Send Purchase transaction request with the Recur and Credential on File info objects included

For updating a Recurring Billing series where you are updating the card number (does not apply if you are only modifying the schedule or amount in a recurring series):

1. Send Card Verification request including the Credential on File info object to get the Issuer ID
2. Send a Recurring Billing Update transaction

For more information about the Recurring Billing object, see [Definition of Request Fields – Recurring](#).

## 15 Customer Information

- 15.1 Using the Customer Information Object
- 15.2 Customer Information Sample Code

The Customer Information object offers a number of fields to be submitted as part of the financial transaction, and stored by Moneris. These details may be viewed in the future in the Merchant Resource Center.

The following transactions support the Customer Information object :

- Purchase (Basic, Interac Debit and Vault)
- Pre-Authorization (Basic and Vault)
- Re-Authorization (Basic)

The Customer Information object holds three types of information:

- Billing/Shipping information
- Miscellaneous customer information properties
- Item information

### Things to Consider:

- If you send characters that are not included in the allowed list, these extra transaction details may not be stored.
- All fields are alphanumeric and allow the following characters: a-z A-Z 0-9 \_ - : . @ \$ = /
- All French accents should be encoded as HTML entities, such as &eacute.
- The data sent in Billing and Shipping Address fields will not be used for any address verification.

### 15.1 Using the Customer Information Object

- 15.1.1 Customer Info Object – Miscellaneous Properties
- 15.1.2 Customer Info Object – Billing/Shipping Information
- 15.1.3 Customer Info Object – Item Information

In addition to instantiating a transaction object and a connection object (as you would for a normal transaction), you must instantiate a CustInfo object.

Any transaction that supports CustInfo has a setCustInfo method. This is used to write the customer information to the transaction object before writing the transaction object to the connection object.

### CustInfo object definition

```
CustInfo customer = new CustInfo();
```

### Transaction object set method

```
<transaction>.setCustInfo(customer);
```

## 15.1.1 Customer Info Object – Miscellaneous Properties

While most of the Customer Information data is organized into objects, there are some values that are properties of the CustInfo object itself. They are explained in the table below.

**Table 21: CustInfo object miscellaneous properties**

Value	Type	Limits	Set method
Email Address	String	60-character alphanumeric	customer.setEmail(email);
Instructions	String	100-character alphanumeric	customer.setInstructions(note);

## 15.1.2 Customer Info Object – Billing/Shipping Information

Billing and shipping information is stored as part of the Customer Information object. They can be written to the object in one of two ways:

- Using set methods
- Using hash tables

Whichever method you use, you will be writing the information found in the table below for both the billing information and the shipping information.

All values are alphanumeric strings. Their maximum lengths are given in the Limit column.

**Table 22: Billing and shipping information values**

Value	Limit	Hash table key
First name	30	"first_name"

**Table 22: Billing and shipping information values (continued)**

Value	Limit	Hash table key
Last name	30	"last_name"
Company name	50	"company_name"
Address	70	"address"
City	30	"city"
Province/State	30	"province"
Postal/Zip code	30	"postal_code"
Country	30	"country"
Phone number (voice)	30	"phone"
Fax number	30	"fax"
Federal tax	10	"tax1"
Provincial/State tax	10	"tax2"
County/Local/Specialty tax	10	"tax3"
Shipping cost	10	"shipping_cost"

### 15.1.2.1 Set Methods for Billing and Shipping Info

The billing information and the shipping information for a given CustInfo object are written by using the `customer.setBilling()` and `customer.setShipping()` methods respectively:

```
customer.setBilling(first_name, last_name, company_name, address, city,
province, postal_code, country, phone, fax, tax1, tax2, tax3, shipping_cost);

customer.setShipping(first_name, last_name, company_name, address, city,
province, postal_code, country, phone, fax, tax1, tax2, tax3, shipping_cost);
```

Both of these methods have the same set of mandatory arguments. They are described in the Billing and shipping information values table in 15.1.2.1 Set Methods for Billing and Shipping Info.

For sample code, see 15.2 Customer Information Sample Code.

### 15.1.2.2 Using Hash Tables for Billing and Shipping Info

Writing billing or shipping information using hash tables is done as follows:

1. Instantiate a CustInfo object.
2. Instantiate a hash table object. (The sample code uses a different hash table for billing and shipping for clarity purposes. However, the skillful developer can re-use the same one.)
3. Build the hash table using put methods with the hash table keys found in the Billing and shipping information values table in 15.1.2 Customer Info Object – Billing/Shipping Information.
4. Call the CustInfo object's setBilling/setShipping method to pass the hash table information to the CustInfo object
5. Call the transaction object's setCustInfo method to write the CustInfo object (with the billing/-shipping information to the transaction object).

For sample code, see 15.2 Customer Information Sample Code.

### 15.1.3 Customer Info Object – Item Information

The Customer Information object can hold information about multiple items. For each item, the values in the table below can be written.

All values are strings, but note the guidelines in the Limits column.

**Table 23: Item information values**

Value	Limits	Hash table key
Item name	45-character alphanumeric	"name"
Item quantity	5-character numeric	"quantity"
Item product code	20-character alphanumeric	"product_code"
Item extended amount	9-character decimal with at least 3 digits and 2 penny values.  0.01-999999.99	"extended_amount"

One way of representing multiple items is with four arrays. This is the method used in the sample code. However, there are two ways to write the item information to the CustInfo object:

- Set methods
- Hash tables

### 15.1.3.1 Set Methods for Item Information

All the item information found in the Item information values table in 15.1.3 Customer Info Object – Item Information is written to the CustInfo object in one instruction for a given item. Such as:

```
customer.setItem(item_description, item_quantity, item_product_code, item_
extended_amount);
```

For sample code (showing how to use arrays to write information about two items), see 15.2 Customer Information Sample Code.

### 15.1.3.2 Using Hash Tables for Item Information

Writing item information using hash tables is done as follows:

1. Instantiate a CustInfo object.
2. Instantiate a hash table object. (The sample code uses a different hash table for each item for clarity purposes. However, the skillful developer can re-use the same one.)
3. Build the hash table using put methods with the hash table keys in the Item information values table in 15.1.3 Customer Info Object – Item Information.
4. Call the CustInfo object's setItem method to pass the hash table information to the CustInfo object
5. Call the transaction object's setCustInfo method to write the CustInfo object (with the item information to the transaction object).

For sample code that shows how to use arrays to write information about two items, see 15.2 Customer Information Sample Code.

## 15.2 Customer Information Sample Code

Below are two examples of a Basic Purchase Transaction with Customer Information. Both samples start with the same declaration of variables, as shown.

Values that are not involved in the Customer Information feature are not shown.

Note that the two items ordered are represented by four arrays, and the billing and shipping details are the same.

### Declaring the variables (common to both methods)

```
***** Billing/Shipping Variables *****
String first_name = "Bob";
String last_name = "Smith";
String company_name = "ProLine Inc.";
String address = "623 Bears Ave";
String city = "Chicago";
String province = "Illinois";
String postal_code = "M1M2M1";
String country = "Canada";
String phone = "777-999-7777";
String fax = "777-999-7778";
String tax1 = "10.00";
String tax2 = "5.78";
```

```

String tax3 = "4.56";
String shipping_cost = "10.00";

***** Order Line Item Variables *****/
String[] item_description = new String[] { "Chicago Bears Helmet", "Soldier Field Poster" };
String[] item_quantity = new String[] { "1", "1" };
String[] item_product_code = new String[] { "CB3450", "SF998S" };
String[] item_extended_amount = new String[] { "150.00", "19.79" };
***** */

```

### Sample Purchase with Customer Information – Set method version

```

CustInfo customer = new CustInfo();

***** Miscellaneous Customer Information Methods *****/
customer.setEmail("nick@widget.com");
customer.setInstructions("Make it fast!");

***** Set Customer Billing Information *****/
customer.setBilling(first_name, last_name, company_name, address, city, province, postal_
code, country, phone, fax, tax1, tax2, tax3, shipping_cost);

***** Set Customer Shipping Information *****/
customer.setShipping(first_name, last_name, company_name, address, city, province, postal_
code, country, phone, fax, tax1, tax2, tax3, shipping_cost);

***** Order Line Items *****/
customer.setItem(item_description[0], item_quantity[0], item_product_code[0], item_
extended_amount[0]);
customer.setItem(item_description[1], item_quantity[1], item_product_code[1], item_
extended_amount[1]);

Purchase purchase = new Purchase();
purchase.setCustInfo(customer);

HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(purchase);
mpgReq.send();

```

### Sample Purchase with Customer Information – Hash table version

```

CustInfo customer2 = new CustInfo();
***** Miscellaneous Customer Information Methods *****/
customer.setEmail("nick@widget.com");
customer.setInstructions("Make it fast!");

***** Billing Hashtable *****/
Hashtable<String, String> b = new Hashtable<String, String>(); //billing hashtable
b.put("first_name", first_name);
b.put("last_name", last_name);
b.put("company_name", company_name);
b.put("address", address);
b.put("city", city);
b.put("province", province);
b.put("postal_code", postal_code);
b.put("country", country);
b.put("phone", phone);
b.put("fax", fax);

```

**Sample Purchase with Customer Information – Hash table version**

```
b.put("tax1", tax1); //federal tax
b.put("tax2", tax2); //prov tax
b.put("tax3", tax3); //luxury tax
b.put("shipping_cost", shipping_cost); //shipping cost
customer2.setBilling(b);
/********************* Shipping Hashtable *****/
Hashtable<String, String> s = new Hashtable<String, String>(); //shipping hashtable
s.put("first_name", first_name);
s.put("last_name", last_name);
s.put("company_name", company_name);
s.put("address", address);
s.put("city", city);
s.put("province", province);
s.put("postal_code", postal_code);
s.put("country", country);
s.put("phone", phone);
s.put("fax", fax);
s.put("tax1", tax1); //federal tax
s.put("tax2", tax2); //prov tax
s.put("tax3", tax3); //luxury tax
s.put("shipping_cost", shipping_cost); //shipping cost
customer2.setShipping(s);
/********************* Order Line Item1 Hashtable *****/
Hashtable<String, String> i1 = new Hashtable<String, String>(); //item hashtable #1
i1.put("name", item_description[0]);
i1.put("quantity", item_quantity[0]);
i1.put("product_code", item_product_code[0]);
i1.put("extended_amount", item_extended_amount[0]);
customer2.setItem(i1);
/********************* Order Line Item2 Hashtable *****/
Hashtable<String, String> i2 = new Hashtable<String, String>(); //item hashtable #2
i2.put("name", "item2's name");
i2.put("quantity", "7");
i2.put("product_code", "item2's product code");
i2.put("extended_amount", "5.01");
customer2.setItem(i2);

Purchase purchase = new Purchase();
purchase.setCustInfo(customer);
HttpsPostRequest mpgReq = new HttpsPostRequest();
mpgReq.setTransaction(purchase);
mpgReq.send();
```



# 16 Status Check

- 16.1 About Status Check
- 16.2 Using Status Check Response Fields
- 16.3 Sample Purchase with Status Check

## 16.1 About Status Check

Status Check is a connection object value that allows merchants to verify whether a previously sent transaction was processed successfully.

To submit a Status Check request, resend the original transaction with all the same parameter values, but set the status check value to either `true` or `false`.

Once set to “true”, the gateway will check the status of a transaction that has an `order_id` that matches the one passed.

- If the transaction is found, the gateway will respond with the specifics of that transaction.
- If the transaction is not found, the gateway will respond with a not found message.

Once it is set to “false”, the transaction will process as a new transaction.

For example, if you send a Purchase transaction with Status Check, include the same values as the original Purchase such as the order ID and the amount.

The feature must be enabled in your merchant profile. To have it enabled, contact Moneris.

### Things to Consider:

- The Status Check request should only be used once and immediately (within 2 minutes) after the last transaction that had failed.
- The Status Check request should not be used to check `openTotals` & `batchClose` requests.
- Do not resend the Status Check request if it has timed out. Additional investigation is required.

## 16.2 Using Status Check Response Fields

After you have used the connection object to send a Status Check request, you can use the Receipt object to obtain the information you want regarding the success of the original transaction.

The status response fields related to the status check are Status Code and Status Message.

Possible Status Code response values:

- 0-49: successful transaction
- 50-999: unsuccessful transaction.

Possible Status Message response values:

- Found: Status code is 0-49
- Not found or Null: Status code is 50-999)

If the Status Message is Found, all other response fields are the same as those from the original transaction.

If the Status Message is Not found, all other response fields will be Null.

## 16.3 Sample Purchase with Status Check

### Sample Purchase transaction with Status Check

```
package Canada;
import JavaAPI.*;
public class TestCanadaPurchase
{
    public static void main(String[] args)
    {
        Purchase purchase = new Purchase();
        purchase.setOrderId("order");
        purchase.setAmount("1.00");
        purchase.setPan("4242424242424242");
        purchase.setExpdate("2202");
        purchase.setCryptType("1");

        HttpsPostRequest mpgReq = new HttpsPostRequest();
        mpgReq.setProcCountryCode("CA");
        mpgReq.setTestMode(true); //false for production transactions
        mpgReq.setstoreId("store1");
        mpgReq.setApiToken("yesguy");
        mpgReq.setTransaction(purchase);
        boolean status_check = true;
        mpgReq.setStatusCheck(status_check);
        mpgReq.send();

        try
        {
            Receipt receipt = mpgReq.getReceipt();
            System.out.println("StatusCode = " + receipt.getStatusCode());
            System.out.println("StatusMessage = " + receipt.getStatusMessage());
        }
        catch (Exception e)
        {
            e.printStackTrace();
        }
    }
}
```



# 17 Testing a Solution

- 17.1 About the Merchant Resource Center
- 17.2 Logging In to the QA Merchant Resource Center
- 17.3 Test Credentials for Merchant Resource Center
- 17.4 Getting a Unique Test Store ID and API Token
- 17.5 Processing a Transaction
- 17.6 Testing INTERAC® Online Payment Solutions
- 17.7 Testing MPI Solutions
- 1 Testing Visa Checkout
- 1 Test Cards
- 17.9 Simulator Host

## 17.1 About the Merchant Resource Center

The Merchant Resource Center is the user interface for Moneris Gateway services. There is also a QA version of the Merchant Resource Center site specifically allocated for you and other developers to use to test your API integrations with the gateway.

You can access the Merchant Resource Center in the test environment at:

<https://esqa.moneris.com/mpg> (Canada)

The test environment is generally available 24/7, but 100% availability is not guaranteed. Also, please be aware that other merchants are using the test environment in the Merchant Resource Center. Therefore, you may see transactions and user IDs that you did not create. As a courtesy to others who are testing, we ask that you use only the transactions/users that you created. This applies to processing Refund transactions, changing passwords or trying other functions.

## 17.2 Logging In to the QA Merchant Resource Center

To log in to the QA Merchant Resource Center for testing purposes:

1. Go to the Merchant Resource Center QA website at <https://esqa.moneris.com/mpg>
2. Enter your username and password, which are the same email address and password you use to log in to the Developer Portal
3. Enter your Store ID, which you obtained from the Developer Portal's My Testing Credentials as described in 17.3 Test Credentials for Merchant Resource Center

## 17.3 Test Credentials for Merchant Resource Center

For testing purposes, you can either use the pre-existing test stores in the Merchant Resource Center, or you can create your own unique test store where you will only see your own transactions. If you want to use the pre-existing stores, use the test credentials provided in the following tables with the corresponding lines of code, as in the examples below.

### Example of Corresponding Code For Canada:

```
String processing_country_code = "CA";
mpgReq.setTestMode(true);

String store_id = "store5";
String api_token = "yesguy";
```

**Table 24: Test Server Credentials - Canada**

store_id	api_token	Username	Password	Other Information
store1	yesguy	demouser	password	
store2	yesguy	demouser	password	
store3	yesguy	demouser	password	
store4	yesguy	demouser	password	
store5	yesguy	demouser	password	
monca00392	yesguy	demouser	password	Use this store to test Convenience Fee transactions
moncaqagt1	mgtokenguy1	demouser	password	Use this store to test Token Sharing
moncaqagt2	mgtokenguy2	demouser	password	Use this store to test Token Sharing
moncaqagt3	mgtokenguy3	demouser	password	Use this store to test Token Sharing

store_id	api_token	Username	Password	Other Information
monca01428	mcmpguy	demouser	password	Use this store to test MasterCard MasterPass

Alternatively, you can create and use a unique test store where you will only see your own transactions. For more on this, see Getting a Unique Test Store ID and API Token (page 497)

## 17.4 Getting a Unique Test Store ID and API Token

Transactions requests via the API will require you to have a Store ID and a corresponding API token. For testing purposes, you can either use the pre-existing test stores in the Merchant Resource Center, or you can create your own unique test store where you will only see your own transactions.

To get your unique Store ID and API token:

1. Log in to the Developer Portal at <https://developer.moneris.com>
2. In the My Profile dialog, click the Full Profile  button
3. Under My Testing Credentials, select Request Testing Credentials
4. Enter your Developer Portal password and select your country
5. Record the Store ID and API token that are given, as you will need them for logging in to the Merchant Resource Center (Store ID) and for API requests (API token).

Alternatively, you can use the pre-existing test stores already set up in the Merchant Resource Center as described in Test Credentials for Merchant Resource Center (page 496).



## 17.5 Processing a Transaction

- 1.1 Overview
- 1.2 HttpsPostRequest Object
- 1.3 Receipt Object

### 17.5.1 Overview

There are some common steps for every transaction that is processed.

1. Instantiate the transaction object (e.g., Purchase), and update it with object definitions that refer to the individual transaction.
2. Instantiate the HttpsPostRequest connection object and update it with connection information, host information and the transaction object that you created in step 17.5  
Section 17.5 (page 499) provides the HttpsPostRequest connection object definition. This object and its variables apply to **every** transaction request.
3. Invoke the HttpsPostRequest object's `send()` method.
4. Instantiate the Receipt object, by invoking the HttpsPostRequest object's get Receipt method. Use this object to retrieve the applicable response details.

Some transactions may require steps in addition to the ones listed here. Below is a sample Purchase transaction with each major step outlined. For extensive code samples of other transaction types, refer to the Java API ZIP file.

**NOTE:** For illustrative purposes, the order in which lines of code appear below may differ slightly from the same sample code presented elsewhere in this document.

import java.io.*; import java.util.*; import java.net.*; import JavaAPI.*;	Include all necessary classes.
String order_id = "Test"+createDate.getTime(); String amount = "5.00"; String pan = "4242424242424242"; String expdate = "1901"; //YYMM format String crypt = "7"; String processing_country_code = "CA";	Define all mandatory values for the transaction object properties.
String store_id = "store5"; String api_token = "yesguy";	Define all mandatory values for the connection object properties.

<pre>Purchase purchase = new Purchase();  purchase.setOrderId(order_id); purchase.setAmount(amount); purchase.setPan(pan); purchase.setExpdate(expdate); purchase.setCryptType(crypt); purchase.setDynamicDescriptor("2134565");</pre>	<p>Instantiate the transaction object and assign values to properties.</p>
<pre>HttpsPostRequest mpgReq = new HttpsPostRequest();  mpgReq.setProcCountryCode(processing_country_code); mpgReq.setTestMode(true); mpgReq.setStoreId(store_id); mpgReq.setApiToken(api_token); mpgReq.setTransaction(purchase); mpgReq.setStatusCheck(status_check);</pre>	<p>Instantiate connection object and assign values to properties, including the transaction object you just created.</p>
<pre>try {     Receipt receipt = mpgReq.getReceipt();      System.out.println("CardType = " + receipt.getCardType());     System.out.println("TransAmount = " + receipt.getTransAmount());     System.out.println("TxnNumber = " + receipt.getTxnNumber());     System.out.println("ReceiptId = " + receipt.getReceiptId());     System.out.println("TransType = " + receipt.getTransType());     System.out.println("ReferenceNum = " + receipt.getReferenceNum());     System.out.println("ResponseCode = " + receipt.getResponseCode());     System.out.println("ISO = " + receipt.getISO());     System.out.println("BankTotals = " + receipt.getBankTotals());     System.out.println("Message = " + receipt.getMessage());     System.out.println("AuthCode = " + receipt.getAuthCode());     System.out.println("Complete = " + receipt.getComplete());     System.out.println("TransDate = " + receipt.getTransDate());     System.out.println("TransTime = " + receipt.getTransTime());     System.out.println("Ticket = " + receipt.getTicket());     System.out.println("TimedOut = " + receipt.getTimedOut());     System.out.println("IsVisaDebit = " + receipt.getIsVisaDebit()); }  catch (Exception e) {     e.printStackTrace(); }</pre>	<p>Instantiate the Receipt object and use its get methods to retrieve the desired response data.</p>

## 17.5.2 HttpsPostRequest Object

The transaction object that you instantiate becomes a property of this object when you call its set transaction method.

### HttpsPostRequest Object Definition

```
HttpsPostRequest mpgReq = new HttpsPostRequest();
```

After instantiating the `HttpsPostRequest` object, update its mandatory and optional values as outlined in the following values tables.

**Table 25: `HttpsPostRequest` object mandatory values**

Value	Type	Limits	Set method
	Description		
Processing country code	String	2-character alphabetic	<code>mpgReq.setProcCountryCode(processing_country_code);</code>  CA for Canada, US for USA.
Test mode	Boolean	true/false	<code>mpgReq.setTestMode(true);</code>  Set to <code>true</code> when in test mode. Set to <code>false</code> (or comment out entire line) when in production mode.
Store ID	String	10-character alphanumeric	<code>mpgReq.setstoreId(store_id);</code>  Unique identifier provided by Moneris upon merchant account set up.  See 17.1 About the Merchant Resource Center for test environment details.
API Token	String	20-character alphanumeric	<code>mpgReq.setApiToken(api_token);</code>  Unique alphanumeric string assigned upon merchant account activation. To locate your production API token, refer to the Merchant Resource Center Admin Store Settings.  See 17.3 Test Credentials for Merchant Resource Center for test environment details.
Transaction	Object	Not applicable	<code>mpgReq.setTransaction(transaction);</code>  This argument is one of the numerous transaction types discussed in the rest of this manual. (Such as Purchase, Refund and so on.) This object is instantiated in step 1 above.

**Table 1 `HttpsPostRequest` object optional values**

Value	Type	Limits	Set method
	Description		
Status Check	Boolean	true/false	<code>mpgReq.setStatusCheck(status_check);</code>  See Appendix A Definition of Request Fields.
			<p><b>NOTE:</b> while this value belongs to the <code>HttpsPostRequest</code> object, it is only supported by some transactions. Check the individual transaction definition to find out whether Status Check can be used.</p>

### 17.5.3 Receipt Object

After you send a transaction using the `HttpsPostRequest` object's `send` method, you can instantiate a receipt object.

#### Receipt Object Definition

```
Receipt receipt = mpgReq.getReceipt();
```

For an in-depth explanation of Receipt object methods and properties, see Appendix B Definitions of Response Fields.

## 17.6 Testing INTERAC® Online Payment Solutions

Axcsys has two websites where merchants can post transactions for testing the fund guarantee porting of INTERAC® Online Payment transactions. The test `IDEBIT_MERCHNUM` value is provided by Moneris after registering in the test environment.

After registering, the following two links become accessible:

- Merchant Test Tool
- Certification Test Tool

#### Merchant Test Tool

[https://merchant-test.interacidebit.ca/gateway/merchant\\_test\\_processor.do](https://merchant-test.interacidebit.ca/gateway/merchant_test_processor.do)

This URL is used to simulate the transaction response process, to validate response variables, and to properly integrate your checkout process.

When testing INTERAC® Online Payment transactions, you are forwarded to the INTERAC® Online Payment Merchant Testing Tool. A screen appears where certain fields need to be completed.

For an approved response, do not alter any of the fields except for the ones listed here.

#### **IDEBIT\_TRACK2**

To form a track2 when testing with the Moneris Gateway, use one of these three numbers:

3728024906540591206=01121122334455000

5268051119993326=011211223344550000000

453781122255=0112112233445500000000000

#### **IDEBIT\_ISSNAME**

RBC

#### **IDEBIT\_ISSCONF**

123456

For a declined response, provide any other value as the `IDEBIT_TRACK2`. Click **Post to Merchant**.

---

Whether the transaction is approved or declined, do **not** click **Validate Data**. This will return validation errors.

### Certification Test Tool

[https://merchant-test.interacidebit.ca/gateway/merchant\\_certification\\_processor.do](https://merchant-test.interacidebit.ca/gateway/merchant_certification_processor.do)

This URL is used to complete the required INTERAC® Online Payment Merchant Front-End Certification test cases, which are outlined in Appendix E (page 605) and Appendix F (page 609).

To confirm the fund that was guaranteed above, an INTERAC® Online Payment Purchase must be sent to the Moneris Gateway QA using the following test store information:

**Host:** esqa.monteris.com

**Store ID:** store3

**API Token:** yesguy

You can always log into the Merchant Resource Center to check the results using the following information:

**URL:** <https://esqa.monteris.com/mpg>

**Store ID:** store3

Note that all response variables that are posted back from the IOP gateway in step 5.4 of 5.4 must be validated for length of field, permitted characters and invalid characters.

## 17.7 Testing MPI Solutions

When testing your implementation of the Moneris MPI, you can use the Visa/MasterCard/Amex PIT (production integration testing) environment. The testing process is slightly different than a production environment in that when the inline window is generated, it does not contain any input boxes. Instead, it contains a window of data and a **Submit** button. Clicking **Submit** loads the response in the testing window. The response will not be displayed in production.

**NOTE:** MasterCard SecureCode and Amex SafeKey may not be directly tested within our current test environment. However, the process and behavior tested with the Visa test cards will be the same for MCSC and SafeKey.

When testing you may use the following test card numbers with any future expiry date. Use the appropriate test card information from the tables below: Visa and MasterCard use the same test card information, while Amex uses unique information.

**Table 26: MPI test card numbers (Visa and MasterCard only)**

Card Number	VERes	PARes	Action
4012001037141112 4242424242424242	Y	true	TXN – Call function to create inLine window. ACS – Send CAVV to Moneris Gateway using either the Cavv Purchase or the Cavv Pre-Authorization transaction.
4012001038488884	U	NA	Send transaction to Moneris Gateway using either the basic Purchase or the basic Pre-Authorization transaction. Set crypt_type = 7.
4012001038443335	N	NA	Send transaction to Moneris Gateway using either the basic Purchase or the basic Pre-Authorization transaction. Set crypt_type = 6.
4012001037461114	Y	false	Card failed to authenticate. Merchant may chose to send transaction or decline transaction. If transaction is sent, use crypt type = 7.

**Table 27: MPI test card numbers (Amex only)**

Card Number	Password				Action
	VERes	Required?	PARes		
375987000000062	U	Not required	N/A	TXN – Call function to create inLine window. ACS – Send CAVV to Moneris Gateway using either the Cavv Purchase or the Cavv Pre-Authorization transaction. Set crypt_type = 7.	
375987000000021	Y	Yes: test13fail	false	Card failed to authenticate. Merchant may chose to send transaction or decline transaction. If transaction is sent, use crypt type = 7.	
375987000000013	N	Not required	N/A	Send transaction to Moneris Gateway using either the basic Purchase or the basic Pre-Authorization transaction. Set crypt_type = 6.	
374500261001009	Y	Yes: test09	true	Card failed to authenticate. Merchant may choose to send transaction or decline transaction. Set crypt_type = 5.	

**VERes**

The result U, Y or N is obtained by using getMessage().

**PARes**

The result “true” or “false” is obtained by using getSuccess().

To access the Merchant Resource Center in the test environment go to <https://esqa.monерис.com/mpg>.

---

Transactions in the test environment should not exceed \$11.00.

## 17.8 Test Card Numbers

Because of security and compliance reasons, the use of live credit and debit card numbers for testing is strictly prohibited. Only test credit and debit card numbers are to be used.

To test general transactions, use the following test card numbers:

Card Plan	Test Card Number
Mastercard	5454545454545454
Visa	4242424242424242
Amex	373599005095005
JCB	3566007770015365
Diners	36462462742008
Track2	5258968987035454=06061015454001060101?
Discover	6011000992927602
UnionPay	6250944000000771

### 17.8.1 Test Card Numbers for Level 2/3

When testing Level 2/3 transactions, use the card numbers below.

Card Brand	Test Card Number
Mastercard	54545444242424
Visa	42424242545454
Amex	373269005095005

## 17.8.2 Test Cards for Visa Checkout

Card Plan	Test Card Number
Visa	4005520201264821 (without card art)
Visa	4242424242424242 (with card art)
MasterCard	5500005555555559
American Express	340353278080900
Discover	6011003179988686

## 17.9 Simulator Host

The test environment has been designed to replicate the production environment as closely as possible. One major difference is that Moneris is unable to send test transactions onto the production authorization network. Therefore, issuer responses are simulated. Additionally, the requirement to emulate approval, decline and error situations dictates that certain transaction variables initiate various response and error situations.

The test environment approves and declines transactions based on the penny value of the amount sent. For example, a transaction made for the amount of \$9.00 or \$1.00 is approved because of the .00 penny value.

Transactions in the test environment must not exceed \$11.00.

For a list of all current test environment responses for various penny values, please see the Test Environment Penny Response Table available at <https://developer.moneris.com>.

**NOTE:** These responses may change without notice. Check the Moneris Developer Portal (<https://developer.moneris.com>) regularly to access the latest documentation and downloads.

# 18 Moving to Production

- 18.1 Activating a Production Store Account
- 18.2 Configuring a Store for Production
- 18.3 Receipt Requirements
- 1 Getting Help

## 18.1 Activating a Production Store Account

The steps below outline how to activate your production account so that you can process production transactions.

1. Obtain your activation letter/fax from Moneris.
2. Go to <https://www.moneris.com/activate>.
3. Input your store ID and merchant ID from the letter/fax and click **Activate**.
4. Follow the on-screen instructions to create an administrator account. This account will grant you access to the Merchant Resource Center.
5. Log into the Merchant Resource Center at <https://www3.moneris.com/mpg> using the user credentials created in step 18.1.
6. Proceed to **ADMIN** and then **STORE SETTINGS**.
7. Locate the API token at the top of the page. You will use this API token along with the store ID that you received in your letter/fax and to send any production transactions through the API.

When your production store is activated, you need to configure your store so that it points to the production host. To learn how do to this, see Configuring a Store for Production (page 507)

**NOTE:** For more information about how to use the Merchant Resource Center, see the Moneris Gateway Merchant Resource Center User's Guide, which is available at <https://developer.moneris.com>.

## 18.2 Configuring a Store for Production

After you have completed your testing and have activated your production store, you are ready to point your store to the production host.

To configure a store for production:

1. Change the test mode set method from `true` to `false`.
2. Change the Store ID to reflect the production store ID that you received when you activated your production store. To review the steps for activating a production store, see Activating a Production Store Account (page 507).

3. Change the API token to the production token that you received during activation.
4. If you haven't done so already, change the code to reflect the correct processing country (Canada for most merchants). For more on this, see

The table below illustrates the steps above using the relevant code (and where **X** is an alphanumeric character).

Step	Code in Testing	Changes for Production
1	No string changes for this item, only set method is altered:  <pre>mpgReq.setTestMode(true);</pre>	Set method for production:  <pre>mpgReq.setTestMode(false);</pre>
2	String:  <pre>String store_id = "store5";</pre> Associated Set Method:  <pre>mpgReq.setstoreId(store_id);</pre>	String for Production:  <pre>String store_id = "monXXXXXXXXX";</pre>
3	String:  <pre>String api_token = "yesguy";</pre> Associated Set Method:  <pre>mpgReq.setApiToken(api_token);</pre>	String for Production:  <pre>String api_token = "XXXX";</pre>

### 18.2.1 Configuring an INTERAC® Online Payment Store for Production

Before you can process INTERAC® Online Payment transactions through your web site, you need to complete the certification registration process with Moneris, as described below. The production IDEBIT\_MERCHNUM value is provided by Moneris after you have successfully completed the certification.

Acxsys' production INTERAC® Online PaymentGateway URL is [https://gateway.interaconline.com/merchant\\_processor.do](https://gateway.interaconline.com/merchant_processor.do).

To access the Moneris Moneris Gateway production gateway URL, use the following:

**Store ID: Provided by Moneris**

**API Token: Generated during your store activation process.**

**Processing country code: CA**

The **production** Merchant Resource Center URL is <https://www3.moneris.com/mpg/>

### 18.2.1.1 Completing the Certification Registration - Merchants

To complete the certification registration, fax or email the information below to our Integration Support helpdesk:

- Merchant logo to be displayed on the INTERAC® Online Payment Gateway page
  - In both French and English
  - 120 × 30 pixels
  - Only PNG format is supported.
- Merchant business name
  - In both English and French
  - Maximum 30 characters.
- List of all referrer URLs. That is, URLs from which the customer may be redirected to the INTERAC® Online Payment gateway.
- List of all URLs that may appear in the IDEBIT\_FUNDEDURL field of the https form POST to the INTERAC® Online Payment Gateway.
- List of all URLs that may appear in the IDEBIT\_NOTFUNDEDURL field of the https form POST to the INTERAC® Online Payment Gateway.

### 18.2.1.2 Third-Party Service/Shopping Cart Provider

In your product documentation, instruct your clients to provide the information below to the Moneris Gateway Integration Support helpdesk for certification registration:

- Merchant logo to be displayed on the INTERAC® Online Payment Gateway page
  - In both French and English
  - 120 × 30 pixels
  - Only PNG format is supported.
- Merchant business name
  - In both English and French
  - Maximum 30 characters.
- List of all referrer URLs. That is, URLs from which the customer may be redirected to the INTERAC® Online Payment gateway.
- List of all URLs that may appear in the IDEBIT\_FUNDEDURL field of the https form POST to the INTERAC® Online Payment Gateway.
- List of all URLs that may appear in the IDEBIT\_NOTFUNDEDURL field of the https form POST to the INTERAC® Online Payment Gateway.

See 5.3.3, page 126 for additional client requirements.

### 18.3 Receipt Requirements

Visa and MasterCard expect certain details to be provided to the cardholder and on the receipt when a transaction is approved.

Receipts must comply with the standards outlined within the Integration Receipts Requirements. For all the receipt requirements covering all transaction scenarios, visit the Moneris Developer Portal at <https://developer.moneris.com>.

Production of the receipt must begin when the appropriate response to the transaction request is received by the application. The transaction may be any of the following:

- **Sale** (Purchase)
- **Authorization** (PreAuth, Pre-Authorization)
- **Authorization Completion** (Completion, Capture)
- **Offline Sale** (Force Post)

- **Sale Void** (Purchase Correction, Void)
- **Refund**.

The boldface terms listed above are the names for transactions as they are to be displayed on receipts. Other terms used for the transaction are indicated in brackets.

### 18.3.1 Certification Requirements

Card-present transaction receipts are required to complete certification.

#### **Card-not-present integration**

Certification is optional but highly recommended.

#### **Card-present integration**

After you have completed the development and testing, your application must undergo a certification process where all the applicable transaction types must be demonstrated, and the corresponding receipts properly generated.

Contact a Client Integration Specialist for the Certification Test checklist that must be completed and returned for verification. (See "Getting Help" on page 1 for contact details.) Be sure to include the application version of your product. Any further changes to the product after certification requires re-certification.

After the certification requirements are met, Moneris will provide you with an official certification letter.

## Appendix A Definition of Request Fields

This section defines transaction request variables. Not all fields are required — refer to individual transaction type topics for information on whether a field is required or optional.

- A.1 Definition of Request Fields – Connection Fields
- A.2 Definition of Request Fields – Core Fields
- A.3 Definition of Request Fields – Credential on File
- A.4 Definition of Request Fields – Vault
- A.5 Definition of Request Fields for Level 2/3 - Visa
- A.6 Definition of Request Fields for Level 2/3 - Mastercard
- A.7 Definition of Request Fields for Level 2/3 - Amex
- Appendix A Definition of Request Fields – MPI
- A.11 Definition of Request Fields – MCP
- A.12 Definition of Request Fields – Offlinx™
- A.13 Definition of Request Fields – Convenience Fee
- A.14 Definition of Request Fields – Recurring

### A.1 Definition of Request Fields – Connection Fields

#### Core connection object fields (all API transactions)

Variable Name	Type and Limits	Description
store ID	<i>String</i>	Unique identifier provided by Moneris upon merchant account setup
store_id	N/A	
API token	<i>String</i>	Unique alphanumeric string assigned by Moneris upon merchant account activation
api_token	N/A	To find your API token, refer to your test or production store's Admin settings in the Merchant Resource Center, at the following URLs:

Variable Name	Type and Limits	Description
		<p>Testing: <a href="https://esqa.-moneris.com/mpg/">https://esqa.-moneris.com/mpg/</a></p> <p>Production: <a href="https://www3.-moneris.com/mpg/">https://www3.-moneris.com/mpg/</a></p>

## A.2 Definition of Request Fields – Core Fields

Variable Name	Type and Limits	Description
amount	<i>String</i>	Transaction dollar amount
amount	10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	This must contain at least 3 digits, two of which are penny values  Minimum allowable value = \$0.01, maximum allowable value = \$9999999.99
	<b>EXAMPLE:</b> 1234567.89	
authorization code	<i>String</i>	An authorization code required to carry out a Force Post; provided in the transaction response from the issuing bank
auth_code	8-character alphanumeric	
completion amount	<i>String</i>	Dollar amount of a Pre-Authorization Completion transaction, which may differ from the original amount authorized in the Pre-Authorization
comp_amount	10-character decimal  Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point	
	<b>EXAMPLE:</b> 1234567.89	
credit card number	<i>String</i>	Credit card number, usually 16 digits —field can be maximum 20 digits in support of future expansion of card number ranges.
pan	max 20-character alphanumeric	

Variable Name	Type and Limits	Description
dynamic descriptor dynamic_descriptor	<p><i>String</i></p> <p>20-character alphanumeric total of 22 characters including your merchant name and separator</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b>            Some special characters are not allowed:            &lt;&gt; \$ % = ? ^ { } [ ] \          </div>	<p>Carries the token for network tokenization transactions.</p> <p>Merchant-defined description sent on a per-transaction basis that will appear on the credit card statement appended to the merchant's business name</p> <p>Dependent on the card issuer, the statement will typically show the dynamic descriptor appended to the merchant's existing business name separated by the "/" character; additional characters will be truncated</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> The 22-character maximum limit must take the "/" into account as one of the characters         </div>
electronic commerce indicator crypt	<p><i>String</i></p> <p>1-character alphanumeric</p>	<p>Describes the category of e-commerce transaction being processed. Allowable values are:</p> <ul style="list-style-type: none"> <li>1 – Mail Order / Telephone Order—Single</li> <li>2 – Mail Order / Telephone Order—Recurring</li> <li>3 – Mail Order / Telephone Order—Instalment</li> <li>4 – Mail Order / Telephone Order—Unknown classification</li> <li>5 – Authenticated e-commerce transaction (3-D Secure)</li> <li>6 – Non-authenticated e-commerce transaction (3-D Secure)</li> <li>7 – SSL-enabled merchant</li> </ul> <p><b>In Credential on File transactions where the request field e-commerce indicator is also being sent:</b> the allowable values for e-commerce indicator are dependent on the value sent for <b>payment indicator</b>, as follows:</p>

Variable Name	Type and Limits	Description
		if payment indicator = R, then allowable values for e-commerce indicator: 2, 5 or 6
		if payment indicator = V, then allowable values for e-commerce indicator: 2, 5 or 6
		if payment indicator = C, then allowable values for e-commerce indicator: 1, 5, 6 or 7
		if payment indicator = U, then allowable values for e-commerce indicator: 1 or 7
		if payment indicator = Z, then allowable values for e-commerce indicator: 1, 5, 6 or 7
		<b>For Apple Pay or Google Pay™ transactions where you are doing decryption:</b> send the value of the <b>ecilIndicator</b> or <b>3dsEcilIndicator</b> field returned in the payload
		If the value is not present in the payload, send the value as 5; if you get a 2-character value (e.g., 05 or 07), remove the initial 0 and just send us the 2nd character
		Allowable values for Apple Pay and Google Pay™ are: 5: Authenticated e-commerce transaction 7: SSL-enabled merchant
expiry date expiry_date	<i>String</i>  4-character alphanumeric  YYMM	Expiry date of the credit card, in YYMM format.  <div style="border: 1px solid #ccc; padding: 5px; background-color: #f0f8ff;"><b>NOTE:</b> This is the reverse of the MMYY date format that is presented on the card.</div>
order ID order_id	<i>String</i>  50-character alphanumeric  a-Z A-Z 0-9 _ - : . @ spaces	Merchant-defined transaction identifier that must be unique for every Purchase, Pre-Authorization and Independent Refund transaction. No two transactions of these types may have the same order ID.

Variable Name	Type and Limits	Description
		For Refund, Completion and Purchase Correction transactions, the order ID must be the same as that of the original transaction.
original order ID  orig_order_id	<i>String</i>	Order ID from the original Pre-Authorization transaction, used as a reference to retrieve the original payment details
shipping indicator  ship_indicator	<i>String</i>  1-character alphanumeric	Used to identify completion transactions that require multiple shipments, also referred to as multiple completions  By default, if shipping indicator is not sent, the Pre-Authorization Completion is listed as final  To indicate that the Pre-Authorization Completion is to be left open by the issuer as supplemental shipments or completions are pending, submit shipping indicator with a value of P  Possible values:  P – Partial  F – Final
transaction number  txn_number	<i>String</i>  255-character, alphanumeric, hyphens or underscores  variable length	Used to reference the original transaction when performing a follow-on transaction (i.e., Pre-Authorization Completion, Purchase Correction or Refund)  This value is returned in the response of the original transaction  Pre-Authorization Completion: references a Pre-Authorization  Refund/Purchase Correction: references a Purchase or Pre-Authorization Completion

Variable Name	Type and Limits	Description
wallet indicator	<i>String</i>	
wallet_indicator	3-character alphanumeric	<p>Indicates when a card number has been collected via a digital wallet, such as in Apple Pay, Google Pay™, Visa Checkout and Mastercard MasterPass, or via network tokenization from the card brand.</p> <p>Required for Apple Pay, Google Pay™ transactions whereby you are using your own API to decrypt the payload</p> <p>Possible values:</p> <ul style="list-style-type: none"> <li>APP –Apple Pay In-App</li> <li>APW – Apple Pay on the Web</li> <li>GPP – Google Pay™ In-App</li> <li>GPW – Google Pay™ Web</li> <li>VCO –Visa Checkout</li> <li>MMP – Mastercard MasterPass</li> </ul>

**NOTE:** Please note that if this field is included to indicate Apple Pay or Google Pay™, then Convenience Fee is not supported.

**NOTE:** Network tokenization wallet indicators are not in the API call but are in the merchant resource centre (MRC).

### A.3 Definition of Request Fields – Credential on File

Variable Name	Type and Limits	Description
issuer ID	<i>String</i> 15-character alphanumeric	Unique identifier for the cardholder's stored credentials

Variable Name	Type and Limits	Description
<p><b>NOTE:</b> This variable is required for all merchant-initiated transactions following the first one; upon sending the first transaction, the issuer ID value is received in the transaction response and then used in subsequent transaction requests.</p>	variable length	<p>Sent back in the response from the card brand when processing a Credential on File transaction</p> <p>If the cardholder's credentials are being stored for the first time, and the issuer ID was returned in the response, you must save the issuer ID on your system to use in subsequent Credential on File transactions (applies to merchant-initiated transactions only)</p> <p>The issuer ID must be saved to your systems when returned from Moneris Gateway in the response data, regardless if the value was received or not</p> <p>As a best practice, if the issuer ID is not returned and you received a value of NULL instead, store that value and send it in the subsequent transaction</p>
payment indicator	<p><i>String</i></p> <p>1-character alphabetic</p>	<p>Indicates the current or intended use of the credentials</p> <p>Possible values for first transactions:</p> <p>C - unscheduled Credential on File (first transactions only)</p> <p>R - recurring</p> <p>V - recurring variable payment transaction</p> <p>Possible values for subsequent transactions:</p> <p>R - recurring</p> <p>V - recurring variable payment transaction</p> <p>U - unscheduled merchant-initiated transaction</p> <p>Z - unscheduled customer-initiated transaction</p> <p>In Credential on File transactions where the request field e-commerce</p>

Variable Name	Type and Limits	Description
		indicator is also being sent, the acceptable values for e-commerce indicator are dependent on the value sent for payment indicator, as follows:
		if payment indicator = R, then allowable values for e-commerce indicator: 2, 5 or 6
		if payment indicator = V, then allowable values for e-commerce indicator: 2, 5 or 6
		if payment indicator = C, then allowable values for e-commerce indicator: 1, 5, 6 or 7
		if payment indicator = U, then allowable values for e-commerce indicator: 1 or 7
		if payment indicator = Z, then allowable values for e-commerce indicator: 1, 5, 6 or 7
payment information	<p><i>String</i></p> <p>1-character numeric</p>	<p>Describes whether the transaction is the first or subsequent in the series</p> <p>Possible values:</p> <p>0 - first transaction in a series (storing payment details provided by the cardholder)</p> <p>2 - subsequent transactions (using previously stored payment details)</p>

#### A.4 Definition of Request Fields – Vault

Variable Name	Type and Limits	Description
data key	<p><i>String</i></p> <p>25-character alphanumeric</p>	<p>Unique identifier for a Vault profile, and used in future Vault financial transactions to associate a transaction with that profile</p> <p>Data key is generated by Moneris and returned to you in the Receipt object when the profile is first registered</p>
data key format	<p><i>String</i></p> <p>2-character alphanumeric</p>	Specifies the data key format being returned

Variable Name	Type and Limits	Description
		If left blank, data key format will default to 25-character alphanumeric  Possible values:  0 – 25 character alphanumeric data key  0U – unique 25-character alphanumeric data key
duration	<i>String</i>  3-character numeric  maximum 900 seconds	Amount of time the temporary token should be available
email address	<i>String</i>  30-character alphanumeric	Customer's email address  Can be sent in when creating or updating a Vault profile
note	<i>String</i>  30-character alphanumeric	Used for any supplementary information related to the customer  Can be sent in when creating or updating a Vault profile
phone number	<i>String</i>  30-character alphanumeric	Customer's phone number  Can be sent in when creating or updating a Vault profile

## A.5 Definition of Request Fields for Level 2/3 - Visa

Table 1 Visa - Corporate Card Common Data - Level 2 Request Fields

Req*	Field Name	Limits	Set Method	Description
Y	National Tax	12-character decimal	TRANSACTIONNAME.setNationalTax(national_tax);	Must reflect the amount of National Tax (GST or HST) appearing on the invoice.  Minimum -

Req*	Field Name	Limits	Set Method	Description
				0.01 Maximum - 999999.99. Must have 2 decimal places.
Y	Merchant VAT Registration/Single Business Reference Number	20-character alphanumeric	TRANSACTIONNAME.setMerchantVatNo(merchant_vat_no);	<p>Merchant's Tax Registration Number must be provided if tax is included on the invoice</p> <div style="border: 1px solid #ccc; padding: 5px; width: fit-content;"> <b>NOTE:</b> Must not be all spaces or all zeroes         </div>
C	Local Tax	12-character decimal	TRANSACTIONNAME.setLocalTax(local_tax);	<p>Must reflect the amount of Local Tax (PST or QST) appearing on the invoice</p> <p>If Local Tax included then must not be all spaces or all zeroes; Must be provided if Local Tax (PST or QST) applies</p> <p>Minimum = 0.01</p> <p>Maximum = 999999.99</p>

Req*	Field Name	Limits	Set Method	Description
				Must have 2 decimal places
C	Local Tax (PST or QST) Registration Number	15-character alphanumeric	TRANSACTIONNAME.setLocalTaxNo(local_tax_no);	<p>Merchant's Local Tax (PST/QST) Registration Number</p> <p>Must be provided if tax is included on the invoice; If Local Tax included then must not be all spaces or all zeroes</p> <p>Must be provided if Local Tax (PST or QST) applies</p>
C	Customer VAT Registration Number	13-character alphanumeric	TRANSACTIONNAME.setCustomerVatNo(customer_vat_no);	If the Customer's Tax Registration Number appears on the invoice to support tax exempt transactions it must be provided here
C	Customer Code/Customer Reference Identifier (CRI)	16-character alphanumeric	TRANSACTIONNAME.setCri(cri);	Value which the customer may choose to provide to the supplier at the point of sale – must be provided if given by the

Req*	Field Name	Limits	Set Method	Description
				customer
N	Customer Code	17-character alphanumeric	TRANSACTIONNAME.setCustomerCode(customer_code);	Optional customer code field that will not be passed along to Visa, but will be included on Moneris reporting
N	Invoice Number	17-character alphanumeric	TRANSACTIONNAME.setInvoiceNumber(invoice_number);	Optional invoice number field that will not be passed along to Visa, but will be included on Moneris reporting

\*Y = Required, N = Optional, C = Conditional

**Table 2 Visa - Corporate Card Common Data- Level 2 Request Fields (VSPurcha)**

Req	Variable Name	Field Name	Size/Type	Description
C*	Buyer Name	buyer_name	30-character alphanumeric	Buyer/Recipient Name  *only required by CRA if transaction is >\$150
C*	Local tax rate	local_tax_rate	4-character decimal	Indicates the detailed tax rate applied in relationship to a local tax amount  <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2e0;"> <b>EXAMPLE:</b> 8% PST should be 8.0.         </div> maximum 99.99

Req	Variable Name	Field Name	Size/Type	Description
				*Must be provided if Local Tax (PST or QST) applies.
N	Duty Amount	duty_amount	9-character decimal	<p>Duty on total purchase amount</p> <p>A minus sign means 'amount is a credit', plus sign or no sign means 'amount is a debit'</p> <p>maximum without sign is 999999.99</p>
N	Invoice Discount Treatment	discount_treatment	1-character numeric	<p>Indicates how the merchant is managing discounts</p> <p>Must be one of the following values:</p> <ul style="list-style-type: none"> <li>0 - if no invoice level discounts apply for this invoice</li> <li>1 - if Tax was calculated on Post-Discount totals</li> <li>2 - if Tax was calculated on Pre-Discount totals</li> </ul>
N	Invoice Level Discount Amount	discount_amt	9-character decimal	<p>Amount of discount (if provided at the invoice level according to the Invoice Discount Treatment)</p> <p>Must be non-zero if Invoice Discount Treatment is 1 or 2</p> <p>Minimum amount is 0.00 and maximum is 999999.99</p>

Req	Variable Name	Field Name	Size/Type	Description
C*	Ship To Postal Code / Zip Code	ship_to_pos_code	10-character alpha-numeric	<p>The postal code or zip code for the destination where goods will be delivered</p> <p>*Required if shipment is involved</p> <p>Full alpha postal code - Valid ANA&lt;space&gt;NAN format required if shipping to an address within Canada</p>
C	Ship From Postal Code / Zip Code	ship_from_pos_code	10-character alpha-numeric	<p>The postal code or zip code from which items were shipped</p> <p>For Canadian addresses, requires full alpha postal code for the merchant with Valid ANA&lt;space&gt;NAN format</p>
C*	Destination Country Code	des_cou_code	2-character alpha-numeric	<p>Code of country where purchased goods will be delivered</p> <p>Use ISO 3166-1 alpha-2 format</p> <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2fd;"> <b>NOTE:</b> Required if it appears on the invoice for an international transaction       </div>
Y	Unique VAT Invoice Reference Number	vat_ref_num	25-character alpha-numeric	Unique Value Added Tax Invoice Reference Number

Req	Variable Name	Field Name	Size/Type	Description
				Must be populated with the invoice number and this cannot be all spaces or zeroes
Y	Tax Treatment	tax_treatment	1-character numeric	<p>Must be one of the following values:</p> <p>0 = Net Prices with tax calculated at line item level;</p> <p>1 = Net Prices with tax calculated at invoice level;</p> <p>2 = Gross prices given with tax information provided at line item level;</p> <p>3 = Gross prices given with tax information provided at invoice level;</p> <p>4 = No tax applies (small merchant) on the invoice for the transaction</p>
N	Freight/Shipping Amount (Ship Amount)	freight_amount	9-character decimal	<p>Freight charges on total purchase</p> <p>If shipping is not provided as a line item it must be provided here, if applicable</p> <p>Signed monetary amount: minus sign means 'amount is a credit', plus sign or no sign means 'amount is a debit', maximum without sign is 999999.99</p>
C	GST HST Freight Rate	gst_hst_freight_rate	4-character decimal	Rate of GST (excludes PST) or HST charged

Req	Variable Name	Field Name	Size/Type	Description
				<p>on the shipping amount (in accordance with the Tax Treatment)</p> <p>If Freight/Shipping Amount is provided then this (National GST or HST) tax rate must be provided.</p> <p>Monetary amount, maximum is 99.99. Such as 13% HST is 13.00</p>
C	GST HST Freight Amount	gst_hst_freight_amount	9-character decimal	<p>Amount of GST (excludes PST) or HST charged on the shipping amount</p> <p>If Freight/Shipping Amount is provided then this (National GST or HST) tax amount must be provided if taxTreatment is 0 or 2</p> <p>Signed monetary amount: maximum without sign is 999999.99.</p>

Table 3 Visa - Line Item Details - Level 3 Request Fields (VSPurchl)

Req	Variable Name	Field Name	Size/Type	Description
C	Item Commodity Code	item_com_code	12-character alphanumeric	Line item Commodity Code (if this field is not sent, then productCode must be

Req	Variable Name	Field Name	Size/Type	Description
				sent)
Y	Product Code	product_code	12-character alpha-numeric	<p>Product code for this line item – merchant’s product code, manufacturer’s product code or buyer’s product code</p> <p>Typically this will be the SKU or identifier by which the merchant tracks and prices the item or service</p> <p>This should always be provided for every line item</p>
Y	Item Description	item_description	35-character alpha-numeric	Line item description
Y	Item Quantity	item_quantity	12-character decimal	<p>Quantity invoiced for this line item</p> <p>Up to 4 decimal places supported, whole numbers are accepted</p> <p>Minimum = 0.0001</p> <p>Maximum = 999999999999</p>
Y	Item Unit of Measure	item_uom	2-character alpha-numeric	<p>Unit of Measure</p> <p>Use ANSI X-12 EDI Allowable Units of</p>

Req	Variable Name	Field Name	Size/Type	Description
				Measure and Codes
Y	Item Unit Cost	unit_cost	12-character decimal	<p>Line item cost per unit</p> <p>2-4 decimal places accepted</p> <p>Minimum = 0.0001</p> <p>Maximum = 999999.9999</p>
N	VAT Tax Amount	vat_tax_amt	12-character decimal	<p>Any value-added tax or other sales tax amount</p> <p>Must have 2 decimal places</p> <p>Minimum = 0.01</p> <p>Maximum = 999999.99</p>
N	VAT Tax Rate	vat_tax_rate	4-character decimal	<p>Sales tax rate</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> 8%            PST should be 8.0         </div> <p>maximum 99.99</p>
Y	Discount Treatment	discount_treatmentL	1-character numeric	<p>Must be one of the following values:</p> <ul style="list-style-type: none"> <li>0 if no invoice level discounts apply for this invoice</li> <li>1 if Tax was calculated on Post-Discount totals</li> <li>2 if Tax was calculated</li> </ul>

Req	Variable Name	Field Name	Size/Type	Description
				on Pre-Discount totals.
C	Discount Amount	discount_amtl	12-character decimal	<p>Amount of discount, if provided for this line item according to the Line Item Discount Treatment</p> <p>Must be non-zero if Line Item Discount Treatment is 1 or 2</p> <p>Must have 2 decimal places</p> <p>Minimum = 0.01</p> <p>Maximum = 999999.99</p>

## A.6 Definition of Request Fields for Level 2/3 - Mastercard

**Table 1 Objects - Level 2/3 MasterCard**

MCCorpais Objects	Description
MCCorpac	Corporate Card Common data
MCCorpal	Line Item Details

**Table 2 MasterCard - Corporate Card Common Data (MCCorpac) - Level 2 Request Fields**

Req	Variable Name	Field Name	Size/Type	Description
N	AustinTetraNumber	Austin-Tetra Number	15-character alphanumeric	Merchant's Austin-Tetra Number
N	NaicsCode	NAICS Code	15-character alphanumeric	North American Industry Classification System (NAICS) code assigned to the merchant

Req	Variable Name	Field Name	Size/Type	Description
N	CustomerCode	Customer Code	25-character alphanumeric	A control number, such as purchase order number, project number, department allocation number or name that the purchaser supplied the merchant. Left-justified; may be spaces
N	UniqueInvoiceNumber	Unique Invoice Number	17-character alphanumeric	Unique number associated with the individual transaction provided by the merchant
N	CommodityCode	Commodity Code	15-character alphanumeric	Code assigned by the merchant that best categorizes the item(s) being purchased
N	OrderDate	Order Date	6-character numeric	The date the item was ordered. If present, must contain a valid date in the format YYMMDD.
N	CorporationVatNumber	Corporation VAT Number	20-character alphanumeric	Contains a corporation's value added tax (VAT) number
N	CustomerVatNumber	Customer VAT Number	20-character alphanumeric	Contains the VAT number for the customer/cardholder used to identify the customer when purchasing goods and services from the merchant
N	FreightAmount	Freight Amount	12-character decimal	The freight on the total purchase. Must have 2 decimals
N	DutyAmount	Duty Amount	12-character decimal	The duty on the total purchase, Must have 2 decimals
N	DestinationProvinceCode	Destination State /	3-character alphanumeric	State or Province of the country where the goods

Req	Variable Name	Field Name	Size/Type	Description
		Province Code		will be delivered. Left justified with trailing spaces. e.g., ONT - Ontario
N	DestinationCountryCode	Destination Country Code	3-character alphanumeric	The country code where goods will be delivered. Left justified with trailing spaces. e.g., CAN - Canada
N	ShipFromPosCode	Ship From Postal Code	10-character alphanumeric	The postal code or zip code from which items were shipped
N	ShipToPosCode	Destination Postal Code	10-character alphanumeric	The postal code or zip code where goods will be delivered
N	AuthorizedContactName	Authorized Contact Name	36-character alphanumeric	Name of an individual or company contacted for company authorized purchases
N	AuthorizedContactPhone	Authorized Contact Phone	17-character alphanumeric	Phone number of an individual or company contacted for company authorized purchases
N	AdditionalCardAcceptordata	Additional Card Acceptor Data	40-character alphanumeric	Information pertaining to the card acceptor
N	CardAcceptorType	Card Acceptor Type	8-character alphanumeric	Various classifications of business ownership characteristics  This field takes 8 characters. Each character represents a different component, as follows:  1st character represents 'Business Type' and contains a code to identify the specific classification or type of business:

Req	Variable Name	Field Name	Size/Type	Description
				<p>Corporation</p> <p>Not known</p> <p>Individual/Sole Proprietorship</p> <p>Partnership</p> <p>Association/Estate/Trust</p> <p>Tax Exempt Organizations (501C)</p> <p>International Organization</p> <p>Limited Liability Company (LLC)</p> <p>Government Agency</p> <p>2nd character represents 'Business Owner Type'. Contains a code to identify specific characteristics about the business owner.</p> <p>1 - No application classification</p> <p>2 - Female business owner</p> <p>3 - Physically handicapped female business owner</p> <p>4 - Physically handicapped male business owner</p> <p>0 - Unknown</p> <p>3rd character represents 'Business Certification Type'. Contains a code to identify specific characteristics about the business certification type, such as small business, disadvantaged, or other certification type:</p>

Req	Variable Name	Field Name	Size/Type	Description
				<p>1 - Not certified</p> <p>2 - Small Business Administration (SBA) certification small business</p> <p>3 - SBA certification as small disadvantaged business</p> <p>4 - Other government or agency-recognized certification (such as Minority Supplier Development Council)</p> <p>5 - Self-certified small business</p> <p>6 - SBA certification as small and other government or agency-recognized certification</p> <p>7 - SBA certification as small disadvantaged business and other government or agency-recognized certification</p> <p>8 - Other government or agency-recognized certification and self-certified small business</p> <p>A - SBA certification as 8(a)</p> <p>B - Self-certified small disadvantaged business (SDB)</p> <p>C - SBA certification as HUBZone</p> <p>0 - Unknown</p> <p>4th character represents 'Business Racial/Ethnic Type'. Contains a code identifying the racial or ethnic type of the</p>

Req	Variable Name	Field Name	Size/Type	Description
				<p>majority owner of the business.</p> <p>1 - African American</p> <p>2 - Asian Pacific American</p> <p>3 - Subcontinent Asian American</p> <p>4 - Hispanic American</p> <p>5 - Native American Indian</p> <p>6 - Native Hawaiian</p> <p>7 - Native Alaskan</p> <p>8 - Caucasian</p> <p>9 - Other</p> <p>0 - Unknown</p> <p>5th character represents 'Business Type Provided Code'</p> <p>Y - Business type is provided.</p> <p>N - Business type was not provided.</p> <p>R - Card acceptor refused to provide business type</p> <p>6th character represents 'Business Owner Type Provided Code'</p> <p>Y - Business owner type is provided.</p> <p>N - Business owner type was not provided.</p> <p>R - Card acceptor refused to provide business type</p>

Req	Variable Name	Field Name	Size/Type	Description
				<p>7th character represents 'Business Certification Type Provided Code'</p> <p>Y - Business certification type is provided.</p> <p>N - Business certification type was not provided.</p> <p>R - Card acceptor refused to provide business type</p> <p>8th character represents 'Business Racial/Ethnic Type'</p> <p>Y - Business racial/ethnic type is provided.</p> <p>N - Business racial/ethnic type was not provided.</p> <p>R - Card acceptor refused to provide business racial/ethnic type</p>
N	CardAcceptorTaxId	Card Acceptor Tax ID	20-character alphanumeric	US Federal tax ID number for value added tax (VAT) ID.
N	CardAcceptorReferenceNumber	Card Acceptor Reference Number	25-character alphanumeric	Code that facilitates card acceptor/corporation communication and record keeping
N	CardAcceptorVatNumber	Card Acceptor VAT Number	20-character alphanumeric	Value added tax (VAT) number for the card acceptor location used to identify the card acceptor when collecting and reporting taxes
C*	Tax	Tax	up to 6 arrays	Can have up to 6 arrays contains different tax

Req	Variable Name	Field Name	Size/Type	Description
				<p>details. See Tax Array below for each field description.</p> <p>*This field is conditionally mandatory — if you use this array, you must fill in all tax array fields as listed in the Tax Array Request Fields below.</p>

**Table 3 MasterCard - Line Item Details (MCCorpal) - Level 3 Request Fields**

Req	Variable Name	Field Name	Size/Type	Description
N	CustomerCode	Customer Code	25-character alphanumeric	A control number, such as purchase order number, project number, department allocation number or name that the purchaser supplied the merchant. Left-justified; may be spaces
N	LineItemDate	Line Item Date	6-character numeric	The purchase date of the line item referenced in the associated Corporate Card Line Item Detail. YYMMDD format
N	ShipDate	Ship Date	6-character numeric	The date the merchandise was shipped to the destination. YYMMDD format

Req	Variable Name	Field Name	Size/Type	Description
N	OrderDate	Order Date	6-character numeric	The date the item was ordered YYMMDD format
Y	ProductCode	Product Code	12-character alpha-numeric	Line item Product Code (if this field is not sent, then itemComCode)  If the order has a Freight/Shipping line item, the productCode value has to be "Freight/Shipping"  If the order has a Discount line item, the productCode value has to be "Discount"
Y	ItemDescription	Item Description	35-character alpha-numeric	Line Item description
Y	ItemQuantity	Item Quantity	12-character alpha-numeric	Quantity of line item
Y	UnitCost	Unit Cost	12-character decimal	Line item cost per unit.  Must contain a minimum of 2 decimal places, up to 5 decimal places supported.  Minimum amount is 0.00001 and maximum is 999999.99999
Y	ItemUnitMeasure	Item Unit Measure	12-character alpha-numeric	The line item unit of measurement code

Req	Variable Name	Field Name	Size/Type	Description
Y	ExtItemAmount	Extended Item Amount	9-character decimal	<p>Contains the individual item amount that is normally calculated as price multiplied by quantity</p> <p>Must contain 2 decimal places</p> <p>Minimum amount is 0.00 and maximum is 999999.99</p>
N	DiscountAmount	Discount Amount	9-character decimal	<p>Contains the item discount amount</p> <p>Must contain 2 decimal places</p> <p>Minimum amount is 0.00 and maximum is 999999.99</p>
N	CommodityCode	Commodity Code	15-character alphanumeric	Code assigned to the merchant that best categorizes the item (s) being purchased
C*	Tax	Tax	Up to 6 arrays	<p>Can have up to 6 arrays contains different tax details. See Tax Array below for each field description.</p> <p>*This field is conditionally mandatory — if you use this array, you must fill in all tax array fields as listed in the Tax Array Request Fields below.</p>

**Table 4 Tax Array Request Fields - MasterCard Level 2/3 Transactions**

Req	Variable Name	Field Name	Size/Type	Description
M	tax_amount	Tax Amount	12-character decimal	<p>Contains detail tax amount for purchase of goods or service</p> <p>Must be 2 decimal places</p> <p>Maximum 999999.99</p>
M	tax_rate	Tax Rate	5-character decimal	<p>Contains the detailed tax rate applied in relationship to a specific tax amount</p> <p><b>EXAMPLE:</b> 5% GST should be '5.0' or 9.975% QST should be '9.975'</p> <p>May contain up to 3 decimals, minimum 0.001, maximum up to 9999.9</p>
M	tax_type	Tax Type	4-character alpha-numeric	Contains tax type such as GST,QST,PST,HST
M	tax_id	Tax ID	20-character alpha-numeric	Provides an identification number used by the card acceptor with the tax authority in relationship to a specific tax amount such as GST/HST number
M	tax_included_in_sales	Tax included in sales indicator	1-character alpha-numeric	This is the indicator used to reflect addi-

Req	Variable Name	Field Name	Size/Type	Description
				tional tax capture and reporting.  Valid values are:  Y = Tax included in total purchase amount  N = Tax not included in total purchase amount

## A.7 Definition of Request Fields for Level 2/3 - Amex

Table 1 Amex- Level 2/3 Request Fields - Table 1 - Heading Fields

Req	Variable Name	Field Name	Size/Type	Description
C	big04	Purchase Order Number	22-character alphanumeric	The cardholder supplied Purchase Order Number, which is entered by the merchant at the point-of-sale  This entry is used in the Statement/Reporting process and may include accounting information specific to the client  Mandatory if the merchant's customer provides a Purchase Order Number
N	big05	Release Number	30-character alphanumeric	A number that identifies a release against a Purchase Order previously placed by the parties involved in the transaction
N	big10	Invoice Number	8-character alphanumeric	Contains the Amex invoice/reference number

Req	Variable Name	Field Name	Size/Type	Description												
Y	n101	Entity Identifier Code	2-character alpha-numeric	Supported values: ‘R6’ - Requester (required) ‘BG’ - Buying Group (optional) ‘SF’ - Ship From (optional) ‘ST’ - Ship To (optional) ‘40’ - Receiver (optional)												
Y	n102	Name	40-character alpha-numeric	<table border="1"> <thead> <tr> <th>n101 code</th> <th>n102 meaning</th> </tr> </thead> <tbody> <tr> <td>R6</td> <td>Requester Name</td> </tr> <tr> <td>BG</td> <td>Buying Group Name</td> </tr> <tr> <td>SF</td> <td>Ship From Name</td> </tr> <tr> <td>ST</td> <td>Ship To Name</td> </tr> <tr> <td>40</td> <td>Receiver Name</td> </tr> </tbody> </table>	n101 code	n102 meaning	R6	Requester Name	BG	Buying Group Name	SF	Ship From Name	ST	Ship To Name	40	Receiver Name
n101 code	n102 meaning															
R6	Requester Name															
BG	Buying Group Name															
SF	Ship From Name															
ST	Ship To Name															
40	Receiver Name															
N	n301	Address	40-character alpha-numeric	Address												
N	n401	City	30-character alpha-numeric	City												
N	n402	State or Province	2-character alpha-numeric	State or Province												
N	n403	Postal Code	15-character alpha-numeric	Postal Code												
Y	ref01	Reference Identification Qualifier	2-character alpha-numeric	This element may contain the following qualifiers for the corresponding occurrences of the N1Loop:												

Req	Variable Name	Field Name	Size/Type	Description												
				<table border="1"> <thead> <tr> <th>n101 value</th> <th>ref01 denotation</th> </tr> </thead> <tbody> <tr> <td>R6</td> <td>Supported values:  4C - Shipment Destination Code (mandatory)  CR - Customer Reference Number (conditional)</td> </tr> <tr> <td>BG</td> <td>n/a</td> </tr> <tr> <td>SF</td> <td>n/a</td> </tr> <tr> <td>ST</td> <td>n/a</td> </tr> <tr> <td>40</td> <td>n/a</td> </tr> </tbody> </table>	n101 value	ref01 denotation	R6	Supported values:  4C - Shipment Destination Code (mandatory)  CR - Customer Reference Number (conditional)	BG	n/a	SF	n/a	ST	n/a	40	n/a
n101 value	ref01 denotation															
R6	Supported values:  4C - Shipment Destination Code (mandatory)  CR - Customer Reference Number (conditional)															
BG	n/a															
SF	n/a															
ST	n/a															
40	n/a															
Y	ref02	Reference Identification	15-character alphanumeric	<p>VR is the Vendor ID Number, other codes describe the following:</p> <table border="1"> <thead> <tr> <th>ref01 code</th> <th>ref02 denotation</th> </tr> </thead> <tbody> <tr> <td>4C</td> <td>Ship to Zip or Canadian Postal Code (required)</td> </tr> <tr> <td>CR</td> <td>Cardmember Reference Number (optional)</td> </tr> </tbody> </table>	ref01 code	ref02 denotation	4C	Ship to Zip or Canadian Postal Code (required)	CR	Cardmember Reference Number (optional)						
ref01 code	ref02 denotation															
4C	Ship to Zip or Canadian Postal Code (required)															
CR	Cardmember Reference Number (optional)															

**Table 2 Amex - Level 2/3 Request Fields - Table 2 - Detail Fields**

Req	Variable Name	Field Name	Size/Type	Description
Y	it102	Line Item Quantity Invoiced	10-character decimal	<p>Quantity of line item.</p> <p>Up to 2 decimal places supported.</p> <p>Minimum amount is 0.0 and maximum is</p>

Req	Variable Name	Field Name	Size/Type	Description
				9999999999.
Y	it103	Unit or Basis for Measurement Code	2-character alphanumeric	<p>The line item unit of measurement code</p> <p>Must contain a code that specifies the units in which the value is expressed or the manner in which a measurement is taken</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> EA = each, E5=inches         </div> <p>See ANSI X-12 EDI Allowable Units of Measure and Codes for the list of codes</p>
Y	it104	Unit Price	15-character decimal	<p>Line item cost per unit</p> <p>Must contain 2 decimal places</p> <p>Minimum amount is 0.00 and maximum is 999999.99</p>
N	it105	Basis or Unit Price Code	2-character alphanumeric	<p>Code identifying the type of unit price for an item</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> DR = dealer, AP = advise price         </div> <p>See ASC X12 004010 Element</p>

Req	Variable Name	Field Name	Size/Type	Description								
				639 for list of codes								
N	it10618	Product/Service ID Qualifier	2-character alphanumeric	<p>Supported values:</p> <p>'MG' - Manufacturer's Part Number</p> <p>'VC' - Supplier Catalog Number</p> <p>'SK' - Supplier Stock Keeping Unit Number</p> <p>'UP' - Universal Product Code</p> <p>'VP' – Vendor Part Number</p> <p>'PO' – Purchase Order Number</p> <p>'AN' – Client Defined Asset Code</p>								
N	it10719	Product/Service ID	<table border="1"> <thead> <tr> <th>it10618</th> <th>it10719 - size/type</th> </tr> </thead> <tbody> <tr> <td>VC</td> <td>20-character alphanumeric</td> </tr> <tr> <td>PO</td> <td>22-character alphanumeric</td> </tr> <tr> <td>Other</td> <td>30-character alphanumeric</td> </tr> </tbody> </table>	it10618	it10719 - size/type	VC	20-character alphanumeric	PO	22-character alphanumeric	Other	30-character alphanumeric	<p>Product/Service ID corresponds to the preceding qualifier defined in it10618</p> <p>The maximum length depends on the qualifier defined in it10618</p>
it10618	it10719 - size/type											
VC	20-character alphanumeric											
PO	22-character alphanumeric											
Other	30-character alphanumeric											
C	txi01	Tax Type code	2-character alphanumeric	<p>Supported values:</p> <p>'CA' – City Tax (optional)</p> <p>'CT' – County/Tax (optional)</p> <p>'EV' – Environmental Tax (optional)</p> <p>'GS' – Good and Services Tax (GST) (optional)</p> <p>'LS' – State and Local</p>								

Req	Variable Name	Field Name	Size/Type	Description
				<p>Sales Tax (optional)</p> <p>'LT' – Local Sales Tax (optional)</p> <p>'PG' – Provincial Sales Tax (PST) (optional)</p> <p>'SP' – State/Provincial Tax a.k.a. Quebec Sales Tax (QST) (optional)</p> <p>'ST' – State Sales Tax (optional)</p> <p>'TX' – All Taxes (required)</p> <p>'VA' – Value-Added Tax a.k.a. Canadian Harmonized Sales Tax (HST) (optional)</p>
C	txi02	Monetary Amount	6-character decimal	<p>This element may contain the monetary tax amount that corresponds to the Tax Type Code in txi01</p> <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2fd;"> <b>NOTE:</b>            If txi02 is used in mandatory occurrence txi01=TX, txi02 must contain the total tax amount applicable to the entire invoice (transaction)            If taxes are not applicable for the entire invoice (transaction), txi02 must be 0.00.         </div> <p>The maximum value that can be entered in this field is "9999.99", which is \$9,999.99 (CAD)</p> <p>A debit is entered as: 9999.99</p>

Req	Variable Name	Field Name	Size/Type	Description
				A credit is entered as: -9999.99
C	txi03	Percent	10-character decimal	<p>Contains the tax percentage (in decimal format) that corresponds to the tax type code defined in txi01</p> <p>Up to 2 decimal places supported</p>
C	txi06	Tax Exempt Code	1-character alphanumeric	<p>This element may contain the Tax Exempt Code that identifies the exemption status from sales and tax that corresponds to the Tax Type Code in txi01</p> <p>Supported values:</p> <ul style="list-style-type: none"> <li>1 – Yes (Tax Exempt)</li> <li>2 – No (Not Tax Exempt)</li> <li>4 – Not Exempt/For Resale</li> <li>A – Labor Taxable, Material Exempt</li> <li>B – Material Taxable, Labor Exempt</li> <li>C – Not Taxable</li> <li>F – Exempt (Goods / Services Tax)</li> <li>G – Exempt (Provincial Sales Tax)</li> <li>L – Exempt Local Service</li> </ul>

Req	Variable Name	Field Name	Size/Type	Description
				R – Recurring Exempt U – Usage Exempt
Y	pam05	Line Item Extended Amount	8-character decimal	Contains the individual item amount that is normally calculated as price multiplied by quantity  Must contain 2 decimal places  Minimum amount is 0.00 and maximum is 99999.99
Y	pid05	Line Item Description	80-character alpha-numeric	Line Item description  Contains the description of the individual item purchased  This field pertain to each line item in the transaction

**Table 3 Amex - Level 2/3 Request Fields - Table 3 - Summary Fields**

Req	Variable Name	Field Name	Size/Type	Description
C	txi01	Tax Type code	2-character alpha-numeric	Supported values:  'CA' – City Tax (optional)  'CT' – County/Tax (optional)  'EV' – Environmental Tax (optional)

Req	Variable Name	Field Name	Size/Type	Description
				<p>'GS' – Good and Services Tax (GST) (optional)</p> <p>'LS' – State and Local Sales Tax (optional)</p> <p>'LT' – Local Sales Tax (optional)</p> <p>'PG' – Provincial Sales Tax (PST) (optional)</p> <p>'SP' – State/Provincial Tax a.k.a. Quebec Sales Tax (QST) (optional)</p> <p>'ST' – State Sales Tax (optional)</p> <p>'TX' – All Taxes (required)</p> <p>'VA' – Value-Added Tax a.k.a. Canadian Harmonized Sales Tax (HST) (optional)</p>
C	txi02	Monetary Amount	6-character decimal	<p>This element may contain the monetary tax amount that corresponds to the Tax Type Code in txi01</p> <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2f1;"> <b>NOTE:</b>            If txi02 is used in mandatory occurrence txi01=TX, txi02 must contain the total tax amount applicable to the entire invoice (transaction)            If taxes are not applicable for the entire invoice (transaction), txi02 must be 0.00.         </div> <p>The maximum value that can be</p>

Req	Variable Name	Field Name	Size/Type	Description
				<p>entered in this field is “9999.99”, which is \$9,999.99 (CAD)</p> <p>A debit is entered as: 9999.99</p> <p>A credit is entered as: –9999.99</p>
C	txi03	Percent	10-character decimal	<p>Contains the tax percentage (in decimal format) that corresponds to the tax type code defined in txi01</p> <p>Up to 2 decimal places supported</p>
C	txi06	Tax Exempt Code	1-character alpha-numeric	<p>Supported values:</p> <p>1 – Yes (Tax Exempt)</p> <p>2 – No (Not Tax Exempt)</p> <p>4 – Not Exempt/For Resale</p> <p>A – Labor Taxable, Material Exempt</p> <p>B – Material Taxable, Labor Exempt</p> <p>C – Not Taxable</p> <p>F – Exempt (Goods / Services Tax)</p> <p>G – Exempt (Provincial Sales Tax)</p> <p>L – Exempt Local Service</p> <p>R – Recurring Exempt</p>

Req	Variable Name	Field Name	Size/Type	Description
				U – Usage Exempt

## A.8 Definition of Request Fields – 3-D Secure 2.2

Variable Name	Type and Limits	Description
billing address	<i>String</i> 50-character alphanumeric	Cardholder billing address
BillAddress1		
billing city	<i>String</i> 50-character alphanumeric	Cardholder billing city
BillCity		
billing country	<i>String</i> 3-character alphanumeric	Defined as 3 digit country code ISO 3166-1
BillCountry		
billing postal code	<i>String</i> 16-character alphanumeric	Cardholder billing postal code
BillPostalCode		
billing province	<i>String</i> 3-character alphanumeric	Cardholder province or state
BillProvince		Defined in country subdivision ISO 3166-2
browser java enabled	<i>String</i> 1-character alphabetic	Indicates whether Java is enabled in the browser
BrowserJavaEnabled		Allowable values: T = True F = False
browser language	<i>String</i> 8-character alphanumeric	As defined in IETF BCP47
BrowserLanguage		
browser screen height	<i>String</i> 6-character numeric	Pixel height of cardholder screen
BrowserScreenHeight		
browser screen width	<i>String</i>	Pixel width of cardholder screen

Variable Name	Type and Limits	Description
BrowserScreenWidth	6-character numeric	
browser user agent	<i>String</i>	Browser User Agent
BrowserUserAgent	2048-character alphanumeric	
cardholder name	<i>String</i>	Name of the cardholder
CardholderName	45-character alphanumeric	<p><b>NOTE:</b> Accented characters are not allowable</p>
challenge window size	<i>String</i>	Relates to the rendering of the ACS challenge within the browser.
ChallengeWindowSize	2-character alphanumeric	<p>Allowable values:</p> <p>01 = 250 x 400            02 = 390 x 400            03 = 500 x 600            04 = 600 x 400            05 = Full screen</p>
cres	<i>String</i>	Response data from the challenge
CRes	200-character alphanumeric	
currency	<i>String</i>	ISO 4217 3 digit currency code (CAD = 124, USD = 840)
Currency	3-character numeric	<p><b>NOTE:</b> This field should not be sent unless Multi Currency Pricing is enabled on your merchant account</p>
DS transaction ID	<i>String</i>	Refers to the DSTransID in the response of the previous 3DS authentication.
DSTransID	36-character alphanumeric	
<b>NOTE:</b> Only used in financial		

Variable Name	Type and Limits	Description
transactions using 3rd Party 3-D Secure services.		
decoupled request async URL DecoupledRequestAsyncUrl	<i>String</i> 256-character alphanumeric	Your URL where Moneris will POST the response back from ACS. Moneris reattempts 3 times to POST the response.
decoupled request indicator DecoupledRequestIndicator	<i>String</i> 1-character alphabetic	Whether the request utilizes Decoupled Authentication or not, if the ACS confirms its use.  Y = Decoupled Authentication is supported and preferred if challenge is necessary  N = Do not use Decoupled Authentication (Default)
decoupled request max time DecoupledRequestMaxTime	<i>String</i> 5-character numeric	The maximum minutes that Moneris waits for an ACS to provide results.  Numeric values between 1 and 10080. The max is equivalent to 7 days.
device channel DeviceChannel	<i>String</i> 2-character numeric	The interface used to initiate the authentication:  02 = Browser (BRW)  03 = 3DS Requestor Initiated (3RI)
email Email	<i>String</i> 254-character alphanumeric	Cardholder email address  <b>NOTE:</b> This field is not mandatory, but it is required. It is highly recommended to provide the cardholder's email address. Lack of providing the cardholder's address, might increase the risk of rejects.
message category	<i>String</i>	Whether the authentication request is for a payment or non-payment

Variable Name	Type and Limits	Description
MessageCategory	2-character numeric	use: 01 = payment authentication (PA) 02 = non-payment authentication (NPA)
notification URL NotificationURL	<i>String</i> 256-character alpha-numeric	Notification URL for receiving the 3DS Method POST response from the issuer ACS.
prior request ref prior_request_auth_ref	<i>String</i> 36-character alphanumeric	Refers to the 3DS ACS Transaction ID in the response of the previous 3DS authentication.
prior request auth method prior_request_auth_method	<i>String</i> 2-character numeric	Mechanism used by the cardholder to authenticate in the previous 3DS authentication:  01 = Frictionless authentication 02 = Challenge authentication 03 = AVS verified 04 = Other issuer methods
prior request auth timestamp prior_request_auth_timestamp	<i>String</i> 12-character numeric	Date and time in UTC of the prior cardholder authentication. Found in the previous 3DS authentication response as 3DS Auth TimeStamp.  Format is YYYYMMDDHHMM.
recurring expiry RecurringExpiry	<i>String</i> 8-character numeric	End date after which no further recurring transactions shall be performed. Format is YYYYMMDD.
recurring frequency RecurringFrequency	<i>String</i> 4-character numeric	The minimum number of days between recurring transactions. Numeric values between 1 and 9999, leading zeroes accepted.
request challenge	<i>String</i>	Indicates whether a browser-based challenge is requested for this trans-

Variable Name	Type and Limits	Description
RequestChallenge	2-character numeric	<p>action. Standard is “01”</p> <ul style="list-style-type: none"> <li>• 01 = No preference</li> <li>• 02 = No challenge requested</li> <li>• 03 = Challenge requested: 3DS Requestor Preference</li> <li>• 04 = Challenge requested: Mandate</li> </ul>
request type RequestType	<i>String</i> 2-character alphanumeric	<p>Indicates the type of browser-based authentication request:</p> <p>01 = cardholder initiated payment 02 = recurring transaction</p>
shipping address ShipAddress1	<i>String</i> 50-character alphanumeric	Shipping destination address
ri indicator RiIndicator	<i>String</i> 2-character numeric	<p>The type of 3DS Requestor Initiated (3RI) request:</p> <p><b>NOTE:</b> Visa Secure only support ri_Indicator = 6 or 11 for Payment Transaction and ri Indicator = 3, 4, 5 and 10 for Non Payment Transaction</p> <ul style="list-style-type: none"> <li>01 = Recurring</li> <li>02 = Installment</li> <li>03 = Add Card</li> <li>04 = Maintain Card Information</li> <li>05 = Account verification</li> <li>06 = Split/Delayed Shipment</li> <li>07 = Top-up</li> <li>08 = Mail Order</li> <li>09 = Telephone Order</li> <li>10 = Whitelist</li> </ul>

Variable Name	Type and Limits	Description
		11 = Other Payment
shipping city	<i>String</i>	Shipping destination city
ShipCity	50-character alphanumeric	
shipping country	<i>String</i>	Shipping destination country
ShipCountry	3-character alphanumeric	Defined as 3-digit country code in ISO 3166-1
shipping postal code	<i>String</i>	Shipping destination postal or ZIP code
ShipPostalCode	16-character alphanumeric	
shipping province	<i>String</i>	Shipping destination province
ShipProvince	3-character alphanumeric	Defined in country subdivision ISO 3166-2
3DS completion indicator	<i>String</i>	indicates whether 3ds method MpiCardLookup was successfully completed
ThreeDSCompletionInd	1-character alphanumeric	<p>Allowable values:</p> <p>Y = Successfully completed</p> <p>N = Did not successfully complete</p> <p>U = Unavailable</p>

## A.9 Definition of Request Fields – PBB Info Object

This table includes fields for the Pay by Bank object pbblInfo included in financial authorization transactions, such as a Purchase or Preauthorization. This object contains the necessary fields to link the authorization to the consent

For the fields used Pay By Bank authentication calls (Get Access Token, Get Consent Data, and Get Payment Transaction Data), refer to "Definition of Request Fields – Pay By Bank" on the facing page.

Variable Name	Type and Limits	Description
Consent ID	<i>String</i>	Consent token obtained from the Interac Konek SDK. Used to authenticate PBB connections.
ConsentId	36-character alphanumeric,	

Variable Name	Type and Limits	Description
	variable	
Payment Method	<i>String</i>	The type of account for the payment
PaymentMethod	27-character alphanumeric, variable	BANK_ACCOUNT_SAVINGS, BANK_ACCOUNT_CHEQUING, BANK_ACCOUNT_LINE_OF_CREDIT, VISA_CREDIT, VISA_DEBIT, MASTERCARD_CREDIT, MASTERCARD_DEBIT, AMEX_CREDIT

## A.10 Definition of Request Fields – Pay By Bank

This table includes fields for the Get Access Token, Get Consent Data, and Get Payment Transaction Data API calls used in the authentication flow for a Pay By Bank transaction.

For the fields used in the pbblInfo object of a financial transaction, such as a Purchase or Preauthorization, refer instead to "Definition of Request Fields – PBB Info Object" on the previous page

Variable Name	Type and Limits	Description
Amount amount	<i>Number</i>  10-character numeric, variable  minimum: 0.01  maximum: 9999999.99	Amount for use in subsequent financial transaction.
Consent ID ConsentId	<i>String</i>  36-character alphanumeric, variable	Consent token obtained from the Interac Konek SDK. Used to authenticate PBB connections.
Currency currency	<i>String</i>  3-character alphanumeric	ISO 4217 currency code used for the payment. Possible values  CAD
Transaction Type transaction_type	<i>String</i>  9-character alphaumeric, variable	Transaction types.  Enums: SINGLE, SPLIT, RECURRING

## A.11 Definition of Request Fields – MCP

Variable Name	Type and Limits	Description
MCP version number	<i>String</i> numeric current version is 1.0	Release version number for MCP
cardholder amount	<i>String</i> 12-character numeric smallest discrete unit of foreign currency	Amount, in units of foreign currency, the cardholder will be charged on the transaction
cardholder currency code	<i>String</i> 3-character numeric	ISO code representing the foreign currency of the cardholder

### Optional MCP fields

Variable Name	Type and Limits	Description
MCP rate token	<i>String</i> N/A	Token representing a temporarily locked-in foreign exchange rate, obtained in the response of the MCP Get Rate transaction and used in subsequent MCP financial transaction requests in order to redeem that rate

### MCP Get Rate transaction request fields

Variable Name	Type and Limits	Description
MCP version number	<i>String</i> numeric current version is 1.0	Release version number for MCP
rate transaction type	<i>String</i> 1-character alphabetic	Value representing the type of subsequent transaction request that the rate token will be used for.  Allowable values:  A

Variable Name	Type and Limits	Description
		P – Purchase  R – Refund
MCP Rate Info	<i>Object</i>  N/A	Nested object in the MCP Get Rate transaction containing the <b>add cardholder amount</b> and <b>add merchant settlement</b> fields

### MCP Rate Info object request fields

At least one of the following variables must be sent:

Variable Name	Type and Limits	Description
add cardholder amount	<i>String array</i>  12-character numeric, 3-character numeric  (smallest discrete unit of foreign currency, currency code)	A string array representing: <ul style="list-style-type: none"><li>• the amount, in units of foreign currency, the cardholder will be charged, and</li><li>• the ISO currency code corresponding to the foreign currency of the cardholder</li></ul>
add merchant settlement amount	<i>String array</i>  12-character numeric, 3-character numeric  (amount in CAD pennies, currency code)	A string array representing: <ul style="list-style-type: none"><li>• the amount the merchant will receive in the transaction, in Canadian dollars</li><li>• the ISO currency code corresponding to the foreign currency of the cardholder</li></ul>

## A.12 Definition of Request Fields – Offlinx™

Applies to Offlinx™ integration only

Variable Name	Type and Limits	Description
card match ID	<i>String</i> 50-character alphanumeric	Corresponds to the Transaction ID used for the Offlinx™ Card Match Pixel Tag, a unique identifier created by the merchant  Must be unique value for each transaction

## A.13 Definition of Request Fields – Convenience Fee

Variable Name	Type and Limits	Description
Convenience Fee Information	<i>Object</i> N/A	Contains fields related to the Convenience Fee feature
convenience fee amount	<i>String</i> 9-character decimal	Dollar amount charged to the customer as a convenience fee

## A.14 Definition of Request Fields – Recurring

### Recurring Billing Info Object Request Fields

Variable Name	Type and Limits	Description
number of recurs	<i>String</i> numeric 1-999	The number of times that the transaction must recur
period	<i>String</i> numeric 1-999	Number of recur unit intervals that must pass between recurring billings
start date	<i>String</i> YYYYMMDD format	Date of the first future recurring billing transaction; this must be a date in the future  If an additional charge will be made

Variable Name	Type and Limits	Description
start now	<p><i>String</i></p> <p>true/false</p>	<p>immediately, the start now variable must be set to true</p> <p>Set to true if a charge will be made against the card immediately; otherwise set to false</p> <p>When set to false, use Card Verification prior to sending the Purchase with Recurring Billing and Credential on File objects</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> Amount to be billed immediately can differ from the subsequent recurring amounts         </div>
recurring amount	<p><i>String</i></p> <p>10-character decimal, minimum three digits</p> <p>Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point</p> <div style="background-color: #e0f2e0; border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> 1234567.89         </div>	<p>Dollar amount of the recurring transaction</p> <p>This amount will be billed on the start date, and then billed repeatedly based on the interval defined by period and recur unit</p>
recur unit	<p><i>String</i></p> <p>day, week, month or eom</p>	<p>Unit to be used as a basis for the interval</p> <p>Works in conjunction with the period variable to define the billing frequency</p>

## A.15 Definition of Request Fields – Installments by Visa

Variable Name	Type and Limits	Description
Installment Info	<p><i>Object</i></p> <p>N/A</p>	Contains request fields related to installments

Variable Name	Type and Limits	Description
installment plan ID	<i>String</i>  36-character alphanumeric  fixed length	Card brand-generated identifier for an installment plan
installment plan reference	<i>String</i>  10-character alphanumeric  fixed length	Unique, human friendly name for the installment plan
terms and conditions version	<i>String</i>  10-character alphanumeric  variable length (1-10 characters)	Version of the terms and conditions of the installment plan accepted by the cardholder  The version is auto-incremented every time an update is made to the plan by the issuer

## Appendix B Definitions of Response Fields

Table 28: Receipt object response values

Value	Type	Limits	Get Method
	Description		
<b>General response fields</b>			
Card type	String	2-character alphabetic (min. 1)	<code>receipt.getCardType();</code>
<p>Represents the type of card in the transaction, e.g., Visa, Mastercard.</p> <p>Possible values:</p> <ul style="list-style-type: none"> <li>• V = Visa</li> <li>• M = Mastercard</li> <li>• AX = American Express</li> <li>• DC = Diner's Card</li> <li>• NO = Novus/Discover</li> <li>• SE = Sears</li> <li>• D = Debit</li> <li>• C1 = JCB</li> </ul>			
Transaction amount	String	10-character decimal Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> 1234567.89         </div>	<code>receipt.getTransAmount();</code>
Transaction amount that was processed.			

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Transaction number	String	255-character alphanumeric	<code>receipt.getTxnNumber();</code>
Gateway Transaction identifier often needed for follow-on transactions (such as Refund and Purchase Correction) to reference the originally processed transaction.			
Receipt ID	String	50-character alphanumeric	<code>receipt.getReceiptId();</code>
Order ID that was specified in the transaction request.			
Transaction type	String	2-character alphanumeric	<code>receipt.getTransType();</code>
<ul style="list-style-type: none"> <li>• 0 = Purchase</li> <li>• 1 = Pre-Authorization</li> <li>• 2 = Completion</li> <li>• 4 = Refund</li> <li>• 11 = Void</li> </ul>			

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Reference number	String	18-character numeric	<code>receipt.getReferenceNum();</code>
		Terminal used to process the transaction as well as the shift, batch and sequence number. This data is typically used to reference transactions on the host systems, and must be displayed on any receipt presented to the customer.  This information is to be stored by the merchant.  Example: 660123450010690030 <ul style="list-style-type: none"> <li>• 66012345: Terminal ID</li> <li>• 001: Shift number</li> <li>• 069: Batch number</li> <li>• 003: Transaction number within the batch.</li> </ul>	
Response code	String	3-character numeric	<code>receipt.getResponseCode();</code>
		<ul style="list-style-type: none"> <li>• &lt; 50: Transaction approved</li> <li>• ≥ 50: Transaction declined</li> <li>• Null: Transaction incomplete.</li> </ul> For further details on the response codes that are returned, see the Response Codes document at <a href="https://developer.moneris.com">https://developer.moneris.com</a> .	
ISO	String	2-character numeric	<code>receipt.getISO();</code>
	ISO response code		
Bank totals	Object		<code>receipt.getBankTotals();</code>
	Response data returned in a Batch Close and Open Totals request. See "Definitions of Response Fields" on page 563.		

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Message	String	100-character alphanumeric	<code>receipt.getMessage();</code>
Response description returned from issuer. The message returned from the issuer is intended for merchant information only, and is <b>not</b> intended for customer receipts.			
Authorization code	String	8-character alphanumeric	<code>receipt.getAuthCode();</code>
Authorization code returned from the issuing institution.			
Complete	String	true/false	<code>receipt.getComplete();</code>
Transaction was sent to authorization host and a response was received			
Transaction date	String	Format: yyyy-mm-dd	<code>receipt.getTransDate();</code>
Processing host date stamp			
Transaction time	String	Format: ##:##:##	<code>receipt.getTransTime();</code>
Processing host time stamp			
Ticket	String	N/A	<code>receipt.getTicket();</code>
Reserved field.			
Timed out	String	true/false	<code>receipt.getTimedOut();</code>
Transaction failed due to a process timing out.			
Is Visa Debit	String	true/false	<code>receipt.getIsVisaDebit();</code>
Indicates whether the card processed is a Visa Debit.			
<b>Batch Close/Open Totals response fields</b>			
Processed card types	String Array	N/A	<code>receipt.getCreditCards(ecr_no);</code>
Returns all of the processed card types in the current batch for the terminal ID/ECR Number from the request.			
Terminal IDs	String	8-character alphanumeric	<code>receipt.getTerminalIDs();</code> code to come
Returns the terminal ID/ECR Number from the request.			

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Purchase count	String	4-character numeric	<code>receipt.getPurchaseCount(ecr, cardType);</code>
Indicates the # of Purchase, Pre-Authorization Completion and Force Post transactions processed. If none were processed in the batch, then the value returned will be 0000.			
Purchase amount	String	11-character alpha-numeric	<code>receipt.getPurchaseAmount(ecr, cardType);</code>
Indicates the dollar amount processed for Purchase, Pre-Authorization Completion or Force Post transactions. This field begins with a + and is followed by 10 numbers, the first 8 indicate the amount and the last 2 indicate the penny value.			
<b>EXAMPLE:</b> +0000000000 = 0.00 and +0000041625 = 416.25			
Refund count	String	4-character numeric	<code>receipt.getRefundCount(ecr, cardType);</code>
Indicates the # of Refund or Independent Refund transactions processed. If none were processed in the batch, then the value returned will be 0000.			
Refund amount	String	11-character alpha-numeric	<code>receipt.getRefundAmount(ecr, cardType);</code>
Indicates the dollar amount processed for Refund, Independent Refund or ACH Credit transactions. This field begins with a + and is followed by 10 numbers, the first 8 indicate the amount and the last 2 indicate the penny value.			
Example, +0000000000 = 0.00 and +0000041625 = 416.25			
Correction count	String	4-character numeric	<code>receipt.getCorrectionCount(ecr, cardType);</code>
Indicates the # of Purchase Correction transactions processed. If none were processed in the batch, then the value returned will be 0000.			

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Correction amount	String	11-character alpha-numeric	<code>receipt.getCorrectionAmount(ecr, cardType);</code>
Indicates the dollar amount processed for Purchase Correction transactions. This field begins with a + and is followed by 10 numbers, the first 8 indicate the amount and the last 2 indicate the penny value.			
<b>EXAMPLE:</b> +0000000000 = 0.00 and +0000041625 = 416.25			
<b>Recurring Billing Response Fields (see Appendix A, page 1)</b>			
Recurring billing success	String	true/false	<code>receipt.getRecurSuccess();</code>
Indicates whether the recurring billing transaction has been successfully set up for future billing.			
Recur update success	String	true/false	<code>receipt.getRecurUpdateSuccess();</code>
Indicates recur update success.			
Next recur date	String	yyyy-mm-dd	<code>receipt.getNextRecurDate();</code>
Indicates next recur billing date.			
Recur end date	String	yyyy-mm-dd	<code>receipt.getRecurEndDate();</code>
Indicates final recur billing date.			
<b>Status Check response fields (see )</b>			
Status code	String	3-character alpha-numeric	<code>receipt.getStatusCode();</code>
<ul style="list-style-type: none"> <li>• &lt; 50: Transaction found and successful</li> <li>• ≥ 50: Transaction not found and not successful</li> </ul>			
<b>NOTE:</b> the status code is only populated if the connection object's Status Check property is set to true.			

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Status message	String	found/not found	<code>receipt.getStatusMessage();</code>  <ul style="list-style-type: none"> <li>• Found: <math>0 \leq \text{Status Code} \leq 49</math></li> <li>• Not Found or null: <math>50 \leq \text{Status Code} \leq 999</math>.</li> </ul> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>NOTE:</b> The status message is only populated if the connection object's Status Check property is set to <b>true</b>.         </div>
<b>AVS response fields (see 10.1, page 403)</b>			
AVS result code	String	1-character alpha-numeric	<code>receipt.getAvsResultCode();</code>  Indicates the address verification result. For a full list of possible response codes refer to Section Appendix B.
<b>CVD response fields (see )</b>			
CVD result code	String	2-character alpha-numeric	<code>receipt.getCvdResultCode();</code>  Indicates the CVD validation result. The first byte is the numeric CVD indicator sent in the request; the second byte is the response code. Possible response codes are shown in Appendix B
<b>MPI response fields (see "MPI" on page 1)</b>			
Type	String	99-character alpha-numeric	  VERes, PARes or error defines what type of response you are receiving .
Success	Boolean	true/false	<code>receipt.getMpiSuccess();</code>  True if attempt was successful, false if attempt was unsuccessful.

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Message	String	100-character alphabetic	<code>receipt.getMpiMessage();</code>
<p>MPI TXN transactions can produce the following values:</p> <ul style="list-style-type: none"> <li>• Y: Create VBV verification form popup window.</li> <li>• N: Send purchase or preauth with crypt type 6</li> <li>• U: Send purchase or preauth with crypt type 7.</li> </ul> <p>MPI ACS transactions can produce the following values:</p> <ul style="list-style-type: none"> <li>• Y or A: (Also <code>receipt.getMpiSuccess()=true</code>) Proceed with cavv purchase or cavv preauth.</li> <li>• N: Authentication failed or high-risk transaction. It is recommended that you do not proceed with the transaction.</li> </ul> <p>Depending on a merchant's risk tolerance and results from other methods of fraud detection, transaction may proceed with crypt type 7.</p> <ul style="list-style-type: none"> <li>• U or time out: Send purchase or preauth as crypt type 7.</li> </ul>			
Term URL	String	255-character alphanumeric	URL to which the PARes is returned
MD	String	1024-character alphanumeric	Merchant-defined data that was echoed back
ACS URL	String	255-character alphanumeric	URL that will be for the generated pop-up
MPI CAVV	String	28-character alphanumeric	<code>receipt.getMpiCavv();</code> VbV/MCSC/American Express SafeKey authentication data
MPI E-Commerce Indicator	String	1-character alphanumeric	<code>receipt.getMPIEci();</code>

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
CAVV result code	String	1-character alpha-numeric	<code>receipt.getCAVVResultCode();</code>
Indicates the Visa CAVV result. For more information, see <a href="#">1 Cavv Result Codes for Verified by Visa</a> . <ul style="list-style-type: none"> <li>• 0 = CAVV authentication results invalid</li> <li>• 1 = CAVV failed validation; authentication</li> <li>• 2 = CAVV passed validation; authentication</li> <li>• 3 = CAVV passed validation; attempt</li> <li>• 4 = CAVV failed validation; attempt</li> <li>• 7 = CAVV failed validation; attempt (US issued cards only)</li> <li>• 8 = CAVV passed validation; attempt (US issued cards only)</li> <li>• The CAVV result code indicates the result of the CAVV validation.</li> </ul>			
MPI inline form			<code>receipt.getMpiInLineForm();</code>
<b>Vault response fields (see <a href="#">4.1, page 63</a>)</b>			
Data key	String	28-character alpha-numeric	<code>receipt.getDataKey();</code>
	The data key response field is populated when you send a Vault Add Credit Card – ResAddCC (page 66), Vault Encrypted Add Credit Card – EncResAddCC (page 70), Vault Tokenize Credit Card – ResTokenizeCC (page 95), Vault Temporary Token Add – ResTempAdd (page 73) or Vault Add Token – ResAddToken (page 91) transaction. It is the profile identifier that all future financial Vault transactions will use to associate with the saved information.		
Vault payment type	String	cc	<code>receipt.getPaymentType();</code>
	Indicates the payment type associated with a Vault profile		

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Expiring card's Payment type	String	cc	<code>receipt.getExpPaymentType();</code>
	Indicates the payment type associated with a Vault profile. Applicable to Vault Get Expiring transaction type.		
Vault masked PAN	String	20-character numeric	<code>receipt.getResMaskedPan();</code>
	Returns the first 4 and/or last 4 of the card number saved in the profile.		
Expiring card's Masked PAN	String	20-character numeric	<code>receipt.getExpMaskedPan();</code>
	Returns the first 4 and/or last 4 of the card number saved in the profile. Applicable to Vault Get Expiring transaction type.		
Vault success	String	true/false	<code>receipt.getResSuccess();</code>
	Indicates whether Vault transaction was successful.		
Vault customer ID	String	30-character alphanumeric	<code>receipt.getResCustId();</code>
	Returns the customer ID saved in the profile.		
Expiring card's customer ID	String	30-character alphanumeric	<code>receipt.getExpCustId();</code>
	Returns the customer ID saved in the profile. Applicable to Vault Get Expiring transaction type.		
Vault phone number	String	30-character alphanumeric	<code>receipt.getResPhone();</code>
	Returns the phone number saved in the profile.		
Expiring card's phone number	String	30-character alphanumeric	<code>receipt.getExpPhone();</code>
	Returns the phone number saved in the profile. Applicable to Vault Get Expiring transaction type.		

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Vault email address	String	30-character alpha-numeric	<code>receipt.getResEmail();</code>  Returns the email address saved in the profile.
Expiring card's email address	String	30-character alpha-numeric	<code>receipt.getExpEmail();</code>  Returns the email address saved in the profile. Applicable to Vault Get Expiring transaction type.
Vault note	String	30-character alpha-numeric	<code>receipt.getResNote();</code>  Returns the note saved in the profile.
Expiring card's note	String	30-character alpha-numeric	<code>receipt.getExpNote();</code>  Returns the note saved in the profile. Applicable to Vault Get Expiring transaction type.
Vault expiry date	String	4-character numeric	<code>receipt.getResExpdate();</code>  Returns the expiry date of the card number saved in the profile. YYMM format.
Expiring card's expiry date	String	4-character numeric	<code>receipt.getExpExpdate();</code>  Returns the expiry date of the card number saved in the profile. YYMM format. Applicable to Vault Get Expiring transaction type.
Vault E-commerce indicator	String	1-character numeric	<code>receipt.getResCryptType();</code>  Returns the e-commerce indicator saved in the profile.
Expiring card's E-commerce indicator	String	1-character numeric	<code>receipt.getExpCryptType();</code>  Returns the e-commerce indicator saved in the profile. Applicable to Vault Get Expiring transaction type.

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Vault AVS street number	String	19-character alpha-numeric	<code>receipt.getResAvsStreetNumber();</code>
		Returns the AVS street number saved in the profile. If no other AVS street number is passed in the transaction request, this value will be submitted along with the financial transaction to the issuer.	
Expiring card's AVS street number	String	19-character alpha-numeric	<code>receipt.getExpAvsStreetNumber();</code>
		Returns the AVS street number saved in the profile. If no other AVS street number is passed in the transaction request, this value will be submitted along with the financial transaction to the issuer. Applicable to Vault Get Expiring transaction type.	
Vault AVS street name	String	19-character alpha-numeric	<code>receipt.getResAvsStreetName();</code>
		Returns the AVS street name saved in the profile. If no other AVS street number is passed in the transaction request, this value will be submitted along with the financial transaction to the issuer.	
Expiring card's AVS street name	String	19-character alpha-numeric	<code>receipt.getExpAvsStreetName();</code>
		Returns the AVS street name saved in the profile. If no other AVS street number is passed in the transaction request, this value will be submitted along with the financial transaction to the issuer. Applicable to Vault Get Expiring transaction type.	
Vault AVS ZIP code	String	9-character alpha-numeric	<code>receipt.getResAvsZipcode();</code>
		Returns the AVS zip/postal code saved in the profile. If no other AVS street number is passed in the transaction request, this value will be submitted along with the financial transaction to the issuer.	
Expiring card's AVS ZIP code	String	9-character alpha-numeric	<code>receipt.getExpAvsZipcode();</code>
		Returns the AVS zip/postal code saved in the profile. If no other AVS street number is passed in the transaction request, this value will be submitted along with the financial transaction to the issuer. Applicable to Vault Get Expiring transaction type.	

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Vault credit card number	String	20-character numeric	<code>receipt.getResPan();</code>
	Returns the full credit card number saved in the Vault profile. Applicable to Vault Lookup Full transaction only.		
Corporate card	String	true/false	<code>receipt.getCorporateCard();</code>
	Indicates whether the card associated with the Vault profile is a corporate card.		
<b>Encrypted Mag Swipe response fields (see Section 1, page 1)</b>			
Masked credit card number	String	20-character alpha-numeric	<code>receipt.getMaskedPan();</code>
<b>Convenience Fee response fields (see Appendix A, page 1)</b>			
Convenience fee success	String	true/false	<code>receipt.getCFSuccess();</code>
	Indicates whether the Convenience Fee transaction processed successfully.		

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Convenience fee status	String	3-character alpha-numeric	<code>receipt.get CfStatus();</code>
		Indicates the status of the merchant and convenience fee transactions. The CfStatus field provides details about the transaction behavior and should be referenced when contacting Moneris Customer Support.  Possible values are: <ul style="list-style-type: none"><li>• 1 or 1F – Completed 1st purchase transaction</li><li>• 2 or 2F – Completed 2nd purchase transaction</li><li>• 3 – Completed void transaction</li><li>• 4A or 4D – Completed refund transaction</li><li>• 7 or 7F – Completed merchant independent refund transaction</li><li>• 8 or 8F – Completed merchant refund transaction</li><li>• 9 or 9F – Completed 1st void transaction</li><li>• 10 or 10F – Completed 2nd void transaction</li><li>• 11A or 11D – Completed refund transaction</li></ul>	
Convenience fee amount	String	9-character decimal	<code>receipt.getFeeAmount();</code>
		The expected Convenience Fee amount. This field will return the amount submitted by the merchant for a successful transaction. For an unsuccessful transaction, it will return the expected convenience fee amount	

**Table 28: Receipt object response values (continued)**

Value	Type	Limits	Get Method
	Description		
Convenience fee rate	String	9-character decimal	<code>receipt.getFeeRate();</code>
<p>The convenience fee rate that has been defined on the merchant's profile. For example:</p> <p>1.00 – a fixed amount or</p> <p>10.0 - a percentage amount</p>			
Convenience fee type	String	AMT/PCT	<code>receipt.getFeeType();</code>
<p>The type of convenience fee that has been defined on the merchant's profile.</p> <p>Available options are:</p> <p>AMT – fixed amount</p> <p>PCT – percentage</p>			
Merchant Advice Code response field			
Advice Code	String	2-character alpha-numeric	<code>receipt.getAdviceCode();</code>
<p>The message returned from the issuer is intended for merchant information only, and is not intended for customer receipts.</p> <p>For further details on the response codes that are returned, see the Advice Code document at <a href="https://developer.moneris.com">https://developer.moneris.com</a>.</p>			

**Table 29: Financial transaction response codes**

Code	Description
< 50	Transaction approved
≥ 50	Transaction declined
NULL	Transaction was not sent for authorization

For more details on the response codes that are returned, see the Response Codes document available at <https://developer.moneris.com>

**Table 30: Vault Admin Responses**

<b>Code</b>	<b>Description</b>
001	Successfully registered CC details. Successfully updated CC details. Successfully deleted CC details. Successfully located CC details. Successfully located # expiring cards. (NOTE: # = the number of cards located)
983	Cannot find previous
986	Incomplete: timed out
987	Invalid transaction
988	Cannot find expiring cards
Null	Error: Malformed XML

## B.1 Definition of Response Fields – 3-D Secure

The following response fields are specific to 3-D Secure transactions

<b>Variable Name</b>	<b>Type and Limits</b>	<b>Description</b>
Cardholder Authentication Value (CAVV)	<i>String</i> 50-character alphanumeric	receipt.getMpiCavv()  Cardholder Authentication Value, to be provided in the financial request
challenge completion indicator	<i>String</i> 1-character alphabetic	receipt.getMpiChallengeCompletionIndicator()  Indicates the result of the challenge request <ul style="list-style-type: none"> <li>• Y = challenge complete</li> </ul>

Variable Name	Type and Limits	Description
		<ul style="list-style-type: none"> <li>• N = challenge not complete</li> <li>• null = field not present</li> </ul>
challenge URL	<i>String</i> 2048-character alphanumeric	<code>receipt.getMpiChallengeURL()</code> If the transaction status is “C” this field will be populated with the URL to POST the challenge data to create the cardholder challenge screen.
message type	<i>String</i> alphanumeric	<code>receipt.getMpiMessageType()</code> Denotes the request message EMV nomenclature “ARES”
3DS method URL	<i>String</i> alphanumeric	<code>receipt.getMpiThreeDSMethodURL()</code> Device fingerprinting endpoint
3DS method data	<i>String</i> alphanumeric	<code>receipt.getMpiThreeDSMethodData()</code> Data that must be posted to 3DS Method URL
3DS server transaction ID	<i>String</i> <b>36-character alphanumeric</b>	<code>receipt.getMpiThreeDSServerTransId()</code> 3-D Secure unique transaction identifier
3DS version	<i>String</i> 10-character numeric	<code>receipt.getThreeDSVersion();</code>
transaction status	<i>String</i> 1-character alphabetic	<code>receipt.getMpiTransStatus()</code> Indicates the result of the authentication. See 3DS TransStatus in the appendix for a full list: <ul style="list-style-type: none"> <li>• Y or A = successful authentication</li> <li>• C = proceed with challenge</li> </ul>

Variable Name	Type and Limits	Description
		<ul style="list-style-type: none"> <li>D = wait for decoupled authentication</li> </ul>
challenge data	alphanumeric	If the transStatus is "C" this field will be populated with the data to post the challengeURL. The data must be posted in a field with the name "creq".
ECI	1-character alphabetic	Crypt Type to be provided in the financial request.  If transaction status is "Y" or "A" this value will return in the response. The ECI is used by subsequent financial transactions.
DS trans ID	36-character alphanumeric	Universally unique transaction identifier assigned by the 3DS Directory Server (DS) to identify a single transaction.
transaction status reason	2-character numeric	<p>Provides additional information on why the TransStatus field has the specified value.</p> <p>Possible values:</p> <ul style="list-style-type: none"> <li>01 = Card authentication failed</li> <li>02 = Unknown Device</li> <li>03 = Unsupported Device</li> <li>04 = Exceeds authentication frequency limit</li> <li>05 = Expired card</li> <li>06 = Invalid card number</li> <li>07 = Invalid transaction</li> <li>08 = No Card record</li> <li>09 = Security failure</li> <li>10 = Stolen card</li> </ul>

Variable Name	Type and Limits	Description
		<ul style="list-style-type: none"> <li>• 11 = Suspected fraud</li> <li>• 12 = Transaction not permitted to cardholder</li> <li>• 13 = Cardholder not enrolled in service</li> <li>• 14 = Transaction timed out at the ACS</li> <li>• 15 = Low confidence</li> <li>• 16 = Medium confidence</li> </ul>
cardholder information	128-character alphanumeric	Text provided by the ACS/Issuer to Cardholder during a Frictionless or Decoupled transaction. This provides information to the cardholder. For example, “Additional authentication is needed for this transaction, please contact (Issuer Name) at xxx-xxx-xxxx.”
Authentication-Type	2-character numeric	<p>Authentication method the issuer will use to challenge the cardholder.</p> <ul style="list-style-type: none"> <li>• 01 = Static</li> <li>• 02 = Dynamic</li> <li>• 03 = OOB</li> <li>• 04 = Decoupled</li> </ul>
3DS ACS Transaction ID	36-character alphanumeric	Universally Unique transaction identifier assigned by the issuer Access Control Server (ACS) to identify a single transaction.
3DS Auth TimeStamp	12-character numeric	<p>Date and time in UTC of the cardholder authentication. Date format = YYYYMMDDHHMM</p>

## B.2 Definition of Response Fields – MCP

### MCP response fields

Variable Name	Type and Limits	Get Method and Description
MCP rate	<p><i>String</i></p> <p>9-character decimal variable length</p>	<pre>receipt.getMCPRate();</pre> <p>The foreign exchange rate (foreign currency to CAD) that will be used for the transaction</p> <p>If a <b>MCP rate token</b> was used, it will reflect the rate secured by the MCP Get Rate transaction; if no token was used, the rate is the current exchange rate retrieved by the Moneris Gateway</p>
merchant settlement currency	<p><i>String</i></p> <p>3-character numeric</p>	<pre>receipt.getMerchantSettlementCurrency();</pre> <p>Currency that the merchant is settling in</p>
merchant settlement amount	<p><i>String</i></p> <p>10-character decimal</p> <p>Up to 7 digits (dollars) + decimal point (.) + 2 digits (cents) after the decimal point</p>	<pre>receipt.getMerchantSettlementAmount();</pre> <p>Amount that will be paid to the merchant, in Canadian dollars</p> <p><b>EXAMPLE:</b> 1234567.89</p>
cardholder currency code	<p><i>String</i></p> <p>3-character numeric</p>	<pre>receipt.getCardholderCurrencyCode();</pre> <p>ISO code for the foreign currency the cardholder is using to pay</p>
cardholder amount	<p><i>String</i></p> <p>12-character numeric variable length</p>	<pre>receipt.getCardholderAmount();</pre> <p>Amount, in units of foreign currency, the cardholder will pay on the transaction</p>
MCP error status	<i>String</i>	<pre>receipt.getMCPErrorStatusCode();</pre>

Variable Name	Type and Limits	Get Method and Description
code	4-character numeric variable length	A number representing a MCP error code response
MCP error message	<i>String</i>  250-character alpha- numeric  variable length	<code>receipt.getMCPErrorMessage();</code>  Message corresponding with an MCP error code
host ID	<i>String</i>  15-character alpha- numeric	<code>receipt.getHostId();</code>  Unique identifier used across the Moneris platform

#### Response fields specific to MCP Get Rate

Variable Name	Type and Limits	Get Method and Description
rate transaction type	<i>String</i>  max 8-character alpha- abetic  PURCHASE or REFUND	<code>receipt.getRateTxnType();</code>  Reflects the transaction type being sent in the request
MCP rate token	<i>String</i>  17-character alpha- numeric	<code>receipt.GetMCPRateToken();</code>  Time-limited token representing a tem- porarily locked in foreign exchange rate for use in financial transactions
		This field is returned in the response to a MCP Get Rate request
rate inquiry start time	<i>String</i>  24-character alpha- numeric	<code>receipt.getRateInqStartTime();</code>  The local time (ISO 8601) when the rate is requested
rate inquiry end time	<i>String</i>  24-character alpha- numeric	<code>receipt.getRateInqEndTime();</code>  The local time (ISO 8601) when the rate is returned

Variable Name	Type and Limits	Get Method and Description
rate validity start time	<i>String</i> 10-character numeric	<code>receipt.getRateValidityStartTime();</code> The time (unix UTC) of when the rate is valid from
rate validity end time	<i>String</i> 10-character numeric	<code>receipt.getRateValidityEndTime();</code> The time (unix UTC) of when the rate is valid until
rate validity period	<i>String</i> 3-character numeric variable length	<code>receipt.getRateValidityPeriod();</code> The time in minutes this rate is valid for

## B.3 Definition of Response Fields –Installments by Visa

### Response fields appearing in the Installment Plan Lookup transaction

Variable Name	Type and Limits	Description
Eligible Installment Plans	<i>Object</i> N/A	Contains fields related to the installment plan
plan count	<i>String</i> numeric	Total number of installment plans available for offer to the cardholder
Plan Details	<i>Array object</i> N/A	Contains fields related to the particular installment plan  Each installment plan on offer to the cardholder is represented by a distinct Plan Details object
annual percentage rate (APR)	<i>String</i> numeric	Annual percentage rate (APR) attached to the installment plan payments; for display purposes only and not used for calculations  Allowable values: 0-10000

Variable Name	Type and Limits	Description
		<p>Percentage rate is represented with two implicit decimals</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> 320 is 3.2%         </div>
installment frequency	<i>String</i> max 10-character alphabetic	Frequency of installments for the plan Potential values: WEEKLY BIWEEKLY MONTHLY BIMONTHLY
installment plan ID	<i>String</i> 36-character alphanumeric fixed length	Card brand-generated identifier for an installment plan Used as a request field in the Installment Info object
installment plan name	<i>String</i> max 255-character alphanumeric	Name of the installment plan; may not be unique
installment plan reference	<i>String</i> 10-character alphanumeric fixed length	Unique, human friendly name for the installment plan Used as a request field in the Installment Info object
installment plan type	<i>String</i> max 20 character alphanumeric	Type of installment plans Potential values: ISSUER_PROMOTION BI_LATERAL ISSUER_DEFAULT MARKET
number of installments	<i>String</i>	Maximum number of installments in the plan

Variable Name	Type and Limits	Description
	4-character numeric min 1, max 1000	
First Installment	<i>Object</i> N/A	Contains cost details for the first installment
first installment amount	<i>String</i> max 9-character numeric	Amount of the first installment payment  Final two digits represent penny values  <div style="background-color: #e0f2e0; padding: 5px; border-radius: 5px;"><b>EXAMPLE:</b> 123112 = \$1231.12</div>
first installment fee	<i>String</i> max 9-character numeric	Fee charged on the first installment  Final two digits represent penny values  <div style="background-color: #e0f2e0; padding: 5px; border-radius: 5px;"><b>EXAMPLE:</b> 123112 = \$1231.12</div>
upfront fee	<i>String</i> numeric	The up-front fee charged to the cardholder for the installment plan; only charged on the first installment
Last Installment	<i>Object</i> N/A	Contains cost details for the last installment
last installment amount	<i>String</i> max 9-character numeric	Amount of the final installment payment  Final two digits represent penny values  <div style="background-color: #e0f2e0; padding: 5px; border-radius: 5px;"><b>EXAMPLE:</b> 123112 = \$1231.12</div>
last installment fee	<i>String</i> max 9-character numeric	Fee charged on the last installment  Final two digits represent penny val-

Variable Name	Type and Limits	Description
		<p>ues</p> <div style="border: 1px solid #ccc; padding: 5px; background-color: #e0f2e0; margin-top: 5px;"> <b>EXAMPLE:</b> 123112 = \$1231.12         </div>
Promotion Info	<i>Object</i> N/A	Contains promotion information shared between the issuer and the merchant
promotion code	<i>String</i> 2-character alphanumeric	An external identifier for the plan provided by the issuer
promotion ID	<i>String</i> max 8-character alphanumeric	An external identifier provided by the issuer that identifies a program or promotion
Terms and Conditions	<i>Array object</i> N/A	Contains fields related to terms and conditions presented to the cardholder
terms and conditions count	<i>String</i> numeric	Number of instances of the set of terms and conditions attached to a particular installment plan, representing the number of languages they are offered in
Terms and Conditions Details	<i>Object</i> N/A	Contains details related to a particular language set (English, French, etc.) of terms and conditions being offered Each language set has its own object
language code	<i>String</i> 3-character alphanumeric	Language code for the terms and conditions text
text	<i>String</i> max 2000-character alphanumeric	Text of the terms and conditions for the installment plan
terms and conditions URL	<i>String</i>	A terms and conditions HTTPS URL hosted by the issuer for displaying to the

Variable Name	Type and Limits	Description
	max 1000 character-alpha-numeric	cardholder
terms and conditions version	<p><i>String</i></p> <p>10-character alphanumeric</p> <p>variable length (1-10 characters)</p>	<p>Version of the terms and conditions of the installment plan accepted by the cardholder</p> <p>The version is auto-incremented every time an update is made to the plan by the issuer</p>
total fees	<p><i>String</i></p> <p>max 9-character numeric</p>	<p>Total fees charged by the plan</p> <p>Final two digits represent penny values</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> 123112 = \$1231.12         </div>
total plan cost	<p><i>String</i></p> <p>numeric</p>	<p>Represents the total amount the selected installment plan will cost</p> <p>The right-most digits represent minor units (e.g., cents in CAD); no fractional minor units</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <b>EXAMPLE:</b> 123112 in CAD represents CAD \$1231.12         </div>

### Response fields appearing in financial transactions

Variable Name	Type and Limits	Description
Installment Results	<p><i>Object</i></p> <p>N/A</p>	Contains fields related to the installment plan in financial transactions
installment plan ID	<p><i>String</i></p> <p>36-character alphanumeric</p> <p>fixed length</p>	Card brand-generated identifier for an installment plan

Variable Name	Type and Limits	Description
installment plan reference	<i>String</i> 10-character alphanumeric fixed length	Unique, human friendly name for the installment plan
terms and conditions version	<i>String</i> 10-character alphanumeric variable length (1-10 characters)	Version of the terms and conditions of the installment plan accepted by the cardholder.  The version is auto-incremented every time an update is made to the plan by the issuer.
plan acceptance ID	<i>String</i> 36-character alphanumeric fixed length	Visa-generated, alphanumeric, unique and short human-readable name for the installment plan
installment plan status	<i>String</i> 1-character alphabetic fixed length	Potential values:  N – new plan, not accepted yet  A – accepted plan  C – cancelled plan
plan response	<i>String</i> max 50-character numeric	Response code for the installment plan  Potential values:  00 – processed and approved  If not 00, indicates installment plan processing failure; a verbose error response message as received from Visa is returned

## Appendix C Response Codes

### Approved Response Codes

Response Code	Messages
000	Approved, Account Balances Included (Balance Inquiry), No Reason to Decline Approved (Balances) File Processed/Successful transaction with fault
001	Approved, Account Balances Not Included Approved – No Balances/Approved or completed successfully VIP Approved (No Balances)/Advice Acknowledged – Financial Liability Accepted
002	Approved, country club
003	Approved, maybe more ID
004	Approved, pending ID (sign paper draft)
005	Approved, blind
006	Approved, VIP
007	Approved, administrative transaction
008	Approved, national NEG file hit OK
009	Approved, commercial
010	Approved for partial amount
023	Amex - credit approval
024	Amex 77 - credit approval

Response Code	Messages
027	Transaction already reversed
028	VIP Credit Approved
029	Credit Response Acknowledgement
900	Global Error
901	Invalid URL
902	Malformed XML

**Declined Response Codes**

Response Code	Messages
050	Do Not Honor Decline Refer to card issuer ID certification fails Deny – Do not Honour Card not initialized Declined: Deny – Unacceptable Fee Unable to locate original transaction Suspected Fraud Deny – Card Acceptor Call Acquirer's Security Dep Amount Not Reconciled – Totals Provided ATM/POS terminal number cannot be located MAC failed Declined: MAC failed

Response Code	Messages
	Reserved Security processing failure No arrears (transaction receipt not printed) Invalid File Type No such File File Locked Unsuccessful Incorrect File Length File Decompression Error File Name Error File cannot be received Deny – Do Not Honour
051	Expired Card
052	PIN retries exceeded PIN try limit exceeded Allowable number of PIN tries exceeded
053	No sharing
054	No security module
055	Invalid transaction
056	No Support/Transaction Not Permitted to Acquirer Tran Not Supported by FI/Not Supported by Receiver
057	Lost or stolen card
058	Invalid status
059	Deny (Keep Card) – Restricted Card

Response Code	Messages
	Restricted Card
060	No Chequing account No Savings Account
061	No PBF
062	PBF update error
063	Invalid authorization type
064	Bad Track 2
065	Adjustment not allowed
066	Invalid credit card advance increment
067	Invalid transaction date
068	PTLF error
069	Bad Message Error/No CVM Results Bad message – edit error/Format error
070	No IDF Invalid Issuer Invalid Issuer/Deny – Issuer/Bank Not Found
071	Invalid route authorization Unable to route/Financial institution or intermediate network facility cannot be found for routing Invalid Rout to Auth /Incorrect IIN
072	Card on National NEG file
073	Invalid route service (destination)
074	Unable to authorize

Response Code	Messages
	Re-enter Transaction Transaction Cannot be Completed Deny – Security Violation Deny – Violation of Law System problem - ask cardholder to insert card in chip card reader Merchant Link not logged on (Network Management Logon required)
075	Invalid PAN length
076	Low funds
077	Pre-auth full
078	Duplicate transaction Duplicate transaction/Request in progress
079	Maximum online refund reached
080	Maximum offline refund reached
081	Maximum credit per refund reached
082	Number of times used exceeded
083	Maximum refund credit reached
084	Duplicate transaction - authorization number has already been corrected by host
085	Inquiry not allowed
086	Over floor limit
087	Maximum number of refund credit by retailer
088	Place call
089	CAF status inactive or closed
090	Referral file full

Response Code	Messages
091	NEG file problem
092	Advance less than minimum
093	Delinquent
094	Over table limit
095	Amount over maximum Amt Over Max/Transaction amount limit exceeded
096	PIN required
097	Mod 10 check failure
098	Force Post
099	Bad PBF

**Referral Response Codes**

Response Code	Messages
100	Unable to process transaction  Invalid Request. Contact Moneris Client POS Certification for repeat declines.  Network Unavailable  System Malfunction
101	Place call
102	Refer – Call  Expired Card  Card Acceptor Contact  Call Card Accpt Acq Secur
103	NEG file problem

Response Code	Messages
104	CAF problem
105	Card not supported
106	Amount over maximum
107	Over daily limit
108	CAF Problem
109	Advance less than minimum
110	Number of times used exceeded
111	Delinquent
112	Over table limit
113	Timeout
115	PTLF error
121	Administration file problem
122	Unable to validate PIN: security module down

### System Error Response Codes

Response Code	Messages
150	Invalid Service Code/Merchant Merchant Not On File Merchant Not on File/Invalid Merchant
200	Invalid account Invalid Card Number Invalid Account/Deny – No Account Type Requested
201	Incorrect PIN

Response Code	Messages
	Invalid PIN/Incorrect personal identification number PIN Block Error
202	Advance less than minimum
203	Administrative card needed
204	Amount over maximum
205	Invalid Advance Amount Original Amnt Incorrect Bad message/Invalid Amount Original transaction amount error
206	CAF not found Invalid “to” account Invalid “from” account Invalid account
207	Invalid transaction date
208	Invalid expiration date
209	Invalid transaction code
210	PIN key sync error
212	Destination not available
251	Error on cash amount
252	Debit not supported

**American Express Response Codes (Declines)**

Response Code	Messages
426	AMEX - Denial 12
427	AMEX - Invalid merchant
429	AMEX - Account error
430	AMEX - Expired card
431	AMEX - Call Amex
434	AMEX - Call 03  Note: Invalid CVD (CID)
435	AMEX - System down
436	AMEX - Call 05
437	AMEX - Declined
438	AMEX - Declined
439	AMEX - Service error
440	AMEX - Call Amex
441	AMEX - Amount error

**Credit Card Response Codes (Declines)**

Response Code	Messages
408	CREDIT CARD - Card use limited - Refer to branch
475	CREDIT CARD - Invalid expiration date
476	CREDIT CARD - Invalid transaction, rejected  No Credit Account  Invalid transaction/Invalid related transactions

Response Code	Messages
	Unable to process/Suspected malfunction; related transaction error Unable to Authorize: Cut off is in process Issuer not capable to process Switch system malfunction Issuer response not received by CUPS Unable to Authorize/Illegal Status of Acquirer
477	CREDIT CARD - Refer Call/Invalid Card Number Invalid card number (no such account) Deny – Card Not Found Items not on Bankbook beyond limit, declined/Invalid card number
478	CREDIT CARD - Decline, Pick up card, Call
479	CREDIT CARD - Decline, Pick up card
480	CREDIT CARD - Decline, Pick up card
481	CREDIT CARD - Decline Transaction not allowed to be processed by cardholder Low funds/Insufficient Balance Invalid Transaction Transaction not allowed to be processed by merchant
482	CREDIT CARD - Expired Card
483	CREDIT CARD – Refer/Refer to Issuer Deny – Card Acceptor Contact Acquirer
484	CREDIT CARD - Expired card - refer
485	CREDIT CARD - Not authorized

Response Code	Messages
486	CREDIT CARD - CVV Cryptographic error
487	CREDIT CARD - Invalid CVV
489	CREDIT CARD - Invalid CVV
490	CREDIT CARD - Invalid CVV
492	System problem - ask cardholder to insert card in chip card reader Withdrawal count exceeded

### System Decline Response Codes

Response Code	Messages
800	Bad format
801	Bad data
802	Invalid Clerk ID
809	Bad close
810	System timeout
811	System error
821	Bad response length
842	Installment plan lookup failure
877	Invalid PIN block
878	PIN length error
880	Final packet of a multi-packet transaction
881	Intermediate packet of a multi-packet transaction
889	MAC key sync error

Response Code	Messages
898	Bad MAC value
899	Bad sequence number - resend transaction
900	Capture - PIN Tries Exceeded
901	Capture - Expired Card
902	Capture - NEG Capture
903	Capture - CAF Status 3
904	Capture - Advance < Minimum
905	Capture - Num Times Used
906	Capture - Delinquent
907	Capture - Over Limit Table
908	Capture - Amount Over Maximum
	Capture - Capture
	Pick up Card
	Suspected Fraud
	Hard Capture
	Deny – Keep Card:
	Special Conditions
	Expired Card
	Fraud
	Card Acceptor Call Acquirer's
	Do Not Honour
950	Admin card is not enabled on Merchant profile

## Other Response Codes

Response Code	Message
599	Decline

## Admin Response Codes

Response Code	Messages
960	Initialization Failure - No Match on Merchant ID
961	Initialization Failure - No Match on PED ID
962	Initialization Failure - No match on Printer ID
963	No match on Poll code
964	Initialization Failure - No match on Concentrator ID
965	Invalid software version number
966	Duplicate terminal name
970	Terminal/Clerk table full
983	Clerk Totals Unavailable: selected Clerk IDs do not exist or have zero totals
989	MAC Error on Transaction 95 (Initialization and Handshake), most often, this indicates that the wrong keys have been injected into a device/KMAC Sync Error

## EMV Reversal Request Codes

Response Code	Messages
990	Chip card declines a host approved transaction
991	Chip card removed before ICC communications are completed

# Appendix D Error Messages

## Error messages that are returned if the gateway is unreachable

### Global Error Receipt

You are not connecting to our servers. This can be caused by a firewall or your internet connection.

### Response Code = NULL

The response code can be returned as null for a variety of reasons. The majority of the time, the explanation is contained within the Message field.

When a 'NULL' response is returned, it can indicate that the issuer, the credit card host, or the gateway is unavailable. This may be because they are offline or because you are unable to connect to the internet.

A 'NULL' can also be returned when a transaction message is improperly formatted.

## Error messages that are returned in the Message field of the response

### XML Parse Error in Request: <System specific detail>

An improper XML document was sent from the API to the servlet.

### XML Parse Error in Response: <System specific detail>

An improper XML document was sent back from the servlet.

### Transaction Not Completed Timed Out

Transaction timed out before the host responds to the gateway.

### Request was not allowed at this time

The host is disconnected.

### Could not establish connection with the gateway: <System specific detail>

Gateway is not accepting transactions or server does not have proper access to internet.

### Input/Output Error: <System specific detail>

Servlet is not running.

### The transaction was not sent to the host because of a duplicate order id

Tried to use an order id which was already in use.

### The transaction was not sent to the host because of a duplicate order id

Expiry Date was sent in the wrong format.

## Vault error messages

### Can not find previous

Data key provided was not found in our records or profile is no longer active.

### Invalid Transaction

Transaction cannot be performed because improper data was sent.

or

Mandatory field is missing or an invalid SEC code was sent.

### Malformed XML

Parse error.

**Incomplete**

Timed out.

**or**

Cannot find expiring cards.

# Appendix E Merchant Checklists for INTERAC® Online Payment Certification Testing

## Merchant Information

Name and URL	Merchant Name (English)	
	Homepage URL (English)	
	Merchant Name (French)	
	Homepage URL (French)	
Number	Merchant Number	
Transaction fee category (Circle one)	Government Education General	

## Checklist for Front-End Tests

Case #	Date Completed	Remarks
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		

Case #	Date Completed	Remarks
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		

## Merchant Requirements

**Table 31: Checklist for web display requirements**

Done	Requirement
	Checkout page

**Table 31: Checklist for web display requirements (continued)**

Done	Requirement
	Displays the INTERAC Online design (logo), wordmark (text "INTERAC Online") or both
<b>Design and Wordmark Requirements (any page)</b>	
	<p>Other payment option logos:</p> <ul style="list-style-type: none"> <li>• Displays the INTERAC Online design (logo) if the merchant displays the trademarks or logos of other payment options.</li> <li>• Design is equal in size and no less prominent than other payment option trademarks.</li> </ul>
	<p>INTERAC wordmark:</p> <ul style="list-style-type: none"> <li>• INTERAC is always either in capital letters or italics (as in "the INTERAC Online service")</li> <li>• In the first use of the INTERAC Online wordmark, INTERAC is followed by the <sup>®</sup> notation in superscript. For example, "<i>Interac</i><sup>®</sup>" (English) or &lt;&lt;<i>Interac</i><sup>MD</sup>&gt;&gt; (French).</li> <li>• On the same page as the first occurrence of the wordmark, the following language-appropriate footnote appears: <ul style="list-style-type: none"> <li>• <sup>®</sup> Trademark of Interac Inc. Used under licence"</li> <li>• <sup>MD</sup> Marque de commerce d'Interac Inc. Utilisée sous licence</li> </ul> </li> </ul>
<b>Version of design</b>	
	<p>Uses the two-colour design on the web:</p> <ul style="list-style-type: none"> <li>• Horizontal version—height no shorter than 25 pixels (width-to-height ratio of 2:37:1)</li> <li>• Vertical version—width no narrower than 30 pixels (width-to-height ratio of 1:1:37)</li> </ul>
<b>"Learn more" information</b>	
	Provides consumers with a link to <a href="http://www.interaconline.com/learn">www.interaconline.com/learn</a> (preferably on the checkout page)
<b>Confirmation page</b>	
	States that the transaction is successful
	Displays the financial institution's name and confirmation number
	Provides ability to print

**Table 31: Checklist for web display requirements (continued)**

Done	Requirement
<b>Error page</b>	
	Indicates that payment was unsuccessful
	States that the order is cancelled or displays other payment options
<b>Timeout message</b>	
	Is displayed if consumer has less than 30 minutes to complete payment
<b>Payment</b>	
	Displays the total in Canadian dollars

**Table 32: Checklist for security/privacy requirements**

Done	Requirement
<b>Merchant</b>	
	Uses no less than 128-bit SSL encryption when collecting personal information
	Protects consumer information in accordance with applicable federal and provincial privacy legislation
	Adheres to the Canadian Code of Practice for Consumer Protection in Electronic Commerce
<b>Provided screenshots</b>	
	Checkout page (where customer selects INTERAC Online option)
	Confirmation page (one of the test case 1, 2, or 3)
	Error page (test case 4)

## Appendix F Third-Party Service Provider Checklists for INTERAC® Online Payment Certification Testing

### Third-Party Service Provider Information

Name	English	
	French	
Merchant Web Application	Solution Name	
	Version	
Acquirer		

### Interaconline.com/Interacenlgne.com Web Site Listing Information

See [http://www.interaconline.com/merchants\\_thirdparty.php](http://www.interaconline.com/merchants_thirdparty.php) for examples.

English contact information	5 lines maximum. 35 characters/line maximum. For example, contact name and title, department, telephone, web site, email.
English logo	File type: PNG. Maximum size: 120x120 pixels.
French contact information	5 lines maximum. 35 characters/line maximum. For example, contact name and title, department, telephone, web site, email.
French logo	File type: PNG. Maximum size: 120x120 pixels.

**Table 33: Checklist for front-end tests**

Case #	Date Completed	Remarks
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		

**Table 33: Checklist for front-end tests**

Case #	Date Completed	Remarks
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		

### **Merchant Requirements**

**Table 34: Checklist for web display requirements**

Done	Requirement
<b>Checkout page</b>	
	Displays the INTERAC Online design (logo), wordmark (text "INTERAC Online) or both
<b>Design and Wordmark Requirements (any page)</b>	
	<p>Other payment option logos:</p> <ul style="list-style-type: none"><li>• Displays the INTERAC Online design (logo) if the merchant displays the trademarks or logos of other payment options.</li><li>• Design is equal in size and no less prominent than other payment option trademarks.</li></ul>

**Table 34: Checklist for web display requirements (continued)**

Done	Requirement
	<p>INTERAC wordmark:</p> <ul style="list-style-type: none"> <li>• INTERAC is always either in capital letters or italics (as in "the INTERAC Online service")</li> <li>• In the first use of the INTERAC Online wordmark, INTERAC is followed by the <sup>®</sup> notation in superscript. For example, "<i>Interac</i><sup>®</sup>" (English) or &lt;&lt;<i>Interac</i><sup>MD</sup>&gt;&gt; (French).</li> <li>• On the same page as the first occurrence of the wordmark, the following language-appropriate footnote appears: <ul style="list-style-type: none"> <li>• <sup>®</sup> Trademark of Interac Inc. Used under licence"</li> <li>• <sup>MD</sup> Marque de commerce d'Interac Inc. Utilisée sous licence</li> </ul> </li> </ul>
<b>Version of design</b>	
	<p>Uses the two-colour design on the web:</p> <ul style="list-style-type: none"> <li>• Horizontal version—height no shorter than 25 pixels (width-to-height ratio of 2:37:1)</li> <li>• Vertical version—width no narrower than 30 pixels (width-to-height ratio of 1:1:37)</li> </ul>
<b>"Learn more" information</b>	
	Provides consumers with a link to <a href="http://www.interaconline.com/learn">www.interaconline.com/learn</a> (preferably on the checkout page)
<b>Confirmation page</b>	
	States that the transaction is successful
	Displays the financial institution's name and confirmation number
	Provides the ability to print
<b>Error page</b>	
	Indicates that payment was unsuccessful
	States that the order is cancelled or displays other payment options
<b>Timeout message</b>	
	Is displayed if consumer has less than 30 minutes to complete payment
<b>Payment</b>	
	Displays the total in Canadian dollars

**Table 35: Checklist for security/privacy requirements**

Done	Requirement
<b>Merchant</b>	
	Uses no less than 128-bit SSL encryption when collecting personal information
	Protects consumer information in accordance with applicable federal and provincial privacy legislation
	Adheres to the Canadian Code of Practice for Consumer Protection in Electronic Commerce

**Table 36: Checklist for required screenshots**

Done	Requirement
<b>Provided screenshots</b>	
	Checkout page (where customer selects INTERAC Online option)
	Confirmation page (one of the test case 1, 2, or 3)
	Error page (test case 4)

# Appendix G Merchant Checklists for INTERAC® Online Payment Certification

## Merchant Information

Name and URL	Merchant Name (English)	
	Homepage URL (English)	
	Merchant Name (French)	
	Homepage URL (French)	
Number	Merchant Number	
Transaction fee category (Circle one)	Government Education General	
Third-party service provider	Company name	
Service provider's merchant web application	Solution name	
	Version	

## Merchant Requirements

Table 37: Checklist for web display requirements

Done	Requirement
Checkout page	Displays the INTERAC Online design (logo), wordmark (text "INTERAC Online) or both
Design and Wordmark Requirements (any page)	<p>Other payment option logos:</p> <ul style="list-style-type: none"><li>• Displays the INTERAC Online design (logo) if the merchant displays the trademarks or logos of other payment options.</li><li>• Design is equal in size and no less prominent than other payment option trademarks.</li></ul>

**Table 37: Checklist for web display requirements (continued)**

Done	Requirement
	<p>INTERAC wordmark:</p> <ul style="list-style-type: none"> <li>• INTERAC is always either in capital letters or italics (as in "the INTERAC Online service")</li> <li>• In the first use of the INTERAC Online wordmark, INTERAC is followed by the <sup>®</sup> notation in superscript. For example, "<i>Interac</i><sup>®</sup>" (English) or &lt;&lt;<i>Interac</i><sup>MD</sup>&gt;&gt; (French).</li> <li>• On the same page as the first occurrence of the wordmark, the following language-appropriate footnote appears:           <ul style="list-style-type: none"> <li>• <sup>®</sup> Trademark of Interac Inc. Used under licence"</li> <li>• <sup>MD</sup> Marque de commerce d'Interac Inc. Utilisée sous licence</li> </ul> </li> </ul>
Version of design	Uses the two-colour design on the web: <ul style="list-style-type: none"> <li>• Horizontal version—height no shorter than 25 pixels (width-to-height ratio of 2:37:1)</li> <li>• Vertical version—width no narrower than 30 pixels (widteh-to-height ratio of 1:1:37)</li> </ul>
"Learn more" information	Provides consumers with a link to <a href="http://www.interaconline.com/learn">www.interaconline.com/learn</a> (preferably on the checkout page)
Confirmation page	<p>States that the transaction is successful</p> <p>Displays the financial institution's name and confirmation number</p> <p>Provides ability to print</p>
Error page	<p>Indicates that payment was unsuccessful</p> <p>States that the order is cancelled or displays other payment options</p>
Timeout message	Is displayed if consumer has less than 30 minutes to complete payment
Payment	Displays the total in Canadian dollars

**Table 38: Checklist for security/privacy requirements**

Done	Requirement
<b>Merchant</b>	
	Uses no less than 128-bit SSL encryption when collecting personal information
	Protects consumer information in accordance with applicable federal and provincial privacy legislation
	Adheres to the Canadian Code of Practice for Consumer Protection in Electronic Commerce
<b>Provided screenshots</b>	
	Checkout page (where customer selects INTERAC Online option)
	Confirmation page (one of the test case 1, 2, or 3)
	Error page (test case 4)

# Appendix H INTERAC® Online Payment Certification

## Test Case Detail

- H.1 Common Validations
- H.2 Test Cases
- H.3 Merchant front-end test case values

### H.1 Common Validations

The Merchant sends a request to the INTERAC Online Merchant Test Tool, which validates the fields as follows:

- All mandatory fields are present.
- All fields are valid according to their definition in the *INTERAC Online Functional Specifications* (including field lengths, valid characters and so on).
- Merchant number is that of a valid registered merchant.
- Funded URL matches one of the merchant's registered funded URLs that were provided during merchant registration.
- The not funded URL matches one of the merchant's registered Not Funded URLs that were provided during merchant registration.
- No additional fields are present.

### H.2 Test Cases

Table 39: Cases 1-3

Objective	To test that the merchant can do all of the following: <ul style="list-style-type: none"><li>• Send a valid request to the Gateway page</li><li>• Receive a valid confirmation of funding from the Issuer Online Banking application</li><li>• Issue a request for purchase completion to the acquirer</li><li>• Receive an approved response from the acquirer.</li></ul>
Pre-requisites	None

**Table 39: Cases 1-3 (continued)**

Configuration	<p>Merchant sends form posts to the Merchant Test Tool, which in turn responds to either the Funded or Not Funded URL.</p> <p>The Merchant is connected to an acquirer emulator, which can be set to confirm any request for payment confirmation. (That is, the back-end process of sending a 0200 Message to the issuer is emulated to always accept the purchase request).</p>
Special tools required	None
Input data requirements	<p>Acquirer must have registered the merchant using the administration system, and have supplied the following:</p> <ul style="list-style-type: none"> <li>• IDEBIT_FUNDEDURL(S)</li> <li>• IDEBIT_NOTFUNDEDURL(S)</li> <li>• HTTP REFERERURL(S)</li> </ul> <p>Data will be provided by the Merchant Test Tool.</p>
Execution strategy	Initiate a payment at the merchant. The two least significant digits of the dollar amount must be equal to the test case number. For example, if you are executing test case 3, the format of the amount must be ### ### #03.##.

**Table 39: Cases 1-3 (continued)**

Expected outcome	<p>The merchant indicates to the customer that the purchase was completed and presents a confirmation screen that includes (depending on the test case) the correct amount, the issuer name and the issuer confirmation number.</p> <p>Test case 1</p> <ul style="list-style-type: none"> <li>• Issuer name: 123Bank</li> <li>• Issuer confirmation number: CONF#123</li> </ul> <p>Test case 2</p> <ul style="list-style-type: none"> <li>• Issuer name: Bank Éàêëï#\$.,-/=?@'</li> <li>• Issuer confirmation number: #\$.,-=/=?@'UPdn9</li> </ul> <p>Test case 3</p> <ul style="list-style-type: none"> <li>• Issuer name: B</li> <li>• Issuer confirmation number: C</li> </ul>
Applicable logs	<ul style="list-style-type: none"> <li>• Merchant Test Tool logs</li> <li>• Screen capture of the merchant's confirmation page.</li> </ul>

**Table 40: Case 4**

Objective	To test that the merchant handles a rejection in response to the acquirer
Pre-requisites	None
Configuration	Same as test cases 1-3 except that the acquirer emulator must be set to decline the request for payment confirmation. (That is, to emulate the scenario in which an issuer sends a decline in the 0210 response to the acquirer's 0200 message.)
Special tools required	None

**Table 40: Case 4 (continued)**

Input data requirements	<p>Acquirer must have registered the merchant using the administration system, and have supplied the following:</p> <ul style="list-style-type: none"> <li>• IDEBIT_FUNDEDURL(S)</li> <li>• IDEBIT_NOTFUNDEDURL(S)</li> <li>• HTTP REFERERURL(S)</li> </ul> <p>Data will be provided by the Merchant Test Tool.</p>
Execution strategy	Initiate a payment at the merchant for any amount where the two least significant dollar digits are 04. (That is, of the form ### ### #04.##.)
Expected outcome	The merchant indicates to the customer that the purchase was declined. Neither the issuer name nor the issuer confirmation number are displayed.
Applicable logs	Merchant Test Tool logs

**Table 41: Cases 5-22**

Objective	To test that a merchant safely handles redirections to the Funded URL with invalid data, and treats the transaction as funded.
Pre-requisites	None
Configuration	<p>None.</p> <p>The acquirer emulator is not needed because the merchant does not submit any requests for payment confirmation.</p>
Special tools required	None
Input data requirements	<p>Acquirer must have registered the merchant using the administration system, and have supplied the following:</p> <ul style="list-style-type: none"> <li>• IDEBIT_FUNDEDURL(S)</li> <li>• IDEBIT_NOTFUNDEDURL(S)</li> <li>• HTTP REFERERURL(S)</li> </ul> <p>Data will be provided by the Merchant Test Tool.</p>

**Table 41: Cases 5-22 (continued)**

Execution strategy	Initiate a payment at the merchant. The two least significant digits of the dollar amount must be equal to the test case number. For example, if you are executing test case 13, the format of the amount must be ### ### #13.##.
Expected outcome	The merchant indicates to the customer that the purchase was declined. Neither the issuer name nor the issuer confirmation number are displayed.
Applicable logs	Merchant Test Tool logs

**Table 42: Case 23**

Objective	To test that a merchant can receive a valid redirection from the issuer that indicates the payment was not funded.
Pre-requisites	None
Configuration	None.  The acquirer emulator is not needed because the merchant does not submit any requests for payment confirmation.
Special tools required	None
Input data requirements	Acquirer must have registered the merchant using the administration system, and have supplied the following: <ul style="list-style-type: none"><li>• IDEBIT_FUNDEDURL(S)</li><li>• IDEBIT_NOTFUNDEDURL(S)</li><li>• HTTP REFERERURL(S)</li></ul> Data is provided by the Merchant Test Tool.
Execution strategy	Initiate a payment at the merchant for any amount where the two least significant dollar digits are 23. (That is, of the form ### ### #23.##.)
Expected outcome	The merchant indicates to the customer that the purchase was declined. Neither the issuer name nor the issuer confirmation number are displayed.
Applicable logs	Merchant Test Tool logs

**Table 43: Cases 24-39**

Objective	To test that a merchant safely handles redirections to the Not Funded URL with invalid data, and treats the transaction as not funded.
Pre-requisites	None
Configuration	None.  The acquirer emulator is not needed because the merchant does not submit any requests for payment confirmation.
Special tools required	None
Input data requirements	Acquirer must have registered the merchant using the administration system, and have supplied the following: <ul style="list-style-type: none"><li>• IDEBIT_FUNDEDURL(S)</li><li>• IDEBIT_NOTFUNDEDURL(S)</li><li>• HTTP REFERERURL(S)</li></ul> Data is provided by the Merchant Test Tool.
Execution strategy	Initiate a payment at the merchant. The two least significant digits of the dollar amount must be equal to the test case number. For example, if you are executing test case 27, the format of the amount must be ### ### #27.##.
Expected outcome	The merchant indicates to the customer that the purchase was declined. Neither the issuer name nor the issuer confirmation number are displayed.
Applicable logs	Merchant Test Tool logs

### H.3 Merchant front-end test case values

These values are automatically sent by the INTERAC Online Merchant Test Tool. They are provided here for reference only.

**Table 44: Test cases 1 and 4—Funded URL**

Redirection URL	Funded
ISSLANG	en
TRACK2	3728024906540591206=12010123456789XYZ
ISSCONF	CONF#123
ISSNAME	123Bank

**Table 44: Test cases 1 and 4—Funded URL**

INVOICE	(Same as supplied by merchant)
MERCHDATA	(Same as supplied by merchant)
VERSION	1

**Table 45: Test case 2—Funded URL**

Redirection URL	Funded
ISSLANG	en
TRACK2	5268051119993326=2912999999999999000
ISSCONF	#\$.,-/=?@'UPdn9
ISSNAME	987Bank Éàêëï#\$.,-/=?@'Àôùûüýç
INVOICE	(Same as supplied by merchant)
MERCHDATA	(Same as supplied by merchant)
VERSION	1

**Table 46: Test case 3—Funded URL**

Redirection URL	Funded
ISSLANG	fr
TRACK2	453781122255=1001ABC11223344550000000
ISSCONF	C
ISSNAME	B
INVOICE	(Same as supplied by merchant)
MERCHDATA	(Same as supplied by merchant)
VERSION	123

**Table 47: Test cases 5-22—invalid fields, Funded URL**

Test case	Purpose	Field	Value
5	missing field	IDEBIT_INVOICE	(missing)
6	missing field	IDEBIT_MERCHDATA	(missing)
7	missing field	IDEBIT_ISSLANG	(missing)
8	missing field	IDEBIT_TRACK2	(missing)

**Table 47: Test cases 5-22—invalid fields, Funded URL (continued)**

Test case	Purpose	Field	Value
9	missing field	IDEBIT_ISSCONF	(missing)
10	missing field	IDEBIT_ISSNAME	(missing)
11	missing field	IDEBIT_VERSION	(missing)
12	missing field	IDEBIT_TRACK2, IDEBIT_ISSCONF, IDEBIT_ISSNAME	(missing)
13	wrong value	IDEBIT_INVOICE	XXX
14	wrong value	IDEBIT_MERCHDATA	XXX
15	invalid value	IDEBIT_ISSLANG	de
16	value too long	IDEBIT_TRACK2	3728024906540591206=12010123456789XYZA
17	invalid check digit	IDEBIT_TRACK2	3728024906540591207=12010123456789XYZ
18	field too long	IDEBIT_ISSCONF	Too long confirm
19	invalid character	IDEBIT_ISSCONF	CONF<123
20	field too long	IDEBIT_ISSNAME	Very, very, very long issuer name
21	invalid character	IDEBIT_ISSNAME	123<Bank
22	invalid value	IDEBIT_VERSION	2

**Table 48: Test case 23—valid data, Not Funded URL**

Redirection URL	Not funded
ISSLANG	en
INVOICE	(Same as supplied by merchant)
MERCHDATA	(Same as supplied by merchant)
VERSION	1

**Table 49: Test cases 5-22—invalid fields, Funded URL**

Test case	Purpose	Field	Value
24	missing field	IDEBIT_INVOICE	(missing)
25	missing field	IDEBIT_MERCHDATA	(missing)
26	missing field	IDEBIT_ISSLANG	(missing)
27	IDEBIT_TRACK2 is present and valid	IDEBIT_TRACK2	3728024906540591206=12010123456789XYZ
28	IDEBIT_ISSCONF is present and valid	IDEBIT_ISSCONF	CONF#123
29	IDEBIT_ISSNAME is present and valid	IDEBIT_ISSNAME	12Bank
30	missing field	IDEBIT_VERSION	(missing)
31	wrong value	IDEBIT_INVOICE	XXX
32	invalid value	IDEBIT_INVOICE	invalid </html> tricky data
33	wrong value	IDEBIT_MERCHDATA	XXX
34	invalid value	IDEBIT_MERCHDATA	<2000 characters in the range hex 20-7E
35	invalid value	IDEBIT_ISSLANG	de
36	invalid IDEBIT_TRACK2 is present	IDEBIT_TRACK2	INVALIDTRACK2, incorrect format and too long
37	invalid IDEBIT_ISSCONF is present	IDEBIT_ISSCONF	Too long confirm
38	invalid IDEBIT_ISSNAME is present	IDEBIT_ISSNAME	Very, very, very long issuer name
39	invalid value	IDEBIT_VERSION	2



## Copyright Notice

Copyright © December 2023 Moneris Solutions, 3300 Bloor Street West, Toronto, Ontario, M8X 2X2

All Rights Reserved. This manual shall not wholly or in part, in any form or by any means, electronic, mechanical, including photocopying, be reproduced or transmitted without the authorized, written consent of Moneris Solutions.

This document has been produced as a reference guide to assist Moneris client's hereafter referred to as merchants. Every effort has been made to make the information in this reference guide as accurate as possible. The authors of Moneris Solutions shall have neither liability nor responsibility to any person or entity with respect to any loss or damage in connection with or arising from the information contained in this reference guide.

## Trademarks

Moneris and the Moneris Solutions logo are registered trademarks of Moneris Solutions Corporation.

Any software, hardware and or technology products named in this document are claimed as trademarks or registered trademarks of their respective companies.

Printed in Canada.

10 9 8 7 6 5 4 3 2 1

