

API Specification (OpenAPI/Swagger Design)

Base URL: /api/v1

1. Auth

POST /auth/login

Authenticates a user and returns a JWT token.

Request Body:

```
{
  "email": "user@mail.com",
  "password": "password123"
}
```

Success Response (200 OK):

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "token_type": "bearer",
  "expires_in": 3600,
  "user": {
    "id": "uuid",
    "full_name": "John Doe",
    "email": "user@mail.com"
  }
}
```

Error Responses:

- 401 Unauthorized: Invalid credentials.
 - 400 Bad Request: Validation error.
-

POST /auth/register

Registers a new user.

Request Body:

```
{
  "full_name": "John Doe",
  "email": "user@mail.com",
  "password": "password123",
  "phone": "+1234567890"
}
```

Success Response (201 Created):

```
{
  "message": "User successfully registered",
  "user": {
    "id": "uuid",
    "full_name": "John Doe",
    "email": "user@mail.com"
  }
}
```

```
}  
}
```

2. Users

GET /users/{id}

Returns details of a specific user.

Success Response (200 OK):

```
{  
  "id": "uuid",  
  "full_name": "John Doe",  
  "email": "user@mail.com",  
  "phone": "+1234567890",  
  "avatar_url": "https://..."  
}
```

3. Services

GET /services

List all active services for a barbershop.

Query Parameters:

- barbershop_id (required): UUID

Success Response (200 OK):

```
[  
  {  
    "id": "uuid",  
    "name": "Classic Haircut",  
    "description": "Standard haircut with scissors and clippers",  
    "price": 25.00,  
    "duration_minutes": 30  
  }  
]
```

POST /services

Create a new service (Admin/Manager only).

Request Body:

```
{  
  "barbershop_id": "uuid",  
  "name": "Classic Haircut",  
  "description": "Standard haircut",  
  "price": 25.00,  
  "duration_minutes": 30  
}
```

Success Response (201 Created): Returns the created service object.

4. Appointments

POST /appointments

Create a new appointment.

Request Body:

```
{
  "barbershop_id": "uuid",
  "client_id": "uuid",
  "barber_id": "uuid",
  "appointment_date": "2026-06-01",
  "start_time": "10:00:00",
  "end_time": "10:30:00",
  "service_ids": ["uuid-service-1", "uuid-service-2"],
  "notes": "Please use scissors only"
}
```

Success Response (201 Created):

```
{
  "id": "uuid",
  "status": "PENDING",
  "appointment_date": "2026-06-01",
  "start_time": "10:00:00",
  "end_time": "10:30:00"
}
```

GET /appointments

List appointments for a user or a barber.

Query Parameters:

- client_id (optional): UUID
- barber_id (optional): UUID
- date (optional): YYYY-MM-DD

Success Response (200 OK): Array of appointment objects.