

SharkHub CRUD Database API

Technical Endpoint Documentation

General Description

The SharkHub CRUD Database API is a RESTful direct-access data API designed for the complete management of SharkHub Barbershop. It provides CRUD operations (Create, Read, Update, Delete) on all system entities: users, barbershops, members, services, products, appointments, availabilities, and invitation codes.

1. Auth Users

Direct management of users in the auth.users table of Supabase. Allows listing, creating, retrieving, updating, and deleting authentication records.

GET /auth-users

Lists all user records in the auth.users table. Optionally filters by email.

Parameters

Parameter	Location	Tipo	Required	Description
email	query	string	No	Filter by email address

Codes de Respuesta

Code	Description
200	User list returned successfully
422	Validation error in submitted parameters

Response Example

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "email": "juan.perez@example.com",
    "created_at": "2024-01-15T10:30:00Z",
    "updated_at": "2024-03-20T08:00:00Z"
  }
]
```

POST /auth-users

Creates a new record in auth.users.

Request Body

```
{
  "email": "nuevo.usuario@example.com",
  "password": "S3cur3P@ssw0rd!"
}
```

Codes de Respuesta

Code	Description
201	User created successfully
422	Validation error in request body

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "email": "juan.perez@example.com",
  "created_at": "2024-01-15T10:30:00Z",
  "updated_at": "2024-03-20T08:00:00Z"
}
```

GET /auth-users/{user_id}

Retrieves a record from auth.users by its ID (UUID).

Parameters

Parameter	Location	Tipo	Required	Description
user_id	path	string	Sí	Unique user identifier

Codes de Respuesta

Code	Description
200	User record returned successfully
422	Validation error

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "email": "juan.perez@example.com",
  "created_at": "2024-01-15T10:30:00Z",
}
```

```
"updated_at": "2024-03-20T08:00:00Z"
}
```

PUT **/auth-users/{user_id}**

Updates specific fields of a record in auth.users.

Parameters

Parameter	Location	Tipo	Required	Description
user_id	path	string	Sí	Unique user identifier

Request Body

```
{
  "email": "nuevo.email@example.com"
}
```

Codes de Respuesta

Code	Description
200	User updated successfully
422	Validation error

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "email": "juan.perez@example.com",
  "created_at": "2024-01-15T10:30:00Z",
  "updated_at": "2024-03-20T08:00:00Z"
}
```

DELETE **/auth-users/{user_id}**

Permanently deletes a record from auth.users.

Parameters

Parameter	Location	Tipo	Required	Description
user_id	auth-users/42257407-408c-4f02-b80f-30a8ea6aa3f2?email=alejo1985@gmail.com&created_at=2026-05-16T20:35:32.364000Z&updated_at=2026-05-16T20:35:32.408000Z	string	Sí	Unique user identifier a eliminar

Codes de Respuesta

Code	Description
204	User deleted successfully (no content in response)
422	Validation error

GET /auth-users/email/{email}

Retrieves a record from auth.users by its email address.

Parameters

Parameter	Location	Tipo	Required	Description
email	path	string	Sí	User email address

Codes de Respuesta

Code	Description
200	User record returned successfully
422	Validation error

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "email": "juan.perez@example.com",
  "created_at": "2024-01-15T10:30:00Z",
  "updated_at": "2024-03-20T08:00:00Z"
}
```

2. Users (Public Profiles)

Management of public user profiles in the system. These profiles are the visible representation of the user within the SharkHub platform.

GET /users

Lists all public user profiles in the system. Optionally filters by email address.

Parameters

Parameter	Location	Tipo	Required	Description
email	query	string	No	Filter by profile email address

Codes de Respuesta

Code	Description
200	Profile list returned successfully
422	Validation error

Response Example

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "full_name": "Juan Pérez",
    "email": "juan.perez@example.com",
    "phone": "+593987654321",
    "avatar_url": "https://cdn.example.com/avatars/juan.jpg",
    "created_at": "2024-01-15T10:30:00Z",
    "updated_at": "2024-03-20T08:00:00Z"
  }
]
```

POST /users

Creates a new public user profile. The id field must match the UUID of the user in auth.users.

Request Body

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "full_name": "Juan Pérez",
  "email": "juan.perez@example.com",
  "phone": "+593987654321",
  "avatar_url": null
}
```

Codes de Respuesta

Code	Description
201	Profile created successfully
422	Validation error

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "full_name": "Juan Pérez",
  "email": "juan.perez@example.com",
  "phone": "+593987654321",
  "avatar_url": "https://cdn.example.com/avatars/juan.jpg",
  "created_at": "2024-01-15T10:30:00Z",
  "updated_at": "2024-03-20T08:00:00Z"
}
```

GET /users/{user_id}

Retrieves the details of a public user profile by its ID.

Parameters

Parameter	Location	Tipo	Required	Description
user_id	path	string	Sí	Unique user profile identifier

Codes de Respuesta

Code	Description
200	Profile returned successfully
422	Validation error

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "full_name": "Juan Pérez",
  "email": "juan.perez@example.com",
  "phone": "+593987654321",
  "avatar_url": "https://cdn.example.com/avatars/juan.jpg",
  "created_at": "2024-01-15T10:30:00Z",
  "updated_at": "2024-03-20T08:00:00Z"
}
```

PUT `/users/{user_id}`

Updates an existing public user profile.

Parameters

Parameter	Location	Tipo	Required	Description
user_id	path	string	Sí	Unique user profile identifier

Request Body

```
{
  "full_name": "Juan Carlos Pérez",
  "phone": "+593998765432",
  "avatar_url": "https://cdn.example.com/avatars/nuevo.jpg"
}
```

Codes de Respuesta

Code	Description
200	Profile updated successfully
422	Validation error

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "full_name": "Juan Pérez",
  "email": "juan.perez@example.com",
  "phone": "+593987654321",
  "avatar_url": "https://cdn.example.com/avatars/juan.jpg",
  "created_at": "2024-01-15T10:30:00Z",
  "updated_at": "2024-03-20T08:00:00Z"
}
```

DELETE `/users/{user_id}`

Deletes a public user profile from the system.

Parameters

Parameter	Location	Tipo	Required	Description
user_id	/users/a0c45272-6b56-4103-ae1a-498fad6cd5d0	string	Sí	Unique identifier of the profile to delete

Codes de Respuesta

Code	Description
204	Profile deleted successfully (no content)
422	Validation error

3. Barbershops

Complete management of barbershops registered on the platform. Allows creating, querying, updating, and deleting barbershop records.

GET /barbershops

Lists all barbershops, allowing optional filtering by slug or invite_code.

Parameters

Parameter	Location	Tipo	Required	Description
slug	query	string	No	Unique barbershop slug (URL-friendly)
invite_code	query	string	No	Code de invitación asociado a la barbería

Codes de Respuesta

Code	Description
200	Barbershop list returned successfully
422	Validation error

Response Example

```
[
  {
    "id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
    "name": "SharkHub Barbershop",
    "slug": "sharkhub-barbershop",
```

```
"description": "The best barbershop in the city",
"logo_url": "https://cdn.example.com/logos/sharkhub.png",
"address": "Av. Amazonas N35-76, Quito",
"phone": "+593999000111",
"email": "info@sharkhub.com",
"invite_code": "SHARK2024",
"is_active": true,
"created_at": "2024-01-01T00:00:00Z",
"updated_at": "2024-06-01T00:00:00Z"
}
]
```

POST **/barbershops**

Registers a new barbershop directly in the database.

Request Body

```
{
  "name": "SharkHub Barbershop",
  "slug": "sharkhub-barbershop",
  "description": "The best barbershop in the city",
  "logo_url": null,
  "address": "Av. Amazonas N35-76, Quito",
  "phone": "+593999000111",
  "email": "info@sharkhub.com"
}
```

Codes de Respuesta

Code	Description
201	Barbershop created successfully
422	Validation error

Response Example

```
{
  "id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "SharkHub Barbershop",
  "slug": "sharkhub-barbershop",
  "description": "The best barbershop in the city",
  "logo_url": "https://cdn.example.com/logos/sharkhub.png",
  "address": "Av. Amazonas N35-76, Quito",
}
```

```
"phone": "+593999000111",
"email": "info@sharkhub.com",
"invite_code": "SHARK2024",
"is_active": true,
"created_at": "2024-01-01T00:00:00Z",
"updated_at": "2024-06-01T00:00:00Z"
}
```

GET **/barbershops/{shop_id}**

Retrieves the details of a barbershop by its ID.

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier

Codes de Respuesta

Code	Description
200	Barbershop returned successfully
422	Validation error

Response Example

```
{
  "id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "SharkHub Barbershop",
  "slug": "sharkhub-barbershop",
  "description": "The best barbershop in the city",
  "logo_url": "https://cdn.example.com/logos/sharkhub.png",
  "address": "Av. Amazonas N35-76, Quito",
  "phone": "+593999000111",
  "email": "info@sharkhub.com",
  "invite_code": "SHARK2024",
  "is_active": true,
  "created_at": "2024-01-01T00:00:00Z",
  "updated_at": "2024-06-01T00:00:00Z"
}
```

PUT **/barbershops/{shop_id}**

Updates the information of an existing barbershop.

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier

Request Body

```
{
  "name": "SharkHub Pro",
  "address": "Calle Nueva 123",
  "is_active": true
}
```

Codes de Respuesta

Code	Description
200	Barbershop updated successfully
422	Validation error

Response Example

```
{
  "id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "SharkHub Barbershop",
  "slug": "sharkhub-barbershop",
  "description": "The best barbershop in the city",
  "logo_url": "https://cdn.example.com/logos/sharkhub.png",
  "address": "Av. Amazonas N35-76, Quito",
  "phone": "+593999000111",
  "email": "info@sharkhub.com",
  "invite_code": "SHARK2024",
  "is_active": true,
  "created_at": "2024-01-01T00:00:00Z",
  "updated_at": "2024-06-01T00:00:00Z"
}
```

DELETE /barbershops/{shop_id}

Deletes a barbershop from the database.

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	/barbershops/f111866a-e6b7-49f3-b9f8-77b5e5f16ceb	string	Sí	Unique barbershop identifier a eliminar

Codes de Respuesta

Code	Description
204	Barbershop deleted successfully (no content)
422	Validation error

GET /barbershops/slug/{slug}

Retrieves the details of a barbershop by its unique slug.

Parameters

Parameter	Location	Tipo	Required	Description
slug	path	string	Sí	Unique barbershop slug (e.g.: sharkhub-barbershop)

Codes de Respuesta

Code	Description
200	Barbershop returned successfully
422	Validation error

Response Example

```
{
  "id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "SharkHub Barbershop",
  "slug": "sharkhub-barbershop",
  "description": "The best barbershop in the city",
  "logo_url": "https://cdn.example.com/logos/sharkhub.png",
  "address": "Av. Amazonas N35-76, Quito",
  "phone": "+593999000111",
  "email": "info@sharkhub.com",
  "invite_code": "SHARK2024",
  "is_active": true,
  "created_at": "2024-01-01T00:00:00Z",
  "updated_at": "2024-06-01T00:00:00Z"
```

```
}

```

4. Barbershop Members

Management of members belonging to a barbershop (barbers, administrators, etc.). Allows managing roles and statuses within each barbershop.

GET /barbershop-members

Lists all barbershop members. Allows filtering by barbershop_id and/or user_id.

Parameters

Parameter	Location	Tipo	Required	Description
barbershop_id	query	string	No	Filter by barbershop ID
user_id	query	string	No	Filter by user ID

Codes de Respuesta

Code	Description
200	Member list returned successfully
422	Validation error

Response Example

```
[
  {
    "id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
    "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
    "user_id": "550e8400-e29b-41d4-a716-446655440000",
    "role": "barber",
    "status": "active",
    "joined_at": "2024-02-10T09:00:00Z"
  }
]
```

POST /barbershop-members

Adds a new member to a barbershop in the database.

Request Body

```
{

```

```
"barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
"user_id": "550e8400-e29b-41d4-a716-446655440000",
"role": "barber",
"status": "active"
}
```

Codes de Respuesta

Code	Description
201	Member added successfully
422	Validation error

Response Example

```
{
  "id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "user_id": "550e8400-e29b-41d4-a716-446655440000",
  "role": "barber",
  "status": "active",
  "joined_at": "2024-02-10T09:00:00Z"
}
```

GET /barbershop-members/{member_id}

Retrieves the details of a member by their membership ID.

Parameters

Parameter	Location	Tipo	Required	Description
member_id	path	string	Sí	Unique membership identifier

Codes de Respuesta

Code	Description
200	Member returned successfully
422	Validation error

Response Example

```
{
```

```
"id": "ble2f3a4-1234-5678-90ab-cdef01234567",
"barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
"user_id": "550e8400-e29b-41d4-a716-446655440000",
"role": "barber",
"status": "active",
"joined_at": "2024-02-10T09:00:00Z"
}
```

PUT `/barbershop-members/{member_id}`

Updates the role or status of a barbershop member.

Parameters

Parameter	Location	Tipo	Required	Description
member_id	path	string	Sí	Unique membership identifier

Request Body

```
{
  "role": "admin",
  "status": "active"
}
```

Codes de Respuesta

Code	Description
200	Member updated successfully
422	Validation error

Response Example

```
{
  "id": "ble2f3a4-1234-5678-90ab-cdef01234567",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "user_id": "550e8400-e29b-41d4-a716-446655440000",
  "role": "barber",
  "status": "active",
  "joined_at": "2024-02-10T09:00:00Z"
}
```


DELETE `/barbershop-members/{member_id}`

Removes a member from a barbershop.

Parameters

Parameter	Location	Tipo	Required	Description
member_id	/barbershop-members/52dd9108-7ae9-4abf-b9f9-99c0f128826d	string	Sí	Unique membership identifier a eliminar

Codes de Respuesta

Code	Description
204	Member deleted successfully (no content)
422	Validation error

5. Services

Management of services offered by each barbershop, such as haircuts, shaves, treatments, etc.

GET `/services`

Lists all services in the system, allowing filtering by barbershop_id.

Parameters

Parameter	Location	Tipo	Required	Description
barbershop_id	query	string	No	Filter services by barbershop ID

Codes de Respuesta

Code	Description
200	Service list returned successfully
422	Validation error

Response Example

```
[  
{
```

```
"id": "c2d3e4f5-aaaa-bbbb-cccc-ddddeeee0001",
"barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
"name": "Classic Haircut",
"description": "Traditional cut with a perfect finish",
"price": "15.00",
"duration_minutes": 30,
"is_active": true
}
]
```

POST /services

Creates a new service in the database.

Request Body

```
{
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "Classic Haircut",
  "description": "Traditional cut with a perfect finish",
  "price": "15.00",
  "duration_minutes": 30
}
```

Codes de Respuesta

Code	Description
201	Service created successfully
422	Validation error

Response Example

```
{
  "id": "c2d3e4f5-aaaa-bbbb-cccc-ddddeeee0001",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "Classic Haircut",
  "description": "Traditional cut with a perfect finish",
  "price": "15.00",
  "duration_minutes": 30,
  "is_active": true
}
```

GET `/services/{service_id}`

Retrieves the details of a service by its ID.

Parameters

Parameter	Location	Tipo	Required	Description
service_id	path	string	Sí	Unique service identifier

Codes de Respuesta

Code	Description
200	Service returned successfully
422	Validation error

Response Example

```
{
  "id": "c2d3e4f5-aaaa-bbbb-cccc-ddddeeee0001",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "Classic Haircut",
  "description": "Traditional cut with a perfect finish",
  "price": "15.00",
  "duration_minutes": 30,
  "is_active": true
}
```

PUT `/services/{service_id}`

Updates an existing service in the database.

Parameters

Parameter	Location	Tipo	Required	Description
service_id	path	string	Sí	Unique service identifier

Request Body

```
{
  "name": "Premium Haircut",
  "price": "18.00",
  "duration_minutes": 40,
}
```

```
"is_active": true
}
```

Codes de Respuesta

Code	Description
200	Service updated successfully
422	Validation error

Response Example

```
{
  "id": "c2d3e4f5-aaaa-bbbb-cccc-ddddeeee0001",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "Classic Haircut",
  "description": "Traditional cut with a perfect finish",
  "price": "15.00",
  "duration_minutes": 30,
  "is_active": true
}
```

DELETE /services/{service_id}

Deletes a service from the database.

Parameters

Parameter	Location	Tipo	Required	Description
service_id	/services/8b5ffe40-3a94-49e0-b32d-f929b483f8ed	string	Sí	Unique service identifier a eliminar

Codes de Respuesta

Code	Description
204	Service deleted successfully (no content)
422	Validation error

6. Products

Management of the product catalog available for sale at each barbershop (pomades, shampoos, accessories, etc.).

GET /products

Lists all products, allowing filtering by barbershop_id.

Parameters

Parameter	Location	Tipo	Required	Description
barbershop_id	query	string	No	Filter products by barbershop ID

Codes de Respuesta

Code	Description
200	Product list returned successfully
422	Validation error

Response Example

```
[
  {
    "id": "d4e5f6a7-1111-2222-3333-444455556666",
    "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
    "name": "Extra Strong Hold Pomade",
    "description": "High-performance pomade for long-lasting styles",
    "price": "12.50",
    "stock": 50,
    "is_active": true,
    "created_at": "2024-03-01T00:00:00Z",
    "updated_at": "2024-03-01T00:00:00Z"
  }
]
```

POST /products

Creates a new product in the database.

Request Body

```
{
```

```
"barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
"name": "Extra Strong Hold Pomade",
"description": "High-performance pomade",
"price": "12.50",
"stock": 50
}
```

Codes de Respuesta

Code	Description
201	Product created successfully
422	Validation error

Response Example

```
{
  "id": "d4e5f6a7-1111-2222-3333-444455556666",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "Extra Strong Hold Pomade",
  "description": "High-performance pomade for long-lasting styles",
  "price": "12.50",
  "stock": 50,
  "is_active": true,
  "created_at": "2024-03-01T00:00:00Z",
  "updated_at": "2024-03-01T00:00:00Z"
}
```

GET /products/{product_id}

Retrieves the details of a product by its ID.

Parameters

Parameter	Location	Tipo	Required	Description
product_id	path	string	Sí	Unique product identifier

Codes de Respuesta

Code	Description
200	Product returned successfully
422	Validation error

Response Example

```
{
  "id": "d4e5f6a7-1111-2222-3333-444455556666",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "name": "Extra Strong Hold Pomade",
  "description": "High-performance pomade for long-lasting styles",
  "price": "12.50",
  "stock": 50,
  "is_active": true,
  "created_at": "2024-03-01T00:00:00Z",
  "updated_at": "2024-03-01T00:00:00Z"
}
```

PUT /products/{product_id}

Updates the information of an existing product.

Parameters

Parameter	Location	Tipo	Required	Description
product_id	path	string	Sí	Unique product identifier

Request Body

```
{
  "name": "Premium Matte Pomade",
  "price": "14.00",
  "stock": 30,
  "is_active": true
}
```

Codes de Respuesta

Code	Description
200	Product updated successfully
422	Validation error

Response Example

```
{
```

```
"id": "d4e5f6a7-1111-2222-3333-444455556666",
"barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
"name": "Extra Strong Hold Pomade",
"description": "High-performance pomade for long-lasting styles",
"price": "12.50",
"stock": 50,
"is_active": true,
"created_at": "2024-03-01T00:00:00Z",
"updated_at": "2024-03-01T00:00:00Z"
}
```

DELETE **/products/{product_id}**

Deletes a product from the database.

Parameters

Parameter	Location	Tipo	Required	Description
product_id	/products/5574fa35-2492-4895-b89b-536c2e58cc77	string	Sí	Unique product identifier a eliminar

Codes de Respuesta

Code	Description
204	Product deleted successfully (no content)
422	Validation error

7. Appointments

Management of appointments/bookings made by clients. Allows scheduling, querying, modifying, and canceling appointments at the barbershop.

GET /appointments

Lists all appointments in the database, allowing filtering by barbershop_id, client_id, barber_id, and date.

Parameters

Parameter	Location	Tipo	Required	Description
barbershop_id	query	string	No	Filter by barbershop ID
client_id	query	string	No	Filter by client ID
barber_id	query	string	No	Filter by barber ID
appointment_date	query	string	No	Filter by date (YYYY-MM-DD)

Codes de Respuesta

Code	Description
200	Appointment list returned successfully
422	Validation error

Response Example

```
[
  {
    "id": "e5f6a7b8-2222-3333-4444-555566667777",
    "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
    "client_id": "550e8400-e29b-41d4-a716-446655440000",
    "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
    "appointment_date": "2024-07-15",
    "start_time": "10:00:00",
    "end_time": "10:30:00",
    "status": "confirmed",
    "notes": "Client prefers cut without clippers on the sides",
    "created_at": "2024-07-10T08:00:00Z",
    "updated_at": "2024-07-10T08:00:00Z"
  }
]
```

POST **/appointments**

Creates a new appointment (booking) directly in the database.

Request Body

```
{
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "client_id": "550e8400-e29b-41d4-a716-446655440000",
  "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
  "appointment_date": "2024-07-15",
  "start_time": "10:00:00",
  "end_time": "10:30:00",
  "notes": "Client prefers cut without clippers on the sides"
}
```

Codes de Respuesta

Code	Description
201	Appointment created successfully
422	Validation error

Response Example

```
{
  "id": "e5f6a7b8-2222-3333-4444-555566667777",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "client_id": "550e8400-e29b-41d4-a716-446655440000",
  "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
  "appointment_date": "2024-07-15",
  "start_time": "10:00:00",
  "end_time": "10:30:00",
  "status": "confirmed",
  "notes": "Client prefers cut without clippers on the sides",
  "created_at": "2024-07-10T08:00:00Z",
  "updated_at": "2024-07-10T08:00:00Z"
}
```

GET **/appointments/{appointment_id}**

Retrieves the details of an appointment by its ID.

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier

Codes de Respuesta

Code	Description
200	Appointment returned successfully
422	Validation error

Response Example

```
{
  "id": "e5f6a7b8-2222-3333-4444-555566667777",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "client_id": "550e8400-e29b-41d4-a716-446655440000",
  "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
  "appointment_date": "2024-07-15",
  "start_time": "10:00:00",
  "end_time": "10:30:00",
  "status": "confirmed",
  "notes": "Client prefers cut without clippers on the sides",
  "created_at": "2024-07-10T08:00:00Z",
  "updated_at": "2024-07-10T08:00:00Z"
}
```

PUT /appointments/{appointment_id}

Updates an existing appointment in the database.

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier

Request Body

```
{
  "start_time": "11:00:00",
  "end_time": "11:30:00",
  "status": "confirmed",
  "notes": "Rescheduled by the client"
}
```

Codes de Respuesta

Code	Description
200	Appointment updated successfully
422	Validation error

Response Example

```
{
  "id": "e5f6a7b8-2222-3333-4444-555566667777",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "client_id": "550e8400-e29b-41d4-a716-446655440000",
  "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
  "appointment_date": "2024-07-15",
  "start_time": "10:00:00",
  "end_time": "10:30:00",
  "status": "confirmed",
  "notes": "Client prefers cut without clippers on the sides",
  "created_at": "2024-07-10T08:00:00Z",
  "updated_at": "2024-07-10T08:00:00Z"
}
```

DELETE /appointments/{appointment_id}

Deletes an appointment from the database.

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	/appointment-services/9785f22b-3a89-4945-82a7-77d379756a78	string	Sí	Unique appointment identifier a eliminar

Codes de Respuesta

Code	Description
204	Appointment deleted successfully (no content)
422	Validation error

8. Appointment Services

Management of the relationship between appointments and services. An appointment can have multiple associated services.

GET /appointment-services

Lists the relationships between appointments and services, allowing filtering by `appointment_id` and/or `service_id`.

Parameters

Parameter	Location	Tipo	Required	Description
<code>appointment_id</code>	query	string	No	Filter by appointment ID
<code>service_id</code>	query	string	No	Filter by service ID

Codes de Respuesta

Code	Description
200	Relationship list returned successfully
422	Validation error

Response Example

```
[
  {
    "id": "f6a7b8c9-3333-4444-5555-666677778888",
    "appointment_id": "e5f6a7b8-2222-3333-4444-555566667777",
    "service_id": "c2d3e4f5-aaaa-bbbb-cccc-ddddeeee0001"
  }
]
```

POST /appointment-services

Links a service to an appointment in the database.

Request Body

```
{
  "appointment_id": "e5f6a7b8-2222-3333-4444-555566667777",
```

```
"service_id": "c2d3e4f5-aaaa-bbbb-cccc-ddddeeee0001"
}
```

Codes de Respuesta

Code	Description
201	Appointment-service relationship created successfully
422	Validation error

Response Example

```
{
  "id": "f6a7b8c9-3333-4444-5555-666677778888",
  "appointment_id": "e5f6a7b8-2222-3333-4444-555566667777",
  "service_id": "c2d3e4f5-aaaa-bbbb-cccc-ddddeeee0001"
}
```

GET /appointment-services/{relation_id}

Retrieves the details of an appointment-service relationship by its ID.

Parameters

Parameter	Location	Tipo	Required	Description
relation_id	path	string	Sí	Unique relationship identifier

Codes de Respuesta

Code	Description
200	Relationship returned successfully
422	Validation error

Response Example

```
{
  "id": "f6a7b8c9-3333-4444-5555-666677778888",
  "appointment_id": "e5f6a7b8-2222-3333-4444-555566667777",
  "service_id": "c2d3e4f5-aaaa-bbbb-cccc-ddddeeee0001"
}
```

DELETE `/appointment-services/{relation_id}`

Unlinks a service from an appointment by the relationship ID.

Parameters

Parameter	Location	Tipo	Required	Description
relation_id	/appointment-services/3f82a1b4-7b9c-4d2e-ae1f-5c6b7a8b9c0d	string	Sí	Unique relationship identifier a eliminar

Codes de Respuesta

Code	Description
204	Relationship deleted successfully (no content)
422	Validation error

DELETE `/appointment-services/appointment/{appointment_id}/service/{service_id}`

Unlinks a service from an appointment using the appointment ID and service ID directly.

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	/appointment-services/appointment/apt-7721/service/srv-404	string	Sí	Appointment ID
service_id	/appointment-services/appointment/9b1deb4d-3b7d-4bad-9bdd-2b0d7b3dcb6d/service/5f4dcc3b-5aa7-4af3-903b-c5ec7ffee0d5	string	Sí	ID of the service to unlink

Codes de Respuesta

Code	Description
204	Relationship deleted successfully (no content)
422	Validation error

9. Availabilities

Management of barber availability time blocks. Defines the schedules during which each barber can attend appointments.

GET /availabilities

Lists all availability blocks, allowing filtering by barber_id and barbershop_id.

Parameters

Parameter	Location	Tipo	Required	Description
barber_id	query	string	No	Filter by barber ID
barbershop_id	query	string	No	Filter by barbershop ID

Codes de Respuesta

Code	Description
200	Availability list returned successfully
422	Validation error

Response Example

```
[
  {
    "id": "a7b8c9d0-4444-5555-6666-777788889999",
    "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
    "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
    "day_of_week": 1,
    "start_time": "09:00:00",
    "end_time": "18:00:00",
    "is_available": true
  }
]
```

POST /availabilities

Registers a new availability block for a barber in the database.

Request Body

```
{
  "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
```



```
"barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
"day_of_week": 1,
"start_time": "09:00:00",
"end_time": "18:00:00",
"is_available": true
}
```

Codes de Respuesta

Code	Description
201	Availability block created successfully
422	Validation error

Response Example

```
{
  "id": "a7b8c9d0-4444-5555-6666-777788889999",
  "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "day_of_week": 1,
  "start_time": "09:00:00",
  "end_time": "18:00:00",
  "is_available": true
}
```

GET /availabilities/{availability_id}

Retrieves the details of an availability block by its ID.

Parameters

Parameter	Location	Tipo	Required	Description
availability_id	path	string	Sí	Unique availability block identifier

Codes de Respuesta

Code	Description
200	Availability block returned successfully
422	Validation error

Response Example

```
{
  "id": "a7b8c9d0-4444-5555-6666-777788889999",
  "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "day_of_week": 1,
  "start_time": "09:00:00",
  "end_time": "18:00:00",
  "is_available": true
}
```

PUT /availabilities/{availability_id}

Updates an existing availability block in the database.

Parameters

Parameter	Location	Tipo	Required	Description
availability_id	path	string	Sí	Unique block identifier

Request Body

```
{
  "start_time": "08:00:00",
  "end_time": "17:00:00",
  "is_available": true
}
```

Codes de Respuesta

Code	Description
200	Availability updated successfully
422	Validation error

Response Example

```
{
  "id": "a7b8c9d0-4444-5555-6666-777788889999",
  "barber_id": "b1e2f3a4-1234-5678-90ab-cdef01234567",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "day_of_week": 1,
```

```
"start_time": "09:00:00",  
"end_time": "18:00:00",  
"is_available": true  
}
```

DELETE /availabilities/{availability_id}

Deletes an availability block from the database.

Parameters

Parameter	Location	Tipo	Required	Description
availability_id	/availabilities/bc1c85f7-3aa7-420a-aed4-379757704e5d	string	Sí	Unique block identifier a eliminar

Codes de Respuesta

Code	Description
204	Availability deleted successfully (no content)
422	Validation error

10. Invitation Codes (Codes de Invitación)

Management of invitation codes that allow users to join a barbershop as members.

GET /invitation-codes

Lists all invitation codes in the system, optionally filtering by barbershop_id and/or code.

Parameters

Parameter	Location	Tipo	Required	Description
barbershop_id	query	string	No	Filter by barbershop ID
code	query	string	No	Filter by invitation code value

Codes de Respuesta

Code	Description
200	Code list returned successfully
422	Validation error

Response Example

```
[
  {
    "id": "b8c9d0e1-5555-6666-7777-888899990000",
    "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
    "code": "SHARK2024",
    "expires_at": "2025-01-01T00:00:00Z",
    "is_active": true,
    "created_at": "2024-01-01T00:00:00Z"
  }
]
```

POST /invitation-codes

Creates a new invitation code in the database.

Request Body

```
{
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "code": "SHARK2024",
  "expires_at": "2025-01-01T00:00:00Z",
  "is_active": true
}
```

Codes de Respuesta

Code	Description
201	Code de invitación creado exitosamente
422	Validation error

Response Example

```
{
  "id": "b8c9d0e1-5555-6666-7777-888899990000",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "code": "SHARK2024",
  "expires_at": "2025-01-01T00:00:00Z",
  "is_active": true,
  "created_at": "2024-01-01T00:00:00Z"
}
```

GET `/invitation-codes/{code_id}`

Retrieves the details of an invitation code by its ID.

Parameters

Parameter	Location	Tipo	Required	Description
code_id	path	string	Sí	Unique code identifier

Codes de Respuesta

Code	Description
200	Code de invitación retornado exitosamente
422	Validation error

Response Example

```
{
  "id": "b8c9d0e1-5555-6666-7777-888899990000",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "code": "SHARK2024",
  "expires_at": "2025-01-01T00:00:00Z",
  "is_active": true,
  "created_at": "2024-01-01T00:00:00Z"
}
```

PUT `/invitation-codes/{code_id}`

Updates the expiration date or active status of an invitation code in the database.

Parameters

Parameter	Location	Tipo	Required	Description
code_id	path	string	Sí	Unique code identifier

Request Body

```
{
  "expires_at": "2026-01-01T00:00:00Z",
  "is_active": false
}
```

```
}

```

Codes de Respuesta

Code	Description
200	Code actualizado exitosamente
422	Validation error

Response Example

```
{
  "id": "b8c9d0e1-5555-6666-7777-888899990000",
  "barbershop_id": "a3f1c2d4-e5b6-7890-abcd-ef1234567890",
  "code": "SHARK2024",
  "expires_at": "2025-01-01T00:00:00Z",
  "is_active": true,
  "created_at": "2024-01-01T00:00:00Z"
}

```

DELETE /invitation-codes/{code_id}

Deletes an invitation code from the database.

Parameters

Parameter	Location	Tipo	Required	Description
code_id	/invitation-codes/e0a1b2c3-d4e5-4f6a-7b8c-9d0e1f2a3b4c	string	Sí	Unique code identifier a eliminar

Codes de Respuesta

Code	Description
204	Code eliminado exitosamente (sin contenido)
422	Validation error

11. System

System endpoints for monitoring and verifying API health status.

GET /health

Verifies the status of the API server and its connectivity with the Supabase database.

Codes de Respuesta

Code	Description
200	The server is operational and connected to the database

Response Example

```
{
  "status": "ok",
  "database": "connected",
  "version": "1.0.0"
}
```