

SharkHub Business Rules API

Technical Endpoint Documentation

Business rules, RBAC, sessions and appointment booking flow

Prepared from Swagger UI, Postman Collection, Postman Environment and validation elements.

v1.0.0 | Confidential

General Description

The SharkHub Business Rules API is a REST API responsible for the operational rules of the SharkHub Barbershop platform. Unlike a direct CRUD database API, this service centralizes authentication, role-based access control, membership validation, schedule availability, appointment booking rules, service linking, owner workflows, barber workflows and customer-facing reservation flows.

The examples in this document use the same coherent validation scenario that was tested in Postman: one owner, one barbershop, one active barber member, one customer, one service, barber availability blocks, one appointment and one invitation code. Tokens are represented through Postman environment variables instead of real JWT values.

Postman Environment

Variable	Tipo	Status	Description
baseUrl	default	Enabled	Postman variable used by the collection
token	default	Enabled	Postman variable used by the collection
tokenBarber	default	Enabled	Postman variable used by the collection
tokenCustomer	default	Enabled	Postman variable used by the collection

Validation Elements Used in Examples

Element	Value	Purpose
owner_user_id	0a4dfa09-c93a-4c90-a4af-e775462367aa	Owner SharkHub
barber_user_id	9d814758-fc3e-4da7-93c1-e6c5768c58c8	Carlos Barber
customer_user_id	2e768092-e34e-47e9-9a1a-60bd4c207794	Test Customer
shop_id	95214e64-98d5-4e39-82d4-487b8673ca90	SharkHub Barbería
barber_member_id	7929e68b-3b5d-438b-90ce-f52186f7df2b	Active barber member
service_id	5be23cc1-3fea-4f38-856c-d21d7bba607b	Corte Normal
appointment_id	afd7e13f-829b-4c3c-b061-470a908eb3f9	Validated appointment
availability_id	c11da953-3d40-463e-95c0-f9abf379f053	Monday availability block
invitation_id	5684c9eb-b5c0-4f4f-9ce8-4fa60bfadbba	Invitation code record

Real JWT values from Postman were intentionally replaced by {{token}}, {{tokenBarber}} and {{tokenCustomer}}.

Endpoint Index

Module	Method	Endpoint	Authentication
Authentication & Sessions	POST	/auth/register	No authentication required
Authentication & Sessions	POST	/auth/login	No authentication required
Authentication & Sessions	POST	/sessions	No authentication required
Authentication & Sessions	GET	/sessions/current	Bearer token required
Authentication & Sessions	DELETE	/sessions/current	Bearer token required
Users	GET	/users	Bearer token required
Users	POST	/users	Bearer token required
Users	GET	/users/me	Bearer token required
Users	GET	/users/{user_id}	Bearer token required
Users	PUT	/users/{user_id}	Bearer token required
Barbershops & Members	GET	/barbershops	No authentication required
Barbershops & Members	POST	/barbershops	No authentication required
Barbershops & Members	GET	/barbershops/{shop_id}	No authentication required / Public query
Barbershops & Members	PUT	/barbershops/{shop_id}	Bearer token required

Module	Method	Endpoint	Authentication
Barbershops & Members	DELETE	/barbershops/{shop_id}	Bearer token required
Barbershops & Members	GET	/barbershops/{shop_id}/members	Bearer token required
Barbershops & Members	POST	/barbershops/{shop_id}/members	Bearer token required
Barbershops & Members	GET	/barbershops/{shop_id}/members/{member_id}	Bearer token required
Barbershops & Members	PUT	/barbershops/{shop_id}/members/{member_id}	Bearer token required
Barbershops & Members	DELETE	/barbershops/{shop_id}/members/{member_id}	Bearer token required
Services	GET	/services	No authentication required / Public query
Services	GET	/barbershops/{shop_id}/services	No authentication required / Public query
Services	POST	/barbershops/{shop_id}/services	Bearer token required
Services	GET	/barbershops/{shop_id}/services/{service_id}	No authentication required / Public query
Services	PUT	/barbershops/{shop_id}/services/{service_id}	Bearer token required
Services	DELETE	/barbershops/{shop_id}/services/{service_id}	Bearer token required
Products	GET	/barbershops/{shop_id}/products	No authentication required / Public query
Products	POST	/barbershops/{shop_id}/products	Bearer token required
Products	GET	/barbershops/{shop_id}/products/{product_id}	No authentication required / Public query
Products	PUT	/barbershops/{shop_id}/products/{product_id}	Bearer token required
Products	DELETE	/barbershops/{shop_id}/products/{product_id}	Bearer token required
Appointments	GET	/appointments	Bearer token required
Appointments	POST	/appointments	Bearer token required
Appointments	GET	/appointments/{appointment_id}	Bearer token required
Appointments	PUT	/appointments/{appointment_id}	Bearer token required
Appointments	DELETE	/appointments/{appointment_id}	Bearer token required
Appointments	GET	/appointments/{appointment_id}/services	Bearer token required
Appointments	POST	/appointments/{appointment_id}/services	Bearer token required
Appointments	DELETE	/appointments/{appointment_id}/services/{service_id}	Bearer token required
Barber Availabilities	GET	/barbers/{barber_id}/availabilities	No authentication required / Public query
Barber Availabilities	POST	/barbers/{barber_id}/availabilities	Bearer token required
Barber Availabilities	PUT	/barbers/{barber_id}/availabilities/{availability_id}	Bearer token required
Barber Availabilities	DELETE	/barbers/{barber_id}/availabilities/{availability_id}	Bearer token required
Invitations	GET	/barbershops/{shop_id}/invitations	No authentication required / Public query
Invitations	POST	/barbershops/{shop_id}/invitations	Bearer token required
Invitations	GET	/barbershops/{shop_id}/invitations/{invitation_id}	No authentication required / Public query
Invitations	PUT	/barbershops/{shop_id}/invitations/{invitation_id}	Bearer token required
Invitations	DELETE	/barbershops/{shop_id}/invitations/{invitation_id}	Bearer token required
Role Dashboards (Owner, Barber, Customer)	PUT	/api/owner/barbershop	Bearer {{token}} (Owner)
Role Dashboards (Owner, Barber, Customer)	POST	/api/owner/barbers	Bearer {{token}} (Owner)
Role Dashboards (Owner, Barber, Customer)	PATCH	/api/owner/barbers/{barber_id}/status	Bearer {{token}} (Owner)
Role Dashboards (Owner, Barber, Customer)	GET	/api/owner/appointments	Bearer {{token}} (Owner)

Module	Method	Endpoint	Authentication
Role Dashboards (Owner, Barber, Customer)	PATCH	/api/owner/appointments/{appointment_id}/status	Bearer {{token}} (Owner)
Role Dashboards (Owner, Barber, Customer)	GET	/api/barber/appointments	Bearer {{tokenBarber}} (Barber)
Role Dashboards (Owner, Barber, Customer)	POST	/api/barber/services	Bearer {{tokenBarber}} (Barber)
Role Dashboards (Owner, Barber, Customer)	POST	/api/barber/products	Bearer {{tokenBarber}} (Barber)
Role Dashboards (Owner, Barber, Customer)	GET	/api/customer/services	Bearer {{tokenCustomer}} (Customer)
Role Dashboards (Owner, Barber, Customer)	GET	/api/customer/available-times	Bearer {{tokenCustomer}} (Customer)
Role Dashboards (Owner, Barber, Customer)	POST	/api/customer/appointments	Bearer {{tokenCustomer}} (Customer)
System	GET	/health	No authentication required

1. Authentication & Sessions

Endpoints for user registration, login, JWT session creation, current-session lookup and logout.

POST

/auth/register

Registers a new user in the platform and creates the related public profile.

Authentication: No authentication required

Request Body

```
{
  "name": "Test Customer",
  "email": "customer1@example.com",
  "password": "1234qwer"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
422	Validation Error

Response Example

```
{
  "message": "Usuario registrado exitosamente",
  "user": {
    "id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
    "name": "Test Customer",
    "email": "customer1@example.com"
  }
}
```

POST

/auth/login

Authenticates a user and returns a JWT access token with the associated profile.

Authentication: No authentication required

Request Body

```
{
  "email": "customer1@example.com",
  "password": "1234qwer"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
201	Created successfully
422	Validation Error

Response Example

```
{
  "message": "Sesión iniciada correctamente",
  "token": "{{tokenCustomer}}",
  "user": {
    "id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
    "name": "Test Customer",
    "email": "customer1@example.com"
  }
}
```

POST

/sessions

Creates an API session using email and password credentials.

Authentication: No authentication required

Request Body

```
{
  "email": "owner@example.com",
  "password": "1234qwer"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
422	Validation Error

Response Example

```
{
  "token": "{{token}}",
  "expires_at": null
}
```

GET

/sessions/current

Returns the active session associated with the provided Bearer token.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
401	Unauthorized - missing or malformed token
422	Validation Error

Response Example

```
{
  "user_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "full_name": "Test Customer",
  "session_active": true
}
```

DELETE

/sessions/current

Destroys the current session and performs logout for the authenticated user.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
422	Validation Error

Response Example

No response body.

2. Users

Endpoints for listing, creating, reading, updating and deleting public user profiles.

GET /users

Lists the registered public user profiles available to the authenticated user.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
  {
    "id": "0a4dfa09-c93a-4c90-a4af-e775462367aa",
    "full_name": "Owner SharkHub",
    "email": "owner@example.com",
    "phone": null,
    "avatar_url": null,
    "created_at": "2026-06-12T01:05:34.000000Z",
    "updated_at": "2026-06-12T01:05:34.000000Z"
  },
  {
    "id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
    "full_name": "Carlos Barber",
    "email": "barber1@example.com",
    "phone": null,
    "avatar_url": null,
    "created_at": "2026-06-12T01:28:54.000000Z",
    "updated_at": "2026-06-12T01:28:54.000000Z"
  },
  {
    "id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
    "full_name": "Test Customer",
    "email": "customer1@example.com",
    "phone": null,
    "avatar_url": null,
    "created_at": "2026-06-12T02:07:29.000000Z",
    "updated_at": "2026-06-12T02:07:29.000000Z"
  }
]
```

POST /users

Creates a public user profile manually from an administrative context.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "full_name": "Jorge Ínigo",
  "email": "admin@example.com",
  "phone": "0987654321",
  "avatar_url": "image.png"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
422	Validation Error

Response Example

```
{
  "id": "7b398d1f-8b27-4f49-be44-2335147c6857",
  "full_name": "Jorge Ínigo",
  "email": "admin@example.com",
  "phone": "0987654321",
  "avatar_url": "image.png",
  "created_at": "2026-06-10T02:22:25.280000Z",
  "updated_at": "2026-06-10T02:22:25.280000Z"
}
```

GET

/users/me

Returns the profile of the currently authenticated user.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "full_name": "Test Customer",
  "email": "customer1@example.com",
  "phone": null,
  "avatar_url": null,
  "created_at": "2026-06-12T02:07:29.000000Z",
  "updated_at": "2026-06-12T02:07:29.000000Z"
}
```

GET

/users/{user_id}

Returns the public profile associated with a specific user identifier.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
user_id	path	string	Sí	Unique user identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "full_name": "Test Customer",
  "email": "customer1@example.com",
  "phone": null,
  "avatar_url": null,
  "created_at": "2026-06-12T02:07:29.000000Z",
  "updated_at": "2026-06-12T02:07:29.000000Z"
}
```

PUT /users/{user_id}

Updates profile data such as full name, phone or avatar URL.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
user_id	path	string	Sí	Unique user identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "full_name": "Test Customer Updated",
  "phone": "0987654321",
  "avatar_url": "image.png"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "full_name": "Test Customer",
  "email": "customer1@example.com",
  "phone": null,
  "avatar_url": null,
  "created_at": "2026-06-12T02:07:29.000000Z",
  "updated_at": "2026-06-12T02:07:29.000000Z"
}
```

3. Barbershops & Members

Endpoints for managing barbershops and their member relationships, including owner and barber roles.

GET	/barbershops
-----	--------------

Lists the barbershops registered in the platform.

Authentication: No authentication required

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
  {
    "id": "95214e64-98d5-4e39-82d4-487b8673ca90",
    "name": "SharkHub Barbería",
    "slug": "sharkhub-barberia",
    "description": "Barbería principal de pruebas",
    "logo_url": "logo.png",
    "address": "Sangolquí",
    "phone": "0987654321",
    "email": "barberia@example.com",
    "invite_code": "SH-4QL-15P",
    "is_active": true,
    "created_at": "2026-06-12T01:18:54.207000Z",
    "updated_at": "2026-06-12T01:18:54.207000Z"
  }
]
```

POST	/barbershops
------	--------------

Registers a new barbershop and assigns the authenticated creator as owner.

Authentication: No authentication required

Request Body

```
{
  "name": "SharkHub Barbería",
  "slug": "sharkhub-barberia",
  "description": "Barbería principal de pruebas",
  "logo_url": "logo.png",
  "address": "Sangolquí",
  "phone": "0987654321",
  "email": "barberia@example.com"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
422	Validation Error

Response Example

```
{
  "id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "name": "SharkHub Barbería",
  "slug": "sharkhub-barberia",
  "description": "Barberia principal de pruebas",
  "logo_url": "logo.png",
  "address": "Sangolquí",
  "phone": "0987654321",
  "email": "barberia@example.com",
  "invite_code": "SH-4QL-15P",
  "is_active": true,
  "created_at": "2026-06-12T01:18:54.207000Z",
  "updated_at": "2026-06-12T01:18:54.207000Z"
}
```

GET	/barbershops/{shop_id}
-----	------------------------

Returns detailed information for a specific barbershop.

Authentication: No authentication required / Public query

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

<pre>{ "id": "95214e64-98d5-4e39-82d4-487b8673ca90", "name": "SharkHub Barbería", "slug": "sharkhub-barberia", "description": "Barbería principal de pruebas", "logo_url": "logo.png", "address": "Sangolquí", "phone": "0987654321", "email": "barberia@example.com", "invite_code": "SH-4QL-15P", "is_active": true, "created_at": "2026-06-12T01:18:54.207000Z", "updated_at": "2026-06-12T01:18:54.207000Z" }</pre>

PUT	/barbershops/{shop_id}
-----	------------------------

Updates the information of a barbershop. Restricted to its owner.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

<pre>{ "name": "SharkHub Barbería", "description": "Descripción actualizada desde Postman.", "logo_url": "logo.png", "address": "Sangolquí", "phone": "0999999999", "email": "barberia@example.com" }</pre>

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "name": "SharkHub Barbería",
  "slug": "sharkhub-barberia",
  "description": "Barberia principal de pruebas",
  "logo_url": "logo.png",
  "address": "Sangolquí",
  "phone": "0987654321",
  "email": "barberia@example.com",
  "invite_code": "SH-4QL-15P",
  "is_active": true,
  "created_at": "2026-06-12T01:18:54.207000Z",
  "updated_at": "2026-06-12T01:18:54.207000Z"
}
```

DELETE

/barbershops/{shop_id}

Deletes a barbershop. Restricted to its owner.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
422	Validation Error

Response Example

No response body.

GET

/barbershops/{shop_id}/members

Lists owner and barber members linked to a barbershop.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
  {
    "member_id": "45594745-5dee-4e20-8e7d-8cc193c6ea07",
    "user_id": "0a4dfa09-c93a-4c90-a4af-e775462367aa",
    "name": "Owner SharkHub",
    "role": "owner",
    "status": "active",
    "joined_at": "2026-06-12T01:18:54.442000Z"
  },
  {
    "member_id": "7929e68b-3b5d-438b-90ce-f52186f7df2b",
    "user_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
    "name": "Carlos Barber",
    "role": "barber",
    "status": "active",
    "joined_at": "2026-06-12T01:33:50.653000Z"
  }
]
```

POST

/barbershops/{shop_id}/members

Links a user as a barbershop member with a role such as barber.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "user_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "role": "barber"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
403	Forbidden - role or ownership restriction
422	Validation Error

Response Example

```
{
  "member_id": "7929e68b-3b5d-438b-90ce-f52186f7df2b",
  "user_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "name": "Carlos Barber",
  "role": "barber",
  "status": "active",
  "joined_at": "2026-06-12T01:33:50.653000Z"
}
```

GET

/barbershops/{shop_id}/members/{member_id}

Returns details for a specific barbershop membership.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
member_id	path	string	Sí	Unique barbershop membership identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "member_id": "7929e68b-3b5d-438b-90ce-f52186f7df2b",
  "user_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "name": "Carlos Barber",
  "role": "barber",
  "status": "active",
  "joined_at": "2026-06-12T01:33:50.653000Z"
}
```

PUT

/barbershops/{shop_id}/members/{member_id}

Updates the role or status of a member. Restricted to the barbershop owner.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
member_id	path	string	Sí	Unique barbershop membership identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "status": "active",
  "role": "barber"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
403	Forbidden - role or ownership restriction
422	Validation Error

Response Example

```
{
  "member_id": "7929e68b-3b5d-438b-90ce-f52186f7df2b",
  "user_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "name": "Carlos Barber",
  "role": "barber",
  "status": "active",
  "joined_at": "2026-06-12T01:33:50.653000Z"
}
```

DELETE

/barbershops/{shop_id}/members/{member_id}

Removes a member from a barbershop. Restricted to the owner.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
member_id	path	string	Sí	Unique barbershop membership identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
401	Unauthorized - missing or malformed token
403	Forbidden - role or ownership restriction
422	Validation Error

Response Example

No response body.

4. Services

Endpoints for global service queries and service management inside a specific barbershop.

GET /services

Returns the list of services registered globally across the system.

Authentication: No authentication required / Public query

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
{
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
  "name": "Corte Normal",
  "price": 5,
  "is_active": true,
  "description": "Para cabellos normales",
  "duration_minutes": 10,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

GET /barbershops/{shop_id}/services

Returns all services offered by a specific barbershop.

Authentication: No authentication required / Public query

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
{
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
  "name": "Corte Normal",
  "price": 5,
  "is_active": true,
  "description": "Para cabellos normales",
  "duration_minutes": 10,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
]
```

POST

/barbershops/{shop_id}/services

Creates a service inside a barbershop. Requires an active owner or barber member.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "name": "Corte Normal",
  "description": "Para cabellos normales",
  "price": 5,
  "duration_minutes": 10
}
```

Codes de Respuesta

Code	Description
201	Created successfully
403	Forbidden - role or ownership restriction
422	Validation Error

Response Example

```
{
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
  "name": "Corte Normal",
  "price": 5,
  "is_active": true,
  "description": "Para cabellos normales",
  "duration_minutes": 10,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

GET

/barbershops/{shop_id}/services/{service_id}

Returns details for one service in a barbershop.

Authentication: No authentication required / Public query

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
service_id	path	string	Sí	Unique service identifier

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
  "name": "Corte Normal",
  "price": 5,
  "is_active": true,
  "description": "Para cabellos normales",
  "duration_minutes": 10,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

PUT	/barbershops/{shop_id}/services/{service_id}
-----	--

Updates service data such as name, description, price, duration or status.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
service_id	path	string	Sí	Unique service identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "name": "Corte Normal",
  "description": "Para cabellos normales",
  "price": 5,
  "duration_minutes": 10,
  "is_active": true
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
  "name": "Corte Normal",
  "price": 5,
  "is_active": true,
  "description": "Para cabellos normales",
  "duration_minutes": 10,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

DELETE /barbershops/{shop_id}/services/{service_id}

Deletes a service from a barbershop.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
service_id	path	string	Sí	Unique service identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
422	Validation Error

Response Example

No response body.

5. Products

Endpoints for managing the products offered by a barbershop.

GET /barbershops/{shop_id}/products

Lists products available in a specific barbershop catalog.

Authentication: No authentication required / Public query

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
  {
    "product_id": "cdc6a4a3-3258-4e75-84a1-cf9458c76786",
    "name": "Crema de afeitar Taurus",
    "stock": 10,
    "price": 10,
    "description": "Facilidad para afeitar",
    "image_url": "image.png",
    "is_active": true,
    "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
  }
]
```

POST /barbershops/{shop_id}/products

Creates a product in a barbershop catalog.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "name": "Crema de afeitar Taurus",
  "description": "Facilidad para afeitar",
  "price": 10,
  "stock": 10,
  "image_url": "image.png"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
422	Validation Error

Response Example

```
{
  "product_id": "cdc6a4a3-3258-4e75-84a1-cf9458c76786",
  "name": "Crema de afeitar Taurus",
  "stock": 10,
  "price": 10,
  "description": "Facilidad para afeitar",
  "image_url": "image.png",
  "is_active": true,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

GET

/barbershops/{shop_id}/products/{product_id}

Returns details of a specific product.

Authentication: No authentication required / Public query

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
product_id	path	string	Sí	Unique product identifier

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "product_id": "cdc6a4a3-3258-4e75-84a1-cf9458c76786",
  "name": "Crema de afeitar Taurus",
  "stock": 10,
  "price": 10,
  "description": "Facilidad para afeitar",
  "image_url": "image.png",
  "is_active": true,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

PUT

/barbershops/{shop_id}/products/{product_id}

Updates product data such as price, stock, image URL or active status.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
product_id	path	string	Sí	Unique product identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "name": "Crema de afeitar Taurus",
  "description": "Facilidad para afeitar",
  "price": 10,
  "stock": 10,
  "image_url": "image.png",
  "is_active": true
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "product_id": "cdc6a4a3-3258-4e75-84a1-cf9458c76786",
  "name": "Crema de afeitar Taurus",
  "stock": 10,
  "price": 10,
  "description": "Facilidad para afeitar",
  "image_url": "image.png",
  "is_active": true,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

DELETE

/barbershops/{shop_id}/products/{product_id}

Deletes a product from the barbershop catalog.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
product_id	path	string	Sí	Unique product identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
422	Validation Error

Response Example

No response body.

6. Appointments

Endpoints for listing, creating, reading, updating, canceling and linking services to appointments.

GET /appointments

Lists appointments, applying role-based visibility and optional filters.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
barbershop_id	query	string	No	Filter by barbershop ID
client_id	query	string	No	Filter by customer/client ID
barber_id	query	string	No	Unique barber user identifier
appointment_date	query	string	No	Filter by appointment date (YYYY-MM-DD)
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
  {
    "appointment_id": "afd7e13f-829b-4c3c-b061-470a908eb3f9",
    "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
    "client_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
    "appointment_date": "2026-06-16",
    "status": "pending",
    "notes": "",
    "start_time": "12:06:00",
    "end_time": "12:36:00",
    "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
  }
]
```

POST /appointments

Creates an appointment and validates barber availability and schedule collisions.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
barbershop_id	query	string	No	Filter by barbershop ID
client_id	query	string	No	Filter by customer/client ID

Parameter	Location	Tipo	Required	Description
barber_id	query	string	No	Unique barber user identifier
appointment_date	query	string	No	Filter by appointment date (YYYY-MM-DD)
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "client_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "appointment_date": "2026-06-16",
  "start_time": "12:06:14",
  "end_time": "12:36:00",
  "notes": "",
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
400	Business rule validation error
422	Validation Error

Response Example

```
{
  "appointment_id": "afd7e13f-829b-4c3c-b061-470a908eb3f9",
  "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "client_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "appointment_date": "2026-06-16",
  "status": "pending",
  "notes": "",
  "start_time": "12:06:00",
  "end_time": "12:36:00",
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

GET	/appointments/{appointment_id}
-----	--------------------------------

Returns details for a specific appointment.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
403	Forbidden - role or ownership restriction
422	Validation Error

Response Example

```
{
  "appointment_id": "afd7e13f-829b-4c3c-b061-470a908eb3f9",
  "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "client_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "appointment_date": "2026-06-16",
  "status": "pending",
  "notes": "",
  "start_time": "12:06:00",
  "end_time": "12:36:00",
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

PUT

/appointments/{appointment_id}

Updates an appointment. Date or time changes trigger availability and collision validations.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "appointment_date": "2026-06-16",
  "start_time": "12:06:00",
  "end_time": "12:36:00",
  "status": "confirmed",
  "notes": "Rescheduled by the client"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
403	Forbidden - role or ownership restriction
422	Validation Error

Response Example

```
{
  "appointment_id": "afd7e13f-829b-4c3c-b061-470a908eb3f9",
  "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "client_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "appointment_date": "2026-06-16",
  "status": "pending",
  "notes": "",
  "start_time": "12:06:00",
  "end_time": "12:36:00",
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

DELETE

/appointments/{appointment_id}

Cancels or deletes an appointment depending on business rules.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
403	Forbidden - role or ownership restriction
422	Validation Error

Response Example

No response body.

GET /appointments/{appointment_id}/services

Lists services linked to a specific appointment.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
  {
    "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
    "name": "Corte Normal",
    "price": 5,
    "is_active": true,
    "description": "Para cabellos normales",
    "duration_minutes": 10,
    "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
  }
]
```

POST /appointments/{appointment_id}/services

Links an additional service to an appointment.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
422	Validation Error

Response Example

```
[
  {
    "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
    "name": "Corte Normal",
    "price": 5,
    "is_active": true,
    "description": "Para cabellos normales",
    "duration_minutes": 10,
    "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
  }
]
```

DELETE /appointments/{appointment_id}/services/{service_id}

Unlinks a service from an appointment.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier
service_id	path	string	Sí	Unique service identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
422	Validation Error

Response Example

No response body.

7. Barber Availabilities

Endpoints used to register and manage the schedule blocks in which a barber can attend appointments.

GET /barbers/{barber_id}/availabilities

Lists availability blocks registered for a specific barber.

Authentication: No authentication required / Public query

Parameters

Parameter	Location	Tipo	Required	Description
barber_id	path	string	Sí	Unique barber user identifier

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
  {
    "availability_id": "c11da953-3d40-463e-95c0-f9abf379f053",
    "day_of_week": 1,
    "start_time": "07:00:00",
    "end_time": "19:00:00",
    "is_available": true
  },
  {
    "availability_id": "caf45ea1-abf6-4e30-bf6d-33c2c2072438",
    "day_of_week": 2,
    "start_time": "07:00:00",
    "end_time": "19:00:00",
    "is_available": true
  },
  {
    "availability_id": "abc5ceb5-1a39-4412-8ad0-bde24c8731f4",
    "day_of_week": 3,
    "start_time": "07:00:00",
    "end_time": "19:00:00",
    "is_available": true
  }
]
```

POST

/barbers/{barber_id}/availabilities

Creates a new availability block for a barber.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
barber_id	path	string	Sí	Unique barber user identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "day_of_week": 1,
  "start_time": "07:00:00",
  "end_time": "19:00:00",
  "is_available": true
}
```

Codes de Respuesta

Code	Description
201	Created successfully
422	Validation Error

Response Example

```
{
  "availability_id": "c11da953-3d40-463e-95c0-f9abf379f053",
  "day_of_week": 1,
  "start_time": "07:00:00",
  "end_time": "19:00:00",
  "is_available": true
}
```

PUT

/barbers/{barber_id}/availabilities/{availability_id}

Updates one availability block for a barber.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
barber_id	path	string	Sí	Unique barber user identifier
availability_id	path	string	Sí	Unique availability block identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "day_of_week": 1,
  "start_time": "07:00:00",
  "end_time": "19:00:00",
  "is_available": true
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "availability_id": "c11da953-3d40-463e-95c0-f9abf379f053",
  "day_of_week": 1,
  "start_time": "07:00:00",
  "end_time": "19:00:00",
  "is_available": true
}
```

DELETE /barbers/{barber_id}/availabilities/{availability_id}

Deletes an availability block from a barber schedule.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
barber_id	path	string	Sí	Unique barber user identifier
availability_id	path	string	Sí	Unique availability block identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
422	Validation Error

Response Example

No response body.

8. Invitations

Endpoints used by owners to create, list, inspect, update and revoke barbershop invitation codes.

GET /barbershops/{shop_id}/invitations

Lists invitation codes generated for a barbershop.

Authentication: No authentication required / Public query

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
{
  "invitation_id": "5684c9eb-b5c0-4f4f-9ce8-4fa60bfadbba",
  "code": "SH-144-TJZ",
  "expires_at": "2026-06-20T05:17:40.737000Z",
  "is_active": true
}
```

POST /barbershops/{shop_id}/invitations

Creates a new invitation code for a barbershop.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "expires_at": "2026-06-20T05:17:40.737000Z"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
422	Validation Error

Response Example

```
{
  "invitation_id": "5684c9eb-b5c0-4f4f-9ce8-4fa60bfadbba",
  "code": "SH-144-TJZ",
  "expires_at": "2026-06-20T05:17:40.737000Z",
  "is_active": true
}
```

GET /barbershops/{shop_id}/invitations/{invitation_id}

Returns details for a specific invitation code.

Authentication: No authentication required / Public query

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
invitation_id	path	string	Sí	Unique invitation code identifier

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "invitation_id": "5684c9eb-b5c0-4f4f-9ce8-4fa60bfadbba",
  "code": "SH-144-TJZ",
  "expires_at": "2026-06-20T05:17:40.737000Z",
  "is_active": true
}
```

PUT /barbershops/{shop_id}/invitations/{invitation_id}

Updates the status or expiration data of an invitation code.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
invitation_id	path	string	Sí	Unique invitation code identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "expires_at": "2026-06-20T05:17:40.737000Z",
  "is_active": true
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "invitation_id": "5684c9eb-b5c0-4f4f-9ce8-4fa60bfadbba",
  "code": "SH-144-TJZ",
  "expires_at": "2026-06-20T05:17:40.737000Z",
  "is_active": true
}
```

DELETE /barbershops/{shop_id}/invitations/{invitation_id}

Revokes or deletes an invitation code.

Authentication: Bearer token required

Parameters

Parameter	Location	Tipo	Required	Description
shop_id	path	string	Sí	Unique barbershop identifier
invitation_id	path	string	Sí	Unique invitation code identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
204	Successful Response - No Content
422	Validation Error

Response Example

No response body.

9. Role Dashboards (Owner, Barber, Customer)

Higher-level role-oriented endpoints used by the owner, barber and customer dashboards.

PUT /api/owner/barbershop

Executes the Owner Update Barbershop operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{token}} (Owner)

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "description": "Descripción actualizada desde Postman.",
  "phone": "0999999999"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "name": "SharkHub Barbería",
  "slug": "sharkhub-barberia",
  "description": "Barbería principal de pruebas",
  "logo_url": "logo.png",
  "address": "Sangolquí",
  "phone": "0987654321",
  "email": "barberia@example.com",
  "invite_code": "SH-4QL-15P",
  "is_active": true,
  "created_at": "2026-06-12T01:18:54.207000Z",
  "updated_at": "2026-06-12T01:18:54.207000Z"
}
```

POST /api/owner/barbers

Executes the Owner Add Barber operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{token}} (Owner)

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "email": "barber1@example.com"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "message": "Barbero asignado de manera exitosa"
}
```

PATCH

/api/owner/barbers/{barber_id}/status

Executes the /api/owner/barbers/{member_id}/status Owner Add Barber operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{token}} (Owner)

Parameters

Parameter	Location	Tipo	Required	Description
barber_id	path	string	Sí	Unique barber user identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "status": "active"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "id": "7929e68b-3b5d-438b-90ce-f52186f7df2b",
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "user_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "role": "barber",
  "status": "inactive",
  "joined_at": "2026-06-12T01:33:50.653000Z"
}
```

GET

/api/owner/appointments

Executes the Owner List Appoinments operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{token}} (Owner)

Parameters

Parameter	Location	Tipo	Required	Description
date	query	string	No	Date used to filter or calculate availability
barber_id	query	string	No	Unique barber user identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
{
  "appointment_id": "afd7e13f-829b-4c3c-b061-470a908eb3f9",
  "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "client_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "appointment_date": "2026-06-16",
  "status": "pending",
  "notes": "",
  "start_time": "12:06:00",
  "end_time": "12:36:00",
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
]
```

PATCH

/api/owner/appointments/{appointment_id}/status

Executes the Owner Patch Appointment Status operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{token}} (Owner)

Parameters

Parameter	Location	Tipo	Required	Description
appointment_id	path	string	Sí	Unique appointment identifier
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "status": "confirmed"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example


```
{
  "appointment_id": "afd7e13f-829b-4c3c-b061-470a908eb3f9",
  "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "client_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
  "appointment_date": "2026-06-16",
  "status": "confirmed",
  "notes": "",
  "start_time": "12:06:00",
  "end_time": "12:36:00",
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

GET

/api/barber/appointments

Executes the Barber List Appointments operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{tokenBarber}} (Barber)

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
403	Forbidden - role or ownership restriction
422	Validation Error

Response Example

```
[
  {
    "appointment_id": "afd7e13f-829b-4c3c-b061-470a908eb3f9",
    "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
    "client_id": "2e768092-e34e-47e9-9a1a-60bd4c207794",
    "appointment_date": "2026-06-16",
    "status": "confirmed",
    "notes": "",
    "start_time": "12:06:00",
    "end_time": "12:36:00",
    "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
  }
]
```

POST

/api/barber/services

Executes the Barber Create Service operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{tokenBarber}} (Barber)

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "name": "Corte Moicano",
  "description": "Para cabellos unicos e inigualables",
  "price": 12.5,
  "duration_minutes": 25
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "id": "ffdef670-bf1c-4a9a-8092-b44ce6c31642",
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "name": "Corte Moicano",
  "description": "Para cabellos unicos e inigualables",
  "price": "12.5",
  "duration_minutes": 25,
  "is_active": true,
  "created_at": "2026-06-12T04:17:15.705000Z"
}
```

POST**/api/barber/products**

Executes the Barber Create Product operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{tokenBarber}} (Barber)

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "name": "Crema de afeitar Taurus",
  "description": "Facilidad para afeitar",
  "price": 10,
  "stock": 10,
  "image_url": "image.png"
}
```

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "product_id": "cdc6a4a3-3258-4e75-84a1-cf9458c76786",
  "name": "Crema de afeitar Taurus",
  "stock": 10,
  "price": 10,
  "description": "Facilidad para afeitar",
  "image_url": "image.png",
  "is_active": true,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
```

GET**/api/customer/services**

Executes the Customer Search Services operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{tokenCustomer}} (Customer)

Parameters

Parameter	Location	Tipo	Required	Description
barbershop_id	query	string	No	Filter by barbershop ID

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
[
{
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
  "name": "Corte Normal",
  "price": 5,
  "is_active": true,
  "description": "Para cabellos normales",
  "duration_minutes": 10,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
},
{
  "service_id": "ffdef670-bf1c-4a9a-8092-b44ce6c31642",
  "name": "Corte Moicano",
  "price": 12.5,
  "is_active": true,
  "description": "Para cabellos unicos e inigualables",
  "duration_minutes": 25,
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90"
}
]
```

GET

/api/customer/available-times

Executes the Customer Get Available Times operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{tokenCustomer}} (Customer)

Parameters

Parameter	Location	Tipo	Required	Description
barber_id	query	string	No	Unique barber user identifier
service_id	query	string	No	Unique service identifier
date	query	string	No	Date used to filter or calculate availability
authorization	header	string	Sí	Bearer token used to authorize the request

Codes de Respuesta

Code	Description
200	Successful Response
422	Validation Error

Response Example

```
{
  "date": "2026-06-17",
  "available_slots": [
    "07:00",
    "07:30",
    "08:00",
    "08:30",
    "09:00",
    "09:30",
    "10:00",
    "10:30",
    "11:00",
    "11:30",
    "12:00",
    "12:30",
    "13:00",
    "13:30",
    "14:00",
    "14:30",
    "15:00",
    "15:30",
    "16:00",
    "16:30",
    "17:00",
    "17:30",
    "18:00",
    "18:30"
  ]
}
```

POST

/api/customer/appointments

Executes the Customer Book Appointment operation in the Role Dashboards (Owner, Barber, Customer) module.

Authentication: Bearer {{tokenCustomer}} (Customer)

Parameters

Parameter	Location	Tipo	Required	Description
authorization	header	string	Sí	Bearer token used to authorize the request

Request Body

```
{
  "barbershop_id": "95214e64-98d5-4e39-82d4-487b8673ca90",
  "barber_id": "9d814758-fc3e-4da7-93c1-e6c5768c58c8",
  "service_id": "5be23cc1-3fea-4f38-856c-d21d7bba607b",
  "appointment_date": "2026-06-18",
  "start_time": "10:00:00",
  "end_time": "10:30:00",
  "notes": "Reserva de prueba"
}
```

Codes de Respuesta

Code	Description
201	Created successfully
400	Business rule validation error
422	Validation Error

Response Example

```
{
  "status": "success",
  "message": "Cita agendada de forma correcta",
  "appointment_id": "4c5260f9-2808-4305-94f4-61fcaf594213"
}
```

10. System

Operational endpoints for health checks and monitoring.

GET	/health
-----	---------

Verifies that the API server is operational.

Authentication: No authentication required

Codes de Respuesta

Code	Description
200	Successful Response

Response Example

```
{
  "status": "ok",
  "database": "connected",
  "version": "1.0.0"
}
```

Validation Notes

During Postman validation, several expected business-rule errors were observed. These errors are useful because they confirm that the API is not only accepting HTTP requests, but also enforcing authorization, ownership and availability rules.

Code	Meaning	Example Context
400	The selected barber is not an active member of the provided barbershop.	Appointment creation with mismatched barber/barbershop IDs.
400	The barber is not available in the requested schedule.	Appointment creation outside an availability block or on an unavailable day.
401	Authorization token missing or malformed.	Request sent without a valid Bearer token.
403	Only the Owner of the barbershop can perform this action.	Member administration executed with a non-owner token.
422	Request body or parameters do not match the expected schema.	Invalid or incomplete request payload.

Recommended Postman execution order

1. Register or login as owner. 2. Create the barbershop. 3. Register/login the barber and customer. 4. Add the barber as an active member of the same barbershop. 5. Create a service. 6. Create barber availability for the required day. 7. Search available times or create an appointment. 8. Validate owner, barber and customer dashboard endpoints using the correct token variable.