

Linux

1. Commands used to show the current directory – pwd
2. Lists files and folders -ls
3. Creates a new directory - mkdir folder_name
4. Removes an empty directory - rmdir myfolder
5. Creates an empty file. - touch file.tx
6. Wsl
7. Ls
8. ls -a
9. ls -l
10. mkdir sample1
11. mkdir sample1.txt
12. touch sample_file1.txt
13. rm -r sample1.txt
14. ll
15. echo "hello" >sample_file1
16. mkdir sample2
17. cd sample2
18. mkdir sample2_in
19. touch F1.txt
20. cp -r F1.txt sample1
21. mv F1_copy.txt F3.txt
22. chmod 700 F1.txt
23. chmod g-x fl.txt
24. umask
25. uname
26. sudo adduser john
27. sudo userdel john
28. sudo adduser monika
29. cat /etc/passwd
30. hostname – displays the host username

Task1

What is the default permission for a newly created file and a directory

- In Linux, the basic default permission for newly created objects is
 - File : 666 , rw-rw-rw- [only read and write permission are available default, execute permission is not allowed for files]
 - Directory : 777, rwxrwxrwx [read, write, execute all are allowed]

Task2

Create a user using Linux

- Sudo useradd username [Sudo useradd user1]
- Useradd username

Task3

Delete the above user

- Sudo userdel Username [Sudo userdel user1]

Task4

- Create another user [Sudo useradd user2]
- Change the password, [Sudo passwd user2]
- Create a third user and switch to 2nd user [Sudo useradd user3 , sudo su – user2, whoami]

Task5

Find the current system time

- date +"%T" [only time]
- date [date and time]

Task 6

What is Chown command used for?

- Change owner command is used to change the ownership of a file or a directory.
- Sudo Chown owner filename [sudo chown user2 F2.txt]

Task 7

What is grep used for?

- The grep is used to search for specific text, word or patterns within file.
- grep “pattern” filename

Task 8

How to use Redirecting in Linux?

- It is used to take input from a file or used to send the output of a command to a file.
- echo “Hello Monika” > F1.txt
- echo “Welcome” >> F2.txt

Task 9

Try to open any files using vi command

- vi filename [vi F1.txt]
- i Insert mode
- Esc Exit insert mode
- :w Save file
- :q Quit
- :wq Save and quit
- :q! Quit without save

Task10

Try to use hostname command

- used to display or set the systems host name
- hostname # CURRENT HOST NAME
- hostnamectl # DETAILED HOST INFORMATION
- hostname -I #IP ADDRESS OF THE HOST

Task 11

Try to use `uname -a` to display detailed system information including the kernel version

- Used to display detailed system information of the host

Task 12

Try to use Sudo command

- `sudo apt update`
- `sudo apt install nginx`
- `sudo systemctl restart nginx`
- `sudo whoami`

Task 13

What do we understand by http and https

- HTTP [Hypertext Transfer Protocol] is used to communicate between a browser and a website, data is less secure and HTTPS [hypertext Transfer Protocol Secure] protects sensitive information such as passwords. Both are basically a protocol used to transfer data between a web browser and a web server.

Task 14

What are the methods in HTTP protocols

1. GET – retrieve the data
2. POST – send the data
3. PUT – update the data
4. DELETE – delete

Task 15

Give few status codes in http protocol

- 200 OK – The request was successful.
- 201 Created – A new resource was created successfully
- 400 Bad Request – The request is invalid or malformed.
- 404 Not Found – The requested resource or page does not exist.
- 500 Internal Server Error – An error occurred on the server.

Task 16

What do we understand by Headers in HTTP protocols

HTTP Headers are key-value pairs sent between a client and a server as part of an HTTP request or response. Headers help the client and server communicate effectively and process requests correctly. Commonly used headers are Head, Accept, Authorization.

HOME

Task 1: Awk

-used for searching, filtering and manipulating text files.

- awk 'pattern {action}' filename [awk '{print}' F1.txt]

Task 2: Sed

- used to **search, replace, insert, delete, and transform text** in files or input streams
- sed 'command' filename
 - sed 'F1.txt - print the file
 - sed 's/foo/bar/' F1.txt - replaces the first occurrence of "foo" with "bar"

Task 3: Piping

- used to send the output of one command as the input to another command
- command1 | command2 [ls | wc -l - list the files and count them]