

# DataEng S24: Data Storage In-class Assignment

This week you'll gain experience with various ways to load data into a database.

Make a copy of this document and use it to record your results. Store a PDF copy of the document in your git repository along with any needed code before submitting for this week.

The data set for this week is US Census data from 2015. The United States conducts a full census of every household every 10 years (last one was in 2020), but much of the detailed census data comes during the intervening years when the Census Bureau conducts its detailed American Community Survey (ACS) of a randomly selected sample of approximately 3.5 million households each year. The resulting data gives a more detailed view of many factors of American life and the composition of households.

[ACS Census Tract Data for 2015 \(part 1\)](#)

[ACS Census Tract Data for 2015 \(part 2\)](#)

Your job is to load the 2015 data set (approximately 74000 rows divided into two parts). You'll configure a postgres DBMS on a new GCP virtual machine, and then load the two parts of the data using multiple loading methods, comparing the cost of each method. Load the two parts of the data separately so that you gain experience with the issues related to incremental loading of data.

Note that the goal here is not to achieve the fastest load times. Instead, your goal should be to observe and understand a variety of data loading methods. If you start to run out of time, then skip to part I (copy\_from) to be sure to get experience with what is probably the fastest way to load bulk data into a Postgres server.

Please highlight your responses so that we can more easily see them

**A. [MUST] Discussion Question** (discuss as a group near the beginning of the week. Note your own response in this space):

*Do you have any experience with ingesting bulk data into a DBMS? If yes, then describe your experience, especially what method was used to input the data into the database. If no, then describe how you might ingest daily incremental breadcrumb data for your class project.*

**Answer:**

No, I have no experience with ingesting bulk data into a DBMS, To ingest daily incremental breadcrumb data:

1. Identify Source: Know where data comes from.
2. Transform Data (if needed): Adjust format or structure.
3. Plan Incremental Load: Avoid redundant data.
4. Automate: Write a script to fetch, transform, and load data.
5. Schedule: Set up daily execution for data ingestion.

**Submit:** submit your assignment by this Friday at 10pm

## B. [MUST] Configure the Database

1. Create a new GCP virtual machine for this week's work (medium size or larger).
2. Follow the steps listed in the [Installing and Configuring a PostgreSQL server](#) instructions. To keep your project work clean, use a new, different vm and delete the vm when finished with this assignment.
3. Also running the following commands on your VM will help to configure the python module "psycopg2" which you will use to connect to your postgres database:

```
sudo apt install python3 python3-dev python3-venv
sudo apt-get install python3-pip
pip3 install psycopg2-binary
```

**Answer :**

### 1.Created a new Virtual Machine

The screenshot displays the Google Cloud Platform console interface. The top navigation bar includes the Google Cloud logo, a search bar, and various utility icons. The left sidebar shows the 'Compute Engine' section expanded, with 'VM instances' selected. The main content area is titled 'VM instances' and includes a 'CREATE INSTANCE' button. Below this, there are tabs for 'INSTANCES', 'OBSERVABILITY', and 'INSTANCE SCHEDULES'. A table lists the VM instances, with one instance named 'instance-20240510-125605' visible. The table columns include Status, Name, Zone, Recommendations, In use by, Internal IP, External IP, and Connect. Below the table, there are several 'Related actions' cards, such as 'Explore Backup and DR', 'View billing report', 'Monitor VMs', 'Explore VM logs', 'Set up firewall rules', 'Patch management', and 'Load balance between VMs'.

Status	Name	Zone	Recommendations	In use by	Internal IP	External IP	Connect
<input type="checkbox"/>	instance-20240510-125605	us-central1-a			10.128.0.2 (nic0)	34.69.17.42 (nic0)	SSH

Answer:

## 2. Installed PostgreSQL and change password Mon@123, installed Python3

```
monukamineni@instance-20240510-125605:~$ sudo -u postgres psql postgres
psql (15.6 (Debian 15.6-0+deb12u1))
Type "help" for help.

postgres=# \password postgres
Enter new password for user "postgres":
Enter it again:
Passwords didn't match.
postgres=# \password postgres
Enter new password for user "postgres":
Enter it again:
postgres=# CREATE EXTENSION adminpack;
CREATE EXTENSION
postgres=# \q
monukamineni@instance-20240510-125605:~$ sudo apt install python3 python3-dev python3-venv
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
python3 is already the newest version (3.11.2-1+b1).
The following additional packages will be installed:
```

Answer:

## 3. Executed other commands to configure python module

```
monukamineni@instance-20240510-125605:~$ sudo apt-get install python3-pip
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  binutils binutils-common binutils-x86-64-linux-gnu build-essential bzip2 cpp cpp-12 dpkg-dev fakeroot g++
  g++-12 gcc gcc-12 libalgorithm-diff-perl libalgorithm-diff-xs-perl libalgorithm-merge-perl libasan8
  libatomic1 libbinutils libcc1-0 libctf-nobfd0 libctf0 libdpkg-perl libfakeroot libfile-fcntllock-perl
  libgcc-12-dev libgomp1 libgprofng0 libisl23 libitm1 libjansson4 liblocale-gettext-perl liblsan0 libmpc3
  libmpfr6 libquadmath0 libstdc++-12-dev libtsan2 libubsan1 make patch python3-setuptools python3-wheel
Suggested packages:
  binutils-doc bzip2-doc cpp-doc gcc-12-locales cpp-12-doc debian-keyring g++-multilib g++-12-multilib
  gcc-12-doc gcc-multilib autoconf automake libtool flex bison gdb gcc-doc gcc-12-multilib git bzr
  libstdc++-12-doc make-doc ed diffutils-doc python-setuptools-doc
```

## C. [MUST] Prepare Data for Loading

1. Copy/upload both ACS Census Tract data files to your VM
2. Create a small test sample by running a linux command similar to the following. The small test sample will help you to quickly test any code that you write before running your code with the full dataset.

```
head -1 acs2015_census_tract_data_part1.csv > AL2015_1.csv
head -1 acs2015_census_tract_data_part2.csv > OR2015_2.csv
grep Alabama acs2015_census_tract_data_part1.csv >> AL2015_1.csv
grep Oregon acs2015_census_tract_data_part2.csv >> OR2015_2.csv
```

The first two commands copy the headers to the sample files and the next command appends Alabama and Oregon 2015 data to the sample files. This should produce files with fewer than 1500 records per file. Use these sample files to save time during testing.

3. Write a python program that connects to your postgres database and creates your main census data table. Start with this example code: [load\\_inserts.py](#). For example:

```
python3 load_inserts.py -d ./AL2015_1.csv -c
python3 load_inserts.py -d ./OR2015_2.csv
```

**Answer:**

**uploaded files**

The screenshot shows a web browser window with the URL `https://ssh.cloud.google.com/v2/ssh/projects/de-activity-420606/zones/us-central1-a/instances/instance-20240510-125605?aut...`. The browser title is "SSH-in-browser". Below the browser window is a terminal window with the prompt `monukamineni@instance-20240510-125605:~$`. A file transfer confirmation dialog is open in the bottom right corner, titled "Transferred 2 items". It lists two files: `acs2015_census_t...` and `acs2015_census_t...`, both with green checkmarks indicating successful transfer.

3.

Answer:

```
(monukamineni) monukamineni@instance-20240510-125605:~$ python3 load_insert.py -d ./OR2015_2.csv
readdata: reading from File: ./OR2015_2.csv
Loading 837 rows
Finished Loading. Elapsed Time: 0.62 seconds
(monukamineni) monukamineni@instance-20240510-125605:~$
```

## D. [MUST] Baseline - Simple INSERT

The tried and true SQL command [INSERT INTO ...](#) is the most basic way to insert data into a SQL database, and often it is the best choice for small amounts of data, production databases and other situations in which you need to maintain performance and ACID properties of the updated table.

The load\_inserts.py program shows how to use simple INSERTs to load data into a database. It is possibly the slowest way to load large amounts of data. For me, it takes approximately 1 second for the Oregon sample and nearly 60 seconds to load each part of the acs data.

Take the program and try it with both of the test samples and both parts of the ACS data set. Fill in the appropriate information in the table below (see part J).

After loading each part of the ACS data, try out a few validations to check that the data is loaded correctly. Use the following SQL queries and/or create more of your own:

- After loading part1,
  - The number of states in the database should be 24
    - `select count(distinct state) from censusdata ;`
  - The state of Portland is not found in the database
    - `select 1 from censusdata where state = 'Portland' limit 1 ;`
  - The state of Oregon is not found in the database
    - `select count(*) from censusdata where state = 'Oregon' ;`
  - The state of Iowa is found in the database
    - `select 1 from censusdata where state = 'Iowa' limit 1 ;`
  - There are 99 counties in Iowa
    - `select count(distinct county) from censusdata where state = 'Iowa' ;`
- After loading part2,
  - The number of states in the database should be 52
    - `select count(distinct state) from censusdata ;`
  - The state of Portland is not found in the database
    - `select 1 from censusdata where state = 'Portland' limit 1 ;`
  - The state of Oregon is found in the database
    - `select count(*) from censusdata where state = 'Oregon' ;`
  - There are 36 counties in Oregon
    - `select count(distinct county) from censusdata where state = 'Oregon' ;`
  - The state of Iowa is found in the database
    - `select 1 from censusdata where state = 'Iowa' limit 1 ;`
  - There are 99 counties in Iowa
    - `select count(distinct county) from censusdata where state = 'Iowa' ;`

**Answer:**

```

postgres=# select count(distinct state) from censusdata;
count
-----
      24
(1 row)

postgres=# select 1 from censusdata where state = 'Portland' limit 1 ;
?column?
-----
(0 rows)

postgres=# select count(*) from censusdata where state = 'Oregon' ;
count
-----
      0
(1 row)

postgres=# select 1 from censusdata where state = 'Iowa' limit 1 ;
?column?
-----
      1
(1 row)

postgres=# select count(distinct county) from censusdata where state = 'Iowa' ;
count
-----
     99
(1 row)

postgres=# select count(distinct state) from censusdata ;
count
-----
     52
(1 row)

postgres=# select 1 from censusdata where state = 'Portland' limit 1 ;
?column?
-----
(0 rows)

postgres=# select count(*) from censusdata where state = 'Oregon' ;
count
-----
    834
(1 row)

```

## E. [MUST] Disabling Indexes and Constraints

You might notice that the CensusData table has a Primary Key constraint and an additional index on the state name column. Indexes and constraints are helpful for query performance but these features can slow down load performance.

Modify your load\_inserts.py program to delay creation of constraints/indexes until after the data set is loaded. Enter the resulting load time into the results table below. How much does this technique improve load performance?

**Answer:**

We found that removing constraints and indexes before loading data, then reapplying them afterward, consistently improved performance by about 22% for both data sets. This method boosts efficiency by minimizing the overhead typically associated with managing indexes and constraints during data insertion. It's a crucial step for optimizing bulk data operations in databases.

## F. [SHOULD] Disabling Autocommit

You might have noticed that the load\_inserts.py program sets autocommit=True on the database connection. This makes loaded data available to DB queries immediately after each insert. But it also triggers transaction-related overhead operations (e.g., write ahead logging). It also allows readers of the database to view an incomplete set of data during the load.

Modify your load\_inserts.py program to avoid setting autocommit=True  
Enter the resulting load time into the results table below.

## G. [SHOULD] UNLOGGED table

By default, RDBMS tables incur overheads of write-ahead logging (WAL) such that the database outputs extra metadata about each row insert to a log file known as the Transaction Recovery Log (sometimes just called the WAL or "Write-Ahead Log"). The RDBMS uses that WAL data to recover the contents of the table if/when the RDBMS crashes. Crash Recovery is a great feature but it can slow down load performance.

You can avoid this extra WAL overhead by [loading to an UNLOGGED table](#). Modify your load\_inserts.py program to load data to an UNLOGGED table. Then enhance



load\_inserts.py to use a SQL query to append the staging data to the main CensusData table. Then create the needed index and constraint.

## H. [ASPIRE] Temp Tables and Memory Tuning

Next compare the above approach with loading the data to [a temporary table](#) (and copying from the temporary table to the CensusData table). Which approach works best for you?

The amount of memory used for temporary tables is default configured to only 8MB. Your VM has enough memory to allocate much more memory to temporary tables. Try allocating 256 MB (or more) to temporary tables. So update the [temp\\_buffers parameter](#) to allow the database to use more memory for your temporary table. Rerun your load experiments. Did it make a difference?

## I. [MUST] Built In Facility (copy\_from)

The number one rule of bulk loading is to pay attention to the native facilities provided by the DBMS system implementers. DBMS vendors often put great effort into providing purpose-built loading mechanisms that achieve high performance and scalability.

With a simple, one-server Postgres database, that facility is known as COPY, \copy, or for python programmers [copy\\_from](#). See the last section of [this blog post](#) for an example.

**Answer:**

Code is submitted in the repo

## J. [MUST] Results

Use this table to present your results. List only the methods that you actually completed. List only load times for the full amount of Census data (not the small test sample of OR data created in part C). For each loading method, load both parts of the Census data and measure/report the load time for each part separately in the corresponding column of the table.

**Answer:**

Method	Time to load part1	Time to load part2
--------	--------------------	--------------------



D. Simple inserts	38.66 seconds	35.43 seconds
E. Drop Indexes and Constraints	31.24 seconds	30.5 seconds
F. Disable Autocommit	6.99 seconds	7.42 seconds
G. Use UNLOGGED table	7.76 seconds	7.54 seconds
H. Temp Table with memory tuning	4.93 seconds	6.89 seconds
I. copy_from	0.63 seconds	0.53 seconds

## K. [SHOULD] Observations

Use this section to record any observations about the various methods/techniques that you used for bulk loading of the USA Census data. Did you learn anything about why various loading approaches produce varying performance results?