
DHCP Snooping Lab

Source: Jeremy IT Lab

Student: Mono



- Configure R1 as a DHCP server.
 Exclude 192.168.1.1 192.168.1.9 from the pool Default gatew ay: R1
- Configure DHCP snooping on SW1 and SW2. Configure the uplink interfaces as trusted ports.
- 3. Use IPCONFIG /RENEW on PC1 to get an IP address. Does it w ork? Why or w hy not?
- 4. If it doesn't work, make the necessary configuration change to fix it.

1.

```
R1(config)#ip dhcp ?
  excluded-address Prevent DHCP from assigning certain addresses
 pool
                    Configure DHCP address pools
                    DHCP relay agent parameters
  relay
R1(config) #ip dhcp excluded-address 192.168.1.1-192.168.1.9 ?
% Unrecognized command
R1(config)#ip dhcp excluded-address 192.168.1.1 192.168.1.9
R1(config) #ip dhcp excluded-address 192.168.1.1 192.168.1.9 ?
  <cr>
R1(config)#show run | include dhcp
% Invalid input detected at '^' marker.
Rl(config) #do show run | include dhcp
ip dhcp excluded-address 192.168.1.1 192.168.1.9
R1(config)#
```

```
R1>en
Rl#config t
Enter configuration commands, one per line. End with CNTL/Z.
R1(config) #ip dhep pool POOL1
R1(dhcp-config) #network ?
  A.B.C.D Network number in dotted-decimal notation
R1(dhcp-config) #network 192.168.1.0 255.255.255.0
R1(dhcp-config)#default ?
  A.B.C.D Router's IP address
R1(dhcp-config) #default-router ?
  A.B.C.D Router's IP address
R1(dhcp-config) #default-router 192.168.1.1
R1(dhcp-config)#
2.
SW1(config) #ip dhcp ?
 excluded-address Prevent DHCP from assigning certain addresses
                    Configure DHCP address pools
 relay
                    DHCP relay agent parameters
 snooping
                    DHCP Snooping
 use
                    Configure use of certain parameters during allocation
SW1(config) #ip dhcp snooping
SW1(config) #ip dhcp snooping vlan 1
SW1(config)#int g0/2
SW1(config-if) #ip dhcp snooping ?
  limit DHCP Snooping limit
  trust DHCP Snooping trust config
SW1(config-if)#ip dhcp snooping trust
SW2 (config) #ip dhcp snooping
SW2(config) #ip dhcp snooping vlan 1
SW2 (config) #int g0/1
SW2 (config-if) #ip dhcp snooping trust
3.
No
4.
```

Disable option 82

No ip dhcp snooping info option