


## Basic thin film process




2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 13

13

## PVD – conceptual system



**Measurements/analysis:**

- Vacuum measurements
- Film thickness, composition, interface,.....

**Source of energy**


- **Thermal (evaporation)**
  - Heating (thermal evaporation)
  - Electron beam (e-beam evaporation)
  - Laser (pulsed laser deposition)
- **High energy ions (sputtering)**
  - Ions from a plasma
  - Ion beams (ion beam sputtering)

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 14

14

## Typical Evaporation System



- **Typical applications**
  - Deposition of metals and metallic compounds
  - Molecular beam epitaxy (MBE) of semiconductors

Angus Rockett, "Material Science of Semiconductors", Springer Verlag, 2008

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 15

15

## Pressure and mean free path

- Mean free path is the average distance between collision events

$$\lambda = \frac{k_B T}{\sqrt{2} \sigma P} = \frac{0.7}{P} \text{ cm}$$

- Where,  $k_B$  is the Boltzman's constant ( $1.38 \times 10^{-23} \text{ JK}^{-1}$ ),  $T$  is the temperature in Kelvin,  $P$  is pressure in Pascal,  $\sigma$  is the collision cross section in  $\text{cm}^2$
- $\sigma \sim 4 \times 10^{-15} \text{ cm}^2$  at 300K
- Mean free path at atmospheric pressure and room temperature is  $\sim 70\text{nm}$ .
- In an evaporation system, the mean free path  $\gg$  chamber dimensions
  - Thermal evaporation,  $P = 10^{-3}$  to  $10^{-6} \text{ Pa}$  ( $7.5 \times 10^{-3}$  mTorr to  $7.5 \times 10^{-6}$  m Torr). Mean free path in the range of 7 m to 7 km!
  - MBE,  $P < 10^{-9} \text{ Pa}$ . Mean free path  $> 7000 \text{ km}$ !

Angus Rockett, "Material Science of Semiconductors", Springer Verlag, 2008

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 16

16

## Why high vacuum?

- Flux of atoms striking a surface (e.g. substrate),

$$F = 2.63 \times 10^{17} \frac{P}{\sqrt{mT}} \text{ cm}^{-2} \text{ s}^{-1}$$

- Where, T is the temperature in Kelvin, P is pressure in Pascal, m is the atomic mass in atomic mass units (AMU)
- For Nitrogen at  $10^{-2}$  Pa,  $F = 3 \times 10^{16} \text{ cm}^{-2} \text{ s}^{-1}$
- If surface density of atoms is  $5 \times 10^{14} \text{ cm}^{-2}$ , about 60 atoms strike one surface site per second! If the atoms stick to the surface, the surface would be covered in less than a second.
- For a pressure of  $10^{-9}$  Pa, 60 atoms strike one surface site in  $10^7$  seconds! (or one atom strike in 46 hours!)
- At such low pressure, the surface can be maintained clean for long durations and the surface and the growing film would have extremely low levels of contamination.


Angus Rockett, "Material Science of Semiconductors", Springer Verlag, 2008

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 17

17

## Evaporation Temperature



Temperature at which the vapor pressure of the material is 10<sup>-2</sup> torr.


John E. Mahan, "Physical Vapor Deposition of Thin Films", John Wiley and Sons, 2000

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 18

18

## E-beam Evaporation



- The power density at the hot spot can be several kilo watts => high melting point materials like Pt, Ir,... can be evaporated
- Evaporant temperature at the hot zone can be much larger than the crucible temperature
- Low levels of contamination from the crucible


Angus Rockett, "Material Science of Semiconductors", Springer Verlag, 2008

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 19

19

## Thermal versus E-beam Evaporation




E-beam evaporation result in cleaner films.

Yaksh Rawal, IITBNF


2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 20


20




21



22



23



24