

## Modifications of the growing film by energetic particles (2)

- · Sputtering of the substrate or growing film
  - · May be useful for cleaning it prior to film deposition.
    - Usually done by back sputtering. Reverse the electrical connections to the anode and cathode.
  - · Change the composition of composite materials if the sputter yield of atoms differs
  - · Sputters atoms from the top of trenches and smoothen topographies
- Displacement cascades
  - · Create interstitials in the material, which enhances diffusion.
  - · Interstitials can relax strain in certain cases.
  - · Mixing of layers of deposited materials. Can be used to avoid phase separations.


2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil

1



## Modifications of the growing film by energetic particles (4)



- · Notice the deposited film at the top corners of the trench
  - · Due to higher sputtering rate at the corners by fast moving particles
- Step coverage

Trikon technologies, UK

2024 Monsoon Session


EE669: Thin Film Deposition; Anil Kottantharayil 3


## Modifications of the growing film by energetic particles (3)

- Enhanced adhesion due to fast particles
  - Surface can be cleaned using fast particles
  - · Surface bonds can be broken and the deposited film can chemically bond to the surface
  - · Surface can be made rough resulting in an "interlocking" of the substrate and the film
  - Short range intermixing of the film and the substrate

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 2






5

# Modifications of the growing film by energetic particles (8)

- Surface events (< 15 eV)</li>
  - · No bulk damage to the film
  - Increased surface diffusion due to the energy transferred from the energetic particle to the surface atoms
  - · Decomposition of small clusters of atoms on the surface
  - Stimulate chemical reactions and desorption from the surface

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 7



6



## **Applications in VLSI**


• PVD deposition of Ni, Co or Ti for salicide processes

EE669: Thin Film Deposition; Anil Kottantharayil 8

- PVD deposition of TiN or TaN for contact plugs as diffusion barrier
- PVD of Cu as seed for electroplating

\_

2024 Monsoon Session




Contacts to MOSFETs D EE669: Thin Film Deposition; Anil Kottantharayil 10

10



- Salicide Process
  A metal silicide is formed after source/drain implant anneal in a CMOS process
- The process is self aligned and hence the name
- The implant screening oxide if any is etched in HF
- Sample loaded into PVD chamber
  - Sputter the wafer using Ar to remove any native oxide => Degas chamber in a PVD system => hardly any selectivity between materials
  - Or etch the oxide in HF in a chamber integrated with the deposition chamber
  - Or reactive Ion Etching may be used for removing the native oxide
  - Sputter deposit pure Ti or Co or Ni as per the requirement
- RTP at a suitable temperature to form a low resistance phase of silicide

EE669: Thin Film Deposition; Anil Kottantharayil 11



11



## Salicide Process (2)

- Metal reacts with Si but not with Si<sub>3</sub>N<sub>4</sub> or SiO<sub>2</sub>
- Wet etch the unreacted metal
- Second RTP to convert silicide to lower resistance phase



Thompson et al., Intel technology journal, vol. 6, no. 2, 2002

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 13

13



## References

### PVD.

- John E. Mahan, "Physical Vapor Deposition of Thin Films", John Wiley and Sons, 2000.
- Donald L. Smith, "Thin Film Deposition: Principles and Practice, McGraw Hill, 1995.
- Angus Rockett, "Material Science of Semiconductors", Springer Verlag, 2008.
- Meenakshi Bhaisare et al., Nanoscience and Nanotechnology Letters, vol. 4 (6), pp. 645, 2012.

2024 Monsoon Session

EE669: Thin Film Deposition; Anil Kottantharayil 15

