


5X7 Dot Character VFD Module

CU40026-TW200A

- ❑ 2 Lines of 40 Characters 5mm High
- ❑ High Speed Parallel/Serial Interface
- ❑ Operating Temp -40°C to +85°C
- ❑ Single 5V Supply
- ❑ High Brightness Blue Green Display
- ❑ ASCII, Katakana & Extended Character Font
- ❑ 2 User Definable Character RAM

The module includes the Vacuum Fluorescent Display glass, driver and micro-controller ICs with refresh RAM, character generator and interface logic. The high speed 8 bit parallel interface is 5V CMOS compatible suitable for connection to a host CPU bus. The asynchronous serial interface accepts baud rates up to 19,200 with or without parity. Two character font tables can be hardware or software selected. User defined characters and many control commands are available.



ELECTRICAL SPECIFICATION

Parameter	Symbol	Value	Condition
Power Supply Voltage	V _{CC}	5.0VDC +/- 5%	GND=0V
Power Supply Current	I _{CC}	500mADC typ.	V _{CC} =5V
Logic High Input	V _{IH}	2.0VDC min.	V _{CC} =5V
Logic Low Input	V _{IL}	0.8VDC max.	V _{CC} =5V
Logic High Output	V _{OH}	4.4VDC min.	I _{OH} = -2.0mA
Logic Low Output	V _{OL}	0.5VDC max.	I _{OL} = 2.0mA

The power on rise time should be less than 100ms. The inrush current at power on can be 2 x I_{CC}.

OPTICAL and ENVIRONMENTAL SPECIFICATIONS

Parameter	Value
Character Size/Pitch (XxY mm)	3.3 x 5.05/4.75 x 9.95
Dot Size/Pitch (XxY mm)	0.5 x 0.55/0.7 x 0.75
Luminance	700 cd/m ² (204 fL) Typ.
Colour of Illumination	Blue-Green (Filter for colours)
Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
Operating Humidity (non condensing)	20 to 80% RH @ 25°C

SOFTWARE COMMANDS

Instruction	D0-D7	Instruction	D0-D7
Back Space	08H	International Font	18H
Horizontal Tab	09H	Katakana Font	19H
Line Feed	0AH	Euro Currency Mark	1AH
Form Feed	0CH	Escape	1BH
Carriage Return	0DH	> Send User Font	+43H
Clear Display	0EH	> Position cursor	+48H
Increment Write Mode	11H	> Software Reset	+49H
Vertical Scroll Mode	12H	> Luminance	+4CH
Horizontal Scroll Mode	13H	> Flickerless Write	+53H
Underline Cursor On	14H	> Cursor Blink Speed	+54H
5x7 Block Cursor On	15H	Character Data	20H+
Cursor Off	16H	User Character Data	00H+
Cursor Blinking	17H		

TIMING PARAMETERS (min)

Data Set Up To Write	100ns	Subject to change without notice.
Write Pulse Width	160ns	Detailed specification on request.
Hold After Write	10ns	IUK Doc Ref:4406 Iss:1 13Aug03

CHARACTER FONTS

CHARACTER FONTS											International Font							Additional Katakana Font						
	00	10	20	30	40	50	60	70	80	90	A0	B0	C0	D0	E0	F0	80	90	A0	B0	C0	D0	E0	F0
00				00	P`	P	E	Σ									5		一	タ	三	日		
01				!1A	Q	a	r	z	1	±	A	N	Z	W			7	3	ア	チ	月			
02				"2B	R	b	r	4	≡	4	2	a	N	Z	W			0	0	イ	ツ	火		
03				#3C	S	c	e	l	×	f	3	a	N	Z	W			8	9	ウ	テ	木		
04				\$4D	T	t	t	L	÷	D	1	a	N	Z	W			3	0	エ	ト	サ	木	
05				%5E	U	e	U	%	0	%	1	a	N	Z	W			W	0	・	オ	ナ	金	
06				&6F	V	v	r	?	1	7	E	O	w					4	0	マ	カ	ニ	ヨ	
07				'7G	H	h	w	E	Σ									1	0	フ	チ	アリ	金	
08				<8H	X	x	e	Σ										0	0	イ	ク	ネ	リ	
09				>9I	Y	y	h	Σ										4	1	ウ	ケ	ル	丹	
0A				*:J	Z	j	z	0	#	1	E	O	w					0	+	エ	コ	ロ	ニ	
0B				+;K	I	k	<	Σ	7	Σ								4	4	サ	セ	ロ	ニ	
0C				,<L	J	l	j	π	3									4	1	マ	シ	フ	ニ	
0D				-=M	I	m	>	7	7									W	1	ス	セ	フ	ニ	
0E				>N	^	n	<	0	0									W	4	セ	セ	ホ	ニ	
0F				/?O	P	o	%	Σ	Σ									5	4	ソ	リ	フ	ニ	

PCB JUMPERS (OPEN/LINK)

Baud	J2	J1	J0
19200	O	O	O
9600	O	O	L
4800	O	L	O
2400	O	L	L
1200	L	O	O
Parity	J4		J3
EVEN	O		O
ODD	O		L
NONE	L		L / O
Font		JA	
International		L	
Katakana		O	

3 PIN POWER CONNECTOR

Pin	Sig
1	V _{CC} (5V)
2	S _{IN} /TEST
3	GND(0V)

IDC DATA CONNECTOR

Pin	Sig	Pin	Sig
1	D7	9	/WR
2	D6	10	/CS
3	D5	11	S _{IN} /TEST
4	D4	12	BUSY
5	D3	13	GND(0V)
6	D2	14	GND(0V)
7	D1	15	V _{CC} (5V)
8	D0	16	V _{CC} (5V)

CONTACT

Noritake Sales Office Tel Nos
 Nagoya Japan: +81 (0)52-561-9867
 Canada: +1-416-291-2946
 Chicago USA: +1-847-439-9020
 Munchen (D): +49 (0)89-3214-290
 Itron UK: +44 (0)1493 601144
 Rest Europe: +49 (0)61-0520-9220
 www.noritake-iron.com