


Packet Tracer - Configuring IPv4 Static and Default Routes

Topology



Addressing Table

Device	Interface	IPv4 Address	Subnet Mask	Default Gateway
R1	G0/0	172.31.1.1	255.255.255.128	N/A
	S0/0/0	172.31.1.194	255.255.255.252	N/A
R2	G0/0	172.31.0.1	255.255.255.0	N/A
	S0/0/0	172.31.1.193	255.255.255.252	N/A
	S0/0/1	172.31.1.197	255.255.255.252	N/A
R3	G0/0	172.31.1.129	255.255.255.192	N/A
	S0/0/1	172.31.1.198	255.255.255.252	N/A
PC1	NIC	172.31.1.126	255.255.255.128	172.31.1.1
PC2	NIC	172.31.0.254	255.255.255.0	172.31.0.1
PC3	NIC	172.31.1.190	255.255.255.192	172.31.1.129

Objectives

Part 1: Examine the Network and Evaluate the Need for Static Routing

Part 2: Configure Static and Default Routes

Part 3: Verify Connectivity

Background

In this activity, you will configure static and default routes. A static route is a route that is entered manually by the network administrator to create a reliable and safe route. There are four different static routes that are used in this activity: a recursive static route, a directly attached static route, a fully specified static route, and a default route.

Part 1: Examine the Network and Evaluate the Need for Static Routing

- Looking at the topology diagram, how many networks are there in total? 5
- How many networks are directly connected to R1, R2, and R3? R1: 2, R2: 3, R3: 2
- How many static routes are required by each router to reach networks that are not directly connected?
R1- 3, R2- 2, R3-3
- Test connectivity to the R2 and R3 LANs by pinging PC2 and PC3 from PC1.

Why were you unsuccessful? Because the routers do not have the routing table entries needed to send data to remote networks.

Part 2: Configure Static and Default Routes

Step 1: Configure recursive static routes on R1.

- What is recursive static route?
A static route that specifies the next-hop IP address only. The router must perform a recursive lookup to forward the packet.
- Why does a recursive static route require two routing table lookups?
The first lookup finds the destination network and matches it to the next-hop IP. The second lookup finds the exit interface associated with that next-hop IP
- Configure a recursive static route to every network not directly connected to R1, including the WAN link between R2 and R3.
- Test connectivity to the R2 LAN and ping the IP addresses of PC2 and PC3.
Why were you unsuccessful?
While R1 can send packets out, the other routers (R2 and R3) do not yet have routes to send the return traffic back to R1.

Step 2: Configure directly attached static routes on R2.

- How does a directly attached static route differ from a recursive static route?
A directly attached static route specifies the exit interface (e.g., Serial0/0/0) instead of a next-hop IP. This resolves in a single lookup.
- Configure a directly attached static route from R2 to every network not directly connected.
- Which command only displays directly connected networks? show ip route connected
- Which command only displays the static routes listed in the routing table? show ip route static
- When viewing the entire routing table, how can you distinguish between a directly attached static route and a directly connected network?
A static route is marked with the code S, while a directly connected network is marked with C.

Step 3: Configure a default route on R3.

- a. How does a default route differ from a regular static route?
A default route uses the destination 0.0.0.0/0, meaning it matches any packet that does not match a more specific route in the table.
- b. Configure a default route on R3 so that every network not directly connected is reachable.
- c. How is a static route displayed in the routing table? It is displayed with the code S (or S* if it is a default

Step 4: Document the commands for fully specified routes.

Note: Packet Tracer does not currently support configuring fully specified static routes. Therefore, in this step, document the configuration for fully specified routes.

- a. Explain a fully specified route.
A route where both the exit interface AND the next-hop IP address are specified in the command.
- b. Which command provides a fully specified static route from R3 to the R2 LAN?
`ip route 172.31.0.0 255.255.255.0 Serial0/0/1 172.31.1.197`
- c. Write a fully specified route from R3 to the network between R2 and R1. Do not configure the route; just calculate it.
`ip route 172.31.1.192 255.255.255.252 Serial0/0/1 172.31.1.197`
- d. Write a fully specified static route from R3 to the R1 LAN. Do not configure the route; just calculate it.
`ip route 172.31.1.0 255.255.255.128 Serial0/0/1 172.31.1.197`

Step 5: Verify static route configurations.

Use the appropriate **show** commands to verify correct configurations.

Which **show** commands can you use to verify that the static routes are configured correctly?

`show ip route`, `show ip route static`, `show running-config`

Part 3: Verify Connectivity

Every device should now be able to ping every other device. If not, review your static and default route configurations.

Suggested Scoring Rubric

Activity Section	Question Location	Possible Points	Earned Points
Part 1: Examine the Network and Evaluate the Need for Static Routing	a - d	10	
Part 1 Total		10	
Part 2: Configure Static and Default Routes	Step 1	7	
	Step 2	7	
	Step 3	3	
	Step 4	10	
	Step 5	3	
Part 2 Total		30	
Packet Tracer Score		60	
Total Score		100	