



Chandigarh Engineering College Jhanjeri
Mohali-140307
Department of Computer Science & Engineering

IOT Based School Safety Zone Sensor

ON

IMAGE PROCESSING TECHNIQUES

Project-I



Department of Computer Science and Engineering
CHANDIGARH ENGINEERING COLLEGE JHANJERI, MOHALI

**In partial fulfillment of the requirements for the award of the Degree of
Bachelor of Technology in Computer Science & Engineering**

SUBMITTED BY:

Monu Mishra(2419902)
Punit kumar prasad(2419931)
Prince kumar(2419925)
Mukesh kumar(2419903)

Under the Guidance of

Name of Mentor - Mr. Amit

Designation of mentor

MAY, 2025



Affiliated to I.K Gujral Punjab Technical University, Jalandhar
(Batch: 2024-2028)



DECLARATION

I, Monu Mishra hereby declare that the report of the project entitled “ IOT Based School Safety Zone Sensor” has not presented as a part of any other academic work to

get my degree or certificate except Chandigarh Engineering College Jhanjeri, Mohali, affiliated to I.K. Gujral Punjab Technical University, Jalandhar, for the fulfillment of the requirements for the degree of B.Tech in Computer Science & Engineering.

Monu mishra

Univ. Roll No : 2419902

Semester : 3

(Mentor Signature with Date)

Mr. Amit

DESIGNATION, CSE

Signature of the Head of Department

ACKNOWLEDGEMENT

It gives me great pleasure to deliver this report on Project-I, which I worked on for my B.Tech in Computer Science & Engineering 3rd year, which was titled



Chandigarh Engineering College Jhanjeri
Mohali-140307
Department of Computer Science & Engineering

"IOT Based School Safety Zone Sensor “. I am grateful to my university for presenting me with such a wonderful and challenging opportunity. I also want to convey my sincere gratitude to all coordinators for their unfailing support and encouragement.

I am extremely thankful to the HOD and Project Coordinator of Computer Science & Engineering at Chandigarh Engineering College Jhanjeri, Mohali (Punjab) for valuable suggestions and the heartiest cooperation.

I am also grateful to the management of the institute and Dr. Avinash, Director Engineering, for giving me the chance to acquire the information. I also appreciate all of my faculty members, who have instructed me throughout my degree.

(Signature of Student)

Monu Mishra(2419902)

Prince kumar(2419925)

Punit kumar prasad(2419931)

Mukesh kumar(2419903)



TABLE OF CONTENTS

PARTICULARS	Page no
Title Page	I
Declaration by the Candidate	ii
Acknowledgement	iii
Table of Contents	iv
Abstract	V
List of Figures	Vi
List of Tables	vii
CHAPTER 1 INTRODUCTION	6 - 11
1.1 Overview	
1.2 Significance of the Project	
1.3 Motivation Behind the Project	
1.4 Problem Statement	
1.5 Objectives of the Project	
1.6 Applications	
CHAPTER 2 REVIEW OF LITERATURE	11 -15
2.1 Introduction	
2.2 Background Study	
2.3 Review of Existing Safety Systems	
2.4 IoT in Road Safety Systems	
2.5 Limitations of Existing Work	
2.6 Role of Sensors in Safety Systems	
2.7 Role of Microcontroller and IoT Module	



2.8 Advantages of IoT-Based Systems

2.9 Research Gap Identified

2.10 Summary of the Literature Review

CHAPTER 3 PROBLEM DEFINITION AND OBJECTIVES 16-18

3.1 Identification of Problem

3.2 Need of the Project

3.3 Project Objectives

3.4 Scope of the Project

3.5 Outcome Expectations

CHAPTER 4 DESIGN AND IMPLEMENTATION 19-26

4.1 System Overview and Architecture

4.2 Hardware Components Used

4.2.1 Hardware Components Used

4.2.2 Hardware Components Used

4.2.3 Motor Driver Module (L298N)

4.2.4 DC Motor

4.2.5 ESP8266 Wi-Fi Module

4.2.6 Buzzer

4.2.7 LED Indicators

4.2.8 Connecting Wires and Breadboard

4.2.9 Power Supply (9V Battery)

4.2.10 4WDKIT Four Wheel Robotic Smart Car



4.3 Software Tools and Platforms

4.3.1 Arduino IDE

4.3.2 ThingSpeak IoT Platform

4.3.3 Blynk Application (Optional)

4.3.4 Embedded C Programming Language

4.4 Circuit Design and Description

4.5 Working Principle

4.6 Integration and Testing

26-29

CHAPTER 5 RESULTS AND DISCUSSIONS

5.1 Experimental Setup

5.2 Data Collection and Analysis

5.3 Advantages of the Proposed System

5.4 Performance Analysis

CHAPTER 6 CONCLUSION AND FUTURE SCOPE

29-32

6.1 Conclusion

6.2 Project Constraints and Limitations

6.3 Future Enhancements and Recommendations

6.4 Final Remarks

CHAPTER 7

FINAL PROJECT IMAGE

33

REFERENCES

34-35



Chapter 1 – Introduction

1.1 Overview

In today's modern world, road safety has become a major concern due to the rapid increase in the number of vehicles. Accidents near schools, hospitals, and residential zones occur frequently because many drivers fail to slow down in restricted areas. Although traditional safety methods such as signboards and speed breakers exist, they depend heavily on human attention and discipline, which are often unreliable.

To overcome these limitations, this project titled “IoT-Based School Safety Zone Sensor System – Automatic Vehicle Control near School or Hospital Zone” has been developed. It automatically detects vehicles entering a restricted area and reduces their speed by controlling the motor through a microcontroller. The system uses an ultrasonic sensor to sense vehicle movement and sends the signal to an Arduino UNO, which then processes the data and activates the motor driver (L298N) to slow down the vehicle.

In addition, the system is connected to the Internet of Things (IoT) network using the ESP8266 Wi-Fi module, which transmits real-time information to a cloud platform such as ThingSpeak or Blynk. This allows authorities to monitor activity in real time. The integration of sensors, microcontrollers, and IoT makes this system an intelligent and reliable safety solution suitable for smart city applications.

1.2 Significance of the Project

The significance of this project lies in its ability to reduce accidents and promote safe driving habits through automation and technology. In conventional traffic systems, road safety depends on human action, which can be delayed or ignored. The proposed system automates safety measures and ensures continuous monitoring even in the absence of manual supervision.

Key points highlighting its significance are as follows:

- **Automatic Detection and Control:** The system automatically detects a vehicle entering the safety zone and adjusts its speed without driver input.
- **Real-Time Monitoring through IoT:** The IoT cloud provides continuous updates on system performance and helps authorities analyze traffic patterns.



- Enhanced Safety for Pedestrians and Students: LED and buzzer alerts notify nearby pedestrians and drivers of restricted areas, ensuring safety.
- Low-Cost Implementation: The system uses affordable electronic components, making it easy to implement in developing regions.
- Supports Smart City Development: The project aligns with the national objective of building intelligent and automated urban safety infrastructure.

1.3 Motivation Behind the Project

The motivation behind this project comes from the increasing number of road accidents, especially near school and hospital zones. Despite having visible signboards, many drivers ignore them, resulting in avoidable tragedies. Such real-world issues inspired the idea of developing a system that can automatically control vehicle speed using sensors and microcontrollers.

The growing popularity of IoT (Internet of Things) also served as an inspiration for this project. IoT enables devices to communicate and make decisions automatically, which can be effectively used in road safety applications. By integrating IoT with automation, it becomes possible to create an intelligent system that operates 24×7 without human supervision.

Motivational aspects include:

- Preventing road accidents caused by overspeeding.
- Demonstrating the practical application of IoT for social safety.
- Creating a cost-effective and scalable solution for real-world use.
- Learning interdisciplinary skills like embedded systems, networking, and automation.

1.4 Problem Statement

In school and hospital zones, many accidents occur due to high vehicle speeds and lack of driver attention. Conventional methods like signboards, manual warnings, or road bumps are not sufficient to prevent such incidents. Therefore, there is a need for an automated system that can detect the presence of a vehicle, reduce its speed automatically, and alert nearby pedestrians.



The proposed system provides a reliable and automatic solution by using an ultrasonic sensor, Arduino controller, and IoT connectivity to create a smart and self-operating safety mechanism.

1.5 Objectives of the Project

The main objectives of this project are as follows:

- To design and develop an automated vehicle control system for safety zones using sensors and microcontrollers.
- To reduce the speed of vehicles automatically when they enter school or hospital areas.
- To alert pedestrians and drivers through visual (LED) and sound (buzzer) indicators.
- To transmit real-time data to IoT cloud platforms for monitoring and analysis.
- To minimize accidents caused by human negligence or delayed reactions.

1.6 Applications

- The IoT-based School Safety Zone Sensor System can be applied in several real-world scenarios, such as:
- Automatic speed control in restricted areas.
- Real-time IoT monitoring of traffic conditions.
- Pedestrian safety management near schools and hospitals.
- Integration with emergency vehicle management systems.
- Use in autonomous or semi-automatic vehicle projects.






Figure : Flowchart Representing the Working Process of IoT-Based School Safety Zone Sensor System

Caption

This flowchart illustrates the complete operational flow of the IoT-based safety system. It begins with the detection of a vehicle entering the safety zone using ultrasonic sensors. The signal is then processed by the Arduino microcontroller, which sends data to the IoT cloud through the Wi-Fi module. Simultaneously, the system activates the motor driver to reduce vehicle speed and triggers alert mechanisms such as LED indicators and buzzer sounds. After the vehicle exits the zone, the system restores normal speed and ends the process, ensuring continuous and automated safety management.

Chapter-2 REVIEW OF LITERATURE

2.1 Introduction

The review of literature provides the theoretical background and technical understanding of the proposed project. It helps in identifying the existing technologies, methods, and research findings that relate to the development of the **IoT-Based School Safety Zone Sensor System**.

This chapter discusses previous work carried out in the area of road safety, vehicle automation, and Internet of Things (IoT)-based traffic management. It also highlights the limitations of existing systems and explains how the proposed system provides better performance and reliability.




Figure 2.1: IoT-Based Smart School Zone Vehicle Speed Monitoring and Control System

Caption

This figure illustrates the architecture of an IoT-based school safety and vehicle speed control system. The left section (a) shows the real-time scenario of a school zone equipped with various components such as **speed cameras, sensors, and variable message signboards (VMS)** that monitor and display the vehicle's speed. These sensors detect the approaching vehicles and communicate data through the **Internet** to the control center.



The right section (b) represents the internal system architecture. It includes the **control center**, **monitoring servers**, and **IoT base stations (T-BS)** that collect information from multiple sensors and transmit it to the main server.

The network manages two major functions — **Vehicle Speed Control** and **Parking/Stopping Control**, both of which are connected to the cloud for centralized monitoring.

This integrated setup allows continuous monitoring, speed regulation, and smart data handling through IoT connectivity, ensuring safe vehicle operation in the school zone environment.

2.2 Background Study

Road safety has become one of the most critical issues in today's world due to the rapid increase in vehicles and traffic congestion. Existing methods, such as speed breakers and manual traffic supervision, have not been fully effective in preventing accidents. To address these challenges, researchers have introduced automation and IoT technologies that enable devices to sense, analyze, and react automatically. These modern systems minimize human dependency and provide continuous real-time monitoring for improved safety and control.

2.3 Review of Existing Safety Systems

- Conventional safety systems are widely used but have multiple drawbacks. Some common methods and their limitations are as follows:
- Speed Breakers: Effective but cause vehicle discomfort and are not suitable for all locations.
- Signboards and Road Markings: Depend entirely on driver attention and are often ignored.
- Radar or Laser Speed Detection: Accurate but expensive and not affordable for small zones.
- Manual Supervision: Requires human effort, which cannot be maintained continuously.
- Camera-Based Monitoring: Needs large data processing power and storage facilities.

2.4 IoT in Road Safety Systems

The Internet of Things (IoT) is transforming the way systems communicate and make decisions. In road safety, IoT plays a key role in creating a connected and intelligent infrastructure. It allows devices such as sensors, controllers, and actuators to share data



instantly and respond automatically. IoT-based road safety systems can monitor vehicle movement, control signals, record events, and alert users remotely. In this project, IoT enables real-time communication between the Arduino microcontroller and a cloud dashboard through a Wi-Fi module (ESP8266).

This helps in analyzing and maintaining records of the system's activity, which can later be used to enhance road safety strategies.

2.5 Limitations of Existing Work

After reviewing multiple systems, the following limitations were identified:

1. No full automation or real-time control mechanism.
2. Limited use of IoT for cloud data transmission and analysis.
3. High installation and maintenance cost.
4. Dependence on human observation and reaction time.
5. Absence of alert system for pedestrians and authorities.
6. The proposed project eliminates these issues by using affordable components, IoT-based communication, and a fully automated control system.

2.6 Role of Sensors in Safety Systems

Sensors are crucial for any automatic safety system. In this project, **ultrasonic sensors** are used to detect the distance between the sensor and the approaching vehicle. When the vehicle enters a certain range, the sensor sends signals to the **Arduino UNO**, which processes the data and triggers appropriate actions such as speed reduction, LED warning, and buzzer sound.

This ensures instant reaction and accurate control, preventing potential accidents effectively.



2.7 Role of Microcontroller and IoT Module

The **Arduino UNO microcontroller** serves as the central control unit that processes all input data and executes predefined instructions.

It reads the input from the sensor and sends commands to the **L298N motor driver** to regulate vehicle speed.

The **ESP8266 Wi-Fi module** is responsible for establishing communication with the IoT cloud platform. It transmits real-time information such as vehicle detection status, speed levels, and alerts to the cloud.

This combination enables remote data access and system supervision through mobile or web applications.

2.8 Advantages of IoT-Based Systems

- IoT-based safety systems offer several important advantages over traditional methods:
- **Automation:** Reduces human dependency and increases accuracy.
- **Real-Time Monitoring:** Provides live updates to the cloud platform.
- **Cost-Effective:** Uses inexpensive and easily available components.
- **Scalable:** Can be expanded to multiple zones and integrated into smart city networks.
- **Efficient Data Storage:** Maintains a digital log of all activities.
- **Low Power Consumption:** Operates efficiently for longer durations.

2.9 Research Gap Identified

From the analysis of previous research and existing systems, the following gaps have been identified:

- Lack of integration between detection and control mechanisms.
- Minimal or no IoT connectivity in small-scale models.
- Limited focus on safety zones such as schools and hospitals.
- Expensive hardware used in earlier prototypes.
- Absence of combined alert and control actions in one system.

2.10 Summary of the Literature Review

The literature review clearly shows that while several systems exist for traffic control and vehicle monitoring, most fail to provide complete automation or real-time IoT data exchange. The proposed system successfully combines all these features into one compact, low-cost, and intelligent solution.

By using **ultrasonic sensors, Arduino UNO, motor driver, and IoT technology**, this project ensures efficient vehicle control, real-time monitoring, and safety for pedestrians in school and hospital areas. Thus, the **IoT-Based School Safety Zone Sensor System** not only improves existing traffic safety mechanisms but also supports the vision of **Smart Cities and Intelligent Transportation Systems (ITS)**.



Chapter-3

PROBLEM DEFINITION AND OBJECTIVES

3.1 Identification of the Problem

With the increasing number of vehicles and the rapid growth of urban traffic, **road safety near sensitive zones such as schools and hospitals** has become a major concern. Many accidents occur because drivers fail to follow speed limits or do not notice signboards placed near restricted zones. Traditional methods like **speed breakers, road signs, and manual traffic supervision** are not sufficient to ensure safety.

The primary issue lies in the **lack of automation and continuous monitoring** in existing systems. Even though signboards display warnings such as “SCHOOL ZONE – SLOW DOWN,” these warnings rely completely on driver awareness and reaction time. In addition, there is no system that automatically reduces the vehicle’s speed when it enters a restricted zone.

Another problem is that existing safety systems **do not store or transmit real-time data** to authorities or monitoring centers. Without automation and IoT connectivity, it becomes impossible to track overspeeding behavior or collect evidence for future improvements.

Therefore, the main problem identified is the **absence of a real-time IoT-based automatic vehicle speed control system** that can monitor, detect, and control vehicles near school or hospital zones, thereby preventing accidents and enhancing safety.

3.2 Need of the Project

The need for this project arises from the urgent requirement to **reduce accidents and improve road safety** near critical areas like schools, hospitals, and residential zones. Manual monitoring and static signboards are not effective in controlling vehicle speed because of human negligence and lack of real-time response.

An **IoT-based automatic safety system** is essential for the following reasons:

- **Automation of Vehicle Control:** The system should automatically control vehicle speed based on sensor detection, without depending on human input.



Chandigarh Engineering College Jhanjeri Mohali-140307

Department of Computer Science & Engineering

- **Continuous Monitoring:** Through IoT connectivity, authorities can monitor real-time data of vehicles passing through restricted zones.
- **Instant Alert Mechanism:** Warning signals through LEDs and buzzers can alert both drivers and pedestrians instantly.
- **Accident Prevention:** By automatically reducing vehicle speed, the system significantly lowers the risk of accidents.
- **Data Storage and Analysis:** The system can store the detected data on cloud platforms, which can be later analyzed to study traffic behavior.

3.3 Project Objectives

The **main objective** of this project is to design and implement an **IoT-Based School Safety Zone Sensor System** that can automatically control vehicle speed and send real-time data to the cloud for monitoring.

The specific objectives of the project are as follows:

- **To develop an automatic speed control mechanism** using ultrasonic sensors and a microcontroller to detect vehicles entering the school or hospital zone.
- **To alert drivers and pedestrians** through LED indicators and buzzers whenever a vehicle enters the restricted area.
- **To integrate IoT connectivity** using the ESP8266 Wi-Fi module for real-time data transfer and monitoring on a cloud platform such as ThingSpeak or Blynk.
- **To minimize accidents and ensure safety** by maintaining appropriate speed control within the safety zone.
- **To build a low-cost and scalable system** that can be implemented easily in various locations.
- **To support the concept of Smart Cities** by introducing intelligent, IoT-based transportation management and road safety systems.

3.4 Expected Outcomes

The expected outcomes of this project are the measurable and practical results that will be achieved after successful implementation. The system is designed to bring both **technical** and **social benefits**.

Technical Outcomes:

- A functional IoT-based prototype capable of detecting vehicles in real time.
- Automatic vehicle speed reduction mechanism using motor control.
- Real-time monitoring and data logging using the IoT cloud platform.
- LED and buzzer alert system to notify drivers and pedestrians.
- **Social Outcomes:**
- Significant reduction in the number of accidents near school and hospital zones.



- Increased public awareness about following traffic rules and speed limits.
- A step toward digital and smart traffic management infrastructure.
- Better safety for children, patients, and pedestrians in sensitive areas.

3.5 Scope and Limitations

Scope of the Project :

The proposed IoT-based system has a wide range of applications in real-world scenarios. Its scope includes:

1. **School and Hospital Zones:** Automatic vehicle control can ensure the safety of students and patients.
2. **Residential and Parking Areas:** Helps maintain safe speeds and prevents collisions.
3. **Industrial and Construction Sites:** Ensures restricted entry and safety of workers.
4. **Smart City Infrastructure:** Can be integrated with municipal monitoring systems for intelligent traffic management.
5. **Educational Demonstration:** Serves as a valuable project model for engineering students to learn about IoT and embedded systems.

Limitations of the Project :

Although the project is efficient and reliable for demonstration purposes, it has certain limitations that can be improved in the future:

1. The detection range of **ultrasonic sensors** is limited (approximately 3–4 meters).
2. **Wi-Fi connectivity** depends on network coverage and signal strength.
3. The prototype uses a **small motor system**, which represents vehicle speed in a simulated environment, not a real car.
4. The system works effectively only within a certain power range; battery maintenance is required for long-term use.
5. Environmental factors such as rain, dust, or light interference may affect sensor performance.



CHAPTER – 4

DESIGN AND IMPLEMENTATION

4.1 System Overview and Architecture

The **IoT-Based School Safety Zone Sensor System** is designed to automatically monitor and control vehicle speed within restricted areas such as school or hospital zones. The system detects an approaching vehicle, reduces its speed, and simultaneously sends real-time data to the IoT cloud platform for monitoring.

The system comprises three major sections:

1. **Sensing Unit:** Detects vehicle presence using ultrasonic sensors.
2. **Control Unit:** Processes data using an Arduino microcontroller.
3. **IoT Communication Unit:** Sends real-time information to the cloud via the ESP8266 Wi-Fi module.

When a vehicle enters the school zone, the **ultrasonic sensor** detects it, and the **Arduino UNO** activates the motor driver to automatically reduce the vehicle's speed. At the same time, the **LED** and **buzzer** are triggered to alert both the driver and nearby pedestrians. The system also uploads the status to the **IoT platform (ThingSpeak/Blynk)**, where it can be monitored remotely by authorities.

The overall architecture of the system can be represented by the following flow:

Sensor → Arduino Controller → Motor Driver → Vehicle Model (DC Motor)
↳ IoT Module → Cloud Server → Monitoring Dashboard

4.2 Hardware Components Used

The hardware part of the project forms the foundation of the system's functioning. Each component plays a unique role in ensuring proper detection, control, and communication.

Below is a detailed description of the components used:

4.2.1 Hardware Components Used

The Arduino UNO is the main control unit of the system. It reads signals from the sensors, executes control logic, and sends commands to the motor driver and IoT module.

It is based on the ATmega328P microcontroller and has 14 digital I/O pins, 6 analog inputs, and a 16

MHz clock.

Functions:

- Receives data from the ultrasonic sensor.
- Controls the motor driver for speed adjustment.
- Sends data to the ESP8266 Wi-Fi module.






Figure 4.2.1 Arduino UNO Microcontroller

4.2.2 Ultrasonic Sensor (HC-SR04)

The HC-SR04 ultrasonic sensor detects the distance between the sensor and the approaching vehicle by emitting ultrasonic waves and measuring their reflection time.

Key Features:

- Operating voltage: 5V DC
- Range: 2 cm to 400 cm
- Accuracy: ± 3 mm

Functions:

- Detects approaching vehicles within the school zone.
- Sends distance data to the Arduino for processing.

4.2.3 Motor Driver Module (L298N)

The L298N motor driver acts as an interface between the microcontroller and the vehicle's motor. It controls the direction and speed of the DC motor.

Functions:

- Drives the DC motor based on commands from the Arduino.
- Controls motor speed automatically when the vehicle enters a restricted area.

4.2.4 DC Motor

The DC motor is used to simulate vehicle movement in the prototype. It demonstrates automatic speed reduction when the vehicle enters the school zone.

Functions:

- Represents vehicle motion in the model.
- Responds to control signals from the motor driver.

4.2.5 ESP8266 Wi-Fi Module

The ESP8266 is a low-cost Wi-Fi microchip that provides wireless connectivity for IoT applications.

Functions:

- Transmits data to cloud platforms such as ThingSpeak or Blynk.
- Enables remote monitoring of vehicle activity and speed status.

4.2.6 Buzzer



The buzzer is used to generate an audible alert when a vehicle enters the safety zone. It acts as a warning system for both drivers and pedestrians.

4.2.7 LED Indicators

Two LEDs (Red and Green) are used in the project.

- Red LED: Indicates danger or overspeed detection.
- Green LED: Indicates safe operation or normal conditions.

4.2.8 Power Supply (9V Battery)

The 9V DC power supply provides the necessary voltage to run the Arduino board, sensors, and other modules.

4.2.9 Connecting Wires and Breadboard

Used for circuit connections during prototyping, ensuring flexibility and ease of modification during testing.

4.2.10 4WDKIT Four Wheel Robotic Smart Car




Figure 4.2.10 4WD Double Layer Car Chassis

4.3 Software Tools and Platforms

The software section provides the intelligence behind the hardware components. The following software tools were used:



4.3.1 Arduino IDE

The Arduino Integrated Development Environment (IDE) is used to program the Arduino UNO. It allows users to write, compile, and upload code to the microcontroller using USB connectivity. Functions:

- Program writing and logic testing.
- Serial communication monitoring.
- Uploading compiled code to the Arduino board.
-

4.3.2 ThingSpeak IoT Platform

ThingSpeak is an open-source IoT analytics platform that allows data storage, visualization, and analysis in real time. It communicates with the ESP8266 module to receive sensor data and display it in graphical form.

4.3.3 Blynk Application (Optional)

Blynk is a mobile-based IoT dashboard that can be used to visualize data and control hardware remotely. It can send notifications and display live status of sensors.

4.3.4 Embedded C Programming Language

The project is programmed in Embedded C, the most common language for Arduino. It defines all logical conditions and sensor responses.

4.4 Circuit Design and Description

The system circuit consists of an Arduino UNO connected to an ultrasonic sensor (HC-SR04) for distance detection, an L298N motor driver for motor control, an ESP8266 Wi-Fi module for IoT communication, and LEDs and buzzer for alerts.



Chandigarh Engineering College Jhanjeri

Mohali-140307

Department of Computer Science & Engineering

When the sensor detects an obstacle (vehicle) within a predefined range, the Arduino sends a signal to the motor driver to slow down the DC motor speed. Simultaneously, the buzzer and red LED are activated. The ESP8266 module then uploads this status to the IoT cloud for monitoring.

4.5 Working Principle

The working of the system can be summarized as follows:

1. Initialization: When the system is powered on, all components are initialized by the Arduino.
2. Detection: The ultrasonic sensor continuously measures distance. If an object (vehicle) is detected within the threshold range, it sends a signal to the Arduino.
3. Processing: The Arduino processes this input and compares it with preset distance limits.
4. Control Action: If the vehicle enters the safety zone, the Arduino signals the motor driver to reduce motor speed automatically.
5. Alert Generation: Simultaneously, the buzzer and red LED are turned ON to warn both driver and pedestrians.
6. IoT Data Update: The ESP8266 module uploads the current status (vehicle detected, speed reduced, alert active) to the IoT cloud platform.
7. Reset State: When the vehicle leaves the safety zone, the system resets to normal, turning ON the green LED and restoring normal speed.

4.6 Integration and Testing

After assembling all components, the system was tested under different conditions to verify its performance and reliability.

Integration Process :

- The hardware connections were verified using a breadboard setup.
- The Arduino was programmed and connected with the ESP8266 module.
- The ThingSpeak platform was linked for IoT data visualization.

Testing Steps:

1. When no vehicle was detected, the green LED remained ON and the motor ran at normal speed.



2. When an obstacle was detected within the defined range, the red LED glowed, the buzzer beeped, and motor speed reduced automatically.
3. The IoT dashboard displayed “Vehicle Detected – Speed Reduced” message in real time.

Results :

- The system successfully detected vehicles entering the school zone.
- The automatic speed control and alert mechanism functioned accurately.
- Data was transmitted successfully to the cloud via Wi-Fi.

Conclusion of Testing :

The prototype performed efficiently and met all design expectations. It is reliable, low-cost, and suitable for implementation in small- or large-scale environments.

CHAPTER – 5

RESULTS AND DISCUSSION

5.1 Experimental Setup

After completing the design and integration of all hardware and software components, the system was assembled on a breadboard for experimental testing. The setup included the Arduino UNO, Ultrasonic Sensor (HC-SR04), Motor Driver (L298N), DC Motor, LEDs, Buzzer, and ESP8266 Wi-Fi module.

A miniature prototype of a vehicle and road segment was created to simulate the real-time working of the system. The ultrasonic sensor was positioned near the “school zone” area to detect any approaching object (representing a vehicle). The DC motor acted as the vehicle engine, and its speed was automatically controlled based on the sensor data received by the Arduino.

The Arduino IDE was used for programming the microcontroller, and ThingSpeak IoT platform was utilized for real-time data visualization. During testing, the system was powered using a 9V DC power supply. The entire setup was compact, cost-efficient, and easily portable for demonstration.

A laptop was connected to the Arduino board for serial monitoring, while the IoT dashboard displayed sensor readings and alert messages. All experiments were conducted under controlled conditions to verify system accuracy, response time, and reliability.



5.2 Data Collection and Analysis

The data for this project was collected during multiple test runs under varying conditions — such as different vehicle distances, speeds, and sensor placements.

When the vehicle entered the safety zone (within 25–30 cm of the sensor), the ultrasonic sensor detected it instantly and sent data to the Arduino. The microcontroller then activated the buzzer and switched ON the red LED while simultaneously reducing the motor speed through the motor driver. The system maintained this state until the vehicle exited the zone.

The ThingSpeak IoT platform collected the following types of data :

- Distance values from the ultrasonic sensor.
- Zone status: “Safe” or “Alert.”
- Motor speed percentage.
- Timestamp of detection.

This real-time data was visualized as line graphs on the ThingSpeak dashboard, clearly showing when the vehicle entered or exited the school zone.

Analysis Summary:

- The system’s detection response time was approximately 1 second.
- The motor speed was reduced by about 50–60% upon detection.
- The alert signals (LED and buzzer) responded instantly without lag.
- IoT data was successfully transmitted to the cloud with no packet loss during stable Wi-Fi conditions.

5.3 Advantages of the Proposed System

The proposed IoT-Based School Safety Zone Sensor System provides several advantages over conventional safety methods:

1. Automation:

The system operates automatically without human intervention. Once powered on, it detects, alerts, and controls vehicle speed autonomously.

2. Real-Time Monitoring:

Through IoT connectivity, authorities can observe live data of vehicle activity in restricted zones, improving transparency and control.



3. Accident Prevention:

By reducing vehicle speed automatically, the risk of accidents is significantly lowered, especially in school and hospital areas.

4. Low Cost and Easy Implementation:

The system uses inexpensive and widely available components, making it suitable for large-scale deployment.

5. Eco-Friendly and Energy Efficient:

The system consumes minimal power and can run continuously using a small battery supply.

6. Scalability:

The model can be expanded to cover multiple lanes or zones by adding more sensors and Wi-Fi modules.

7. Data Analytics:

IoT cloud storage enables long-term data logging, allowing authorities to analyze traffic patterns and plan improvements.

8. Improved Public Safety:

The combination of automatic control and instant alerts ensures better safety for pedestrians, students, and patients.

5.4 Performance Analysis

The performance of the system was evaluated on the basis of response time, accuracy, reliability, and IoT connectivity.

1. Response Time

The sensor detected vehicles almost instantly (average delay of 0.8–1.2 seconds). This fast response is sufficient for real-time applications in short-distance zones like school entrances.

2. Accuracy



The system accurately measured distances between 2 cm to 300 cm, maintaining consistent readings. The speed control mechanism responded correctly to every valid detection, ensuring reliable performance.

3. Reliability

During repeated trials, the system performed consistently without failure. Both hardware and software components worked in synchronization, and no false detections were observed under stable environmental conditions.

4. IoT Connectivity

The ESP8266 Wi-Fi module transmitted all readings to the ThingSpeak platform successfully. The average data update interval was 15 seconds, and all sensor readings were plotted correctly in real time.

5. Safety and Efficiency

By automating speed control, the system achieved around 70–80% reduction in potential overspeeding cases during the experiment. It ensures safety while maintaining operational simplicity.

CHAPTER – 6

CONCLUSION AND FUTURE SCOPE

6.1 Conclusion

The project titled “IoT-Based School Safety Zone Sensor System – Automatic Vehicle Control near School or Hospital Zone” has been successfully designed, implemented, and tested. The main objective of this project was to enhance safety in school and hospital zones by automatically detecting and controlling vehicle speed through the integration of sensors, microcontrollers, and IoT technology.

The system operates on a simple yet effective principle — when a vehicle approaches the safety zone, ultrasonic sensors detect its presence, the Arduino UNO microcontroller processes the information, and the motor driver automatically reduces the speed of the vehicle. Simultaneously, LED indicators and a buzzer alert both drivers and pedestrians. The ESP8266 Wi-Fi module ensures that all activity is sent to an IoT cloud platform (ThingSpeak or Blynk), allowing remote monitoring and analysis.

The experimental results proved that the system works efficiently, with accurate detection, quick response time, and stable IoT connectivity. The proposed system is not only cost-effective but also reliable and easy to implement.



This project demonstrates how embedded systems and IoT technologies can be combined to create real-world smart safety solutions. It effectively minimizes the chances of accidents in sensitive zones, promotes road discipline, and contributes to the vision of Smart City and Intelligent Transportation Systems (ITS).

In conclusion, the IoT-Based School Safety Zone Sensor System successfully achieves its objectives of automation, safety, and monitoring, making it a practical, innovative, and scalable solution for modern traffic management.

6.2 Project Constraints and Limitations

Although the proposed system achieved its intended objectives, there are certain limitations and constraints that must be considered for real-world implementation. These limitations primarily arise from hardware and environmental conditions.

1. Hardware Limitations

- The ultrasonic sensor has a limited detection range (up to approximately 4 meters). Beyond this range, the accuracy of detection decreases.
- The DC motor used in the prototype represents vehicle speed symbolically; in real vehicles, more powerful control systems will be required.
- The Arduino UNO can handle a limited number of input/output operations; scaling up the system for multiple zones would require advanced controllers.

2. Connectivity Constraints

- The Wi-Fi module (ESP8266) requires a stable internet connection. Any network disruption can cause temporary data loss or delay in IoT updates.
- Real-world environments may face signal interference due to obstacles, distance, or electromagnetic noise.

3. Environmental and Operational Factors

- Dust, rain, or excessive sunlight can affect the performance of the ultrasonic sensor.
- The system's accuracy depends on the proper alignment of the sensor and the reflective surface of vehicles.
- Continuous operation for long durations may require regular maintenance and power management to ensure reliability.



4. Power Supply Constraints

- The system is powered by a 9V DC supply, which is suitable for prototypes but not for large-scale setups.
 - For continuous use, the system will need a regulated power source or solar energy integration.
- Despite these limitations, the system performs remarkably well under controlled conditions and serves as a strong foundation for future development.

6.3 Future Enhancements and Recommendations

The present system is developed as a prototype model demonstrating the concept of automatic vehicle speed control using IoT technology. However, it can be enhanced further for real-world deployment through the following improvements and modifications:

1. Integration with GPS and GSM Modules

By adding GPS (Global Positioning System) and GSM (Global System for Mobile Communication) modules, the system can send live alerts and location data to authorities or emergency services during overspeed detection or accidents.

2. Advanced Sensors and AI Integration

Incorporating infrared (IR) sensors, LIDAR, or camera-based detection systems with Artificial Intelligence (AI) can improve accuracy and allow for object classification (vehicles, pedestrians, obstacles, etc.).

3. Centralized Traffic Management

The system can be connected to a centralized IoT-based traffic management platform, where multiple zones can be monitored simultaneously, improving coordination and response time.

4. Mobile Application Development

A dedicated mobile app can be developed for administrators and drivers to view live IoT data, receive alerts, and access safety analytics.

5. Solar Power Implementation

To make the system energy-efficient and environment-friendly, solar panels can be used to power sensors, controllers, and communication modules.

6. Integration with Smart City Infrastructure

The system can be integrated with smart city IoT networks to form part of an intelligent transportation system, enabling data sharing, predictive analysis, and automated law enforcement (speed violation records).



7. Machine Learning for Predictive Analysis

Using IoT data logs collected over time, machine learning algorithms can predict high-risk times or locations for accidents and automatically adjust system sensitivity.

8. Real Vehicle Implementation

The final goal of this project would be to install this system in actual vehicles, where the onboard control system automatically interacts with roadside sensors and adjusts the vehicle's throttle accordingly.

By implementing these enhancements, the system can evolve from a prototype to a real-time smart transportation solution suitable for large-scale deployment.

6.4 Final Remarks

This project successfully demonstrates the application of IoT in road safety and automation. Through a combination of low-cost sensors, a microcontroller, and a cloud-based monitoring platform, the system ensures safety, awareness, and efficiency in school and hospital zones.

The project provides a comprehensive learning experience in hardware design, embedded programming, and IoT integration. It shows how technology can solve real-world safety problems while being cost-effective and accessible.

The proposed system aligns with the government's vision of Digital India and Smart City initiatives, promoting the use of intelligent systems for public safety and traffic control.


In future, such systems can be installed across cities to form a network of connected safety zones, significantly reducing accidents and ensuring safer roads for everyone.

The project demonstrates that even a simple IoT-based prototype can make a meaningful contribution toward the development of smart, safe, and sustainable communities.



CHAPTER 7

FINAL PROJECT IMAGE





References :

1. E. George, Nawfal A. Hussein, “LoRaWAN-Based Architecture for Speed Control in Area Zones Using Radar Sensor Nodes,” Applied Loay Sciences, MDPI, 2024.

<https://www.mdpi.com/2076-3417/14/20/9243>

2. Wikipedia contributors, “Intelligent Speed Assistance,” Wikipedia,

https://en.wikipedia.org/wiki/Intelligent_speed_assistance

4. IJRASET, “Intelligent IoT-Based Automatic Vehicle Speed Control and Alert System,” International Journal for Research in Applied Science and Engineering Technology, 2022.

<https://www.ijraset.com/research-paper/intelligent-iot-based-automatic-vehicle-speed-control-and-alert-system>

5. IJERT, “Solar Based Automatic Speed Control of Vehicles in Sensitive Zones,” International Journal of Engineering Research & Technology, 2021.

<https://www.ijert.org/solar-based-automatic-speed-control-of-vehicles-insensitive-zones>

6. Vinitha P. et al., “Automatic Vehicle Speed Reduction & Accident Prevention System Using RF Technology,” ResearchGate, 2021.

<https://www.researchgate.net/publication/368026253>

7. IJARIT, “Automatic Vehicle Speed Control,” International Journal of Advance Research, Ideas and Innovations in Technology, 2020.



Chandigarh Engineering College Jhanjeri
Mohali-140307
Department of Computer Science & Engineering

<https://www.ijariit.com/manuscript/automatic-vehicle-speed-control>

8. Wikipedia contributors, “Radar Speed Sign,”

Wikipedia,

https://en.wikipedia.org/wiki/Radar_speed_sign

