САНКТ-ПЕТЕРБУРГСКИЙ НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ УНИВЕРСИТЕТ ИТМО

Дисциплина: Бэк-энд разработка

Отчет

Лабораторная работа 2 "Тестирование, разработка и документирование RESTful API"

Выполнил:

До Ван Тхиен

K33402

Проверил: Добряков Д. И.

Санкт-Петербург

2022 г.

Задача

Peaлизовать RESTful API средствами express + typescript

Ход работы

1. подключиться к бд

```
import mongoose from "mongoose";
  import config from "config";
  import log from "../logger";
v function connect() {
    const dbUri = config.get("dbUri") as string;
    return
      .connect(dbUri, {
        useNewUrlParser: true,
        useUnifiedTopology: true,
      })
      .then(() => {
        log.info("Database connected");
      })
      .catch((error) => {
        log.error("db error", error);
        process.exit(1);
      });
  export default connect;
```

2. controller..user.ts

```
import { Request, Response } from "express";
import { omit } from "lodash";
import { createUser } from "../service/user.service";
import log from "../logger";

export async function createUserHandler(req: Request, res: Response) {
   try {
      const user = await createUser(req.body);
      return res.send(omit(user.toJSON(), "password"));
   } catch (e) {
      log.error((e as Error).message);
      return res.status(409).send((e as Error).message);
   }
}
```

3. service.user.ts

```
import { DocumentDefinition, FilterQuery } from "mongoose";
import { omit } from "lodash";
import User, { UserDocument } from "../model/user.model";
export async function createUser(input: DocumentDefinition<UserDocument>) {
 try {
  return await User.create(input);
 } catch (error) {
  throw new Error((error as Error).message);
export async function findUser(query: FilterQuery<UserDocument>) {
 return User.findOne(query).lean();
export async function validatePassword({
 email,
 password,
}: {
 email: UserDocument["email"];
 password: string;
}) {
 const user = await User.findOne({ email });
 if (!user) {
  return false;
 const isValid = await user.comparePassword(password);
 if (!isValid) {
 return omit(user.toJSON(), "password");
```

4. model.user.ts

```
export interface
                              extends
  password: string;
 createdAt: Date;
 updatedAt: Date;
  comparePassword(candidatePassword: string): Promise<boolean>;
const UserSchema = new mongoose.Schema(
   name: { type: String, required: true },
  { timestamps: true }
);
UserSchema.pre("save", async function (next: mongoose.HookNextFunction) \P
 if (!user.isModified("password")) return next();
  // Random additional data
  const salt = await bcrypt.genSalt(config.get("saltWorkFactor"));
  const hash = await bcrypt.hashSync(user.password, salt);
  // Replace the password with the hash
 user.password = hash;
 return next();
别);
// Used for logging in
UserSchema.methods.comparePassword = async function (
 candidatePassword: string
) {
 return bcrypt.compare(candidatePassword, user.password).catch((e) => false);
};
                                  cument>("User", UserSchema);
                     .model<Use
export default User;
```

5. app.ts


```
import express from "express";
import config from "config";
import log from "./logger";
import connect from "./db/connect";
import routes from "./routes";
import { deserializeUser } from "./middleware";
const port = config.get("port") as number;
const host = config.get("host") as string;
const app = express();
app.use(deserializeUser);
app.use(express.json());
app.use(express.urlencoded({ extended: false }));
app.listen(port, host, () => {
 log.info(`Server listing at http://${host}:${port}`);
 connect();
 routes(app);
```


6. routes.ts


```
export default function (app: Exp
                                    s) {
 app.get("/healthcheck", (req: Reques
                                      st, res: Response) => res.sendStatus(200));
 // Register user
 app.post("/api/users", validateRequest(createUserSchema), createUserHandler);
 // Login
 app.post(
   "/api/sessions",
   validateRequest(createUserSessionSchema),
   createUserSessionHandler
  );
 // Get the user's sessions
 app.get("/api/sessions", requiresUser, getUserSessionsHandler);
 // Logout
 app.delete("/api/sessions", requiresUser, invalidateUserSessionHandler);
 // Create a post
 app.post(
   "/api/posts",
   [requiresUser, validateRequest(createPostSchema)],
   createPostHandler
  );
 // Update a post
 app.put(
   "/api/posts/:postId",
    [requiresUser, validateRequest(updatePostSchema)],
   updatePostHandler
  );
 // Get a post
 app.get("/api/posts/:postId", getPostHandler);
 // Delete a post
 app.delete(
   "/api/posts/:postId",
   [requiresUser, validateRequest(deletePostSchema)],
   deletePostHandler
  );
```


Postman

Create user









Вывод

Узнал как создать RESTful API средствами express + typescript для создания публикацию.