

Internal



Tamm Profile Management

Integration Guide

Date : 12-12-2023

Version : 0.2

Document Privacy: Confidential

Contents

- 1 Introduction 4
 - 1.1.1 Purpose 4
 - 1.1.2 Scope 4
 - 1.1.3 Definitions, acronyms, and abbreviations 4
- 2 Authentication 5
- 3 Load Profile 5
- 4 Switch Profile 8
- 5 Headers required in other APIs..... 9
- 6 Appendix.....10
 - 6.1.1 Service Configuration10
 - 6.1.2 Error codes10

Internal
Document History Log

Version	Author	Issue Date	Revision Source	Changes
0.1	Mohammad Hewedy	01-01-2023		Initiated
0.2	Shueb Dalvi	12-12-2023		Updated links
0.3	Manazir Khan	03-01-2024		Modified

1 Introduction

1.1.1 Purpose

The purpose of this document is to communicate to the client the APIs for use.

This document discusses in detail APIs of Profile Management, their resources, and their request/response parameters. The details of each parameter field like its type is also described, so that the clients of the API are aware of the expected inputs and the response provided by the API with samples of request and response.

1.1.2 Scope

The document mainly focuses on the APIs available for Driving Authorizations and the parameters required in invoking these web services.

1.1.3 Definitions, acronyms, and abbreviations

Acronym or Abbreviation	Definition
NIC	National Information Center
NIN	National Identification Number
OTP	One Time Password
URI	Uniform Resource Locator
HTTP	Hyper Text Transfer Protocol

Internal 2 Authentication

Tamm uses OpenID Connect (OIDC) protocol to authenticate API users. To invoke any API, user need to have an Access Token and send it in the request headers as a bearer token.

OpenID Connect (OIDC) is an open authentication protocol that works on top of the OAuth 2.0 framework. Targeted toward consumers, OIDC allows individuals to use single sign-on (SSO) to access relying party sites using OpenID Providers (OPs), such as an email provider or social network, to authenticate their identities.

Then using the Client Id and Client Secret with user's Username and Password from Tamm, user need to get an Access Token from Elm Identity Provider server (IdP) at [https://idp.elm.sa \(production\)](https://idp.elm.sa (production)).

And finally, using this access token user can invoke Tamm APIs by including that token in the HTTP request headers as a bearer token.

Refresh token can be used as well to refresh Access Tokens according to the OIDC protocol.

The only OIDC Authentication flows allowed are Client Credentials

You can call the API with the access token in the Authorization header:

```
Request curl --location --request GET '{{baseUrl}}/api/v1/test/ping' \
--header 'Authorization: Bearer eyJhbGciOiJSUzI1 . . . . . pMreJp3AsCTnWZQo26QWEg'
```

The ping API made available so API developers can test their OIDC client setup.

3 Load Profile

This API allows the user to load his profile and returns information critical to the usage of the APIs, such as the user id that to be used in subsequent API calls.

If the user has single profile, meaning the user's National ID Number is registered once in TAMM, then the response will contain a list of single object along with any message and actions required.

NOTE

This API should be called when the user uses the OAuth Code Flow. If user logged to idP using the client credentials flow, then see the document "Integrators Integration Guide"

Internal

URL

POST {{baseUrl}}/api/v1/integrator/users/profiles/load

Input: Request body

Name	Description	Example	Type	Required
userIdNumber	NationalId/Iqama number	10237828**	Long	Yes
accountMoiNumber	Moi number	70013969**	Long	Yes

Headers

Authorization:IdP access token sent as bearer token

Output

Name	Description	Type
User	Object contains basic information about user, branch, and account	Object (see example blow)
privileges	List of user’s privileges	List of Strings
message	Messages field indicate some error case that prevents the user from using the system, such as transaction invoices not paid. If there’s any message retuned from the API, then you need to display to the user so that user can read and understand the message and act accordingly. example messages might be related to subscription fees or transaction fees is not paid.	LingualString (see example blow)

Internal
actions

List of actions that user should take to login to the system via Portal.
When this list is not empty, the user need to login to portal so he can do such actions.

Example actions such as updating the invoice address.

You need to check if this list contains elements, then you will display a message with the meaning that user has to login to TAMM Portal to complete required actions.

List of Strings

Example:

Output

```
[
  {
    "user": {
      "id": 71000,
      "language": "EN",
      "email": "clienthq21aug@elm.sa",
      "phone": "583914459",
      "isDeleted": false,
      "userType": "HQ_ADMIN",
      "branch": {
        "id": 71000,
        "name": {
          "ar": "السند فرع",
          "en": "branch1"
        }
      },
      "account": {
        "id": 120032,
        "clientTypeCode": 8,
        "name": {
          "ar": "رقم شركة 118",
          "en": "ClientHq21"
        }
      },
      "isDeleted": false,
      "type": "CLIENT",
      "moiNumber": "70013969**",
      "isPostpaid": true
    },
    "isDeleted": false
  },
  "identity": {
    "id": "10237828**",
    "fullName": "خالد سعد محمد علي",
    "name": null,
    "dob": null,
    "isDeleted": false,
    "isInSync": true,
    "mobile": null,
    "isVerifiedWithOTP": null
  },
  "group": null,
  "isPhoneVerified": true,
  "isEmailVerified": false
},
"privileges": null,
"message": null,
"messageLevel": null,
"actions": null
]
```

Internal

4 Headers required in other APIs

To call other APIs, you need to set special header with name “X-Integrator-User-Id” and value of User Id returned in the Id field from the Load profile APIs.

The header “X-Integrator-User-Id” is required only if the user has multiple profiles.

Internal 5 Appendix

6.1.1 Service Configuration

Service	Staging	Production
Tamm base URL	https://tamm-qa-api.apps.devocp4.elm.sa	https://tamm.api.elm.sa
IdP	https://idp.apps.devocp4.elm.sa/	https://idp.elm.sa
IdP Realm	Tamm-QA	Tamm

6.1.2 Error codes

Code	Type	Message
400	Business error	Business error message translated in Arabic and English
500	System error	"Generic error occurred" or "حدث خطأ أثناء تنفيذ طلبك"

Example

Error	<pre>{ "status": 400, "timestamp": "2022-10-02T09:52:06.858339401Z", "message": { "ar": "ال توجد تفاويض خاصة بالمركبة ذات الرقم التسلسلي 2121060274", "en": "nodrivingauthorizationexistsforvehiclewithsequence 2121060274" }, "traceId": "9d17f8ad2931b40e", "errors": null }</pre>
-------	--