Coditu — emergency card

One page. Print it. For the night something is gone and nobody remembers any of this.

Written 2026-08-31. Verified by following it literally, changing nothing — see `docs/06-PROGRESS.md`.

---

1. Read this first

Your data is not inside the application. It is a nightly encrypted archive, ~19 MB, and there are several copies. The application being down and the data being gone are different problems, and only one of them has ever been likely.

The fastest useful thing you can do is get the rows back, not get the site back. That takes minutes and needs no provider account.

---

2. Where the copies are

Copy	Where	Needs
PRIMARY	Mohamed's Mac: `~/Library/Application Support/coditu-backups/`	The Mac
Off-site 1	The Google Drive folder named in `~/.config/coditu/nightly.env` as `OFFSITE_drive_DIR`	A Google sign-in, or any machine where that Drive is synced
Off-site 2	An external disk with `.coditu-backup-volume` in its Coditu folder	The disk
Older sets	`MooTamer/coditu-recovery` GitHub releases, up to 2026-08-31 only	A GitHub sign-in

Each copy is the same pair of files per night:

```
<id>.tar.gz.age        the encrypted archive
<id>.metadata.json     its checksum, row counts and bucket counts
```

`<id>` is `YYYY-MM-DDTHHMMSSZ`. **Newest is best; any of them works.**

---

3. The key — read this before anything else fails

The archives are encrypted with **age**. Without the private key they are noise, and there is no recovery, no escrow and no reset.

Where the key is	`~/.config/coditu/backup.agekey` on Mohamed's Mac, mode 0600
Second copy	□ *fill this in* — the safe, the wallet, the password manager entry, the sealed envelope
Public recipient (not secret)	`ops/backup-recipient.txt` in the repository

> **If there is no second copy and the Mac is gone, stop reading: every archive everywhere is unreadable.** Make the second copy today, and **not** where the archives are — a key stored beside its ciphertext is not a key. Paper in a different building. A password-manager entry. Anywhere the Drive folder is not.

Never type the key into a chat, a ticket, a commit, or this card.

---

4. Get the data back — the short version

On any Mac or Linux machine with Docker and `age`:

```
brew install age                          # or: apt install age
docker run -d --name coditu-restore -e POSTGRES_PASSWORD=postgres -p 5599:5432 postgres:17
age -d -i /path/to/backup.agekey <id>.tar.gz.age | tar -xz -C /tmp/coditu-restore
psql 'postgresql://postgres:postgres@127.0.0.1:5599/postgres' -f /tmp/coditu-restore/database.sql
```

Then the data is queryable:

```
psql 'postgresql://postgres:postgres@127.0.0.1:5599/postgres' \
  -c 'select count(*) from public.work_items'
```

Measured, unattended, with the network off: see §7.

Storage files (avatars, attachments) are in the same archive under `storage/`, as ordinary files. They need no database and no tool — open them.

---

5. Get the application back

Only if you need the app, not just the data.

1. Create a new Supabase project. Note its URL, anon key and service-role key.
2. Restore as in §4, but against the new project's connection string.
3. **Reapply the two triggers no dump carries** — without them there is no profile creation and **no sign-up gate**:

   ```
   scripts/reapply-managed-triggers.sh '<new project connection string>'
   ```

4. Set `NEXT_PUBLIC_SUPABASE_URL`, `NEXT_PUBLIC_SUPABASE_ANON_KEY`, `SUPABASE_SERVICE_ROLE_KEY` on Vercel and redeploy, or run `npm run build && npm start` anywhere.

Estimated 30–60 minutes. It is an estimate and `docs/14-DEPENDENCY-LEDGER.md` says what it is made of.

---

6. Verify you actually got everything

```
node scripts/check-materialised.mjs /path/to/the/archives
```

Prints `materialised=true` only when every archive read back byte-for-byte and matched its own sidecar. **A file that is the right size is not evidence** — a cloud folder can hold a placeholder with the right name, the right size and no bytes at all.

Compare the restored counts to the sidecar:

```
cat <id>.metadata.json     # databaseTables, databaseRows, storageBuckets, storageObjects
```

---

7. How long it takes

Step	Time	Measured how
Decrypt and restore the database	*see* `docs/06-PROGRESS.md`*, offline pass*	Unattended, **wifi off**
Read the Storage files	immediate	They are files
Stand the application up again	30–60 min	Estimate; components in the ledger

---

8. Who and what

Repository	`MooTamer/coditu` (private) — every clone is a complete copy

Recovery tooling	`MooTamer/coditu-recovery` — self-contained, so recovery never begins by checking out the thing that was lost
Hosting	Vercel Hobby, project `coditu`, `https://coditu-phi.vercel.app`
Database	Supabase Free, `hayfsvsepgfescojesbd`, eu-central-1
Longer runbook	`docs/12-RECOVERY-RUNBOOK.md`
What each provider is worth	`docs/14-DEPENDENCY-LEDGER.md`