

## Quiz about Latex in em, Blaine Mooers yr2022mo09day01hr09min07sec07

1. In Emacs parlance, syntax highlighting is called \_\_\_\_.
2. To view the dvi file, enter \_\_\_\_.
3. To close a command pair, enter \_\_\_\_.
4. To put the error message shell on the screen, enter \_\_\_\_.
5. Enter \_\_\_\_ in a document with chapters, sections, or both to display a navigable Table of Contents in a separate buffer.
6. To check the entire buffer for syntax errors before compiling, enter \_\_\_\_.
7. Enter \_\_\_\_ at the end of a line in an itemize list to insert a new indented item.
8. Enter \_\_\_\_ to fill and indent the current environment.
9. To count the words in LaTeX file and not include the LaTeX markup in the word count, enter \_\_\_\_.
10. Errors are listed in an \*occur\* buffer. Goto to line with error, with the \_\_\_\_ command.
11. To check the region for syntax errors, enter \_\_\_\_.
12. Position the cursor right after a left brace and enter \_\_\_\_ to find the matching right brace.
13. Enter \_\_\_\_ to compile a LaTeX tex file.
14. Enter \_\_\_\_ to reload a LaTeX tex file.
15. Enter \_\_\_\_ to comment out a paragraph.
16. The default dvi viewer on Linux and Macs is \_\_\_\_.
17. M-q is an alias for \_\_\_\_.
18. To insert an item in the middle of list, enter \_\_\_\_.
19. To view a dvi file in Emacs, enter \_\_\_\_.
20. Enter \_\_\_\_ to compile a LaTeX tex file and display the PDF in your systems default PDF-viewer.
21. When the cursor is between braces, enter \_\_\_\_ to move the cursor just beyond the right brace.
22. Enter \_\_\_\_ to comment out a region.
23. To insert two braces with the cursor (or point) between the braces, enter \_\_\_\_.
24. To check the buffer for syntax errors, enter \_\_\_\_.
25. Enter \_\_\_\_ to invoke LFD: newline and indent cursor (or point).
26. To insert the document begin and end environment pair, enter \_\_\_\_ RET document RET RET.
27. To check a region for mismatched braces or dollar signs before compiling, enter \_\_\_\_.
28. To wrap a region in a command pair after writing the region, enter \_\_\_\_.
29. Enter \_\_\_\_ to fill and indent the current section.
30. To run M-x tex-bibtex-file, enter \_\_\_\_.
31. To compile the current buffer, enter \_\_\_\_.
32. To kill the current tex file compiling, enter \_\_\_\_.
33. Enter \_\_\_\_ to move the point past the right brace when it is between braces.
34. To process a file, enter \_\_\_\_.
35. Enter \_\_\_\_ to fill and indent the current region.
36. To print the dvi output, enter \_\_\_\_.
37. To save and compile the current file, enter \_\_\_\_.
38. Enter \_\_\_\_ to insert opening and closing braces and positioning the between the braces.
39. To close the last unclosed latex block, enter \_\_\_\_.
40. To fill and indent the current paragraph, enter \_\_\_\_.
41. Linebreaks are inserted automatically when line filling is enabled with the \_\_\_\_-mode.
42. To terminate a paragraph with two hard Returns, enter \_\_\_\_.
43. To type a literal quotation mark, enter \_\_\_\_.

**Answers to quiz about Latex in em    yr2022mo09day01hr09min07sec07**

1. font locking
2. C-c C-v
3. C-c C-e
4. C-c C-d
5. C-c =
6. M-x tex-validate-buffer
7. C-c C-j
8. C-c C-q C-e
9. C-c w
10. M-x goto-line
11. M-x tex-validate-buffer
12. C-c }
13. C-c C-c
14. C-c C-n
15. C-c %
16. xdvi
17. C-c C-q C-p
18. M-RET
19. C-c C-v
20. C-c C-a
21. C-c }
22. C-c ;
23. C-c {
24. M-x tex-validate-buffer
25. C-j
26. C-c C-e
27. M-x tex-validate-region
28. C-c C-e
29. C-c C-q C-s
30. C-c TAB
31. C-c c-b
32. C-c C-k
33. C-c }
34. C-c C-f
35. C-c C-q C-r
36. C-c C-p
37. C-c C-f
38. C-c {
39. C-c C-u
40. M-q
41. auto-fill
42. C-j
43. C-q "

**References cited in quiz about Latex in em    yr2022mo09day01hr09min07sec07**

- 1.
2. 'Living in Emacs' on [ibm.com/developerWorks](https://ibm.com/developerWorks)