

Automated Program Analyzer

시간 제한	메모리 제한	제출	정답	맞힌 사람	정답 비율
2 초	1024 MB	130	27	24	22.018%

문제

Let $x_1, x_2, x_3, \dots$ be variables. n constraints of form $x_i = x_j$ or $x_i \neq x_j$ are given. The task asks for whether it is possible to assign values to the variables so that all constraints can be satisfied. For example, if the constraints are $x_1 = x_2, x_2 = x_3, x_3 = x_4, x_1 \neq x_4$, then those constraints cannot be satisfied simultaneously.

입력

The first line of the input is an integer t representing the number of instances to solve. The instances are independent. For each instance, the first line is an integer n representing the number of constraints to be satisfied. In the following n lines, each line has three integers i, j, e representing an equality/inequality constraint. If $e = 1$, the constraint shall be $x_i = x_j$. If $e = 0$, the constraint shall be $x_i \neq x_j$.

출력

The output has t lines. The k -th line of the output is a string YES or NO. Output YES if the constraints in that instance can be satisfied and NO otherwise.

제한

- $1 \leq n \leq 100,000$
- $1 \leq i, j \leq 1,000,000,000$
- $1 \leq t \leq 10$
- $e \in \{0, 1\}$

예제 입력 1

2

2

1 2 1

1 2 0

2

1 2 1

2 1 1

예제 출력 1

NO

YES

예제 입력 2

2

3

1 2 1

2 3 1

3 1 1

4

1 2 1

2 3 1

3 4 1

1 4 0

예제 출력 2

YES

NO

출처

[Olympiad](#) > [National Olympiad in Informatics \(China\)](#) > [NOI 2015 1번](#)

알고리즘 분류

- 자료 구조
- 분리 집합
- 값 / 좌표 압축