

1. 解压压缩包到 xampp 的 htdocs 文件夹下。
2. 在解压后的文件夹中进入命令行中执行 init.bat 命令，并选择开发者模式，如下图所示：

```
F:\xampp-low\htdocs\yii>init.bat
Yii Application Initialization Tool v1.0

Which environment do you want the application to be initialized in?

[0] Development
[1] Production

Your choice [0-1, or "q" to quit] 0

Initialize the application under 'Development' environment? [yes|no] yes

Start initialization ...
```

3. 在相同命令行中执行 yii 初始化命令 yii.bat，如下图所示：

```
F:\xampp-low\htdocs\yii>yii.bat

This is Yii version 2.0.32.

The following commands are available:

- asset                Allows you to combine and compress your JavaScript and CSS files.
  asset/compress (default)  Combines and compresses the asset files according to the given
                             configuration.
  asset/template           Creates template of configuration file for [[actionCompress]].
```

4. 在 PHPMyAdmin 中新建一个数据库，然后修改\common\config\main-local.php，如下图所示：

```
<?php
return [
    'components' => [
        'db' => [
            'class' => 'yii\db\Connection',
            'dsn' => 'mysql:host=localhost;dbname=yii2advanced',
            'username' => 'root',
            'password' => '',
            'charset' => 'utf8',
        ],
        'mailer' => [
            'class' => 'yii\swiftmailer\Mailer',
            'viewPath' => '@common/mail',
            // send all mails to a file by default. You have to set
            // 'useFileTransport' to false and configure a transport
            // for the mailer to send real emails.
            'useFileTransport' => true,
        ],
    ],
];
```

将 dbname 修改为刚刚创建的数据库名称，修改 username, password 为本机上 mysql 的用户名和密码，修改后如下图：

```

<?php
return [
    'components' => [
        'db' => [
            'class' => 'yii\db\Connection',
            'dsn' => 'mysql:host=localhost;dbname=test0',
            'username' => 'root',
            'password' => '',
            'charset' => 'utf8',
        ],
        'mailer' => [
            'class' => 'yii\swiftmailer\Mailer',
            'viewPath' => '@common/mail',
            // send all mails to a file by default. You have to set
            // 'useFileTransport' to false and configure a transport
            // for the mailer to send real emails.
            'useFileTransport' => true,
        ],
    ],
];

```

这里我新建的数据库名为 test0

5. 在与第三步相同的命令行中执行 yii.bat migrate 命令，如下图所示：

```

F:\xampp-low\htdocs\yii>yii.bat migrate
Yii Migration Tool (based on Yii v2.0.32)

Creating migration history table "migration"...Done.
Total 2 new migrations to be applied:
    m130524_201442_init
    m190124_110200_add_verification_token_column_to_user_table

Apply the above migrations? (yes|no) [no]:yes
*** applying m130524_201442_init
    > create table {%user}% ... done (time: 0.018s)
*** applied m130524_201442_init (time: 0.030s)

*** applying m190124_110200_add_verification_token_column_to_user_table
    > add column verification_token string NULL DEFAULT NULL to table {%user}% ... done (time: 0.032s)
*** applied m190124_110200_add_verification_token_column_to_user_table (time: 0.041s)

2 migrations were applied.
Migrated up successfully.

```

6. 将压缩包中 data 文件夹下的数据库 sql 文件导入到刚刚新建的数据库中，部署完成。

7. 前台访问页面 <http://localhost/advanced/frontend/web/>;

后台访问页面 <http://localhost/advanced/backend/web/>;