GROUND Lite Communications Protocol Specification $\frac{\text{Version 1.1.0}}{\text{Version 1.1.0}}$

B.B.F.M. Verspaandonk, M.Y.A. Wierckx

January 25, 2025

Contents

1	Overview	1
2	Packet Structure Field Descriptions	1
3	Handling magic_number in Content	2
4	Encoding order	2
5	Examples Single Value	2 2 2

1 Overview

The GROUND (GAIA Radio OUtput Network Delivery) Lite protocol is a power and data efficiency optimized version of the original GROUND protocol. All data is serialized in little-endian format, meaning the least significant byte is sent first. For example, the number 0x1234 would be transmitted as 0x34 0x12.

2 Packet Structure

A packet comprises the following fields:

#	Field Name	Size
1	magic_number	4 bytes
2	<pre>packet_number</pre>	2 bytes
3	content_type	1 bytes
4	content_size	1 bytes
5	content	content_size bytes

Field Descriptions

magic_number: A constant value 0x67616961 (ASCII for gaia) that marks the start of a packet.

content_type: Specifies the type and structure of the data. Its definitions are listed in the table below.

Value	Data Type	Type	Description
0x01	float	GPS_POS[3]	GPS coordinates
0x02	float	G_FORCES[3]	G-force measurement
0x03	float	ROTATION[3]	Angle measurement
0x04	uint32_t	TIME	Time
0x05	uint32_t	GPS_FIX_AGE	Time in ms since last gps fix
0x06	float	GPS_HDOP	Horizontal Dilution of Precision
0x07	uint8_t	GPS_NUM_OF_SATS	Number of satellites in view
80x0	float	GPS_FAIL_PERCENTAGE	Percentage of GPS cheksums failed
0x09	uint16_t	CO2_CONCENTRATION	UNUSED CO ₂ concentration in ppb
0x0A	float	TEMPERATURE	Temperature in °C
0x0B	float	PRESSURE	Pressure in Pa
0x0C	uint16_t	DUST_CONCENTRATION	Dust concentration in $\mu g/m^3$
0x0D	float	UV_RADIATON	UV radiation in mW/cm^2

content_size: The number of bytes in the content field.

content: The actual data payload. Its interpretation depends on content_type.

3 Handling magic_number in Content

If the magic_number sequence 0x67616961 appears in the content, it must be escaped by appending a 0x00 byte immediately after. For example:

```
67 61 69 61 \rightarrow 67 61 69 61 00
```

The escape byte contributes to content_size but should be removed during packet parsing.

4 Encoding order

The fields in a packet are encoded in the following order:

- 1. Check if the magic_number sequence appears in the content field. If so, escape it.
- 2. Calculate the content size.
- 3. Add the magic_number sequence, content_type, content_size and content fields.
- 4. Transmit the packet.

5 Examples

Single Value

Packet encoding a single 32-bit float with value 1013.25:

```
67 61 69 61 01 00 0B 04 00 50 7D 44
```

Breakdown:

Array

Packet encoding GPS coordinates (Latitude, Longitude, Altitude) as three 32-bit floats:

```
67 61 69 61 02 00 03 0C 00 00 B4 42 9A 99 16 43 C3 F5 48 40
```

Breakdown:

Escaped Magic Number

GPS coordinates with a magic_number sequence in the content:

```
67 61 69 61 03 00 01 0E 67 61 69 61 00 00 00 20 40 67 61 69 61 00
```

Breakdown:

```
67 61 69 61
                        // Magic Number
03 00
                        // Packet number: 3
01
                       // Content type: GPS coordinates (float GPS_POS[3])
0E
                       // Content size: 14 bytes
67 61 69 61 00
                        // Latitude with escaped magic number: 26906937000000000000
                           (this isn't actually possible with GPS coordinates
                           but you get the point it's for demonstration)
00 00 20 40
                        // Longitude: 2.5
67 61 69 61 00
                        // Altitude with escaped magic number: 26906937000000000000
                           (about 28441 light years above sea level)
```