GROUND Communications Protocol Specification

Version 1.1

B.B.F.M. Verspaandonk

December 15, 2024

Overview

The GROUND (GAIA Radio OUtput Network Delivery) protocol is designed for transmitting data from the Cansat to the ground station. All data is serialized in little-endian format, meaning the least significant byte is sent first. For example, the number `0x1234` would be transmitted as `0x34 0x12`.

Packet Structure

A packet comprises the following fields:

#	Field Name	Size
1	`magic`	4 bytes
2	`content_type`	2 bytes
3	`content_size`	2 bytes
4	`content`	`content_size` bytes

Field Descriptions

`magic`: A constant value `0x47414941` (ASCII for `GAIA`) that marks the start of a packet.

`content_type`: Specifies the type and structure of the data. Its two bytes are interpreted as follows:

- **First byte**:
  - High nibble (`0xF0`): Indicates if the content includes a CRC checksum (`0x0` = no, `0x1` = yes).
  - Low nibble (`0x0F`): Specifies the data category (see Data Types). May never be `0x0`.
- **Second byte**:
  - High nibble (`0xF0`): Indicates whether the data is a single value (`0x0`) or an array (`0x1`).
  - Low nibble (`0x0F`): Specifies the data's primitive type (see Data Types).

`content_size`: The number of bytes in the `content` field.

`content`: The actual data payload. Its interpretation depends on `content_type`.

Handling `magic` in Content

If the `magic` sequence `0x47414941` appears in the `content`, it must be escaped by appending a `0x00` byte immediately after. For example:

`47 41 49 41` → `47 41 49 41 00`

The escape byte contributes to `content_size` but is excluded from array length calculations. It should be removed during packet parsing.

Data Types

Raw Data Types

Value	Type	Description
`0x00`	`u8`	Unsigned 8-bit integer
`0x01`	`u16`	Unsigned 16-bit integer
`0x02`	`u32`	Unsigned 32-bit integer
`0x03`	`u64`	Unsigned 64-bit integer
`0x04`	`s8`	Signed 8-bit integer
`0x05`	`s16`	Signed 16-bit integer
`0x06`	`s32`	Signed 32-bit integer
`0x07`	`s64`	Signed 64-bit integer
`0x08`	`float`	32-bit floating point number
`0x09`	`double`	64-bit floating point number
`0x0A`	`bool`	Boolean
`0x0B`	`char`	ASCII character

Categorical Data Types

Value	Type	Description
`0x01`	`GPS`	GPS coordinates
`0x02`	`G-force`	G-force measurement
`0x03`	`Angle`	Angle measurement
`0x04`	`Time`	GPS Time
`0x05`	`Age`	Time in ms since last gps fix

Examples

Single Value

Packet encoding a single unsigned 16-bit integer with value `4660`:

```
47 41 49 41 21 01 02 00 34 12
```

Breakdown:

```
47 41 49 41 // Magic number
21          // Content type: Unsigned 16-bit integer
02 00       // Content size: 2 bytes
34 12       // Content: 4660
```

Array

Packet encoding GPS coordinates (latitude, longitude) as two 64-bit doubles:

```
47 41 49 41 11 19 11 00 8C 01 E2 36 9D B4 49 40 1B F1 90 7B 96 F4 15 40 6D
```

Breakdown:

```
47 41 49 41             // Magic number
11                      // Content category: GPS coordinates with CRC
19                      // Content type: Array of 64-bit doubles
10 00                   // Content size: 17 bytes
1F 8B 8C 0C F4 B6 49 40 // Latitude: 51.411047802309525
77 05 98 4A 64 D4 15 40 // Longitude: 5.488855295869395
6D                      // CRC-8 checksum
```

Escaped Magic Number

GPS coordinates with a `magic` sequence in the content:

```
47 41 49 41 11 19 12 00 47 41 49 41 00 F8 B6 49 40 10 61 4A 8F 35 D4 15 40 6D
```

Breakdown:

```
47 41 49 41                // Magic number
11                         // Content category: GPS coordinates with CRC
19                         // Content type: Array of 64-bit doubles
12 00                      // Content size: 17 bytes
47 41 49 41 00 F8 B6 49 40 // Latitude: 51.429451142090834 (with escaped magic number)
10 61 4A 8F 35 D4 15 40    // Longitude: 5.457235564150565
6D                         // CRC-8 checksum
```