

Lab 8

Moshe Weiss

11:59PM April 7, 2019

Load the `ggplot2` library and its dataset called `mpg`. Print out a summary of the dataset using `summary` and `str`.

```
pacman::p_load(ggplot2)
```

```
data(mpg)
```

```
mpg$drv = factor(mpg$drv)
```

```
mpg$manufacturer = factor(mpg$manufacturer)
```

```
mpg$model = factor(mpg$model)
```

```
mpg$fl = factor(mpg$fl)
```

```
mpg$class = factor(mpg$class)
```

```
mpg$cyl = factor(mpg$cyl)
```

```
summary(mpg)
```

```
##      manufacturer      model      displ      year
## dodge      :37  caravan 2wd      : 11  Min.   :1.600  Min.   :1999
## toyota      :34  ram 1500 pickup 4wd: 10  1st Qu.:2.400  1st Qu.:1999
## volkswagen:27  civic      : 9  Median :3.300  Median :2004
## ford        :25  dakota pickup 4wd : 9  Mean    :3.472  Mean    :2004
## chevrolet   :19  jetta      : 9  3rd Qu.:4.600  3rd Qu.:2008
## audi        :18  mustang     : 9  Max.    :7.000  Max.    :2008
## (Other)     :74  (Other)      :177
## cyl      trans      drv      cty      hwy      fl
## 4:81  Length:234      4:103  Min.   : 9.00  Min.   :12.00  c: 1
## 5: 4   Class :character f:106  1st Qu.:14.00  1st Qu.:18.00  d: 5
## 6:79  Mode  :character  r: 25  Median :17.00  Median :24.00  e: 8
## 8:70      Mean :16.86  Mean    :23.44  p: 52
##      3rd Qu.:19.00  3rd Qu.:27.00  r:168
##      Max.    :35.00  Max.    :44.00
##
##      class
## 2seater   : 5
## compact   :47
## midsize   :41
## minivan   :11
## pickup    :33
## subcompact:35
## suv       :62
```

```
?mpg
```

```
str(mpg)
```

```
## Classes 'tbl_df', 'tbl' and 'data.frame': 234 obs. of 11 variables:
## $ manufacturer: Factor w/ 15 levels "audi","chevrolet",...: 1 1 1 1 1 1 1 1 1 ...
## $ model       : Factor w/ 38 levels "4runner 4wd",...: 2 2 2 2 2 2 3 3 3 ...
## $ displ      : num 1.8 1.8 2 2 2.8 2.8 3.1 1.8 1.8 2 ...
## $ year       : int 1999 1999 2008 2008 2008 1999 1999 2008 1999 2008 ...
## $ cyl        : Factor w/ 4 levels "4","5","6","8": 1 1 1 1 3 3 3 1 1 1 ...
## $ trans      : chr "auto(15)" "manual(m5)" "manual(m6)" "auto(av)" ...
```


```
## $ drv      : Factor w/ 3 levels "4","f","r": 2 2 2 2 2 2 2 1 1 1 ...
## $ cty      : int   18 21 20 21 16 18 18 18 16 20 ...
## $ hwy      : int   29 29 31 30 26 26 27 26 25 28 ...
## $ fl       : Factor w/ 5 levels "c","d","e","p",...: 4 4 4 4 4 4 4 4 4 4 ...
## $ class    : Factor w/ 7 levels "2seater","compact",...: 2 2 2 2 2 2 2 2 2 2 ...
```

Visualize a histogram then a density estimate of the `displ` variable, the engine displacement. Use `labs` to create a title, subtitle, caption and x-label via `x` and y-label via `y`. Do this for every single illustration in this lab.

```
ggplot(mpg) +
  aes(displ) +
  geom_histogram() +
  labs(title = "Engine Displacement Histogram" , subtitle = "", x = "Displacement (L)", caption = "Source
```

```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```


Engine Displacement Histogram



Source: EPA 2008 Fuel Economy Dataset

```
ggplot(mpg) +
  aes(displ) +
  geom_density(fill = "blue", alpha = 0.2, col = "white") +
  labs(title = "Engine Displacement Density" , subtitle = "", x = "Displacement (L)", caption = "Source
```


Engine Displacement Density



Source: EPA 2008 Fuel Economy Dataset

Visualize a histogram the `displ` variable, but then fill the color of the bar by the `class` of the car. You will have to pass `class` in as the `fill` in the aesthetic of the histogram.


```
ggplot(mpg) +  
  aes(displ) +  
  geom_histogram(aes(fill = class)) +  
  labs(title = "Engine Displacement Histogram" , subtitle = "Colored by Vehicle Type", x = "Displacement")  
  
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```



Source: EPA 2008 Fuel Economy Dataset

Visualize overlapping densities of `cty` (city miles per gallon) and `hwy` (highway miles per gallon) using two colors with an alpha blend.

```
ggplot(mpg) +
  geom_density(aes(cty), fill = "red", col = "white", alpha = 0.2) +
  geom_density(aes(hwy), fill = "blue", col = "white", alpha = 0.2) +
  xlim(5, 50) +
  labs(title = "Fuel Efficiency Density", subtitle = "City in Red and Highway in Blue", x = "miles per gallon")
```




Plot `cty` (city miles per gallon) vs `hwy` (highway miles per gallon) and draw a best fit line with a confidence region of that line.

```
ggplot(mpg, aes(x = cty, y = hwy)) +  
  geom_point() +  
  geom_smooth(method = "lm") +  
  labs(title = "City vs Highway Fuel Efficiency", subtitle = "With best fit line and confidence interval")
```

City vs Highway Fuel Efficiency

With best fit line and confidence interval




Source: EPA 2008 Fuel Economy Dataset

Plot `cty` (city miles per gallon) vs `hwy` (highway miles per gallon) and draw a best fit non-parametric functional relationship with a confidence region of that relationship.

```
ggplot(mpg, aes(x = cty, y = hwy)) +  
  geom_point() +  
  geom_smooth() +  
  labs(title = "City vs Highway Fuel Efficiency", subtitle = "With best fit line and confidence interval")  
  
## `geom_smooth()` using method = 'loess' and formula 'y ~ x'
```

City vs Highway Fuel Efficiency


With best fit line and confidence interval



Source: EPA 2008 Fuel Economy Dataset

Plot `cty` (city miles per gallon) vs `hwy` (highway miles per gallon) and then try to visualize *as many other variables* as you can visualize effectively on the same plot. Try text, color, size, shape, etc.

```
ggplot(mpg, aes(x = cty, y = hwy)) +  
  geom_point(aes(col = drv, shape = cyl, size = displ)) +  
  geom_text(aes(label = fl)) +  
  labs(title = "City vs Highway Fuel Efficiency", x = "City (mpg)", y = "Highway (mpg)", caption = "Sou
```




Convert `cyl` to an ordinal factor. Then use the package `dplyr` to retain only cars with 4, 6, 8 cylinders in the dataset. Then make a canonical illustration of `cty` by `cyl`.

```
pacman::p_load(dplyr)

mpg %<>%
  mutate(cyl = factor(cyl, ordered = TRUE)) %>%
  filter(cyl %in% c(4, 6, 8))
ggplot(mpg, aes(x = cyl, y = cty)) +
  geom_boxplot() +
  labs(title = "City Fuel Efficiency by Number of Cylinders", x = "Number of Cylinders", y = "City (mpg)")
```


City Fuel Efficiency by Number of Cylinders



Source: EPA 2008 Fuel Economy Dataset

Load the `stringr` library. Use the `str_detect` function in this library to rewrite the `trans` variable in the data frame to be just “manual” or “automatic”.


```
pacman::p_load(stringr)
mpg$trans = ifelse(str_detect(mpg$trans, "^a"), 'automatic', 'manual')
mpg$trans
```

```
## [1] "automatic" "manual"    "manual"    "automatic" "automatic"
## [6] "manual"    "automatic" "manual"    "automatic" "manual"
## [11] "automatic" "automatic" "manual"    "automatic" "manual"
## [16] "automatic" "automatic" "automatic" "automatic" "automatic"
## [21] "automatic" "automatic" "automatic" "manual"    "automatic"
## [26] "manual"    "automatic" "manual"    "automatic" "automatic"
## [31] "automatic" "automatic" "automatic" "automatic" "automatic"
## [36] "automatic" "automatic" "automatic" "automatic" "automatic"
## [41] "automatic" "automatic" "automatic" "automatic" "automatic"
## [46] "automatic" "automatic" "automatic" "manual"    "automatic"
## [51] "automatic" "manual"    "automatic" "automatic" "automatic"
## [56] "manual"    "automatic" "automatic" "automatic" "automatic"
## [61] "automatic" "automatic" "automatic" "automatic" "manual"
## [66] "automatic" "automatic" "automatic" "manual"    "manual"
## [71] "automatic" "manual"    "automatic" "automatic" "automatic"
## [76] "automatic" "automatic" "automatic" "manual"    "automatic"
## [81] "automatic" "automatic" "automatic" "automatic" "manual"
## [86] "manual"    "automatic" "automatic" "automatic" "automatic"
## [91] "manual"    "automatic" "manual"    "automatic" "automatic"
## [96] "manual"    "manual"    "automatic" "manual"    "manual"
## [101] "automatic" "manual"    "manual"    "automatic" "manual"
```

```
## [106] "automatic" "automatic" "manual" "automatic" "manual"
## [111] "automatic" "manual" "automatic" "manual" "automatic"
## [116] "automatic" "manual" "manual" "automatic" "automatic"
## [121] "manual" "manual" "automatic" "automatic" "automatic"
## [126] "automatic" "automatic" "automatic" "automatic" "automatic"
## [131] "automatic" "automatic" "automatic" "automatic" "automatic"
## [136] "automatic" "automatic" "automatic" "automatic" "automatic"
## [141] "automatic" "manual" "automatic" "automatic" "manual"
## [146] "manual" "automatic" "automatic" "manual" "automatic"
## [151] "automatic" "manual" "automatic" "automatic" "automatic"
## [156] "automatic" "automatic" "automatic" "automatic" "manual"
## [161] "automatic" "manual" "manual" "automatic" "automatic"
## [166] "automatic" "manual" "manual" "automatic" "automatic"
## [171] "automatic" "manual" "manual" "manual" "automatic"
## [176] "automatic" "manual" "automatic" "automatic" "manual"
## [181] "automatic" "manual" "automatic" "automatic" "manual"
## [186] "automatic" "automatic" "manual" "manual" "automatic"
## [191] "automatic" "manual" "automatic" "automatic" "automatic"
## [196] "manual" "manual" "automatic" "automatic" "automatic"
## [201] "manual" "automatic" "manual" "manual" "automatic"
## [206] "manual" "automatic" "manual" "automatic" "manual"
## [211] "automatic" "manual" "manual" "manual" "automatic"
## [216] "automatic" "manual" "automatic" "manual" "manual"
## [221] "automatic" "manual" "automatic" "manual" "automatic"
## [226] "automatic" "manual" "automatic" "manual" "automatic"
```


Now visualize `cty` by `trans` via two overlapping alpha-blended densities.

```
ggplot(mapping = aes(cty)) +
  geom_density(data = mpg %>% filter(trans == "automatic"), fill = "blue", col = "white", alpha = 0.2) +
  geom_density(data = mpg %>% filter(trans == "manual"), fill = "red", col = "white", alpha = 0.2)
```




Now visualize cty by trans via a box and whisker plot.

```
ggplot(mpg, aes(x = cty, y = trans)) +  
  geom_boxplot()
```




Now visualize cty by drv by trans via two box and whisker plots horizontally laid out.

```
ggplot(mpg, aes(x = drv, y = cty)) +  
  geom_boxplot()
```




```
ggplot(mpg, aes(x = drv, y = trans)) +  
  geom_boxplot()
```




Now visualize cty by class via a violin plot. Look at the ggplot cheatsheet!

```
ggplot(mpg, aes(x = class, y = cty)) +  
  geom_violin(fill = "brown", alpha = 0.4) +  
  labs(title = "City Fuel Efficiency by Vehicle Type", x = "Class", y = "City (mpg)", caption = "Source")
```




Make a pie chart of class.

```
pie(table(mpg$class))
```



Visualize trans vs class. Look at the ggplot cheat-sheet!

```
ggplot(mpg, aes(x = class, y = trans)) +  
  geom_point() +  
  labs(title = "Transmission by Vehicle Type", x = "Class", y = "Trans (Automatic or Manual", caption =
```




Source: EPA 2008 Fuel Economy Dataset

Using the package `ggExtra`'s `ggMarginal` function, look at the `hwy` by `year` and plot the marginal density on both the x and y axes.


```
pacman::p_load(ggExtra)

p2 = ggplot(mpg, aes(x = hwy, y = year)) +
  geom_count()

ggMarginal(p2, type = "density")
```

p2




Using the package `ggcorrplot`'s `ggcorrplot` function, look at the correlations for all variables in this dataset that are legal in a correlogram. Use `dplyr` to `select_if` the variable is appropriate.

```
pacman::p_load(ggcorrplot, dplyr)
supply(mpg, class) == "ordered" "factor"
```


```
## manufacturer      model      displ      year      cyl
##      FALSE      FALSE      FALSE      FALSE      FALSE
##      trans        drv        cty        hwy        fl
##      FALSE      FALSE      FALSE      FALSE      FALSE
##      class
##      FALSE
```

```
mpg %>%
  mutate(cyl = as.numeric(as.character(cyl))) %>%
  select_if(is.numeric) %>%
  ggcorrplot()
```




Use the `stat_ecdf` function to plot the estimated cumulative distribution of 'cyl'.

```
ggplot(mpg, aes(cty)) +
  stat_ecdf()
```



Create a data generating process where x is uniform between 0 and 10 and y is x^2 plus $N(0,1)$ noise. Plot $n = 200$ points and then plot the quadratic relationship $y = x^2$ using the function `stat_function`.

```
x = runif(100,0,10)
y = x^2 + rnorm(200)
Xy = cbind(x,y)
Xy = data.frame(Xy)
ggplot(Xy, aes(x,y)) +
  geom_point() +
  stat_function(fun = function(x){y=x^2}, col = "green")
```



We now move to Rcpp. Load the library.

```
library(Rcpp)
```

Write an R function `is_odd` and a C++ function `is_odd_cpp` that evaluates if a number is odd and returns true if so.

```
is_odd = function(n){
  n %% 2 == 1
}
cppFunction('
  bool is_odd_cpp(int n){
    return n % 2 == 1;
  }
')
```

Using `'system.time'`, run both functions 1,000,000 times on the numbers 1, 2, ..., 1000000. Who is faster and by how much?

```
system.time(
  for(i in 1:1e6){
    is_odd(i)
  }
)
```

```
##      user  system elapsed
##    0.509   0.001   0.509
```

```
system.time(
  for(i in 1:1e6){
```

```

    is_odd_cpp(i)
  }
)

```

```

##      user   system elapsed
##  1.713    0.020    1.733

```

Write an R function `fun` and a C++ function `fun_cpp` that takes a natural number n returns n if n is 0 or 1 otherwise the result of the function on $n - 1$ and $n - 2$. This is the function that returns the n th Fibonacci number.

```

fun = function(n){
  if(n==0 | n==1) n
  fun(n-2) + fun(n-1)
}

cppFunction('
  int fun_cpp(int n){
    if(n==0 || n==1) return n;
    return fun_cpp(n-2) + fun_cpp(n-1);
  }
')

```

Using `'system.time'`, run both functions on the numbers 1, 2, ..., 100. Who is faster and by how much?

```

#system.time(
#  for(i in 1:100){
#    fun(i)
#  }
#)
#system.time(
#  for(i in 1:100){
#    fun_cpp(i)
#  }
#)
#this breaks

```

Write an R function `logs` and a C++ function `logs_cpp` that takes a natural number n and returns an array of $\ln(1), \ln(2), \dots, \ln(n)$.

```

logs = function(n){
  array(log(1:n), n)
}

cppFunction('
  NumericVector logs_cpp(int n){
    NumericVector v(n);
    for(int i=1; i<=n;i++){
      v[i] = log(i);
    }
    return v;
  }
')

```

Using `'system.time'`, run both functions on the numbers 1, 2, ..., 1000000. Who is faster and by how much?

```

#system.time(
#  for(i in 1:1e6){

```

```
#   logs(i)
# }
#)
#system.time(
#   for(i in 1:1e6){
#     logs_cpp(i)
#   }
#)
```

Write an R function `max_distances` and a C++ function `max_distances_cpp` that takes an $n \times p$ matrix X and returns an $n \times n$ matrix called D of NA's where the upper triangular portion above the diagonal is the max distances between the elements of the i, j th rows of X .

```
max_distances = function(X){
  n = nrow(X)
  p = ncol(X)
  D = matrix(NA, nrow = n, ncol = n)
  for(i_1 in 1:(n - 1)){
    for(i_2 in (i_1 + 1):n){
      sqd_diff = 0
      for(j in 1:p){
        sqd_diff = sqd_diff + (X[i_1, j] - X[i_2, j])^2
      }
      D[i_1, i_2] = sqrt(sqd_diff)
    }
  }
  D
}

cppFunction('
NumericMatrix max_distances_cpp(NumericMatrix X) {
  int n = X.nrow();
  int p = X.ncol();
  NumericMatrix D(n, n);
  std::fill(D.begin(), D.end(), NA_REAL);

  for (int i_1 = 0; i_1 < (n - 1); i_1++){
    for (int i_2 = i_1 + 1; i_2 < n; i_2++){
      int sqd_diff = 0;
      for (int j = 0; j < p; j++){
        sqd_diff += pow(X(i_1, j) - X(i_2, j), 2); //by default the cmath library in std is loaded
      }
      D(i_1, i_2) = sqrt(sqd_diff); //by default the cmath library in std is loaded
    }
  }
  return D;
}')
```

Create a matrix X of $n = 1000$ and $p = 20$ filled with iid $N(0, 1)$ realizations. Using 'system.time', calculate D using both functions. Who is faster and by how much?

```
n = 1000
p = 20
m = matrix(rnorm(n*p), nrow = n, ncol = p)
```

```
system.time(  
  max_distances(m)  
)
```

```
##      user  system elapsed  
##    1.133    0.024    1.157
```

```
system.time(  
  max_distances_cpp(m)  
)
```

```
##      user  system elapsed  
##    0.040    0.004    0.044
```