

Static Code Analysis With JavaParser

(A case study of the Visitors design pattern)

Lecture 11

Dr. Graham McDonald

graham.mcdonald@glasgow.ac.uk

Learning Outcome

- Learn how to build a system from reusable publicly available frameworks by studying its documentation.
- Understand the architecture of static analysis systems
- Understand the relationship between program code and its abstract syntax tree
- Demonstrate how static analysis can be used as a software engineering tool


What is Static Analysis?

Systematic examination of an **abstraction** of program **state space**

Don't track everything
(That's normal
interpretation)

Ensure everything is checked
in the same way

What is Static Analysis?



Building a model of the program

- Lexical analysis
- Parsing
- **Abstract syntax**
- Semantic Analysis
- Tracking control flow
- Tracking Dataflow
- Taint propagation

Abstract Syntax Tree (AST)

- Intermediate program representation which depicts source code as a tree
 - Defines a tree - preserves program hierarchy
 - Node types defined by class hierarchy
 - Nodes can be associated with properties
 - Generated by parser

Building a Java AST

- Popular APIs for generating AST from source code:
 - Eclipse JDT (<https://www.eclipse.org/jdt/>)
 - Java Parser (<http://javaparser.org>)

Getting Started with Java Parser

- Quickest way is to install JavaParser:
 - Create a simple Maven project in Eclipse
 - Add the following dependency to the POM.xml file

```
1 <dependency>
2   <groupId>com.github.javaparser</groupId>
3   <artifactId>javaparser-core</artifactId>
4   <version>3.12.0</version>
5 </dependency>
```

<https://javaparser.org/getting-started.html>


Java Parser API

- **JavaParser** class is what produces the AST from the code
- **CompilationUnit** is the root of the AST
- **Visitors** are classes which are useful to find specific parts of the AST

Java Doc (javaparser-core 3.12.0 API):


<http://www.javadoc.io/doc/com.github.javaparser/javaparser-core/3.12.0>

AST




- The root is a **CompilationUnit** representing the whole file
- nodes directly connected to the root are all the top elements of a file (i.e package, import and class declarations)
- From a single class declarations multiple nodes, representing the fields or the methods of the class can be reached.

AST



Drilling down the MethodDeclaration, we can see the name, the return type and the parameter(s) for the method along with a BlockStmt, which again can be further elaborated.

AST




- A syntax tree gets complex quickly from small line of code.
- Each node is visitable

Visitable Nodes

1 AnnotationDeclaration	25 DoStmt	49 MarkerAnnotationExpr	73 TryStmt
2 AnnotationMemberDeclaration	26 DoubleLiteralExpr	50 MemberValuePair	74 TypeExpr
3 ArrayAccessExpr	27 EmptyMemberDeclarationclass	51 MethodCallExpr	75 TypeParameter
4 ArrayCreationExpr	28 EnclosedExpr	52 MethodDeclaration	76 UnaryExpr
5 ArrayCreationLevel	29 EnumConstantDeclaration	53 MethodReferenceExpr	77 UnionType
6 ArrayInitializerExpr	30 EnumDeclaration	54 Name	78 UnknownType
7 ArrayType	31 ExplicitConstructorInvocationStmt	55 NameExpr	79 VariableDeclarationExpr
8 AssertStmt	32 ExpressionStmt	56 NodeList	80 VariableDeclarator
9 AssignExpr	33 FieldAccessExpr	57 NormalAnnotationExpr	81 VoidType
10 BinaryExpr	34 FieldDeclaration	58 NullLiteralExpr	82 WhileStmt
11 BlockComment	35 ForeachStmt	59 ObjectCreationExpr	83 WildcardType
12 BlockStmt	36 ForStmt	60 PackageDeclaration	
13 BooleanLiteralExpr	37 IfStmt	61 Parameter	
14 BreakStmt	38 ImportDeclaration	62 PrimitiveType	
15 CastExpr	39 InitializerDeclaration	63 ReturnStmt	
16 CatchClause	40 InstanceOfExpr	64 SimpleName	
17 CharLiteralExpr	41 IntegerLiteralExpr	65 SingleMemberAnnotationExpr	
18 ClassExpr	42 IntersectionType	66 StringLiteralExpr	
19 ClassOrInterfaceDeclaration	43 JavadocComment	67 SuperExpr	
20 ClassOrInterfaceType	44 LabeledStmt	68 SwitchEntryStmt	
21 CompilationUnit	45 LambdaExpr	69 SwitchStmt	
22 ConditionalExpr	46 LineComment	70 SynchronizedStmt	
23 ConstructorDeclaration	47 LocalClassDeclarationStmt	71 ThisExpr	
24 ContinueStmt	48 LongLiteralExpr	72 ThrowStmt	

AST:

Applying the Visitors Design Pattern




This is the Visitors Design Pattern

Visitor Class

How JavaParser applies the Visitor Design Pattern


- Architecture used when the aim is **not** to modify the underlying AST



Visitor Class

How JavaParser applies the Visitor Design Pattern

- Architecture used when the aim is **not** to modify the underlying AST



Visitor Class

How JavaParser applies the Visitor Design Pattern

- Architecture used when the aim is **not** to modify the underlying AST

```
34 /**
35  * A visitor that returns nothing, and has a default implementation for all its visit
36  * methods that simply visit their children in an unspecified order.
37  *
38  * @author Julio Vilmar Gesser
39  */
40 public abstract class VoidVisitorAdapter<A> implements VoidVisitor<A> {

    @Override
    @Generated("com.github.javaparser.generator.core.visitor.VoidVisitorAdapterGenerator")
    public void visit(final AnnotationDeclaration n, final A arg) {
        n.getMembers().forEach(p -> p.accept(this, arg));
        n.getName().accept(this, arg);
        n.getAnnotations().forEach(p -> p.accept(this, arg));
        n.getComment().ifPresent(l -> l.accept(this, arg));
    }

    @Override
    @Generated("com.github.javaparser.generator.core.visitor.VoidVisitorAdapterGenerator")
    public void visit(final AnnotationMemberDeclaration n, final A arg) {
        n.getDefaultValue().ifPresent(l -> l.accept(this, arg));
        n.getName().accept(this, arg);
        n.getType().accept(this, arg);
        n.getAnnotations().forEach(p -> p.accept(this, arg));
        n.getComment().ifPresent(l -> l.accept(this, arg));
    }
}
```

Also observe that the transversal of the AST structure is executed via the Visitor

Observe that the visit method takes two parameters

<https://github.com/javaparser/javaparser/blob/master/javaparser-core/src/main/java/com/github/javaparser/ast/visitor/VoidVisitorAdapter.java>

Exercise 1:

- Build a static code analyser that reports all comments in a source code showing its line number, text and whether it is an orphan comment or not

```
import java.time.LocalDateTime;

// Orphaned 1
//Attributed 1
public class TimePrinterWithComments {

    //Orphaned 2

    //Attributed 2
    public static void main(String args[]) {
        System.out.print(LocalDateTime.now());
    }
    //orphaned 3
}
```

Example of source code with orphaned and attributed comments

Solution

- Implement a CommentReport class as the container for the properties of comments of interest

```
public class CommentReport {
    private String type;
    private String text;
    private int lineNumber;
    private boolean isOrphan;

    public CommentReport(String type, String text,
                        int lineNumber, boolean isOrphan) {
        this.type = type;
        this.text = text;
        this.lineNumber = lineNumber;
        this.isOrphan = isOrphan;
    }

    @Override
    public String toString() {
        return lineNumber + "|" + type + "|" + isOrphan
            + "|" + text.replaceAll("\n", "").trim();
    }
}
```

Solution

- Create a collection of CommentReport items, by mapping the fields of interest from the JavaParser Comment type.

```
public class CommentsAnalyser {

    private static final String FILE_PATH = "../TimePrinterWithComments.java";

    public static void main(String args []) {
        try {
            CompilationUnit cu = JavaParser.parse(new FileInputStream(FILE_PATH));
            List<Comment> comments = cu.getAllContainedComments();

            comments.forEach(com -> {
                CommentReport cer = new CommentReport(com.getClass().getSimpleName(),
                    com.getContent(),
                    com.getRange().get().begin.line,
                    !com.getCommentedNode().isPresent());

                System.out.println(cer);
            });
        } catch (FileNotFoundException e) {
            e.printStackTrace();
        }
    }
}
```

Output

```
5|LineComment|true|Orphaned 1
6|LineComment|false|Attributed 1
9|LineComment|true|Orphaned 2
14|LineComment|true|Orphaned 3
10|LineComment|false|Attributed 2
```

Exercise 2:

- Build a static code analyser with a Visitor that examines all the methods in a source code and prints their name and line length to the console.

```
public class Calculator {  
    public Calculator(){}  
  
    public int add(int a, int b) {  
        return a + b;  
    }  
    ...  
    public static void main(String[] args) {  
        Calculator myCalculator = new Calculator();  
        System.out.println(myCalculator.add(5, 7));  
        System.out.println(myCalculator.subtract(45, 11));  
    }  
}
```

Solution 1

Visitor without state:

- Next, we defined the overriding implementation of visit. We're interested in method declarations so the first argument is of the type MethodDeclaration. The second argument is the VoidVisitorAdaptor's parameterised type.

```
public class MethodAnalyser1 extends VoidVisitorAdapter <Void>{  
    @Override  
    public void visit(MethodDeclaration md, Void arg) {  
        super.visit(md, arg);  
  
        String methodName = md.getName().asString();  
        int begin = md.getRange().get().begin.line;  
        int end = md.getRange().get().end.line;  
        int length = end - begin;  
  
        System.out.println(methodName+"|"+length);  
    }  
}
```

Solution 1

Visitor without state:

- Define a class that extends **VoidVisitorAdaptor**. This class also takes a type parameter, which is passed as argument into the visit method. But we make the parameter type void since the feature is not used for this solution

```
public class MethodAnalyser1 extends VoidVisitorAdapter <Void>{  
  
}
```

Solution 1

Visitor without state:

- Instantiate the defined class and provide it with a ComputationUnit to operate on.

```
public class MethodMetricsDriver1 {  
    private static final String FILE_PATH = "../src/main/java";  
  
    public static void main(String args []) {  
        try {  
            CompilationUnit cu = JavaParser.parse(new FileInputStream(FILE_PATH));  
  
            VoidVisitor<?> methodVisitor = new MethodAnalyser1();  
            methodVisitor.visit(cu, null);  
        }  
        catch (FileNotFoundException e) {  
            e.printStackTrace();  
        }  
    }  
}
```

Output

```
add|2  
subtract|2  
multiply|2  
divide|7  
modulo|7  
main|4
```

- Static analysis is an important software engineering tool
- One way to design a static analysis system is to use an Abstract Syntax Tree (AST) to discover interesting properties in program code.
- JavaParser is a publicly available framework for generating and analysing ASTs