

## Laboratory Sheet 1 – Sample Solutions

### Part 1

- a) Following the pseudocode for INSERTION-SORT introduced in Lecture 1 (slide 13), implement the InsertionSort algorithm in Java.

```
public class InsertionSort{

    public static void sort(int a[]){
        int n = a.length;
        for (int j = 1; j < n; j++){
            int key = a[j];
            int i = j-1;
            while ((i >= 0) && (a[i] > key)){
                a[i+1] = a[i];
                i--;
            }
            a[i+1] = key;
        }
    }
}
```

- b) Write a test program, TestSortingAlgorithms, to check that your implementation is correct, namely that the output array is in *ascending order*.

```
public class TestSortingAlgorithms{

    public static boolean isSorted(int a[]){
        int n = a.length;
        for (int i = 0; i < n-1; i++){
            if (a[i] > a[i+1]){
                return false;
            }
        }
        return true;
    }
}
```

- c) What is the complexity of TestSortingAlgorithms?

$O(n)$

- d) Implement InsertionSortDescending to sort arrays in *descending order*.

```
public class InsertionSortDescending {

    public static void sort(int a[]) {
        int n = a.length;
        for (int j = 1; j < n; j++) {
            int key = a[j];
            int i = j-1;
            while ((i >= 0) && (a[i] < key)) {
                a[i+1] = a[i];
                i--;
            }
            a[i+1] = key;
        }
    }
}
```

**Part 2** SELECTION-SORT is a sorting algorithm informally described as follows:

Input: an array A of integers (with indices between 0 and n-1)

Output: a permutation of the input such that  $A[0] \leq A[1] \leq \dots \leq A[n-1]$

Algorithm: Array A is imaginary divided into two parts - sorted one and unsorted one. At the beginning, the sorted part is empty, while unsorted one contains the whole array. The algorithm sorts A by repeatedly picking the minimum element from the unsorted subarray and moving it to the end of the sorted subarray.

- a) Write pseudocode for SELECTION-SORT corresponding to the natural language description above.

```
SELECTION-SORT(A)
  for i = 0 to n-2
    index := i
    for j = i+1 to n-1
      if A[j] < A[index] then
        index := j
    min := A[index]
    A[index] := A[i]
    A[i] := min
```

- b) What is the running time of SELECTION-SORT in the worst case? And in the best case? How does it compare to INSERTION-SORT?

SELECTION-SORT has quadratic running time in both cases while INSERTION-SORT has linear running time in the best case.

- c) Is it a stable sorting algorithm?

It is not stable (show that the relative order of elements with equal keys is changed).

- d) Does it sort in-place?

Yes, as the memory requirement is  $O(1)$ .

- e) Implement the SelectionSort algorithm in Java following your pseudocode for SELECTION-SORT. Use TestSortingAlgorithms to check that your implementation is correct.

```
public class SelectionSort{

    public static void sort(int a[]){
        int n = a.length;
        for (int i = 0; i < n - 1; i++){
            int index = i;
            //find minimum
            for (int j = i + 1; j < n; j++){
                if (a[j] < a[index]){
                    index = j;
                }
            }
            //swap
            int min = a[index];
            a[index] = a[i];
            a[i] = min;
        }
    }
}
```

```
    }  
}
```

**Part 3** You have been provided with a suite of test text files `int10.txt`, `int50.txt`, `int100.txt` and `int1000.txt` where each `int $n$ .txt` contains  $n$  integers in randomly sorted order. Write a program `TimeSortingAlgorithms.java` to generate timing runs for `InsertionSort` and `SelectionSort` outputting the time taken to sort (an array read from) each of the text files above. Example output might be something like:

```
-----  
Time taken to sort int10.txt:  
  
InsertionSort: 310 milliseconds  
SelectionSort: 530 milliseconds  
  
-----  
Time taken to sort int50.txt:  
(etc.)
```

Only a snippet of the timing method. Method `scanner.nextInt()` or similar can be used to implement `readArray`.

```
System.out.print("\nInsertionSort: ");  
readArray(arr, longName);  
time1=System.currentTimeMillis();  
InsertionSort.sort(arr);  
time2=System.currentTimeMillis();  
timeTaken=time2-time1;  
System.out.print(timeTaken + " milliseconds\n");
```