

# Package ‘marklpp’

September 18, 2023

**Type** Functions for marked point patterns on linear networks.

**Title** Functions for marked point patterns on linear networks.

**Version** 0.1.3

**Author** `c(person("Mehdi", "Moradi", email = "m2.moradi@yahoo.com",  
role = c("aut", "cre")),  
person("Matthias", "Eckardt", role = "ctb"))`

**Maintainer** Mehdi Moradi <m2.moradi@yahoo.com>

**Description** Functions for marked point patterns on linear networks.

**Depends** R (>= 4.2.0), spatstat.linnet

**Imports** stats

**License** GPL (>= 2)

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.2.3

## R topics documented:

<code>fmarkcorr.linnet</code> . . . . .	1
<code>linearinhommarkk.lpp</code> . . . . .	3
<code>linearmarkk.lpp</code> . . . . .	4
<code>markcorr.lpp</code> . . . . .	4

<b>Index</b>	6
--------------	---

---

<code>fmarkcorr.linnet</code>	<i>Functional mark correlation function for point patterns over a linear network</i>
-------------------------------	--

---

## Description

Functional mark correlation function for point patterns over a linear network

**Usage**

```
fmarkcorr.linnet(
  X,
  r,
  normalise = FALSE,
  f = function(m1, m2) {
    m1 * m2
  },
  ftype = c("corr", "vario", "rcorr", "schlather", "breisgart"),
  method = c("density", "loess"),
  ...
)
```

**Arguments**

X	an object of class lpp
r	Optional. Numeric vector. The values of the argument r at which the mark correlation function should be evaluated.
normalise	If normalise=FALSE, compute only the numerator of the expression for the mark correlation.
f	Optional. Test function f used in the definition of the mark correlation function. An R function with at least two arguments. There is a sensible default.
ftype	type of test function used in argument f. Currently any selection of the options "corr","vario","rcorr","schlather","equ","breisgart"
method	type of smoothing, either density or loess.

**Value**

a numeric vector.

**Author(s)**

Mehdi Moradi <m2.moradi@yahoo.com> and Matthias Eckardt

**References**

Eckardt, M., Mateu, J., and Moradi, M. (2023) Point processes on linear networks with function-valued marks.

**Examples**

```
L <- spiders$domain
X <- runiflpp(150,L=L)
m <- t(replicate(150,runif(513)))
marks(X) <- as.data.frame(m)
Fcor <- fmarkcorr.linnet(X,r, ftype = "corr", method = "density", normalise = TRUE)
plot(Fcor$r,Fcor$gw,type = "l")
```

---

linearinhommarkk.lpp	<i>Mark-Weighted inhomogeneous K Function for point patterns over a linear network</i>
----------------------	--

---

## Description

Mark-Weighted inhomogeneous K Function for point patterns over a linear network

## Usage

```
linearinhommarkk.lpp(X, r = r, lambda = lambda, normalize = FALSE, ...)
```

## Arguments

X	an object of class lpp
r	Optional. Numeric vector. The values of the argument r at which the mark correlation function should be evaluated.
lambda	Intensity values at data points.
normalize	Logical.

## Value

a numeric vector.

## Author(s)

Mehdi Moradi <m2.moradi@yahoo.com> and Matthias Eckardt

## References

Eckardt, M., and Moradi, M. (2023) Marked point processes on linear networks.

## Examples

```
X <- rpoislpp(10,simplenet)
r <- seq(0,boundingradius(simplenet),length.out=513)
dx <- densityQuick.lpp(X,at = "points")
linearinhommarkk.lpp(X,r=r,lambda=dx)
```

---

linearmarkk.lpp	<i>Mark-Weighted homogeneous K Function for point patterns over a linear network</i>
-----------------	--

---

## Description

Mark-Weighted homogeneous K Function for point patterns over a linear network

## Usage

```
linearmarkk.lpp(X, r = r)
```

## Arguments

X	an object of class lpp
r	Optional. Numeric vector. The values of the argument r at which the mark correlation function should be evaluated.

## Value

a numeric vector.

## Author(s)

Mehdi Moradi <m2.moradi@yahoo.com> and Matthias Eckardt

## References

Eckardt, M., and Moradi, M. (2023) Marked point processes on linear networks.

## Examples

```
X <- rpoislpp(10,simplenet)
r <- seq(0,boundingradius(simplenet),length.out=513)
linearmarkk.lpp(X,r=r)
```

---

markcorr.lpp	<i>Mark correlation function for point patterns over a linear network</i>
--------------	---

---

## Description

Mark correlation function for point patterns over a linear network

**Usage**

```
markcorr.lpp(
  X,
  r,
  normalise = TRUE,
  f = function(m1, m2) {
    m1 * m2
  },
  ftype = c("corr", "vario", "rcorr", "schlather", "equ", "breisgart"),
  method = c("density", "loess"),
  ...
)
```

**Arguments**

X	an object of class lpp
r	Optional. Numeric vector. The values of the argument r at which the mark correlation function should be evaluated.
normalise	If normalise=FALSE, compute only the numerator of the expression for the mark correlation.
f	Optional. Test function f used in the definition of the mark correlation function. An R function with at least two arguments. There is a sensible default.
ftype	type of test function used in argument f. Currently any selection of the options "corr","vario","rcorr","schlather","equ","breisgart"
method	type of smoothing, either density or loess.

**Value**

a numeric vector.

**Author(s)**

Mehdi Moradi <m2.moradi@yahoo.com> and Matthias Eckardt

**References**

Eckardt, M., and Moradi, M. (2023) Marked point processes on linear networks.

**Examples**

```
X <- rpoislpp(10,simplenet)
r <- seq(0,boundingradius(simplenet),length.out=513)
markcorr.lpp(X,r=r,ftype = "equ",f=function(m1,m2){m1==m2})
```

# Index

fmarkcorr.linnet, [1](#)

linearinhommarkk.lpp, [3](#)

linearmarkk.lpp, [4](#)

markcorr.lpp, [4](#)