

ISE 2: Modern Full-Stack Development [MERN Authentication Project]

Name: Prajita More

Roll.no: 74

Div: A

CODE:

FRONTEND:

APP.js

```
import React, { useState } from 'react';

import { Form, Input, Button, Card, Typography, message, Tabs } from 'antd';

import { UserOutlined, LockOutlined, MailOutlined } from '@ant-design/icons';

import axios from 'axios';

import './App.css'; // We will add a small background tweak here


const { Title, Text } = Typography;


const App = () => {

  const [loading, setLoading] = useState(false);

  const [activeTab, setActiveTab] = useState('1');


  // Handle Form Submission

  const onFinish = async (values) => {

    setLoading(true);

    const isLogin = activeTab === '1';

    const url = isLogin ? 'http://localhost:5000/api/signin' : 'http://localhost:5000/api/signup';

    try {

      const res = await axios.post(url, values);

      message.success(res.data.message || "Operation Successful!");

    } catch (err) {
```

```

        message.error(err.response?.data?.error || "Something went wrong");
    } finally {
        setLoading(false);
    }
};

return (
    <div className="auth-container">
        <Card className="auth-card" hoverable>
            <div style={{ textAlign: 'center', marginBottom: 20 }}>
                <Title level={2}>KIT's IMER</Title>
                <Text type="secondary">MCA Department Auth System</Text>
            </div>

            <Tabs
                activeKey={activeTab}
                onChange={setActiveTab}
                centered
                items={[
                    { label: 'Sign In', key: '1' },
                    { label: 'Sign Up', key: '2' },
                ]}
            />

            <Form name="auth_form" onFinish={onFinish} layout="vertical">
                {activeTab === '2' && (
                    <>
                        <Form.Item name="firstName" rules={[{ required: true, message: 'Please input First Name!'
}}}>

                            <Input prefix={<UserOutlined />} placeholder="First Name" size="large" />
                        </Form.Item>

```

```

    <Form.Item name="lastName" rules={[{ required: true, message: 'Please input Last Name!'
  ]}]>
      <Input prefix={<UserOutlined />} placeholder="Last Name" size="large" />
    </Form.Item>
  </>
})

```

```

    <Form.Item name="email" rules={[{ required: true, type: 'email', message: 'Please input a valid
  Email!' }]}>
      <Input prefix={<MailOutlined />} placeholder="Email Address" size="large" />
    </Form.Item>
  </>

```

```

    <Form.Item name="password" rules={[{ required: true, message: 'Please input Password!' }]}>
      <Input.Password prefix={<LockOutlined />} placeholder="Password" size="large" />
    </Form.Item>
  </>

```

```

    <Form.Item>
      <Button type="primary" htmlType="submit" block size="large" loading={loading}>
        {activeTab === '1' ? 'Login' : 'Register'}
      </Button>
    </Form.Item>
  </Form>
</Card>
</div>

```

```
);
```

```
};
```

```
export default App;
```

BACKEND:

USER.js

```
const mongoose = require('mongoose');

const UserSchema = new mongoose.Schema({
  firstName: { type: String, required: true },
  lastName: { type: String, required: true },
  email: { type: String, required: true, unique: true },
  password: { type: String, required: true }
});

module.exports = mongoose.model('User', UserSchema);
```

SERVER.js

```
const express = require('express');
const mongoose = require('mongoose');
const cors = require('cors');
const bcrypt = require('bcryptjs');
const User = require('./models/User');

const app = express();
app.use(express.json());
app.use(cors());

// Connect to MongoDB (Replace with your local or Atlas URI)
mongoose.connect('mongodb://127.0.0.1:27017/mern_db')
  .then(() => console.log("MongoDB Connected"))
  .catch(err => console.log(err));

// SIGN UP ROUTE
app.post('/api/signup', async (req, res) => {
```

```

try {
  const { firstName, lastName, email, password } = req.body;

  const hashedPassword = await bcrypt.hash(password, 10);

  const newUser = new User({ firstName, lastName, email, password: hashedPassword });

  await newUser.save();

  res.status(201).json({ message: "User Created Successfully" });
} catch (err) {
  res.status(400).json({ error: "Email already exists or invalid data" });
}
});

// SIGN IN ROUTE
app.post('/api/signin', async (req, res) => {
  const { email, password } = req.body;

  const user = await User.findOne({ email });

  if (!user) return res.status(400).json({ error: "User not found" });

  const isMatch = await bcrypt.compare(password, user.password);


  if (!isMatch) return res.status(400).json({ error: "Invalid credentials" });

  res.json({ message: "Login Successful", user: user.firstName });
});


app.listen(5000, () => console.log("Server running on port 5000"));

```



OUTPUT:



A screenshot of a web browser displaying the login page for 'KIT's IMER'. The browser's address bar shows 'http://localhost:3000'. The page has a light blue gradient background. In the center, there is a white card with the title 'KIT's IMER' and subtitle 'MCA Department Auth System'. Below the title are two links: 'Sign In' (underlined) and 'Sign Up'. There are two input fields: 'Email Address' and 'Password'. The 'Email Address' field is empty, and the 'Password' field is also empty. Below the input fields is a blue 'Login' button.



A screenshot of the same web browser displaying the login page for 'KIT's IMER'. The browser's address bar shows 'http://localhost:3000'. At the top center of the page, there is a red error message: 'User not found'. Below the error message, the login card is visible. The 'Email Address' field now contains the text 'moreptajita@gmail.com'. The 'Password' field contains seven asterisks '*****'. The blue 'Login' button is still present.



```
• PS E:\MCA\SEM2\FullStack\ISE2\client> cd..
• PS E:\MCA\SEM2\FullStack\ISE2> git init
Initialized empty Git repository in E:/MCA/SEM2/FullStack/ISE2/.git/
• PS E:\MCA\SEM2\FullStack\ISE2> git add .
warning: adding embedded git repository: client
hint: You've added another git repository inside your current repository.
hint: Clones of the outer repository will not contain the contents of
hint: the embedded repository and will not know how to obtain it.
hint: If you meant to add a submodule, use:
hint:
hint:   git submodule add <url> client
hint:
hint: If you added this path by mistake, you can remove it from the
hint: index with:
hint:
hint:   git rm --cached client
hint:
hint: See "git help submodule" for more information.
hint: Disable this message with "git config set advice.addEmbeddedRepo false"
warning: in the working copy of 'server/package-lock.json', LF will be replaced by CRLF
the next time Git touches it
warning: in the working copy of 'server/package.json', LF will be replaced by CRLF the n
ext time Git touches it
• PS E:\MCA\SEM2\FullStack\ISE2> git commit -m "Complete MERN Authentication Project"
[master (root-commit) a5b0b33] Complete MERN Authentication Project
 8 files changed, 1292 insertions(+)
 create mode 100644 .gitignore
 create mode 100644 New Microsoft Word Document.docx
 create mode 160000 client
 create mode 100644 server/models/User.js
 create mode 100644 server/package-lock.json
 create mode 100644 server/package.json
 create mode 100644 server/server.js
 create mode 100644 ~$w Microsoft Word Document.docx
• PS E:\MCA\SEM2\FullStack\ISE2> git remote add origin https://github.com/MorePrajita/Mode
rn-Full_Stack-Development-MERN-Authentication-Project-.git
• PS E:\MCA\SEM2\FullStack\ISE2> git branch -M main
• PS E:\MCA\SEM2\FullStack\ISE2> git push -u origin main
Enumerating objects: 11, done.
Counting objects: 100% (11/11), done.
Delta compression using up to 12 threads
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

PS E:\MCA\SEM2\FullStack\ISE2> git add .

hint: git submodule add <url> client

hint:

hint: If you added this path by mistake, you can remove it from the

hint: index with:

hint:

hint: git rm --cached client

hint:

hint: See "git help submodule" for more information.

hint: Disable this message with "git config set advice.addEmbeddedRepo false"

warning: in the working copy of 'server/package-lock.json', LF will be replaced by CRLF the next time Git touches it

warning: in the working copy of 'server/package.json', LF will be replaced by CRLF the next time Git touches it

● PS E:\MCA\SEM2\FullStack\ISE2> git commit -m "Complete MERN Authentication Project"

[master (root-commit) a5b0b33] Complete MERN Authentication Project

8 files changed, 1292 insertions(+)

create mode 100644 .gitignore

create mode 100644 New Microsoft Word Document.docx

create mode 160000 client

create mode 100644 server/models/User.js

create mode 100644 server/package-lock.json

create mode 100644 server/package.json

create mode 100644 server/server.js

create mode 100644 ~\$w Microsoft Word Document.docx

● PS E:\MCA\SEM2\FullStack\ISE2> git remote add origin https://github.com/MorePrajita/Modern-Full_Stack-Development-MERN-Authentication-Project-.git

● PS E:\MCA\SEM2\FullStack\ISE2> git branch -M main

● PS E:\MCA\SEM2\FullStack\ISE2> git push -u origin main

Enumerating objects: 11, done.

Counting objects: 100% (11/11), done.

Delta compression using up to 12 threads

Compressing objects: 100% (9/9), done.

Writing objects: 100% (11/11), 12.81 KiB | 820.00 KiB/s, done.

Total 11 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)

To https://github.com/MorePrajita/Modern-Full_Stack-Development-MERN-Authentication-Project-.git

* [new branch] main -> main

branch 'main' set up to track 'origin/main'.

○ PS E:\MCA\SEM2\FullStack\ISE2> □