

Shirt Construction Spec



REFERENCE PHOTO: <https://davidrady.com/shirt.jpg>

WHITE CONTRAST TOPSTITCHING (most important detail): White contrast topstitch thread on: placket fold, yoke seam, collar, cuffs, pocket edges, and bottom hem. NOT on sleeve seams. See reference photo for exact placement.

PLACKET: No traditional placket. Clean front fold with multiple rows of white contrast edge stitching (approximately 4 parallel rows, evenly spaced). See reference photo for spacing.

POCKETS: Two identical chest pockets, left and right. Open top patch pockets, no flaps, double stitch detailing, with button closure at top center of each pocket. White contrast stitching on all pocket edges.

COLLAR: Semi spread. Soft, unfused or very lightly fused interlining for a relaxed casual drape.

CUFFS: One button square cuff.

BUTTONS: White resin buttons, larger than standard dress shirt size (around 12 to 14mm). Only 4 front buttons excluding collar button, spaced wider apart than standard. Shirt designed to be worn with top button open.

BACK: Split yoke, no pleat.

HEM: Curved bottom, length designed for untucked wear.

GUSSET: V shape clip gusset at side seams.

FABRIC: Red/rose end on end cotton, ideally in the 120 to 140 gsm range for a workwear weight with some body to it.

FIT: Relaxed/casual, not slim. Designed to be worn untucked over jeans.

BODY MEASUREMENTS:

Neck: 16.5"

Chest: 39"

Waist: 33.5"

Shoulder: 19.5"

Sleeve: 25.75"

Shirt Length: 27.5"

Bicep: 13"

Wrist: 7.5"