Motion-Adaptive Internal Force Allocation for Dual-Arm Cooperative Manipulation // Or // Task-on-Demand Grasp Force Optimization for Dual-Arm Object Transport

1st Luca Morello
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

2nd Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

3rd Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

***Abstract*—**

- **Cooperative dual-arm transport needs enough squeeze force to prevent slip, but constant or over-conservative squeeze force wastes actuation effort and risks damaging fragile objects.**
- **We decompose the 12D dual-arm contact wrench into internal (squeeze) and external (task) components via a nullspace projection of the grasp matrix.**
- **We formulate a real-time 2-variable QP that allocates per-arm normal forces, minimizing squeeze effort and balancing the load between arms subject to friction-derived bounds.**
- **We couple the minimal grasp-force bound to the motion state of the manipulation task (”task-on-demand”), so the safety margin grows only while the object is in transit and relaxes at rest.**
- **We extend the same QP, at no extra decision-variable cost, with a joint-torque-aware penalty that biases squeeze-force allocation toward the arm with more actuation margin.**
- **We report internal force tracking error, friction-margin utilization, and squeeze effort with vs. without the motion-adaptive term, and with vs. without the joint-torque-aware penalty.**

***Index Terms*—ToDo [1]**

INTRODUCTION

Motivation

- Dual-arm cooperative transport needs sufficient normal (squeeze) force to prevent slip under load/inertial disturbance.
- Excess squeeze force is wasted actuation effort and risks damaging or destabilizing fragile/compliant objects.
- Human grip-force control scales with load/motion state rather than staying constant [to cite]: Westling & Johansson 1984 (grip force / load force coupling with friction-dependent safety margin).

Positioning

- Cooperative-manipulation force-distribution literature optimizes internal force statically or per-instant, without a motion-state-dependent target.
- Motion/slip-adaptive grip-force literature is mostly single-gripper and slip-reactive (triggered after slip is detected/predicted), not posed as a dual-arm allocation problem.
- Force-distribution literature rarely couples the allocation decision back to each arm’s actuation margin (joint torque headroom); it is typically treated at the end-effector/wrench level only.

Gap

- No existing framework couples: (a) nullspace-based internal/external wrench decomposition, (b) real-time QP allocation of squeeze force between two arms, and (c) a motion-derived force demand that is proactive (scheduled/estimated from the task’s motion state) rather than reactive (slip-triggered).
- Joint-space actuation capacity (torque headroom, proximity to singularity/thermal limits) is not typically fed back into a real-time end-effector-level force allocator, despite the wrench-to-torque map being affine and cheap to exploit.

What to prove

- goal of this paper is: adaptively allocating dual-arm squeeze (normal) forces based on the object’s motion can significantly improve efficiency and safety compared to a fixed safety margin.
- prove that coupling the minimal grasp force to the motion state (a “task-on-demand” safety margin) will reduce wasted actuation effort (and thus energy/power) without compromising slip stability.
- demonstrate that biasing the force allocation toward the arm with more joint torque capacity further improves overall performance
- **Motion-adaptive grip force reduces effort**
  - We hypothesize that tying the minimum grasp force to object velocity (instead of a constant margin) will

lower the average commanded squeeze force and the total actuator work
  - directly inspired by human grip behavior
  - Likewise, adaptive grasp designs can hold objects securely with much lower forces By analogy, our motion-driven scheme should yield noticeably lower total squeeze force (hence lower power draw) than a constant-margin controller, especially when the object is at rest.
- **Slip safety is maintained when needed**
  - Even though we reduce unnecessary force at rest, we expect the *dynamic slip margin* to remain safe during motion
- **Balanced load and torque awareness**
  - Our QP also enforces balanced force distribution (penalizing one arm doing all the work) and can include a joint-torque cost.
  - We hypothesize that adding the torque-aware quadratic terms will shift squeeze effort onto the arm with more actuation headroom. This should *increase each arm's torque margin* (distance to its limits) relative to a force-unaware allocation.

Contributions

- a two-variable QP can allocate normal forces to both arms in real time while enforcing friction and actuation bounds
- making the safety floor velocity-dependent (task-on-demand) measurably reduces overall effort
- adding a small torque-penalty reshapes the force split to protect the arm with tighter joint capacity
- We will contrast each element against simpler baselines (e.g. fixed safety margin, no torque cost) and show the improvements in clear metrics.

RELATED WORK

Internal/external force decomposition and QP-based load distribution

- Classical hybrid two-arm coordination and internal/external wrench split (Uchiyama & Dauchez).
- QP-based minimization of internal forces in cooperating manipulators (Nahon & Angeles, 1992).
- NLP/QP force-distribution schemes with normal-force constraints (Kwon & Lee; Kazerooni).
- Recent result: non squeezing internal load distributions from a generalized inverse of the grasp matrix are **not unique**
- Admittance/QP dual-arm cobot frameworks regulating internal vs. external effort for safe bimanual interaction (BAZAR-style hierarchical QP).

Friction-cone-constrained grasp/contact force optimization

- Canonical exact formulation: friction-cone feasibility as positive-definiteness / SDP (Buss, Hashimoto & Moore, 1996).
- Polyhedral/linear approximations of the friction cone for LP/QP tractability (Kerr & Roth; Cheng & Orin).

Motion and slip-adaptive grip force control

- Biological grounding: grip force/load force coordination and friction-dependent safety margin (Westling & Johansson, 1984).
- Trajectory modulation as an alternative (not just complement) to grip-force modulation for slip prevention (Nature Machine Intelligence, 2025)
  contrast: this paper treats grip force as the adaptive variable and trajectory as given, the inverse framing.
- Human hand-acceleration modulation alongside grip-force modulation for slip prevention (2024 study)
  motivates a velocity/acceleration-estimated demand term.
- Reactive slip control via internal-force optimization for multifingered hands, arguing uniform force increases perturb object pose vs. allocation-aware optimization (Théo Ayral)

SYSTEM OVERVIEW

Platform and FSM

- Dual xArm7 setup in mc_rtc.
- FSM: Idle $\rightarrow$ Independent (reach) $\rightarrow$ Collaborative Build-Grasp $\rightarrow$ Trajectory $\rightarrow$ Cooperative Motion .
- One system-diagram figure.

Problem Statement

- At every control cycle, find the per-arm normal (squeeze) forces
$$\mathbf{x} = \begin{bmatrix} F_{n,L} \\ F_{n,R} \end{bmatrix} \tag{1}$$
  that:
  - track a desired internal grasp force level,
  - respect friction-derived and actuation bounds,
  - remain balanced between the two arms,

INTERNAL WRENCH DECOMPOSITION AND SQUEEZE ISOLATION

System Wrench and Grasp Matrix

- dual-arm wrench $w \in \mathbb{R}^{1\times 12}$:
$$w = \begin{bmatrix} w_L \\ w_R \end{bmatrix} \in \mathbb{R}^{12}, \tag{2}$$
  where $w_L = [\tau_L; f_L]$ and $w_R = [\tau_R; f_R]$.
- Grasp matrix $G \in \mathbb{R}^{6\times 12}$ and internal-wrench nullspace projector:
$$P_{\text{int}} = I_{12} - G^{\dagger} G. \tag{3}$$
- Internal wrench:
$$w_{\text{int}} = P_{\text{int}}\, w. \tag{4}$$

Squeeze Subspace Isolation

- defined the squeeze direction n_s
- Let N denote the orthonormal nullspace basis of G, obtained via singular value decomposition (SVD).
- Normalized, kinematically valid squeeze direction:
$$n_{\text{squeeze}} = \frac{N N^T n_s}{\|N N^T n_s\|}. \tag{5}$$

Scalar Grasp Force

- The grasp-force scalar is given by

$$\lambda_{\text{grasp}} = n_{\text{squeeze}}^T w_{\text{int}} \tag{6}$$
$$= n_{\text{squeeze}}^T P_{\text{int}}\, w. \tag{7}$$

- Since $n_{\text{squeeze}} \in \mathcal{N}(G)$, it follows that $P_{\text{int}} n_{\text{squeeze}} = n_{\text{squeeze}}$. Moreover, P_{int} is an orthogonal projector and is therefore symmetric, i.e., $P_{\text{int}}^T = P_{\text{int}}$. Hence,

$$\lambda_{\text{grasp}} = n_{\text{squeeze}}^T P_{\text{int}}\, w \tag{8}$$
$$= \left(P_{\text{int}} n_{\text{squeeze}}\right)^T w \tag{9}$$
$$= n_{\text{squeeze}}^T w. \tag{10}$$

- This identity shows that only the component of w lying in the internal-wrench subspace contributes to λ_{grasp}; any object-motion wrench is orthogonal to n_{squeeze}.

Decomposing w into Fixed and Optimized Parts

- The total contact wrench is decomposed as

$$w = w_{\text{fixed}} + S_n x, \tag{11}$$

  where w_{fixed} contains the measured contact moments and tangential forces (which are not optimized), and $S_n \in \mathbb{R}^{12\times 2}$ maps the decision variables to the world-frame normal-force wrench components through the unit contact normals $\hat{u}_L$ and $\hat{u}_R$.
- Substituting the above decomposition into $\lambda_{\text{grasp}} = n_{\text{squeeze}}^T w$ yields the affine grasp-force model:

$$\lambda_{\text{grasp}}(x) = c^T x + \lambda_0, \tag{12}$$

  where

$$c^T = n_{\text{squeeze}}^T S_n, \tag{13}$$
$$\lambda_0 = n_{\text{squeeze}}^T w_{\text{fixed}}. \tag{14}$$

- The coefficients c_L and c_R quantify the contribution of a unit normal force applied by the left and right manipulators, respectively, to the internal squeeze force. The offset λ_0 represents the squeeze already generated by the fixed contact moments and tangential force components.

MOTION-ADAPTIVE FORCE DEMAND

Motivation

- Constant-safety-margin baseline is simple but not motion-aware: over-conservative at rest, potentially insufficient at peak dynamic load.
- Design goal: the minimum grasp-force floor should increase during object transport and relax when the object is at rest.

Trajectory-Schedule-Driven Formulation

- Considered index: acceleration profile Rejected because $|\ddot{s}(\tau)|$ exhibits a double-lobe profile that returns to zero at peak velocity, despite cumulative inertial and frictional loading still being present.
- Adopted index: velocity profile This profile is single-lobed, continuous, and zero only at the trajectory endpoints. The choice is deliberate and should be justified explicitly in the text.
- measured or estimated task-space velocity signal, e.g., the average of the commanded or measured end-effector velocities:

$$v_{\text{obj,est}} = \left\| \frac{1}{2}\left(\dot{x}_L + \dot{x}_R\right) \right\| \tag{15}$$

$$F_{\text{demand}} = k\, v_{\text{obj,est}} \tag{16}$$

- Since the formulation relies on a measured signal rather than a planner-specific trajectory clock, it generalizes across different trajectory generators
- **Optional for future works** hybrid formulation: use the schedule-driven term as a smooth feedforward baseline with a small proportional correction based on the planned-versus-measured velocity error. This configuration is proposed as the ablation condition (c) in Section X.

Minimal Grasp Force Bound

- Minimum normal-force bound (per arm):

$$F_{\min} = \max\left(\frac{\|F_t\|}{\mu},\ F_{\text{static}} + F_{\text{demand}}\right). \tag{17}$$

- Interpretation: the minimum normal-force floor is given by the larger of the friction-required minimum and the combined static and motion-adaptive safety margin.

QP FORMULATION FOR SQUEEZE FORCE OPTIMIZATION

Cost Function

- Objective function:

$$J(x) = \underbrace{\alpha\, \lambda_{\text{grasp}}(x)^2}_{\text{minimize squeeze}} + \underbrace{\beta\left(F_{n,L} - F_{n,R}\right)^2}_{\text{balance}}, \qquad \alpha, \beta > 0. \tag{18}$$

- α: penalizes the total squeeze effort (crushing risk, actuation cost).
- β: penalizes load imbalance between the two arms (avoids one arm doing all the work).

Standard QP Form Derivation

- Expanding the grasp-force term:

$$\lambda_{\text{grasp}}(x)^2 = x^T c c^T x + 2\lambda_0 c^T x + \lambda_0^2. \tag{19}$$

- Defining $d = [1, -1]^T$, the balance term is written as

$$\left(F_{n,L} - F_{n,R}\right)^2 = x^T d d^T x. \tag{20}$$

- Dropping the constant term $\alpha\lambda_0^2$, the objective becomes

$$J(x) = x^T \left(\alpha cc^T + \beta dd^T\right) x + 2\alpha\lambda_0 c^T x. \tag{21}$$

- Matching the standard QP form

$$J(x) = \frac{1}{2} x^T H x + g^T x, \tag{22}$$

yields

$$H = 2 \begin{bmatrix} \alpha c_L^2 + \beta & \alpha c_L c_R - \beta \\ \alpha c_L c_R - \beta & \alpha c_R^2 + \beta \end{bmatrix}, \tag{23}$$

and

$$g = 2\alpha\lambda_0 \begin{bmatrix} c_L \\ c_R \end{bmatrix}. \tag{24}$$

Constraints

- Friction constraints (per contact):

$$\|F_{t,L}\| \le \mu_L F_{n,L}, \tag{25}$$
$$\|F_{t,R}\| \le \mu_R F_{n,R}, \tag{26}$$

where the tangential contact forces are obtained from the force sensors and are treated as fixed (i.e., not optimization variables).
- Positivity / minimum-force constraints:

$$F_{n,L} \ge F_{\min}, \tag{27}$$
$$F_{n,R} \ge F_{\min}, \tag{28}$$

- The friction constraints use the tangential force measured during the *previous* control cycle to constrain the *next* commanded normal force, introducing a one-cycle lag. This is a deliberate linear/QP approximation of the exact friction-cone constraint, avoiding the need for a jointly optimized SOCP formulation (Section II-B).

Final Problem

- The optimization problem is formulated as

$$\min_x \ J(x) \tag{29}$$

subject to

$$F_{n,L} \ge F_{\min}, \tag{30}$$
$$F_{n,R} \ge F_{\min}, \tag{31}$$

together with the upper actuation bounds.

Sensitivity to α, β

- Small figure or table: sweep α (with fixed β) and β (with fixed α), and report the resulting λ_{grasp} tracking performance and inter-arm load imbalance. This provides intuition for parameter tuning and serves as a robustness check.

JOINT-TORQUE-CAPACITY-AWARE EXTENSION

Motivation

- The QP formulated thus far allocates squeeze force exclusively at the end-effector wrench level and does not account for the joint-space cost associated with each allocation.
- End-effector wrenches are mapped to joint torques through the Jacobian transpose,

$$\tau = J^T w. \tag{32}$$

Since w is already an affine function of x, the resulting joint torques are also affine in x, allowing this information to be incorporated without introducing additional decision variables.
- The objective is to bias the squeeze-force allocation toward the manipulator with greater available actuation margin (e.g., farther from a singular configuration, subject to lower thermal loading, or with greater torque headroom), while preserving the original real-time QP structure.

Affine Torque Map

- Per-arm contact wrench:

$$w_L = w_{fixed,L} + S_{n,L} F_{n,L},$$
$$w_R = w_{fixed,R} + S_{n,R} F_{n,R}.$$

- Corresponding joint-torque contributions:

$$\tau_{c,L}(x) = J_L^T w_{fixed,L} + J_L^T S_{n,L} F_{n,L},$$
$$\tau_{c,R}(x) = J_R^T w_{fixed,R} + J_R^T S_{n,R} F_{n,R},$$

which are affine in x, with the same structure as $\lambda_{grasp}(x)$ in section number.

Extended Cost Function

$$J(x) = \alpha\, \lambda_{grasp}(x)^2 + \beta \left(F_{n,L} - F_{n,R}\right)^2 \tag{33}$$
$$+ \gamma_L \|\tau_{c,L}(x)\|^2 + \gamma_R \|\tau_{c,R}(x)\|^2 \tag{34}$$

- Each new term is quadratic in x no change to problem dimension (still 2 variables) or solver.
- Term-by-term reading of the four-way trade-off: α (avoid crushing the object), β (keep contact forces even), γ_L, γ_R (avoid joint torque overload on each arm respectively).

Role and Tuning of γ_L, γ_R

- $\gamma_L = \gamma_R = 0$ recovers the original formulation exactly the extension is strictly backward-compatible, useful for a clean ablation (with/without torque awareness) rather than a redesign.
- Small, equal, nonzero values (e.g., 0.01–0.1) protect joint torque margin without materially disrupting grasp-force tracking report the smallest γ that yields a measurable protective effect.
- Asymmetric values ($\gamma_L \neq \gamma_R$) let the allocator favor the arm with more capacity e.g., setting γ_L higher than γ_R

to shift squeeze effort onto the right arm when the left arm is known (a priori, per configuration/experiment) to be closer to a singularity, torque limit, or thermal derate.

Target Formulation (future work)

- Reformulate as orthogonal task-space separation: decompose the task space into complementary force-controlled and motion-controlled subspaces so spring/wrench-gain terms and lateral motion-tracking terms act on disjoint directions by construction, rather than being reconciled post hoc via gain blending.
- Cite the classical hybrid position/force orthogonal-subspace formulation (Raibert & Craig, 1981) and a recent interaction-frame instance (2026) as the target formalism.

Experimental Validation

Platform and Protocol

- Dual xArm7, `mc_rtc`.
- Pick–carry–place trajectory; force-demand conditions:
  - (a) constant `F_static` baseline,
  - (b) schedule-driven `F_demand`,
  - (c) motion-estimated `F_demand`,
  - (d) hybrid.
- Torque-awareness conditions: with vs. without the extension, symmetric vs. asymmetric γ_L, γ_R.

Metrics

- Internal force
- Peak/RMS tangential force relative to the friction bound (slip-margin proxy).
- Total squeeze effort $\int \|x\|\, dt$.
- Peak/RMS joint torque per arm, and margin-to-limit, with vs. without extension.
- QP solve time distribution

Figures

- FSM / system diagram.
- Internal force vs. trajectory phase, with all demand conditions overlaid.
- Friction-margin utilization over the trajectory.
- Joint torque per arm, with vs. without torque-aware weighting, under an induced asymmetric-capacity scenario.
- Contact-loss / activation-blend before-after comparison.
- Solve-time histogram.

Discussion and Limitations

- Nonuniqueness of the internal/external decomposition: the weighted objective is a design choice, not “the” optimal split. State what it privileges (low effort vs. balance vs. torque margin) and how that choice was made.
- Linearized, one-cycle-lagged friction bound versus the exact friction cone: identify the operating regime in which this approximation may fail (e.g., fast tangential-force transients).
- Fixed versus state-driven weighting coefficients, γ_L and γ_R: fixed weights are straightforward to justify but do not capture the instantaneous actuation capacity of each manipulator. **in future works** to present state-dependent weighting as the natural next step.

Conclusion and Future Work

- **Summary:** The proposed framework combines QP-based dual-arm squeeze-force allocation, a motion-adaptive force-demand formulation, and a joint-torque-capacity-aware extension, and is validated experimentally on a dual `xArm7` platform.
- **Future Work:**
  - Adopt the closed-loop, motion-estimated force-demand formulation as the primary approach, rather than as a fallback strategy.
  - Replace the fixed weighting coefficients γ_L and γ_R with state-driven weights based on online measures such as manipulability, joint-torque headroom, or actuator thermal state.
  - Incorporate exact friction-cone handling through a second-order cone programming (SOCP) formulation, subject to real-time computational constraints.

References

- **Internal force decomposition / dual-arm QP allocation**
  - Nahon, M., and Angeles, J. (1992) — QP-based minimization of internal forces in cooperating manipulators.
  - Kwon, W., and Lee, B.H. — NLP/QP force-distribution scheme with normal-force constraints.
  - Recent analysis on the nonuniqueness of nonsqueezing load distributions in cooperative manipulation (2023).
  - Admittance-QP dual-arm cobot framework regulating internal/external efforts (BAZAR, 2017–2018).
  - Recent HQP variants for mobile/free-floating dual-arm manipulation (2025–2026).
- **Grasp/contact force optimization under friction**
  - Buss, M., Hashimoto, H., and Moore, J.B. (1996), *Dextrous Hand Grasping Force Optimization*, IEEE Transactions on Robotics and Automation.
  - Kerr, J., and Roth, B.; Cheng, F., and Orin, D. — polyhedral/linear friction-cone approximations.
  - Recent work comparing SOCP and QP formulations for real-time grasp-force control (2026).
- **Motion-adaptive / slip-driven grip force**
  - Westling, G., and Johansson, R.S. (1984), *Factors Influencing the Force Control During Precision Grip*, Experimental Brain Research, 53:277–284.
  - Nature Machine Intelligence (2025) — trajectory modulation versus grip-force modulation for slip control.
  - Human hand-acceleration modulation study for slip prevention (2024).

- Reactive slip control via internal-force optimization for multifingered hands (2026 arXiv).
- **Joint-space capacity-aware allocation**
  - Classical minimum-norm / weighted-pseudoinverse torque allocation for redundant and multi-arm systems.
  - Whole-body and multi-contact QP controllers with torque- or actuation-margin-aware cost terms (locomotion / multi-contact force-distribution literature).
- **Contact-state transition / hybrid position-force control**
  - Raibert, M.H., and Craig, J.J. (1981) — classical orthogonal position/force subspace hybrid control.
  - Recent orthogonal interaction-frame decomposition for contact-rich manipulation (2026).
  - Smooth controller blending / gain interpolation across contact-state transitions (changing-contact manipulation frameworks).
- **Impact-aware contact establishment (background only)**
  - van Steen, J.J., Coşgun, A., van de Wouw, N., and Saccon, A., *Dual-Arm Impact-Aware Grasping through Time-Invariant Reference Spreading Control*, IFAC-PapersOnLine, 2023.
  - van Steen, J.J., van den Brandt, G., van de Wouw, N., Kober, J., and Saccon, A., *QP-Based Reference Spreading Control for Dual-Arm Robotic Manipulation with Planned Simultaneous Impacts*, IEEE Transactions on Robotics, 2024.
  - Arita, H., Nakamura, H., Fujiki, T., and Tahara, K. — *Smoothly Connected Preemptive Impact Reduction and Contact Impedance Control*, 2022/2023.
  - Khatib, O. — effective/reflected mass in operational-space control.
  - Wang, Y., Dehio, N., Tanguy, A., and Kheddar, A., *Impact-Aware Task-Space Quadratic-Programming Control*, International Journal of Robotics Research, 2023.

REFERENCES

[1] M. Uchiyama and P. Dauchez, "A symmetric hybrid position/force control scheme for the coordination of two robots," in *Proceedings. 1988 IEEE international conference on robotics and automation*. IEEE, 1988, pp. 350–356.