

Embedded Systems

02131

R-peak detection!
2013

Jakob Welner, s124305
Jacob Gjerstruo, s113440

Abstract

The task of this assignment was to develop an Electro-Cardiogram (ECG) scanner using the Pan-Thomkins QRS-Detection Algorithm, and then implement this algorithm in the language C. Using this algorithm, a program has been created that can determine a persons heartbeat and give warnings when either the intensity or the heartrate falls below a certain threshold. The program has initially been based on sample data gathered from an ECG scanner and read from a file. However, care has been taken in making it easy to replace the data source at a later point. All algorithms provided by the assignment were implemented successfully although certain issues persisted.

Indhold

1	Introduction	1
1.1	Requirements	1
2	Theory	2
2.1	Problem 1: Data acquisition	2
2.2	Problem 2: Implementation of Filters	2
2.3	Problem 3: Implementation of R-peak detection	3
2.4	Problem 4: Relevant data	3
2.5	Problem 5: Critical parts	3
3	Design	4
4	Implementation	5
4.1	Core structure	5
4.2	Real-time data acquisition	6
4.3	Implementation of Filters	6
4.4	Implementation of RPeakDetection	7
4.5	Relevant data	7
4.6	Critical parts	7
5	Results	8
5.1	Test results of filters	9
6	Discussion	9
6.1	Improvements	10
7	Conclusion	11
A	Who wrote what	13
B	Output of the RPeakDetection	13
C	Sourcecode - introductory exercises	20
C.1	ReadFromFile	20
C.2	HelloWorld	21

D	Sourcecode - the real program	21
D.1	Buffer	21
D.2	Filters	22
D.3	RPeakDetection	25
D.4	Sensor	34
D.5	Header files	35
	D.5.1 sensor.h	35
	D.5.2 buffer.h	35
D.6	Tests	36

1 Introduction

This report will investigate the Pan-Thomas QRS detection algorithm, more specifically, if it is possible to implement this algorithm into the company Medembed's next product, which is a wearable ElectroCardioGram (from now on simply called ECG) scanner.

The algorithm will be implemented in the programming language C, and this report will discuss the following topics: Data acquisition, implementing filters, implementing the peak-detection algorithm, outputting the data to the user and finally, an analysis of the algorithm in terms of power consumption, speed (clock cycles per second) and code size.

For the purpose of this report, we will only implement the C program, and will simulate the data acquisition in real time through data files. Furthermore, the program will be run on an all-purpose processor, whereas in the final product of Medembed, a dedicated processor with limited resources will be used.

1.1 Requirements

Below follows a list of functional and non-functional requirements:

Functional requirements for the application:

- Data acquisition in simulated real-time
- Implementation of the 5 filters
- Implementation of the R-peak detection
- Output of relevant data to the user, based on the algorithm
- An analysis of our implementation as well as the critical parts, runtime and memory requirements.

Non-functional requirements for the application:

- The programming language used for this is C

2 Theory

In order to initiate the structure- and design-process of the program, a number of questions needed to be answered first:

1. How should the real-time data acquisition be simulated?
2. How should the filters be integrated?
3. How should the R-peak detection be integrated?
4. Which data would be relevant for the user, and how should it be shown?
5. How do you determine the critical parts?

2.1 Problem 1: Data acquisition

As specified in the introduction, the dataset used was only sample data and not current readings. To ensure that the program would work on live data as well as samples, a method for reading single datapoints sequentially was implemented, thus simulating real data acquisition. Loading single datapoints while needing to handle both the current data as well is the biggest challenge when it comes to data acquisition.

2.2 Problem 2: Implementation of Filters

To use the QRS-algorithm to it's full extent, the raw data should go through a list of 5 filters, cleaning up the data, amplifying peaks and removing unwanted noise. 4 of these filters use multiple datapoints simultaneously, both current and previous samples, while lowpass and highpass use previous samples from their own filtered output. To allow for easy access to the saved datapoints at different given points in time, the readData buffer method was extended to include a time offset input value. This would work as an index for the data array, though combined with the built-in counter, would amount to a number of steps back in time. ReadData(buffer, 0) would read latest pushed data from 'buffer' and readData(buffer, 3) would read the data stored 3 loops earlier. Furthermore, passing pointers of buffer structs to the buffer-methods allowed to change the provided buffers inplace

Having extended the method successfully while simply returning 0-values when requesting data before 1st loop, implementing the filters was a matter of writing the equations from the assignment and requesting the appropriate datapoints directly. Allowing lowpass and highpass to read from their own output was then

elementary. Passing a pointer of the input- and another of the output-buffer would give each filter access to read/write on both

2.3 Problem 3: Implementation of R-peak detection

Once all the filters had been implemented, the actual QRS-algorithm was the next step. The QRS-algorithm would be the one to determine what constitutes a heartbeat, and how to analyse it. Furthermore, it would serve to determine how R-peaks are identified, and after each peak, it will update certain variables to ensure the heartbeats are tracked correctly. These variables will be the ones determining when a heartbeat is certain than a threshold, and if it is, this peak is referred to as an R-peak. Once an R-peak has been determined, data is updated further to classify the next peaks as either heartbeats or noise. This algorithm, however, introduces three challenges - how to determine whether the patient simply has irregular and/or weak heartbeats or whether the patient is having a heart attack; and how to ensure that every heartbeat is detected correctly. The final challenge was that the algorithm requires that all peaks are stored, and as there is no knowing how many peaks will be found, a list of flexible length was needed.

2.4 Problem 4: Relevant data

The requirement states that the program must show at the very least the value of the latest R-peak that was detected, and also, it must show when this R-peak happened, plus the patient's pulse. Furthermore, the patient must be given a warning if the R-peaks value is less than 2000 (as this is a sign of an impending heart attack) and finally, if 5 successive RR-intervals has missed the RR- LOW and HIGH values, these must be shown. However, how these data are to be shown has not been defined, and therefore must be specified.

There are several ways to show these data, of which the simplest is to make a text-based screen with the information necessary, and keep this screen updated in real-time, showing the data as we calculate them. Alternatively, the data can be plotted and shown in a graph, or one could combine these two, giving both a graph that keeps getting updated in real-time, as well as text-based information.

2.5 Problem 5: Critical parts

The final issue that was to be clarified is the critical parts of the program. Here, there are three points to discuss, memory requirement, time consumption and power consumption.

Memory requirement is important as the bigger the program is, that is, the more memory it requires, the more physical memory must be implemented into the final device, and therefore, the device will become larger and more cumbersome to wear. Furthermore, more memory also means that the device becomes more power-consuming.

Time consumption is important as the device must be able to read at least 250 data points a second, and if the functions are very time consuming, a stronger processor is needed that requires more power. Furthermore, it is also important that the processor used does not process the data too fast, either, as this will mean that the processor will idle and use power for nothing, meaning a smaller processor can be used that requires less power.

Power consumption is important as it determines how often the user must either recharge the battery or be issued a new battery.

3 Design

When designing the program, it was quickly decided that multiple files should be used for easier readability. Each file would consist of functions concerning a single topic, ie: the `filter.c` would contain filters-related methods only. The files used are: `filter.c`, `buffer.c`, `main.c`, `RRhandling.c` and `sensor.c`.

Furthermore, it was decided that the data from each filter, as well as the raw data, would each be stored for a set amount of time. An amount of 33 samples was chosen given that no filters request values older than 32 readings before current. Allocating more memory would therefore be a waste and having less samples stored, would break the algorithm.

To handle the actual data a buffer was created. The mainloop would then run through the data-set, scanning in a point and passing it to the buffer. The buffer would then handle storing and retrieving data through a struct type and 4 dedicated buffer-methods. This array would then be passed on to the filters which would sample individual datapoints, apply the appropriate math and update the buffer-values accordingly.

For a more direct look at how the program is designed, a class diagram has been created, as can be seen on figure 1. This diagram also shows what function is placed where, as well as how each class is related to each other.




Figure 1: The above diagram shows how each of the classes are related to each other

4 Implementation

4.1 Core structure

To support the overall functionality and readability of the program, a core structure needed to be created. First, the data flow should be handled - data coming from the sensor should be stored for later processing. Storing such data could be handled in many ways but it was decided to construct a type of buffer which would allow for easy pushing and pulling data, while only keeping a certain amount of history. The buffer will also keep track of where in the array the data is, and should it exceed the size of the array, it will return to the first place in the array (indexed to 0) and overwrite the data there. In order to get around returning huge lists of data between functions, the buffer would instead update the input variables in-place through pointers.

The last bit of the core was to set up a list for containing validated R-Peaks. Given that all R-peaks should be saved, the list would be of an arbitrary length. While the C-language is very poor at handling arrays with ill-defined length, a linked list was used instead. The linked list works by defining a Struct type which contains a variable pointer to another struct of the same type. Adding each R-peak as a new

struct instance while assigning it a pointer to the previous r-peak struct, would allow for a so-called linked list of arbitrary length.

4.2 Real-time data acquisition

As described, the program must acquire the data and calculate in real-time. To ensure this simulation, the program loads one data point, then passes it and the corresponding array to the one filter at a time before it finally passes it to the peak detection and subsequently, to the R-peak detection. Once all these calculations have been done, it loads in a new data point and restarts through a while loop. This while-loop will run through the entire data-set, and will not stop before it reaches the end of the file (in the finished product, it will of course run until the battery runs dry).

Furthermore, it was found that in order to always keep a list of previous samples while maintaining easy access to their relation to the current data, structs and methods could be used to create a buffer - more specifically, this buffer was implemented using a struct containing an integer array as well as a counter. Using a list of simple method-functions to handle pushing of data as well as reading, a simple circular First In First Out (FIFO)-list was created.

Therefore, the combination of the while-loop that runs forever, and the continual loading and subsequent calculations through the buffer solves the challenge of real-time data acquisition.

4.3 Implementation of Filters

The first implementation of the filters were simply done with strict if/else sentences. However, this was changed to using an adaptive index that, should it reach negative values, moves to the end of the array instead. This way, the program should never encounter data under- or overflow, and thereby, the first of the challenges were solved.

The second challenge, to ensure the correct transfer of data from one filter to another, was solved by using two arrays, one for the raw data and one for the filtered data. Each array is then passed to the next part of the program, ensuring all filters have both raw and processed data to be operated on, as 4 of them requires.

Therefore, the use of two arrays and an adaptive index solves the challenge of the implementation of the filters.

4.4 Implementation of RPeakDetection

When implementing the RPeakDetection, the filtered data was run through a simple local-maxima detection and saved in a new list. As noted in Problem 3 - Implementation of RPeakDetection, this list needed to be of flexible length, and looking at the different options for implementing such a list, the decision fell on linked lists through structs. This struct contains a 'next'-variable with a pointer to the same type of struct. For each new instance of the struct, the intern next-value is set to point at the previous struct, thus linking the two together. Having implemented the linked list, 3 variables were added to the struct; VALUE, CLOCK and TYPE. Accordingly, these would contain the signal-strength of the peak, at what time the sample had occurred and what type it had been classified as. TYPE was handled as integer values where -1 meant noise-peak, 0 meant a local-maxima peak, 1 meant an R-peak and 2 meant a regular R-peak. This would allow for all the peaks to be stored in a single list while enabling searching through the list and filtering for several types at a time while comparing results. After this had been set up, the algorithm for determining r-peaks was implemented. To allow a few samples to appear before trying to enhance variable values, a MINSAMPLES value was defined.

Therefore, the combination of the algorithm and the linked list solves the challenges of the implementation of RPeakDetection.

4.5 Relevant data

To display the relevant data, a simple text-based display was created. This would show the required information, that is, the value of the latest R-peak, the time of the R-peak, the patients pulse. Furthermore, it will also display the warning and the RR-LOW and RR-HIGH values if 5 RR-intervals has been missed.

Therefore, the challenge of the relevant data has been solved.

4.6 Critical parts

As mentioned in the theory, the three critical parts of the program is memory consumption, power consumption and time consumption. The program was initially tested on a machine running a powerful all-purpose Intel Core i7-2630M CPU with a clock speed of 2GHz and consumes a maximum of 45 Watt.

As can be seen on figure 2, the processor manages to process 10.000 data points on 0.02 milliseconds which is far more than what is required (250 data points per second).

In terms of power, as said, the current processor on which the program was tested consumes a maximum of 45 Watt. This can be reduced by either reducing the calculation-power of the processor (clock frequency) or the size of the processor.

```
G:\Users\Jacob\workspace\IndSys_13\src>gprof -p a.exe gmon.out
Flat profile:
Each sample counts as 0.01 seconds.
```

% time	cumulative seconds	self seconds	calls	self us/call	total us/call	name
50.00	0.01	0.01	489988	0.02	0.02	getIndex
50.00	0.02	0.01	10000	1.00	1.63	mwInt2
0.00	0.02	0.00	489988	0.00	0.02	readData
0.00	0.02	0.00	60000	0.00	0.00	incrementCounter
0.00	0.02	0.00	60000	0.00	0.00	pushData
0.00	0.02	0.00	10001	0.00	0.00	getNextData
0.00	0.02	0.00	10000	0.00	0.08	derivative2
0.00	0.02	0.00	10000	0.00	0.10	highPass2
0.00	0.02	0.00	10000	0.00	0.10	lowPass2
0.00	0.02	0.00	10000	0.00	0.02	squaring2
0.00	0.02	0.00	9996	0.00	0.00	RRcalculate
0.00	0.02	0.00	184	0.00	0.00	add_to_peaks
0.00	0.02	0.00	183	0.00	0.00	peak_prev_clock
0.00	0.02	0.00	73	0.00	0.00	peak_average_interval
0.00	0.02	0.00	38	0.00	0.00	peak_sumOfType
0.00	0.02	0.00	36	0.00	0.00	update_RpeakVariables
0.00	0.02	0.00	1	0.00	0.00	peak_searchback
0.00	0.02	0.00	1	0.00	0.00	update_searchbackVariables
0.00	0.02	0.00	1	0.00	0.00	update_thresholdVariables

Figure 2: The table above shows the time spent in the various filters in our program. It should be noted that this profiling was done without code optimization.

In regards to size, figure 3 shows the console after 10000 data samples, and of particular interest is the “Size of Stuff” and the “elements in peak”, as these denominate the size of the linked list of peaks (in bytes), as well as the amount of elements in that list. As can be seen, after 10000 data points, 98 peaks has been found, and the total size is 1568 bytes, making it by far the largest part of the program (the second-to-largest part is the arrays of the filters, each having the size of 136 bytes)

```
sensor.c::getNextData - Reached EOF. Terminating
main::Received termination value: 65536
main::Ran 10000 times
Size of stuff: 1568
elements in peak: 98
/mnt/Dropbox/Private/__synched/DTU/Embedded_Systems/Assignments/ECG/git/Embedde
```

Figure 3: The screenshot above is a screenshot from the console after the program has been run on 10000 data samples.

5 Results

Figure 4 shows a screenshot of the output from the RPeak detection algorithm. It shows the output, both when the user has a normal heartbeat (the first part), the warning when the users heartbeat suddenly drops dangerously low, and the warning when the user has a heart attack. Furthermore, it always shows the heartrate (in Beats Per Minute (BMP)), as well as the RPeak values and the time since the last RPeak. The full output can be seen in section B

```
Heartrate: 75 bpm, value: 4893, Since last peak: 0.036 s
Heartrate: 75 bpm, value: 5466, Since last peak: 0.636 s
Heartrate: 75 bpm, value: 5334, Since last peak: 0.672 s
Heartrate: 75 bpm, value: 5367, Since last peak: 1.260 s
Heartrate: 75 bpm, value: 4388, Since last peak: 0.636 s
Heartrate: 75 bpm, value: 4286, Since last peak: 0.672 s
Heartrate: 75 bpm, value: 5008, Since last peak: 1.264 s
Heartrate: 75 bpm, value: 4908, Since last peak: 0.040 s
Heartrate: 75 bpm, value: 4295, Since last peak: 0.636 s
Heartrate: 75 bpm, value: 4185, Since last peak: 0.668 s
Heartrate: 75 bpm, value: 3958, Since last peak: 1.268 s
Heartrate: 75 bpm, value: 3846, Since last peak: 0.040 s
Heartrate: 75 bpm, value: 189, Since last peak: 0.384 s, WARNING. Heartintensity below minimum!
Heartrate: 75 bpm, value: 4356, Since last peak: 0.476 s
Heartrate: 75 bpm, value: 4237, Since last peak: 0.512 s
Heartrate: 75 bpm, value: 4490, Since last peak: 1.176 s
Heartrate: 74 bpm, value: 4372, Since last peak: 0.040 s
Heartrate: 74 bpm, value: 1224, Since last peak: 0.496 s, WARNING. Heartintensity below minimum!
Heartrate: 74 bpm, value: 1164, Since last peak: 0.536 s, WARNING. Heartintensity below minimum!
Heartrate: 74 bpm, value: 474, Since last peak: 0.896 s, WARNING. Heartintensity below minimum!
Heartrate: 74 bpm, value: 366, Since last peak: 0.940 s, WARNING. Heartintensity below minimum!
Heartrate: 74 bpm, value: 306, Since last peak: 1.256 s, WARNING. Heartintensity below minimum!
Heartrate: 75 bpm, value: 443, Since last peak: 0.040 s, WARNING. Heartintensity below minimum!
Heartrate: 75 bpm, value: 332, Since last peak: 0.084 s, WARNING. Heartintensity below minimum!
```

Figure 4: A screenshot of the output of the RPeak detection.

5.1 Test results of filters

For the purpose of ensuring the correctness of the filters, a small program was created that would go through each datapoint, load in the value from its supposed data source, run this point through the filter and compare it to the result. Figure 5 shows the result of this program, showing that all filters calculates correctly. The code for this program can be seen in section D.6

```
C:\Users\Jacob\My Documents\Github\Embedded_Systems\ECG_2013\A1\src-test>a.exe
No errors found. You're clear for takeoff
Comparing input: Datafiles/ECG.txt with file: Datafiles/x_low.txt

No errors found. You're clear for takeoff
Comparing input: Datafiles/x_low.txt with file: Datafiles/x_high.txt

No errors found. You're clear for takeoff
Comparing input: Datafiles/x_high.txt with file: Datafiles/x_der.txt

No errors found. You're clear for takeoff
Comparing input: Datafiles/x_der.txt with file: Datafiles/x_sqr.txt

No errors found. You're clear for takeoff
Comparing input: Datafiles/x_sqr.txt with file: Datafiles/x_mwi_div_after.txt

C:\Users\Jacob\My Documents\Github\Embedded_Systems\ECG_2013\A1\src-test>
```

Figure 5: A screenshot of the output of the tests of the filters.

6 Discussion

As mentioned in the critical parts, the processor which the program is tested on is more than powerful enough to fulfil the requirements of 250 data points per second. Therefore, the final processor that is to be used for the ECG scanner should be much less powerful - it makes little sense to use a very powerful processor if it idles most of the time, using power for nothing - and thus, the power consumption will be

reduced greatly.

However, if the processor had been too slow, the code could be optimized for speed. To do this, the two functions `getIndex` and `mwInt2` should be examined, as it was determined through a profiler (the GNU Gprof profiler) that it is in these two functions that the most time is spent (see figure 2).

Another way to optimize power would be to use the technical improvements of modern time to make the battery recharge during daily use, for instance by converting the kinetic energy of walking into power for the scanner.

Regarding the size, the program is generally optimized mostly in terms of speed - currently, an array of 33 data points is used for each filter, but this could be optimized down to using only 2 arrays - one for input, one for output. However, this would also increase the complexity of the task by a great deal and therefore, it was decided to simply use an array for each filter.

In terms of what should be made as software and what should be put into hardware, it should first be determined which tasks are the most processor-heavy. However, due to the profiler, this is already known - the tasks are `getIndex` and `mwInt2`. Therefore, it would also make sense to develop a special processor for these two specific tasks, using a coprocessor for each of these tasks, and a more general-purpose-like processor for the rest of the tasks.

6.1 Improvements

There are two types of improvements to be discussed - Hardware improvements and software improvements.

Within the domain of software improvements, several improvements could be done. The first improvement would be to start the QRS algorithm with dynamically allocated values, rather than hardcoded values, for all the variables. This would improve the correctness of the initial part of the algorithm, ensuring also that it works well on both males and females with varying heart-sizes.

The second improvement would be to set a maximum size for the list of peaks - currently, it is unlimited and will only grow as the device lives on - setting a maximum size and using the same theory as on the arrays for the filters could decrease the size of this list.

The third improvement would be to implement a timer that starts when a user has a heart attack, and continues to update and show the data so that when rescuers come to assist the user, they will know precisely how long the heart attack has lasted.

The final improvement that was identified were regarding the warning showed during heart attacks - currently, this warning only lasts until 5 regular heartbeats has been detected in a row, but in the final device, a doctor should be questioned

upon just how many regular heartbeats needs to be detected before it is safe to assume that the patient is stable again.

Within the domain of hardware improvements, there are two main upgrades that can be done. The first is to convert the entire project to run on a dedicated processor, using co-processors for the requiring tasks (getIndex and mwInt2 in this case). This will improve both power consumption and calculation speed.

The second improvement would be to implement modern technologies of converting kinetic energy from, for instance, walking, into power and using this to recharge the battery of the device, thus increasing its lifespan.

7 Conclusion

Implementing the algorithm has been done successfully, enabling the detection of heartbeats according to time and fulfilling all requirements. Furthermore, the processor used in the final product can easily be downscaled, using a lower clock frequency to reduce power consumption. Finally, all the challenges discovered and discussed in the Theory has been solved.

Litteratur

- [1] Michael Reibel Boesen, Linas Kaminskas, Paul Pop, Karsten Juul Frederiksen
Assignment 1: Software implementation of a personal ECG scanner
3rd Edition
2013.
- [2] <http://www.notebookcheck.net/Intel-Core-i7-2630QM-Notebook-Processor.41483.0.html>
Date of use: 25/09/2013

Appendix

A Who wrote what

Jacob Gjerstrup, s113440 wrote: Abstract, Introduction, Theory, Discussion (50%), Conclusion

Jakob Welner, s124305 wrote: Design, Implementation, Results, Discussion (50%)

B Output of the RPeakDetection

```
1 Heartrate: 60 bpm, value: 5073, Since last peak: 0.604 s
2 Heartrate: 60 bpm, value: 4932, Since last peak: 0.040 s
3 Heartrate: 60 bpm, value: 4796, Since last peak: 0.640 s
4 Heartrate: 60 bpm, value: 4683, Since last peak: 0.040 s
5 Heartrate: 60 bpm, value: 5032, Since last peak: 0.636 s
6 Heartrate: 37 bpm, value: 4958, Since last peak: 0.036 s
7 Heartrate: 37 bpm, value: 5415, Since last peak: 0.632 s
8 Heartrate: 37 bpm, value: 5266, Since last peak: 0.040 s
9 Heartrate: 37 bpm, value: 4864, Since last peak: 0.636 s
10 Heartrate: 37 bpm, value: 4738, Since last peak: 0.040 s
11 Heartrate: 37 bpm, value: 4920, Since last peak: 0.636 s
12 Heartrate: 37 bpm, value: 4800, Since last peak: 0.040 s
13 Heartrate: 37 bpm, value: 4501, Since last peak: 0.640 s
14 Heartrate: 37 bpm, value: 4385, Since last peak: 0.040 s
15 Heartrate: 37 bpm, value: 4920, Since last peak: 0.640 s
16 Heartrate: 37 bpm, value: 4810, Since last peak: 0.040 s
17 Heartrate: 37 bpm, value: 4991, Since last peak: 0.636 s
18 Heartrate: 37 bpm, value: 4872, Since last peak: 0.040 s
19 Heartrate: 37 bpm, value: 4765, Since last peak: 0.636 s
20 Heartrate: 37 bpm, value: 4698, Since last peak: 0.040 s
21 Heartrate: 37 bpm, value: 4817, Since last peak: 0.628 s
22 Heartrate: 37 bpm, value: 4683, Since last peak: 0.044 s
23 Heartrate: 37 bpm, value: 4953, Since last peak: 0.636 s
24 Heartrate: 37 bpm, value: 4866, Since last peak: 0.040 s
25 Heartrate: 37 bpm, value: 4804, Since last peak: 0.632 s
26 Heartrate: 37 bpm, value: 4673, Since last peak: 0.040 s
27 Heartrate: 37 bpm, value: 4664, Since last peak: 0.468 s
28 Heartrate: 37 bpm, value: 4534, Since last peak: 0.504 s
29 Heartrate: 37 bpm, value: 4420, Since last peak: 1.180 s
30 Heartrate: 37 bpm, value: 4315, Since last peak: 0.716 s
31 Heartrate: 69 bpm, value: 4089, Since last peak: 0.648 s
```

```
32 Heartrate: 69 bpm, value: 5104, Since last peak: 1.236 s
33 Heartrate: 75 bpm, value: 5336, Since last peak: 0.048 s
34 Heartrate: 75 bpm, value: 4453, Since last peak: 0.656 s
35 Heartrate: 75 bpm, value: 4348, Since last peak: 0.692 s
36 Heartrate: 75 bpm, value: 4498, Since last peak: 1.284 s
37 Heartrate: 75 bpm, value: 4391, Since last peak: 0.040 s
38 Heartrate: 75 bpm, value: 4626, Since last peak: 0.636 s
39 Heartrate: 75 bpm, value: 4529, Since last peak: 0.672 s
40 Heartrate: 75 bpm, value: 5258, Since last peak: 1.272 s
41 Heartrate: 75 bpm, value: 5131, Since last peak: 0.040 s
42 Heartrate: 75 bpm, value: 4866, Since last peak: 0.640 s
43 Heartrate: 75 bpm, value: 4742, Since last peak: 0.676 s
44 Heartrate: 75 bpm, value: 4994, Since last peak: 1.276 s
45 Heartrate: 75 bpm, value: 4893, Since last peak: 0.036 s
46 Heartrate: 75 bpm, value: 5466, Since last peak: 0.636 s
47 Heartrate: 75 bpm, value: 5334, Since last peak: 0.672 s
48 Heartrate: 75 bpm, value: 5367, Since last peak: 1.260 s
49 Heartrate: 75 bpm, value: 4388, Since last peak: 0.636 s
50 Heartrate: 75 bpm, value: 4286, Since last peak: 0.672 s
51 Heartrate: 75 bpm, value: 5008, Since last peak: 1.264 s
52 Heartrate: 75 bpm, value: 4908, Since last peak: 0.040 s
53 Heartrate: 75 bpm, value: 4295, Since last peak: 0.636 s
54 Heartrate: 75 bpm, value: 4185, Since last peak: 0.668 s
55 Heartrate: 75 bpm, value: 3958, Since last peak: 1.268 s
56 Heartrate: 75 bpm, value: 3846, Since last peak: 0.040 s
57 Heartrate: 75 bpm, value: 189, Since last peak: 0.384 s ,
    WARNING. Heartintensity below minimum!
58 Heartrate: 75 bpm, value: 4356, Since last peak: 0.476 s
59 Heartrate: 75 bpm, value: 4237, Since last peak: 0.512 s
60 Heartrate: 75 bpm, value: 4490, Since last peak: 1.176 s
61 Heartrate: 74 bpm, value: 4372, Since last peak: 0.040 s
62 Heartrate: 74 bpm, value: 1224, Since last peak: 0.496 s ,
    WARNING. Heartintensity below minimum!
63 Heartrate: 74 bpm, value: 1164, Since last peak: 0.536 s ,
    WARNING. Heartintensity below minimum!
64 Heartrate: 74 bpm, value: 474, Since last peak: 0.896 s ,
    WARNING. Heartintensity below minimum!
65 Heartrate: 74 bpm, value: 366, Since last peak: 0.940 s ,
    WARNING. Heartintensity below minimum!
66 Heartrate: 74 bpm, value: 306, Since last peak: 1.256 s ,
    WARNING. Heartintensity below minimum!
67 Heartrate: 75 bpm, value: 443, Since last peak: 0.040 s ,
    WARNING. Heartintensity below minimum!
```

68 Heartrate: 75 bpm, value: 332, Since last peak: 0.084 s ,
WARNING. Heartintensity below minimum!

69 Heartrate: 75 bpm, value: 393, Since last peak: 0.436 s ,
WARNING. Heartintensity below minimum!

70 Heartrate: 75 bpm, value: 282, Since last peak: 0.480 s ,
WARNING. Heartintensity below minimum!

71 Heartrate: 75 bpm, value: 568, Since last peak: 0.792 s ,
WARNING. Heartintensity below minimum!

72 Heartrate: 75 bpm, value: 710, Since last peak: 0.828 s ,
WARNING. Heartintensity below minimum!

73 Heartrate: 75 bpm, value: 816, Since last peak: 1.192 s ,
WARNING. Heartintensity below minimum!

74 Heartrate: 74 bpm, value: 1261, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

75 Heartrate: 74 bpm, value: 1072, Since last peak: 0.080 s ,
WARNING. Heartintensity below minimum!

76 Heartrate: 74 bpm, value: 439, Since last peak: 0.400 s ,
WARNING. Heartintensity below minimum!

77 Heartrate: 74 bpm, value: 552, Since last peak: 0.440 s ,
WARNING. Heartintensity below minimum!

78 Heartrate: 74 bpm, value: 663, Since last peak: 0.808 s ,
WARNING. Heartintensity below minimum!

79 Heartrate: 74 bpm, value: 1289, Since last peak: 0.844 s ,
WARNING. Heartintensity below minimum!

80 Heartrate: 74 bpm, value: 716, Since last peak: 1.208 s ,
WARNING. Heartintensity below minimum!

81 Heartrate: 73 bpm, value: 1242, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

82 Heartrate: 73 bpm, value: 1076, Since last peak: 0.084 s ,
WARNING. Heartintensity below minimum!

83 Heartrate: 73 bpm, value: 1105, Since last peak: 0.444 s ,
WARNING. Heartintensity below minimum!

84 Heartrate: 73 bpm, value: 897, Since last peak: 0.484 s ,
WARNING. Heartintensity below minimum!

85 Heartrate: 73 bpm, value: 543, Since last peak: 0.808 s ,
WARNING. Heartintensity below minimum!

86 Heartrate: 73 bpm, value: 913, Since last peak: 0.844 s ,
WARNING. Heartintensity below minimum!

87 Heartrate: 73 bpm, value: 765, Since last peak: 0.884 s ,
WARNING. Heartintensity below minimum!

88 Heartrate: 73 bpm, value: 986, Since last peak: 1.244 s ,
WARNING. Heartintensity below minimum!

89 Heartrate: 73 bpm, value: 829, Since last peak: 0.368 s ,
WARNING. Heartintensity below minimum!

90 Heartrate: 73 bpm, value: 1367, Since last peak: 0.404 s ,
WARNING. Heartintensity below minimum!

91 Heartrate: 73 bpm, value: 1165, Since last peak: 0.448 s ,
WARNING. Heartintensity below minimum!

92 Heartrate: 73 bpm, value: 1003, Since last peak: 0.772 s ,
WARNING. Heartintensity below minimum!

93 Heartrate: 73 bpm, value: 1669, Since last peak: 0.808 s ,
WARNING. Heartintensity below minimum!

94 Heartrate: 73 bpm, value: 910, Since last peak: 1.212 s ,
WARNING. Heartintensity below minimum!

95 Heartrate: 73 bpm, value: 619, Since last peak: 0.048 s ,
WARNING. Heartintensity below minimum!

96 Heartrate: 73 bpm, value: 787, Since last peak: 0.368 s ,
WARNING. Heartintensity below minimum!

97 Heartrate: 73 bpm, value: 1194, Since last peak: 0.404 s ,
WARNING. Heartintensity below minimum!

98 Heartrate: 73 bpm, value: 916, Since last peak: 0.444 s ,
WARNING. Heartintensity below minimum!

99 Heartrate: 73 bpm, value: 565, Since last peak: 0.768 s ,
WARNING. Heartintensity below minimum!

100 Heartrate: 73 bpm, value: 772, Since last peak: 0.844 s ,
WARNING. Heartintensity below minimum!

101 Heartrate: 73 bpm, value: 674, Since last peak: 1.172 s ,
WARNING. Heartintensity below minimum!

102 Heartrate: 72 bpm, value: 1089, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

103 Heartrate: 72 bpm, value: 578, Since last peak: 0.408 s ,
WARNING. Heartintensity below minimum!

104 Heartrate: 72 bpm, value: 1005, Since last peak: 0.444 s ,
WARNING. Heartintensity below minimum!

105 Heartrate: 72 bpm, value: 1207, Since last peak: 0.852 s ,
WARNING. Heartintensity below minimum!

106 Heartrate: 72 bpm, value: 1142, Since last peak: 0.896 s ,
WARNING. Heartintensity below minimum!

107 Heartrate: 72 bpm, value: 520, Since last peak: 1.220 s ,
WARNING. Heartintensity below minimum!

108 Heartrate: 72 bpm, value: 804, Since last peak: 0.044 s ,
WARNING. Heartintensity below minimum!

109 Heartrate: 72 bpm, value: 687, Since last peak: 0.088 s ,
WARNING. Heartintensity below minimum!

110 Heartrate: 72 bpm, value: 773, Since last peak: 0.412 s ,
WARNING. Heartintensity below minimum!

111 Heartrate: 72 bpm, value: 1336, Since last peak: 0.448 s ,
WARNING. Heartintensity below minimum!

112 Heartrate: 72 bpm, value: 1198, Since last peak: 0.492 s ,
WARNING. Heartintensity below minimum!

113 Heartrate: 72 bpm, value: 1059, Since last peak: 0.856 s ,
WARNING. Heartintensity below minimum!

114 Heartrate: 72 bpm, value: 712, Since last peak: 1.228 s ,
WARNING. Heartintensity below minimum!

115 Heartrate: 72 bpm, value: 1212, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

116 Heartrate: 72 bpm, value: 1085, Since last peak: 0.084 s ,
WARNING. Heartintensity below minimum!

117 Heartrate: 72 bpm, value: 829, Since last peak: 0.404 s ,
WARNING. Heartintensity below minimum!

118 Heartrate: 72 bpm, value: 1256, Since last peak: 0.444 s ,
WARNING. Heartintensity below minimum!

119 Heartrate: 72 bpm, value: 986, Since last peak: 0.484 s ,
WARNING. Heartintensity below minimum!

120 Heartrate: 72 bpm, value: 777, Since last peak: 0.812 s ,
WARNING. Heartintensity below minimum!

121 Heartrate: 72 bpm, value: 1157, Since last peak: 0.848 s ,
WARNING. Heartintensity below minimum!

122 Heartrate: 72 bpm, value: 851, Since last peak: 1.216 s ,
WARNING. Heartintensity below minimum!

123 Heartrate: 72 bpm, value: 1312, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

124 Heartrate: 72 bpm, value: 946, Since last peak: 0.408 s ,
WARNING. Heartintensity below minimum!

125 Heartrate: 72 bpm, value: 1427, Since last peak: 0.444 s ,
WARNING. Heartintensity below minimum!

126 Heartrate: 72 bpm, value: 1107, Since last peak: 0.484 s ,
WARNING. Heartintensity below minimum!

127 Heartrate: 72 bpm, value: 714, Since last peak: 0.812 s ,
WARNING. Heartintensity below minimum!

128 Heartrate: 72 bpm, value: 1027, Since last peak: 0.848 s ,
WARNING. Heartintensity below minimum!

129 Heartrate: 72 bpm, value: 778, Since last peak: 0.892 s ,
WARNING. Heartintensity below minimum!

130 Heartrate: 72 bpm, value: 946, Since last peak: 1.224 s ,
WARNING. Heartintensity below minimum!

131 Heartrate: 72 bpm, value: 1490, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

132 Heartrate: 72 bpm, value: 1238, Since last peak: 0.084 s ,
WARNING. Heartintensity below minimum!

133 Heartrate: 72 bpm, value: 567, Since last peak: 0.412 s ,
WARNING. Heartintensity below minimum!

134 Heartrate: 72 bpm, value: 787, Since last peak: 0.452 s ,
WARNING. Heartintensity below minimum!

135 Heartrate: 72 bpm, value: 578, Since last peak: 0.496 s ,
WARNING. Heartintensity below minimum!

136 Heartrate: 72 bpm, value: 545, Since last peak: 0.824 s ,
WARNING. Heartintensity below minimum!

137 Heartrate: 72 bpm, value: 906, Since last peak: 0.856 s ,
WARNING. Heartintensity below minimum!

138 Heartrate: 72 bpm, value: 638, Since last peak: 1.228 s ,
WARNING. Heartintensity below minimum!

139 Heartrate: 72 bpm, value: 1045, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

140 Heartrate: 72 bpm, value: 897, Since last peak: 0.080 s ,
WARNING. Heartintensity below minimum!

141 Heartrate: 72 bpm, value: 717, Since last peak: 0.412 s ,
WARNING. Heartintensity below minimum!

142 Heartrate: 72 bpm, value: 1085, Since last peak: 0.448 s ,
WARNING. Heartintensity below minimum!

143 Heartrate: 72 bpm, value: 774, Since last peak: 0.820 s ,
WARNING. Heartintensity below minimum!

144 Heartrate: 72 bpm, value: 1129, Since last peak: 0.856 s ,
WARNING. Heartintensity below minimum!

145 Heartrate: 72 bpm, value: 879, Since last peak: 0.896 s ,
WARNING. Heartintensity below minimum!

146 Heartrate: 72 bpm, value: 927, Since last peak: 1.224 s ,
WARNING. Heartintensity below minimum!

147 Heartrate: 72 bpm, value: 1461, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

148 Heartrate: 72 bpm, value: 1204, Since last peak: 0.084 s ,
WARNING. Heartintensity below minimum!

149 Heartrate: 72 bpm, value: 607, Since last peak: 0.408 s ,
WARNING. Heartintensity below minimum!

150 Heartrate: 72 bpm, value: 1032, Since last peak: 0.444 s ,
WARNING. Heartintensity below minimum!

151 Heartrate: 72 bpm, value: 895, Since last peak: 0.488 s ,
WARNING. Heartintensity below minimum!

152 Heartrate: 72 bpm, value: 744, Since last peak: 0.816 s ,
WARNING. Heartintensity below minimum!

153 Heartrate: 72 bpm, value: 997, Since last peak: 0.896 s ,
WARNING. Heartintensity below minimum!

154 Heartrate: 72 bpm, value: 1350, Since last peak: 1.260 s ,
WARNING. Heartintensity below minimum!

155 Heartrate: 72 bpm, value: 1174, Since last peak: 0.048 s ,
WARNING. Heartintensity below minimum!

156 Heartrate: 72 bpm, value: 844, Since last peak: 0.372 s ,
WARNING. Heartintensity below minimum!

157 Heartrate: 72 bpm, value: 1236, Since last peak: 0.408 s ,
WARNING. Heartintensity below minimum!

158 Heartrate: 72 bpm, value: 907, Since last peak: 0.780 s ,
WARNING. Heartintensity below minimum!

159 Heartrate: 72 bpm, value: 1412, Since last peak: 0.816 s ,
WARNING. Heartintensity below minimum!

160 Heartrate: 72 bpm, value: 1143, Since last peak: 0.856 s ,
WARNING. Heartintensity below minimum!

161 Heartrate: 72 bpm, value: 976, Since last peak: 1.192 s ,
WARNING. Heartintensity below minimum!

162 Heartrate: 73 bpm, value: 1583, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

163 Heartrate: 73 bpm, value: 1323, Since last peak: 0.084 s ,
WARNING. Heartintensity below minimum!

164 Heartrate: 73 bpm, value: 845, Since last peak: 0.412 s ,
WARNING. Heartintensity below minimum!

165 Heartrate: 73 bpm, value: 1319, Since last peak: 0.452 s ,
WARNING. Heartintensity below minimum!

166 Heartrate: 73 bpm, value: 1084, Since last peak: 0.492 s ,
WARNING. Heartintensity below minimum!

167 Heartrate: 73 bpm, value: 855, Since last peak: 0.820 s ,
WARNING. Heartintensity below minimum!

168 Heartrate: 73 bpm, value: 1289, Since last peak: 0.856 s ,
WARNING. Heartintensity below minimum!

169 Heartrate: 73 bpm, value: 1004, Since last peak: 0.900 s ,
WARNING. Heartintensity below minimum!

170 Heartrate: 73 bpm, value: 692, Since last peak: 1.224 s ,
WARNING. Heartintensity below minimum!

171 Heartrate: 73 bpm, value: 1108, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

172 Heartrate: 73 bpm, value: 1136, Since last peak: 0.452 s ,
WARNING. Heartintensity below minimum!

173 Heartrate: 73 bpm, value: 1009, Since last peak: 0.496 s ,
WARNING. Heartintensity below minimum!

174 Heartrate: 73 bpm, value: 1342, Since last peak: 0.860 s ,
WARNING. Heartintensity below minimum!

175 Heartrate: 73 bpm, value: 1138, Since last peak: 0.904 s ,
WARNING. Heartintensity below minimum!

176 Heartrate: 73 bpm, value: 926, Since last peak: 1.232 s ,
WARNING. Heartintensity below minimum!

177 Heartrate: 73 bpm, value: 1390, Since last peak: 0.040 s ,
WARNING. Heartintensity below minimum!

```

178 Heartrate: 73 bpm, value: 1101, Since last peak: 0.084 s ,
    WARNING. Heartintensity below minimum!
179 Heartrate: 73 bpm, value: 1820, Since last peak: 0.452 s ,
    WARNING. Heartintensity below minimum!
180 Heartrate: 73 bpm, value: 1498, Since last peak: 0.496 s ,
    WARNING. Heartintensity below minimum!
181 Heartrate: 73 bpm, value: 867, Since last peak: 0.824 s ,
    WARNING. Heartintensity below minimum!
182 Heartrate: 73 bpm, value: 1348, Since last peak: 0.860 s ,
    WARNING. Heartintensity below minimum!
183 Heartrate: 73 bpm, value: 1116, Since last peak: 0.908 s ,
    WARNING. Heartintensity below minimum!

```

C Sourcecode - introductory exercises

C.1 ReadFromFile

Below is the sourcecode for the introductory-exercise (From september the 4th)
- more precisely, the ReadFromFile source-code.

```

1 #include <stdio.h>
2
3 int main(void)
4 {
5     printf("Hey, I'm reading a file!\n");
6
7     static const char filename[] = "ECG.txt";
8     FILE *file = fopen ( filename , "r");
9     int line , rVal;
10    int max;
11
12    rVal = fscanf(file , "%i" , &line);
13    max = line;
14
15    while(rVal != EOF) {
16
17        rVal = fscanf(file , "%i" , &line);
18        if (max < line) {
19            printf("Found a new larger number: %i\n" , line
20                );
21            max=line;
22        }
23    }
24 }

```



```

23     printf("Finally, this is the largest number: %i\n", max)
        ;
24     return 0;
25 }

```

C.2 HelloWorld

The next is the sourcecode from the same exercise - this time, it's the sourcecode of our HelloWorld program.

```

1 #include <stdio.h>
2
3 /*
4  * Created by Bastian Buch, s113432, and Jacob Gjerstrup,
5  * s113440
6  */
7 int main (void){
8     printf("Hello world!");
9     return 0;
10 }

```

D Sourcecode - the real program

Below follows the sourcecode for each of the parts of our program, split into sections. The first part, the program, is where the various functions are called, and all our data is stored. The Filter.c contains the 5 different filters. The RPeakDetection contains the detection of each peak, along with the calculations of the various thresholds. The sensor is what scans data from the file, and thus simulates that we scan the patient, and finally, the header files is what contains all the prototypes for our functions.

D.1 Buffer

```

1 #include <stdio.h>
2 #include "buffer.h"
3
4 // Bufferindex
5 int pushData(BUFFER* buffer, int data)
6 {

```

```
7      //printf(" Buffer::pushData: Adding stuff to the buffer
      !: %i\n", data);
8      (*buffer).Data[( *buffer).counter] = data;
9      incrementCounter( buffer );
10
11     return 0;
12 }
13
14
15 // Getting values based on index offset
16 // compared to current buffer counter
17 int readData(BUFFER* buffer , int offset)
18 {
19     int index = getIndex( buffer , offset );
20     return (*buffer).Data[index];
21 }
22
23
24 void incrementCounter(BUFFER* buffer)
25 {
26     (*buffer).counter++;
27     if (( *buffer).counter >= BUFFERSIZE) {
28         (*buffer).counter -= BUFFERSIZE;
29     }
30 }
31
32
33 int getIndex(BUFFER *buffer , int offset) {
34     int index = (*buffer).counter - offset -1;
35     if (index < 0){
36         index = index+BUFFERSIZE;
37     }
38
39     return index;
40 }
```

D.2 Filters

```
1 #include <stdlib.h>
2 #include <stdio.h>
3 #include "buffer.h"
4
5
6
7 int lowPass2(BUFFER* inputBuffer , BUFFER* filtered) {
```

```
8      /*
9      *   GroupDelay: 25 ms
10     */
11
12     // Retrieving values
13     int x = readData(inputBuffer , 0);
14     int x6 = readData(inputBuffer , 6);
15     int x12 = readData(inputBuffer , 12);
16     int y1 = readData(filtered , 0);
17     int y2 = readData(filtered , 1);
18
19     // Filter math
20     int y = (2*y1-y2) + ((x - 2*x6 + x12) / 32);
21
22     // pushing data back to buffer object
23     pushData(filtered , y);
24
25     return 0;
26 }
27
28
29 int highPass2(BUFFER* inputBuffer , BUFFER* filtered) {
30     /*
31     *   GroupDelay: 80 ms
32     */
33
34     // Retrieving values
35     int x = readData(inputBuffer , 0);
36     int x16 = readData(inputBuffer , 16);
37     int x17 = readData(inputBuffer , 17);
38     int x32 = readData(inputBuffer , 32);
39     int y1 = readData(filtered , 0);
40
41     // Filter math
42     int y = y1-(x/32)+x16-x17+(x32/32);
43
44     // Pushing data back to buffer object
45     pushData(filtered , y);
46
47     return 0;
48 }
49
50
51 int derivative2(BUFFER* inputBuffer , BUFFER* filtered) {
```

```
52     /*
53     *   GroupDelay: 10 ms
54     */
55
56     // Retrieving values
57     int x = readData(inputBuffer , 0);
58     int x1 = readData(inputBuffer , 1);
59     int x3 = readData(inputBuffer , 3);
60     int x4 = readData(inputBuffer , 4);
61
62     // Filter math
63     int y = (2*x+x1-x3-2*x4) / 8;
64
65     // Pushing data back to buffer object
66     pushData(filtered , y);
67
68     return 0;
69 }
70
71
72 int squaring2(BUFFER* inputBuffer , BUFFER* filtered) {
73     /*
74     *   GroupDelay: 0 ms
75     */
76
77     // Retrieving values
78     int x = readData(inputBuffer , 0);
79
80     // Filter math
81     int y = x*x;
82
83     // Pushing data back to buffer object
84     pushData(filtered , y);
85
86     return 0;
87 }
88
89
90 int mwInt2(BUFFER* inputBuffer , BUFFER* filtered) {
91     /*
92     *   GroupDelay: 72.5 ms
93     */
94
95     int N = 30;
```

```
96
97     // Dynamic Retrieving of values
98     int i = 0;
99     int sum = 0;
100
101     for (i = 0; i < N; i++) {
102         sum += readData(inputBuffer , i);
103     }
104
105     // Filter math
106     int y = sum / N;
107
108     // Pushing data back to buffer object
109     pushData(filtered , y);
110
111     return 0;
112 }
```

D.3 RPeakDetection

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 #define MINSAMPLES 3 // Minimum number of samples before
   updating variables
5 #define VERBOSE 1
6
7 struct PEAK {
8     int clock;           // If older than buffer size cannot
   be reevaluated
9     int type;           // -1 noise , 0 peak, 1 R-peak, 2
   regular R-peak
10    int value;           // speaks for itself
11    struct PEAK *next;
12 };
13
14
15 struct PEAK *head = NULL;
16 struct PEAK *curr = NULL;
17
18
19 int RR_AVERAGE1 = 250;
20 int RR_AVERAGE2 = 250;
21 int RR_LOW = 100;
22 int RR_HIGH = 200;
```

```
23 int RR_MISS = 400;
24
25 int SPKF = 0;
26 int NPKF = 0;
27 int THRESHOLD1 = 2000;
28 int THRESHOLD2 = 0;
29
30 int missed_peaks = 0;
31
32
33
34 // Adding node to beginning of list
35 struct PEAK* add_to_peaks(int clock, int val, int type) {
36
37     struct PEAK *ptr = (struct PEAK*)malloc(sizeof(struct
        PEAK));
38
39     ptr->value = val;
40     ptr->clock = clock;
41     ptr->type = type;
42     ptr->next = NULL;
43
44     if(NULL == head) head = curr = ptr;
45     else {
46         ptr->next = head;
47         head = ptr;
48     }
49     return ptr;
50 }
51
52
53
54
55
56
57
58
59
60 int peak_prev_clock(int type)
61 {
62     struct PEAK *ptr = head;
63     ptr = ptr->next; // Skipping current element
64     while (NULL != ptr){
65         if (ptr->type == type) {
```

```
66         return ptr->clock;
67     };
68     ptr = ptr->next;
69 }
70 return 0;
71 }
72
73
74
75
76
77 int peak_sumOfType(int type)
78 {
79     struct PEAK *ptr = head;
80     int count = 0;
81     while (NULL != ptr){
82         if (ptr->type >= type) {
83             count++;
84         };
85         ptr = ptr->next;
86     }
87     return count;
88 }
89
90
91
92 struct PEAK* peak_searchback()
93 {
94     struct PEAK *ptr = head;
95
96
97     int i = 0;
98
99     while (NULL != ptr){
100         i++;
101         if (ptr->type >= 0) {
102             if (ptr->value > THRESHOLD2) {
103                 ptr->type = 2;
104                 printf("Searchback 'ed %i levels deep\n", i)
105                     ;
106                 return ptr;
107             }
108         }
109     }
110 }
```

```
109         ptr = ptr->next;
110     }
111     return NULL;
112 }
113
114
115
116 int peak_average_interval(int type, int amount)
117 {
118     struct PEAK *ptr = head;
119     if (NULL != ptr) {
120         int clock = ptr->clock;
121
122         int clockSum = 0;
123         int i = 0;
124         ptr = ptr->next;
125         while (NULL != ptr){
126             if (ptr->type >= type) {
127                 int newClock = ptr->clock;
128                 int tempDiff = clock - newClock;
129
130                 clockSum += tempDiff; // Summing value of
131                                     found peaks
132                 clock = newClock;
133                 i++;
134             };
135             if (amount == i) break;
136             ptr = ptr->next;
137         }
138         if (i) {
139             int avg = clockSum/i;
140             return avg;
141         }
142     }
143     return 0;
144 }
145
146
147
148
149
150
151 void update_RpeakVariables(struct PEAK* ptr) {
```

```

152 // get latest 8 RR-intervals
153 if (NULL != ptr) {
154     int peakVal = ptr->value;
155     SPKF = 0.125 * peakVal + 0.875 * NPKF;
156     RR_AVERAGE2 = peak_average_interval(2, 8);
157     RR_AVERAGE1 = peak_average_interval(1, 8);
158     RR_LOW = 0.92 * RR_AVERAGE2;
159     RR_HIGH = 1.16 * RR_AVERAGE2;
160     RR_MISS = 1.66 * RR_AVERAGE2;
161     THRESHOLD1 = NPKF + 0.25 * (SPKF-NPKF);
162
163     if (VERBOSE > 1){
164         printf("SPKF: %i\nRR_AVERAGE2: %i\nRR_AVERAGE1:
165                %i\nRR_LOW: %i\nRR_HIGH: %i\nRR_MISS: %i\n
166                nTHRESHOLD1: %i\n",
167                SPKF,
168                RR_AVERAGE2,
169                RR_AVERAGE1,
170                RR_LOW,
171                RR_HIGH,
172                RR_MISS,
173                THRESHOLD1);
174     }
175 }
176 else printf("ERROR: update_RpeakVariables::input_ptr ==
177            NULL\n");
178
179 return;
180 }
181
182 void update_searchbackVariables(struct PEAK* ptr) {
183     // get latest 8 RR-intervals
184     if (NULL != ptr) {
185         int peakVal = ptr->value;
186         SPKF = 0.25 * peakVal + 0.75 * SPKF;
187         RR_AVERAGE1 = peak_average_interval(1, 8);
188         RR_LOW = 0.92 * RR_AVERAGE1;
189         RR_HIGH = 1.16 * RR_AVERAGE1;
190         RR_MISS = 1.66 * RR_AVERAGE1;
191
192         THRESHOLD1 = NPKF + 0.25 * (SPKF-NPKF);
193         THRESHOLD2 = 0.5 * THRESHOLD1;
194     }
195 }

```

```
193         if (VERBOSE > 1){
194             printf("\nUpdate_searchbackVariables:\nSPKF: %i
                \nRR_AVERAGE1: %i\nRR_AVERAGE2: %i\nRR_LOW: %i
                i\nRR_HIGH: %i\nRR_MISS: %i\nTHRESHOLD1: %i\n
                nTHRESHOLD2: %i\n" ,
195                 SPKF,
196                 RR_AVERAGE1,
197                 RR_AVERAGE2,
198                 RR_LOW,
199                 RR_HIGH,
200                 RR_MISS,
201                 THRESHOLD1,
202                 THRESHOLD2);
203         }
204     }
205     else {
206         printf("ERROR: update_searchbackVariables::input_ptr
                ==_NULL\n");
207     }
208     return;
209 }
210
211
212
213 void update_thresholdVariables( struct PEAK* ptr ) {
214     if (NULL != ptr) {
215         int peakVal = ptr->value;
216         NPKF = 0.125 * peakVal + 0.875 * NPKF;
217         THRESHOLD1 = NPKF + 0.25 * (SPKF - NPKF);
218         THRESHOLD2 = 0.5 * THRESHOLD1;
219     }
220     else printf("ERROR: update_thresholdVariables::input_
                ptr ==_NULL\n");
221
222     return;
223 }
224
225
226 /***** Sampling 3 points on each side of test-point *****/
227 int checkPeak(int samples[]) {
228
229     if ( samples[0] < samples[1] &&
230         samples[1] < samples[2] &&
231         samples[2] < samples[3] &&
```

```
232         samples[3] > samples[4] &&
233         samples[4] > samples[5] &&
234         samples[5] > samples[6] ) return 1;
235
236     /*
237     if (
238         samples[2] < samples[3] &&
239         samples[3] > samples[4] ) return 1;*/
240     return 0;
241 }
242
243
244
245
246
247
248 int RRcalculate(int x1, int samples[], int clock)
249 {
250
251     struct PEAK *ptr = NULL;
252
253     // Checks for peak
254     if ( checkPeak(samples) ) {
255         ptr = add_to_peaks(clock-1, x1, 0); // Point is a
                peak. Save in list , type 0
256
257         if (ptr->value > THRESHOLD1) {
258             ptr->type = 1; // Classifying as R-peak
259
260
261             //printf("clock: %i , r-peak val: %i\n", clock
                -1, x1);
262             int lastClock = peak_prev_clock(2);
263             int timediff = clock - lastClock;
264
265
266             /***** USER output *****/
267             // For every R-peak print this:
268             if (VERBOSE == 1) {
269                 printf("Heart rate: %3i bpm, Intensity: %4i ,
                \nLast peak: %.3fs", (int) (1.0/
                RRAVERAGE2*60.0*250.0), x1, timediff
                /250.0);
```

```

270         //printf(" Heartrate: %3i bpm, value: %4i ,
           Since last peak: %i s", (RR_AVERAGE2*60)
           /250, x1, timediff);
271     if (x1 < 2000) printf("###_Heartintensity
           _below _minimum! _###");
272     if (missed_peaks > 5) printf("###_Missed _
           more _than _5 _peaks . _Dude, _you 're _dying! _###
           ");
273     printf("\n");
274 }
275 else if (VERBOSE == 0) {
276     FILE *file;
277     file = fopen("output.txt", "a+");
278     fprintf(file, " Heartrate: _%3i _bpm, _Intencity
           : _%4i , _Last _peak: _%.3fs", (int) (1.0/
           RR_AVERAGE2*60.0*250.0), x1, timediff
           /250.0);
279     if (x1 < 2000) fprintf(file, ", _WARNING. _
           Heartintensity _below _minimum!");
280     fprintf(file, "\n");
281     fclose(file);
282 }
283 /*****/
284
285
286 if (RR_LOW < timediff && timediff < RR_HIGH ) {
287     if (missed_peaks > 0) missed_peaks--;
288
289     ptr->type = 2; // Classify as regular R-
           peak
290     // Only updating variables if more than
           MINSAMPLES are available
291
292     if (peak_sumOfType(2) >= MINSAMPLES) {
293         update_RpeakVariables( ptr );
294     }
295 }
296 else if (RR_MISS < timediff){
297     // searchback
298     update_searchbackVariables( peak_searchback
           () );
299 }
300 else {
301     if (missed_peaks < 10) missed_peaks++;

```

```
302         }
303     }
304     else {
305         update_thresholdVariables( ptr );
306     }
307 }
308 return 0;
309 }
310
311
312
313
314 /* Function for determining size of PEAK array */
315 int sizeof_peaks() {
316     struct PEAK *ptr = head;
317     int size = 0;
318     int i = 0;
319
320     while(ptr != NULL)
321     {
322         size += sizeof(struct PEAK);
323         ptr = ptr->next;
324         i++;
325     }
326     printf("Size of stuff: %i\n", size);
327     printf("elements in peak: %i\n", i);
328
329 }
330
331
332
333
334
335
336 /****** Mainly for testing purposes *****/
337 void print_list(void)
338 {
339     struct PEAK *ptr = head;
340
341     printf("\n————Printing list Start————\n");
342     while(ptr != NULL)
343     {
344         printf("\ntime: %i , Value: %d\n", ptr->clock , ptr->
            value);
```

```

345     ptr = ptr->next;
346 }
347 printf("\n————Printing list End————\n");
348
349     return;
350 }
351
352
353
354 void print_latest(int backwards)
355 /*
356  * Prints the latest [backwards] number of peaks in list
357  * Latest first
358  */
359 {
360     struct PEAK *ptr = head;
361
362     int i;
363     for (i=0; i<backwards; i++){
364         if(NULL == ptr) {
365             break;
366         }
367         printf("\ntime: %i, Value: %d, type: %i\n", ptr->
                 clock, ptr->value, ptr->type);
368         ptr = ptr->next;
369     }
370     return;
371 }

```

D.4 Sensor

```

1  /*
2  * Todo:
3  *   Restricting speed to 250 requests pr second
4  *
5  *
6  *
7  */
8
9  #include <stdio.h>
10 #include <stdlib.h>
11 #include "sensor.h"
12
13 // returning INT16_MAX will terminate main loop.
14 int getNextData(FILE *file){

```

```
15
16     signed int line = 0;
17     if( file == NULL){
18         printf("sensor.c::getNextData_--couldnt_open_file_--
           Terminating");
19         return INT16_MAX;
20     }
21
22     fscanf( file ,"%i",&line);
23
24     if (feof( file )) {
25         printf("sensor.c::getNextData_--Reached_EOF_--
           Terminating\n");
26         fclose( file );
27         return INT16_MAX;
28     }
29     return line;
30 }
```

D.5 Header files

D.5.1 sensor.h

Below is the first of the header files, called sensor.h. This file contains the prototype for the sensor as well as the peak detection.

```
1 #ifndef ADD_H_GUARD
2 #define ADD_H_GUARD
3 #define INT16_MAX 1 << 16
4 int getNextData(FILE *file);
5 #endif
```

D.5.2 buffer.h

After this one, the next header file called filter.h comes - this file contains the prototypes of the filters as well as for the buffer.

```
1 #define BUFFERSIZE 33
2
3 typedef struct {
4     int Data[BUFFERSIZE];
5     unsigned int counter;
6 } BUFFER;
```

```
7
8 int pushData(BUFFER* buffer , int data);
9 void incrementCounter(BUFFER* buffer);
10 int getIndex(BUFFER* buffer , int offset);
11 int readData(BUFFER* buffer , int offset);
12
13 int lowPass2(BUFFER* inputBuffer , BUFFER* filtered);
14 int highPass2(BUFFER* inputBuffer , BUFFER* filtered);
15 int derivative2(BUFFER* inputBuffer , BUFFER* filtered);
16 int squaring2(BUFFER* inputBuffer , BUFFER* filtered);
17 int mwInt2(BUFFER* inputBuffer , BUFFER* filtered);
```

D.6 Tests

```
1 #include <stdio.h>
2 #include <stdlib.h>
3 #include "sensor.h"
4 #include "buffer.h"
5
6 void testing(int choice , char inputpath[] , char comparepath
7             []) {
8     FILE *inputfile = fopen ( inputpath , "r");
9     FILE *comparefile = fopen ( comparepath , "r");
10
11     BUFFER buff_source = {{0}, 0};
12     BUFFER buff_filtered = {{0}, 0};
13
14     int errorFound = 0;
15     int lineNumber = 0;
16     int ran = 0;
17
18
19     int inputdata = getNextData(inputfile);
20     int comparedata = getNextData(comparefile);
21
22
23
24     while(inputdata != INT16_MAX && comparedata !=
25           INT16_MAX) {
26         lineNumber++;
27         pushData(&buff_source , inputdata);
28         switch (choice) {
```

```
28         case 1: lowPass2(&buff_source , &buff_filtered);
29             break;
30         case 2: highPass2(&buff_source , &buff_filtered)
31             ; break;
32         case 3: derivative2(&buff_source , &
33             buff_filtered); break;
34         case 4: squaring2(&buff_source , &buff_filtered)
35             ; break;
36         case 5: mwInt2(&buff_source , &buff_filtered);
37             break;
38     }
39
40     int filterVal = readData(&buff_filtered , 0);
41     if (filterVal != comparedata) {
42         printf("Value_mismatch_on_line_%i_filtered:_%i
43             ,_comparedata:_%i\n", lineNumber , filterVal ,
44             comparedata);
45         errorFound++;
46     }
47     inputdata = getNextData(inputfile);
48     comparedata = getNextData(comparefile);
49     ran = 1;
50 }
51
52 if (!errorFound && ran) printf("No_errors_found..You're
53     _clear_for_takeoff\nComparing_input:_%s_with_file:_%s
54     \n\n", inputpath , comparepath);
55 else if (!ran) printf("Didn't_run..No_conclusion\n\n");
56 else printf("ERROR:_%i_value-mismatch_found\nComparing_
57     input:_%s_with_file:_%s\n\n", errorFound , inputpath ,
58     comparepath);
59
60 return;
61 }
62
63 int main() {
64     testing(1, "Datafiles/ECG.txt", "Datafiles/x_low.txt");
```

```
60     testing(2, "Datafiles/x_low.txt", "Datafiles/x_high.txt"
61             );
62     testing(3, "Datafiles/x_high.txt", "Datafiles/x_der.txt"
63             );
64     testing(4, "Datafiles/x_der.txt", "Datafiles/x_sqr.txt")
65             ;
66     testing(5, "Datafiles/x_sqr.txt", "Datafiles/
        x_mwi_div_after.txt");
67
68     return 0;
69 }
```