PSScript Script Lifecycle And Support Suite

Last updated: April 29, 2026.

This document is the professional training and support playbook for script design and management in PSScript. It is written for script authors, reviewers, admins, and support staff working against the hosted Netlify and Supabase production architecture.

Executive Summary

PSScript manages PowerShell script work through a governed lifecycle:

1. Design the script with clear intent, safe parameters, examples, and test expectations.
2. Upload the script to the hosted app with accurate metadata.
3. Review the script detail page for identity, ownership, category, tags, and version state.
4. Run or review AI analysis using the current criteria payload.
5. Remediate findings and document accepted risk.
6. Export a PDF report for evidence.
7. Search and reuse approved patterns through keyword, vector, documentation, and assistant workflows.
8. Delete or bulk-delete only disposable test data or approved records.
9. Support issues with screenshots, deploy evidence, Netlify Function logs, and Supabase logs.



Source Guidance Used

The April 2026 training model is aligned with:

- Microsoft PowerShell publishing guidance: use PSScriptAnalyzer, include documentation and examples, include tests, sign code where appropriate, and use semantic versioning. Source: https://learn.microsoft.com/en-us/powershell/gallery/concepts/publishing-guidelines?view=powershellget-3.x
- Netlify Functions guidance: UI and Functions are deployed together, Functions are immutable per deploy, and buffered synchronous Functions have request and response payload limits. Source: https://docs.netlify.com/build/functions/overview/
- Supabase RLS guidance: Supabase maps requests to `anon` and `authenticated` Postgres roles and policies should be explicit for those roles. Source: https://supabase.com/docs/guides/database/postgres/row-level-security
- Supabase production checklist: enable RLS, SSL enforcement, MFA, backups, and performance/security review before production operations. Source: https://supabase.com/docs/guides/deployment/going-into-prod

Roles

Role	Primary work	Evidence they produce
Script author	Design, upload, metadata, remediation	Script file, tags, description, analysis result
Reviewer	Security, quality, operational fit	Findings, remediation notes, approval decision
Admin	Access approval, data maintenance, deploy health	User state, backup records, deploy id, logs
Support	Reproduction, triage, escalation	Screenshots, route, payload status, timestamps

Lifecycle Standard

Stage	Goal	App surface	Completion evidence
1. Intake	Define problem, owner, environment, and risk	Outside app plus Scripts	Intake note or ticket
2. Design	Write safe PowerShell with examples and test plan	Upload preparation	`.ps1` script, comments, sample usage
3. Upload	Store script in hosted Supabase through Netlify API	Upload	Script record with metadata
4. Review	Validate metadata, ownership, and version state	Scripts and script detail	Screenshot or script id
5. Analyze	Score security, quality, maintainability, and risk	Analysis	Criteria version, score, findings
6. Remediate	Fix findings or record accepted risk	Analysis and detail	Updated script or risk note
7. Export	Produce portable evidence	Analysis PDF export	PDF file, not JSON
8. Discover	Reuse patterns safely	Search, docs, chat, assistant	Search result or assistant transcript
9. Govern	Track health, trends, and cleanup	Analytics and Settings	Backup, cleanup, audit notes
10. Support	Resolve incidents using hosted evidence	Support workflow	Reproduction, logs, resolution

Script Design Checklist

Use this checklist before upload:

- Name functions with approved PowerShell Verb-Noun style when possible.
- Include comment-based help for reusable scripts.
- Provide examples for important parameters.
- Avoid hardcoded secrets, tokens, tenant IDs, and environment-specific paths.
- Use parameter validation for required user input.

- Prefer `SupportsShouldProcess` for operations that modify or delete resources.
- Include safe defaults and clear failure behavior.
- Add tests or manual verification steps for the expected environment.
- Run static analysis when available and document any accepted findings.
- Record owner, system, category, and operational impact in metadata.

Upload And Metadata Standard



Required metadata:

Field	Standard
Title	Clear script name, preferably Verb-Noun for script/function identity
Description	One or two sentences that explain purpose and operational impact
Category	Current taxonomy value used by the app
Tags	Technology, team, system, risk, and lifecycle tags
Owner	Team or person accountable for future changes
Version note	What changed and why, when re-uploading

Hosted uploads are intentionally capped at 4 MB in the UI. Larger scripts should be split, compressed into documented release artifacts outside this app, or reviewed for embedded binary/content misuse.

AI Analysis Standard



Reviewers should read analysis output in this order:

1. Criteria version and confidence.
2. Security score and critical findings.
3. Quality and maintainability findings.
4. Remediation recommendations.
5. Testing recommendations.
6. PDF export result.

An analysis is not complete until the reviewer can answer:

- What are the highest-risk behaviors?
- What should be fixed before execution?
- What risk is accepted, by whom, and why?
- Does the downloaded report open as a PDF?

Search And Reuse Standard



Use search to avoid rewriting unsafe or duplicate scripts:

- Keyword search for known cmdlets, systems, ticket identifiers, and tags.
- Vector search for intent-based discovery.
- Documentation search for policy and implementation context.
- Assistant workflows for explanation, remediation ideas, and review summaries.

Search results are advisory. Reviewers still validate the actual script, metadata, and analysis result before reuse.

Delete And Cleanup Standard



Delete behavior must be intentional:

- Delete only disposable test records or records approved for removal.
- Confirm the script id, title, owner, and environment before deletion.
- Use bulk delete only after selecting the exact target records.
- For data maintenance cleanup, create or confirm a backup first.

- Attach support evidence when deletion fails: route, response status, script ids, user role, and timestamp.

Support Operating Model



Every support case should include:

- Route and production or deploy-preview URL.
- Active user role and whether the account is enabled.
- Screenshot of the failed state.
- Exact reproduction steps.
- Netlify deploy id and Function log window.
- Supabase Auth/database log window for data, auth, upload, delete, backup, or RLS issues.
- Expected behavior and actual behavior.



Lab Sequence

Lab	Lifecycle coverage
Lab 01	Design, upload, metadata, analysis, PDF export
Lab 02	Search, similarity, reuse, and duplicate avoidance
Lab 03	Documentation and assistant-assisted review
Lab 04	Analytics, health, deploy, and governance checks
Lab 05	Support evidence, deletion, cleanup, and escalation

Completion Criteria

A trainee completes the lifecycle when they can:

- Explain why hosted Supabase is the database of record.
- Upload a safe script with complete metadata.
- Interpret the analysis criteria, scores, findings, remediation, and confidence.
- Export a PDF and verify it is not JSON.
- Use search and assistant workflows without treating AI output as final approval.

- Delete test data safely and prove cleanup.
- Collect enough support evidence for an admin or developer to reproduce a hosted issue.

Generated 2026-04-29 14:08 UTC