SFWR ENG 3F03 Summary

Author: Kemal Ahmed Instructor: Dr. Ned² Date: Winter 2014

Please join GitHub and contribute to this document. There is a guide on how to do this on my GitHub.

UNIX Commands

UNIX commands are a set of commands saved on UNIX systems that let you perform many tasks that you may want to execute.

There are a number of ways you can run UNIX commands:

- **Terminal**: a program that is shell that runs commands as they are manually entered
- Bash files are scripts that automate the execution of a number of UNIX commands
 - o Represented by .sh

Regular Expressions

Regular expressions (regexp) are one of the most important thing to know in terms of knowing how to use UNIX commands, especially learning how to use the **Kleene star** [*].

Remember from SE 2FA3 (for the tron kids who never took that course)

...commands continued

When you first open your terminal, it says your username followed by " ~". This is because the tilde represents your username. It's redundant to say the same name multiple times.

In this document, I will represent a field by \$field\$, where the word in between the two percent signs will represent the description of what should go in the field

%command% -%option(s)% %target%
you can stack options, too
e.g. list files in directory: ls
options:

- r: reverse order
- 1: display modified date and permissions
- t: sort by modified date
- a: hidden files
- more on the man page

all options:

ls -ltr Documents/Dropbox

Notice how the target is Documents/Dropbox, although the full directory name would be /user/Documents/Dropbox

This is because the default present working directory (pwd) is /user/
From a given current working directory, it is assumed (unless specified) that you are referring to a directory in the pwd.

The default lowest drive name is /

%command% man: gives the man page, which explains what the command does and hopefully all the options and what they do.

\$%variable%: retrieves the value of a variable, whereas normally without the \$ it would be interpreted as a file/directory

There are some variables made by default, known as environment variables:

- pwd: variable that holds your present working directory
 - o it is also a command that is the equivalent of echo \$pwd
 - o for some reason, echo \$pwd doesn't work properly in terminal
- HOME: variable that holds the location of your home folder, i.e. where are all your personal user files saved

View all your environment variables by the command printenv.

To store a value in a variable, simply do: %variable name% = %value%

Sometimes you may have folders or files with spaces in them. Unfortunately, each word will usually be treated as a different file. To avoid this, cluster everything in quotations, e.g. "My Documents/ENG III/SFWR ENG 3F03/a1.sh"

cd %target%: change working directory to the target

echo: prints the value of the variable or word in the terminal

mv: moves file, a.k.a. "cut"

cut %target%: extracts parts of a line of input, usually a file

- -c %character min #%-%char max #% %file%: extracts characters min to max from each line in a file
- if you don't include a max #, it will extract to the end of the line; if you don't include a min #, it will extract from the beginning of the line
- -d'%delimiter%': parses

cp %source% %target%: copies files and directories from source to target; if the target doesn't exist, it is created options:

• -r or -R: recursively copies, i.e. includes sub-directories if it's a folder

- -H: doesn't actually copy the directory by having 2 versions of the same data, but rather makes a **symbolic link**, which means it just creates another pointer to the same location. Note: this is different from a shortcut because a shortcut is a program that opens the folder from a different location, whereas a symbolic link works as if it is a folder and can even be worked from
 - o e.g. if I make a symbolic link of my directory, phone, and call it mobile, I can cd into phone OR mobile

find: finds a file options:

- -maxdepth %n%: only look inside n-1 levels of directories (i.e. n, including pwd)
- -mtime %days%: find a file modified within a certain day range. Here are the definitions of the day ranges (1 day = 24 hours, ignore Gregorian days):
 - o 0: past 1 day (now-1 < date < now)
 - o -%n%: modified less than n days ago (now-n < date ≤ now)
 - +%n%: modified more than n days ago (date < now-n)
 - o n: modified on the day n days ago (now-n-1 < date < now-n)
 - You can also stack conditions, like if you want to find a date that is between 3-5 days ago, you could say: -mtime +5 -mtime -3
- -mmin %minutes%: same as mtime, but instead of day range, it is minute range
- -name %name%: finds a file of a given name
- -type %type%: find a file of a given type
 - o d: directory
 - o f: file
 - o 1: symlink
 - o s: socket

wc: prints the number of words, new lines, and bytes in a file

sed: string processing:

- reads a line from a file into a buffer
- executes the command(s) on the buffer
- outputs the buffer to the standard output

If you push any data, you MUST pop it, since terminal does not have the garbage collection necessary to avoid that.

Remember <u>SFWR ENG 3GA3</u>? When calling a label (i.e. function), the address of the label will be pushed onto the stack and saved in RA (Return Address). "Return" will pop the return address from the stack.

nm: gives you the functions inside an object file Undefined functions are functions called, but not located within the file, such as standard functions, e.g. printf scanf: inputs string with the formatting tags of printf

lea: load effective address

which %command%: shows the location of where the command is stored

printf: prints and formats using regular sets as well as its own set of commands; it doesn't know the number of arguments

ps: gives you a list of your running tasks as well as the PID for each (Process IDentification number)

```
kill -%signal #% %PID%: terminates a process
```

chmod: this lets you change permissions for files. There are 3 types of permissions: read, write, and execute. There are also 3 groups of users you can change the permissions to: owner, group, and other. To change the permissions for a file you need to enter the appropriate code. Use this to determine the code.

If you remove execute permissions to yourself of a directory, you can create files in the directory, list contents (ls), and list permissions of the contents (ls -l). However, you cannot change into the directory (cd).

You can save the result of a command in a file:

%command% > %target file name, inc. extension%

This is especially useful when concatenating two files:
cat file1.c file2.o > file3.txt

Two accents (>>) instead of one (>) will open the file after the command is executed.

Pipelining: ?

Conditional Blocks

conditional blocks are ended with fi:
if %condition 1%
%command set 1%
else %condition 2%
%command set 2%
fi

Most conditions use the test command: if test %condition% OR the equivalent is using square brackets: if [%condition%]

Some comparisons include:

• OR: %cond1% -0 %cond2%

• AND: %cond1% -a %cond2% • file exists and is readable: -r %file% • file exists and is writable: -w %file% • checks if it is a directory (as opposed to a file): -d %file% • checks if it is a file (as opposed to a directory): -f %file% • file size > 0: -s %file% case \$%case% %value 1 of case%) %command 1% ;; %value 2 of case%) %command 2% ;; esac **Loop Examples** for i in \$files echo "Echoing file name: " \$i done COUNTER=0 while [\$COUNTER -lt 10]; do echo The counter is \$COUNTER let COUNTER=COUNTER+1 done

Extra Bash Stuff

Start every bash script with the following line: #!/bin/bash Bash debug mode should begin with: #!/bin/sh -x

One of the useful parts of bash files is that you can execute functions.

If users add arguments when executing the script in command line, some default variables include:

- \$0: name of the script
- \$1: argument 1
- \$2: arg 2
- etc.
- \$FILES: a set containing all arguments

You can make files that identify things that run before each shell:

- .bashrc: while user is logging in
- .bashrc_profile: while user is opening a shell

Makefiles

Makefile is a utility that compiles a set of source code (usually a project), like a shell-script extension of bash, since it uses UNIX commands. This is especially useful for large projects. Use

Makefiles to automate removing libraries from directory before using SVN. It is useful for any type of source that can be compiled with bash, but the most common application is compiling C/C++ source code.

If you have multiple files in a project that refer to one another, such as objects, you usually compile them into their individual object files. However, they don't actually refer to anything other than symbols, until you use an overall compiler to join them into one main executable. Makefiles can compile and will also join the files together.

Whatever format you use to save the source for the Makefile, you'll need to compile that, using the command:

```
make -f MyMakefile
```

Similar to bash, signify different elements in a list using spaces

Declare:

- LIBS: folders
- INCLUDE PATH:

Simply running the make command in the shell will run the first target in the file.

Makefiles have executable sections, similar to functions, known as **targets**. Each target is saved as an executable, so when you run a target, it'll only run it if you don't have a file that already has that name. When you execute a target, you run off a directory. To execute a target from the shell, run:

```
make target
```

However, if you want a function that does not save as executable, such as "all", at the very top above the variables, put

```
.PHONY all
```

If you have multiple executables you want to compile simultaneously, place a target called "all" at the top of your file that refers to each of your targets (one for each project)

Access Makefile variables with \$(var_name) Access bash variables with \$\$var_name

```
Compile using: gcc -c *.c -I../
```

This means: use the c-compiler from gcc on all c files (although you could just specify which file(s)) that are Included in the given directory

The compiled files have the extension .o

You'll need to move all the object files to one central location before you make your executable from them.

You should also include a section to remove your previous files, called "clean"

inc represents a library

driver.c calls assembly files

include a target called clean that deletes all the files and is only activated when make clean is run.

Processor Information

There are two main processors we're going to look at:

- 8086
- 80386+
- 80286

Registers

8086: Real Mode

Memory $\leq 2^{20}$ bytes = 1MB

16 × selector + offset ← optimization of finding the address

16-bit registers:

- General Purpose:
 - o Other Registers: AX, BX, CX, DX
 - Accumulator, Base, Counter, Data
 - all can be decomposed into an upper and lower part, e.g. AX = [AH|AL] (Higher and Lower part)
 - o Index registers: SI, DI
 - Source, **D**estination
 - o Pointers to data in the machine language stack: **B**P, **S**P
 - Base, top of Stack
- Segment registers:
 - o *CS*, *DS*, *SS*, *ES*
 - o Code, Data, Stack, Extra
- IP: Instruction Pointer, address of next instruction to be executed
- FLAGS: a register with bits that store results of operations and processor state
 - o ZF: zero flag
 - Unsigned integers
 - CF: carry flag
 - Signed integers
 - OF: overflow flag (1 if overflow)
 - SF: sign flag (1 if negative)

Each register's address is saved

Selector: is an index into a descriptor table

- segment register
- segments are useful if you don't have enough RAM

Offset:

Non-unique address

80386+:

- 32-bit registers: (Extended)
 - o EAX, EBX, ECX, EDX
 - o ESI, EDI: Source, Destination
 - o EBP, ESP, EIP
 - Base Pointer
 - Stack Pointer
 - Index Pointer
- 16-bit registers:
 - o General segment registers: FS, GS

80286:

- processor arrangement that is used by Windows, Mac, and Linux
- segments (files) not at fixed positions, since
- segments are simply referenced from a descriptor table
- segments moved between virtual memory, memory, and disk as necessary
- segments can only be 4GB
- segments divided into 4K pages

Assembly Files

There are many ways of implementing Assembly language. We'll learn NASM.

The assembly language we use is similar to that of MIPS (from SFWR ENG 3GA3) in terms of its syntax:

%mnemonic (a.k.a. command)% %operator(s)%

Assembly files are saved under the extension .asm

Comment using semicolon ';'

Approach: initially think in pseudo code, then translate it into assembly to make it faster

Some Commands

Most of the commands are in terms of a **source** and a **destination**. The source can either be an **immediate** (number directly specified in the command), an implied value (such as i++, which is implied to have a source value of 1), or a memory variable. However, the destination must be a variable. Also, **variables** could either refer to a register or memory location. I'll explain what each command means in terms of source and destination so you'll get a better understanding of what each of the terms mean in each context.

Immediates are denoted by the \$ operator

```
add %destination%, %source%: destination = destination + source
sub %destination%, %source%: destination = destination - source
inc %destination%: destination++
dec %destination%: destination—
mov %destination%, %source%:

    both destination and source cannot be memory locations

   • both dest & src must have the same size (# bits)
mul ??: multiply for unsigned integers
imul ???: same as mul, but for signed integers
div ??: divide for unsigned integers
idiv ??: same as div, but for signed integers
cmp %?%, %?%: flags?: compares the two numbers by doing a – b and seeing if the zero flag = 1
jmp $label$: jump unconditionally to the specified label (function)?
call $label$: branch unconditionally to the specified label (like goto label?)
jump vs branch?
jxx %option% %label%: branch if flags?? otherwise continues to next statement
Note that the options for jxx don't have a '-', like bash commands
   • near: (default) jump within segment
          o 32-bit label
   • short: jump is?
   • word: 16-bit label
   • far: outside of segment
ptr?
Common Segments
Some segments you should include are (in order):
   • segment .data: define initialized variables here
   • segment .bss: define uninitialized variables here
```

Directives

directive assembler and not CPU? some applications include:

segment .text: place the commands and code and everything else here

- define constants
- define memory to store data?
- group memory into segments
- conditionally include source code?
- include other files

equ: defines a constant symbol, i.e. cannot be re-defined later

syntax: %symbol name% equ %value%

put '%' at the beginning of each line with pre-processor directives, which is different from C, which denotes them with a '#'

syntax: %%descriptor% %symbol name% %value% descriptors:

- include: include other files by replacing the assembled code with the file itself
- define: defines a **symbol** that <u>can</u> be re-defined later

(sorry that I use that symbol for all fields, but it's more clear than italics, like they do in the text, because I can put spaces, e.g. %any field% and %any% %field% could both be interpreted as: *any field*.)

Data Directives

Data directives (DD) are used in segments to define/reserve room for memory. There are 2 types of data directives:

- resx: uninitialized room that is the specified size
- dx: initialized room that is the size of the input

The 'x' in each is selected as one of the following letters:

Unit	Letter	Size	
byte	b	1B; 4b	
word	W	2B; 8b	
double word	d	4B; 16b	
quad word	đ	8B; 32b	
ten bytes	t	10B; 40b	

Define each directive with a label

syntax: %label% %type% %value% example: L1 resb 100

(100 uninitialized bytes labeled L1)

Note: the values of each dx can be multiple number systems, so it is necessary to identify which number system you are using, unless you want to initialize it to 0.

Number system	Symbol
Binary	b
Octal	0
Hexadecimal	h

Syntax: %value% type%

Example: L6 dd 1A92h; double word initialized to hex 1A92

You can use either "double" or 'single' quotes to identify characters/strings of characters.

Faster way to make eax 0 would be:

```
xor eax, eax
```

Reliance on a C Driver

Learning to program in assembly helps gain a deeper understanding of how computers work. It also helps better understand compilers and high level languages, such as C.

We'll need a C driver to do many things in assembly, including to:

- call assembly functions
- initialize all segments and registers
- I/O

Compiling

The driver file can be named anything except for that of your assembly file. Let's call the driver file driver.c and the assembly file first.asm (because that's the example Ned² gave.

- 1. Compile assembly source: nasm -f elf first.asm
 - a. elf: Executable and Linkable File
 - i. specifies that elf is the prefered executable type, similar to .exe for Windows
 - b. produces compiled object file: first.o
 - c. -d ELF_TYPE: ELF_TYPE is a variable that is similar to define?
- 2. Compile C driver: gcc -c driver.c
 - a. -c: compile only
 - b. produces driver.o
 - c. -m32: enforces 32-bit code if compiling on 64-bit system
 - d. -pg: compile link, profiling
 - i. creates gmon.out
 - ii. run gprof on this executable
 - iii. kprof: application that does profiling
- 3. Link the 2 compiled object files: gcc -o first driver.o first.o asm_io.o
 - a. -o %output file name%: gives a name to the output file
 - i. If not specified, default name is: a.out
- 4. Debug your code by **splicing**, using: dump_regs %choose random, unique dump number%.

Pointers compared to C

C

Variables

static: only in file

local: in block where declared, don't use for recursion, but may take up space otherwise

global: everywhere in file or any other file (if not static)

volatile: prevents compiler from optimizing

Dynamic

```
int *a = malloc(n*sizeof(int))
stack grows
free(a) 

malloc: simply reserves a piece of memory
calloc: zeroes everything within the given memory
memset:
```

Operators

*%variable%: **pointer**: returns pointer of variable &%variable%: **reference**: returns address of variable

Arrays

```
Making a pointer array:
int a = 1;
int b = 2;

int * pointer[2] = {&a, &b};
printf(*pointer[0]) //1
printf(*pointer[1]) //2
```

Other stuff

Personal Questions

Why do you need interrupts when gam

Table of Contents

NIX Commands]
Regular Expressions	4
commands continued	
Conditional Blocks	4
Loop Examples	4

Extra Bash Stuff	5
Makefiles	5
Processor Information	7
Registers	7
Assembly Files	8
Some Commands	8
Common Segments	9
Directives	9
Data Directives	10
Reliance on a C Driver	11
Compiling	11
Pointers compared to C	11
C	12
Variables	12
Dynamic	12
Operators	12
Arrays	12
Other stuff	12
Personal Questions	12
Shifts	13
Profiling	13

ing if you know that the person will be gaming? Why don't you just put all the "interrupts" on a different core?

Shifts

Shifts are in bytes:

%number% %arrows% %number of bytes%

int a = 1;

a << 3; a leftward shift of 3 bytes, so first convert to hex 10001h

0008h

Profiling

Profiling: time it takes to run certain segments of your code

Some of them even provide information about memory efficiency (but not all of them) Memory leaks

Code coverage:

Loop-unrolling: reducing number of loops by including more steps in each loop. This allows for better load-sharing over multiple cores