Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

All Rules

This article contains all Stellar Cyber rules, including SigmaHQ rules and rules developed internally by Stellar Cyber. The rules are listed alphabetically by their rule ID.

Due to silent or deleted rules, the rule IDs are not sequential.

Active Directory (AD) Rule IDs

Rule Details: Active Directory MachineAccountQuota Compromise

MachineAccountQuota is an attribute in Active Directory that specifies how many machine accounts a user can create in the domain. Compromise of MachineAccountQuota occurs when an attacker abuses this privilege to create unauthorised machine accounts. Machine accounts are assigned credentials, just like user accounts. Attackers can extract the credentials (password hashes) for further use. These accounts can then be used for other malicious purposes, often bypassing standard account monitoring mechanisms.

Rule ID

```
ad_machineAccountQuota_compromise
```

Query

```
{'selection': {'EventID': [4741, 4720], 'TargetUserName|endswith': '$'}, 'condition':
 'selection | count() by SubjectUserName > 3', 'timeframe': '15m'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1136

References

- https://rootguard.gitbo/cyberops/detection-engineering/ad-attack-detections-and-mitigations/machineaccountquota-compromise

Severity

50

Suppression Logic Based On

- event_data.SubjectUserName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/06/13	medium	• False positives are possible if multiple machine accounts are created by legitimate users. We recommend excluding trusted service accounts or administrators. However, limiting the ability of non-privileged users to register devices is highly recommended.

Amazon Web Services (AWS) Rule IDs

Rule Details: Restore Public AWS RDS Instance

Detects the recovery of a new public database instance from a snapshot. It may be a part of data exfiltration.

Rule ID

`aws_1`

Query

```
{'selection_source': {'eventSource': 'rds.amazonaws.com', 'responseElements_publiclyAccessible': True, 'eventName': 'RestoreDBInstanceFromDBSnapshot'}, 'condition': 'selection_source'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,c3f265c7-ff03-4056-8ab2-d486227b4599

Author: faloker

Tactics, Techniques, and Procedures

TA0010, T1020

References

- https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/rds__explore_snapshots/main.py

Severity

75

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/02/12	high	• Unknown

Rule Details: AWS User Login Profile Was Modified

An attacker with the iam:UpdateLoginProfile permission on other users can change the password used to login to the AWS console on any user that already has a login profile setup. With this alert, it is used to detect anyone is changing password on behalf of other users.

Rule ID

`aws_2`

Query

```
{'selection_source': {'eventSource': 'iam.amazonaws.com', 'eventName': 'UpdateLoginProfile'}, 'filter': {'userIdentity_arn|contains': 'requestParameters.userName'}, 'condition': 'selection_source and not filter'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,055fb148-60f8-462d-ad16-26926ce050f1

Author: toffeebr33k

Tactics, Techniques, and Procedures

TA0003, T1098

References

- https://github.com/RhinoSecurityLabs/AWS-IAM-Privilege-Escalation

Severity

75

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName

- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/09	high	• Legit User Account Administration

Rule Details: SES Identity Has Been Deleted

Detects an instance of an SES identity being deleted via the "DeleteIdentity" event. This may be an indicator of an adversary removing the account that carried out suspicious or malicious activities.

Rule ID

`aws_3`

Query

```
{'selection': {'eventSource': 'ses.amazonaws.com', 'eventName': 'DeleteIdentity'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,20f754db-d025-4a8f-9d74-e0037e999a9a

Author: Janantha Marasinghe

Tactics, Techniques, and Procedures

TA0005, T1070

References

- https://unit42.paloaltonetworks.com/compromised-cloud-compute-credentials/

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/13	medium	• Unknown

Rule Details: AWS GuardDuty Important Change

Detects updates of the GuardDuty list of trusted IPs, perhaps to disable security alerts against malicious IPs.

Rule ID

`aws_4`

Query

```
{'selection_source': {'eventSource': 'guardduty.amazonaws.com', 'eventName': 'CreateIPSet'}, 'condition': 'selection_source'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,6e61ee20-ce00-4f8d-8aee-bedd8216f7e3

Author: faloker

Tactics, Techniques, and Procedures

TA0005, T1562.001

References

- https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/guardduty__whitelist_ip/main.py#L9

Severity

75

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/02/11	high	• Valid change in the GuardDuty (e.g. to ignore internal scanners)

Rule Details: AWS Glue Development Endpoint Activity

Detects possible suspicious glue development endpoint activity.

Rule ID

`aws_5`

Query

```
{'selection': {'eventSource': 'glue.amazonaws.com', 'eventName': ['CreateDevEndpoint', 'DeleteDevEndpoint', 'UpdateDevEndpoint']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber AWS configured f

- AWS Cloudtrail

Rule Source

SigmaHQ,4990c2e3-f4b8-45e3-bc3c-30b14ff0ed26

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0004, T1078

References

- https://rhinosecuritylabs.com/aws/aws-privilege-escalation-methods-mitigation/
- https://docs.aws.amazon.com/glue/latest/webapi/API_CreateDevEndpoint.html

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/10/03	low	• Glue Development Endpoint Activity may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Potential Bucket Enumeration on AWS

Looks for potential enumeration of AWS buckets via ListBuckets.

Rule ID

`aws_6`

Query

```
{'selection': {'eventSource': 'ec2.amazonaws.com', 'eventName': 'ListBuckets'}, 'filter': {'type': 'AssumedRole'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,f305fd62-beca-47da-ad95-7690a0620084

Author: Christopher Peacock @[redacted]urepeacock, SCYTHE @scythe_io

Tactics, Techniques, and Procedures

TA0007, T1580

References

- https://github.com/Lifka/hacking-resources/blob/c2ae355d381bd0c9f0b32c4ead049f44e5b1573f/cloud-hacking-cheat-sheets.md
- https://jamesonhacking.blogspot.com/2020/12/pivoting-to-private-aws-s3-buckets.html
- https://securitycafe.ro/2022/12/14/aws-enumeration-part-ii-practical-enumeration/

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/06	low	• Administrators listing buckets, it may be necessary to filter out users who commonly conduct this activity.

Rule Details: AWS ECS Backdoor Task Definition

Detects when an Elastic Container Service (ECS) Task Definition has been modified and run. This can indicate an adversary adding a backdoor to establish persistence or escalate privileges. This rule is based on examining events created upon execution of Rhino Security Lab's Pacu in a lab environment.

Rule ID

`aws_7`

Query

```
{'selection': {'eventSource': 'ecs.amazonaws.com', 'eventName': ['DescribeTaskDefinition', 'RegisterTaskDefinition', 'RunTask'], 'requestParameters_containerDefinitions_command|contains|all': ['169.254', '$AWS_CONTAINER_CREDENTIALS']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,b94bf91e-c2bf-4047-9c43-c6810f43baad

Author: Darin Smith

Tactics, Techniques, and Procedures

TA0003, T1525

References

- https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/ecs__backdoor_task_def/main.py
- https://docs.aws.amazon.com/AmazonECS/latest/APIReference/API_RegisterTaskDefinition.html

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/07	medium	• Task Definition being modified to request credentials from the Task Metadata Service for valid reasons

Rule Details: AWS EC2 Startup Shell Script Change

Detects changes to the EC2 instance startup script. The shell script will be executed as root/SYSTEM every time the specific instances are booted up.

Rule ID

`aws_8`

Query

```
{'selection_source': {'eventSource': 'ec2.amazonaws.com', 'requestParameters_attribute': 'userData', 'eventName': 'ModifyInstanceAttribute'}, 'condition': 'selection_source'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,1ab3c5ed-5baf-417b-bb6b-78ca33f6c3df

Author: faloker

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/ec2__startup_shell_script/main.py#L9

Severity

75

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/02/12	high	• Valid changes to the startup script

Rule Details: AWS Attached Malicious Lambda Layer

Detects when an user attached a Lambda layer to an existing function to override a library that is in use by the function, where their malicious code could utilize the function's IAM role for AWS API calls. This would give an adversary access to the privileges associated with the Lambda service role that is attached to that function.

Rule ID

`aws_9`

Query

```
{'selection': {'eventSource': 'lambda.amazonaws.com', 'eventName|startswith': 'Update FunctionConfiguration'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,97fbabf8-8e1b-47a2-b7d5-a418d2b95e3d

Author: Austin Songer

Tactics, Techniques, and Procedures

TA0004, T1548

References

- https://docs.aws.amaz[image_ref id="1" box="0.343,0.057,0.387,0.089"]om/lambda/latest/dg/API_UpdateFunctionConfiguration.html

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/23	medium	• Lambda Layer being attached may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Lambda Layer being attached from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS EKS Cluster Created or Deleted

Identifies when an EKS cluster is created or deleted.

Rule ID

`aws_10`

Query

```
{'selection': {'eventSource': 'eks.amazonaws.com', 'eventName': ['CreateCluster', 'DeleteCluster']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,33d50d03-20ec-4b74-a74e-1e65a38af1c0

Author: Austin Songer

Tactics, Techniques, and Procedures

TA0040, T1485

References

- https://any-api.com/amazonaws_com/eks/docs/API_Description

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/16	low	• EKS Cluster being created or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • EKS Cluster created or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS S3 Data Management Tampering

Detects when a user tampers with S3 data management in Amazon Web Services.

Rule ID

`aws_11`

Query

```
{'selection': {'eventSource': 's3.amazonaws.com', 'eventName': ['PutBucketLogging', 'PutBucketWebsite', 'PutEncryptionConfiguration', 'PutLifecycleConfiguration', 'PutReplicationConfiguration', 'ReplicateObject', 'RestoreObject']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,78b3756a-7804-4ef7-8555-7b9024a02e2d

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0010, T1537

References

- https://github.com/elastic/detection-rules/pull/1145/files
- https://docs.aws.amazon.com/AmazonS3/latest/API/API_Operations.html
- https://docs.aws.amazon.com/AmazonS3/latest/API/API_PutBucketLogging.html
- https://docs.aws.amazon.com/AmazonS3/latest/API/API_PutBucketWebsite.html
- https://docs.aws.amazon.com/AmazonS3/latest/API/API_PutBucketEncryption.html

- https://docs.aws.amazon.com/AmazonS3/latest/userguide/setting-repl-config-perm-overview.html
- https://docs.aws.amazon.com/AmazonS3/latest/API/API_RestoreObject.html

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/24	low	• A S3 configuration change may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. S3 configuration change from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Root Credentials

Detects AWS root account usage.

Rule ID

`aws_12`

Query

```
{'selection1': {'eventSource': 'signin.amazonaws.com'}, 'selection_usertype': {'userIdentity_type': 'Root'}, 'selection_eventtype': {'eventType': 'AwsServiceEvent'}, 'condition': 'selection1 and selection_usertype and not selection_eventtype'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,8ad1600d-e9dc-4251-b0ee-a65268f29add

Author: vitaliy0x1

Tactics, Techniques, and Procedures

TA0003, T1078.004

References

- https://docs.aws.amazon.com/IAM/latest/UserGuide/id_root-user.html

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/01/21	medium	• AWS Tasks That Require AWS Account Root User Credentials https://docs.aws.amazon.com/general/latest/gr/aws_tasks-that-require-root.html

Rule Details: AWS IAM Backdoor Users Keys

Detects AWS API key creation for a user by another user. Backdoored users can be used to obtain persistence in the AWS environment. Also with this alert, you can detect a flow of AWS keys in your org.

Rule ID

`aws_13`

Query

```
{'selection_source': {'eventSource': 'iam.amazonaws.com', 'eventName': 'CreateAccessKey'}, 'filter': {'userIdentity_arn|contains': 'responseElements.accessKey.userName'}, 'condition': 'selection_source and not filter'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,0a5177f4-6ca9-44c2-aacf-d3f3d8b6e4d2

Author: faloker

Tactics, Techniques, and Procedures

TA0003, T1098

References

- https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/iam__backdoor_users_keys/main.py

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName

- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/02/12	medium	• Adding user keys to their own accounts (the filter cannot cover all possible variants of user naming) • AWS API keys legitimate exchange workflows

Rule Details: AWS RDS Master Password Change

Detects the change of database master password. It may be a part of data exfiltration.

Rule ID

`aws_14`

Query


```
{'selection_source': {'eventSource': 'rds.amazonaws.com', 'responseElements_pendingModifiedValues_masterUserPassword|contains': '*', 'eventName': 'ModifyDBInstance'}, 'condition': 'selection_source'}
```


Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,8a63cdd4-6207-414a-85bc-7e032bd3c1a2

Author: faloker

Tactics, Techniques, and Procedures

TA0010, T1020

References

- https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/rds__explore_snapshots/main.py

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/02/12	medium	• Benign changes to a db instance

Rule Details: AWS SecurityHub Findings Evasion

Detects the modification of the findings on SecurityHub.

Rule ID

`aws_15`

Query

```
{'selection': {'eventSource': 'securityhub.amazonaws.com', 'eventName': ['BatchUpdate
Findings', 'DeleteInsight', 'UpdateFindings', 'UpdateInsight']}, 'condition': 'select
ion'}
```

Log Source

Stellar Cyber AWS configured for:

- AWS Cloudtrail

Rule Source

SigmaHQ,a607e1fe-74bf-4440-a3ec-b059b9103157

Author: Sittikorn S

Tactics, Techniques, and Procedures

TA0005, T1562

References

- https://docs.aws.amazon.com/cli/latest/reference/securityhub/

Severity

75

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2021/06/28	high	• System or Network administrator behaviors • DEV, UAT, SAT environment. You should apply this rule with PROD environment only.

Rule Details: AWS GuardDuty Detector Deletion

Identifies the deletion of an Amazon GuardDuty detector. Upon deletion, GuardDuty stops monitoring the environment and all existing findings are lost.

Rule ID

`aws_16`

Query

```
{'selection1': {'eventSource': 'guardduty.amazonaws.com'}, 'selection2': {'eventName'
: 'DeleteDetector'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References

N/A

Severity

75

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/28	high	• The GuardDuty detector may be deleted by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Detector deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Route Table Created

Identifies when an AWS Route Table has been created.

Rule ID

`aws_18`

Query

```
{'selection1': {'eventSource': 'cloudtrail.amazonaws.com'}, 'selection2': {'eventName
': ['CreateRoute', 'CreateRouteTable']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar  er

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/06/05	low	• Route Tables may be created by a system or network administrators. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Route Table creation by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. Automated processes that use Terraform may lead to false positives.

Rule Details: AWS RDS Snapshot Export

Identifies the export of an Amazon Relational Database Service (RDS) Aurora database snapshot.

Rule ID

```
aws_21
```

Query

```
{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'StartExportTask'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0010, T1567

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/06/06	low	• Exporting snapshots may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Snapshot exports from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS ElastiCache Security Group Created

Identifies when an ElastiCache security group has been created.

Rule ID

`aws_22`

Query

```
{'selection1': {'eventSource': 'elasticache.amazonaws.com'}, 'selection2': {'eventName': 'Create Cache Security Group'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/07/19	low	• A ElastiCache security group may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Security group creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS IAM User Addition to Group

Identifies the addition of a user to a specified group in AWS Identity and Access Management (IAM).

Rule ID

`aws_24`

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'AddUserToGroup'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/04	low	• Adding users to a specified group may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. User additions from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS IAM Password Recovery Requested

Identifies AWS IAM password recovery requests. An adversary may attempt to gain unauthorized AWS access by abusing password recovery mechanisms.

Rule ID

`aws_25`

Query

```
{'selection1': {'eventSource': 'signin.amazonaws.com'}, 'selection2': {'eventName': '
PasswordRecoveryRequested'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1078

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/07/02	low	• Verify whether the user identity, user agent, and/or hostname should be requesting changes in your environment. Password reset attempts from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS IAM Group Creation

Identifies the creation of a group in AWS Identity and Access Management (IAM). Groups specify permissions for multiple users. Any user in a group automatically has the permissions that are assigned to the group.

Rule ID

`aws_26`

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'Cre
ateGroup'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured. 

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1136

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/05	low	• A group may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Group creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS EventBridge Rule Disabled or Deleted

Identifies when a user has disabled or deleted an EventBridge rule. This activity can result in an unintended loss of visibility in applications or a break in the flow with other AWS services.

Rule ID

`aws_27`

Query

```
{'selection1': {'eventSource': 'eventbridge.amazonaws.com'}, 'selection2': {'eventName': ['DeleteRule', 'DisableRule']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1489

References
N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/10/17	low	• EventBridge Rules could be deleted or disabled by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. EventBridge Rules being deleted or disabled by unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS CloudWatch Alarm Deletion

Identifies the deletion of an AWS CloudWatch alarm. An adversary may delete alarms in an attempt to evade defenses.

Rule ID

```
aws_28
```

Query

```
{'selection1': {'eventSource': 'monitoring.amazonaws.com'}, 'selection2': {'eventName': 'DeleteAlarms'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References
N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/15	medium	• Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Alarm deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Route Table Modified or Deleted

Identifies when an AWS Route Table has been modified or deleted.

Rule ID

```
aws_29
```

Query

```
{'selection1': {'eventSource': 'cloudtrail.amazonaws.com'}, 'selection2': {'eventName': ['ReplaceRoute', 'ReplaceRouteTableAssociation', 'DeleteRouteTable', 'DeleteRoute', 'DisassociateRouteTable']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/06/05	low	• Route Table could be modified or deleted by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Route Table being modified from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule. Also automated processes that use Terraform may lead to false positives.

Rule Details: AWS EC2 Network Access Control List Creation

Identifies the creation of an AWS Elastic Compute Cloud (EC2) network access control list (ACL) or an entry in a network ACL with a specified rule number.

Rule ID

```
aws_30
```

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': ['CreateNetworkAcl', 'CreateNetworkAclEntry']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1133

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/04	low	• Network ACL's may be created by a network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Network ACL creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Management Console Root Login

Identifies a successful login to the AWS Management Console by the Root user.

Rule ID

```
aws_31
```

Query

```
{'selection1': {'eventSource': 'signin.amazonaws.com'}, 'selection2': {'eventName': 'ConsoleLogin'}, 'selection3': {'userIdentity_type': 'Root'}, 'condition': 'selection1 and selection2 and selection3'}
```

Log Source

Stellar Cyber AWS configured. 

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1078

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/11	medium	• It's strongly recommended that the root user is not used for everyday tasks, including the administrative ones. Verify whether the IP address, location, and/or hostname should be logging in as root in your environment. Unfamiliar root logins should be investigated immediately. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Route53 private hosted zone associated with a VPC

Identifies when a Route53 private hosted zone has been associated with VPC.

Rule ID

`aws_32`

Query

```
{'selection1': {'eventSource': 'route53.amazonaws.com'}, 'selection2': {'eventName': 'AssociateVPCWithHostedZone'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity



25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/07/19	low	• A private hosted zone may be asssociated with a VPC by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS CloudTrail Log Updated

Identifies an update to an AWS log trail setting that specifies the delivery of log files.

Rule ID

`aws_34`

Query

```
{'selection1': {'eventSource': 'cloudtrail.amazonaws.com'}, 'selection2': {'eventName': 'UpdateTrail'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1530, TA0040, T1565

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/10	low	• Trail updates may be made by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Trail updates from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Route 53 Domain Transfer Lock Disabled

Identifies when a transfer lock was removed from a Route 53 domain. It is recommended to refrain from performing this action unless intending to transfer the domain to a different registrar.

Rule ID

```
aws_35
```

Query

```
{'selection1': {'eventSource': 'route53.amazonaws.com'}, 'selection2': {'eventName': 'DisableDomainTransferLock'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/05/10	low	• A domain transfer lock may be disabled by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Activity from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS RDS Cluster Creation

Identifies the creation of a new Amazon Relational Database Service (RDS) Aurora DB cluster or global database spread across multiple regions.

Rule ID

`aws_36`

Query

`{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': ['CreateDBCluster', 'CreateGlobalCluster']}, 'condition': 'selection1 and selection2'}`

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1133

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/20	low	• Valid clusters may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Cluster creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS S3 Bucket Configuration Deletion

Identifies the deletion of various Amazon Simple Storage Service (S3) bucket configuration components.

Rule ID

`aws_37`

Query

`{'selection1': {'eventSource': 's3.amazonaws.com'}, 'selection2': {'eventName': ['DeleteBucketPolicy', 'DeleteBucketReplication', 'DeleteBucketCors', 'DeleteBucketEncrypt`

ion', 'DeleteBucketLifecycle']}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1070

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/27	low	• Bucket components may be deleted by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Bucket component deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Configuration Recorder Stopped

Identifies an AWS configuration change to stop recording a designated set of resources.

Rule ID

aws_39

Query

{'selection1': {'eventSource': 'config.amazonaws.com'}, 'selection2': {'eventName': 'StopConfigurationRecorder'}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References
N/A

Severity
75

Suppression Logic Based On
- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/16	high	• Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Recording changes from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Config Resource Deletion
Identifies attempts to delete an AWS Config Service resource. An adversary may tamper with Config services in order to reduce visibility into the security posture of an account and / or its workload instances.

Rule ID
`aws_41`

Query

```
{'selection1': {'eventSource': 'config.amazonaws.com'}, 'selection2': {'eventName': [
'DeleteConfigRule', 'DeleteOrganizationConfigRule', 'DeleteConfigurationAggregator',
'DeleteConfigurationRecorder', 'DeleteConformancePack', 'DeleteOrganizationConformanc
ePack', 'DeleteDeliveryChannel', 'DeleteRemediationConfiguration', 'DeleteRetentionCo
nfiguration']}, 'condition': 'selection1 and selection2'}
```


Log Source
Stellar Cyber AWS configured.

Rule Source
Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures
TA0005, T1562

References
N/A

Severity
25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/26	low	• Privileged IAM users with security responsibilities may be expected to make changes to the Config service in order to align with local security policies and requirements. Automation, orchestration, and security tools may also make changes to the Config service, where they are used to automate setup or configuration of AWS accounts. Other kinds of user or service contexts do not commonly make changes to this service.

Rule Details: AWS IAM Assume Role Policy Update

Identifies attempts to modify an AWS IAM Assume Role Policy. An adversary may attempt to modify the AssumeRolePolicy of a misconfigured role in order to gain the privileges of that role.

Rule ID

```
aws_42
```

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'UpdateAssumeRolePolicy'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0004, T1078

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/07/06	low	• Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Policy updates from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS STS GetSessionToken Abuse

Identifies the suspicious use of GetSessionToken. Tokens could be created and used by attackers to move laterally and escalate privileges.

Rule ID

```
aws_43
```

Query

```
{'selection1': {'eventSource': 'sts.amazonaws.com'}, 'selection2': {'eventName': 'GetSessionToken'}, 'selection3': {'userIdentity_type': 'IAMUser'}, 'condition': 'selection1 and selection2 and selection3'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0004, T1548, TA0008, T1550

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/05/17	low	• GetSessionToken may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. GetSessionToken from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS IAM Deactivation of MFA Device

Identifies the deactivation of a specified multi-factor authentication (MFA) device and removes it from association with the user name for which it was originally enabled. In AWS Identity and Access Management (IAM), a device must be deactivated before it can be deleted.

Rule ID

`aws_44`

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': ['DeactivateMFADevice', 'DeleteVirtualMFADevice']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1531

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/26	medium	• A MFA device may be deactivated by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. MFA device deactivations from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS EC2 Network Access Control List Deletion

Identifies the deletion of an Amazon Elastic Compute Cloud (EC2) network access control list (ACL) or one of its ingress/egress entries.

Rule ID

`aws_45`

Query

{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': ['DeleteNetworkAcl', 'DeleteNetworkAclEntry']}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/26	medium	• Network ACL's may be deleted by a network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Network ACL deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS WAF Rule or Rule Group Deletion

Identifies the deletion of a specified AWS Web Application Firewall (WAF) rule or rule group.

Rule ID

aws_46

Query

{'selection1': {'eventSource': ['waf.amazonaws.com', 'waf-regional.amazonaws.com', 'wafv2.amazonaws.com']}, 'selection2': {'eventName': ['DeleteRule', 'DeleteRuleGroup']}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References
N/A

Severity
50

Suppression Logic Based On
- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/09	medium	• WAF rules or rule groups may be deleted by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Rule deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS ElastiCache Security Group Modified or Deleted

Identifies when an ElastiCache security group has been modified or deleted.

Rule ID
`aws_47`

Query
```
{'selection1': {'eventSource': 'elasticache.amazonaws.com'}, 'selection2': {'eventName': ['Delete Cache Security Group', 'Authorize Cache Security Group Ingress', 'Revoke Cache Security Group Ingress', 'AuthorizeCacheSecurityGroupEgress', 'RevokeCacheSecurityGroupEgress']}, 'condition': 'selection1 and selection2'}
```

Log Source
Stellar Cyber AWS configured.

Rule Source
Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures
TA0005, T1562

References
N/A

Severity
25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/07/19	low	• A ElastiCache security group deletion may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Security Group deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS WAF Access Control List Deletion

Identifies the deletion of a specified AWS Web Application Firewall (WAF) access control list.

Rule ID

```
aws_49
```

Query

```
{'selection1': {'eventSource': 'waf.amazonaws.com'}, 'selection2': {'eventName': 'DeleteWebACL'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/21	medium	• Firewall ACL's may be deleted by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Web ACL deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS IAM Group Deletion

Identifies the deletion of a specified AWS Identity and Access Management (IAM) resource group. Deleting a resource group does not delete resources that are members of the group; it only deletes the group structure.

Rule ID

```
aws_50
```

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'DeleteGroup'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1531

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/21	low	• A resource group may be deleted by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Resource group deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS EC2 Snapshot Activity

An attempt was made to modify AWS EC2 snapshot attributes. Snapshots are sometimes shared by threat actors in order to exfiltrate bulk data from an EC2 fleet. If the permissions were modified, verify the snapshot was not shared with an unauthorized or unexpected AWS account.

Rule ID

`aws_51`

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'ModifySnapshotAttribute'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0010, T1537

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/24	medium	• IAM users may occasionally share EC2 snapshots with another AWS account belonging to the same organization. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS CloudWatch Log Stream Deletion

Identifies the deletion of an AWS CloudWatch log stream, which permanently deletes all associated archived log events with the stream.

Rule ID

`aws_52`

Query

```
{'selection1': {'eventSource': 'logs.amazonaws.com'}, 'selection2': {'eventName': 'DeleteLogStream'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562, TA0040, T1485

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/20	medium	• A log stream may be deleted by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Log stream deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS SAML Activity

Identifies when SAML activity has occurred in AWS. An adversary could manipulate SAML to maintain access to the target.

Rule ID

```
aws_53
```

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com', 'eventName': 'AssumeRoleWithSAML'
}, 'selection2': {'eventSource': 'sts.amazonaws.com', 'eventName': 'UpdateSAMLProvide
r'}, 'condition': 'selection1 or selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1078, TA0005, T1550

References
N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/09/22	low	• SAML Provider could be updated by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. SAML Provider updates by unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS EC2 VM Export Failure

Identifies an attempt to export an AWS EC2 instance. A virtual machine (VM) export may indicate an attempt to extract or exfiltrate information.

Rule ID

```
aws_54
```

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'CreateInstanceExportTask'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1005, TA0010, T1537

References
N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/04/22	low	• VM exports may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. VM exports from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS CloudWatch Log Group Deletion

Identifies the deletion of a specified AWS CloudWatch log group. When a log group is deleted, all the archived log events associated with the log group are also permanently deleted.

Rule ID

`aws_55`

Query

```
{'selection1': {'eventSource': 'logs.amazonaws.com'}, 'selection2': {'eventName': 'DeleteLogGroup'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562, TA0040, T1485

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/18	medium	• Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Log group deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS KMS Customer Managed Key Disabled or Scheduled for Deletion

Identifies attempts to disable or schedule the deletion of an AWS KMS Customer Managed Key (CMK). Deleting an AWS KMS key is destructive and potentially dangerous. It deletes the key material and all metadata associated with the KMS key and is irreversible. After a KMS key is deleted, the data that was encrypted under that KMS key can no longer be decrypted, which means that data becomes unrecoverable.

Rule ID

`aws_56`

Query

```
{'selection1': {'eventSource': 'kms.amazonaws.com'}, 'selection2': {'eventName': ['DisableKey', 'ScheduleKeyDeletion']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1485

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/09/21	medium	• A KMS customer managed key may be disabled or scheduled for deletion by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Key deletions by unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS EC2 Full Network Packet Capture Detected

Identifies potential Traffic Mirroring in an Amazon Elastic Compute Cloud (EC2) instance. Traffic Mirroring is an Amazon VPC feature that you can use to copy network traffic from an Elastic network interface. This feature can potentially be abused to exfiltrate sensitive data from unencrypted internal traffic.

Rule ID

aws_57

Query



{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': ['CreateTrafficMirrorFilter', 'CreateTrafficMirrorFilterRule', 'CreateTrafficMirrorSession', 'CreateTrafficMirrorTarget']}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1074, TA0010, T1020

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/05/05	medium	• Traffic Mirroring may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Traffic Mirroring from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS EC2 Encryption Disabled

Identifies disabling of Amazon Elastic Block Store (EBS) encryption by default in the current region. Disabling encryption by default does not change the encryption status of your existing volumes.

Rule ID

aws_58

Query

{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'DisableEbsEncryptionByDefault'}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1565

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/05	medium	• Disabling encryption may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Disabling encryption by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS RDS Snapshot Restored

Identifies when an attempt was made to restore an RDS Snapshot. Snapshots are sometimes shared by threat actors in order to exfiltrate bulk data or evade detection after performing malicious activities. If the permissions were modified, verify if the snapshot was shared with an unauthorized or unexpected AWS account.

Rule ID

```
aws_59
```

Query

```
{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'RestoreDBInstanceFromDBSnapshot', 'responseElements_publiclyAccessible': False}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1578

References
N/A

Severity
50

Suppression Logic Based On
- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/06/29	medium	• Restoring snapshots may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Snapshot restoration by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS RDS Instance/Cluster Stoppage

Identifies that an Amazon Relational Database Service (RDS) cluster or instance has been stopped.

Rule ID

```
aws_60
```

Query

```
{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': ['StopDBCluster', 'StopDBInstance']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1489

References
N/A

Severity
50

Suppression Logic Based On
- service_id

- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/20	medium	• Valid clusters or instances may be stopped by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Cluster or instance stoppages from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Redshift Cluster Creation

Identifies the creation of an Amazon Redshift cluster. Unexpected creation of this cluster by a non-administrative user may indicate a permission or role issue with current users. If unexpected, the resource may not properly be configured and could introduce security vulnerabilities.

Rule ID

```
aws_61
```

Query

```
{'selection1': {'eventSource': 'redshift.amazonaws.com'}, 'selection2': {'eventName':
 'CreateCluster'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1078

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/04/12	low	• Valid clusters may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Cluster creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Route 53 Domain Transferred to Another Account

Identifies when a request has been made to transfer a Route 53 domain to another AWS account.

Rule ID

`aws_63`

Query

```
{'selection1': {'eventSource': 'route53.amazonaws.com'}, 'selection2': {'eventName': 'TransferDomainToAnotherAwsAccount'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/05/10	low	• A domain may be transferred to another AWS account by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Domain transfers from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Deletion of RDS Instance or Cluster

Identifies the deletion of an Amazon Relational Database Service (RDS) Aurora database cluster, global database cluster, or database instance.

Rule ID

aws_64

Query

```
{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': ['DeleteDBCluster', 'DeleteGlobalCluster', 'DeleteDBInstance']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1485

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/05/21	medium	• Clusters or instances may be deleted by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Cluster or instance deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS RDS Security Group Deletion

Identifies the deletion of an Amazon Relational Database Service (RDS) Security group.

Rule ID

aws_65

Query

```
{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'DeleteDBSecurityGroup'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar  er

Tactics, Techniques, and Procedures

TA0040, T1531

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/06/05	low	• An RDS security group deletion may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Security group deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS VPC Flow Logs Deletion

Identifies the deletion of one or more flow logs in AWS Elastic Compute Cloud (EC2). An adversary may delete flow logs in an attempt to evade defenses.

Rule ID

`aws_66`

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'DeleteFlowLogs'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References

N/A

Severity

75

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/06/15	high	• Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Flow log deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS EFS File System or Mount Deleted

Detects when an EFS File System or Mount is deleted. An adversary could break any file system using the mount target that is being deleted, which might disrupt instances or applications using those mounts. The mount must be deleted prior to deleting the File System, or the adversary will be unable to delete the File System.

Rule ID

```
aws_67
```

Query

```
{'selection1': {'eventSource': 'elasticfilesystem.amazonaws.com'}, 'selection2': {'eventName': ['DeleteMountTarget', 'DeleteFileSystem']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1485

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/08/27	medium	• File System or Mount being deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. File System Mount deletion by unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS RDS Instance Creation

Identifies the creation of an Amazon Relational Database Service (RDS) Aurora database instance.

Rule ID

```
aws_68
```

Query

```
{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'CreateDBInstance'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1078

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/06/06	low	• A database instance may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Instances creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: AWS Security Token Service (STS) AssumeRole Usage

Identifies the use of AssumeRole. AssumeRole returns a set of temporary security credentials that can be used to access AWS resources. An adversary could use those credentials to move laterally and escalate privileges.

Rule ID

`aws_70`

Query

```
{'selection1': {'eventSource': 'sts.amazonaws.com'}, 'selection2': {'eventName': 'AssumedRole'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0004, T1548, TA0008, T1550

References

N/A

Severity

25

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/05/17	low	• Automated processes that use Terraform may lead to false positives.

Rule Details: AWS New MFA Method Registered For User

The following analytic identifies the registration of a new Multi Factor authentication method for an AWS account. Adversaries who have obtained unauthorized access to an AWS account may register a new MFA method to maintain persistence.

Rule ID

`aws_75`

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'CreateVirtualMFADevice'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1556

References

- https://aws.amazon.com/blogs/security/you-can-now-assign-multiple-mfa-devices-in-iam/
- https://twitter.com/jhencinski/status/1618660062352007174

Severity

80

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2023-01-31	medium	• Newly onboarded users who are registering an MFA method for the first time will also trigger this detection.

Rule Details: EC2 Snapshot Attribute Modification

The following analytic utilizes AWS CloudTrail events to identify when an EC2 snapshot permissions are modified.

Rule ID

`aws_76`

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'ModifySnapshotAttribute'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0010, T1537

References

- https://labs.nettitude.com/blog/how-to-exfiltrate-aws-ec2-data/
- https://stratus-red-team.cloud/attack-techniques/AWS/aws.exfiltration.ec2-share-ebs-snapshot/
- https://hackingthe.cloud/aws/enumeration/loot_public_ebs_snapshots/

Severity

60

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2023-03-20	medium	• It is possible that an AWS admin has legitimately modified permissions of EC2 Snapshot.

Rule Details: AWS EC2 Security Group Deleted

An EC2 security group has been deleted.

Rule ID

`aws_77`

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'DeleteSecurityGroup'}, 'selection3': {'userAgent': 'cloudformation.amazonaws.com'}, 'condition': 'selection1 and selection2 and not selection3'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS EC2 Security Group Modified

An EC2 security group has been modified.

Rule ID

`aws_78`

Query


```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'DeleteRouteTable'}, 'selection3': {'eventName': 'DeleteSubnet'}, 'selection4': {'eventName': 'CreateDBSubnetGroup'}, 'selection5': {'eventName': 'DeleteDBSubnetGroup'}, 'selection6': {'eventName': 'ModifyDBSubnetGroup'}, 'selection7': {'userAgent': 'cloudformation.amazonaws.com'}, 'condition': 'selection1 and (selection2 or selection3 or selection4 or selection5 or selection6) and not selection7'}
```


Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS EC2 Security Group Created

An EC2 security group has been created.

Rule ID

`aws_79`

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'CreateSecurityGroup'}, 'selection3': {'userAgent': 'cloudformation.amazonaws.com'}, 'condition': 'selection1 and selection2 and not selection3'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS IAM User Created

A new account has been created in AWS IAM.

Rule ID

`aws_80`

Query

{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'CreateUser'}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1136

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: Created AWS IAM Credentials

New IAM credentials have been generated.

Rule ID

aws_81

Query

{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'CreateAccessKey'}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: IAM Policy Modification

The IAM policies associated with a user have been modified.

Rule ID

`aws_82`

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'UpdateUserAccessPolicy'}, 'selection3': {'eventName': 'DeleteUserAccessPolicy'}, 'selection4': {'eventName': 'AddAccessPolicyToGroup'}, 'selection5': {'eventName': 'AddUserToGroup'}, 'selection6': {'eventName': 'RemoveUsersFromGroup'}, 'condition': 'selection1 and (selection2 or selection3 or selection4 or selection5 or selection6)'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName

- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS IAM AccessDenied Discovery Event

The following detection identifies AccessDenied event. It is possible that an access key to AWS may have been stolen and is being misused to perform discovery events.

Rule ID

```
aws_83
```

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'errorCode': 'AccessDenied'}, 'selection3': {'userIdentity_type': 'IAMUser'}, 'selection4': {'userAgent': '*.amazonaws.com'}, 'condition': 'selection1 and selection2 and selection3 and not selection4'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1580

References

- https://aws.amazon.com/premiumsupport/knowledge-center/troubleshoot-iam-permission-errors/

Severity

20

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-11-12	medium	• It is possible to start this detection will need to be tuned by source IP or user.

Rule Details: AWS IAM Delete Policy

The following detection identifies when a policy is deleted on AWS. This does not identify whether successful or failed, but the error messages tell a story of suspicious attempts.

Rule ID

```
aws_84
```

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'DeletePolicy'}, 'selection3': {'userAgent': '*.amazonaws.com'}, 'condition': 'selection1 and selection2 and not selection3'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

- https://docs.aws.amazon.com/IAM/latest/APIReference/API_DeletePolicy.html
- https://docs.aws.amazon.com/cli/latest/reference/iam/delete-policy.html

Severity

20

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-04-01	medium	• This detection will require tuning to provide high fidelity detection capabilities. Tune based on src addresses (corporate offices, VPN terminations) or by groups of users. Not every user with AWS access should have permission to delete policies (least privilege). In addition, this may be saved separately and tuned for failed or success attempts only.

Rule Details: AWS IAM Failure Group Deletion

This detection identifies failure attempts to delete groups. We want to identify when a group is attempting to be deleted, but either access is denied, there is a conflict or there is no group. This is indicative of administrators performing an action, but also could be suspicious behavior occurring.

Rule ID

aws_85

Query



```
{'selection2': {'eventSource': 'iam.amazonaws.com'}, 'selection3': {'eventName': 'DeleteGroup'}, 'selection4': {'errorCode': ['NoSuchEntityException', 'DeleteConflictException']}, 'selection5': {'errorCode': 'AccessDenied'}, 'selection6': {'userAgent': '*.amazonaws.com'}, 'condition': 'selection2 and selection3 and (selection4 or selection5) and not selection6'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

- https://awscli.amazonaws.com/v2/documentation/api/latest/reference/iam/delete-group.html
- https://docs.aws.amazon.com/IAM/latest/APIReference/API_DeleteGroup.html

Severity

10

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-04-01	medium	• This detection will require tuning to provide high fidelity detection capabilities. Tune based on src addresses (corporate offices, VPN terminations) or by groups of users. Not every user with AWS access should have permission to delete groups (least privilege).

Rule Details: AWS SetDefaultPolicyVersion

This search looks for AWS CloudTrail events where a user has set a default policy versions. Attackers have been know to use this technique for Privilege Escalation in case the previous versions of the policy had permissions to access more resources than the current version of the policy.

Rule ID

aws_86

Query

```
{'selection2': {'eventName': 'SetDefaultPolicyVersion'}, 'selection3': {'eventSource'
: 'iam.amazonaws.com'}, 'condition': 'selection2 and selection3'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1078.004

References

- https://bishopfox.com/blog/privilege-escalation-in-aws
- https://rhinosecuritylabs.com/aws/aws-privilege-escalation-methods-mitigation-part-2/

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-03-02	medium	• While this search has no known false positives, it is possible that an AWS admin has legitimately set a default policy to allow a user to access all resources. That said, AWS strongly advises against granting full control to all AWS resources

Rule Details: AWS Create Policy Version to allow all resources

This search looks for AWS CloudTrail events where a user created a policy version that allows them to access any resource in their account.

Rule ID

```
aws_87
```

Query

```
{'selection2': {'eventName': 'CreatePolicyVersion'}, 'selection3': {'eventSource': 'i
am.amazonaws.com'}, 'selection4': {'errorCode': 'success'}, 'condition': 'selection2
and selection3 and selection4'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1078.004

References

- https://bishopfox.com/blog/privilege-escalation-in-aws
- https://rhinosecuritylabs.com/aws/aws-privilege-escalation-methods-mitigation-part-2/

Severity

70

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022-05-17	medium	• While this search has no known false positives, it is possible that an AWS admin has legitimately created a policy to allow a user to access all resources. That said, AWS strongly advises against granting full control to all AWS resources and you must verify this activity.

Rule Details: AWS Credential Access GetPasswordData

This detection analytic identifies GetPasswordData API call made to your AWS account. Attackers can retrieve the encrypted administrator password for a running Windows instance.

Rule ID

`aws_88`

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'GetPasswordData'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1110.001

References

- https://stratus-red-team.cloud/attack-techniques/AWS/aws.credential-access.ec2-get-password-data/

Severity

70

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022-08-10	medium	• Administrator tooling or automated scripts may make these calls

Rule Details: AWS Lambda UpdateFunctionCode

This analytic is designed to detect IAM users attempting to update/modify AWS lambda code via the AWS CLI to gain persistence, further access into AWS environment and to facilitate planting backdoors. In this instance, an attacker may upload malicious code/binary to a lambda function which will be executed automatically when the function is triggered.

Rule ID

`aws_89`

Query

```
{'selection2': {'eventSource': 'lambda.amazonaws.com'}, 'selection3': {'eventName': '
UpdateFunctionCode*'}, 'selection4': {'errorCode': 'success'}, 'selection5': {'userId
entity_type': 'IAMUser'}, 'condition': 'selection2 and selection3 and selection4 and
selection5'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1204

References

- https://sysdig.com/blog/exploit-mitigate-aws-lambdas-mitre/

Severity

70

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022-02-24	medium	• While this search has no known false positives, it is possible that an AWS admin or an authorized IAM user has updated the lambda function code legitimately.

Rule Details: AWS ECR Container Scanning Findings

This search looks for AWS CloudTrail events from AWS Elastic Container Registry (ECR) Service.

Rule ID

`aws_90`

Query

```
{'selection2': {'eventSource': 'ecr.amazonaws.com'}, 'selection3': {'eventName': 'DescribeImageScanFindings'}, 'condition': 'selection2 and selection3'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1204

References

- https://docs.aws.amazon.com/AmazonECR/latest/userguide/image-scanning.html

Severity

10

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022-08-25	medium	• unknown

Rule Details: Modification of AWS S3 Access Control List

This search detects modification of Access Control List of an S3 Bucket.

Rule ID

```
aws_92
```

Query

```
{'selection2': {'eventSource': 's3.amazonaws.com'}, 'selection3': {'eventName': 'PutBucketAcl'}, 'condition': 'selection2 and selection3'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1530

References

N/A

Severity

60

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-07-19	medium	• Unknown

Rule Details: EBS Snapshot Created

A copy of an EBS volume has been created.

Rule ID

```
aws_96
```

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'CreateSnapshots'}, 'selection3': {'eventName': 'BackupEBSVolume'}, 'condition': 'selecti
```

on1 and (selection2 or selection3)'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1074

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS RDS Snapshot Created

A copy of an AWS RDS database has been created.

Rule ID

aws_97

Query

{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'CreateDBSnapshot'}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1074

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS ELB Security Group Modified

Identifies the modification of an ELB security group.

Rule ID

`aws_98`

Query

```
{'selection1': {'eventSource': 'elasticloadbalancing.amazonaws.com'}, 'selection2': {'eventName': 'ApplySecurityGroupsToLoadBalancer'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: Update SSL Certificate Created

A new SSL certificate has been ated in your environment.

Rule ID

`aws_99`

Query


```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'Upl
oadServerCertificate'}, 'condition': 'selection1 and selection2'}
```


Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0042, T1588

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: Update SSL Certificate Deleted

A certificate used for establishing SSL connection in your environment has been deleted.

Rule ID

`aws_100`

Query


```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'Del
eteServerCertificate'}, 'condition': 'selection1 and selection2'}
```


Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0042, T1588

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS RDS Security Group Modified

A RDS security group has been modified.

Rule ID

`aws_103`

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'AuthorizeDBSecurityGroupIngress'}, 'selection3': {'eventName': 'RevokeDBSecurityGroupIngress'}, 'selection4': {'eventName': 'AuthorizeDBSecurityGroupEgress'}, 'selection5': {'eventName': 'RevokeDBSecurityGroupEgress'}, 'selection6': {'userAgent': 'cloudformation.amazonaws.com'}, 'condition': 'selection1 and (selection2 or selection3 or selection4 or selection5) and not selection6'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS VPC Network ACL Modified

The ACL for a VPC has been modified.

Rule ID

```
aws_104
```

Query

```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'Cre
ateACLEntry'}, 'selection3': {'eventName': 'DeleteACL'}, 'selection4': {'eventName':
'DeleteACLEntry'}, 'selection5': {'eventName': 'UpdateACLAssociation'}, 'selection6':
 {'userAgent': 'cloudformation.amazonaws.com'}, 'condition': 'selection1 and (selecti
on2 or selection3 or selection4 or selection5) and not selection6'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: Update VPC Mirror created

A VPC mirror session has been created.

Rule ID

`aws_107`

Query


```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'CreateTrafficMirrorSession'}, 'selection3': {'userIdentity_sessionContext_sessionIssuer_userName': ''}, 'condition': 'selection1 and selection2 and not selection3'}
```


Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1119

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: Update VPC Mirror deleted

A VPC mirror session has been deleted.

Rule ID

`aws_108`

Query


```
{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'DeleteTrafficMirrorSession'}, 'selection3': {'eventName': 'DeleteTrafficMirrorTarget'},
```

'selection4': {'eventName': 'DeleteTrafficMirrorFilter'}, 'selection5': {'userIdentity_sessionContext_sessionIssuer_userName': ''}, 'condition': 'selection1 and (selection2 or selection3 or selection4) and not selection5'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: Root access key created

An access key was created for the root account.

Rule ID

aws_109

Query

{'selection1': {'eventSource': 'cloudtrail.amazonaws.com'}, 'selection2': {'userIdentity_type': 'Root'}, 'selection3': {'eventName': 'CreateAccessKey'}, 'condition': 'selection1 and selection2 and selection3'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1078

References
N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: Federated user attempting to assume role

A federated user is attempting to assume a role. Federation users enable to manage access to AWS accounts by adding and removing users from the corporate directory, such as Microsoft Active Directory.

Rule ID

```
aws_110
```

Query

```
{'selection1': {'eventSource': 'cloudtrail.amazonaws.com'}, 'selection2': {'errorMess
age': 'Roles may not be assumed by federated users'}, 'condition': 'selection1 and se
lection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0004, T1078

References
N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	medium	N/A

Rule Details: AWS SAML Access by Provider User and Principal

This search provides specific SAML access from specific Service Provider, user and targeted principal at AWS. It also provides specific information to detect abnormal access or potential credential hijack or forgery, specially in federated environments using SAML protocol inside the perimeter or cloud provider.

Rule ID

`aws_111`

Query

```
{'selection1': {'eventSource': 'sts.amazonaws.com'}, 'selection2': {'eventName': 'AssumeRoleWithSAML'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1078

References

- https://www.cisa.gov/uscert/ncas/alerts/aa21-008a
- https://www.splunk.com/en_us/blog/security/a-golden-saml-journey-solarwinds-continued.html
- https://www.fireeye.com/content/dam/fireeye-www/blog/pdfs/wp-m-unc2452-2021-000343-01.pdf
- https://www.cyberark.com/resources/threat-research-blog/golden-saml-newly-discovered-attack-technique-forges-authentication-to-cloud-apps

Severity

80

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-01-26	medium	• Attacks using a Golden SAML or SAML assertion hijacks or forgeries are very difficult to detect as accessing cloud providers with these assertions looks exactly like normal access, however things such as source IP sourceIPAddress user, and principal targeted at receiving cloud provider along with endpoint credential access and abuse detection searches can provide the necessary context to detect these attacks.

Rule Details: AWS Defense Evasion PutBucketLifecycle

This analytic identifies `PutBucketLifecycle` events in CloudTrail logs where a user has created a new lifecycle rule for an S3 bucket with a short expiration period.

Rule ID

`aws_113`

Query

```
{'selection1': {'eventSource': 's3.amazonaws.com'}, 'selection2': {'eventName': 'PutBucketLifecycle'}, 'selection3': {'userIdentity_type': 'IAMUser'}, 'selection4': {'errorCode': 'success'}, 'condition': 'selection1 and selection2 and selection3 and selection4'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.008

References

- https://stratus-red-team.cloud/attack-techniques/AWS/aws.defense-evasion.cloudtrail-lifecycle-rule/

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022-07-25	medium	• While this search has no known false positives, it is possible that it is a legitimate admin activity. Please consider filtering out these noisy events using userAgent, user_arn field names.

Rule Details: AWS Impair Security Services

This analytic looks for several d[image_ref id="1" box="0.343,0.057,0.388,0.089"]e specific API calls made to AWS Security Services like CloudWatch, GuardDuty and Web Application Firewalls.

Rule ID

`aws_116`

Query

```
{'selection1': {'eventSource': 'cloudtrail.amazonaws.com'}, 'selection2': {'eventName': 'DeleteLogStream'}, 'selection3': {'eventName': 'DeleteDetector'}, 'selection4': {'eventName': 'DeleteIPSet'}, 'selection5': {'eventName': 'DeleteWebACL'}, 'selection6': {'eventName': 'DeleteRule'}, 'selection7': {'eventName': 'DeleteRuleGroup'}, 'selection8': {'eventName': 'DeleteLoggingConfiguration'}, 'selection9': {'eventName': 'DeleteAlarms'}, 'condition': 'selection1 and (selection2 or selection3 or selection4 or selection5 or selection6 or selection7 or selection8 or selection9)'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.008

References

- https://docs.aws.amazon.com/cli/latest/reference/guardduty/index.html
- https://docs.aws.amazon.com/cli/latest/reference/waf/index.html
- https://www.elastic.co/guide/en/security/current/prebuilt-rules.html

Severity

70

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022-07-26	medium	• While this search has no known false positives, it is possible that it is a legitimate admin activity.

Rule Details: AWS Console Login Failed During MFA Challenge

The following analytic identifies an authentication attempt event against an AWS Console that fails during the Multi Factor Authentication challenge.

Rule ID

```
aws_117
```

Query

```
{'selection1': {'eventSource': 'signin.amazonaws.com'}, 'selection2': {'eventName': '
ConsoleLogin'}, 'selection3': {'errorMessage': 'Failed authentication'}, 'selection4'
: {'additionalEventData_MFAUsed': 'Yes'}, 'condition': 'selection1 and selection2 and
 selection3 and selection4'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0042, T1586

References

- https://aws.amazon.com/what-is/mfa/

Severity

80

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022-10-03	medium	• Legitimate users may miss to reply the MFA challenge within the time window or deny it by mistake.

Rule Details: KMS Keys Creation

This search provides detection of KMS Keys Creation.

Rule ID

```
aws_118
```

Query

```
{'selection1': {'eventSource': 'kms.amazonaws.com'}, 'selection2': {'eventName': 'Cre
ateKey'}, 'selection3': {'eventName': 'PutKeyPolicy'}, 'condition': 'selection1 and (
```

selection2 or selection3)'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1486

References

- https://rhinosecuritylabs.com/aws/s3-ransomware-part-1-attack-vector/
- https://github.com/d1vious/git-wild-hunt
- https://www.youtube.com/watch?v=PgzNib37g0M

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-01-11	medium	• unknown

Rule Details: AWS CreateLoginProfile

This search looks for AWS CloudTrail events where a user A (victim A) creates a login profile.

Rule ID

aws_119

Query

{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'CreateLoginProfile'}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1136.003

References

- https://bishopfox.com/blog/privilege-escalation-in-aws
- https://rhinosecuritylabs.com/aws/aws-privilege-escalation-methods-mitigation-part-2/

Severity

90

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-07-19	medium	• While this search has no known false positives, it is possible that an AWS admin has legitimately created a login profile.

Rule Details: AWS CreateAccessKey

This search looks for AWS CloudTrail events where a user creates access keys.

Rule ID

`aws_120`

Query

```
{'selection1': {'eventSource': 'iam.amazonaws.com'}, 'selection2': {'eventName': 'CreateAccessKey'}, 'selection3': {'userAgent': 'console.amazonaws.com'}, 'selection4': {'errorCode': 'success'}, 'condition': 'selection1 and (selection2 and (not selection3) and selection4)'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1136.003

References

- https://bishopfox.com/blog/privilege-escalation-in-aws
- https://rhinosecuritylabs.com/aws/aws-privilege-escalation-methods-mitigation-part-2/

Severity

70

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- aws.errorCode
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022-03-03	medium	• Unknown

Rule Details: AWS Privilege Escalation via Group/Role/User Policy

Identifies the request for privilege escalation by modifying AWS Group/Role/User Policy

Rule ID

`aws_200`

Query


```
{'selection1': {'eventSource': 'cloudtrail.amazonaws.com', 'eventName': ['AttachGroupPolicy', 'PutGroupPolicy', 'AttachRolePolicy', 'PutRolePolicy', 'AttachUserPolicy', 'PutUserPolicy']}, 'selection2': {'requestParameters_policyArn': ['arn:aws:iam::aws:policy/AdministratorAccess', 'arn:aws:iam::aws:policy/AmazonSNSFullAccess', 'arn:aws:iam::aws:policy/AmazonEC2FullAccess', 'arn:aws:iam::aws:policy/AmazonS3FullAccess', 'arn:aws:iam::aws:policy/AmazonDynamoDBFullAccess', 'arn:aws:iam::aws:policy/AWSCodeCommitPowerUser', 'arn:aws:iam::aws:policy/AWSKeyManagementServicePowerUser', 'arn:aws:iam::aws:policy/PowerUserAccess', 'arn:aws:iam::aws:policy/DatabaseAdministrator', 'arn:aws:iam::aws:policy/NetworkAdministrator', 'arn:aws:iam::aws:policy/SystemAdministrator', 'arn:aws:iam::aws:policy/Billing']}, 'condition': 'selection1 and selection2'}
```


Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0004, T1548

References

N/A

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2023/06/22	high	• Valid changes to policy by authorized user/administrator

AWS Config Rule IDs

Rule Details: AWS High-Risk Ports Exposed to Internet

Identifies when a specified inbound (ingress) rule is added or adjusted for a VPC security group in AWS EC2 that allows traffic from any IP address to common remote access ports.

Rule ID

`aws_config_1`

Query


```
{'selection1': {'configResourceType': 'AWS::EC2::SecurityGroup'}, 'selection2': {'ipPermissions_fromPort': [22, 3389, 389, 445], 'ipPermissions_ipRanges': ['0.0.0.0/0', '::/0']}, 'condition': 'selection1 and selection2'}
```


Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.007

References

- https://www.linkedin.com/pulse/my-backdoors-your-aws-infrastructure-part-3-network-micha%C5%82-brygidyn/

Severity

50

Suppression Logic Based On

- aws.configurationItem.ARN
- aws.configurationItem.configuration.ipPermissions.fromPort
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/12/17	medium	N/A

Rule Details: Public Access in AWS S3 Bucket Policy

Detects S3 bucket policies that allow public access by granting permissions to all principals (Principal: "*"). This configuration can result in unauthorized data exposure and potential data breaches.

Rule ID

`aws_config_2`

Query

```
{'selection1': {'configResourceType': 'AWS::S3::Bucket'}, 'selection2': {'bucketPolicy_statement_principle': '*', 'bucketPolicy_statement_effect': 'Allow', 'bucketPolicy_statement_action': ['s3:GetObject']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1530

References

N/A

Severity

70

Suppression Logic Based On

- aws.configurationItem.ARN
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/12/17	high	N/A

Rule Details: AWS IAM Policy with Wildcard Privileges

Detects IAM policies that grant excessive privileges using wildcard (*) in either the Action or Resource fields. Policies with Action set to "*" or "*:*" grant full permissions to all AWS services and operations. Policies with Resource set to "*" allow actions on all resources. This violates the principle of least privilege and can lead to privilege escalation and unauthorized access to sensitive resources.

Rule ID

`aws_config_3`

Query

{'selection1': {'configResourceType': 'AWS::IAM::Policy'}, 'selection2': {'policyVersionList|contains': ["'Resource': '*'", "'Action': '*'", "'Action': '*:*'"]}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0004, T1078.004

References

N/A

Severity

70

Suppression Logic Based On

- aws.configurationItem.ARN
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/12/17	high	N/A

Rule Details: AWS Security Group Deletion Detected

Detects the deletion of AWS EC2 Security Groups. Unexpected deletion of Security Groups may indicate misconfiguration, operational errors, or malicious activity aimed at disrupting network security controls or creating gaps in security posture.

Rule ID

`aws_config_4`

Query

{'selection1': {'configResourceType': 'AWS::EC2::SecurityGroup'}, 'selection2': {'configurationItemStatus': 'ResourceDeleted'}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.007

References

N/A

Severity

50

Suppression Logic Based On

- aws.configurationItem.ARN
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/12/17	medium	N/A

Rule Details: AWS Default VPC Usage

Detects the use of AWS default VPCs. Default VPCs are automatically created by AWS in each region and come with preconfigured network settings that may not align with security best practices. They often have permissive default security groups, automatic public IP assignment, and Internet gateway configurations that can lead to unintended exposure of resources.

Rule ID

```
aws_config_5
```

Query

```
{'selection1': {'configResourceType': 'AWS::EC2::VPC'}, 'selection2': {'configuration
_isDefault': True}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1190

References

N/A

Severity

25

Suppression Logic Based On

- aws.configurationItem.ARN
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/12/17	low	N/A

Rule Details: AWS S3 Bucket Missing Server-Side Encryption

Detects S3 buckets that lack server-side encryption (SSE) configuration. Without SSE enabled, data stored in S3 buckets is vulnerable to unauthorized access if the bucket permissions are misconfigured or if physical media is compromised.

Rule ID

`aws_config_6`

Query

```
{'selection1': {'configResourceType': 'AWS::S3::Bucket'}, 'selection2': {'serverSideEncryptionConfiguration': ''}, 'selection3': {'serverSideEncryptionConfiguration_sseAlgorithm': ''}, 'condition': 'selection1 and (not selection2) and selection3'}
```

Log Source

Stellar Cyber AWS configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1530

References

N/A

Severity

50

Suppression Logic Based On

- aws.configurationItem.ARN
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/12/17	medium	N/A

Azure Rule IDs

Rule Details: Discovery Using AzureHound

Detects AzureHound (A BloodHound data collector for Microsoft Azure) activity via the default User-Agent that is used during its operation after successful authentication.

Rule ID

`azure_1`

Query

```
{'selection': {'userAgent|contains': 'azurehound', 'login_result': 'success'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra E[image_ref id="1" box="0.343,0.057,0.387,0.089"]s configured.

Rule Source

SigmaHQ,35b781cc-1a08-4a5a-80af-42fd7c315c6b

Author: Janantha Marasinghe

Tactics, Techniques, and Procedures

TA0007, T1087.004, T1526

References

- https://github.com/BloodHoundAD/AzureHound

Severity

75

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/11/27	high	• Unknown

Rule Details: Sign-in Failure Due to Conditional Access Requirements Not Met

Define a baseline threshold for failed sign-ins due to Conditional Access failures

Rule ID

`azure_3`

Query

```
{'selection': {'ResultType': 53003}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,b4a6d707-9430-4f5f-af68-0337f52d5c42

Author: Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0001, T1078.004, TA0006, T1110

References

- https://docs.microsoft.com/en-gb/azure/active-directory/fundamentals/security-operations-privileged-accounts

Severity

75

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/01	high	• Service Account misconfigured • Misconfigured Systems • Vulnerability Scanners

Rule Details: Multifactor Authentication Denied

User has indicated they haven't instigated the MFA prompt and could indicate an attacker has the password for the account.

Rule ID

`azure_4`

Query

```
{'selection': {'status_additionalDetails|contains': 'MFA denied'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,e40f4962-b02b-4192-9bfe-245f7ece1f99

Author: AlertIQ

Tactics, Techniques, and Procedures

TA0001, T1078.004, TA0006, T1110

References

- https://www.microsoft.com/security/blog/2022/03/22/dev-0537-criminal-actor-targeting-organizations-for-data-exfiltration-and-destruction/

Severity

50

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/24	medium	Users actually login but mis-click into the Deny button when MFA prompt.

Rule Details: Multifactor Authentication Interrupted

Identifies user login with multifactor authentication failures, which might be an indication an attacker has the password for the account but can't pass the MFA challenge.

Rule ID

`azure_5`

Query

```
{'selection_50074': {'ResultType': 50074}, 'selection_500121': {'ResultType': 500121}
, 'condition': '1 of selection_*'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,5496ff55-42ec-4369-81cb-00f417029e25

Author: AlertIQ

Tactics, Techniques, and Procedures

TA0001, T1078.004, TA0006, T1110

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts

Severity

50

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/10/10	medium	• Unknown

Rule Details: Account Lockout

Identifies user account which has been locked because the user tried to sign in too many times with an incorrect user ID or password.

Rule ID

`azure_6`

Query

{'selection': {'ResultType': 50053}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,2b7d6fc0-71ac-4cf7-8ed1-b5788ee5257a

Author: AlertIQ

Tactics, Techniques, and Procedures

TA0006, T1110

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts

Severity

50

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/10/10	medium	• Unknown

Rule Details: Use of Legacy Authentication Protocols

Alert on when legacy authentication has been used on an account.

Rule ID

azure_9

Query

{'selection': {'login_result': 'success', 'ClientApp': ['Other clients', 'IMAP', 'POP3', 'MAPI', 'SMTP', 'Exchange ActiveSync', 'Exchange Web Services']}, 'filter': {'srcip_username': ''}, 'condition': 'selection and not filter'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,60f6535a-760f-42a9-be3f-c9a0a025906e

Author: Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0001, T1078.004, TA0006, T1110

References

- https://docs.microsoft.com/en-gb/azure/active-directory/fundamentals/security-operations-privileged-accounts

Severity

75

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/17	high	• User has been put in exception group so they can use legacy authentication

Rule Details: Suspicious Sign-ins From a Non-Registered Device

Detects risky authentication from a non AD registered device without MFA being required.

Rule ID

`azure_10`

Query

```
{'selection': {'ResultType': 0, 'RiskState': 'atRisk', 'DeviceDetail_trusttype': ''},
 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,572b12d4-9062-11ed-a1eb-0242ac120002

Author: Harjot Singh, '@cyb3rjy0t'

Tactics, Techniques, and Procedures

TA0001, T1078

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-devices#non-compliant-device-sign-in

Severity

75

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/10	high	• Unknown

Rule Details: Device Registration or Join without MFA

Monitor and alert for device registration or join events where MFA was not performed.

Rule ID

`azure_11`

Query

```
{'selection': {'ResourceDisplayName': 'Device Registration Service', 'conditionalAccessStatus': 'success'}, 'filter_mfa': {'status_additionalDetails|startswith': 'MFA'}, 'condition': 'selection and not filter_mfa'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,5afa454e-030c-4ab4-9253-a90aa7fcc581

Author: Michael Epping, '@mepples21'

Tactics, Techniques, and Procedures

TA0001, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-devices#device-registrations-and-joins-outside-policy

Severity

50

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/28	medium	• Unknown

Rule Details: Azure Unusual Authentication Interruption

Detects when there is an interruption in the authentication process.

Rule ID

`azure_12`

Query

{'selection_50097': {'ResultType': 50097}, 'selection_50155': {'ResultType': 50155}, 'selection_50158': {'ResultType': 50158}, 'condition': '1 of selection_*'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,8366030e-7216-476b-9927-271d79f13cf3

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0001, T1078

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts

Severity

50

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/11/26	medium	• Unknown

Rule Details: Login to Disabled Account

Detect failed attempts to sign in to disabled accounts.

Rule ID

`azure_14`

Query

{'selection': {'ResultType': 50057}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,908655e0-25cf-4ae1-b775-1c8ce9cf43d8

Author: AlertIQ

Tactics, Techniques, and Procedures

TA0001, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts

Severity

50

Suppression Logic Based On

- srcip_username
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/10/10	medium	• Unknown

Rule Details: Application AppID Uri Configuration Changes

Detects when a configuration change is made to an application's AppID URI.

Rule ID

```
azure_16
```

Query

```
{'selection': {'properties_message': ['Update Application', 'Update Service principal
']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,1b45b0d1-773f-4f23-aedc-814b759563b1

Author: Mark Morowczynski '@markmorow', Bailey Bercik '@baileybercik'

Tactics, Techniques, and Procedures

TA0003, T1078.004, TA0006, T1552

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-applications#appid-uri-added-modified-or-removed

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/02	high	• When an administrator is making legitimate AppID URI configuration changes to an application. This should be a planned event.

Rule Details: Added Credentials to Existing Application

Detects when a new credential is added to an existing application. Any additional credentials added outside of expected processes could be a malicious actor using those credentials.

Rule ID

`azure_18`

Query

```
{'selection': {'properties_message': 'Update Service principal/Update Application'}, 'selection2': {'properties_message|contains|all': ['Update Application', 'Certificates and secrets management']}, 'condition': 'selection or selection2'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,cbb67ecc-fb70-4467-9350-c910bdf7c628

Author: Mark Morowczynski '@markmorow', Bailey Bercik '@baileybercik'

Tactics, Techniques, and Procedures

TA0003, T1098.001

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-applications#application-credentials

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/05/26	high	• When credentials are added/removed as part of the normal working hours/workflows

Rule Details: App Granted Privileged Delegated or App Permissions

Detects when administrator grants either application permissions (app roles) or highly privileged delegated permissions.

Rule ID

`azure_21`

Query

```
{'selection': {'properties_message': 'Add app role assignment to service principal'},
 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,5aecf3d5-f8a0-48e7-99be-3a759df7358f

Author: Bailey Bercik '@baileybercik', Mark Morowczynski '@markmorow'

Tactics, Techniques, and Procedures

TA0004, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-applications#application-granted-highly-privileged-permissions

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/07/28	high	• When the permission is legitimately needed for the app

Rule Details: Added Owner to Application

Detects when a new owner is added to an application. This gives that account privileges to make modifications and configuration changes to the application.

Rule ID

`azure_23`

Query

```
{'selection': {'properties_message': 'Add owner to application'}, 'condition': 'selec
tion'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,74298991-9fc4-460e-a92e-511aa60baec1

Author: Mark Morowczynski '@markmorow', Bailey Bercik '@baileybercik'

Tactics, Techniques, and Procedures

TA0003, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-applications#new-owner

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/02	medium	• When a new application owner is added by an administrator

Rule Details: App Role Added

Detects when an app is assigned Microsoft Entra roles, such as global administrator, or Microsoft Entra RBAC roles, such as subscription owner.

Rule ID

`azure_24`

Query

```
{'selection': {'properties_message': ['Add member to role', 'Add eligible member to role', 'Add scoped member to role']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,b04934b2-0a68-4845-8a19-bdfed3a68a7a

Author: Bailey Bercik '@baileybercik', Mark Morowczynski '@markmorow'

Tactics, Techniques, and Procedures

TA0004, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-applications#service-principal-assigned-to-a-role

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/07/19	medium	• When the permission is legitimately needed for the app

Rule Details: BitLocker Key Retrieval

Monitor and alert for BitLocker key retrieval.

Rule ID

`azure_25`

Query

```
{'selection': {'Category': 'KeyManagement', 'OperationName': 'Read BitLocker key'}, '
condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,a0413867-daf3-43dd-9245-734b3a787942

Author: Michael Epping, '@mepples21'

Tactics, Techniques, and Procedures

TA0006, T1555

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-devices#bitlocker-key-retrieval

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/28	medium	• Unknown

Rule Details: Changes to Device Registration Policy

Monitor and alert for changes to the device registration policy.

Rule ID

`azure_27`

Query

```
{'selection': {'Category': 'Policy', 'ActivityDisplayName': 'Set device registration policies'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,9494bff8-959f-4440-bbce-fb87a208d517

Author: Michael Epping, '@mepples21'

Tactics, Techniques, and Procedures

TA0005, T1484

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-devices#device-registrations-and-joins-outside-policy

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/28	high	• Unknown

Rule Details: New CA Policy by Non-Approved Actor

Monitor and alert on conditional access changes.

Rule ID

`azure_28`

Query

{'selection': {'properties_message': 'Add conditional access policy'}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,0922467f-db53-4348-b7bf-dee8d0d348c6

Author: Corissa Koopmans, '@corissalea'

Tactics, Techniques, and Procedures

TA0005, T1556

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-infrastructure

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/07/18	medium	• Misconfigured role permissions • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment.

Rule Details: CA Policy Updated by Non-Approved Actor

Monitor and alert on conditional access changes. Is Initiated by (actor) approved to make changes? Review Modified Properties and compare "old" vs "new" value.

Rule ID

azure_29

Query

{'keywords': {'properties_message': 'Update conditional access policy'}, 'condition': 'keywords'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,50a3c7aa-ec29-44a4-92c1-fce229eef6fc

Author: Corissa Koopmans, '@corissalea'

Tactics, Techniques, and Procedures

TA0005, T1548, T1556

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-infrastructure#conditional-access

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/07/19	medium	• Misconfigured role permissions • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment.

Rule Details: User Added to Group with CA Policy Modification Access

Monitor and alert on group membership additions of groups that have CA policy modification access.

Rule ID

`azure_30`

Query

```
{'selection': {'properties_message': 'Add member from group'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,91c95675-1f27-46d0-bead-d1ae96b97cd3

Author: Mark Morowczynski '@markmorow', Thomas Detzner '@tdetzner'

Tactics, Techniques, and Procedures

TA0005, T1548, T1556

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-infrastructure#conditional-access

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/04	medium	• User removed from the group is approved

Rule Details: CA Policy Removed by Non-Approved Actor

Monitor and alert on conditional access changes where non approved actor removed CA Policy.

Rule ID

`azure_31`

Query

```
{'selection': {'properties_message': 'Delete conditional access policy'}, 'condition' : 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,26e7c5e2-6545-481e-b7e6-050143459635

Author: Corissa Koopmans, '@corissalea'

Tactics, Techniques, and Procedures

TA0005, T1548, T1556

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-infrastructure#conditional-access

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/07/19	medium	• Misconfigured role permissions • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment.

Rule Details: Password Reset by User Account

Detect when a user has reset their password in Microsoft Entra ID

Rule ID

`azure_34`

Query

```
{'selection': {'Category': 'UserManagement', 'Result': 'Success', 'ActivityDisplayNam
e|contains': 'Password reset'}, 'self_service_activity': {'ActivityDisplayName|contai
ns': 'flow activity progress'}, 'self_service_reason': {'ResultReason': 'User success
fully reset password'}, 'filter': {'initiatedBy_user_userPrincipalName': ''}, 'condit
ion': 'selection and not filter and (not self_service_activity or self_service_reason
)'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,340ee172-4b67-4fb4-832f-f961bdc1f3aa

Author: YochanaHenderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0003, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts

Severity

30

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/03	medium	• If this was approved by System Administrator or confirmed user action.

Rule Details: Azure Subscription Permission Elevation via AuditLogs

Detects when a user has been elevated to manage all Azure Subscriptions. This change should be investigated immediately if it isn't planned. This setting could allow an attacker access to Azure subscriptions in your environment.

Rule ID

`azure_35`

Query

```
{'selection': {'Category': 'Administrative', 'OperationName': 'Assigns the caller to user access admin'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,ca9bf243-465e-494a-9e54-bf9fc239057d

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0004, T1078

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts#assignment-and-elevation

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/11/26	high	• If this was approved by System Administrator.

Rule Details: Temporary Access Pass Added to an Account

Detects when a temporary access pass (TAP) is added to an account. TAPs added to privileged accounts should be investigated.

Rule ID

`azure_36`

Query

```
{'selection': {'ResultReason': 'Admin registered temporary access pass method for user', 'properties_message': 'Admin registered security info'}, 'condition': 'selection'
```

}

Log Source



Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,fa84aaf5-8142-43cd-9ec2-78cfebf878ce

Author: Mark Morowczynski '@markmorow', Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0003, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts#changes-to-privileged-accounts

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/10	high	• Administrator adding a legitimate temporary access pass

Rule Details: Privileged Account Creation

Detects when a new admin is created.

Rule ID

`azure_37`

Query

```
{'selection': {'Result': 'Success', 'properties_message|contains|all': ['Add user', '
Add member to role']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,f7b5b004-dece-46e4-a4a5-f6fd0e1c6947

Author: Mark Morowczynski '@markmorow', Yochana Henderson, '@Yochana-H', Tim Shelton

Tactics, Techniques, and Procedures

TA0003, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts#changes-to-privileged-accounts

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/11	medium	• A legitimate new admin account being created

Rule Details: Guest User Invited by Non-Approved Inviters

Detects when a user that doesn't have permissions to invite a guest user attempts to invite one.

Rule ID

`azure_38`

Query

```
{'selection': {'Result': 'failure', 'properties_message': 'Invite external user'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,0b4b72e3-4c53-4d5b-b198-2c58cfef39a9

Author: Mark Morowczynski '@markmorow', Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0003, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-accounts#things-to-monitor

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/10	medium	• A non malicious user is unaware of the proper process

Rule Details: Bulk Deletion Changes to Privileged Account Permissions

Detects when a user is removed from a privileged role. Bulk changes should be investigated.

Rule ID

`azure_39`

Query


```
{'selection': {'properties_message': ['Remove eligible member (permanent)', 'Remove eligible member (eligible)']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,102e11e3-2db5-4c9e-bc26-357d42585d21

Author: Mark Morowczynski '@markmorow', Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0004, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-identity-management#azure-ad-roles-assignment

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/05	high	• Legitimate administrator actions of removing members from a role

Rule Details: PIM Approvals and Deny Elevation

Detects when a PIM elevation is approved or denied. Outside of normal operations should be investigated.

Rule ID

`azure_40`

Query

```
{'selection': {'properties_message': 'Request Approved/Denied'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,039a7469-0296-4450-84c0-f6966b16dc6d

Author: Mark Morowczynski '@markmorow', Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0004, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-identity-management#azure-ad-roles-assignment

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/09	high	• Actual admin using PIM.

Rule Details: Changes to PIM Settings

Detects when changes are made to PIM roles.

Rule ID

```
azure_41
```

Query

```
{'selection': {'properties_message': 'Update role setting in PIM'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,db6c06c4-bf3b-421c-aa88-15672b88c743

Author: Mark Morowczynski '@markmorow', Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0004, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-identity-management#azure-ad-roles-assignment

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/09	high	• Legit administrative PIM setting configuration changes

Rule Details: User Added to Privilege Role

Detects when a user is added to a privileged role.

Rule ID

`azure_42`

Query

```
{'selection': {'properties_message': ['Add eligible member (permanent)', 'Add eligible member (eligible)']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,49a268a4-72f4-4e38-8a7b-885be690c5b5

Author: Mark Morowczynski '@markmorow', Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0004, T1078.004

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-identity-management#azure-ad-roles-assignment

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/06	high	• Legitimate administrator actions of adding members from a role

Rule Details: PIM Alert Setting Changes to Disabled

Detects when PIM alerts are set to disabled.

Rule ID

`azure_43`

Query

```
{'selection': {'properties_message': 'Disable PIM Alert'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,aeaef14c-e5bf-4690-a9c8-835caad458bd

Author: Mark Morowczynski '@markmorow', Yochana Henderson, '@Yochana-H'

Tactics, Techniques, and Procedures

TA0004, T1078

References

- https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/security-operations-privileged-identity-management#azure-ad-roles-assignment

Severity

75

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/09	high	• Administrator disabling PIM alerts as an active choice.

Rule Details: Azure Domain Federation Settings Modified

Identifies when a user or application modified the federation settings on the domain.

Rule ID

azure_45

Query



{'selection': {'ActivityDisplayName': 'Set federation settings on domain'}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,352a54e1-74ba-4929-9d47-8193d67aba1e

Author: Austin Songer

Tactics, Techniques, and Procedures

TA0005, T1484

References

- https://docs.microsoft.com/en-us/azure/active-directory/hybrid/how-to-connect-monitor-federation-changes

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/09/06	medium	• Federation Settings being modified or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Federation Settings modified from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Kubernetes Pods Deleted

Identifies the deletion of Azure Kubernetes Pods.

Rule ID

azure_46

Query

{'selection': {'operationName': 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/PODS/DELETE'}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,b02f9591-12c3-4965-986a-88028629b2e1

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1485

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://github.com/elastic/detection-rules/blob/065bf48a9987cd8bd826c098a30ce36e6868ee46/rules/integrations/azure/impact_kubernetes_pod_deleted.toml

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/24	medium	• Pods may be deleted by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Pods deletions from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Device No Longer Managed or Compliant

Identifies when a device in Azure is no longer managed or compliant.

Rule ID

`azure_47`

Query

```
{'selection': {'properties_message': ['Device no longer compliant', 'Device no longer managed']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,542b9912-c01f-4e3f-89a8-014c48cdca7d

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1498

References

- https://docs.microsoft.com/en-us/azure/active-directory/reports-monitoring/reference-audit-activities#core-directory

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/03	medium	• Administrator may have forgotten to review the device.

Rule Details: Number Of Resource Creation Or Deployment Activities

Number of VM creations or deployment activities occur in Azure via Azure Activity Log.

Rule ID

`azure_48`

Query

```
{'selection': {'OperationNameValue': ['Microsoft.Compute/virtualMachines/write', 'Microsoft.Resources/deployments/write']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,d2d901db-7a75-45a1-bc39-0cbf00812192

Author: sawwinnnaung

Tactics, Techniques, and Procedures

TA0040, T1496

References

- https://github.com/Azure/Azure-Sentinel/blob/e534407884b1ec5371efc9f76ead282176c9e8bb/Detections/AzureActivity/Creating_Anomalous_Number_Of_Resources_detection.yaml

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/07	medium	• Valid change

Rule Details: Azure VPN Connection Modified or Deleted

Identifies when a VPN connection is modified or deleted.

Rule ID

`azure_49`

Query

```
{'selection': {'operationName': ['MICROSOFT.NETWORK/VPNGATEWAYS/VPNCONNECTIONS/WRITE'
, 'MICROSOFT.NETWORK/VPNGATEWAYS/VPNCONNECTIONS/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,61171ffc-d79c-4ae5-8e10-9323dba19cd3

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1498

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/08	medium	• VPN Connection being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • VPN Connection modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Firewall Rule Configuration Modified or Deleted

Identifies when a Firewall Rule Configuration is Modified or Deleted.

Rule ID

`azure_50`

Query

```
{'selection': {'operationName': ['MICROSOFT.NETWORK/FIREWALLPOLICIES/RULECOLLECTIONGROUPS/WRITE', 'MICROSOFT.NETWORK/FIREWALLPOLICIES/RULECOLLECTIONGROUPS/DELETE', 'MICROSOFT.NETWORK/FIREWALLPOLICIES/RULEGROUPS/WRITE', 'MICROSOFT.NETWORK/FIREWALLPOLICIES/RULEGROUPS/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,2a7d64cf-81fa-4daf-ab1b-ab80b789c067

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1562.007

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/08	medium	• Firewall Rule Configuration being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Firewall Rule Configuration modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Application Credential Modified

Identifies when an application credential is modified.

Rule ID

`azure_51`

Query

```
{'selection': {'properties_message': 'Update application -
 Certificates and secrets management'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,cdeef967-f9a1-4375-90ee-6978c5f23974

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0003, T1098

References

- https://www.cloud-architekt.net/auditing-of-msi-and-service-principals/

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/02	medium	• Application credential addition may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Application credential added from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Disabled MFA to Bypass Authentication Mechanisms

Detection for when multi-factor authentication has been disabled, which might indicate a malicious activity to bypass authentication mechanisms.

Rule ID

`azure_52`

Query

```
{'selection': {'properties_message': 'Disable Strong Authentication', 'result': 'success'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,7ea78478-a4f9-42a6-9dcd-f861816122bf

Author: @ionsor

Tactics, Techniques, and Procedures

TA0005, T1556.006

References

- https://docs.microsoft.com/en-us/azure/active-directory/authentication/howto-mfa-userstates

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/08	medium	• Authorized modification by administrators

Rule Details: Azure Kubernetes Cluster Created or Deleted

Detects when a Azure Kubernetes Cluster is created or deleted.

Rule ID

`azure_54`

Query

```
{'selection': {'operationName': ['MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,9541f321-7cba-4b43-80fc-fbd1fb922808

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1485

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://www.microsoft.com/security/blog/2021/03/23/secure-containerized-environments-with-updated-threat-matrix-for-kubernetes/
- https://www.microsoft.com/security/blog/2020/04/02/attack-matrix-kubernetes/
- https://medium.com/mitre-engenuity/att-ck-for-containers-now-available-4c2359654bf1
- https://attack.mitre.org/matrices/enterprise/cloud/

Severity

25

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/07	low	• Kubernetes cluster being created or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Kubernetes cluster created or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Active Directory Hybrid Health AD FS New Server

This detection uses Azure Activity Log (Administrative category) to identify the creation or update of a server instance in a Microsoft Entra Hybrid health AD FS service. A threat actor can create a new Health AD FS service and create a fake server instance to spoof AD FS signing logs. There is no need to compromise an on-prem AD FS server. This can be done programmatically via HTTP requests to Azure.

Rule ID

```
azure_55
```

Query

{'selection': {'CategoryValue': 'Administrative', 'ResourceId|contains': 'AdFederationService', 'OperationNameValue': 'Microsoft.ADHybridHealthService/services/servicemembers/action'}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,288a39fc-4914-4831-9ada-270e9dc12cb4

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research), MSTIC

Tactics, Techniques, and Procedures

TA0007, T1087

References

- https://o365blog.com/post/hybridhealthagent/

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/26	medium	• Legitimate AD FS servers added to an AAD Health AD FS service instance

Rule Details: Azure New CloudShell Created

Identifies when a new cloudshell is created inside of Azure portal.

Rule ID

azure_56

Query

{'selection': {'operationName': 'MICROSOFT.PORTAL/CONSOLES/WRITE'}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,72af37e2-ec32-47dc-992b-bc288a2708cb

Author: Austin Songer

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/21	medium	• A new cloudshell may be created by a system administrator.

Rule Details: Azure Owner Removed from Application or Service Principal

Identifies when an owner was removed from an application or service principal in Azure.

Rule ID

`azure_57`

Query

```
{'selection': {'properties_message': ['Remove owner from service principal', 'Remove owner from application']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,636e30d5-3736-42ea-96b1-e6e2f8429fd6

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1070

References

- https://docs.microsoft.com/en-us/azure/active-directory/reports-monitoring/reference-audit-activities#application-proxy

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/03	medium	• Owner being removed may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Owner removed from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Kubernetes Events Deleted

Detects when Events are deleted in Azure Kubernetes. An adversary may delete events in Azure Kubernetes in an attempt to evade detection.

Rule ID

`azure_58`

Query

```
{'selection': {'operationName': 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/EVENTS.K8S.IO/EVENTS/DELETE'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,225d8b09-e714-479c-a0e4-55e6f29adf35

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1562.001

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://github.com/elastic/detection-rules/blob/da3852b681cf1a33898b1535892eab1f3a76177a/rules/integrations/azure/defense_evasion_kubernetes_events_deleted.toml

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/24	medium	• Event deletions may be done by a system or network administrator. Verify whether the username, hostname, and/or resource name should be making changes in your environment. Events deletions from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Kubernetes Service Account Modified or Deleted

Identifies when a service account is modified or deleted.

Rule ID

`azure_59`

Query


```
{'selection': {'operationName': ['MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/SERVICEACCOUNTS/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/SERVICEACCOUNTS/DELETE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/SERVICEACCOUNTS/IMPERSONATE/ACTION']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,12d027c3-b48c-4d9d-8bb6-a732200034b2

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1531

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://www.microsoft.com/security/blog/2021/03/23/secure-containerized-environments-with-updated-threat-matrix-for-kubernetes/
- https://www.microsoft.com/security/blog/2020/04/02/attack-matrix-kubernetes/
- https://medium.com/mitre-engenuity/att-ck-for-containers-now-available-4c2359654bf1
- https://attack.mitre.org/matrices/enterprise/cloud/

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/07	medium	• Service account being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Service account modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Keyvault Key Modified or Deleted

Identifies when a Keyvault Key is modified or deleted in Azure.

Rule ID

`azure_60`

Query


```
{'selection': {'operationName': ['MICROSOFT.KEYVAULT/VAULTS/KEYS/UPDATE/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/KEYS/CREATE', 'MICROSOFT.KEYVAULT/VAULTS/KEYS/CREATE/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/KEYS/IMPORT/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/KEYS/RECOVER/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/KEYS/RESTORE/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/KEYS/DELETE', 'MICROSOFT.KEYVAULT/VAULTS/KEYS/BACKUP/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/KEYS/PURGE/ACTION']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,80eeab92-0979-4152-942d-96749e11df40

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0006, T1555.006

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/16	medium	• Key being modified or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Key modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Kubernetes Network Policy Change

Identifies when a Azure Kubernetes network policy is modified or deleted.

Rule ID

`azure_61`

Query

```
{'selection': {'operationName': ['MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/NETWORKING.K8S.IO/NETWORKPOLICIES/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/NETWORKING.K8S.IO/NETWORKPOLICIES/DELETE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/EXTENSIONS/NETWORKPOLICIES/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/EXTENSIONS/NETWORKPOLICIES/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,08d6ac24-c927-4469-b3b7-2e422d6e3c43

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1498

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://www.microsoft.com/security/blog/2021/03/23/secure-containerized-environments-with-updated-threat-matrix-for-kubernetes/
- https://www.microsoft.com/security/blog/2020/04/02/attack-matrix-kubernetes/
- https://medium.com/mitre-engenuity/att-ck-for-containers-now-available-4c2359654bf1
- https://attack.mitre.org/matrices/enterprise/cloud/

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId

- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/07	medium	• Network Policy being modified and deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Network Policy being modified and deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Kubernetes CronJob

Identifies when a Azure Kubernetes CronJob runs in Azure Cloud. Kubernetes Job is a controller that creates one or more pods and ensures that a specified number of them successfully terminate. Kubernetes Job can be used to run containers that perform finite tasks for batch jobs. Kubernetes CronJob is used to schedule Jobs. An Adversary may use Kubernetes CronJob for scheduling execution of malicious code that would run as a container in the cluster.

Rule ID

`azure_62`

Query

```
{'selection': {'operationName|startswith': ['MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/BATCH', 'MICROSOFT.CONTAINERSERVICE/MANAGEDCLUSTERS/BATCH'], 'operationName|endswith': ['/CRONJOBS/WRITE', '/JOBS/WRITE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,1c71e254-6655-42c1-b2d6-5e4718d7fc0a

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0003, T1053.007

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://kubernetes.io/docs/concepts/workloads/controllers/cron-jobs/
- https://kubernetes.io/docs/concepts/workloads/controllers/job/
- https://www.microsoft.com/security/blog/2020/04/02/attack-matrix-kubernetes/

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/11/22	medium	• Azure Kubernetes CronJob/Job may be done by a system administrator. • If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Firewall Rule Collection Modified or Deleted

Identifies when Rule Collections (Application, NAT, and Network) is being modified or deleted.

Rule ID

`azure_63`

Query

```
{'selection': {'operationName': ['MICROSOFT.NETWORK/AZUREFIREWALLS/APPLICATIONRULECOLLECTIONS/WRITE', 'MICROSOFT.NETWORK/AZUREFIREWALLS/APPLICATIONRULECOLLECTIONS/DELETE', 'MICROSOFT.NETWORK/AZUREFIREWALLS/NATRULECOLLECTIONS/WRITE', 'MICROSOFT.NETWORK/AZUREFIREWALLS/NATRULECOLLECTIONS/DELETE', 'MICROSOFT.NETWORK/AZUREFIREWALLS/NETWORKRULECOLLECTIONS/WRITE', 'MICROSOFT.NETWORK/AZUREFIREWALLS/NETWORKRULECOLLECTIONS/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,025c9fe7-db72-49f9-af0d-31341dd7dd57

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1562.007

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/08	medium	• Rule Collections (Application, NAT, and Network) being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Rule Collections (Application, NAT, and Network) modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Application Security Group Modified or Deleted

Identifies when a application security group is modified or deleted.

Rule ID

`azure_64`

Query

```
{'selection': {'operationName': ['MICROSOFT.NETWORK/APPLICATIONSECURITYGROUPS/WRITE',
 'MICROSOFT.NETWORK/APPLICATIONSECURITYGROUPS/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,835747f1-9329-40b5-9cc3-97d465754ce6

Author: Austin Songer

Tactics, Techniques, and Procedures

TA0005, T1562

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/16	medium	• Application security group being modified or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Application security group modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Container Registry Modified or Deleted

Detects when a Container Registry is created, updated, or deleted.

Rule ID

`azure_65`

Query

```
{'selection': {'operationName': ['MICROSOFT.CONTAINERREGISTRY/REGISTRIES/WRITE', 'MICROSOFT.CONTAINERREGISTRY/REGISTRIES/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,93e0ef48-37c8-49ed-a02c-038aab23628e

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1485

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://www.microsoft.com/security/blog/2021/03/23/secure-containerized-environments-with-updated-threat-matrix-for-kubernetes/
- https://www.microsoft.com/security/blog/2020/04/02/attack-matrix-kubernetes/
- https://medium.com/mitre-engenuity/att-ck-for-containers-now-available-4c2359654bf1
- https://attack.mitre.org/matrices/enterprise/cloud/

Severity

25

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/07	low	• Container Registry being created, updated, or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Container Registry created, updated, or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Suppression Rule Created

Identifies when a suppression rule is created in Azure. Adversary's could attempt this to evade detection.

Rule ID

`azure_66`

Query

```
{'selection': {'operationName': 'MICROSOFT.SECURITY/ALERTSSUPPRESSIONRULES/WRITE'}, '
condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,92cc3e5d-eb57-419d-8c16-5c63f325a401

Author: Austin Songer

Tactics, Techniques, and Procedures

TA0005, T1562

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/16	medium	• Suppression Rule being created may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Suppression Rule created from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Firewall Modified or Deleted

Identifies when a firewall is created, modified, or deleted.

Rule ID

`azure_67`

Query

{'selection': {'operationName': ['MICROSOFT.NETWORK/AZUREFIREWALLS/WRITE', 'MICROSOFT.NETWORK/AZUREFIREWALLS/DELETE']}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,512cf937-ea9b-4332-939c-4c2c94baadcd

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1562.007

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/08	medium	• Firewall being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Firewall modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Kubernetes Secret or Config Object Access

Identifies when a Kubernetes account access a sensitive objects such as configmaps or secrets.

Rule ID

azure_68

Query

{'selection': {'operationName': ['MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/CONFIGMAPS/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/CONFIGMAPS/DELETE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/SECRETS/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/SECRETS/DELETE']}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,7ee0b4aa-d8d4-408[illegible]61-20efdf41a04c

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0006, T1552.001

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://www.microsoft.com/security/blog/2021/03/23/secure-containerized-environments-with-updated-threat-matrix-for-kubernetes/
- https://www.microsoft.com/security/blog/2020/04/02/attack-matrix-kubernetes/
- https://medium.com/mitre-engenuity/att-ck-for-containers-now-available-4c2359654bf1
- https://attack.mitre.org/matrices/enterprise/cloud/

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/07	medium	• Sensitive objects may be accessed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Sensitive objects accessed from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Key Vault Modified or Deleted

Identifies when a key vault is modified or deleted.

Rule ID

`azure_69`

Query

```
{'selection': {'operationName': ['MICROSOFT.KEYVAULT/VAULTS/WRITE', 'MICROSOFT.KEYVAULT/VAULTS/DELETE', 'MICROSOFT.KEYVAULT/VAULTS/DEPLOY/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/ACCESSPOLICIES/WRITE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,459a2970-bb84-4e6a-[illegible]2e-ff0fbd99448d

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0006, T1555.006

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/16	medium	• Key Vault being modified or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Key Vault modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Device or Configuration Deleted

Identifies when a device or device configuration in Azure is deleted.

Rule ID

```
azure_70
```

Query

```
{'selection': {'properties_message': ['Delete device', 'Delete device configuration']
}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,46530378-f9db-4af9-a9e5-889c177d3881

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1498

References

- https://docs.microsoft.com/en-us/azure/active-directory/reports-monitoring/reference-audit-activities#core-directory

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/03	medium	• Device or device configuration being modified or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Device or device configuration modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Subscription Permission Elevation Via ActivityLogs

Detects when a user has been elevated to manage all Azure Subscriptions. This change should be investigated immediately if it isn't planned. This setting could allow an attacker access to Azure subscriptions in your environment.

Rule ID

`azure_71`

Query

```
{'selection': {'operationName': 'MICROSOFT.AUTHORIZATION/ELEVATEACCESS/ACTION'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,09438caa-07b1-4870-8405-1dbafe3dad95

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0004, T1098.003

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftauthorization

Severity

75

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/11/26	high	• If this was approved by System Administrator.

Rule Details: Azure Active Directory Hybrid Health AD FS Service Delete

This detection uses Azure Activity Log (Administrative category) to identify the deletion of a Microsoft Entra Hybrid health AD FS service instance in a tenant. A threat actor can create a new Health AD FS service and create a fake server to spoof AD FS signing logs. The health AD FS service can then be deleted after it is not longer needed via HTTP requests to Azure.

Rule ID

`azure_72`

Query

```
{'selection': {'CategoryValue': 'Administrative', 'ResourceId|contains': 'AdFederatio
nService', 'OperationNameValue': 'Microsoft.ADHybridHealthService/services/delete'},
'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,48739819-8230-4ee3-a8ea-e0289d1fb0ff

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research), MSTIC

Tactics, Techniques, and Procedures

TA0005, T1578.003

References

- https://o365blog.com/post/hybridhealthagent/

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/26	medium	Legitimate AAD Health AD FS service instances being deleted in a tenant

Rule Details: Azure DNS Zone Modified or Deleted

Identifies when DNS zone is modified or deleted.

Rule ID

`azure_73`

Query

```
{'selection': {'operationName|startswith': 'MICROSOFT.NETWORK/DNSZONES', 'operationName|endswith': ['/WRITE', '/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,af6925b0-8826-47f1-9324-337507a0babd

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0011, T1071.004

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/08	medium	• DNS zone modified and deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • DNS zone modification from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Service Principal Created

Identifies when a service principal is created in Azure.

Rule ID

azure_74

Query



{'selection': {'properties_message': 'Add service principal'}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,0ddcff6d-d262-40b0-804b-80eb592de8e3

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1578

References

- https://docs.microsoft.com/en-us/azure/active-directory/reports-monitoring/reference-audit-activities#application-proxy

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/02	medium	• Service principal being created may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Service principal created from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Service Principal Removed

Identifies when a service principal was removed in Azure.

Rule ID

azure_75

Query

{'selection': {'properties_message': 'Remove service principal'}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,448fd1ea-2116-4c62-9cde-a92d120e0f08

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1578.003

References

- https://docs.microsoft.com/en-us/azure/active-directory/reports-monitoring/reference-audit-activities#application-proxy

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/03	medium	• Service principal being removed may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Service principal removed from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Kubernetes Sensitive Role Access

Identifies when ClusterRoles/Roles are being modified or deleted.

Rule ID

`azure_76`

Query


```
{'selection': {'operationName': ['MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/ROLES/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/ROLES/DELETE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/ROLES/BIND/ACTION', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/ROLES/ESCALATE/ACTION', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/CLUSTERROLES/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/CLUSTERROLES/DELETE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/CLUSTERROLES/BIND/ACTION', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/CLUSTERROLES/ESCALATE/ACTION']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,818fee0c-e0ec-4e45-824e-83e4817b0887

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0004, T1078

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://www.microsoft.com/security/blog/2021/03/23/secure-containerized-environments-with-updated-threat-matrix-for-kubernetes/
- https://www.microsoft.com/security/blog/2020/04/02/attack-matrix-kubernetes/
- https://medium.com/mitre-engenuity/att-ck-for-containers-now-available-4c2359654bf1
- https://attack.mitre.org/matrices/enterprise/cloud/

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/07	medium	• ClusterRoles/Roles being modified and deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • ClusterRoles/Roles modification from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Point-to-site VPN Modified or Deleted

Identifies when a Point-to-site VPN is Modified or Deleted.

Rule ID

`azure_77`

Query


```
{'selection': {'operationName': ['MICROSOFT.NETWORK/P2SVPNGATEWAYS/WRITE', 'MICROSOFT.NETWORK/P2SVPNGATEWAYS/DELETE', 'MICROSOFT.NETWORK/P2SVPNGATEWAYS/RESET/ACTION', 'MICROSOFT.NETWORK/P2SVPNGATEWAYS/GENERATEVPNPROFILE/ACTION', 'MICROSOFT.NETWORK/P2SVPNG
```

ATEWAYS/DISCONNECTP2SVPNCONNECTIONS/ACTION', 'MICROSOFT.NETWORK/P2SVPNGATEWAYS/PROVIDERS/MICROSOFT.INSIGHTS/DIAGNOSTICSETTINGS/WRITE']}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,d9557b75-267b-4b43-922f-a775e2d1f792

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1498

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/08	medium	• Point-to-site VPN being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Point-to-site VPN modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Application Gateway Modified or Deleted

Identifies when a application gateway is modified or deleted.

Rule ID

azure_78

Query

{'selection': {'operationName': ['MICROSOFT.NETWORK/APPLICATIONGATEWAYS/WRITE', 'MICROSOFT.NETWORK/APPLICATIONGATEWAYS/DELETE']}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,ad87d14e-7599-4633-ba81-aeb60cfe8cd6

Author: Austin Songer

Tactics, Techniques, and Procedures

TA0003, T1133

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/16	medium	• Application gateway being modified or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Application gateway modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Kubernetes RoleBinding/ClusterRoleBinding Modified and Deleted

Detects the creation or patching of potential malicious RoleBinding/ClusterRoleBinding.

Rule ID

`azure_79`

Query


```
{'selection': {'operationName': ['MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/CLUSTERROLEBINDINGS/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/CLUSTERROLEBINDINGS/DELETE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/ROLEBINDINGS/WRITE', 'MICROSOFT.KUBERNETES/CONNECTEDCLUSTERS/RBAC.AUTHORIZATION.K8S.IO/ROLEBINDINGS/DELETE']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,25cb259b-bbdc-4b87-98b7-90d7c72f8743

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0004, T1078

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations#microsoftkubernetes
- https://www.microsoft.com/security/blog/2021/03/23/secure-containerized-environments-with-updated-threat-matrix-for-kubernetes/
- https://www.microsoft.com/security/blog/2020/04/02/attack-matrix-kubernetes/
- https://medium.com/mitre-engenuity/att-ck-for-containers-now-available-4c2359654bf1
- https://attack.mitre.org/matrices/enterprise/cloud/

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/07	medium	• RoleBinding/ClusterRoleBinding being modified and deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • RoleBinding/ClusterRoleBinding modification from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Application Deleted

Identifies when an application is deleted in Azure.

Rule ID

`azure_80`

Query

```
{'selection': {'properties_message': ['Delete application', 'Hard Delete application']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,410d2a41-1e6d-452f-85e5-abdd8257a823

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1489

References

- https://docs.microsoft.com/en-us/azure/active-directory/reports-monitoring/reference-audit-activities#application-proxy

Severity

50

Suppression Logic Based On

- azure_ad.initiatedBy.user.id
- azure_ad.initiatedBy.app.servicePrincipalId
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/03	medium	• Application being deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Application deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Granting Of Permissions To An Account

Identifies IPs from which users grant access to other users on azure resources and alerts when a previously unseen source IP address is used.

Rule ID

`azure_82`

Query

```
{'selection': {'OperationNameValue': ['Microsoft.Authorization/roleAssignments/write']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,a622fcd2-4b5a-436a-b8a2-a4171161833c

Author: sawwinnnaung

Tactics, Techniques, and Procedures

TA0004, T1098.003

References

- https://github.com/Azure/Azure-Sentinel/blob/e534407884b1ec5371efc9f76ead282176c9e8bb/Detections/AzureActivity/Granting_Permissions_To_Account_detection.yaml

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/07	medium	• Valid change

Rule Details: Azure Network Security Configuration Modified or Deleted

Identifies when a network security configuration is modified or deleted.

Rule ID

`azure_84`

Query

```
{'selection': {'operationName': ['MICROSOFT.NETWORK/NETWORKSECURITYGROUPS/WRITE', 'MICROSOFT.NETWORK/NETWORKSECURITYGROUPS/DELETE', 'MICROSOFT.NETWORK/NETWORKSECURITYGROUPS/SECURITYRULES/WRITE', 'MICROSOFT.NETWORK/NETWORKSECURITYGROUPS/SECURITYRULES/DELETE', 'MICROSOFT.NETWORK/NETWORKSECURITYGROUPS/JOIN/ACTION', 'MICROSOFT.NETWORK/NETWORKSECURITYGROUPS/PROVIDERS/MICROSOFT.INSIGHTS/DIAGNOSTICSETTINGS/WRITE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,d22b4df4-5a67-4859-a578-8c9a0b5af9df

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1562

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/08	medium	• Network Security Configuration being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Network Security Configuration modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Network Firewall Policy Modified or Deleted

Identifies when a Firewall Policy is Modified or Deleted.

Rule ID

`azure_85`

Query

```
{'selection': {'operationName': ['MICROSOFT.NETWORK/FIREWALLPOLICIES/WRITE', 'MICROSOFT.NETWORK/FIREWALLPOLICIES/JOIN/ACTION', 'MICROSOFT.NETWORK/FIREWALLPOLICIES/CERTIFICATES/ACTION', 'MICROSOFT.NETWORK/FIREWALLPOLICIES/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,83c17918-746e-4bd9-920b-8e098bf88c23

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0005, T1562.007

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/02	medium	• Firewall Policy being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Firewall Policy modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Virtual Network Modified or Deleted

Identifies when a Virtual Network is modified or deleted in Azure.

Rule ID

`azure_86`

Query

```
{'selection': {'operationName|startswith': ['MICROSOFT.NETWORK/VIRTUALNETWORKGATEWAYS/', 'MICROSOFT.NETWORK/VIRTUALNETWORKS/'], 'operationName|endswith': ['/WRITE', '/DELETE']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,bcfcc962-0e4a-4fd9-84bb-a833e672df3f

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0040, T1498

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/08	medium	• Virtual Network being modified or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Virtual Network modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: Azure Keyvault Secrets Modified or Deleted

Identifies when secrets are modified or deleted in Azure.

Rule ID

`azure_87`

Query

```
{'selection': {'operationName': ['MICROSOFT.KEYVAULT/VAULTS/SECRETS/WRITE', 'MICROSOFT.KEYVAULT/VAULTS/SECRETS/DELETE', 'MICROSOFT.KEYVAULT/VAULTS/SECRETS/BACKUP/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/SECRETS/PURGE/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/SECRETS/UPDATE/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/SECRETS/RECOVER/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/SECRETS/RESTORE/ACTION', 'MICROSOFT.KEYVAULT/VAULTS/SECRETS/SETSECRET/ACTION']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft Entra Events configured.

Rule Source

SigmaHQ,b831353c-1971-477b-abb6-2828edc3bca1

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0006, T1555.006

References

- https://docs.microsoft.com/en-us/azure/role-based-access-control/resource-provider-operations

Severity

50

Suppression Logic Based On

- azure_activity_log.resourceId
- azure_activity_log.operationName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/16	medium	• Secrets being modified or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Secrets modified or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

certutil.exe Rule IDs

Rule Details: certutil.exe Certificate Extraction

The following analytic identifies the use of certutil.exe with arguments indicating the manipulation or extraction of certificates. This activity is significant because extracting certificates can allow attackers to sign new authentication tokens, particularly in federated environments like Windows ADFS. If confirmed malicious, this could enable attackers to forge authentication tokens, potentially leading to unauthorized access and privilege escalation within the network.

Rule ID

`certutil_exe_certificate_extraction`

Query

```
{'selection1': {'Image|endswith': '\\certutil.exe'}, 'selection2': {'CommandLine|contains': '-exportPFX'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1649

References

- https://blog.sygnia.co/detection-and-hunting-of-golden-saml-attack
- https://strontic.github.io/xcyclopedia/library/certutil.exe-09A8A29BAA3A451713FD3D07943B4A43.html

Severity

90

Suppression Logic Based On

- computer_name
- process_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/08/18	critical	• Unless there are specific use cases, manipulating or exporting certificates using certutil is uncommon. Extraction of certificate has been observed during attacks such as Golden SAML and other campaigns targeting Federated services.

Domain Name Service (DNS) Rule IDs

Rule Details: DNS Query to TOR Proxy Domain

DNS query to onion domains and proxy domains for TOR network.

Rule ID



`dns_1`

Query


```
{'selection_domain': {'DnsQuestionName|endswith': ['.onion', '.tor2web.org', '.tor2web.com', '.torlink.co', '.onion.to', '.onion.ink', '.onion.cab', '.onion.nu', '.onion.link', '.onion.it', '.onion.city', '.onion.direct', '.onion.top', '.onion.casa', '.onion.plus', '.onion.rip', '.onion.dog', '.tor2web.fi', '.tor2web.blutmagie.de', '.onion.sh', '.onion.lu', '.onion.pet', '.t2w.pw', '.tor2web.ae.org', '.tor2web.io', '.tor2web.xyz', '.onion.lt', '.s1.tor-gateways.de', '.s2.tor-gateways.de', '.s3.tor-gateways.de', '.s4.tor-gateways.de', '.s5.tor-gateways.de', '.hiddenservice.net']}, 'condition': 'selection_domain'}
```


Log Source

Stellar Cyber Network Events configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0010, T1048, TA0011, T1090.003

References

- https://github.com/Azure/Azure-Sentinel/blob/f99542b94afe0ad2f19a82cc08262e7ac8e1428e/Detections/ASimDNS/imDNS_TorProxies.yaml

Severity

30

Suppression Logic Based On

- srcip
- dns.question.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/05/15	medium	• Legitimate access to TOR network. TOR network is rarely used for normal daily use unless your services have special anonymity needs.

Rule Details: Phishing Domain With File Extension TLD

DNS query to TLDs that resemble file extensions. Attackers may use these TLDs for phishing.

Rule ID

`dns_2`

Query

```
{'selection_domain': {'DnsQuestionName|endswith': ['.zip', '.mov']}, 'condition': 'selection_domain'}
```

Log Source

Stellar Cyber Network Events configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1566

References

- https://arstechnica.com/information-technology/2023/05/critics-say-googles-new-zip-and-mov-domains-will-be-a-boon-to-scammers/
- https://www.trendmicro.com/en_us/research/23/e/future-exploitation-vector-file-extensions-as-top-level-domains.html

Severity

30

Suppression Logic Based On

- srcip
- dns.question.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/05/15	low	• Legitimate domains with .zip or .mov TLDs. These new TLDs are rarely seen in common websites.

Rule Details: DNS Query to External Service Interaction Domains

DNS query to external service interaction domains often used for out-of-band interactions after successful RCE.

Rule ID

```
dns_3
```

Query

```
{'selection_domain': {'DnsQuestionName|endswith': ['.interact.sh', '.oast.pro', '.oast.live', '.oast.site', '.oast.online', '.oast.fun', '.oast.me', '.burpcollaborator.net', '.oastify.com', '.canarytokens.com', '.requestbin.net', '.dnslog.cn']}, 'condition': 'selection_domain'}
```

Log Source

Stellar Cyber Network Events configured.

Rule Source

SigmaHQ,aff715fa-4dd5-497a-8db3-910bea555566

Author: Florian Roth (Nextron Systems), Matt Kelly (list of domains)

Tactics, Techniques, and Procedures

TA0001, T1190, TA0043, T1595.002

References

- https://github.com/SigmaHQ/sigma/blob/598d29f811c1859ba18e05b8c419cc94410c9a55/rules/network/dns/net_dns_external_service_interaction_domains.yml
- https://twitter.com/breakersall/status/1533493587828260866

Severity

30

Suppression Logic Based On

- srcip
- dns.question.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/06/07	medium	• Legitimate external service access. May be initiated by internal security engineers for out-of-band application security testing.

Rule Details: DNS Query to Monero Crypto Coin Mining Pool Domains

DNS query to Monero crypto coin mining pool domains.

Rule ID

`dns_4`

Query


```
{'selection_domain': {'DnsQuestionName|endswith': ['pool.minexmr.com', 'fr.minexmr.com', 'de.minexmr.com', 'sg.minexmr.com', 'ca.minexmr.com', 'us-west.minexmr.com', 'pool.supportxmr.com', 'mine.c3pool.com', 'xmr-eu1.nanopool.org', 'xmr-eu2.nanopool.org', 'xmr-us-east1.nanopool.org', 'xmr-us-west1.nanopool.org', 'xmr-asia1.nanopool.org', 'xmr-jp1.nanopool.org', 'xmr-au1.nanopool.org', 'xmr.2miners.com', 'xmr.hashcity.org', 'xmr.f2pool.com', 'xmrpool.eu', 'pool.hashvault.pro']}, 'condition': 'selection_domain'}
```


Log Source

Stellar Cyber Network Events configured.

Rule Source

SigmaHQ,b593fd50-7335-4682-a36c-4edcb68e4641

Author: Florian Roth (Nextron S ms)

Tactics, Techniques, and Procedures

TA0040, T1496, TA0010, T1567

References

- https://github.com/SigmaHQ/sigma/blob/598d29f811c1859ba18e05b8c419cc94410c9a55/rules/network/dns/net_dns_pua_cryptocoin_mining_xmr.yml
- https://www.nextron-systems.com/2021/10/24/monero-mining-pool-fqdns/

Severity

50

Suppression Logic Based On

- srcip
- dns.question.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2021/10/24	high	• Legitimate access to Monero mining pools. Rarely happens unless legitimate programs contain crypto mining functions.

Rule Details: DNS Query to Anonymous File Upload Domains

DNS query to anonymous file upload platform domains often used for malicious purposes.

Rule ID

`dns_6`

Query

```
{'selection_domain': {'DnsQuestionName|endswith': ['.anonfiles.com', '.api.put.io', '.upload.put.io', '.ufile.io']}, 'condition': 'selection_domain'}
```

Log Source

Stellar Cyber Network Events configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0010, T1567.002

References

- https://github.com/SigmaHQ/sigma/blob/29dce312bc49a9101d33e4d390a7c349c8d985a2/rules/windows/builtin/dns_client/win_dns_client_anonymfiles_com.yml

- https://www.trendmicro.com/vinfo/us/security/news/ransomware-spotlight/ransomware-spotlight-blackbyte
- https://github.com/SigmaHQ/sigma/blob/29dce312bc49a9101d33e4d390a7c349c8d985a2/rules/windows/builtin/dns_client/win_dns_client_put_io.yml
- https://darkatlas.io/blog/medusa-ransomware-group-opsec-failure
- https://github.com/SigmaHQ/sigma/blob/598d29f811c1859ba18e05b8c419cc94410c9a55/rules/windows/builtin/dns_client/win_dns_client_ufile_io.yml
- https://thedfirreport.com/2021/12/13/diavol-ransomware/

Severity

20

Suppression Logic Based On

- srcip
- dns.question.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2024/12/20	low	• Legitimate use of anonymous file sharing services.

Mimikatz Rule IDs

Rule Details: Mimikatz Credential Dump

The mask the suspicious process used to obtain access privilege. the different access_mask means different capability obtained by the suspicious process.

Rule ID

```
mimikatz_mem_scan
```

Query

```
{'selection1': {'DetectionFlag': 2301}, 'selection2': {'SourceImage': ['C:\\Windows\\System32\\MsiExec.exe', 'C:\\Program Files\\McAfee\\Endpoint Security\\Adaptive Threat Protection\\mfeatp.exe', 'C:\\Program Files\\Guardicore\\gc-launcher.exe', 'c:\\Program Files\\Microsoft Security Client\\MsMpEng.exe']}, 'selection3': [{'SourceImage|re': 'C:\\\\Program Files\\\\SentinelOne\\\\Sentinel Agent ([0-9]{2,3}\\.[0-9]\\.[0-9]\\.[0-9]{1,4})\\\\SentinelAgent\\.exe'}], 'condition': 'selection1 and not selection2 and not selection3'}
```

Detection Flag

Note: `detection_flag` is a Stellar enriched field.

- **2301:** Mimikatz access to lsass.exe

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003

References

N/A

Severity

90

Suppression Logic Based On

- computer_name
- access_subject
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/12/13	critical	N/A

Network Security Rule IDs

Rule Details: Possible Impacket SecretDump Remote Activity

Detect AD credential dumping using Impacket SecretDump HKTL.

Rule ID

`network_security_2`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|contains|all': ['ADMIN$', 'SYSTEM32\\',
 '.tmp']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003

References

N/A

Severity

75

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/01	high	• Unknown

Rule Details: Windows Network Access Suspicious desktop.ini Action

Detects unusual processes accessing desktop.ini remotely over network share, which can be leveraged to alter how Explorer displays a folder's content (i.e. renaming files) without changing them on disk.

Rule ID

`network_security_3`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|re': "'request'\\s*:\\s*\\{[^}]*(?:'filename'|'path')\\s*:\\s*'[^']*desktop\\.ini[^']*'[^}]*'command'\\s*:\\s*9[^}]*\\}"}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1547.009

References

- https://isc.sans.edu/forums/diary/Desktopini+as+a+postexploitation+tool/25912/

Severity

50

Suppression Logic Based On

- appid_name
- srcip
- dstip

- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/13	medium	• Unknown

Rule Details: Possible PetitPotam Coerce Authentication Attempt

Detect PetitPotam coerced authentication activity.

Rule ID

`network_security_4`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|contains|all': ['IPC$', 'lsarpc', 'ANONYMOUS LOGON']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1187

References

- https://github.com/topotam/PetitPotam
- https://github.com/splunk/security_content/blob/0dd6de32de2118b2818550df9e65255f4109a56d/detections/endpoint/petitpotam_network_share_access_request.yml

Severity

75

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/05	high	• Unknown.

Rule Details: Protected Storage Service Access

Detects access to a protected_storage service over the network. Potential abuse of DPAPI to extract domain backup keys from Domain Controllers.

Rule ID

`network_security_5`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|re': "'request'\\s*:\\s*\\{[^}]*(?:'filename'|'path')\\s*:\\s*'[^']*protected_storage[^']*'[^}]*'command'\\s*:\\s*9[^}]*\\}"}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

- https://threathunterplaybook.com/hunts/windows/190620-DomainDPAPIBackupKeyExtraction/notebook.html

Severity

75

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/13	high	• Unknown

Rule Details: Startup/Logon Script added to Group Policy Object

Detects the modification of Group Policy Objects (GPO) to add a startup/logon script to users or computer objects.

Rule ID

`network_security_6`

Query

{'selection_protocol': {'appid_name': 'smb'}, 'selection_share': {'metadata|contains': 'Policies'}, 'selection_recursive_target_name': {'metadata|re': "'request'\\s*:\\s*\\{[^}]*(?:'filename'|'path')\\s*:\\s*'[^']*scripts\\.ini[^']*'[^}]*'command'\\s*:\\s*9[^}]*\\}"}, 'condition': 'all of selection*'}

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1547, TA0005, T1484

References

N/A

Severity

50

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/05	medium	• Unknown

Rule Details: Remote Task Creation via ATSVC Named Pipe

Detects remote task creation via at.exe or API interacting with ATSVC namedpipe.

Rule ID

network_security_7

Query

{'selection': {'appid_name': 'smb', 'metadata|contains': ['IPC$']}, 'selection_atsvc': {'metadata|re': "'request'\\s*:\\s*\\{[^}]*(?:'filename'|'path')\\s*:\\s*'[^']*atsvc[^']*'[^}]*'command'\\s*:\\s*9[^}]*\\}"}, 'condition': 'selection and selection_atsvc'}

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1053.002

References

N/A

Severity

50

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/09	medium	• Unknown

Rule Details: DCERPC SMB Spoolss Named Pipe

Detects the use of the spoolss named pipe over SMB. This can be used to trigger the authentication via NTLM of any machine that has the spoolservice enabled.

Rule ID

`network_security_8`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|contains|all': ['IPC$']}, 'selection_spoolss': {'metadata|re': "'request'\\s*:\\s*\\{[^}]*(?:'filename'|'path')\\s*:\\s*'[^']*spoolss[^']*'[^}]*'command'\\s*:\\s*9[^}]*\\}"}, 'condition': 'selection and selection_spoolss'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

- https://posts.specterops.io/hunting-in-active-directory-unconstrained-delegation-forests-trusts-71f2b33688e1
- https://dirkjanm.io/a-different-way-of-abusing-zerologon/
- https://twitter.com/_dirkjan/status/1309214379003588608

Severity

50

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/13	medium	N/A

Rule Details: Persistence and Execution at Scale via GPO Scheduled Task

Detect lateral movement using GPO scheduled task, usually used to deploy ransomware at scale.

Rule ID

`network_security_9`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|re': "'request'\\s*:\\s*\\{[^}]*(?:'filename'|'path')\\s*:\\s*'[^']*ScheduledTasks\\.xml[^']*'[^}]*'command'\\s*:\\s*9[^}]*\\}"}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1053.005

References

- https://twitter.com/menasec1/status/1106899890377052160
- https://www.secureworks.com/blog/ransomware-as-a-distraction

Severity

75

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/05	high	• Unknown

Rule Details: Impacket PsExec Execution

Detects execution of Impacket's psexec.py.

Rule ID

`network_security_10`

Query


```
{'selection_protocol': {'appid_name': 'smb'}, 'selection_sharename': {'metadata|contains': ['IPC$']}, 'selection_relative_target_name': {'metadata|contains': ['RemCom_stdin', 'RemCom_stdout', 'RemCom_stderr']}, 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

N/A

Severity

75

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation D	Risk Level	False Positives
experimental	2024/07/09	high	• Unknown

Rule Details: Suspicious PsExec Execution

Detects execution of psexec or paexec with renamed service name, this rule helps to filter out the noise if psexec is used for legit purposes or if attacker uses a different psexec client other than sysinternal one.

Rule ID

`network_security_11`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|contains': ['-stdin', '-stdout', '-stderr']}, 'filter': {'metadata|contains': 'PSEXESVC'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

N/A

Severity

75

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/13	high	• Unknown

Rule Details: Remote Service Activity via SVCCTL Named Pipe

Detects remote service activity via remote access to the svcctl named pipe.

Rule ID

`network_security_12`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|contains': ['IPC$']}, 'selection_svcctl': {'metadata|re': "'request'\\s*:\\s*\\{[^}]*(?:'filename'|'path')\\s*:\\s*'[^']*svcctl[^']*'[^}]*'command'\\s*:\\s*9[^}]*\\}"}, 'condition': 'selection and selection_svcctl'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

N/A

Severity

50

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/13	medium	• Unknown

Rule Details: T1047 Wmiprvse Wbemcomn DLL Hijack

Detects a threat actor creating a file named `wbemcomn.dll` in the `C:\Windows\System32\wbem\` directory over the network for a WMI DLL Hijack scenario.

Rule ID

`network_security_13`

Query

```
{'selection': {'appid_name': 'smb', 'metadata|contains': ['\\\\wbem\\\\wbemcomn.dll']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1047, TA0008, T1021.002

References

- https://threathunterplaybook.com/hunts/windows/201009-RemoteWMIWbemcomnDLLHijack/notebook.html

Severity

75

Suppression Logic Based On

- appid_name
- srcip
- dstip
- dstip_host
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024/07/13	high	• Unknown

Rule Details: BloodHound Enumeration Activity

Detects unusual LDAP search requests, which can be potential domain enumeration activity from BloodHound or other Active Directory data collection tools.

Rule ID

`network_security_14`

Query


```
{'selection_search': {'metadata|contains': ["'message_type': 3"]}, 'selection_generic': {'metadata|contains': ['(grouptype:1.2.840.113556.1.4.803:=2147483648)', '(grouptype:1.2.840.113556.1.4.803:=2147483656)', '(grouptype:1.2.840.113556.1.4.803:=2147483652)', '(grouptype:1.2.840.113556.1.4.803:=2147483650)', '(samaccounttype=805306369)', '(samaccounttype=805306368)', '(samaccounttype=536870913)', '(samaccounttype=536870912)', '(samaccounttype=268435457)', '(samaccounttype=268435456)', '(objectcategory=grouppolicycontainer)', '(objectcategory=organizationalunit)', '(objectcategory=computer)', '(objectcategory=ntdsdsa)', '(objectcategory=server)', '(objectcategory=domain)', '(objectcategory=person)', '(objectcategory=group)', '(objectcategory=user)', '(objectclass=trusteddomain)', '(objectclass=computer)', '(objectclass=server)', '(objectclass=group)', '(objectclass=user)', '(primarygroupid=521)', '(primarygroupid=516)', '(primarygroupid=515)', '(primarygroupid=512)', 'objectguid=', '(schemaidguid=']}, 'se
```

lection_dn_enum': {'metadata|contains': ['cn=domain admins', 'cn=enterprise admins', 'cn=group policy creator owners']}, 'selection_allobject': {'metadata|contains': ["'filter': '(objectclass=*)'"]}, 'selection_suspicious': {'metadata|contains': ['(useraccountcontrol:1.2.840.113556.1.4.803:=4194304)', '(useraccountcontrol:1.2.840.113556.1.4.803:=2097152)', '!(useraccountcontrol:1.2.840.113556.1.4.803:=1048574)', '(useraccountcontrol:1.2.840.113556.1.4.803:=524288)', '(useraccountcontrol:1.2.840.113556.1.4.803:=65536)', '(useraccountcontrol:1.2.840.113556.1.4.803:=8192)', '(useraccountcontrol:1.2.840.113556.1.4.803:=544)', '!(useraccountcontrol:1.2.840.113556.1.4.803:=2)', 'msds-allowedtoactonbehalfofotheridentity', 'msds-allowedtodelegateto', 'msds-groupmanagedserviceaccount', '(accountexpires=9223372036854775807)', '(accountexpires=0)', '(admincount=1)', 'ms-mcs-admpwd']}, 'filter_generic': {'metadata|contains': ['(domainsid=', '(objectsid=', '(cn=']}, 'condition': 'selection_search and (((selection_generic or (selection_dn_enum and selection_allobject)) and not filter_generic) or selection_suspicious)'}

Log Source

Stellar Cyber Network Events configured for:

- Requirements: Network/Security/Modular sensor must be able to capture network traffic

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1482, T1087.002, T1069.002

References

- https://github.com/SigmaHQ/sigma/blob/master/rules/windows/builtin/ldap/win_ldap_recon.yml
- https://techcommunity.microsoft.com/t5/microsoft-defender-for-endpoint/hunting-for-reconnaissance-activities-using-ldap-search-filters/ba-p/824726
- https://github.com/PowerShellMafia/PowerSploit/blob/d943001a7defb5e0d1657085a77a0e78609be58f/Recon/PowerView.ps1
- https://github.com/BloodHoundAD/SharpHound3/blob/7d96b991b1887ff50349ce59c80980bc0d95c86a/SharpHound3/LdapBuilder.cs
- https://medium.com/falconforce/falconfriday-detecting-active-directory-data-collection-0xff21-c22d1a57494c
- https://github.com/fox-it/BloodHound.py/blob/d65eb614831cd30f26028ccb072f5e77ca287e0b/bloodhound/ad/domain.py#L427
- https://ipurple.team/2024/07/15/sharphound-detection/

Severity

Suppression Logic Based On

- srcip
- dstip
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2024/10/28	high	• LDAP search requests sent by legitimate tools or services

Oracle Cloud Infrastructure (OCI) Audit Rule IDs

Rule Details: OCI IAM Successful Group Deletion

Identifies the deletion of a specified Oracle Cloud Infrastructure (OCI) Identity and Access Management (IAM) group, which is a collection of users who share a similar set of access privileges. The group must be empty.

Rule ID

`oci_audit_1`

Query

```
{'selection1': {'eventName': 'deletegroup'}, 'selection2': {'status': ['200', '204']}
, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1531

References

N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/21	low	• Routine administrative tasks may trigger alerts when IAM groups are deleted as part of regular maintenance or restructuring. To manage this, create exceptions for known maintenance periods or specific administrative accounts.

Maturity	Creation Date	Risk Level	False Positives

- Automated scripts or tools that manage IAM resources might delete groups as part of their normal operation. Identify these scripts and exclude their actions from triggering alerts by using specific user or role identifiers.
- Temporary groups created for short-term projects or testing purposes might be deleted frequently. Document these groups and exclude their deletion from monitoring by using naming conventions or tags.
- Changes in organizational structure or policy might necessitate the deletion of certain groups. Coordinate with relevant teams to anticipate these changes and adjust monitoring rules accordingly.

Rule Details: OCI IAM Failure Group Deletion

Identifies failed attempts to delete OCI IAM groups, detecting events where the DeleteGroup action fails due to errors like Forbidden, Not Found, or Conflict. This activity is significant as it may indicate unauthorized attempts to modify IAM group configurations, which could be a precursor to privilege escalation or other malicious actions. If confirmed malicious, this could allow an attacker to disrupt IAM policies, potentially leading to unauthorized access or denial of service within the OCI environment.

Rule ID

`oci_audit_2`

Query

```
{'selection1': {'eventName': 'deletegroup'}, 'selection2': {'status': ['400', '401', '403', '404', '409', '412', '429']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

10

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/21	medium	• This detection will require tuning to provide high fidelity detection capabilities. Tune based on src addresses (corporate offices, VPN terminations) or by groups of users. Not every user with OCI access should have permission to delete groups (least privilege).

Rule Details: OCI IAM Delete Policy

The following detection identifies when a policy is deleted on OCI. This does not identify whether successful or failed, but the error messages tell a story of suspicious attempts.

Rule ID

`oci_audit_3`

Query

```
{'selection': {'eventName': 'deletepolicy'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

20

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/21	medium	• This detection will require tuning to provide high fidelity detection capabilities. Tune based on src addresses (corporate offices, VPN terminations) or by groups of users. Not every user with OCI access should have permission to delete policies (least privilege). In addition, this may be saved separately and tuned for failed or success attempts only.

Rule Details: OCI IAM Group Creation

Identifies the creation of a group in Oracle Cloud Infrastructure (OCI) Identity and Access Management (IAM). Groups specify permissions for multiple users. Any user in a group automatically has the permissions that are assigned to the group.

Rule ID

`oci_audit_4`

Query



```
{'selection': {'eventName': 'creategroup'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1136

References

N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	low	• Routine administrative actions by authorized personnel can trigger alerts. Regularly review and document legitimate group creation activities to differentiate them from unauthorized actions. • Automated scripts or tools used for infrastructure management may create groups as part of their normal operation. Identify and whitelist these scripts to prevent unnecessary alerts. • Temporary groups created for short-term projects or testing purposes might be flagged. Implement a naming convention for such groups and exclude them from alerts based on this pattern. • Scheduled tasks or maintenance activities that involve group creation should be logged and approved in advance. Use these logs to create exceptions in the detection rule. • Third-party integrations or services that require group creation for functionality can cause false positives. Verify these integrations and adjust the rule to exclude their known actions.

Rule Details: OCI Route Table Created

Identifies when an OCI Route Table has been created for the specified VCN.

Rule ID

`oci_audit_5`

Query

```
{'selection1': {'eventName': 'createroutetable'}, 'selection2': {'status': '200'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source



Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	low	• Routine infrastructure updates or deployments may trigger route table creation events. To manage this, establish a baseline of expected behavior during scheduled maintenance windows and exclude these from alerts. • Automated cloud management tools often create route tables as part of their operations. Identify these tools and create exceptions for their known activities to reduce noise. • Development and testing environments frequently undergo changes, including the creation of route tables. Consider excluding these environments from alerts or applying a different set of monitoring rules. • Legitimate changes by authorized personnel can be mistaken for suspicious activity. Implement a process to verify and document authorized changes, allowing for quick exclusion of these events from alerts. • Multi-account setups might have centralized networking teams that create route tables across accounts. Coordinate with these teams to understand their activities and exclude them from triggering alerts.

Rule Details: OCI Route Table Modified or Deleted

Identifies OCI events where a route table has been modified or deleted. Route table can be used by attackers to disrupt network traffic, reroute communications, or maintain persistence in a compromised environment.

Rule ID

`oci_audit_6`

Query

```
{'selection': {'eventName': ['deleteroutetable']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	low	• Route table modifications are often part of routine administrative tasks, such as creating new routes, updating associations, or removing unused resources. • Automated workflows may trigger these events. Verify whether the source IP matches known automation tools. • Confirm whether these actions align with maintenance activities or scaling events (e.g., adding or removing subnets).

Rule Details: OCI Network Security Group Configuration Change Detection

Identifies a change to an OCI network security group configuration. A network security group (NSG) provides virtual firewall rules for a specific set of VNICs in a VCN. A security rule is one of the items in a NetworkSecurityGroup; it can be for either inbound or outbound IP packets. Modifying configurations may allow unauthorized access. Threat actors may abuse this to establish persistence, exfiltrate data, or pivot in an OCI environment.

Rule ID

```
oci_audit_7
```

Query

```
{'selection': {'eventName': ['createnetworksecuritygroup', 'updatenetworksecuritygroup', 'deletenetworksecuritygroup', 'updatenetworksecuritygroupsecurityrules', 'removenetworksecuritygroupsecurityrules']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References
N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	low	• Network security group modifications may be part of regular infrastructure maintenance. Verify if this action aligns with known, scheduled administrative activities. • If you are using automated tools like `Terraform` or `CloudFormation`, confirm if the change matches expected configuration drift corrections or deployments.

Rule Details: OCI IAM Policy Modification

OCI IAM policies associated with a user have been modified.

Rule ID

`oci_audit_8`

Query

```
{'selection': {'eventName': ['addusertogroup', 'removeuserfromgroup']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References
N/A

Severity

50

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	medium	N/A

Rule Details: OCI Defense Evasion PutObjectLifecyclePolicy

This analytic identifies `PutObjectLifecyclePolicy` events in OCI audit logs where a user has created or replaced an object lifecycle policy for a bucket. This detection leverages OCI logs to identify suspicious lifecycle configurations. This activity is significant because attackers may use it to delete logs quickly, thereby evading detection and impairing forensic investigations. If confirmed malicious, this could allow attackers to cover their tracks, making it difficult to trace their actions and respond to the breach effectively.

Rule ID

`oci_audit_9`

Query

```
{'selection1': {'eventName': 'putobjectlifecyclepolicy'}, 'selection2': {'status': '200'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.008, TA0040, T1485.001

References

N/A

Severity

50

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	medium	• While this search has no known false positives, it is possible that it is a legitimate admin activity. Please consider filtering out these noisy events.

Rule Details: OCI Log Group Deletion

Identifies the deletion of a specified OCI LogGroup. When a log group is deleted, all the archived log entries associated with the log group are also permanently deleted.

Rule ID

`oci_audit_10`

Query

```
{'selection': {'eventName': 'deleteloggroup'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.001, TA0040, T1485

References

N/A

Severity

50

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	medium	• Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Log group deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. • If this rule is noisy in your environment due to expected activity, consider adding exceptions — preferably with a combination of user and IP address conditions.

Rule Details: OCI Log Object Deletion

Identifies the deletion of an OCI log object, which permanently deletes all associated archived log entries.

Rule ID

`oci_audit_11`

Query

```
{'selection': {'eventName': 'deletelog'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.001, TA0040, T1485

References

N/A

Severity

50

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	medium	• A log object may be deleted by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Log deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. • If this rule is noisy in your environment due to expected activity, consider adding exceptions — preferably with a combination of user and IP address conditions.

Rule Details: OCI Impair Security Services

Identifies attempts to delete critical OCI security service configurations, such as CloudGuard detector recipes and recipes from Vulnerability Scanning Service (VSS). This activity is significant because it indicates potential efforts to disable security monitoring and evade detection. If confirmed malicious, this could allow attackers to operate undetected, escalate privileges, or exfiltrate data without triggering security alerts, severely compromising the security posture of the OCI environment.

Rule ID

`oci_audit_12`

Query

```
{'selection': {'eventName': ['deletecontainerscanrecipe', 'deletehostscanrecipe', 'deletecontainerscantarget', 'deletehostscantarget', 'deletedetectorrecipe', 'deletedetectorrecipedetectorrule', 'deletedetectorrecipedetectorruledatasource']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.001

References
N/A

Severity

75

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	high	• Routine maintenance or administrative actions may lead to the deletion of a detector or scan recipe. Verify if the deletion aligns with scheduled maintenance or administrative tasks. • Automated scripts or tools used for environment cleanup might inadvertently delete detector or scan recipes. Review and adjust automation scripts to prevent unintended deletions. • Organizational policy changes or restructuring could result in recipe deletions. Ensure that policy changes are communicated and understood by all relevant teams to avoid unnecessary deletions. • Exclude known and authorized users or roles from triggering alerts by creating exceptions for specific IAM roles or user accounts that are responsible for legitimate recipe deletions. • Implement logging and alerting for recipe deletions to quickly identify and verify the legitimacy of the action, allowing for rapid response to potential false positives.

Rule Details: OCI Log Object Updated

Identifies an update to an existing OCI log object with configuration that specifies the delivery of log files.

Rule ID

```
oci_audit_13
```

Query

```
{'selection': {'eventName': 'updatelog'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1530, TA0040, T1565.001

References
N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/25	low	• Log object updates may be made by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Log object updates from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule -- preferably with a combination of user and IP address conditions.

Rule Details: OCI Potential Bucket Enumeration

Looks for potential enumeration of OCI buckets via ListBuckets. A bucket is a container for storing objects in a compartment within a namespace.

Rule ID

```
oci_audit_14
```

Query

```
{'selection': {'eventName': 'listbuckets'}, 'filter1': {'principalId|contains': ['.instance.', ':cloudguard-agent:']}, 'filter2': {'principalId|startswith': 'cloudguard/'}, 'condition': 'selection and not (filter1 or filter2)'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1580

References

N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/25	low	• Administrators listing buckets, it may be necessary to filter out users who commonly conduct this activity.

Rule Details: OCI IAM Deactivation of MFA Device

Identifies the deactivation of a specified multi-factor authentication (MFA) time-based one-time password (TOTP) device and removes it from association with the user for which it was originally enabled.

Rule ID

`oci_audit_15`

Query

```
{'selection': {'eventName': 'deletemfatotpdevice'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1531, TA0003, T1556.006

References

N/A

Severity

50

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/26	medium	• A MFA device may be deactivated by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. MFA device deactivations from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. • While this activity can be done by administrators, all users must use MFA. The security team should address any potential benign true positive (B-TP), as this configuration can risk the user and domain.

Rule Details: OCI Instance Image Export Failure

Identifies a failed attempt to export an OCI instance. A virtual machine (VM) export may indicate an attempt to extract or exfiltrate information.

Rule ID

`oci_audit_16`

Query

```
{'selection1': {'eventName': 'exportimage'}, 'selection2': {'status': ['400', '401', '404', '409', '412']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1005, TA0010, T1537

References

N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/26	low	• VM exports may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. VM exports from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. • Routine backup operations may trigger the rule if they involve failed export attempts. To manage this, identify and whitelist specific IAM roles or users that regularly perform legitimate backup tasks. • Development and testing environments often involve frequent export attempts for non-production instances. Exclude these environments by tagging instances appropriately and adjusting the detection rule to ignore these tags. • Misconfigured export tasks due to incorrect permissions or settings can lead to false positives. Regularly review and update IAM policies and export configurations to ensure they align with intended operations. • Automated scripts or tools that manage instances might occasionally fail due to transient issues, causing false alerts. Monitor and log these scripts' activities to distinguish between expected failures and potential threats.

Rule Details: OCI Kubernetes Cluster Created or Deleted

Detects when an OCI Kubernetes Cluster is created or deleted.

Rule ID

`oci_audit_17`

Query

```
{'selection': {'eventName': reatecluster', 'deletecluster']}, 'condition': 'select
ion'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1485

References

N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/27	low	• Kubernetes cluster being created or deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Kubernetes cluster created or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

Rule Details: OCI Event Rule Deleted

Detects when event rule was deleted.

Rule ID

```
oci_audit_18
```

Query

```
{'selection': {'eventName': 'deleterule'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1070

References
N/A

Severity
75

Suppression Logic Based On
- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/27	high	N/A

Rule Details: OCI Insecure Metadata Endpoint

Detects insecure metadata endpoint.

Rule ID

```
oci_audit_19
```

Query

```
{'selection': {'url|contains': ['/opc/v1', '/openstack'], 'status': '200'}, 'conditio
n': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1069

References
N/A

Severity
75

Suppression Logic Based On
- oracle.data.resourceId
- oracle.data.request.headers.oci-original-url
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/27	high	N/A

Rule Details: OCI Discovery Activity

Detects possible discovery activity.

Rule ID

`oci_audit_20`

Query

```
{'selection': {'eventName|startswith': ['get', 'list']}, 'condition': 'selection |
 count() by CreatedBy > 20', 'timeframe': '10m'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1580

References

N/A

Severity

50

Suppression Logic Based On

- oracle.data.definedTags.Oracle-Tags.CreatedBy
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/03/03	medium	N/A

Rule Details: OCI Multiple Instances Terminated

Detects when multiple instances were terminated.

Rule ID

`oci_audit_21`

Query

```
{'selection': {'eventName': 'TerminateInstance'}, 'condition': 'selection |
 count() by srcip >= 5', 'timeframe': '10m'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1529

References
N/A

Severity

75

Suppression Logic Based On

- srcip
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/03/03	high	N/A

Rule Details: OCI Multiple Instances Launched

Detects when multiple instances were launched.

Rule ID

```
oci_audit_22
```

Query

```
{'selection': {'eventName': 'LaunchInstance'}, 'condition': 'selection |
 count() by srcip >= 5', 'timeframe': '10m'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1496

References
N/A

Severity

50

Suppression Logic Based On

- srcip
- stellar.rule_id

Additional Information

Maturity	Creation D	Risk Level	False Positives
experimental	2025/03/03	medium	N/A

Rule Details: OCI Unexpected User Agent

Detects unexpected user agent strings.

Rule ID

`oci_audit_23`

Query

```
{'selection': {'userAgent|re': '^.{1,10}$'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1190

References

N/A

Severity

50

Suppression Logic Based On

- oracle.data.identity.userAgent
- srcip
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/03/04	medium	N/A

Rule Details: OCI Bucket Public Access Type Configuration

Identifies potential OCI bucket misconfiguration of public access type. A bucket is a container for storing objects in a compartment within a namespace. If a bucket that contains sensitive information is set to be public accessible, it can lead to subsequent data exfiltration.

Rule ID

`oci_audit_24`

Query

```
{'selection': {'eventName': ['createbucket', 'updatebucket']}, 'filter1': {'publicAcc
essType': 'NoPublicAccess'}, 'condition': 'selection and not filter1'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1580

References

N/A

Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/04/16	low	• A bucket could be intentionally configured to be publicly accessible and does not contain any sensitive information.

Rule Details: OCI Insecure NFS Export

Identifies potentially insecure OCI NFS server export configuration. If the NFS server is poorly configured (e.g., no IP or read-only restrictions and no root squash), malicious hosts can mount the file systems and lead to subsequent data exfiltration.

Rule ID

```
oci_audit_25
```

Query

```
{'selection': {'eventName': ['createexport', 'updateexport']}, 'filter1': {'exportSource': '0.0.0.0/0'}, 'filter2': {'exportAccess': 'READ_ONLY'}, 'filter3': {'exportIdentitySquash': 'NONE'}, 'condition': 'selection and (filter1 or not filter2 or filter3)'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1580

References
N/A



Severity

25

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/04/16	low	• An NFS server could be intentionally configured without IP or read-only restrictions, or without root squash.

OCI Virtual Cloud Network (VCN) Rule IDs

Rule Details: OCI Inbound SSH Connection

Detects inbound SSH connection.

Rule ID

`oci_vcn_1`

Query

```
{'selection1': {'srcip_type': 'private'}, 'selection2': {'dstport': 22}, 'condition':
 'not selection1 and selection2'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1190

References
N/A

Severity

50

Suppression Logic Based On

- srcip
- dstip
- stellar.rule_id

Additional Information

Maturity	Creation D	Risk Level	False Positives
experimental	2025/02/27	medium	N/A

Rule Details: OCI Instance Metadata Access

Detects instance metadata access.

Rule ID

```
oci_vcn_2
```

Query

```
{'selection': {'dstip': '169.254.169.254'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1069

References

N/A

Severity

50

Suppression Logic Based On

- srcip
- dstip
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/28	medium	N/A

Rule Details: OCI SSH Scanner

Detects possible SSH scanning activity.

Rule ID

```
oci_vcn_3
```

Query

```
{'selection1': {'action': 'REJECT', 'dstip_type': 'private', 'dstport': 22}, 'selecti
on2': {'srcip_type': 'private'}, 'condition': 'selection1 and not selection2 |
 count(dstip) by srcip > 5', 'timeframe': '5m'}
```

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0043, T1595

References

N/A

Severity

75

Suppression Logic Based On

- srcip
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/03/03	high	N/A

Office 365 Mail Rule IDs

Rule Details: Office365 Mail Redirect via ExO Transport Rule

Identifies when an Exchange Online transport rule is configured to forward emails. This could be an adversary mailbox configured to collect mail from multiple user accounts.

Rule ID

`office365_mail_1`

Query

```
{'selection1': {'Operation': ['new-transportrule', 'set-transportrule']}, 'selection2': {'BlindCopyTo': ''}, 'selection3': {'RedirectMessageTo': ''}, 'condition': 'selection1 and (not selection2 or not selection3)'}
```

Log Source

Stellar Cyber Microsoft 365 configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1114, TA0010, T1020

References

N/A

Severity

50

Suppression Logic Based On

- office365.Operation
- office365.ObjectId
- office365.Name
- user.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/06/09	medium	N/A

Rule Details: Malicious Office365 Inbox Rule

Often times after the initial compromise, the attackers create inbox rules to delete emails that contain certain keywords. This is done so as to limit ability to warn compromised users that they have been compromised.

Rule ID

`office365_mail_2`

Query


```
{'selection1': {'Operation': 'new-
inboxrule', 'ResultStatus': ['true', 'succeeded'], 'Parameters|contains': ['deleted i
tems', 'junk email', 'deletemessage']}, 'selection2': {'SubjectContainsWords|contains
': ['helpdesk', ' alert', ' suspicious', 'fake', 'malicious', 'phishing', 'spam', 'do
 not click', 'do not open', 'hijacked', 'fatal']}, 'selection3': {'BodyContainsWords|
contains': ['helpdesk', ' alert', ' suspicious', 'fake', 'malicious', 'phishing', 'sp
am', 'do not click', 'do not open', 'hijacked', 'fatal']}, 'selection4': {'SubjectOrB
odyContainsWords|contains': ['helpdesk', ' alert', ' suspicious', 'fake', 'malicious'
, 'phishing', 'spam', 'do not click', 'do not open', 'hijacked', 'fatal']}, 'conditio
n': 'selection1 and (selection2 or selection3 or selection4)'}
```


Log Source

Stellar Cyber Microsoft 365 configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1564.008, TA0003, T1098

References

- https://www.reddit.com/r/sysadmin/comments/7kyp0a/recent_phishing_attempts_my_experience_and_what/

Severity

50

Suppression Logic Based On

- office365.Operation
- user.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/06/09	medium	N/A

Rule Details: Suspicious Office365 Inbox MoveToFolder Rule

Identifies when the parameters of Microsoft 365 inbox MoveToFolder rules have suspicious characteristics that move emails to the RSS folder, which attackers sometimes use to hide incoming mail like security alerts or MFA notifications.

Rule ID

`office365_mail_3`

Query

```
{'selection': {'Operation': ['new-inboxrule', 'set-
inboxrule'], 'MoveToFolder|contains': 'rss'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Microsoft 365 configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1564.008, TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- office365.Operation
- user.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/06/09	medium	N/A

Rule Details: Suspicious Office365 Inbox Rule Name

Identifies when the parameters of Microsoft 365 inbox rules have suspicious characteristics that are often used in automated or attacker-created rules, specifically rule names that contain strange strings or strings used in known attacks.

Rule ID

`office365_mail_4`

Query


```
{'selection1': {'Operation': ['new-inboxrule', 'set-
inboxrule']}, 'selection2': {'Name|contains': ['erder', 'ddd']}, 'selection3': [{'Nam
e|re': '/(^|\\s+)\\.+($|\\s+)/'}, {'Name|re': '/(^|\\s+)\\w{0,3}\\.\\w{0,3}
($|\\s+)/'}, {'Name|re': '/(^|\\s+).($|\\s+)/'}, {'Name|re': '/(^|\\s+)\\,+,
($|\\s+)/'}, {'Name|re': '/(^|\\s+)\\W{0,4}($|\\s+)/'}, {'Name|re': '/(^|\\s+)
(.)\\1{0,3}($|\\s+)/'}, {'Name|re': '/(^|\\s+)[a-z]{0,3}
($|\\s+)/'}], 'condition': 'selection1 and (selection2 or selection3)'}
```


Log Source

Stellar Cyber Microsoft 365 configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1564.008, TA0003, T1098

References

N/A

Severity

25

Suppression Logic Based On

- office365.Operation
- user.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/06/09	low	N/A

Rule Details: Rare and Potentially High-Risk Office365 Operations

Identifies Office365 operations that are typically rare and can provide capabilities useful to attackers.

Rule ID

`office365_mail_5`

Query

{'selection1': {'Operation': ['add-mailboxfolderpermission', 'new-managementroleassignment', 'new-inboxrule', 'set-inboxrule', 'set-transportrule']}, 'selection2': {'Operation': ['add-mailboxpermission', 'set-mailbox']}, 'selection3': {'UserId|contains': ['nt authority\\system (microsoft.exchange.servicehost)', 'nt authority\\system (microsoft.exchange.adminapi.netcore)', 'nt authority\\system (w3wp)', 'devilfish-applicationaccount']}, 'condition': 'selection1 or (selection2 and not selection3)'}

Log Source

Stellar Cyber Microsoft 365 configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098, TA0009, T1114

References

N/A

Severity

25

Suppression Logic Based On

- office365.Operation
- user.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/06/09	low	N/A

Rule Details: Malicious Office365 Inbox Deletion Rule

Identifies when a Microsoft 365 inbox rule is set up such that it deletes all incoming messages, without specifying any condition (e.g., from a specific sender, with a certain subject, etc.). Attackers often use this to hide inbound warnings, MFA emails, or incident response communication after compromising an account.

Rule ID

`office365_mail_6`

Query

{'selection': {'Operation': ['new-inboxrule', 'set-inboxrule'], 'DeleteMessage': 'true'}, 'condition': 'selection'}

Log Source

Stellar Cyber Microsoft 365 configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1564.008, TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- office365.Operation
- user.name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/06/09	medium	N/A

PowerShell Command and Control (CNC) Rule IDs

Rule Details: PowerShell Remote Access

A Windows host executed a PowerShell script interacting with a remote host. Investigate the script and the remote host to determine whether the script is malicious. If so, consider quarantining the host.

Rule ID

`powershell_cnc_2200`

Query

```
{'selection1': {'DetectionFlag': 2200}, 'selection2': [{'RemoteIP|re': '^169\\.254\\.169\\.254$'}, {'RemoteIP|re': '\\.0$'}], 'condition': 'selection1 and not selection2'}
```

Detection Flag

Note: `detection_flag` is a Stellar enriched field.

- **2200:** PowerShell script embedded with remote IP

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059

References
N/A

Severity

80

Suppression Logic Based On

- computer_name
- remote_ip
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/03/30	critical	N/A

Rule Details: PowerShell Remote Access (High Fidelity)

A Windows host executed a PowerShell script interacting with a remote host. Investigate the script and the remote host to determine whether the script is malicious. If so, consider quarantining the host.

Rule ID

```
powershell_cnc_2201
```

Query

```
{'selection1': {'DetectionFlag': 2201}, 'selection2': [{'RemoteIP|re': '^169\\.254\\.169\\.254$'}, {'RemoteIP|re': '\\.0$'}], 'condition': 'selection1 and not selection2'}
```

Detection Flag

Note: `detection_flag` is a Stellar enriched field.

- **2201:** PowerShell script block with IP embedded at warning level (High fidelity)

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059

References
N/A

Severity

80

Suppression Logic Based On

- computer_name
- remote_ip
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/03/30	critical	N/A

PowerShell Scriptblock Rule ID

Rule Details: PowerShell Mailbox Collection Script

Detects PowerShell scripts that can be used to collect data from mailboxes. Adversaries may target user email to collect sensitive information.

Rule ID

`powershell_scriptblock_1`

Query


```
{'selection1': {'ScriptBlockText|contains': ['Microsoft.Office.Interop.Outlook', 'Interop.Outlook.olDefaultFolders', '::olFolderInBox', 'Microsoft.Exchange.WebServices.Data.Folder', 'Microsoft.Exchange.WebServices.Data.FileAttachment']}, 'condition': 'selection1'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0009, T1114

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2023/01/11	medium	N/A

Rule Details: Live Memory Dump Using Powershell

Detects usage of a PowerShell mand to dump the live memory of a Windows machine.

Rule ID

`powershell_scriptblock_3`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Get-StorageDiagnosticInfo', '-IncludeLiveDump']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,cd185561-4760-45d6-a63e-a51325112cae

Author: Max Altgelt (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1003

References

- https://docs.microsoft.com/en-us/powershell/module/storage/get-storagediagnosticinfo

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/21	high	• Diagnostics

Rule Details: Invoke-Obfuscation CLIP+ Launcher - PowerShell

Detects Obfuscated use of Clip.exe to execute PowerShell.

Rule ID

`powershell_scriptblock_4`

Query

```
{'selection_4104': {'ScriptBlockText|re': '.*cmd.{0,5}(?:/c|/r).+clip(?:\\.exe)?.{0,4}&&.+clipboard]::\\(\\s\\\\"\\{\\d\\}.+-f.+"'}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,73e67340-0d25-11eb-adc1-0242ac120002

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/13	high	• Unknown

Rule Details: Suspicious Service DACL Modification Via Set-Service Cmdlet - PS

Detects usage of the "Set-Service" powershell cmdlet to configure a new SecurityDescriptor that allows a service to be hidden from other utilities such as "sc.exe", "Get-Service"...etc. (Works only in powershell 7.)

Rule ID

```
powershell_scriptblock_5
```

Query

```
{'selection_sddl_flag': {'ScriptBlockText|contains': ['-SecurityDescriptorSddl ', '-sd ']}, 'selection_set_service': {'ScriptBlockText|contains|all': ['Set-Service ', 'D;;'], 'ScriptBlockText|contains': [';;;IU', ';;;SU', ';;;BA', ';;;SY', ';;;WD']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,22d80745-6f2c-46da-826b-77adaededd74

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1574.011

References

- https://twitter.com/Alh4zr3d/status/1580925761996828672
- https://learn.microsoft.com/en-us/powershell/module/microsoft.powershell.management/set-service?view=powershell-7.2

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/24	high	• Rare intended use of hidden services • Rare FP could occure due to the non linearity of the ScriptBlockText log

Rule Details: Potential Invoke-Mimikatz PowerShell Script

Detects Invoke-Mimikatz PowerShell script and alike. Mimikatz is a credential dumper capable of obtaining plaintext Windows account logins and passwords.

Rule ID

`powershell_scriptblock_6`

Query


```
{'selection_1': {'ScriptBlockText|contains|all': ['DumpCreds', 'DumpCerts']}, 'selection_2': {'ScriptBlockText|contains': 'sekurlsa::logonpasswords'}, 'selection_3': {'ScriptBlockText|contains|all': ['crypto::certificates', 'CERT_SYSTEM_STORE_LOCAL_MACHINE']}, 'condition': '1 of selection*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

SigmaHQ,189e3b02-82b2-4b90-9662-411eb64486d4

Author: Tim Rauch, Elastic (idea)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1003

References

- https://www.elastic.co/guide/en/security/current/potential-invoke-mimikatz-powershell-script.html#potential-invoke-mimikatz-powershell-script

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/28	high	• Mimikatz can be useful for testing the security of networks

Rule Details: Disable-WindowsOptionalFeature Command PowerShell

Detect built in PowerShell cmdlet Disable-WindowsOptionalFeature, Deployment Image Servicing and Management tool. Similar to DISM.exe, this cmdlet is used to enumerate, install, uninstall, configure, and update features and packages in Windows images.

Rule ID

```
powershell_scriptblock_7
```

Query

```
{'selection_cmd': {'ScriptBlockText|contains|all': ['Disable-
WindowsOptionalFeature', '-Online', '-
FeatureName']}, 'selection_feature': {'ScriptBlockText|contains': ['Windows-Defender-
Gui', 'Windows-Defender-Features', 'Windows-Defender', 'Windows-Defender-
ApplicationGuard']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,99c4658d-2c5e-4d87-828d-7c066ca537c3

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1562.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/5b67c9b141[illegible]918017f8fa44f2f88f0b1ecb9e1/atomics/T1562.001/T1562.001.md
- https://docs.microsoft.com/en-us/powershell/module/dism/disable-windowsoptionalfeature?view=windowsserver2022-ps

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/10	high	• Unknown

Rule Details: Powershell DNSExfiltration

DNSExfiltrator allows for transferring (exfiltrate) a file over a DNS request covert channel.

Rule ID

`powershell_scriptblock_8`

Query

```
{'selection_cmdlet': [{'ScriptBlockText|contains': 'Invoke-DNSExfiltrator'}, {'ScriptBlockText|contains|all': [' -i ', ' -d ', ' -p ', ' -doh ', ' -t ']}], 'condition': 'selection_cmdlet'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,d59d7842-9a21-4bc6-ba98-64bfe0091355

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0010, T1048

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1048/T1048.md#atomic-test-3---dnsexfiltration-doh
- https://github.com/Arno0x/DNSExfiltrator

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/07	high	• Legitimate script

Rule Details: Powershell Empire agent CnC activity

A Powershell Empire framework agent is running on the machine, and it's trying to access the CnC server.

Rule ID

`powershell_scriptblock_9`

Query

```
{'selection1': {'ScriptBlockText|contains': 'IF($PSVERSIonTAblE.PSVERsIOn.MajOr -
ge 3)
{'}, 'selection2': {'ScriptBlockText|contains': '[Ref].ASsEmbLY.GeTTYpe('}, 'selectio
n3': {'ScriptBlockText|contains': 'System.Management.Automation.AmsiUtils'}, 'conditi
on': 'selection1 and selection2 and selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Powershell Directory Enumeration

Detects technique used by MAZE ransomware to enumerate directories using Powershell.

Rule ID

`powershell_scriptblock_10`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['foreach', 'Get-ChildItem', '-Path ', '-ErrorAction ', 'SilentlyContinue', 'Out-File ', '-append']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,162e69a7-7981-4344-84a9-0f1c9a217a52

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1083

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1083/T1083.md
- https://www.mandiant.com/resources/tactics-techniques-procedures-associated-with-maze-ransomware-incidents

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/17	medium	• Legitimate PowerShell scripts

Rule Details: Invoke-Obfuscation Via Use MSHTA - PowerShell

Detects Obfuscated Powershell via use MSHTA in Scripts.

Rule ID

`powershell_scriptblock_11`

Query

{'selection_4104': {'ScriptBlockText|contains|all': ['set', '&&', 'mshta', 'vbscript:createobject', '.run', '(window.close)']}, 'condition': 'selection_4104'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,e55a5195-4724-480e-a77e-3ebe64bd3759

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/08	high	• Unknown

Rule Details: Root Certificate Installed - PowerShell

Adversaries may install a root certificate on a compromised system to avoid warnings when connecting to adversary controlled web servers.

Rule ID

`powershell_scriptblock_12`

Query

{'selection1': {'ScriptBlockText|contains|all': ['Move-Item', 'Cert:\\LocalMachine\\Root']}, 'selection2': {'ScriptBlockText|contains|all': ['Import-Certificate', 'Cert:\\LocalMachine\\Root']}, 'condition': '1 of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,42821614-9264-4761-acfc-5772c3286f76

Author: oscd.community, @redcanary, Zach Stanford @svch0st

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1553.004

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1553.004/T1553.004.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/10	medium	• Help Desk or IT may need to manually add a corporate Root CA on occasion. Need to test if GPO push doesn't trigger FP

Rule Details: Clearing Windows Console History

Identifies when a user attempts to clear console history. An adversary may clear the command history of a compromised account to conceal the actions undertaken during an intrusion.

Rule ID

```
powershell_scriptblock_15
```

Query

```
{'selection1': {'ScriptBlockText|contains': 'Clear-
History'}, 'selection2a': {'ScriptBlockText|contains': ['Remove-
Item', 'rm']}, 'selection2b': {'ScriptBlockText|contains': ['ConsoleHost_history.txt'
, '(Get-
PSReadlineOption).HistorySavePath']}, 'condition': 'selection1 or selection2a and sel
ection2b'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,bde47d4b-9987-405c-c7-b080410e8ea7

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1070.003

References

- https://stefanos.cloud/blog/kb/how-to-clear-the-powershell-command-history/
- https://www.shellhacks.com/clear-history-powershell/
- https://community.sophos.com/sophos-labs/b/blog/posts/powershell-command-history-forensics

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/11/25	high	• Unknown

Rule Details: Windows Firewall Profile Disabled

Detects when a user disables the Windows Firewall via a Profile to help evade defense.

Rule ID

`powershell_scriptblock_16`

Query

```
{'selection_args': {'ScriptBlockText|contains|all': ['Set-NetFirewallProfile ', ' -Enabled ', ' False']}, 'selection_opt': {'ScriptBlockText|contains': [' -All ', 'Public', 'Domain', 'Private']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,488b44e7-3781-4a71-888d-c95abfacf44d

Author: Austin Songer @austinsonger

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1562.004

References

- https://docs.microsoft.com/en-us/powershell/module/netsecurity/set-netfirewallprofile?view=windowsserver2019-ps
- https://www.tutorialspoint.com/how-to-get-windows-firewall-profile-settings-using-powershell
- http://powershellhelp.space/commands/set-netfirewallrule-psv5.php
- http://woshub.com/manage-windows-firewall-powershell/
- https://www.elastic.co/guide/en/security/current/windows-firewall-disabled-via-powershell.html

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/10/12	medium	• Unknown

Rule Details: Suspicious Portable Executable Encoded in Powershell Script

Detects the presence of a portable executable (PE) in a PowerShell script by looking for its encoded header. Attackers embed PEs into PowerShell scripts to inject them into memory, avoiding defences by not writing to disk.

Rule ID

`powershell_scriptblock_17`

Query

```
{'selection1': {'ScriptBlockText|contains': 'TVqQAAMAAAAEAAAA'}, 'selection2': {'User Id': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity



49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/10/15	medium	N/A

Rule Details: PowerShell Suspicious Script with Screenshot Capabilities

Detects PowerShell scripts that can take screenshots, which is a common feature in post-exploitation kits and remote access tools (RATs).

Rule ID

`powershell_scriptblock_19`

Query

```
{'selection1': {'ScriptBlockText|contains': 'CopyFromScreen'}, 'selection2': {'Script
BlockText|contains': 'System.Drawing.Bitmap'}, 'selection3': {'ScriptBlockText|contai
ns': 'Drawing.Bitmap'}, 'selection4': {'UserId': 'S-1-5-
18'}, 'condition': 'selection1 and (selection2 or selection3) and (not selection4)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0009, T1113

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/10/19	medium	N/A

Rule Details: Registry-Free Process Scope COR_PROFILER

Adversaries may leverage the COR_PROFILER environment variable to hijack the execution flow of programs that load the .NET CLR. The COR_PROFILER is a .NET Framework feature which allows developers to specify an unmanaged (or external of .NET) profiling DLL to be loaded into each .NET process that loads the Common Language Runtime (CLR). These profiliers are designed to monitor, troubleshoot, and debug managed code executed by the .NET CLR. (Citation: Microsoft Profiling Mar 2017) (Citation: Microsoft COR_PROFILER Feb 2013)

Rule ID

`powershell_scriptblock_20`

Query


```
{'selection': {'ScriptBlockText|contains|all': ['$env:COR_ENABLE_PROFILING', '$env:COR_PROFILER', '$env:COR_PROFILER_PATH']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,23590215-4702-4a70-8805-8dc9e58314a2

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1574.012

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1574.012/T1574.012.md#atomic-test-3---registry-free-process-scope-cor_profiler

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/30	medium	• Legitimate administrative script

Rule Details: Invoke-Obfuscation RUNDLL LAUNCHER - PowerShell

Detects Obfuscated Powershell RUNDLL LAUNCHER.

Rule ID

`powershell_scriptblock_21`

Query

```
{'selection_4104': {'ScriptBlockText|contains|all': ['rundll32.exe', 'shell32.dll', '
shellexec_rundll', 'powershell']}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,e6cb92b4-b470-4eb8-8a9d-d63e8583aae0

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/18	medium	• Unknown

Rule Details: Execution via CL_Invocation.ps1 - Powershell

Detects Execution via SyncInvoke in CL_Invocation.ps1 module.

Rule ID

`powershell_scriptblock_23`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['CL_Invocation.ps1', 'SyncInvoke']},
'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,4cd29327-685a-460e-9dac-c3ab96e549dc

Author: oscd.community, Natalia Shornikova

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1216

References

- https://lolbas-project.github.io/lolbas/Scripts/CI_invocation/
- https://twitter.com/bohops/status/948061991012327424

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/14	high	• Unknown

Rule Details: Suspicious TCP Tunnel Via PowerShell Script

Detects powershell scripts that creates sockets/listeners which could be indicative of tunneling activity.

Rule ID

```
powershell_scriptblock_24
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['[System.Net.HttpWebRequest]', 'System.Net.Sockets.TcpListener', 'AcceptTcpClient']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,bd33d2aa-497e-4651-9893-5c5364646595

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0[redacted], T1090

References

- https://github.com/Arno0x/PowerShellScripts/blob/a6b7d5490fbf0b20f91195838f3a11156724b4f7/proxyTunnel.ps1

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/07/08	medium	• Unknown

Rule Details: Powershell Store File In Alternate Data Stream

Storing files in Alternate Data Stream (ADS) similar to Astaroth malware.

Rule ID

```
powershell_scriptblock_25
```

Query

```
{'selection_compspec': {'ScriptBlockText|contains|all': ['Start-Process', '-FilePath "$env:comspec" ', '-ArgumentList ', '>']}, 'condition': 'selection_compspec'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,a699b30e-d010-46c8-bbd1-ee2e26765fe9

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1564.004

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1564.004/T1564.004.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/02	medium	• Unknown

Rule Details: Potential PowerShell Obfuscation Using Character Join

Detects specific techniques often seen used inside of PowerShell scripts to obfscuate Alias creation.

Rule ID

`powershell_scriptblock_26`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['-Alias', ' -Value (-join(']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,e8314f79-564d-4f79-bc13-fbc0bf2660d8

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

N/A

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/09	low	• Unknown

Rule Details: Windows UAC Bypass

A User Account Control Bypass activity was detected. This can be due to either regular operation or because an attacker is trying to escalate privileges.

Rule ID

```
powershell_scriptblock_27
```

Query

```
{'selection1': {'ScriptBlockText|contains': 'Invoke-
UACBypass'}, 'selection2': {'ScriptBlockText|contains': 'Invoke-
EventVwrBypass'}, 'selection3': {'ScriptBlockText|contains': 'Invoke-
SDCLTBypass'}, 'condition': 'selection1 or selection2 or selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Suspicious IO.FileStream

Open a handle on the drive volume via the \\.\ DOS device path specifier and perform direct access read of the first few bytes of the volume.

Rule ID

```
powershell_scriptblock_28
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['New-
Object', 'IO.FileStream', '\\\\.\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,70ad982f-67c8-40e0-a955-b920c2fa05cb

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1070.003

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1006/T1006.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/09	medium	• Legitimate PowerShell scripts

Rule Details: Invoke-Obfuscation VAR+ Launcher - PowerShell

Detects Obfuscated use of Environment Variables to execute PowerShell.

Rule ID

```
powershell_scriptblock_29
```

Query

```
{'selection_4104': {'ScriptBlockText|re': '.*cmd.{0,5}(?:/c|/r)(?:\\s|)"set\\s[a-zA-Z]{3,6}.*(?:\\{\\d\\}){1,}\\\\"\\s+?-f(?:.*\\)){1,}.*"'}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,0adfbc14-0ed1-11eb-adc1-0242ac120002

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/15	high	• Unknown

Rule Details: Powershell XML Execute Command

Adversaries may abuse PowerShell commands and scripts for execution. PowerShell is a powerful interactive command-line interface and scripting environment included in the Windows operating system. (Citation: TechNet PowerShell) Adversaries can use PowerShell to perform a number of actions, including discovery of information and execution of code.

Rule ID

`powershell_scriptblock_30`

Query

```
{'selection_xml': {'ScriptBlockText|contains|all': ['New-
Object', 'System.Xml.XmlDocument', '.Load']}, 'selection_exec': {'ScriptBlockText|con
tains': ['IEX ', 'Invoke-Expression ', 'Invoke-Command ', 'ICM -
']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,6c6c6282-7671-4fe9-a0ce-a2dcebdc342b

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1059.001/T1059.001.md#atomic-test-8---powershell-xml-requests

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/01/19	medium	• Legitimate administrative script

Rule Details: Dump Credentials from Windows Credential Manager With PowerShell

Adversaries may search for common password storage locations to obtain user credentials. Passwords are stored in several places on a system, depending on the operating system or application holding the credentials.

Rule ID

`powershell_scriptblock_33`

Query


```
{'selection_kiddie': {'ScriptBlockText|contains': ['Get-PasswordVaultCredentials', 'Get-CredManCreds']}, 'selection_rename_Password': {'ScriptBlockText|contains|all': ['New-Object', 'Windows.Security.Credentials.PasswordVault']}, 'selection_rename_credman': {'ScriptBlockText|contains|all': ['New-Object', 'Microsoft.CSharp.CSharpCodeProvider', '[System.Runtime.InteropServices.RuntimeEnvironment]::GetRuntimeDirectory())', 'Collections.ArrayList', 'System.CodeDom.Compiler.CompilerParameters']}, 'condition': '1 of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,99c49d9c-34ea-45f7-84a7-4751ae6b2cbc

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1555

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d[illegible]6057fdfcdd3742bfcf365fee2a9/atomics/T1555/T1555.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/20	medium	• Unknown

Rule Details: Potential Suspicious Windows Feature Enabled

Detects usage of the built-in PowerShell cmdlet "Enable-WindowsOptionalFeature" used as a Deployment Image Servicing and Management tool. Similar to DISM.exe, this cmdlet is used to enumerate, install, uninstall, configure, and update features and packages in Windows images.

Rule ID

```
powershell_scriptblock_35
```

Query

```
{'selection_cmd': {'ScriptBlockText|contains|all': ['Enable-
WindowsOptionalFeature', '-Online', '-
FeatureName']}, 'selection_feature': {'ScriptBlockText|contains': ['TelnetServer', 'I
nternet-Explorer-Optional-amd64', 'TFTP', 'SMB1Protocol', 'Client-
ProjFS', 'Microsoft-Windows-Subsystem-Linux']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,55c925c1-7195-426b-a136-a9396800e29b

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://docs.microsoft.com/en-us/powershell/module/dism/enable-windowsoptionalfeature?view=windowsserver2022-ps
- https://learn.microsoft.com/en-us/windows/win32/projfs/enabling-windows-projected-file-system

- https://learn.microsoft.com/en-us/windows/wsl/install-on-server

Severity



49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/10	medium	• Unknown

Rule Details: Suspicious PowerShell Mailbox SMTP Forward Rule

Detects usage of the powerShell Set-Mailbox Cmdlet to set-up an SMTP forwarding rule.

Rule ID

`powershell_scriptblock_36`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Set-Mailbox ', ' -DeliverToMailboxAndForward ', ' -ForwardingSmtpAddress ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,15b7abbb-8b40-4d01-9ee2-b51994b1d474

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://m365internals.com/2022/10/07/hunting-in-on-premises-exchange-server-logs/

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/26	me	• Legitimate usage of the cmdlet to forward emails

Rule Details: Powershell Add Name Resolution Policy Table Rule

Detects powershell scripts that adds a Name Resolution Policy Table (NRPT) rule for the specified namespace. This will bypass the default DNS server and uses a specified server for answering the query.

Rule ID

```
powershell_scriptblock_37
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Add-DnsClientNrptRule', '-Namesp', '-NameSe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,4368354e-1797-463c-bc39-a309effbe8d7

Author: Borna Talebi

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0040, T1565

References

- https://twitter.com/NathanMcNulty/status/1569497348841287681
- https://docs.microsoft.com/en-us/powershell/module/dnsclient/add-dnsclientnrptrule?view=windowsserver2022-ps

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/14	high	• Unknown

Rule Details: Security Software Discovery by Powershell

Adversaries may attempt to get a listing of security software, configurations, defensive tools, and sensors that are installed on a system or in a cloud environment. This may include things such as firewall rules and anti-virus.

Rule ID

```
powershell_scriptblock_38
```

Query

```
{'selection_1': {'ScriptBlockText|contains|all': ['get-process', '.Description', '-like']}, 'selection_2': {'ScriptBlockText|contains': ['"*virus*"', '"*carbonblack*"', '"*defender*"', '"*cylance*"']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,904e8e61-8edf-4350-b59c-b905fc8e810c

Author: frack113, Anish Bogati, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1518.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1518.001/T1518.001.md

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/16	low	• Unknown

Rule Details: Suspicious New-PSDrive to Admin Share

Adversaries may use to interact with a remote network share using Server Message Block (SMB). The adversary may then perform actions as the logged-on user.

Rule ID

```
powershell_scriptblock_39
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['New-PSDrive', '-psprovider ', 'filesystem', '-root ', '\\\\', '$']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,1c563233-030e-4a07-af8c-ee0490a66d3a

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0008, T1021.002

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1021.002/T1021.002.md#atomic-test-2---map-admin-share-powershell
- https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.management/new-psdrive?view=powershell-7.2

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/13	medium	• Unknown

Rule Details: PowerShell Script with Token Impersonation Capabilities

Detects scripts that contain PowerShell functions, structures, or Windows API functions related to token impersonation/theft. Attackers may duplicate then impersonate another user's token to escalate privileges and bypass access controls.

Rule ID

```
powershell_scriptblock_40
```

Query

{'selection1': {'ScriptBlockText|contains': ['Invoke-TokenManipulation', 'ImpersonateNamedPipeClient', 'NtImpersonateThread']}, 'selection2': {'ScriptBlockText|contains': 'STARTUPINFOEX'}, 'selection3': {'ScriptBlockText|contains': 'UpdateProcThreadAttribute'}, 'selection4': {'ScriptBlockText|contains': 'AdjustTokenPrivileges'}, 'selection5': {'ScriptBlockText|contains': 'SeDebugPrivilege'}, 'selection6': {'UserId': 'S-1-5-18'}, 'condition': '(selection1 or (selection2 and selection3) or (selection4 and selection5)) and (not selection6)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, T1106, TA0005, T1134

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/08/17	medium	N/A

Rule Details: Disable of ETW Trace - Powershell

Detects usage of powershell cmdlets to disable or remove ETW trace sessions.

Rule ID

`powershell_scriptblock_41`

Query

{'selection_pwsh_remove': {'ScriptBlockText|contains': 'Remove-EtwTraceProvider '}, 'selection_pwsh_set': {'ScriptBlockText|contains|all': ['Set-EtwTraceProvider ', '0x11']}, 'condition': '1 of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,115fdba9-f017-42e6-84cf-d5573bf2ddf8

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1070, T1562.006

References

- https://medium.com/palantir/tampering-with-windows-event-tracing-background-offense-and-defense-4be7ac62ac63

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/28	high	• Unknown

Rule Details: Service Registry Permissions Weakness Check

Adversaries may execute their own malicious payloads by hijacking the Registry entries used by services. Adversaries may use flaws in the permissions for registry to redirect from the originally specified executable to one that they control, in order to launch their own code at Service start. Windows stores local service configuration information in the Registry under HKLM\SYSTEM\CurrentControlSet\Services.

Rule ID

`powershell_scriptblock_42`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['get-acl', 'REGISTRY::HKLM\\SYSTEM\\CurrentControlSet\\Services\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,95afc12e-3cbb-40c3-9340-84a032e596a3

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1574.011

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1574.011/T1574.011.md#atomic-test-1---service-registry-permissions-weakness
- https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.security/get-acl?view=powershell-7.2

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/30	medium	• Legitimate administrative script

Rule Details: Potential COM Objects Download Cradles Usage - PS Script

Detects usage of COM objects that can be abused to download files in PowerShell by CLSID.

Rule ID

`powershell_scriptblock_43`

Query


```
{'selection_1': {'ScriptBlockText|contains': '[Type]::GetTypeFromCLSID('}, 'selection_2': {'ScriptBlockText|contains': ['0002DF01-0000-0000-C000-000000000046', 'F6D90F16-9C73-11D3-B32E-00C04F990BB4', 'F5078F35-C551-11D3-89B9-0000F81FE221', '88d96a0a-f192-11d4-a65f-0040963251e5', 'AFBA6B42-5692-48EA-8141-DC517DCF0EF1', 'AFB40FFD-B609-40A3-9828-F88BBE11E4E3', '88d96a0b-f192-11d4-a65f-0040963251e5', '2087c2f4-2cef-4953-a8ab-66779b670495', '000209FF-0000-0000-C000-000000000046', '00024500-0000-0000-C000-000000000046']}, 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Script Block Logging must be enable

Rule Source

SigmaHQ,3c7d1587-3b13-439f-9941-7d14313dbdfe

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://learn.microsoft.com/en-us/dotnet/api/system.type.gettypefromclsid?view=net-7.0
- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=57

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/25	medium	• Legitimate use of the library

Rule Details: Dnscat Execution

Dnscat exfiltration tool execution.

Rule ID

```
powershell_scriptblock_44
```

Query

```
{'selection': {'ScriptBlockText|contains': 'Start-Dnscat2'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,a6d67db4-6220-436d-8afc-f3842fe05d43

Author: Daniil Yugoslavskiy, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0010, T1048

References

N/A

Severity

95

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	critical	• Legitimate usage of PowerShell Dnscat2 — DNS Exfiltration tool (unlikely)

Rule Details: Suspicious Unblock-File

Remove the Zone.Identifier alternate data stream which identifies the file as downloaded from the internet.

Rule ID

`powershell_scriptblock_45`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Unblock-File ', '-
Path ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,5947497f-1aa4-41dd-9693-c9848d58727d

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1553

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1553.005/T1553.005.md#atomic-test-3---remove-the-zoneidentifier-alternate-data-stream
- https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.utility/unblock-file?view=powershell-7.2

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/01	ium	• Legitimate PowerShell scripts

Rule Details: AMSI Bypass Pattern Assembly GetType

Detects code fragments found in small and obfuscated AMSI bypass PowerShell scripts.

Rule ID

```
powershell_scriptblock_47
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['[Ref].Assembly.GetType', 'SetValue($
null,$true)', 'NonPublic,Static']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,e0d6c087-2d1c-47fd-8799-3904103c5a98

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1562.001

References

- https://www.mdsec.co.uk/2018/06/exploring-powershell-amsi-and-logging-evasion/

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/11/09	high	• Unknown

Rule Details: Remove Account From Domain Admin Group

Adversaries may interrupt availability of system and network resources by inhibiting access to accounts utilized by legitimate users. Accounts may be deleted, locked, or manipulated (ex: changed credentials) to remove access to accounts.

Rule ID

```
powershell_scriptblock_48
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Remove-ADGroupMember', '-Identity ', '-Members ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,48a45d45-8112-416b-8a67-46e03a4b2107

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0040, T1531

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1531/T1531.md#atomic-test-3---remove-account-from-domain-admin-group

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/26	medium	• Unknown

Rule Details: Suspicious Hyper-V Cmdlets

Adversaries may carry out malicious operations using a virtual instance to avoid detection.

Rule ID

```
powershell_scriptblock_49
```

Query

```
{'selection': {'ScriptBlockText|contains': ['New-VM', 'Set-VMFirmware', 'Start-VM']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,42d36aa1-3240-4db0-8257-e0118dcdd9cd

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1564.006

References

- https://docs.microsoft.com/en-us/virtualization/hyper-v-on-windows/quick-start/enable-hyper-v
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1564.006/T1564.006.md#atomic-test-3---create-and-start-hyper-v-virtual-machine

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/04/09	medium	• Legitimate PowerShell scripts

Rule Details: Zip A Folder With PowerShell For Staging In Temp - PowerShell Script

Use living off the land tools to zip a file and stage it in the Windows temporary folder for later exfiltration.

Rule ID

```
powershell_scriptblock_50
```

Query

```
{'selection_4104': {'ScriptBlockText|contains|all': ['Compress-Archive ', ' -Path ', ' -DestinationPath ', '$env:TEMP\\']}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,b7a3c9a3-09ea-4934-8864-6a32cacd98d9

Author: Nasreddine Bencherchali (Nextron Systems), frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0[illegible], T1074.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1074.001/T1074.001.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/07/20	medium	• Unknown

Rule Details: PowerShell ShellCode

Detects Base64 encoded Shellcode.

Rule ID

`powershell_scriptblock_52`

Query

```
{'selection': {'ScriptBlockText|contains': 'AAAAYInlM'}, 'selection2': {'ScriptBlockText|contains': ['OiCAAAAYInlM', 'OiJAAAAYInlM']}, 'condition': 'selection and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,16b37b70-6fcf-4814-a092-c36bd3aafcbd

Author: David Ledbetter (shellcode), Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1055

References

- https://twitter.com/cyb3rops/status/1063072865992523776

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/11/17	high	• Unknown

Rule Details: Suspicious Eventlog Clear

Detects usage of known powershell cmdlets such as "Clear-EventLog" to clear the windows event logs.

Rule ID

```
powershell_scriptblock_53
```

Query

```
{'selection': {'ScriptBlockText|contains': ['Clear-EventLog ', 'Remove-
EventLog ', 'Limit-EventLog ', 'Clear-WinEvent ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,0f017df3-8f5a-414f-ad6b-24aff1128278

Author: Nasreddine Bencherchali (Nextron Systems), Swachchhanda Shrawan Poudel (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1070.001

References

- https://twitter.com/oroneequalsone/status/1568432028361830402
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1070.001/T1070.001.md
- https://eqllib.readthedocs.io/en/latest/analytics/5b223758-07d6-4100-9e11-238cfdd0fe97.html

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/12	medium	• Rare need to clear logs before doing something. Sometimes used by installers or cleaner scripts. The script should be investigated to determine if it's legitimate

Rule Details: Powershell Local Email Collection

Adversaries may target user email on local systems to collect sensitive information. Files containing email data can be acquired from a users local system, such as Outlook storage or cache files.

Rule ID

`powershell_scriptblock_54`

Query

```
{'selection': {'ScriptBlockText|contains': ['Get-Inbox.ps1', 'Microsoft.Office.Interop.Outlook', 'Microsoft.Office.Interop.Outlook.olDefaultFolders', '-comobject outlook.application']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,2837e152-93c8-43d2-85ba-c3cd3c2ae614

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0009, T1114.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1114.001/T1114.001.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/21	medium	• Unknown

Rule Details: Suspicious FromBase64String Usage On Gzip Archive - Ps Script

Detects attempts of decoding a base64 Gzip archive in a PowerShell script. This technique is often used as a method to load malicious content into memory afterward.

Rule ID

`powershell_scriptblock_55`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['FromBase64String', 'MemoryStream', '
H4sI']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,df69cb1d-b891-4cd9-90c7-d617d90100ce

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=43

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/23	medium	• Legitimate administrative script

Rule Details: PowerShell ADRecon Execution

Detects execution of ADRecon.ps1 for AD reconnaissance which has been reported to be actively used by FIN7.

Rule ID

`powershell_scriptblock_56`

Query

```
{'selection': {'ScriptBlockT contains': ['Function Get-ADRExcelComOb', 'Get-
ADRGPO', 'Get-ADRDomainController', 'ADRecon-
Report.xlsx']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,bf72941a-cba0-41ea-b18c-9aca3925690d

Author: Bhabesh Raj

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/sense-of-security/ADRecon/blob/11881a24e9c8b207f31b56846809ce1fb189bcc9/ADRecon.ps1
- https://bi-zone.medium.com/from-pentest-to-apt-attack-cybercriminal-group-fin7-disguises-its-malware-as-an-ethical-hackers-c23c9a75e319

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/07/16	high	• Unknown

Rule Details: Access to Browser Login Data

Adversaries may acquire credentials from web browsers by reading files specific to the target browser. Web browsers commonly save credentials such as website usernames and passwords so that they do not need to be entered manually in the future. Web browsers typically store the credentials in an encrypted format within a credential store.

Rule ID

```
powershell_scriptblock_57
```

Query

{'selection_cmd': {'ScriptBlockText|contains|all': ['Copy-Item', '-Destination']}, 'selection_p': {'ScriptBlockText|contains': ['\\Opera Software\\Opera Stable\\Login Data', '\\Mozilla\\Firefox\\Profiles', '\\Microsoft\\Edge\\User Data\\Default', '\\Google\\Chrome\\User Data\\Default\\Login Data', '\\Google\\Chrome\\User Data\\Default\\Login Data For Account']}, 'condition': 'all of selection_*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,fc028194-969d-4122-8abe-0470d5b8f12f

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1555.003

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1555.003/T1555.003.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/30	medium	• Unknown

Rule Details: Abuse of Service Permissions to Hide Services Via Set-Service - PS

Detects usage of the "Set-Service" powershell cmdlet to configure a new SecurityDescriptor that allows a service to be hidden from other utilities such as "sc.exe", "Get-Service"...etc. (Works only in powershell 7.)

Rule ID

`powershell_scriptblock_58`

Query

{'selection': {'ScriptBlockText|contains|all': ['Set-Service ', 'DCLCWPDTSD'], 'ScriptBlockText|contains': ['-SecurityDescriptorSddl ', '-sd ']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,953945c5-22fe-4a92-9f8a-a9edc1e522da

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1574.011

References

- https://twitter.com/Alh4zr3d/status/1580925761996828672
- https://learn.microsoft.com/en-us/powershell/module/microsoft.powershell.management/set-service?view=powershell-7.2

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/17	high	• Rare intended use of hidden services • Rare FP could occure due to the non linearity of the ScriptBlockText log

Rule Details: Computer Discovery And Export Via Get-ADComputer Cmdlet - PowerShell

Detects usage of the Get-ADComputer cmdlet to collect computer information and output it to a file.

Rule ID

`powershell_scriptblock_59`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Get-ADComputer ', ' -Filter *'], 'ScriptBlockText|contains': [' | Select ', 'Out-File', 'Set-Content', 'Add-Content']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,db885529-903f-4c5d-9864-28fe199e6370

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1033

References

- http://blog.talosintelligence.com/2022/09/lazarus-three-rats.html
- https://www.microsoft.com/en-us/security/blog/2022/10/18/defenders-beware-a-case-for-post-ransomware-investigations/
- https://www.cisa.gov/uscert/sites/default/files/publications/aa22-320a_joint_csa_iranian_government-sponsored_apt_actors_compromise_federal%20network_deploy_crypto%20miner_credential_harvester.pdf

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/11/17	medium	• Legitimate admin scripts may use the same technique, it's better to exclude specific computers or users who execute these commands or scripts often

Rule Details: PowerShell PSAttack

Detects the use of PSAttack PowerShell hack tool

Rule ID

`powershell_scriptblock_60`

Query

```
{'selection': {'ScriptBlockText|contains': 'PS ATTACK!!!'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,b7ec41a4-042c-4f31-a5db-d0fcde9fa5c5

Author: Sean Metcalf (source), [illegible]an Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://adsecurity.org/?p=2921

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/03/05	high	• Unknown

Rule Details: PowerShell Invoke-NinjaCopy script

Detects PowerShell scripts that contain the default exported functions used on Invoke-NinjaCopy. Attackers can use Invoke-NinjaCopy to read SYSTEM files that are normally locked, such as the NTDS.dit file or registry hives.

Rule ID

`powershell_scriptblock_61`

Query

```
{'selection1': {'ScriptBlockText|contains': ['StealthReadFile', 'StealthReadFileAddr'
, 'StealthCloseFileDelegate', 'StealthOpenFile', 'StealthCloseFile', 'Invoke-
NinjaCopy']}, 'selection2': {'UserId': 'S-1-5-
18'}, 'condition': 'selection1 and (not selection2)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1003

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2023/01/23	medium	N/A

Rule Details: Delete Volume Shadow Copies via WMI with PowerShell - PS Script

Deletes Windows Volume Shadow Copies with PowerShell code and Get-WMIObject. This technique is used by numerous ransomware families such as Sodinokibi/REvil.

Rule ID

```
powershell_scriptblock_62
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Get-
WmiObject', 'Win32_Shadowcopy', '.Delete()']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,e17121b4-ef2a-4418-8a59-12fb1631fa9e

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0040, T1490

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1490/T1490.md#atomic-test-5---windows---delete-volume-shadow-copies-via-wmi-with-powershell

Severity

80

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/26	high	• Unknown

Rule Details: PowerShell ICMP Exfiltration

Detects Exfiltration Over Alternative Protocol - ICMP. Adversaries may steal data by exfiltrating it over an un-encrypted network protocol other than that of the existing command and control channel.

Rule ID

```
powershell_scriptblock_63
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['New-
Object', 'System.Net.NetworkInformation.Ping', '.Send(']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,4c4af3cd-2115-479c-8193-6b8bfce9001c

Author: Bartlomiej Czyz @bczyz1, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0010, T1048.003

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1048.003/T1048.003.md#atomic-test-2---exfiltration-over-alternative-protocol---icmp

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/10	medium	• Legitimate usage of System.Net.NetworkInformation.Ping class

Rule Details: AD Groups Or Users Enumeration Using PowerShell - ScriptBlock

Adversaries may attempt to find domain-level groups and permission settings. The knowledge of domain-level permission groups can help adversaries determine which groups exist and which

users belong to a particular group. Adversaries may use this information to determine which users have elevated permissions such as domain administrators.

Rule ID

```
powershell_scriptblock_64
```

Query

```
{'test_2': {'ScriptBlockText|contains': 'get-ADPrincipalGroupMembership'}, 'test_7': {'ScriptBlockText|contains|all': ['get-aduser', '-f ', '-pr ', 'DoesNotRequirePreAuth']}, 'condition': '1 of test_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,88f0884b-331d-403d-a3a1-b668cf035603

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1069.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1069.002/T1069.002.md

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/15	low	• Unknown

Rule Details: Tamper Windows Defender Remove-MpPreference - ScriptBlockLogging

Detects attempts to remove windows defender configuration using the 'MpPreference' cmdlet.

Rule ID

```
powershell_scriptblock_65
```

Query

{'selection_remove': {'ScriptBlockText|contains': 'Remove-MpPreference'}, 'selection_tamper': {'ScriptBlockText|contains': ['-ControlledFolderAccessProtectedFolders ', '-AttackSurfaceReductionRules_Ids ', '-AttackSurfaceReductionRules_Actions ', '-CheckForSignaturesBeforeRunningScan ']}, 'condition': 'all of selection_*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,ae2bdd58-0681-48ac-be7f-58ab4e593458

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1562.001

References

- https://techcommunity.microsoft.com/t5/core-infrastructure-and-security/windows-10-controlled-folder-access-event-search/ba-p/2326088

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/05	high	• Legitimate PowerShell scripts

Rule Details: Invoke-Obfuscation COMPRESS OBFUSCATION - PowerShell

Detects Obfuscated Powershell via COMPRESS OBFUSCATION.

Rule ID

powershell_scriptblock_66

Query

{'selection_4104': {'ScriptBlockText|contains|all': ['new-object', 'text.encoding]::ascii'], 'ScriptBlockText|contains': ['system.io.compression.deflatestream', 'system.io.streamreader'], 'ScriptBlockText|endswith': 'readtoend'}, 'condition': 'selection_4104'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,20e5497e-331c-4cd5-8d36-935f6e2a9a07

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/18	medium	• Unknown

Rule Details: Potential Data Exfiltration Via Audio File

Detects potential exfiltration attempt via audio file using PowerShell.

Rule ID

`powershell_scriptblock_67`

Query

```
{'selection_main': {'ScriptBlockText|contains|all': ['[System.Math]::', '[IO.FileMode]::', 'BinaryWriter']}, 'selection_header_wav': {'ScriptBlockText|contains|all': ['0x52', '0x49', '0x46', '0x57', '0x41', '0x56', '0x45', '0xAC']}, 'condition': 'selection_main and 1 of selection_header_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,e4f93c99-396f-47c8-bb0f-201b1fa69034

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/gtworek/PSBits/blob/e97cbbb173b31cbc4d37244d3412de0a114dacfb/NoDLP/bin2wav.ps1

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/16	medium	• Unknown

Rule Details: Create Volume Shadow Copy with Powershell

Adversaries may attempt to access or create a copy of the Active Directory domain database in order to steal credential information.

Rule ID

`powershell_scriptblock_68`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['win32_shadowcopy', ').Create(', 'ClientAccessible']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,afd12fed-b0ec-45c9-a13d-aa86625dac81

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1003.003

References

- https://attack.mitre.org/datasources/DS0005/

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/12	high	• Legitimate PowerShell scripts

Rule Details: Invoke-Obfuscation Obfuscated IEX Invocation - PowerShell

Detects all variations of obfuscated powershell IEX invocation code generated by Invoke-Obfuscation framework from the following code block \u2014.

Rule ID

`powershell_scriptblock_69`

Query

```
{'selection_iex': [{'ScriptBlockText|re': '\\$PSHome\\
[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$PSHome\\['}, {'ScriptBlockText|re': '\\$ShellId\\
[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$ShellId\\
['}, {'ScriptBlockText|re': '\\$env:Public\\
[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$env:Public\\
['}, {'ScriptBlockText|re': '\\$env:ComSpec\\[(\\s*\\d{1,3}\\s*,)
{2}'}, {'ScriptBlockText|re': '\\*mdr\\*\\W\\s*\\)\\.Name'}, {'ScriptBlockText|re': '
\\$VerbosePreference\\.ToString\\('}], 'condition': 'selection_iex'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,1b9dc62e-6e9e-42a3-8990-94d7a10007f7

Author: Daniel Bohannon (@Mandiant/@FireEye), oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/danielbohannon/Invoke-Obfuscation/blob/f20e7f843edd0a3a7716736e9eddfa423395dd26/Out-ObfuscatedStringCommand.ps1#L873-L888

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/11/08	high	• Unknown

Rule Details: Malicious ShellIntel PowerShell Commandlets

Detects Commandlet names from ShellIntel exploitation scripts.

Rule ID

`powershell_scriptblock_70`

Query

```
{'selection': {'ScriptBlockText|contains': ['Invoke-SMBAutoBrute', 'Invoke-GPOLinks', 'Invoke-Potato']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,402e1e1d-ad59-47b6-bf80-1ee44985b3a7

Author: Max Altgelt (Nextron Systems), Tobias Michalski (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/ShellIntel/scripts/

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/09	high	• Unknown

Rule Details: Change User Agents with WebRequest

Adversaries may communicate using application layer protocols associated with web traffic to avoid detection/network filtering by blending in with existing traffic. Commands to the remote

system, and often the results of those commands, will be embedded within the protocol traffic between the client and server.

Rule ID

`powershell_scriptblock_71`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Invoke-WebRequest', '-UserAgent ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,d4488827-73af-4f8d-9244-7b7662ef046e

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0011, T1071.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1071.001/T1071.001.md#t1071001---web-protocols

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/01/23	medium	• Unknown

Rule Details: Powershell Timestomp

Adversaries may modify file time attributes to hide new or changes to existing files. Timestomping is a technique that modifies the timestamps of a file (the modify, access, create, and change times), often to mimic files that are in the same folder.

Rule ID

`powershell_scriptblock_72`

Query

{'selection_ioc': {'ScriptBlockText|contains': ['.CreationTime =', '.LastWriteTime =', '.LastAccessTime =', '[IO.File]::SetCreationTime', '[IO.File]::SetLastAccessTime', '[IO.File]::SetLastWriteTime'], 'condition': 'selection_ioc'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,c6438007-e081-42ce-9483-b067fbef33c3

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1070.006

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1070.006/T1070.006.md
- https://www.offensive-security.com/metasploit-unleashed/timestomp/

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/03	medium	• Legitimate admin script

Rule Details: Powershell MsXml COM Object

Adversaries may abuse PowerShell commands and scripts for execution. PowerShell is a powerful interactive command-line interface and scripting environment included in the Windows operating system. (Citation: TechNet PowerShell) Adversaries can use PowerShell to perform a number of actions, including discovery of information and execution of code.

Rule ID

powershell_scriptblock_73

Query

{'selection': {'ScriptBlockText|contains|all': ['New-Object', '-ComObject', 'MsXml2.', 'XmlHttp']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,78aa1347-1517-4454-9982-b338d6df8343

Author: frack113, MatilJ

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1059.001/T1059.001.md#atomic-test-7---powershell-msxml-com-object---with-prompt
- https://docs.microsoft.com/en-us/previous-versions/windows/desktop/ms766431(v=vs.85)
- https://www.trendmicro.com/en_id/research/22/e/uncovering-a-kingminer-botnet-attack-using-trend-micro-managed-x.html

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/01/19	medium	• Legitimate administrative script

Rule Details: User Discovery And Export Via Get-ADUser Cmdlet - PowerShell

Detects usage of the Get-ADUser cmdlet to collect user information and output it to a file.

Rule ID

`powershell_scriptblock_74`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Get-ADUser ', ' -Filter *'], 'ScriptBlockText|contains': [' > ', ' | Select ', 'Out-File', 'Set-Content', 'Add-Content']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,c2993223-6da8-4b1a-88ee-668b8bf315e9

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1033

References

- http://blog.talosintelligence.com/2022/09/lazarus-three-rats.html
- https://www.microsoft.com/en-us/security/blog/2022/10/18/defenders-beware-a-case-for-post-ransomware-investigations/

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/11/17	medium	• Legitimate admin scripts may use the same technique, it's better to exclude specific computers or users who execute these commands or scripts often

Rule Details: Active Directory Group Enumeration With Get-AdGroup

Detects usage of the "Get-AdGroup" cmdlet to enumerate Groups within Active Directory.

Rule ID

```
powershell_scriptblock_75
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Get-AdGroup ', '-Filter']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,8c3a6607-b7dc-4f0d-a646-ef38c00b76ee

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1069.002

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1018/T1018.md

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/03/17	low	• Unknown

Rule Details: WMIC Unquoted Services Path Lookup - PowerShell

Detects known WMI recon method to look for unquoted service paths, often used by pentest inside of powershell scripts attackers enum scripts.

Rule ID

`powershell_scriptblock_76`

Query

```
{'selection': {'ScriptBlockText|contains': ['Get-WmiObject ', 'gwmi '], 'ScriptBlockText|contains|all': [' Win32_Service ', 'Name', 'DisplayName', 'PathName', 'StartMode']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,09658312-bc27-4a3b-91c5-e49ab9046d1b

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1047, T1059.001

References

- https://github.com/nccgroup/redsnarf/blob/35949b30106ae543dc6f2bc3f1be10c6d9a8d40e/redsnarf.py
- https://github.com/S3cur3Th1sSh1t/Creds/blob/eac23d67f7f90c7fc8e3130587d86158c22aa398/PowershellScripts/jaws-enum.ps1
- https://www.absolomb.com/2018-01-26-Windows-Privilege-Escalation-Guide/

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/20	medium	• Unknown

Rule Details: Get-ADUser Enumeration Using UserAccountControl Flags

Detects AS-REP roasting is an attack that is often-overlooked. It is not very common as you have to explicitly set accounts that do not require pre-authentication.

Rule ID

`powershell_scriptblock_77`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Get-ADUser', '-Filter', 'useraccountcontrol', '-band', '4194304']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,96c982fe-3d08-4df4-bed2-eb14e02f21c8

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1033

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1069.002/T1069.002.md#atomic-test-11---get-aduser-enumeration-using-useraccountcontrol-flags-as-rep-roasting

- https://shellgeek.com/useraccountcontrol-flags-to-manipulate-properties/

Severity



49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/17	medium	• Legitimate PowerShell scripts

Rule Details: Windows Defender Exclusions Added - PowerShell

Detects modifications to the Windows Defender configuration settings using PowerShell to add exclusions.

Rule ID

```
powershell_scriptblock_79
```

Query

```
{'selection_args_exc': {'ScriptBlockText|contains': [' -ExclusionPath ', ' -ExclusionExtension ', ' -ExclusionProcess ', ' -ExclusionIpAddress ']}, 'selection_args_pref': {'ScriptBlockText|contains': ['Add-MpPreference ', 'Set-MpPreference ']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,c1344fa2-323b-4d2e-9176-84b4d4821c88

Author: Tim Rauch, Elastic (idea)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1562

References

- https://www.elastic.co/guide/en/security/current/windows-defender-exclusions-added-via-powershell.html

Severity

49

Suppression Logic Based On

- computer_name

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/16	medium	• Unknown

Rule Details: Suspicious Get-ADReplAccount

The DSInternals PowerShell Module exposes several internal features of Active Directory and Microsoft Entra ID. These include FIDO2 and NGC key auditing, offline ntds.dit file manipulation, password auditing, DC recovery from IFM backups and password hash calculation.

Rule ID

`powershell_scriptblock_80`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Get-ADReplAccount', '-All ', '-Server ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,060c3ef1-fd0a-4091-bf46-e7d625f60b73

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1003.006

References

- https://www.powershellgallery.com/packages/DSInternals
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1003.006/T1003.006.md#atomic-test-2---run-dsinternals-get-adreplaccount

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/06	medium	• Legitimate PowerShell scripts

Rule Details: PowerShell Suspicious Script with Audio Capture Capabilities

Detects PowerShell scripts that record audio, a common feature in popular post-exploitation tooling.

Rule ID

`powershell_scriptblock_81`

Query

```
{'selection1': {'ScriptBlockText|contains': 'Get-
MicrophoneAudio'}, 'selection2': {'ScriptBlockText|contains': 'waveInGetNumDevs'}, 's
election3': {'ScriptBlockText|contains': 'mciSendStringA'}, 'selection4': {'UserId':
'S-1-5-
18'}, 'condition': '(selection1 or (selection2 and selection3)) and (not selection4)'
}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0009, T1123

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/10/19	medium	N/A

Rule Details: PowerShell Suspicious Script with Clipboard Retrieval Capabilities

Detects PowerShell scripts that can get the contents of the clipboard, which attackers can abuse to retrieve sensitive information like credentials, messages, etc.

Rule ID

`powershell_scriptblock_82`

Query

{'selection1': {'ScriptBlockText|contains': 'Get-Clipboard'}, 'selection2': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0009, T1115

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2023/01/12	medium	N/A

Rule Details: PowerShell Get-Process LSASS in ScriptBlock

Detects a Get-Process command on lsass process, which is in almost all cases a sign of malicious activity.

Rule ID

powershell_scriptblock_83

Query

{'selection': {'ScriptBlockText|contains': 'Get-Process lsass'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,84c174ab-d3ef-481f-9c86-a50d0b8e3edb

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0[illegible], T1003.001

References

- https://twitter.com/PythonResponder/status/1385064506049630211

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/04/23	high	• Legitimate certificate exports invoked by administrators or users (depends on processes in the environment - filter if unusable)

Rule Details: Password Policy Discovery With Get-AdDefaultDomainPasswordPolicy

Detetcts PowerShell activity in which Get-Addefaultdomainpasswordpolicy is used to get the default password policy for an Active Directory domain.

Rule ID

```
powershell_scriptblock_84
```

Query

```
{'selection': {'ScriptBlockText|contains': 'Get-AdDefaultDomainPasswordPolicy'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,bbb9495b-58fc-4016-b9df-9a3a1b67ca82

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1201

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1201/T1201.md#ato

mic-test-9---enumerate-active-directory-password-policy-with-get-addefaultdomainpasswordpolicy

- https://docs.microsoft.com/en-us/powershell/module/activedirectory/get-addefaultdomainpasswordpolicy

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/17	low	• Legitimate PowerShell scripts

Rule Details: Suspicious PowerShell Invocations - Generic

Detects suspicious PowerShell invocation command parameters.

Rule ID

```
powershell_scriptblock_85
```

Query

```
{'selection_encoded': {'ScriptBlockText|contains': [' -enc ', ' -EncodedCommand ', ' -ec ']}, 'selection_hidden': {'ScriptBlockText|contains': [' -w hidden ', ' -window hidden ', ' -windowstyle hidden ', ' -w 1 ']}, 'selection_noninteractive': {'ScriptBlockText|contains': [' -noni ', ' -noninteractive ']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,ed965133-513f-41d9-a441-e38076a0798f

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/03/12	high	• Very special / sneaky PowerShell scripts

Rule Details: NTFS Alternate Data Stream

Detects writing data into NTFS alternate data streams from powershell. Needs Script Block Logging.

Rule ID

`powershell_scriptblock_88`

Query

```
{'selection_content': {'ScriptBlockText|contains': ['set-content', 'add-content']}, 'selection_stream': {'ScriptBlockText|contains': '-stream'}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,8c521530-5169-495d-a199-0a3a881ad24e

Author: Sami Ruohonen

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1564.004

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1564.004/T1564.004.md

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/07/24	high	• Unknown

Rule Details: Suspicious Invoke-Item From Mount-DiskImage

Adversaries may abuse container files such as disk image (.iso, .vhd) file formats to deliver malicious payloads that may not be tagged with MOTW.

Rule ID

```
powershell_scriptblock_89
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Mount-DiskImage ', '-
ImagePath ', 'Get-Volume', '.DriveLetter', 'invoke-
item ', '):\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,902cedee-0398-4e3a-8183-6f3a89773a96

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1553

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1553.005/T1553.005.md#atomic-test-2---mount-an-iso-image-and-run-executable-from-the-iso
- https://docs.microsoft.com/en-us/powershell/module/storage/mount-diskimage?view=windowsserver2022-ps

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/01	medium	• Legitimate PowerShell scripts

Rule Details: PowerShell WMI Win32_Product Install MSI

Detects the execution of an MSI file using PowerShell and the WMI Win32_Product class.

Rule ID



```
powershell_scriptblock_90
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Invoke-CimMethod ', '-
ClassName ', 'Win32_Product ', '-MethodName ', '.msi']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,91109523-17f0-4248-a800-f81d9e7c081d

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1218.007

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1218.007/T1218.007.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/04/24	medium	• Unknown

Rule Details: Suspicious GetTypeFromCLSID ShellExecute

Detects suspicious Powershell code that execute COM Objects.

Rule ID

```
powershell_scriptblock_92
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['::GetTypeFromCLSID(', '.ShellExecute
(']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,8bc063d5-3a3a-4f01-a140-bc15e55e8437

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1546.015

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1546.015/T1546.015.md#atomic-test-2---powershell-execute-com-object

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/04/02	medium	• Legitimate PowerShell scripts

Rule Details: Silence.EDA Detection

Detects Silence EmpireDNSAgent as described in the Group-IP report.

Rule ID

`powershell_scriptblock_93`

Query

```
{'empire': {'ScriptBlockText|contains|all': ['System.Diagnostics.Process', 'Stop-Computer', 'Restart-Computer', 'Exception in execution', '$cmdargs', 'Close-Dnscat2Tunnel']}, 'dnscat': {'ScriptBlockText|contains|all': ['set type=$LookupType`n server', '$Command | nslookup 2>&1 | Out-String', 'New-RandomDNSField', '[Convert]::ToString($SYNOptions, 16)', '$Session.Dead = $True', '$Session["Driver"] -eq']}, 'condition': 'empire and dnscat'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,3ceb2083-a27f-449a-be33-14ec1b7cc973

Author: Alina Stepchenkova, Group-IB, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0011, T1071.004, T1572, TA0040, T1529

References

- https://www.group-ib.com/resources/threat-research/silence_2.0.going_global.pdf

Severity

95

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/11/01	critical	• Unknown

Rule Details: Potential Active Directory Enumeration Using AD Module - PsScript

Detects usage of the "Import-Module" cmdlet to load the "Microsoft.ActiveDirectory.Management.dl" DLL. Which is often used by attackers to perform AD enumeration.

Rule ID

`powershell_scriptblock_94`

Query


```
{'selection_generic': {'ScriptBlockText|contains|all': ['Import-
Module ', 'Microsoft.ActiveDirectory.Management.dll']}, 'selection_specific': {'Scrip
tBlockText|contains': 'ipmo Microsoft.ActiveDirectory.Management.dll'}, 'condition':
'1 of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enable

Rule Source

SigmaHQ,9e620995-f2d8-4630-8430-4afd89f77604

Author: frack113, Nasreddine Bencherchali

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/samratashok/ADModule
- https://twitter.com/cyb3rops/status/1617108657166061568?s=20
- https://www.ired.team/offensive-security-experiments/active-directory-kerberos-abuse/active-directory-enumeration-with-ad-module-without-rsat-or-admin-privileges

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/22	medium	• Legitimate use of the library for administrative activity

Rule Details: Automated Collection Bookmarks Using Get-ChildItem PowerShell

Adversaries may enumerate browser bookmarks to learn more about compromised hosts. Browser bookmarks may reveal personal information about users (ex: banking sites, interests, social media, etc.) as well as details about internal network resources such as servers, tools/dashboards, or other related infrastructure.

Rule ID

```
powershell_scriptblock_95
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Get-ChildItem', ' -Recurse ', ' -Path ', ' -Filter Bookmarks', ' -ErrorAction SilentlyContinue', ' -Force']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,e0565f5d-d420-4e02-8a68-ac00d864f9cf

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1217

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1217/T1217.md

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/13	low	• Unknown

Rule Details: SyncAppvPublishingServer Execution to Bypass Powershell Restriction

Detects SyncAppvPublishingServer process execution which usually utilized by adversaries to bypass PowerShell execution restrictions.

Rule ID

```
powershell_scriptblock_96
```

Query

```
{'selection': {'ScriptBlockText|contains': 'SyncAppvPublishingServer.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,dddfebae-c46f-439c-af7a-fdb6bde90218

Author: Ensar Şamil, @sblmsrsn, OSCD Community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1218

References

- https://lolbas-project.github.io/lolbas/Binaries/Syncappvpublishingserver/

Severity

49

Suppression Logic Based On

- computer_name

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/05	medium	• App-V clients

Rule Details: Disable Powershell Command History

Detects scripts or commands that disabled the Powershell command history by removing psreadline module.

Rule ID

```
powershell_scriptblock_97
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Remove-
Module', 'psreadline']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,602f5669-6927-4688-84db-0d4b7afb2150

Author: Ali Alwashali

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1070.003

References

- https://twitter.com/DissectMalware/status/1062879286749773824

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/21	high	• Legitimate script that disables the command history

Rule Details: Manipulation of User Computer or Group Security Principals Across AD

Adversaries may create a domain account to maintain access to victim systems. Domain accounts are those managed by Active Directory Domain Services where access and

permissions are configured across systems and services that are part of that domain.

Rule ID



`powershell_scriptblock_98`

Query

```
{'selection': {'ScriptBlockText|contains': 'System.DirectoryServices.AccountManagement'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,b29a93fb-087c-4b5b-a84d-ee3309e69d08

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1136.002

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1136.002/T1136.002.md#atomic-test-3---create-a-new-domain-account-using-powershell
- https://docs.microsoft.com/en-us/dotnet/api/system.directoryservices.accountmanagement?view=dotnet-plat-ext-6.0

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/28	medium	• Legitimate administrative script

Rule Details: PowerShell Suspicious Payload Encoded and Compressed

Identifies the use of .NET functionality for decompression and base64 decoding combined in PowerShell scripts, which malware and security tools heavily use to deobfuscate payloads and load them directly in memory to bypass defenses.

Rule ID

powershell_scriptblock_99

Query



{'selection1': {'ScriptBlockText|contains': 'System.IO.Compression.DeflateStream'}, 'selection2': {'ScriptBlockText|contains': 'System.IO.Compression.GzipStream'}, 'selection3': {'ScriptBlockText|contains': 'IO.Compression.DeflateStream'}, 'selection4': {'ScriptBlockText|contains': 'IO.Compression.GzipStream'}, 'selection5': {'ScriptBlockText|contains': 'FromBase64String'}, 'selection6': {'UserId': 'S-1-5-18'}, 'condition': '(selection1 or selection2 or selection3 or selection4) and selection5 and (not selection6)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027, T1140

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/10/19	medium	• Legitimate PowerShell Scripts which makes use of compression and encoding.

Rule Details: Powershell Trigger Profiles by Add_Content

Adversaries may gain persistence and elevate privileges by executing malicious content triggered by PowerShell profiles.

Rule ID

powershell_scriptblock_100

Query

{'selection': {'ScriptBlockText|contains|all': ['Add-Content', '$profile', '-Value'], 'ScriptBlockText|contains': ['Start-Process', '""']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,05b3e303-faf0-4f4a-9b30-46cc13e69152

Author: frack113, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1546.013

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1546.013/T1546.013.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/18	medium	• Unknown

Rule Details: Windows Screen Capture with CopyFromScreen

Adversaries may attempt to take screen captures of the desktop to gather information over the course of an operation. Screen capturing functionality may be included as a feature of a remote access tool used in post-compromise operations.

Rule ID

`powershell_scriptblock_101`

Query

```
{'selection': {'ScriptBlockText|contains': '.CopyFromScreen'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,d4a11f63-2390-411c-9adf-d791fd152830

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0009, T1113

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1113/T1113.md#atomic-test-6---windows-screen-capture-copyfromscreen

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/28	medium	• Unknown

Rule Details: Clear PowerShell History - PowerShell

Detects keywords that could indicate clearing PowerShell history.

Rule ID

```
powershell_scriptblock_102
```

Query

```
{'selection1a': {'ScriptBlockText|contains': ['del', 'Remove-
Item', 'rm']}, 'selection1b': {'ScriptBlockText|contains': '(Get-
PSReadlineOption).HistorySavePath'}, 'selection_2': {'ScriptBlockText|contains|all':
['Set-PSReadlineOption', '-
HistorySaveStyle', 'SaveNothing']}, 'selection_3': {'ScriptBlockText|contains|all': [
'Set-PSReadlineOption', '-
HistorySaveStyle', 'SaveNothing']}, 'condition': '1 of selection_* or all of selectio
n1*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,26b692dc-1722-49b2-b496-a8258aa6371d

Author: Ilyas Ochkov, Jonhnathan Ribeiro, Daniil Yugoslavskiy, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1070.003

References

- https://gist.github.com/hook-s3c/7363a856c3cdbadeb71085147f042c1a

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/01/25	medium	• Legitimate PowerShell scripts

Rule Details: PowerShell Share Enumeration Script

Detects scripts that contain PowerShell functions, structures, or Windows API functions related to windows share enumeration activities. Attackers, mainly ransomware groups, commonly identify and inspect network shares, looking for critical information for encryption and/or exfiltration.

Rule ID

```
powershell_scriptblock_103
```

Query

```
{'selection1': {'ScriptBlockText|contains': ['Invoke-ShareFinder', 'Invoke-
ShareFinderThreaded']}, 'selection2': {'ScriptBlockText|contains': 'shi1_netname'}, '
selection3': {'ScriptBlockText|contains': 'shi1_remark'}, 'selection4': {'ScriptBlock
Text|contains': 'NetShareEnum'}, 'selection5': {'ScriptBlockText|contains': 'NetApiBu
fferFree'}, 'selection6': {'UserId': 'S-1-5-
18'}, 'condition': '(selection1 or (selection2 and selection3) or (selection4 and sel
ection5)) and (not selection6)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, T1106, TA0007, T1135

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/08/17	medium	N/A

Rule Details: DirectorySearcher Powershell Exploitation

Enumerates Active Directory to determine computers that are joined to the domain.

Rule ID

```
powershell_scriptblock_104
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['New-
Object ', 'System.DirectoryServices.DirectorySearcher', '.PropertiesToLoad.Add', '.fi
ndall()', 'Properties.name']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,1f6399cf-2c80-4924-ace1-6fcff3393480

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1018

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1018/T1018.md#atomic-test-15---enumerate-domain-computers-within-active-directory-using-directorysearcher

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/12	medium	• Unknown

Rule Details: Invoke-Obfuscation STDIN+ Launcher - Powershell

Detects Obfuscated use of stdin to execute PowerShell.

Rule ID

`powershell_scriptblock_105`

Query

```
{'selection_4104': {'ScriptBlockText|re': '.*cmd.{0,5}(?:/c|/r).+powershell.+(?:\\$?
\\{?input\\}?|noexit).+"'}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,779c8c12-0eb1-11eb-adc1-0242ac120002

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/15	high	• Unknown

Rule Details: Powershell Install a DLL in System Directory

Uses PowerShell to install/copy a file into a system directory such as "System32" or "SysWOW64".

Rule ID

`powershell_scriptblock_106`

Query

{'selection_copy': {'ScriptBlockText|contains|all': ['Copy-Item ', '-Destination ']}, 'selection_paths': {'ScriptBlockText|contains': ['\\Windows\\System32', '\\Windows\\SysWOW64']}, 'condition': 'all of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,63bf8794-9917-45bc-88dd-e1b5abc0ecfd

Author: frack113, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1556.002

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1556.002/T1556.002.md#atomic-test-1---install-and-register-password-filter-dll

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/27	high	• Unknown

Rule Details: Deletion of Volume Shadow Copies via WMI with PowerShell - PS Script

Detects deletion of Windows Volume Shadow Copies with PowerShell code and Get-WMIObject. This technique is used by numerous ransomware families such as Sodinokibi/REvil.

Rule ID

powershell_scriptblock_107

Query

{'selection_get': {'ScriptBlockText|contains': ['Get-WmiObject', 'gwmi', 'Get-CimInstance', 'gcim']}, 'selection_shadowcopy': {'ScriptBlockText|contains': 'Win32_Shadowcopy'}, 'selection_delete': {'ScriptBlockText|contains': ['.Delete()', 'Remove-WmiObject', 'rwmi', 'Remove-CimInstance', 'rcim']}, 'condition': 'all of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

SigmaHQ,c1337eb8-921a-4b59-855b-4ba188ddcc42

Author: Tim Rauch, frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0040, T1490

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1490/T1490.md#atomic-test-5---windows---delete-volume-shadow-copies-via-wmi-with-powershell
- https://www.elastic.co/guide/en/security/current/volume-shadow-copy-deletion-via-powershell.html

Severity

80

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/20	high	• Unknown

Rule Details: Code Executed Via Office Add-in XLL File

Adversaries may abuse Microsoft Office add-ins to obtain persistence on a compromised system. Office add-ins can be used to add functionality to Office programs.

Rule ID

```
powershell_scriptblock_108
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['new-object ', '-ComObject ', '.application', '.RegisterXLL']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,36fbec91-fa1b-4d5d-8df1-8d8edcb632ad

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1137.006

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1137.006/T1137.006.md

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/28	high	• Unknown

Rule Details: PSAsyncShell - Asynchronous TCP Reverse Shell

Detects the use of PSAsyncShell an Asynchronous TCP Reverse Shell written in powershell.

Rule ID

```
powershell_scriptblock_109
```

Query

```
{'selection': {'ScriptBlockText|contains': 'PSAsyncShell'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,afd3df04-948d-46f6-ae44-25966c44b97f

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/JoelGMSec/PSAsyncShell

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/04	high	• Unlikely

Rule Details: Recon Information for Export with PowerShell

Once established within a system or network, an adversary may use automated techniques for collecting internal data.

Rule ID

```
powershell_scriptblock_110
```

Query

```
{'selection_action': {'ScriptBlockText|contains': ['Get-Service ', 'Get-
ChildItem ', 'Get-
Process ']}, 'selection_redirect': {'ScriptBlockText|contains': '> $env:TEMP\\'}, 'co
ndition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,a9723fcc-881c-424c-8709-fd61442ab3c3

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0009, T1119

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1119/T1119.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/30	medium	• Unknown

Rule Details: Enable Windows Remote Management

Adversaries may use Valid Accounts to interact with remote systems using Windows Remote Management (WinRM). The adversary may then perform actions as the logged-on user.

Rule ID

```
powershell_scriptblock_111
```

Query

```
{'selection_cmdlet': {'ScriptBlockText|contains': 'Enable-
PSRemoting '}, 'condition': 'selection_cmdlet'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,991a9744-f2f0-44f2-bd33-9092eba17dc3

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0008, T1021.006

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1021.006/T1021.006.md#atomic-test-1---enable-windows-remote-management
- https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.core/enable-psremoting?view=powershell-7.2

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/07	medium	• Legitimate script

Rule Details: Enumerate Credentials from Windows Credential Manager With PowerShell

Adversaries may search for common password storage locations to obtain user credentials. Passwords are stored in several places on a system, depending on the operating system or application holding the credentials.

Rule ID

`powershell_scriptblock_112`

Query


```
{'selection_cmd': {'ScriptBlockText|contains|all': ['vaultcmd', '/listcreds:']}, 'selection_option': {'ScriptBlockText|contains': ['Windows Credentials', 'Web Credentials']}, 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,603c6630-5225-49c1-8047-26c964553e0e

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1555

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1555/T1555.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/20	medium	• Unknown

Rule Details: Potential Persistence Via Security Descriptors - ScriptBlock

Detects usage of certain functions and keywords that are used to manipulate security descriptors in order to potentially set a backdoor. As seen used in the DAMP project.

Rule ID

`powershell_scriptblock_114`

Query

{'selection': {'ScriptBlockText|contains|all': ['win32_Trustee', 'win32_Ace', '.AccessMask', '.AceType', '.SetSecurityDescriptor'], 'ScriptBlockText|contains': ['\\Lsa\\JD', '\\Lsa\\Skew1', '\\Lsa\\Data', '\\Lsa\\GBG']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,2f77047c-e6e9-4c11-b088-a3de399524cd

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/HarmJ0y/DAMP

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/05	high	• Unknown

Rule Details: PowerShell Script with Encryption/Decryption Capabilities

Identifies the use of Cmdlets and methods related to encryption/decryption of files in PowerShell scripts, which malware and offensive security tools can abuse to encrypt data or decrypt payloads to bypass security solutions.

Rule ID

`powershell_scriptblock_115`

Query

{'selection1': {'ScriptBlockText|contains': 'Cryptography.AESManaged'}, 'selection2': {'ScriptBlockText|contains': 'Cryptography.RijndaelManaged'}, 'selection3': {'ScriptBlockText|contains': 'Cryptography.SHA1Managed'}, 'selection4': {'ScriptBlockText|contains': 'Cryptography.SHA256Managed'}, 'selection5': {'ScriptBlockText|contains': 'Cryptography.SHA384Managed'}, 'selection6': {'ScriptBlockText|contains': 'Cryptography.SHA512Managed'}, 'selection7': {'ScriptBlockText|contains': 'Cryptography.SymmetricAlgorithm'}, 'selection8': {'ScriptBlockText|contains': 'PasswordDeriveBytes'}, 'select

ion9': {'ScriptBlockText|contains': 'Rfc2898DeriveBytes'}, 'selection10': {'ScriptBlockText|contains': 'CipherMode'}, 'selection11': {'ScriptBlockText|contains': 'PaddingMode'}, 'selection12': {'ScriptBlockText|contains': '.CreateEncryptor'}, 'selection13': {'ScriptBlockText|contains': '.CreateDecryptor'}, 'selection14': {'UserId': 'S-1-5-18'}, 'condition': '(selection1 or selection2 or selection3 or selection4 or selection5 or selection6 or selection7 or selection8 or selection9) and selection10 and selection11 and (selection12 or selection13) and (not selection14)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1140, T1027

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2023/01/23	medium	• Legitimate PowerShell Scripts which makes use of encryption.

Rule Details: Suspicious SSL Connection

Adversaries may employ a known encryption algorithm to conceal command and control traffic rather than relying on any inherent protections provided by a communication protocol.

Rule ID

`powershell_scriptblock_116`

Query

{'selection': {'ScriptBlockText|contains|all': ['System.Net.Security.SslStream', 'Net.Security.RemoteCertificateValidationCallback', '.AuthenticateAsClient']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,195626f3-5f1b-4403-93b7-e6cfd4d6a078

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0011, T1573

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1573/T1573.md#atomic-test-1---openssl-c2
- https://medium.com/walmartglobaltech/openssl-server-reverse-shell-from-windows-client-aee2dbfa0926

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/23	low	• Legitimate administrative script

Rule Details: Potential Keylogger Activity

Detects PowerShell scripts that contains reference to keystroke capturing functions.

Rule ID

`powershell_scriptblock_117`

Query

```
{'selection': {'ScriptBlockText|contains': '[Windows.Input.Keyboard]::IsKeyDown([System.Windows.Input.Key]::'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,965e2db9-eddb-4cf6-a986-7a967df651e4

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1056.001

References

- https://twitter.com/ScumBots/status/1610626724257046529
- https://www.virustotal.com/gui/file/d4486b63512755316625230e0c9c81655093be93876e0d80732e7eeaf7d83476/content
- https://www.virustotal.com/gui/file/720a7ee9f2178c70501d7e3f4bcc28a4f456e200486dbd401b25af6da3b4da62/content
- https://learn.microsoft.com/en-us/dotnet/api/system.windows.input.keyboard.iskeydown?view=windowsdesktop-7.0

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/04	medium	• Unknown

Rule Details: Invoke-Obfuscation Via Use Clip - Powershell

Detects Obfuscated Powershell via use Clip.exe in Scripts.

Rule ID

`powershell_scriptblock_118`

Query

```
{'selection_4104': {'ScriptBlockText|re': '(?i).*?echo.*clip.*&&.*(Clipboard|i`?n`?v`?o`?k`?e`?).*'}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,db92dd33-a3ad-49cf-8c2c-608c3e30ace0

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/09	high	• Unknown

Rule Details: Execution via CL_Mutexverifiers.ps1

Detects Execution via runAfterCancelProcess in CL_Mutexverifiers.ps1 module.

Rule ID

```
powershell_scriptblock_119
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['CL_Mutexverifiers.ps1', 'runAfterCancelProcess']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,39776c99-1c7b-4ba0-b5aa-641525eee1a4

Author: oscd.community, Natalia Shornikova

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1216

References

- https://lolbas-project.github.io/lolbas/Scripts/CL_mutexverifiers/
- https://twitter.com/pabraeken/status/995111125447577600

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/14	high	• Unknown

Rule Details: Bloodhound Hack Tool Usage via PowerShell

Detects the usage of PowerShell to execute Bloodhound hacktool on endpoint.

Rule ID

`powershell_scriptblock_120`

Query

```
{'selection': {'ScriptBlockText|contains': ['Invoke-BloodHound', 'Invoke-AzureHound', 'Get-BloodHoundData']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1482

References

- https://github.com/BloodHoundAD/BloodHound

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2023/03/30	high	• Unknown

Rule Details: Suspicious X509Enrollment - Ps Script

Detect use of X509Enrollment.

Rule ID

`powershell_scriptblock_121`

Query

```
{'selection': {'ScriptBlockT contains': ['X509Enrollment.CBinaryConverter', '884e2
002-217d-11da-b2a4-000e7bbb2b09']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,504d63cb-0dba-4d02-8531-e72981aace2c

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=42
- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=41
- https://learn.microsoft.com/en-us/dotnet/api/microsoft.hpc.scheduler.store.cx509enrollmentwebclassfactoryclass?view=hpc-sdk-5.1.6115

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/23	medium	• Legitimate administrative script

Rule Details: Add New Windows Capability - ScriptBlock

Detects usage of the "Add-WindowsCapability" cmdlet to add new windows capabilities. Notable capabilities could be "OpenSSH" and others.

Rule ID

```
powershell_scriptblock_122
```

Query

```
{'selection_cmdlet': {'ScriptBlockText|contains': 'Add-
WindowsCapability '}, 'selection_capa': {'ScriptBlockText|contains': 'OpenSSH.'}, 'co
ndition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,155c7fd5-47b4-49b2-bbeb-eb4fab335429

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://learn.microsoft.com/en-us/windows-server/administration/openssh/openssh_install_firstuse?tabs=powershell
- https://www.virustotal.com/gui/file/af1c82237b6e5a3a7cdbad82cc498d298c67845d92971bada450023d1335e267/content

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/22	medium	• Legitimate usage of the capabilities by administartors or users. Filter accordingly

Rule Details: Invoke-Obfuscation Via Use Rundll32 - PowerShell

Detects Obfuscated Powershell via use Rundll32 in Scripts.

Rule ID

```
powershell_scriptblock_123
```

Query

```
{'selection_4104': {'ScriptBlockText|contains|all': ['&&', 'rundll32', 'shell32.dll',
 'shellexec_rundll'], 'ScriptBlockText|contains': ['value', 'invoke', 'comspec', 'iex
']}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,a5a30a6e-75ca-4233-8b8c-42e0f2037d3b

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/10/08	high	• Unknown

Rule Details: Anti-VM check with WMI Query

WMI Queries allow to inspect Windows properties like the BIOS features. This technique is used by malware to identify virtual and sandboxed host machines, in order to evade security analysis.

Rule ID

```
powershell_scriptblock_124
```

Query

```
{'selection1': {'ScriptBlockText|contains': '-
query'}, 'selection2': {'ScriptBlockText|re': '.*(Get-WMIObject|gwmi) .*?-
query .*? win32_(BIOS|SystemBIOS).*?
(bochs|qemu|VBOX|VirtualBox|VM).*'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity



49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Suspicious Connection to Remote Account

Adversaries with no prior knowledge of legitimate credentials within the system or environment may guess passwords to attempt access to accounts. Without knowledge of the password for an account, an adversary may opt to systematically guess the password using a repetitive or iterative mechanism.

Rule ID

`powershell_scriptblock_125`

Query


```
{'selection': {'ScriptBlockText|contains': ['System.DirectoryServices.Protocols.LdapDirectoryIdentifier', 'System.Net.NetworkCredential', 'System.DirectoryServices.Protocols.LdapConnection']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,1883444f-084b-419b-ac62-e0d0c5b3693f

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1110.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1110.001/T1110.001.md#atomic-test-2---brute-force-credentials-of-single-active-directory-domain-user-via-ldap-against-domain-controller-ntlm-or-kerberos

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/27	low	• Unknown

Rule Details: Suspicious Export-PfxCertificate

Detects Commandlet that is used to export certificates from the local certificate store and sometimes used by threat actors to steal private keys from compromised machines.

Rule ID

```
powershell_scriptblock_126
```

Query

```
{'selection': {'ScriptBlockText|contains': ['Export-PfxCertificate', 'export-certificate']}, 'filter_moduleexport': {'ScriptBlockText|contains': 'CmdletsToExport = @('}, 'condition': 'selection and not 1 of filter*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,aa7a3fce-bef5-4311-9cc1-5f04bb8c308c

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1552.004

References

- https://us-cert.cisa.gov/ncas/analysis-reports/ar21-112a
- https://docs.microsoft.com/en-us/powershell/module/pki/export-pfxcertificate
- https://dev.to/iamthecarisma/managing-windows-pfx-certificates-through-powershell-3pj
- https://learn.microsoft.com/en-us/powershell/module/pki/export-certificate?view=windowsserver2022-ps

Severity

74

Suppression Logic Based On

- computer_name

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/04/23	high	• Legitimate certificate exports invoked by administrators or users (depends on processes in the environment - filter if unusable)

Rule Details: Powershell Sensitive File Discovery

Detect adversaries enumerate sensitive files.

Rule ID

```
powershell_scriptblock_127
```

Query

```
{'selection_action': {'ScriptBlockText|contains': ['ls', 'get-childitem', 'gci']}, 'selection_recurse': {'ScriptBlockText|contains': '-recurse'}, 'selection_file': {'ScriptBlockText|contains': ['.pass', '.kdbx', '.kdb']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,7d416556-6502-45b2-9bad-9d2f05f38997

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1083

References

- https://twitter.com/malmoeb/status/1570814999370801158

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/16	medium	• Unknown

Rule Details: Invoke-Obfuscation VAR++ LAUNCHER OBFUSCATION - PowerShell

Detects Obfuscated Powershell via VAR++ LAUNCHER.

Rule ID



```
powershell_scriptblock_128
```

Query

```
{'selection_4104': {'ScriptBlockText|re': '(?i).*&&set.*(\\{\\d\\}){2,}\\\\"\\s+?-f.*&&.*cmd.*/c'}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,e54f5149-6ba3-49cf-b153-070d24679126

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/13	high	• Unknown

Rule Details: Testing Usage of Uncommonly Used Port

Adversaries may communicate using a protocol and port paring that are typically not associated. For example, HTTPS over port 8088(Citation: Symantec Elfin Mar 2019) or port 587(Citation: Fortinet Agent Tesla April 2018) as opposed to the traditional port 443.

Rule ID

```
powershell_scriptblock_129
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Test-NetConnection', '-ComputerName ', '-
```

port ']}, 'filter': {'ScriptBlockText|contains': [' 443 ', ' 80 ']}, 'condition': 'selection and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,adf876b3-f1f8-4aa9-a4e4-a64106feec06

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0011, T1571

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1571/T1571.md#atomic-test-1---testing-usage-of-uncommonly-used-port-with-powershell
- https://docs.microsoft.com/en-us/powershell/module/nettcpip/test-netconnection?view=windowsserver2022-ps

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/23	medium	• Legitimate administrative script

Rule Details: Troubleshooting Pack Cmdlet Execution

Detects execution of "TroubleshootingPack" cmdlets to leverage CVE-2022-30190 or action similar to "msdt" lolbin (as described in LOLBAS).

Rule ID

powershell_scriptblock_130

Query

{'selection': {'ScriptBlockText|contains|all': ['Invoke-TroubleshootingPack', 'C:\\Windows\\Diagnostics\\System\\PCW', '-AnswerFile', '-Unattended']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,03409c93-a7c7-49ba-9a4c-a00badf2a153

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1202

References

- https://twitter.com/nas_bench/status/1537919885031772161
- https://lolbas-project.github.io/lolbas/Binaries/Msdt/

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/21	medium	• Legitimate usage of "TroubleshootingPack" cmdlet for troubleshooting purposes

Rule Details: Invoke-Obfuscation Via Stdin - Powershell

Detects Obfuscated Powershell via Stdin in Scripts.

Rule ID

```
powershell_scriptblock_131
```

Query

```
{'selection_4104': {'ScriptBlockText|re': '(?i).*(set).*&&\\s?set.*
(environment|invoke|\\$\\{?input).*&&.*"'}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,86b896ba-ffa1-4fea-83e3-ee28a4c915c7

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0[illegible], T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/12	high	• Unknown

Rule Details: Suspicious Mount-DiskImage

Adversaries may abuse container files such as disk image (.iso, .vhd) file formats to deliver malicious payloads that may not be tagged with MOTW.

Rule ID

```
powershell_scriptblock_132
```

Query

```
{'selection': {'ScriptBlockText|contains|all': ['Mount-DiskImage ', '-
ImagePath ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,29e1c216-6408-489d-8a06-ee9d151ef819

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1553

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1553.005/T1553.005.md#atomic-test-1---mount-iso-image

- https://docs.microsoft.com/en-us/powershell/module/storage/mount-diskimage?view=windowsserver2022-ps

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/01	low	• Legitimate PowerShell scripts

Rule Details: Suspicious PowerShell Mailbox Export to Share - PS

Detects usage of the powerShell New-MailboxExportRequest Cmdlet to exports a mailbox to a remote or local share, as used in ProxyShell exploitations.

Rule ID

`powershell_scriptblock_133`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['New-MailboxExportRequest', ' -Mailbox ', ' -FilePath \\\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,4a241dea-235b-4a7e-8d76-50d817b146c4

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://youtu.be/5mqid-7zp8k?t=2481
- https://blog.orange.tw/2021/08/proxylogon-a-new-attack-surface-on-ms-exchange-part-1.html
- https://peterjson.medium.com/reproducing-the-proxyshell-pwn2own-exploit-49743a4ea9a1
- https://m365internals.com/2022/10/07/hunting-in-on-premises-exchange-server-logs/

Severity

95

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/26	critical	• Unknown

Rule Details: Data Compressed - PowerShell

An adversary may compress data (e.g., sensitive documents) that is collected prior to exfiltration in order to make it portable and minimize the amount of data sent over the network.

Rule ID

`powershell_scriptblock_134`

Query

```
{'selection': {'ScriptBlockText|contains|all': ['-Recurse', '|', 'Compress-Archive']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,6dc5d284-69ea-42cf-9311-fb1c3932a69a

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0009, T1560

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1560/T1560.md

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/21	low	• Highly likely if archive operations are done via PowerShell.

Rule Details: PowerShell Create Local User

Detects creation of a local user via PowerShell.

Rule ID

```
powershell_scriptblock_135
```

Query

```
{'selection': {'ScriptBlockText|contains': 'New-
LocalUser'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,243de76f-4725-4f2e-8225-a8a69b15ad61

Author: @ROxPinTeddy

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1136.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1136.001/T1136.001.md

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/04/11	medium	• Legitimate user creation

Rule Details: WMI lateral movement using MSI package

Windows Management Instrumentation (WMI) is able to install MSI packages in remote computers. An attacker can use it to performa lateral movement and execute malicious code.

Rule ID

powershell_scriptblock_136

Query



{'selection1': {'ScriptBlockText|contains': 'win32_product'}, 'selection2': {'ScriptBlockText|contains': 'install'}, 'selection3': {'ScriptBlockText|contains': '-ComputerName'}, 'selection4': {'ScriptBlockText|contains': '-Credential'}, 'condition': 'selection1 and selection2 and selection3 and selection4'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Replace Desktop Wallpaper by Powershell

An adversary may deface systems internal to an organization in an attempt to intimidate or mislead users. This may take the form of modifications to internal websites, or directly to user systems with the replacement of the desktop wallpaper.

Rule ID

powershell_scriptblock_137

Query

{'selection_1': {'ScriptBlockText|contains|all': ['Get-ItemProperty', 'Registry::', 'HKEY_CURRENT_USER\\Control Panel\\Desktop\\', 'WallPaper']}, 'selection_2': {'ScriptBlockText|contains': 'SystemParametersInfo(20,0,*,3)'}, 'condition': '1 of selection_*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,c5ac6a1e-9407-45f5-a0ce-ca9a0806a287

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0040, T1491.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1491.001/T1491.001.md

Severity

24

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/26	low	• Unknown

Rule Details: PowerShell MiniDump Script

This rule detects PowerShell scripts capable of dumping process memory using WindowsErrorReporting or Dbghelp.dll MiniDumpWriteDump. Attackers can use this tooling to dump LSASS and get access to credentials.

Rule ID

```
powershell_scriptblock_138
```

Query

```
{'selection1': {'ScriptBlockText|contains': ['MiniDumpWriteDump', 'MiniDumpWithFullMemory', 'pmuDetirWpmuDiniM']}, 'selection2': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1003

References
N/A

Severity
74

Suppression Logic Based On
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/10/05	high	• PowerShell scripts that use this capability for troubleshooting.

Rule Details: PowerShell PSReflect Script
Detects the use of PSReflect in PowerShell scripts. Attackers leverage PSReflect as a library that enables PowerShell to access win32 API functions.

Rule ID
```
powershell_scriptblock_139
```

Query
```
{'selection1': {'ScriptBlockText|contains': ['New-InMemoryModule', 'Add-Win32Type', 'psenum', 'DefineDynamicAssembly', 'DefineDynamicModule', 'Reflection.TypeAttributes', 'Reflection.Emit.OpCodes', 'Reflection.Emit.CustomAttributeBuilder', 'Runtime.InteropServices.DllImportAttribute']}, 'selection2': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}
```

Log Source
Stellar Cyber Windows Server Sensor configured for:
- Monitoring PowerShell scripts

Rule Source
Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures
TA0002, T1059.001, T1106

References
N/A

Severity
49

Suppression Logic Based On
- computer_name

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/10/15	medium	• Legitimate PowerShell scripts that make use of PSReflect to access the win32 API

Rule Details: Winlogon Helper DLL

Winlogon.exe is a Windows component responsible for actions at logon/logoff as well as the secure attention sequence (SAS) triggered by Ctrl-Alt-Delete. Registry entries in HKLM\Software[Wow6432Node]Microsoft\Windows NT\CurrentVersion\Winlogon\ and HKCU\Software\Microsoft\Windows NT\CurrentVersion\Winlogon\ are used to manage additional helper programs and functionalities that support Winlogon. Malicious modifications to these Registry keys may cause Winlogon to load and execute malicious DLLs and/or executables.

Rule ID

```
powershell_scriptblock_140
```

Query

```
{'selection': {'ScriptBlockText|contains': 'CurrentVersion\\Winlogon'}, 'selection2':
 {'ScriptBlockText|contains': ['Set-ItemProperty', 'New-
Item']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,851c506b-6b7c-4ce2-8802-c703009d03c0

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1547.004

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1547.004/T1547.004.md

Severity

49

Suppression Logic Based On

- computer_name

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/10/21	medium	• Unknown

Rule Details: Code Executed Via Office Add-in

Adversaries may abuse Microsoft Office add-ins to obtain persistence on a compromised system. Office add-ins can be used to add functionality to Office programs.

Rule ID

```
powershell_scriptblock_147
```

Query

```
{'selection_xll': {'ScriptBlockText|contains|all': ['Copy', '\\Microsoft\\AddIns\\', '.xll']}, 'selection_wll': {'ScriptBlockText|contains|all': ['Copy', '\\Microsoft\\Word\\Startup\\', '.wll']}, 'selection_xlam': {'ScriptBlockText|contains|all': ['Copy', '\\Microsoft\\Excel\\XLSTART\\', '.xlam']}, 'selection_ppam': {'ScriptBlockText|contains|all': ['Copy', '\\Microsoft\\Addins\\', '.ppam']}, 'condition': '1 of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1137.006

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1137.006/T1137.006.md

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2024/01/26	high	• Unknown

Rule Details: Potential Unconstrained Delegation Discovery Via Get-ADComputer - ScriptBlock

Detects the use of the "Get-ADComputer" cmdlet in order to identify systems which are configured for unconstrained delegation.

Rule ID

```
powershell_scriptblock_148
```

Query

```
{'selection1': {'ScriptBlockText|contains': 'Get-
ADComputer'}, 'selection2': {'ScriptBlockText|contains': ['-
Properties*TrustedForDelegation', '-Properties*TrustedToAuthForDelegation', '-
Properties*msDS-AllowedToDelegateTo', '-
Properties*PrincipalsAllowedToDelegateToAccount', '-LDAPFilter*
(userAccountControl:1.2.840.113556.1.4.803:=524288)']}, 'condition': 'selection1 and
selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enable

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0043, T1589.002, TA0007, T1018, TA0006, T1558

References

- https://pentestlab.blog/2022/03/21/unconstrained-delegation/
- https://learn.microsoft.com/en-us/powershell/module/activedirectory/get-adcomputer?view=windowsserver2022-ps

Severity

50

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025-03-05	medium	• Legitimate use of the library for administrative activity

Rule Details: PowerShell Kerberos Ticket Dump

Detects PowerShell scripts that have the capability of dumping Kerberos tickets from LSA, which potentially indicates an attacker's attempt to acquire credentials for lateral movement.

Rule ID

`powershell_scriptblock_149`

Query


```
{'selection1': {'ScriptBlockText|contains': 'LsaCallAuthenticationPackage'}, 'selection2': {'ScriptBlockText|contains': ['KerbRetrieveEncodedTicketMessage', 'KerbQueryTicketCacheMessage', 'KerbQueryTicketCacheExMessage', 'KerbQueryTicketCacheEx2Message', 'KerbRetrieveTicketMessage', 'KerbDecryptDataMessage']}, 'condition': 'selection1 and selection2'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1003, T1558

References

N/A

Severity

75

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2023/07/26	high	N/A

Rule Details: DSInternals Suspicious PowerShell Cmdlets - ScriptBlock

Detects execution and usage of the DSInternals PowerShell module. Which can be used to perform what might be considered as suspicious activity such as dumping DPAPI backup keys or manipulating NTDS.DIT files. The DSInternals PowerShell Module exposes several internal features of Active Directory and Azure Active Directory. These include FIDO2 and NGC key auditing, offline ntds.dit file manipulation, password auditing, DC recovery from IFM backups and password hash calculation.

Rule ID

powershell_scriptblock_150

Query



{'selection': {'ScriptBlockText|contains': ['Add-ADDBSidHistory', 'Add-ADNgcKey', 'Add-ADReplNgcKey', 'ConvertFrom-ADManagedPasswordBlob', 'ConvertFrom-GPPrefPassword', 'ConvertFrom-ManagedPasswordBlob', 'ConvertFrom-UnattendXmlPassword', 'ConvertFrom-UnicodePassword', 'ConvertTo-AADHash', 'ConvertTo-GPPrefPassword', 'ConvertTo-KerberosKey', 'ConvertTo-LMHash', 'ConvertTo-MsoPasswordHash', 'ConvertTo-NTHash', 'ConvertTo-OrgIdHash', 'ConvertTo-UnicodePassword', 'Disable-ADDBAccount', 'Enable-ADDBAccount', 'Get-ADDBAccount', 'Get-ADDBBackupKey', 'Get-ADDBDomainController', 'Get-ADDBGroupManagedServiceAccount', 'Get-ADDBKdsRootKey', 'Get-ADDBSchemaAttribute', 'Get-ADDBServiceAccount', 'Get-ADDefaultPasswordPolicy', 'Get-ADKeyCredential', 'Get-ADPasswordPolicy', 'Get-ADReplAccount', 'Get-ADReplBackupKey', 'Get-ADReplicationAccount', 'Get-ADSIAccount', 'Get-AzureADUserEx', 'Get-BootKey', 'Get-KeyCredential', 'Get-LsaBackupKey', 'Get-LsaPolicy', 'Get-SamPasswordPolicy', 'Get-SysKey', 'Get-SystemKey', 'New-ADDBRestoreFromMediaScript', 'New-ADKeyCredential', 'New-ADNgcKey', 'New-NTHashSet', 'Remove-ADDBObject', 'Save-DPAPIBlob', 'Set-ADAccountPasswordHash', 'Set-ADDBAccountPassword', 'Set-ADDBBootKey', 'Set-ADDBDomainController', 'Set-ADDBPrimaryGroup', 'Set-ADDBSysKey', 'Set-AzureADUserEx', 'Set-LsaPolicy', 'Set-SamAccountPasswordHash', 'Set-WinUserPasswordHash', 'Test-ADDBPasswordQuality', 'Test-ADPasswordQuality', 'Test-ADReplPasswordQuality', 'Test-PasswordQuality', 'Unlock-ADDBAccount', 'Write-ADNgcKey', 'Write-ADReplNgcKey']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,846c7a87-8e14-4569-9d49-ecfd4276a01c

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://github.com/MichaelGrafnetter/DSInternals/blob/39ee8a69bbdc1cfd12c9afdd7513b4788c4895d4/Src/DSInternals.PowerShell/DSInternals.psd1

Severity

75

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2024-06-26	high	• Legitimate usage of DSInternals for administration or audit purpose.

Rule Details: Windows PowerSploit GPP Discovery

The following analytic detects the execution of the Get-GPPPassword PowerShell cmdlet, which is used to search for unsecured credentials in Group Policy Preferences (GPP). This detection leverages PowerShell Script Block Logging to identify specific script block text associated with this cmdlet. Monitoring this activity is crucial as it can indicate an attempt to retrieve and decrypt stored credentials from SYSVOL, potentially leading to unauthorized access. If confirmed malicious, this activity could allow an attacker to escalate privileges or move laterally within the network by exploiting exposed credentials.

Rule ID

`powershell_scriptblock_151`

Query

```
{'selection': {'ScriptBlockText|contains': ['Get-GPPPassword', 'Get-CachedGPPPassword']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1552.006

References

- https://pentestlab.blog/2017/03/20/group-policy-preferences/
- https://adsecurity.org/?p=2288
- https://www.hackingarticles.in/credential-dumping-group-policy-preferences-gpp/
- https://adsecurity.org/?p=2288
- https://support.microsoft.com/en-us/topic/ms14-025-vulnerability-in-group-policy-preferences-could-allow-elevation-of-privilege-may-13-2014-60734e15-af79-26ca-ea53-8cd617073c30

Severity

50

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2025-02-10	medium	• Unknown

Rule Details: Windows PowerView Unconstrained Delegation Discovery

The following analytic detects the use of PowerView commandlets to discover Windows endpoints with Kerberos Unconstrained Delegation. It leverages PowerShell Script Block Logging (EventCode=4104) to identify specific commands like `Get-DomainComputer` or `Get-NetComputer` with the `-Unconstrained` parameter. This activity is significant as it indicates potential reconnaissance efforts by adversaries or Red Teams to map out privileged delegation settings in Active Directory. If confirmed malicious, this could allow attackers to identify high-value targets for further exploitation, potentially leading to privilege escalation or lateral movement within the network.

Rule ID

`powershell_scriptblock_152`

Query

```
{'selection1': {'ScriptBlockText|contains': ['Get-DomainComputer', 'Get-NetComputer']}, 'selection2': {'ScriptBlockText|contains': '-Unconstrained'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1018

References

- https://adsecurity.org/?p=1667
- https://docs.microsoft.com/en-us/defender-for-identity/cas-isp-unconstrained-kerberos
- https://www.ired.team/offensive-security-experiments/active-directory-kerberos-abuse/domain-compromise-via-unrestricted-kerberos-delegation
- https://www.cyberark.com/resources/threat-research-blog/weakness-within-kerberos-delegation

Severity

50

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2024-11-13	medium	• Administrators or power users may leverage PowerView for system management or troubleshooting.

Rule Details: Get-ForestTrust with PowerShell Script Block

The following analytic detects the execution of the Get-ForestTrust command from PowerSploit using PowerShell Script Block Logging (EventCode=4104). This method captures the full command sent to PowerShell, providing detailed visibility into potentially suspicious activities. Monitoring this behavior is crucial as it can indicate an attempt to gather domain trust information, which is often a precursor to lateral movement or privilege escalation. If confirmed malicious, this activity could allow an attacker to map trust relationships within the domain, facilitating further exploitation and access to sensitive resources.

Rule ID

`powershell_scriptblock_153`

Query

```
{'selection': {'ScriptBlockText|contains': ['get-
foresttrust']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1482

References

- https://powersploit.readthedocs.io/en/latest/Recon/Get-ForestTrust/
- https://www.splunk.com/en_us/blog/security/hunting-for-malicious-powershell-using-script-block-logging.html

Severity

50

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2024-11-13	medium	• False positives may be present. Tune as needed.

Rule Details: PowerShell Kerberos Ticket Request

Detects PowerShell scripts that have the capability of requesting kerberos tickets, which is a common step in Kerberoasting toolkits to crack service accounts.

Rule ID

```
powershell_scriptblock_154
```

Query

```
{'selection1': {'ScriptBlockText|contains': 'KerberosRequestorSecurityToken'}, 'selection2': {'UserId': ['S-1-5-18', 'S-1-5-20']}, 'selection3': {'ScriptBlockText|contains': 'sentinelbreakpoints'}, 'selection4': {'ScriptBlockText|contains': ['Set-PSBreakpoint', 'Set-HookFunctionTabs']}, 'selection5': {'ScriptBlockText|contains|all': ['function global', '\\windows\\sentinel\\4']}, 'condition': 'selection1 and (not selection2) and (not ((selection3 and selection4) or selection5))'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1003, T1558

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/01/24	medium	N/A

Process Creation Commandline Rule IDs

Rule Details: SystemNightmare Exploitation Script Execution

Detects the exploitation of PrinterNightmare to get a shell as LOCAL_SYSTEM.

Rule ID

`process_creation_commandline_1`

Query

```
{'selection': {'CommandLine|contains': ['printnightmare.gentilkiwi.com', ' /user:gentilguest ', 'Kiwi Legit Printer']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c01f7bd6-0c1d-47aa-9c61-187b91273a16

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0004, T1068

References

- https://github.com/GossiTheDog/SystemNightmare

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/11	critical	• Unknown

Rule Details: Suspicious Reg Add Open Command

Threat actors performed dumping of SAM, SECURITY and SYSTEM registry hives using DelegateExecute key.

Rule ID

`process_creation_commandline_2`

Query

{'selection_1': {'CommandLine|contains|all': ['reg', 'add', 'hkcu\\software\\classes\\ms-settings\\shell\\open\\command', '/ve ', '/d']}, 'selection_2': {'CommandLine|contains|all': ['reg', 'add', 'hkcu\\software\\classes\\ms-settings\\shell\\open\\command', '/v', 'DelegateExecute']}, 'selection_3': {'CommandLine|contains|all': ['reg', 'delete', 'hkcu\\software\\classes\\ms-settings']}, 'condition': '1 of selection_*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,dd3ee8cc-f751-41c9-ba53-5a32ed47e563

Author: frack113, Swachchhanda Shrawan Poudel (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1003

References

- https://thedfirreport.com/2021/12/13/diavol-ransomware/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/20	medium	• Unknown

Rule Details: CL_LoadAssembly.ps1 Proxy Execution

Detects the use of a Microsoft signed script to execute commands and bypassing AppLocker.

Rule ID

`process_creation_commandline_3`

Query

{'selection': {'CommandLine|contains': ['\\CL_LoadAssembly.ps1', 'LoadAssemblyFromPath ']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c57872c7-614f-4d7f-a40d-b78c8df2d30d

Author: frack113, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1216

References

- https://bohops.com/2018/01/07/executing-commands-and-bypassing-applocker-with-powershell-diagnostic-scripts/
- https://lolbas-project.github.io/lolbas/Scripts/CL_LoadAssembly/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/05/21	medium	• Unknown

Rule Details: Suspicious Characters in CommandLine

Detects suspicious Unicode characters in the command line, which could be a sign of obfuscation or defense evasion.

Rule ID

`process_creation_commandline_4`

Query

```
{'selection_spacing_modifiers': {'CommandLine|contains': ['ˣ', 'ˌ', 'ˢ']}, 'selection_unicode_slashes': {'CommandLine|contains': ['⁄', '⁄']}, 'selection_unicode_hyphens': {'CommandLine|contains': ['—', '—']}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,2c0d2d7b-30d6-4d14-9751-7b9113042ab9

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://www.wietzebeukema.nl/blog/windows-command-line-obfuscation

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/04/27	high	• Unknown

Rule Details: Firewall Disabled via Netsh.EXE

Detects netsh commands that turns off the Windows firewall.

Rule ID

`process_creation_commandline_5`

Query

```
{'selection_img': [{'Image|endswith': '\\netsh.exe'}, {'OriginalFileName': 'netsh.exe'}], 'selection_cli_1': {'CommandLine|contains|all': ['firewall', 'set', 'opmode', 'disable']}, 'selection_cli_2': {'CommandLine|contains|all': ['advfirewall', 'set', 'state', 'off']}, 'condition': 'selection_img and 1 of selection_cli_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,57c4bf16-227f-4394-8ec7-1b745ee061c3

Author: Fatih Sirin

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.004

References

- https://www.winhelponline.com/blog/enable-and-disable-windows-firewall-quickly-using-command-line/
- https://app.any.run/tasks/210244b9-0b6b-4a2c-83a3-04bd3175d017/

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1562.004/T1562.004.md#atomic-test-1---disable-microsoft-defender-firewall

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/11/01	medium	• Legitimate administration activity

Rule Details: Ke3chang Registry Key Modifications

Detects Registry modifications performed by Ke3chang malware in campaigns running in 2019 and 2020.

Rule ID

```
process_creation_commandline_6
```

Query

```
{'selection1': {'CommandLine|contains': ['-Property DWORD -
name DisableFirstRunCustomize -value 2 -Force', '-Property String -
name Check_Associations -value', '-Property DWORD -name IEHarden -value 0 -
Force']}, 'condition': 'selection1'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7b544661-69fc-419f-9a59-82ccc328f205

Author: Markus Neis, Swisscom

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://www.verfassungsschutz.de/embed/broschuere-2020-06-bfv-cyber-brief-2020-01.pdf
- https://unit42.paloaltonetworks.com/operation-ke3chang-resurfaces-with-new-tidepool-malware/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/06/18	critical	• Will need to be looked for combinations of those processes

Rule Details: Potential PowerShell Obfuscation Via WCHAR

Detects suspicious encoded character syntax often used for defense evasion.

Rule ID

`process_creation_commandline_7`

Query

```
{'selection': {'CommandLine|contains': '(WCHAR)0x'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e312efd0-35a1-407f-8439-b8d434b438a6

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://twitter.com/0gtweet/status/1281103918693482496

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/07/09	high	• Unknown

Rule Details: Conti Volume Shadow Listing

Detects a command used by conti to find volume shadow backups.

Rule ID

`process_creation_commandline_8`

Query

```
{'selection': {'CommandLine|contains|all': ['vssadmin list shadows', 'log.txt']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7b30e0a7-c675-4b24-8a46-82fa67e2433d

Author: Max Altgelt (Nextron Systems), Tobias Michalski (Nextron Systems)

Tactics, Techniques, and Procedures

TA0042, T1587.001, TA0002, T1059.003

References

- https://twitter.com/vxunderground/status/1423336151860002816?s=20
- https://www.virustotal.com/gui/file/03e9b8c2e86d6db450e5eceec057d7e369ee2389b9daecaf06331a95410aa5f8/detection

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/09	high	• Unknown

Rule Details: InfDefaultInstall.exe .inf Execution

Executes SCT script using scrobj.dll from a command in entered into a specially prepared INF file.

Rule ID

`process_creation_commandline_9`

Query

{'selection': {'CommandLine|contains|all': ['InfDefaultInstall.exe ', '.inf']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ce7cf472-6fcc-490a-9481-3786840b5d9b

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1218/T1218.md#atomic-test-4---infdefaultinstallexe-inf-execution
- https://lolbas-project.github.io/lolbas/Binaries/Infdefaultinstall/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/13	medium	• Unknown

Rule Details: Root Certificate Installed From Susp Locations

Adversaries may install a root certificate on a compromised system to avoid warnings when connecting to adversary controlled web servers.

Rule ID

process_creation_commandline_10

Query

{'selection': {'CommandLine|contains|all': ['Import-Certificate', ' -FilePath ', 'Cert:\\LocalMachine\\Root'], 'CommandLine|contains': ['\\AppData\\Local\\Temp\\', ':\\Windows\\TEMP\\', '\\Desktop\\', '\\Downloads\\', '\\Perflogs\\', ':\\Users\\Public\\']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,5f6a601c-2ecb-498b-9c33-660362323afa

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1553.004

References

- https://www.microsoft.com/security/blog/2022/09/07/profiling-dev-0270-phosphorus-ransomware-operations/
- https://docs.microsoft.com/en-us/powershell/module/pki/import-certificate?view=windowsserver2022-ps

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/09	high	• Unlikely

Rule Details: Suspicious PrinterPorts Creation (CVE-2020-1048)

Detects new commands that add new printer port which point to suspicious file.

Rule ID

`process_creation_commandline_11`

Query

```
{'selection1': {'CommandLine|contains': 'Add-PrinterPort -
Name'}, 'selection2': {'CommandLine|contains': ['.exe', '.dll', '.bat']}, 'selection3
': {'CommandLine|contains': 'Generic / Text Only'}, 'condition': '(selection1 and sel
ection2) or selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,cc08d590-8b90-413a-aff6-31d1a99678d7

Author: EagleEye Team, Florian Roth

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://windows-internals.com/printdemon-cve-2020-1048/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/13	high	• New printer port install on host

Rule Details: PowerShell Script Run in AppData

Detects a suspicious command line execution that invokes PowerShell with reference to an AppData folder.

Rule ID

`process_creation_commandline_12`

Query

```
{'selection1': {'CommandLine|contains': ['powershell.exe', '\\powershell', '\\pwsh', 'pwsh.exe']}, 'selection2': {'CommandLine|contains|all': ['/c ', '\\AppData\\'], 'CommandLine|contains': ['Local\\', 'Roaming\\']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ac175779-025a-4f12-98b0-acdaeb77ea85

Author: Florian Roth (Nextron Systems), Jonhnathan Ribeiro, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://twitter.com/JohnLaTwC/status/1082851155481288706
- https://app.any.run/tasks/f87f1c4e-47e2-4c46-9cf4-31454c06ce03

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/01/09	medium	• Administrative scripts

Rule Details: Potential Remote Desktop Tunneling

Detects potential use of an SSH utility to establish RDP over a reverse SSH Tunnel. This can be used by attackers to enable routing of network packets that would otherwise not reach their intended destination.

Rule ID

`process_creation_commandline_13`

Query

```
{'selection': {'CommandLine|contains': ':3389'}, 'selection_opt': {'CommandLine|conta
ins': [' -L ', ' -P ', ' -R ', ' -pw ', ' -ssh ']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,8a3038e8-9c9d-46f8-b184-66234a160f6f

Author: Tim Rauch, Elastic (idea)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0008, T1021

References

- https://www.elastic.co/guide/en/security/current/potential-remote-desktop-tunneling-detected.html

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation D	Risk Level	False Positives
experimental	2022/09/27	medium	• Unknown

Rule Details: MSTSC Shadowing

Detects RDP session hijacking by using MSTSC shadowing.

Rule ID

`process_creation_commandline_14`

Query

```
{'selection': {'CommandLine|contains|all': ['noconsentprompt', 'shadow:']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,6ba5a05f-b095-4f0a-8654-b825f4f16334

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0008, T1563.002

References

- https://twitter.com/kmkz_security/status/1220694202301976576
- https://github.com/kmkz/Pentesting/blob/47592e5e160d3b86c2024f09ef04ceb87d204995/Post-Exploitation-Cheat-Sheet

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/01/24	high	• Unknown

Rule Details: Suspicious Scan Loop Network

Adversaries may attempt to get a listing of other systems by IP address, hostname, or other logical identifier on a network that may be used for Lateral Movement from the current system.

Rule ID

`process_creation_commandline`

Query

```
{'selection_loop': {'CommandLine|contains': ['for ', 'foreach ']}, 'selection_tools':
 [{'CommandLine|re': '\\bnslookup\\b'}, {'CommandLine|re': '\\bping\\b'}], 'condition
': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f8ad2e2c-40b6-4117-84d7-20b89896ab23

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0007, T1018

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1018/T1018.md
- https://ss64.com/nt/for.html
- https://ss64.com/ps/foreach-object.html

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/12	medium	• Legitimate script

Rule Details: Obfuscated IP Download

Detects use of an encoded/obfuscated version of an IP address (hex, octal...) in an URL combined with a download command.

Rule ID

`process_creation_commandline_16`

Query

```
{'selection_img': {'CommandLine|contains': ['Invoke-
WebRequest', 'iwr ', 'wget ', 'curl ', 'DownloadFile', 'DownloadString']}, 'selection
```

_ip': [{'CommandLine|contains': ['//0x', '.0x', '.00x']}, {'CommandLine|contains|all'
: ['http://%', '%2e']}], 'condition': 'all of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,cb5a2333-56cf-4562-8fcb-22ba1bca728d

Author: Florian Roth (Nextron Systems), X__Junior (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://h.43z.one/ipconverter/
- https://twitter.com/Yasser_Elsnbary/status/1553804135354564608

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/03	medium	• Unknown

Rule Details: MSExchange Transport Agent Installation

Detects the Installation of a Exchange Transport Agent.

Rule ID

process_creation_commandline_17

Query

{'selection': {'CommandLine|contains': 'Install-
TransportAgent'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,83809e84-4475-4b69-bc3e-4aad8568612f

Author: Tobias Michalski (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1505.002

References

- https://speakerdeck.com/heirhabarov/hunting-for-persistence-via-microsoft-exchange-server-or-outlook?slide=7

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/06/08	medium	• Legitimate installations of exchange TransportAgents. AssemblyPath is a good indicator for this.

Rule Details: Pubprn.vbs Proxy Execution

Detects the use of the 'Pubprn.vbs' Microsoft signed script to execute commands.

Rule ID

`process_creation_commandline_18`

Query

```
{'selection': {'CommandLine|contains|all': ['\\pubprn.vbs', 'script:']}, 'condition':
 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,1fb76ab8-fa60-4b01-bddd-71e89bf555da

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1216.001

References

- https://lolbas-project.github.io/lolbas/Scripts/Pubprn/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/05/28	medium	• Unknown

Rule Details: Tamper Windows Defender Remove-MpPreference

Detects attempts to remove windows defender configuration using the 'MpPreference' cmdlet.

Rule ID

```
process_creation_commandline_19
```

Query

```
{'selection_remove': {'CommandLine|contains': 'Remove-
MpPreference'}, 'selection_tamper': {'CommandLine|contains': ['-
ControlledFolderAccessProtectedFolders ', '-AttackSurfaceReductionRules_Ids ', '-
AttackSurfaceReductionRules_Actions ', '-
CheckForSignaturesBeforeRunningScan ']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,07e3cb2c-0608-410d-be4b-1511cb1a0448

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://techcommunity.microsoft.com/t5/core-infrastructure-and-security/windows-10-controlled-folder-access-event-search/ba-p/2326088

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/05	high	• Legitimate PowerShell scripts

Rule Details: AnyDesk Silent Installation

Detects AnyDesk Remote Desktop silent installation. Which can be used by attackers to gain remote access.

Rule ID

`process_creation_commandline_20`

Query

```
{'selection': {'CommandLine|contains|all': ['--install', '--start-with-win', '--silent']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,114e7f1c-f137-48c8-8f54-3088c24ce4b9

Author: Ján Trenčanský

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0011, T1219

References

- https://twitter.com/TheDFIRReport/status/1423361119926816776?s=20

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/06	high	• Legitimate deployment of AnyDesk

Rule Details: Execution via CL_Invocation.ps1

Detects Execution via SyncInvoke in CL_Invocation.ps1 module.

Rule ID

`process_creation_commandline_21`

Query

```
{'selection': {'CommandLine|contains|all': ['CL_Invocation.ps1', 'SyncInvoke']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,a0459f02-ac51-4c09-b511-b8c9203fc429

Author: Nasreddine Bencherchali (Nextron Systems), oscd.community, Natalia Shornikova

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1216

References

- https://lolbas-project.github.io/lolbas/Scripts/CI_invocation/
- https://twitter.com/bohops/status/948061991012327424

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/14	high	• Unknown

Rule Details: Writing Of Malicious Files To The Fonts Folder

Monitors for the hiding possible malicious files in the C:\Windows\Fonts\ location. This folder doesn't require admin privillege to be written and executed from.

Rule ID

```
process_creation_commandline_24
```

Query

```
{'selection_1': {'CommandLine|contains': ['echo', 'copy', 'type', 'file createnew', 'cacls']}, 'selection_2': {'CommandLine|contains': 'C:\\Windows\\Fonts\\'}, 'selection_3': {'CommandLine|contains': ['.sh', '.exe', '.dll', '.bin', '.bat', '.cmd', '.js', '.msh', '.reg', '.scr', '.ps', '.vb', '.jar', '.pl', '.inf', '.cpl', '.hta', '.msi', '.vbs']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ae9b0bd7-8888-4606-b444-0ed7410cb728

Author: Sreeman

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1211

References

- https://thedfirreport.com/2020/04/20/sqlserver-or-the-miner-in-the-basement/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/04/21	medium	• Unknown

Rule Details: Suspicious FromBase64String Usage On Gzip Archive - Process Creation

Detects attempts of decoding a base64 Gzip archive via PowerShell. This technique is often used as a method to load malicious content into memory afterward.

Rule ID

```
process_creation_commandline_25
```

Query

```
{'selection': {'CommandLine|contains|all': ['FromBase64String', 'MemoryStream', 'H4sI
']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,d75d6b6b-adb9-48f7-824b-ac2e786efe1f

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=43

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/23	medium	• Legitimate administrative script

Rule Details: Suspicious Usage Of ShellExec_RunDLL

Detects suspicious usage of the ShellExec_RunDLL function to launch other commands as seen in the the raspberry-robin attack.

Rule ID

`process_creation_commandline_26`

Query

```
{'selection_openasrundll': {'CommandLine|contains': 'ShellExec_RunDLL'}, 'selection_suspcli': {'CommandLine|contains': ['regsvr32', 'msiexec', '\\Users\\Public\\', 'odbcconf', '\\Desktop\\', '\\Temp\\', 'Invoke-
', 'iex', 'comspec']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,d87bd452-6da1-456e-8155-7dc988157b7d

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://redcanary.com/blog/raspberry-robin/
- https://www.microsoft.com/en-us/security/blog/2022/10/27/raspberry-robin-worm-part-of-larger-ecosystem-facilitating-pre-ransomware-activity/
- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/01	high	• Unknown

Rule Details: Turla Group Lateral Movement

Detects automated lateral movement by Turla group.

Rule ID

`process_creation_commandline_27`

Query

```
{'selection': {'CommandLine': ['net use \\\\%DomainController%\\C$ "P@ssw0rd" *', 'dir c:\\*.doc* /s', 'dir %TEMP%\\*.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c601f20d-570a-4cde-a7d6-e17f99cb8e7f

Author: Markus Neis

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0007, T1083, T1135, TA0008, T1021.002

References

- https://securelist.com/the-epic-turla-operation/65545/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/11/07	critical	• Unknown

Rule Details: Netsh RDP Port Opening

Detects netsh commands that opens the port 3389 used for RDP, used in Sarwent Malware.

Rule ID

`process_creation_commandline_28`

Query

```
{'selection1': {'CommandLine|contains|all': ['netsh', 'firewall add portopening', 'tcp 3389']}, 'selection2': {'CommandLine|contains|all': ['netsh', 'advfirewall firewall add rule', 'action=allow', 'protocol=TCP', 'localport=3389']}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,01aeb693-138d-49d2-9403-c4f52d7d3d62

Author: Sander Wiebing

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.004

References

- https://labs.sentinelone.com/sarwent-malware-updates-command-detonation/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/23	high	• Legitimate administration

Rule Details: PowerShell DownloadFile

Detects the execution of powershell, a WebClient object creation and the invocation of DownloadFile in a single command line.

Rule ID

`process_creation_commandline_29`

Query

{'selection': {'CommandLine|contains|all': ['powershell', '.DownloadFile', 'System.Net.WebClient']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,8f70ac5f-1f6f-4f8e-b454-db19561216c5

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0011, T1104, T1105

References

- https://www.fireeye.com/blog/threat-research/2020/03/apt41-initiates-global-intrusion-campaign-using-multiple-exploits.html

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/08/28	high	• Unknown

Rule Details: Powershell Defender Exclusion

Detects requests to exclude files, folders or processes from Antivirus scanning using PowerShell cmdlets.

Rule ID

`process_creation_commandline_30`

Query

{'selection1': {'CommandLine|contains': ['Add-MpPreference ', 'Set-MpPreference ']}, 'selection2': {'CommandLine|contains': [' -ExclusionPath ', ' -ExclusionExtension ', ' -ExclusionProcess ', ' -ExclusionIpAddress ']}, 'condition': 'all of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,17769c90-230e-488[illegible]63-e05c08e9d48f

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://docs.microsoft.com/en-us/microsoft-365/security/defender-endpoint/configure-process-opened-file-exclusions-microsoft-defender-antivirus
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1562.001/T1562.001.md
- https://twitter.com/AdamTheAnalyst/status/1483497517119590403

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/04/29	medium	• Possible Admin Activity • Other Cmdlets that may use the same parameters

Rule Details: Lazarus Loaders

Detects different loaders as described in various threat reports on Lazarus group activity.

Rule ID

`process_creation_commandline_31`

Query

```
{'selection_cmd1': {'CommandLine|contains|all': ['cmd.exe /c ', ' -
p 0x']}, 'selection_cmd2': {'CommandLine|contains': ['C:\\ProgramData\\', 'C:\\RECYCL
ER\\']}, 'selection_rundll1': {'CommandLine|contains|all': ['rundll32.exe ', 'C:\\Pro
gramData\\']}, 'selection_rundll2': {'CommandLine|contains': ['.bin,', '.tmp,', '.dat
,', '.io,', '.ini,', '.db,']}, 'condition': '( selection_cmd1 and selection_cmd2 ) or
 ( selection_rundll1 and selection_rundll2 )'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7b49c990-4a9a-4e65-95-47c9cc448f6e

Author: Florian Roth (Nextron Systems), wagga

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://www.hvs-consulting.de/lazarus-report/
- https://securelist.com/lazarus-covets-covid-19-related-intelligence/99906/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/12/23	critical	• Unknown

Rule Details: Suspicious GrpConv Execution

Detects the suspicious execution of a utility to convert Windows 3.x .grp files or for persistence purposes by malicious software or actors.

Rule ID

`process_creation_commandline_32`

Query

```
{'selection': {'CommandLine|contains': ['grpconv.exe -o', 'grpconv -
o']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f14e169e-9978-4c69-acb3-1cff8200bc36

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1547

References

- https://twitter.com/0gtweet/status/1526833181831200770

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/05/19	high	• Unknown

Rule Details: Disabled RestrictedAdminMode For RDS - ProcCreation

Detect activation of DisableRestrictedAdmin to desable RestrictedAdmin mode. RestrictedAdmin mode prevents the transmission of reusable credentials to the remote system to which you connect using Remote Desktop. This prevents your credentials from being harvested during the initial connection process if the remote server has been compromise.

Rule ID

`process_creation_commandline_33`

Query

```
{'selection': {'CommandLine|contains|all': ['\\System\\CurrentControlSet\\Control\\Lsa\\', 'DisableRestrictedAdmin', ' 1']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,28ac00d6-22d9-4a3c-927f-bbd770104573

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1112

References

- https://github.com/redcanaryco/atomic-red-team/blob/a8e3cf63e97b973a25903d3df9fd55da6252e564/atomics/T1112/T1112.md
- https://social.technet.microsoft.com/wiki/contents/articles/32905.remote-desktop-services-enable-restricted-admin-mode.aspx

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/13	high	• Unknown

Rule Details: Malicious Base64 Encoded Powershell Invoke Cmdlets

Detects base64 encoded powershell cmdlet invocation of known suspicious cmdlets.

Rule ID

`process_creation_commandline_34`

Query


```
{'selection': {'CommandLine|contains': ['SQBuAHYAbwBrAGUALQBCAGwAbwBvAGQASABvAHUAbgBkA', 'kAbgB2AG8AawBlAC0AQgBsAG8AbwBkAEgAbwB1AG4AZA', 'JAG4AdgBvAGsAZQAtAEIAbABvAG8AZABIAG8AdQBuAGQA', 'SQBuAHYAbwBrAGUALQBNAGkAbQBpAGsAYQB0AHoA', 'kAbgB2AG8AawBlAC0ATQBpAG0AaQBrAGEAdAB6A', 'JAG4AdgBvAGsAZQAtAE0AaQBtAGkAawBhAHQAeg', 'SQBuAHYAbwBrAGUALQBXAE0ASQBFAHgAZQBjA', 'kAbgB2AG8AawBlAC0AVwBNAEkARQB4AGUAYw', 'JAG4AdgBvAGsAZQAtAFcATQBJAEUAeABlAGMA']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,fd6e2919-3936-40c9-99db-0aa922c356f7

Author: pH-T (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://thedfirreport.com/2022/05/09/seo-poisoning-a-gootloader-story/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/31	high	• Unlikely

Rule Details: Uninstall Crowdstrike Falcon

Adversaries may disable security tools to avoid possible detection of their tools and activities by uninstalling Crowdstrike Falcon.

Rule ID

`process_creation_commandline_35`

Query

```
{'selection': {'CommandLine|contains|all': ['\\WindowsSensor.exe', ' /uninstall', ' /quiet']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f0f7be61-9cf5-43be-9836-99d6ef448a18

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1562.001/T1562.001.md

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/12	medium	• Uninstall by admin

Rule Details: Suspicious Powershell No File or Command

Detects suspicious powershell execution that ends with a common flag instead of a command or a filename to execute (could be a sign of implicit execution that uses files in WindowsApps directory).

Rule ID

`process_creation_commandline`

Query

```
{'selection': {'CommandLine|endswith': [' -windowstyle hidden"', ' -windowstyle hidden', " -windowstyle hidden'", ' -w hidden"', ' -w hidden', " -w hidden'", ' -ep bypass"', ' -ep bypass', " -ep bypass'", ' -noni"', ' -noni', " -noni'"]}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b66474aa-bd92-4333-a16c-298155b120df

Author: pH-T (Nextron Systems), Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0003, T1053.005

References

- https://blog.malwarebytes.com/threat-intelligence/2022/04/colibri-loader-combines-task-scheduler-and-powershell-in-clever-persistence-technique/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/04/08	high	• Unknown

Rule Details: New Network Provider - CommandLine

Detects when an attacker tries to add a new network provider in order to dump clear text credentials, similar to how the NPPSpy tool does it.

Rule ID

`process_creation_commandline_37`

Query

```
{'selection': {'CommandLine|contains|all': ['\\System\\CurrentControlSet\\Services\\', '\\NetworkProvider']}, 'filter': {'CommandLine|contains': ['\\System\\CurrentContro
```

lSet\\Services\\WebClient\\NetworkProvider', '\\System\\CurrentControlSet\\Services\\LanmanWorkstation\\NetworkProvider', '\\System\\CurrentControlSet\\Services\\RDPNP\\NetworkProvider']}, 'condition': 'selection and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,baef1ec6-2ca9-47a3-97cc-4cf2bda10b77

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1003

References

- https://docs.microsoft.com/en-us/troubleshoot/windows-client/deployment/network-provider-settings-removed-in-place-upgrade
- https://github.com/gtworek/PSBits/tree/master/PasswordStealing/NPPSpy

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/23	high	• Other legitimate network providers used and not filtred in this rule

Rule Details: Turla Group Commands May 2020

Detects commands used by Turla group as reported by ESET in May 2020.

Rule ID

process_creation_commandline_38

Query

{'selection1': {'CommandLine|contains': ['tracert -h 10 yahoo.com', '.WSqmCons))|iex;', 'Fr`omBa`se6`4Str`ing']}, 'selection2': {'CommandLine|contains|all': ['net use https://docs.live.net', '@aol.co.uk']}, 'condition': '1 of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,9e2e51c5-c699-4794-ba5a-29f5da40ac0c

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0003, T1053.005, TA0005, T1027

References

- https://www.welivesecurity.com/wp-content/uploads/2020/05/ESET_Turla_ComRAT.pdf

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/26	critical	• Unknown

Rule Details: Potential Data Stealing Via Chromium Headless Debugging

Detects chromium based browsers starting in headless and debugging mode and pointing to a user profile. This could be a sign of data stealing or remote control.

Rule ID

`process_creation_commandline_39`

Query

```
{'selection': {'CommandLine|contains|all': ['--remote-debugging-', '--user-data-dir', '--headless']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,3e8207c5-fcd2-4ea6-9418-15d45b4890e4

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1185

References

- https://github.com/defa[illegible]amehere/cookie_crimes/
- https://mango.pdf.zone/stealing-chrome-cookies-without-a-password
- https://embracethered.com/blog/posts/2020/cookie-crimes-on-mirosoft-edge/
- https://embracethered.com/blog/posts/2020/chrome-spy-remote-control/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/23	high	• Unknown

Rule Details: Invoke-Obfuscation Via Use MSHTA

Detects Obfuscated Powershell via use MSHTA in Scripts.

Rule ID

`process_creation_commandline_40`

Query

```
{'selection': {'CommandLine|contains|all': ['set', '&&', 'mshta', 'vbscript:createobj
ect', '.run', '(window.close)']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ac20ae82-8758-4f38-958e-b44a3140ca88

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/08	high	• Unknown

Rule Details: Suspicious Rundll32 Script in CommandLine

Detects suspicious process related to rundll32 based on arguments.

Rule ID

`process_creation_commandline_41`

Query

```
{'selection': {'CommandLine|contains|all': ['rundll32', 'mshtml,RunHTMLApplication'],
 'CommandLine|contains': ['javascript:', 'vbscript:']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,73fcad2e-ff14-4c38-b11d-4172c8ac86c7

Author: frack113, Zaw Min Htun (ZETA)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.011

References

- https://gist.github.com/ryhanson/227229866af52e2d963cf941af135a52
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1218.011/T1218.011.md

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/04	medium	• False positives depend on scripts and administrative tools used in the monitored environment

Rule Details: Suspicious Base64 Encoded Powershell Invoke

Detects base64 encoded powershell 'Invoke-' call.

Rule ID

`process_creation_commandline_42`

Query


```
{'selection': {'CommandLine|contains': ['SQBuAHYAbwBrAGUALQ', 'kAbgB2AG8AawBlAC0A', 'JAG4AdgBvAGsAZQAtA']}, 'filter_other_rule': {'CommandLine|contains': ['SQBuAHYAbwBrAGUALQBCAGwAbwBvAGQASABvAHUAbgBkA', 'kAbgB2AG8AawBlAC0AQgBsAG8AbwBkAEgAbwB1AG4AZA', 'JAG4AdgBvAGsAZQAtAEIAbABvAG8AZABIAG8AdQBuAGQA', 'SQBuAHYAbwBrAGUALQBNAGkAbQBpAGsAYQB0AHoA', 'kAbgB2AG8AawBlAC0ATQBpAG0AaQBrAGEAdAB6A', 'JAG4AdgBvAGsAZQAtAE0AaQBtAGkAawBhAHQAeg', 'SQBuAHYAbwBrAGUALQBXAE0ASQBFAHgAZQBjA', 'kAbgB2AG8AawBlAC0AVwBNAEkARQB4AGUAYw', 'JAG4AdgBvAGsAZQAtAFcATQBJAEUAeABlAGMA']}, 'condition': 'selection and not 1 of filter*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,6385697e-9f1b-40bd-8817-f4a91f40508e

Author: pH-T (Nextron Systems), Harjot Singh, @cyb3rjy0t

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://thedfirreport.com/2022/05/09/seo-poisoning-a-gootloader-story/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/20	high	• Unlikely

Rule Details: HackTool - Bloodhound/Sharphound Execution

Detects command line parameters used by Bloodhound and Sharphound hack tools.

Rule ID

`process_creation_commandline_44`

Query

```
{'selection_cli_1': {'CommandLine|contains': [' -CollectionMethod All ', ' --
CollectionMethods Session ', ' --Loop --Loopduration ', ' --
PortScanTimeout ', '.exe -c All -d ', 'Invoke-Bloodhound', 'Get-
BloodHoundData']}, 'selection_cli_2': {'CommandLine|contains|all': [' -
JsonFolder ', ' -
ZipFileName ']}, 'selection_cli_3': {'CommandLine|contains|all': [' DCOnly ', ' --
NoSaveCache ']}, 'condition': '1 of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f376c8a7-a2d0-4ddc-aa0c-16c17236d962

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0007, T1087, T1482, T1069

References

- https://github.com/BloodHoundAD/BloodHound
- https://github.com/BloodHoundAD/SharpHound

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/12/20	high	• Other programs that use these command line option and accepts an 'All' parameter

Rule Details: Explorer Process Tree Break

Detects a command line process that uses explorer.exe to launch arbitrary commands or binaries, which is similar to cmd.exe /c, only it breaks the process tree and makes its parent a new instance of explorer spawning from "svchost".

Rule ID

`process_creation_commandline`

Query


```
{'selection': [{'CommandLine|contains': '/factory,{75dff2b7-6936-4c06-a8bb-676a7b00b24b}'}, {'CommandLine|contains|all': ['explorer.exe', ' /root,']}], 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,949f1ffb-6e85-4f00-ae1e-c3c5b190d605

Author: Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems), @gott_cyber

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1036

References

- https://twitter.com/CyberRaiju/status/1273597319322058752
- https://twitter.com/bohops/status/1276357235954909188?s=12
- https://twitter.com/nas_bench/status/1535322450858233858

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/06/29	medium	• Unknown how many legitimate software products use that method

Rule Details: Suspicious Del in CommandLine

Detects suspicious command line to remove and 'exe' or 'dll'.

Rule ID

`process_creation_commandline_46`

Query


```
{'susp_del_exe': {'CommandLine|contains|all': ['del ', '*.exe', '/f ', '/q ']}, 'susp_del_dll': {'CommandLine|contains|all': ['del ', '*.dll', 'C:\\ProgramData\\']}, 'con
```

dition': 'susp_del_exe or susp_del_dll'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,204b17ae-4007-471b-917b-b917b315c5db

Author: frack113 , X__Junior (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1070.004

References

- https://www.joesandbox.com/analysis/509330/0/html#1044F3BDBE3BB6F734E357235F4D5898582D

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/02	medium	• Unknown

Rule Details: Invoke-Obfuscation COMPRESS OBFUSCATION

Detects Obfuscated Powershell via COMPRESS OBFUSCATION.

Rule ID

process_creation_commandline_47

Query

{'selection': {'CommandLine|contains|all': ['new-object', 'text.encoding]::ascii'], 'CommandLine|contains': ['system.io.compression.deflatestream', 'system.io.streamreader', 'readtoend(']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7eedcc9d-9fdb-4d94-9c54-474e8affc0c7

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/18	medium	• Unknown

Rule Details: Operation Wocao Activity

Detects activity mentioned in Operation Wocao report.

Rule ID

```
process_creation_commandline_48
```

Query

```
{'selection': {'CommandLine|contains': ['checkadmin.exe 127.0.0.1 -
all', 'netsh advfirewall firewall add rule name=powershell dir=in', 'cmd /c powershel
l.exe -ep bypass -
file c:\\s.ps1', '/tn win32times /f', 'create win32times binPath=', '\\c$\\windows\\s
ystem32\\devmgr.dll', ' -exec bypass -
enc JgAg', 'type *keepass\\KeePass.config.xml', 'iie.exe iie.txt', 'reg query HKEY_CU
RRENT_USER\\Software\\*\\PuTTY\\Sessions\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,1cfac73c-be78-4f9a-9b08-5bde0c3953ab

Author: Florian Roth (Nextron Systems), frack113

Tactics, Techniques, and Procedures

TA0002, T1059, TA0003, T1053.005, TA0005, T1036.004, T1027, TA0007, T1012

References

- https://twitter.com/SBousseaden/status/1207671369963646976

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/12/20	high	• Administrators that use checkadmin.exe tool to enumerate local administrators

Rule Details: Fireball Archer Install

Detects Archer malware invocation via rundll32.

Rule ID

`process_creation_commandline_49`

Query

```
{'selection': {'CommandLine|contains|all': ['rundll32.exe', 'InstallArcherSvc']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,3d4aebe0-6d29-45b2-a8a4-3dfde586a26d

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.011

References

- https://www.virustotal.com/en/file/9b4971349ae85aa09c0a69852ed3e626c954954a3927b3d1b6646f139b930022/analysis/
- https://www.hybrid-analysis.com/sample/9b4971349ae85aa09c0a69852ed3e626c954954a3927b3d1b6646f139b930022?environmentId=100

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/06/03	high	• Unknown

Rule Details: Zip A Folder With PowerShell For Staging In Temp

Use living off the land tools to zip a file and stage it in the Windows temporary folder for later exfiltration.

Rule ID

`process_creation_commandline_50`

Query

```
{'selection': {'CommandLine|contains|all': ['Compress-Archive ', ' -Path ', ' -DestinationPath ', '$env:TEMP\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,85a8e5ba-bd03-4bfb-bbfa-a4409a8f8b98

Author: Nasreddine Bencherchali (Nextron Systems), frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1074.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1074.001/T1074.001.md

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/20	medium	• Unknown

Rule Details: Registry Dump of SAM Creds and Secrets

Adversaries may attempt to extract credential material from the Security Account Manager (SAM) database either through Windows Registry where the SAM database is stored.

Rule ID

`process_creation_commandline_51`

Query


```
{'selection_reg': {'CommandLine|contains': ' save '}, 'selection_key': {'CommandLine|contains': ['HKLM\\sam', 'HKLM\\system', 'HKLM\\security']}, 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,038cd51c-3ad8-41c5-ba8f-5d1c92f3cc1e

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1003.002

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1003.002/T1003.002.md#atomic-test-1---registry-dump-of-sam-creds-and-secrets

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/05	high	• Unknown

Rule Details: Procdump Evasion

Detects uses of the SysInternals Procdump utility in which procdump or its output get renamed or a dump file is moved ot copied to a different name.

Rule ID

`process_creation_commandline`

Query

```
{'selection1': {'CommandLine|contains': ['copy procdump', 'move procdump']}, 'selecti
on2': {'CommandLine|contains|all': ['copy ', '.dmp '], 'CommandLine|contains': ['2.dm
p', 'lsass', 'out.dmp']}, 'selection3': {'CommandLine|contains': ['copy lsass.exe_',
'move lsass.exe_']}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,79b06761-465f-4f88-9ef2-150e24d3d737

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1036, TA0006, T1003.001

References

- https://twitter.com/mrd0x/status/1480785527901204481

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/11	high	• Cases in which procdump just gets copied to a different directory without any renaming

Rule Details: Powershell Token Obfuscation - Process Creation

Detects TOKEN OBFUSCATION technique from Invoke-Obfuscation.

Rule ID

`process_creation_commandline_53`

Query

```
{'selection': [{'CommandLine|re': '\\w+`(\\w+|-
|.)`[\\w+|\\s]'}, {'CommandLine|re': '"(\\{\\d\\})+"\\s*-
f'}, {'CommandLine|re': '\\$\\{((e|n|v)*`(e|n|v)*)+:path\\}|\\$\\
```

{((e|n|v)*`(e|n|v)*)+:((p|a|t|h)*`(p|a|t|h)*)+\\}|\\$\\{env:
((p|a|t|h)*`(p|a|t|h)*)+\\}'` 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,deb9b646-a508-44ee-b7c9-d8965921c6b6

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1027

References

- https://github.com/danielbohannon/Invoke-Obfuscation

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/27	high	• Unknown

Rule Details: Suspicious Minimized MSEdge Start

Detects the suspicious minimized start of MsEdge browser, which can be used to download files from the Internet.

Rule ID

`process_creation_commandline_54`

Query

{'selection': {'CommandLine|contains': 'start /min msedge'}, 'condition': 'selection'
}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,94771a71-ba41-4b6e-a757-b531372eaab6

Author: Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0011, T1105

References

- https://twitter.com/mrd0x/status/1478234484881436672?s=12

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/11	high	• Software that uses MsEdge to download components in the background (see ParentImage, ParentCommandLine)

Rule Details: Suspicious PowerShell Download and Execute Pattern

Detects suspicious PowerShell download patterns that are often used in malicious scripts, stagers or downloaders (make sure that your backend applies the strings case-insensitive).

Rule ID

`process_creation_commandline_55`

Query

```
{'selection': {'CommandLine|contains': ['IEX ((New-
Object Net.WebClient).DownloadString', 'IEX (New-
Object Net.WebClient).DownloadString', 'IEX((New-
Object Net.WebClient).DownloadString', 'IEX(New-
Object Net.WebClient).DownloadString', ' -command (New-
Object System.Net.WebClient).DownloadFile(', ' -c (New-
Object System.Net.WebClient).DownloadFile(']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e6c54d94-498c-4562-a37c-b469d8e9a275

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://gist.github.com/jivoi/c354eaaf3019352ce32522f916c03d70
- https://www.trendmicro.com/en_us/research/22/j/lv-ransomware-exploits-proxyshell-in-attack.html

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/02/28	high	• Software installers that pull packages from remote systems and execute them

Rule Details: Add User to Local Administrators

Detects suspicious command line that adds an account to the local administrators/administrateurs group.

Rule ID

`process_creation_commandline_56`

Query

```
{'selection_net': {'Image|endswith': ['\\net.exe', '\\net1.exe'], 'CommandLine|contai
ns|all': ['localgroup ', ' /add']}, 'selection_powershell': {'Image|endswith': ['\\po
wershell.exe', '\\pwsh.exe'], 'CommandLine|contains|all': ['Add-
LocalGroupMember ', ' -
Group ']}, 'selection_group': {'CommandLine|contains': [' administrators ', ' adminis
trateur']}, 'filter_domain_admins_compliance': {'UserId': 'S-1-5-
18', 'CommandLine|contains': 'domain admin'}, 'condition': '(selection_net or selecti
on_powershell) and selection_group and not filter_domain_admins_compliance'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1098

References

- https://blog.talosintelligence.com/2022/08/recent-cyber-attack.html?m=1

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/12	medium	• Administrative activity

Rule Details: Taskkill Symantec Endpoint Protection

Detects one of the possible scenarios for disabling symantec endpoint protection. Symantec Endpoint Protection antivirus software services incorrectly implement the protected service mechanism. As a result, the NT AUTHORITY/SYSTEM user can execute the taskkill /im command several times ccSvcHst.exe /f, thereby killing the process belonging to the service, and thus shutting down the service.

Rule ID

`process_creation_commandline_57`

Query

```
{'selection': {'CommandLine|contains|all': ['taskkill', ' /F ', ' /IM ', 'ccSvcHst.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,4a6713f6-3331-11ed-a261-0242ac120002

Author: Ilya Krestinichev, Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://www.exploit-db.com/exploits/37525
- https://community.spiceworks.com/topic/2195015-batch-script-to-uninstall-symantec-endpoint-protection

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/13	high	• Unknown

Rule Details: MsiExec Web Install

Detects suspicious msiexec process starts with web addresses as parameter.

Rule ID

`process_creation_commandline_58`

Query

```
{'selection': {'CommandLine|contains|all': [' msiexec', '://']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f7b5f842-a6af-4da5-9e95-e32478f3cd2f

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.007, TA0011, T1105

References

- https://blog.trendmicro.com/trendlabs-security-intelligence/attack-using-windows-installer-msiexec-exe-leads-lokibot/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/02/09	medium	• False positives depend on scripts and administrative tools used in the monitored environment

Rule Details: PsExec Service Start

Detects a PsExec service start.

Rule ID

`process_creation_commandline_59`

Query

```
{'selection': {'CommandLine': 'C:\\Windows\\PSEXESVC.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,3ede524d-21cc-472d-a3ce-d21b568d8db7

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1569.002, T1059.003

References

N/A

Severity

24

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/03/13	low	• Administrative activity

Rule Details: Scheduled Task WScript VBScript

Detects specific process parameters as used by ACTINIUM scheduled task persistence creation.

Rule ID

`process_creation_commandline_60`

Query

```
{'selection': {'CommandLine|contains|all': ['schtasks', 'create', 'wscript', 'e:vbscript']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e1118a8f-82f5-44b3-bb6b-8a284e5df602

Author: Andreas Hunkeler (@Karneades)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1053.005

References

- https://www.microsoft.com/security/blog/2022/02/04/actinium-targets-ukrainian-organizations

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/07	high	• Unlikely

Rule Details: Dropping Of Password Filter DLL

Detects dropping of dll files in system32 that may be used to retrieve user credentials from LSASS.

Rule ID

`process_creation_commandline_61`

Query

```
{'selection_cmdline': {'CommandLine|contains|all': ['HKLM\\SYSTEM\\CurrentControlSet\
\Control\\Lsa', 'scecli\\0*', 'reg add']}, 'condition': 'selection_cmdline'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b7966f4a-b333-455b-8370-8ca53c229762

Author: Sreeman

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1556.002

References

- https://pentestlab.blog0/02/10/credential-access-password-filter-dll/
- https://github.com/3gstudent/PasswordFilter/tree/master/PasswordFilter

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/29	medium	• Unknown

Rule Details: Suspicious UltraVNC Execution

Detects suspicious UltraVNC command line flag combination that indicate a auto reconnect upon execution, e.g. startup (as seen being used by Gamaredon threat group).

Rule ID

`process_creation_commandline_62`

Query

```
{'selection': {'CommandLine|contains|all': ['-autoreconnect ', '-connect ', '-id:']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,871b9555-69ca-4993-99d3-35a59f9f3599

Author: Bhabesh Raj

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0008, T1021.005

References

- https://www.ria.ee/sites/default/files/content-editors/kuberturve/tale_of_gamaredon_infection.pdf
- https://unit42.paloaltonetworks.com/unit-42-title-gamaredon-group-toolset-evolution

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/04	high	• Unknown

Rule Details: Potential AMSI Bypass Using NULL Bits - ProcessCreation

Detects usage of special strings/null bits in order to potentially bypass AMSI functionalities.

Rule ID

`process_creation_commandline_63`

Query

```
{'selection': {'CommandLine|contains': ["if(0){{{0}}}' -f $(0 -as [char]) +", '#<NULL>']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,92a974db-ab84-457f-9ec0-55db83d7a825

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://github.com/r00t-3xp10it/hacking-material-books/blob/43cb1e1932c16ff1f58b755bc9ab6b096046853f/obfuscation/simple_obfuscation.md#amsi-bypass-using-null-bits-satoshi

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/04	medium	• Unknown

Rule Details: Invoke-Obfuscation CLIP+ Launcher

Detects Obfuscated use of Clip to execute PowerShell.

Rule ID

`process_creation_commandline_65`

Query

```
{'selection': {'CommandLine|contains|all': ['cmd', '&&', 'clipboard]::', '-f'], 'CommandLine|contains': ['/c', '/r']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b222df08-0e07-11eb-adc1-0242ac120002

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/13	high	• Unknown

Rule Details: SyncAppvPublishingServer VBS Execute Arbitrary PowerShell Code

Executes arbitrary PowerShell code using SyncAppvPublishingServer.vbs.

Rule ID

`process_creation_commandline_67`

Query

```
{'selection': {'CommandLine|contains|all': ['\\SyncAppvPublishingServer.vbs', ';']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,36475a7d-0f6d-4dce-9b01-6aeb473bbaf1

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218, T1216

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1216/T1216.md
- https://lolbas-project.github.io/lolbas/Binaries/Syncappvpublishingserver/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/07/16	medium	• Unknown

Rule Details: Suspicious Add User to Remote Desktop Users Group

Detects suspicious command line in which a user gets added to the local Remote Desktop Users group.

Rule ID

```
process_creation_commandline_68
```

Query

```
{'selection_main': [{'CommandLine|contains|all': ['localgroup ', ' /add']}, {'Command
Line|contains|all': ['Add-LocalGroupMember ', ' -
Group ']}], 'selection_group': {'CommandLine|contains': ['Remote Desktop Users', 'Uti
lisateurs du Bureau à distance', 'Usuarios de escritorio remoto']}, 'condition': 'all
 of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ffa28e60-bdb1-46e0-9f82-05f7a61cc06e

Author: Florian Roth (Nextron S ms)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1133, T1136.001, TA0008, T1021.001

References

- https://www.microsoft.com/security/blog/2021/11/16/evolving-trends-in-iranian-threat-actor-activity-mstic-presentation-at-cyberwarcon-2021/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/06	high	• Administrative activity

Rule Details: GatherNetworkInfo.vbs Script Usage

Adversaries can abuse of C:\Windows\System32\gatherNetworkInfo.vbs script along with cscript.exe to gather information about the target.

Rule ID

`process_creation_commandline_69`

Query

```
{'selection': {'CommandLine|contains|all': ['cscript.exe', 'gatherNetworkInfo.vbs']},
 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,575dce0c-8139-4e30-9295-1ee75969f7fe

Author: blueteamer8699

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://posts.slayerlabs.com/living-off-the-land/#gathernetworkinfovbs

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/03	medium	• Administrative activity

Rule Details: APT29

This method detects a suspicious PowerShell command line combination as used by APT29 in a campaign against U.S. think tanks.

Rule ID

`process_creation_commandline_70`

Query

```
{'selection': {'CommandLine|contains|all': ['-noni', '-
ep', 'bypass', '$']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,033fe7d6-66d1-4240-ac6b-28908009c71f

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://www.microsoft.com/security/blog/2018/12/03/analysis-of-cyberattack-on-u-s-think-tanks-non-profits-public-sector-by-unidentified-attackers/
- https://www.fireeye.com/blog/threat-research/2018/11/not-so-cozy-an-uncomfortable-examination-of-a-suspected-apt29-phishing-campaign.html

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/12/04	high	• Unknown

Rule Details: Suspicious WMIC ActiveScriptEventConsumer Creation

Detects WMIC executions in which a event consumer gets created in order to establish persistence.

Rule ID

`process_creation_commandline_71`

Query

```
{'selection': {'CommandLine|contains|all': ['ActiveScriptEventConsumer', ' CREATE ']}
, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ebef4391-1a81-4761-a40a-1db446c0e625

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1546.003

References

- https://twitter.com/johnlatwc/status/1408062131321270282?s=12
- https://www.fireeye.com/content/dam/fireeye-www/global/en/current-threats/pdfs/wp-windows-management-instrumentation.pdf

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/06/25	high	• Legitimate software creating script event consumers

Rule Details: TAIDOOR RAT DLL Load

Detects specific process characteristics of Chinese TAIDOOR RAT malware load.

Rule ID



`process_creation_commandline_72`

Query


```
{'selection1': {'CommandLine|contains': ['dll,MyStart', 'dll MyStart']}, 'selection2a': {'CommandLine|endswith': ' MyStart'}, 'selection2b': {'CommandLine|contains': 'rundll32.exe'}, 'condition': 'selection1 or ( selection2a and selection2b )'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,d1aa3382-abab-446f-96ea-4de52908210b

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1055.001

References

- https://us-cert.cisa.gov/ncas/analysis-reports/ar20-216a

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/07/30	high	• Unknown

Rule Details: Empire PowerShell UAC Bypass

Detects some Empire PowerShell UAC bypass methods.

Rule ID

`process_creation_commandline_73`

Query


```
{'selection': {'CommandLine|contains': [' -NoP -NonI -w Hidden -c $x=$((gp HKCU:Software\\Microsoft\\Windows Update).Update)', ' -NoP -NonI -c $x=$((gp HKCU:Software\\Microsoft\\Windows Update).Update);']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,3268b746-88d8-4cd3-bffc-30077d02c787

Author: Ecco

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1548.002

References

- https://github.com/EmpireProject/Empire/blob/e37fb2eef8ff8f5a0a689f1589f424906fe13055/data/module_source/privesc/Invoke-EventVwrBypass.ps1#L64
- https://github.com/EmpireProject/Empire/blob/e37fb2eef8ff8f5a0a689f1589f424906fe13055/data/module_source/privesc/Invoke-FodHelperBypass.ps1#L64

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2019/08/30	critical	• Unknown

Rule Details: Emotet Process Creation

Detects all Emotet like process executions that are not covered by the more generic rules.

Rule ID

`process_creation_commandline_74`

Query


```
{'selection': {'CommandLine|contains': [' -
e* PAA', 'JABlAG4AdgA6AHUAcwBlAHIAcAByAG8AZgBpAGwAZQ', 'QAZQBuAHYAOgB1AHMAZQByAHAAcgB
vAGYAaQBsAGUA', 'kAGUAbgB2ADoAdQBzAGUAcgBwAHIAbwBmAGkAbABlA', 'IgAoACcAKgAnACkAOwAkA'
, 'IAKAAnACoAJwApADsAJA', 'iACgAJwAqACcAKQA7ACQA', 'JABGAGwAeAByAGgAYwBmAGQ', 'PQAkAG
UAbgB2ADoAdABlAG0AcAArACgA', '0AJABlAG4AdgA6AHQAZQBtAHAAKwAoA', '9ACQAZQBuAHYAOgB0AGU
AbQBwACsAKA']}, 'filter': {'CommandLine|contains': ['fAAgAEMAbwBuAHYAZQByAHQAVABvAC0A
SgBzAG8AbgAgAC0ARQByAHIAbwByAEEAYwB0AGkAbwBuACAAUwBpAGwAZQBuAHQAbAB5AEMAbwBuAHQAaQBuA
HUAZQ', 'wAIABDAG8AbgB2AGUAcgB0AFQAbwAtAEoAcwBvAG4AIAAtAEUAcgByAG8AcgBBAGMAdABpAG8Abg
AgAFMAaQBsAGUAbgB0AGwAeQBDAG8AbgB0AGkAbgB1AGUA', '8ACAAQwBvAG4AdgBlAHIAdABUAG8ALQBKAH
```

MAbwBuACAALQBFAHIAcgBvAHIAQQBjAHQAaQBvAG4AIABTAGkAbABlAG4AdABsAHkAQwBvAG4AdABpAG4AdQBlA']}, 'condition': 'selection and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,d02e8cf5-6099-48cf-9bfc-1eec2d0c7b18

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://app.any.run/tasks/e13ab713-64cf-4b23-ad93-6dceaa5429ac/
- https://app.any.run/tasks/81f3c28c-c686-425d-8a2b-a98198d244e1/
- https://app.any.run/tasks/97f875e8-0e08-4328-815f-055e971ba754/
- https://app.any.run/tasks/84fc9b4a-ea2b-47b1-8aa6-9014402dfb56/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2019/09/30	high	• Unlikely

Rule Details: Esentutl Gather Credentials

Conti recommendation to its affiliates to use esentutl to access NTDS dumped file. Trickbot also uses this utilities to get MSEdge info via its module pwgrab.

Rule ID

process_creation_commandline_75

Query

{'selection': {'CommandLine|contains|all': ['esentutl', ' /p']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7df1713a-1a5b-4a4b-a071-dc83b144a101

Author: sam0x90

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1003.003

References

- https://twitter.com/vxunderground/status/1423336151860002816
- https://attack.mitre.org/software/S0404/
- https://thedfirreport.com/2021/08/01/bazarcall-to-conti-ransomware-via-trickbot-and-cobalt-strike/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/06	medium	• To be determined

Rule Details: EvilNum Golden Chickens Deployment via OCX Files

Detects Golden Chickens deployment method as used by Evilnum in report published in July 2020.

Rule ID

`process_creation_commandline_76`

Query

```
{'selection': {'CommandLine|contains|all': ['regsvr32', '/s', '/i', '\\AppData\\Roaming\\', '.ocx']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,8acf3cfa-1e8c-4099-83de-a0c4038e18f0

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0[illegible], T1218.011

References

- https://www.welivesecurity.com/2020/07/09/more-evil-deep-look-evilnum-toolset/
- https://app.any.run/tasks/33d37fdf-158d-4930-aa68-813e1d5eb8ba/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/07/10	critical	• Unknown

Rule Details: Suspicious Dosfuscation Character in Commandline

Detects possible payload obfuscation via the commandline.

Rule ID

`process_creation_commandline_77`

Query

```
{'selection': {'CommandLine|contains': ['^^', ',;,', '%COMSPEC:~', ' s^et ', ' s^e^t ', ' se^t ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,a77c1610-fc73-4019-8e29-0f51efc04a51

Author: frack113, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://www.fireeye.com/content/dam/fireeye-www/blog/pdfs/dosfuscation-report.pdf

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/02/15	medium	• Legitimate use

Rule Details: WhoAmI as Parameter

Detects a suspicious process command line that uses whoami as first parameter (as e.g. used by EfsPotato).

Rule ID

`process_creation_commandline_78`

Query

```
{'selection': {'CommandLine|contains': '.exe whoami'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e9142d84-fbe0-401d-ac50-3e519fb00c89

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0007, T1033

References

- https://twitter.com/blackarrowsec/status/1463805700602224645?s=12

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/11/29	high	• Unknown

Rule Details: Powershell Inline Execution From A File

Detects inline execution of PowerShell code from a file.

Rule ID

`process_creation_commandline_79`

Query

```
{'selection_exec': {'CommandLine|contains': ['iex ', 'Invoke-Expression ', 'Invoke-Command ', 'icm ']}, 'selection_read': {'CommandLine|contains': ['cat ', 'get-content ', 'type ']}, 'selection_raw': {'CommandLine|contains': ' -raw'}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ee218c12-627a-4d27-9e30-d6fb2fe22ed2

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=50

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/25	medium	• Unknown

Rule Details: Base64 Encoded PowerShell Command Detected

Detects usage of the "FromBase64String" function in the commandline which is used to decode a base64 encoded string.

Rule ID

`process_creation_commandline_80`

Query

```
{'selection': {'CommandLine|contains': '::FromBase64String('}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e32d4572-9826-4738-b651-95fa63747e8a

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027, T1140

References

- https://gist.github.com/Neo23x0/6af876ee72b51676c82a2db8d2cd3639

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/01/29	high	• Administrative script libraries

Rule Details: CL_Mutexverifiers.ps1 Proxy Execution

Detects the use of a Microsoft signed script to execute commands.

Rule ID

`process_creation_commandline_81`

Query

```
{'selection': {'CommandLine|contains|all': ['\\CL_Mutexverifiers.ps1', 'runAfterCancelProcess ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,1e0e1a81-e79b-44bc-935b-ddb9c8006b3d

Author: Nasreddine Bencherchali (Nextron Systems), oscd.community, Natalia Shornikova, frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1216

References

- https://lolbas-project.github.io/lolbas/Scripts/CL_mutexverifiers/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/05/21	medium	• Unknown

Rule Details: Suspicious X509Enrollment - Process Creation

Detect use of X509Enrollment.

Rule ID

`process_creation_commandline_82`

Query


```
{'selection': {'CommandLine|contains': ['X509Enrollment.CBinaryConverter', '884e2002-217d-11da-b2a4-000e7bbb2b09']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,114de787-4eb2-48cc-abdb-c0b449f93ea4

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=42
- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=41
- https://learn.microsoft.com/en-us/dotnet/api/microsoft.hpc.scheduler.store.cx509enrollmentwebclassfactoryclass?view=hpc-sdk-5.1.6115

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/23	medium	• Legitimate administrative script

Rule Details: Suspicious Regsvr32 HTTP IP Pattern

Detects a certain command line flag combination used by regsvr32 when used to download and register a DLL from a remote address which uses HTTP (not HTTPS) and a IP address and not FQDN.

Rule ID

`process_creation_commandline_83`

Query


```
{'selection_flags': {'CommandLine|contains|all': [' /s', ' /u']}, 'selection_ip': {'CommandLine|contains': [' /i:http://1', ' /i:http://2', ' /i:http://3', ' /i:http://4', ' /i:http://5', ' /i:http://6', ' /i:http://7', ' /i:http://8', ' /i:http://9', ' /i:https://1', ' /i:https://2', ' /i:https://3', ' /i:https://4', ' /i:https://5', ' /i:https://6', ' /i:https://7', ' /i:https://8', ' /i:https://9']}, 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,2dd2c217-bf68-437a-b57c-fe9fd01d5de8

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.010

References

- https://twitter.com/mrd0x/status/1461041276514623491c19-ps
- https://twitter.com/tccontre18/status/1480950986650832903

Severity

74

Suppression Logic Based On

- computer_name

- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/01/11	high	• FQDNs that start with a number

Rule Details: Rundll32 Without Parameters

Detects rundll32 execution without parameters as observed when running Metasploit windows/smb/psexec exploit module.

Rule ID

`process_creation_commandline_84`

Query

```
{'selection': {'CommandLine': 'rundll32.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,5bb68627-3198-40ca-b458-49f973db8752

Author: Bartlomiej Czyz, Relativity

Tactics, Techniques, and Procedures

TA0002, T1569.002, T1059.003, TA0008, T1021.002, T1570

References

- https://bczyz1.github.io/2021/01/30/psexec.html

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/01/31	high	• Unknown

Rule Details: Suspicious Ntdll Pipe Redirection

Detects command that type the content of ntdll.dll to a different file or a pipe in order to evade AV / EDR detection.

Rule ID

process_creation_commandline

Query

{'selection': {'CommandLine|contains': ['type %windir%\\system32\\ntdll.dll', 'type %systemroot%\\system32\\ntdll.dll', 'type c:\\windows\\system32\\ntdll.dll', '\\ntdll.dll > \\\\.\\pipe\\']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,bbc865e4-7fcd-45a6-8ff1-95ced28ec5b2

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/05	high	• Unknown

Rule Details: Raccine Uninstall

Detects commands that indicate a Raccine removal from an end system. Raccine is a free ransomware protection tool.

Rule ID

process_creation_commandline_86

Query

{'selection1': {'CommandLine|contains|all': ['taskkill ', 'RaccineSettings.exe']}, 'selection2': {'CommandLine|contains|all': ['reg.exe', 'delete', 'Raccine Tray']}, 'selection3': {'CommandLine|contains|all': ['schtasks', '/DELETE', 'Raccine Rules Updater']}, 'condition': '1 of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,a31eeaed-3fd5-478e-a8ba-e62c6b3f9ecc

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://github.com/Neo23x0/Raccine

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/01/21	high	• Legitimate deinstallation by administrative staff

Rule Details: REGISTER_APP.VBS Proxy Execution

Detects the use of a Microsoft signed script 'REGISTER_APP.VBS' to register a VSS/VDS Provider as a COM+ application.

Rule ID

`process_creation_commandline_88`

Query

```
{'selection': {'CommandLine|contains|all': ['\\register_app.vbs', '-register']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,1c8774a0-44d4-4db0-91f8-e792359c70bd

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218

References

- https://twitter.com/sblmsrsn/status/1456613494783160325?s=20

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/19	medium	• Legitimate usage of the script. Always investigate what's being registered to confirm if it's benign

Rule Details: PowerShell Get-Process LSASS

Detects a "Get-Process" cmdlet and it's aliases on lsass process, which is in almost all cases a sign of malicious activity.

Rule ID

`process_creation_commandline_89`

Query

```
{'selection': {'CommandLine|contains': ['Get-
Process lsas', 'ps lsas', 'gps lsas']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b2815d0d-7481-4bf0-9b6c-a4c48a94b349

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1552.004

References

- https://twitter.com/PythonResponder/status/1385064506049630211

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/04/23	high	• Unknown

Rule Details: Raspberry Robin Dot Ending File

Detects commandline containing reference to files ending with a "." This scheme has been seen used by raspberry-robin.

Rule ID

`process_creation_commandline_90`

Query

```
{'selection': {'CommandLine|re': '\\\\([a-zA-Z0-9]{1,32})\\.([a-zA-Z0-9]{1,6})\\.(\\s*(["\'])|(\\s+[^a-zA-Z0-9\\s.]))'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,a35c97c8-d9c4-4c89-a3e7-533dc0bcb73a

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://www.microsoft.com/en-us/security/blog/2022/10/27/raspberry-robin-worm-part-of-larger-ecosystem-facilitating-pre-ransomware-activity/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/28	high	• Unknown

Rule Details: LockerGoga Ransomware

Detects LockerGoga Ransomware command line.

Rule ID

`process_creation_commandline_91`

Query

```
{'selection': {'CommandLine|contains': '-i SM-tgytutrc -s'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,74db3488-fd28-480a-95aa-b7af626de068

Author: Vasiliy Burov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0040, T1486

References

- https://medium.com/@malwaredancer/lockergoga-input-arguments-ipc-communication-and-others-bd4e5a7ba80a
- https://blog.f-secure.com/analysis-of-lockergoga-ransomware/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2020/10/18	critical	• Unlikely

Rule Details: Write Protect For Storage Disabled

Looks for changes to registry to disable any write-protect property for storage devices. This could be a precursor to a ransomware attack and has been an observed technique used by cypherpunk group.

Rule ID

`process_creation_commandline_92`

Query

```
{'selection': {'CommandLine|contains|all': ['reg add', '\\system\\currentcontrolset\\control', 'write protection', '0'], 'CommandLine|contains': ['storage', 'storagedevicepolicies']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,75f7a0e2-7154-4c4d-9eae-5cdb4e0a5c13

Author: Sreeman

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/06/11	medium	• Unknown

Rule Details: Audio Capture via PowerShell

Detects audio capture via PowerShell Cmdlet.

Rule ID

```
process_creation_commandline_93
```

Query

```
{'selection': {'CommandLine|contains': 'WindowsAudioDevice-Powershell-Cmdlet'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,932fb0d8-692b-4b0f-a26e-5643a50fe7d6

Author: E.M. Anhaus (originally Atomic Blue Detections, Endgame), oscd.community, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1123

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1123/T1123.md
- https://eqllib.readthedocs.io/en/latest/analytics/ab7a6ef4-0983-4275-a4f1-5c6bd3c31c23.html

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	medium	• Legitimate audio capture by legitimate user.

Rule Details: Potential Suspicious Windows Feature Enabled - ProcCreation

Detects usage of the built-in PowerShell cmdlet "Enable-WindowsOptionalFeature" used as a Deployment Image Servicing and Management tool. Similar to DISM.exe, this cmdlet is used to enumerate, install, uninstall, configure, and update features and packages in Windows images.

Rule ID

`process_creation_commandline_94`

Query

```
{'selection_cmd': {'CommandLine|contains|all': ['Enable-WindowsOptionalFeature', '-Online', '-
FeatureName']}, 'selection_feature': {'CommandLine|contains': ['TelnetServer', 'Internet-Explorer-Optional-amd64', 'TFTP', 'SMB1Protocol', 'Client-ProjFS', 'Microsoft-Windows-Subsystem-Linux']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c740d4cf-a1e9-41de-bb16-8a46a4f57918

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://docs.microsoft.com/en-us/powershell/module/dism/enable-windowsoptionalfeature?view=windowsserver2022-ps
- https://learn.microsoft.com/en-us/windows/win32/projfs/enabling-windows-projected-file-system
- https://learn.microsoft.com/en-us/windows/wsl/install-on-server

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/29	medium	• Unknown

Rule Details: Reg Disable Security Service

Detects a suspicious reg.exe invocation that looks as if it would disable an important security service.

Rule ID

`process_creation_commandline_96`

Query

```
{'selection_reg_add': {'CommandLine|contains|all': ['reg', 'add']}, 'selection_cli_reg_start': {'CommandLine|contains|all': [' /d 4', ' /v Start'], 'CommandLine|contains': ['\\Sense', '\\WinDefend', '\\MsMpSvc', '\\NisSrv', '\\WdBoot', '\\WdNisDrv', '\\WdNisSvc', '\\wscsvc', '\\SecurityHealthService', '\\wuauserv', '\\UsoSvc', '\\WdFilter', '\\AppIDSvc']}, 'selection_cli_reg_disable_defender': {'CommandLine|contains|all': [' /d 1', 'Windows Defender'], 'CommandLine|contains': ['DisableIOAVProtection', 'DisableOnAccessProtection', 'DisableRoutinelyTakingAction', 'DisableScanOnRealtimeEnable', 'DisableBlockAtFirstSeen', 'DisableBehaviorMonitoring', 'DisableEnhancedNotifications', 'DisableAntiSpyware', 'DisableAntiSpywareRealtimeProtection', 'DisableConfig', 'DisablePrivacyMode', 'SignatureDisableUpdateOnStartupWithoutEngine', 'DisableArchiveScanning', 'DisableIntrusionPreventionSystem', 'DisableScriptScanning']}, 'condition': 'selection_reg_add and 1 of selection_cli_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process cre n

Rule Source

SigmaHQ,5e95028c-5229-4214-afae-d653d573d0ec

Author: Florian Roth (Nextron Systems), John Lambert (idea), elhoim

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://twitter.com/JohnLaTwC/status/1415295021041979392
- https://github.com/gordonbay/Windows-On-Reins/blob/e587ac7a0407847865926d575e3c46f68cf7c68d/wor.ps1
- https://vms.drweb.fr/virus/?i=24144899
- https://bidouillesecurity.com/disable-windows-defender-in-powershell/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/07/14	high	• Unknown • Other security solution installers

Rule Details: Serv-U Exploitation CVE-2021-35211 by DEV-0322

Detects patterns as noticed in exploitation of Serv-U CVE-2021-35211 vulnerability by threat group DEV-0322.

Rule ID

`process_creation_commandline_97`

Query

```
{'selection_whoami': {'CommandLine|contains': 'whoami'}, 'selection_cmd_1': {'Command
Line|contains': ['./Client/Common/', '.\\Client\\Common\\']}, 'selection_cmd_2': {'Co
mmandLine|contains': 'C:\\Windows\\Temp\\Serv-
U.bat'}, 'condition': 'selection_whoami and 1 of selection_cmd*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,75578840-9526-4b2a-9462-af469a45e767

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1136.001

References

- https://www.microsoft.com/security/blog/2021/07/13/microsoft-discovers-threat-actor-targeting-solarwinds-serv-u-software-with-0-day-exploit/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/14	critical	• Unlikely

Rule Details: Suspicious Debugger Registration Cmdline

Detects the registration of a debugger for a program that is available in the logon screen (sticky key backdoor).

Rule ID

`process_creation_commandline_98`

Query

```
{'selection1': {'CommandLine|contains': '\\CurrentVersion\\Image File Execution Options\\'}, 'selection2': {'CommandLine|contains': ['sethc.exe', 'utilman.exe', 'osk.exe', 'magnify.exe', 'narrator.exe', 'displayswitch.exe', 'atbroker.exe', 'HelpPane.exe']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ae215552-081e-44c7-805f-be16f975c8a2

Author: Florian Roth (Nextron Systems), oscd.community, Jonhnathan Ribeiro

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1546.008

References

- https://blogs.technet.microsoft.com/jonathantrull/2016/10/03/detecting-sticky-key-backdoors/
- https://bazaar.abuse.ch/sample/6f3aa9362d72e806490a8abce245331030d1ab5ac77e400dd475748236a6cc81/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/09/06	high	• Unknown

Rule Details: CrackMapExec Command Execution

Detect various execution methods of the CrackMapExec pentesting framework.

Rule ID

`process_creation_commandline_99`

Query

```
{'selection': {'CommandLine|endswith': ['cmd.exe /Q /c * 1> \\\\*\\*\\* 2>&1', 'cmd.exe /C * > \\\\*\\*\\* 2>&1', 'cmd.exe /C * > *\\Temp\\* 2>&1'], 'CommandLine|contains': ['powershell.exe -exec bypass -noni -nop -w 1 -C "', 'powershell.exe -noni -nop -w 1 -enc ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,058f4380-962d-40a5-afce-50207d36d7e2

Author: Thomas Patzke

Tactics, Techniques, and Procedures

TA0002, T1047, T1059, TA0003, T1053

References

- https://github.com/byt3bl33d3r/CrackMapExec

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2020/05/22	high	• Unknown

Rule Details: DevInit Lolbin Download

Detects a certain command line flag combination used by devinit.exe lolbin to download arbitrary MSI packages on a Windows system.

Rule ID

`process_creation_commandline_100`

Query

```
{'selection': {'CommandLine|contains|all': [' -t msi-install ', ' -
i http']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,90d50722-0483-4065-8e35-57efaadd354d

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218

References

- https://twitter.com/mrd0x/status/1460815932402679809

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/11	high	• Unknown

Rule Details: Sticky-Key Backdoor Copy Cmd.exe

By replacing the sticky keys executable with the local admins CMD executable, an attacker is able to access a privileged windows console session without authenticating to the system. When the sticky keys are "activated" the privilleged shell is launched.

Rule ID

`process_creation_commandline_101`

Query

```
{'selection': {'CommandLine': 'copy /y C:\\windows\\system32\\cmd.exe C:\\windows\\system32\\sethc.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,1070db9a-3e5d-412e-8e7b-7183b616e1b3

Author: Sreeman

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1546.008

References

- https://www.fireeye.com/blog/threat-research/2017/03/apt29_domain_frontin.html
- https://www.clearskysec.com/wp-content/uploads/2020/02/ClearSky-Fox-Kitten-Campaign-v1.pdf

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/02/18	medium	• Unknown

Rule Details: Suspicious Use of Procdump on LSASS

Detects suspicious uses of the SysInternals Procdump utility by using a special command line parameter in combination with the lsass.exe process. This way we're also able to catch cases in which the attacker has renamed the procdump executable.

Rule ID

process_creation_commandline_102

Query



```
{'selection1': {'CommandLine|contains': [' -
ma ', ' /ma ']}, 'selection2': {'CommandLine|contains': ' ls'}, 'condition': 'all of
selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,5afee48e-67dd-4e03-a783-f74259dcf998

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1036, TA0006, T1003.001

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2018/10/30	high	• Unlikely, because no one should dump an lsass process memory • Another tool that uses the command line switches of Procdump

Rule Details: Suspicious Rundll32 Activity Invoking Sys File

Detects suspicious process related to rundll32 based on command line that includes a *.sys file as seen being used by UNC2452.

Rule ID

process_creation_commandline_103

Query

```
{'selection1': {'CommandLine|contains': 'rundll32.exe'}, 'selection2': {'CommandLine|
contains': ['.sys,', '.sys ']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,731231b9-0b5d-4219-94dd-abb6959aa7ea

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.011

References

- https://www.microsoft.com/security/blog/2021/03/04/goldmax-goldfinder-sibot-analyzing-nobelium-malware/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/03/05	high	• Unknown

Rule Details: ETW Logging Tamper In .NET Processes

Detects changes to environment variables related to ETW logging. This could indicate potential adversaries stopping ETW providers recording loaded .NET assemblies.

Rule ID

`process_creation_commandline_104`

Query

```
{'selection': {'CommandLine|contains': ['COMPlus_ETWEnabled', 'COMPlus_ETWFlags']}, '
condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,41421f44-58f9-455d-838a-c398859841d4

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562

References

- https://twitter.com/_xpn_/status/1268712093928378368
- https://github.com/dotnet/runtime/blob/ee2355c801d892f2894b0f7b14a20e6cc50e0e54/docs/design/coreclr/jit/viewing-jit-dumps.md#setting-configuration-variables
- https://github.com/dotnet/runtime/blob/f62e93416a1799aecc6b0947adad55a0d9870732/src/coreclr/src/inc/clrconfigvalues.h#L35-L38
- https://github.com/dotnet/runtime/blob/7abe42dc1123722ed385218268bb9fe04556e3d3/src/coreclr/src/inc/clrconfig.h#L33-L39
- http://managed670.rssing.com/chan-5590147/all_p1.html
- https://github.com/dotnet/runtime/blob/4f9ae42d861fcb4be2fcd5d3d55d5f227d30e723/docs/coding-guidelines/clr-jit-coding-conventions.md#1412-disabling-code
- https://i.blackhat.com/EU-21/Wednesday/EU-21-Teodorescu-Veni-No-Vidi-No-Vici-Attacks-On-ETW-Blind-EDRs.pdf

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/02	high	• Unlikely

Rule Details: Suspicious WMIC Execution - ProcessCallCreate

Detects WMIC executing "process call create" with suspicious calls to processes such as "rundll32", "regsrv32"...etc.

Rule ID

`process_creation_commandline_105`

Query


```
{'selection': {'CommandLine|contains|all': ['process ', 'call ', 'create '], 'CommandLine|contains': ['rundll32', 'bitsadmin', 'regsvr32', 'cmd.exe /c ', 'cmd.exe /k ', 'cmd.exe /r ', 'cmd /c ', 'cmd /k ', 'cmd /r ', 'powershell', 'pwsh', 'certutil', 'cscript', 'wscript', 'mshta', '\\Users\\Public\\', '\\Windows\\Temp\\', '\\AppData\\Local\\', '%temp%', '%tmp%', '%ProgramData%', '%appdata%', '%comspec%', '%localappdata%']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,3c89a1e8-0fba-449e-[illegible]b-8409d6267ec8

Author: Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1047, T1059.003

References

- https://thedfirreport.com/2020/10/08/ryuks-return/
- https://symantec-enterprise-blogs.security.com/blogs/threat-intelligence/ransomware-hive-conti-avoslocker

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/12	high	• Unknown

Rule Details: Potential APT-C-12 BlueMushroom DLL Load Activity Via Regsvr32

Detects potential BlueMushroom DLL loading activity via regsvr32 from AppData Local.

Rule ID

`process_creation_commandline_106`

Query

```
{'selection': {'CommandLine|contains|all': ['regsvr32', '\\AppData\\Local\\', '.dll',
 ',DllEntry']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,bd70d3f8-e60e-4d25-89f0-0b5a9cff20e0

Author: Florian Roth (Nextron Systems), Tim Shelton, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.010

References

- https://pbs.twimg.com/media/EF3yLGoWkAEGeLa?format=jpg

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/02	medium	• Unknown

Rule Details: Mshtml DLL RunHTMLApplication Abuse

Detects suspicious command line using the "mshtml.dll" RunHTMLApplication export to run arbitrary code via different protocol handlers (vbscript, javascript, file, htpp...).

Rule ID

`process_creation_commandline_107`

Query

```
{'selection': {'CommandLine|contains|all': ['\\..\\', 'mshtml', 'RunHTMLApplication']
}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,4782eb5a-a513-4523-a0ac-f3082b26ac5c

Author: Nasreddine Bencherchali (Nextron Systems), Florian Roth (Nextron Systems), Josh Nickels, frack113, Zaw Min Htun (ZETA)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://twitter.com/n1nj4sec/status/1421190238081277959

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/14	high	• Unlikely

Rule Details: Persistence Via TypedPaths - CommandLine

Detects modification addition to the 'TypedPaths' key in the user or admin registry via the commandline. Which might indicate persistence attempt.

Rule ID

`process_creation_commandline_109`

Query

```
{'selection': {'CommandLine|contains': '\\Software\\Microsoft\\Windows\\CurrentVersion\\Explorer\\TypedPaths'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ec88289a-7e1a-4cc3-8d18-bd1f60e4b9ba

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://twitter.com/dez_/status/1560101453150257154
- https://forensafe.com/blogs/typedpaths.html

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/22	medium	• Unknown

Rule Details: UtilityFunctions.ps1 Proxy Dll

Detects the use of a Microsoft signed script executing a managed DLL with PowerShell.

Rule ID

```
process_creation_commandline
```

Query

```
{'selection': {'CommandLine|contains': ['UtilityFunctions.ps1', 'RegSnapin ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,0403d67d-6227-4ea8-8145-4e72db7da120

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1216

References

- https://lolbas-project.github.io/lolbas/Scripts/UtilityFunctions/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/05/28	medium	• Unknown

Rule Details: Unidentified Attacker November 2018

A sigma rule detecting an unidetefied attacker who used phishing emails to target high profile orgs on November 2018. The Actor shares some TTPs with YYTRIUM/APT29 campaign in 2016.

Rule ID

```
process_creation_commandline_111
```

Query

```
{'selection': {'CommandLine|contains': 'cyzfc.dat,', 'CommandLine|endswith': 'PointFunctionCall'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7453575c-a747-40b9-839b-125a0aae324b

Author: Florian Roth (Nextron Systems), @41thexplorer

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.011

References

- https://twitter.com/DrunkBinary/status/1063075530180886529

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2018/11/20	high	N/A

Rule Details: Powershell AMSI Bypass via .NET Reflection

Detects Request to "amsiInitFailed" that can be used to disable AMSI Scanning.

Rule ID

`process_creation_commandline_112`

Query

```
{'selection': {'CommandLine|contains': ['System.Management.Automation.AmsiUtils', 'amsiInitFailed']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,30edb182-aa75-42c0-b0a9-e998bb29067c

Author: Markus Neis, @Kostastsale

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://s3cur3th1ssh1t.github.io/Bypass_AMSI_by_manual_modification/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/08/17	high	• Unlikely

Rule Details: PowerShell SAM Copy

Detects suspicious PowerShell scripts accessing SAM hives.

Rule ID

`process_creation_commandline_113`

Query

```
{'selection_1': {'CommandLine|contains|all': ['\\HarddiskVolumeShadowCopy', 'System32
\\config\\sam']}, 'selection_2': {'CommandLine|contains': ['Copy-
Item', 'cp $_.', 'cpi $_.', 'copy $_.', '.File]::Copy(']}, 'condition': 'all of selec
tion*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,1af57a4b-460a-4738-9034-db68b880c665

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1003.002

References

- https://twitter.com/splinter_code/status/1420546784250769408

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/29	high	• Some rare backup scenarios • PowerShell scripts fixing HiveNightmare / SeriousSAM ACLs

Rule Details: UAC Bypass Using Event Viewer RecentViews

Detects the pattern of UAC Bypass using Event Viewer RecentViews.

Rule ID

`process_creation_commandline_114`

Query

```
{'selection_path': {'CommandLine|contains': ['\\Event Viewer\\RecentViews', '\\EventV
~1\\RecentViews']}, 'selection_redirect': {'CommandLine|contains': '>'}, 'condition':
 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,30fc8de7-d833-40c4-96b6-28319fbc4f6c

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://twitter.com/orange_8361/status/1518970259868626944
- https://lolbas-project.github.io/lolbas/Binaries/Eventvwr/#execute

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/11/22	high	• Unknown

Rule Details: Suspicious Office Token Search Via CLI

Detects possible search for office tokens via CLI by looking for the string "eyJ0eX". This string is used as an anchor to look for the start of the JWT token used by office and similar apps.

Rule ID

`process_creation_commandline_5`

Query

```
{'selection': {'CommandLine|contains': ['eyJ0eXAiOi', ' eyJ0eX', ' "eyJ0eX"', " 'eyJ0eX'"]}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,6d3a3952-6530-44a3-8554-cf17c116c615

Author: Nasreddine Bencherchali (Nextron Systems), kagebunsher

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1528

References

- https://mrd0x.com/stealing-tokens-from-office-applications/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/25	medium	• Legitimate command-lines containing the string mentioned in the command-line

Rule Details: Change Default File Association To Executable

Detects when a program changes the default file association of any extension to an executable.

Rule ID

`process_creation_commandline_116`

Query

```
{'selection': {'CommandLine|contains|all': ['cmd', 'assoc ', 'exefile'], 'CommandLine|contains': [' /c ', ' /r ', ' /k ']}, 'filter': {'CommandLine|contains': '.exe=exefile'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ae6f14e6-14de-45b0-9f44-c0986f50dc89

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1546.001

References

- https://docs.microsoft.com/en-us/windows-server/administration/windows-commands/assoc

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/06/28	high	• Unknown

Rule Details: Conti Backup Database

Detects a command used by conti to dump database.

Rule ID

`process_creation_commandline_118`

Query

```
{'selection_tools': {'CommandLine|contains': ['sqlcmd ', 'sqlcmd.exe']}, 'selection_s
vr': {'CommandLine|contains': ' -
S localhost '}, 'selection_query': {'CommandLine|contains': ['sys.sysprocesses', 'mas
ter.dbo.sysdatabases', 'BACKUP DATABASE']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,2f47f1fd-0901-466e-a770-3b7092834a1b

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1005

References

- https://twitter.com/vxunderground/status/1423336151860002816?s=20
- https://www.virustotal.com/gui/file/03e9b8c2e86d6db450e5eceec057d7e369ee2389b9daecaf06331a95410aa5f8/detection
- https://docs.microsoft.com/en-us/sql/tools/sqlcmd-utility?view=sql-server-ver15

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/16	high	• Unknown

Rule Details: Winnti Pipemon Characteristics

Detects specific process characteristics of Winnti Pipemon malware reported by ESET.

Rule ID

`process_creation_commandline_119`

Query

```
{'selection1': {'CommandLine|contains': 'setup0.exe -
p'}, 'selection2a': {'CommandLine|contains': 'setup.exe'}, 'selection2b': {'CommandLi
ne|endswith': ['-x:0', '-x:1', '-
x:2']}, 'condition': 'selection1 or all of selection2*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,73d70463-75c9-4258-92c6-17500fe972f2

Author: Florian Roth (Nextron Systems), oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1574.002

References

- https://www.welivesecurity.com/2020/05/21/no-game-over-winnti-group/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2020/07/30	critical	• Legitimate setups that use similar flags

Rule Details: Suspicious ZipExec Execution

ZipExec is a Proof-of-Concept (POC) tool to wrap binary-based tools into a password-protected zip file.

Rule ID

`process_creation_commandline_120`

Query

```
{'run': {'CommandLine|contains|all': ['/generic:Microsoft_Windows_Shell_ZipFolder:filename=', '.zip', '/pass:', '/user:']}, 'delete': {'CommandLine|contains|all': ['/delete', 'Microsoft_Windows_Shell_ZipFolder:filename=', '.zip']}, 'condition': 'run or delete'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,90dcf730-1b71-4ae7-9ffc-6fcf62bd0132

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218, T1202

References

- https://twitter.com/SBousseaden/status/1451237393017839616
- https://github.com/Tylous/ZipExec

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/11/07	medium	• Unknown

Rule Details: NirCmd Tool Execution As LOCAL SYSTEM

Detects the use of NirCmd tool for command execution as SYSTEM user.

Rule ID

`process_creation_commandline_121`

Query

```
{'selection': {'CommandLine|contains': ' runassystem '}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,d9047477-0359-48c9-b8c7-792cedcdc9c4

Author: Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1569.002, T1059.003

References

- https://www.nirsoft.net/utils/nircmd.html
- https://www.winhelponline.com/blog/run-program-as-system-localsystem-account-windows/
- https://www.nirsoft.net/utils/nircmd2.html#using

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/24	high	• Legitimate use by administrators

Rule Details: Invoke-Obfuscation Via Use Clip

Detects Obfuscated Powershell via use Clip.exe in Scripts.

Rule ID

`process_creation_commandline_2`

Query

```
{'selection': {'CommandLine|contains|all': ['echo', 'clip', '&&'], 'CommandLine|contains': ['clipboard', 'invoke', 'i`', 'n`', 'v`', 'o`', 'k`', 'e`']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e1561947-b4e3-4a74-9bdd-83baed21bdb5

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/09	high	• Unknown

Rule Details: PowerShell Base64 Encoded Shellcode

Detects Base64 encoded Shellcode.

Rule ID

`process_creation_commandline_123`

Query

```
{'selection': {'CommandLine|contains': ['OiCAAAAYInlM', 'OiJAAAAYInlM']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,2d117e49-e626-4c7c-bd1f-c3c0147774c8

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1027

References

- https://twitter.com/cyb3rops/status/1063072865992523776

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2018/11/17	critical	• Unknown

Rule Details: Ryuk Ransomware

Detects Ryuk ransomware activity.

Rule ID

`process_creation_commandline_124`

Query

```
{'selection': {'CommandLine|contains|all': ['Microsoft\\Windows\\CurrentVersion\\Run'
, 'C:\\users\\Public\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c37510b8-2107-4b78-aa32-72f251e7a844

Author: Florian Roth (Nextron Systems), Vasiliy Burov, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1547.001

References

- https://app.any.run/tasks/d860402c-3ff4-4c1f-b367-0237da714ed1/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2019/12/16	high	• Unlikely

Rule Details: Arbitrary Shell Command Execution Via Settingcontent-Ms

The .SettingContent-ms file type was introduced in Windows 10 and allows a user to create "shortcuts" to various Windows 10 setting pages. These files are simply XML and contain paths to various Windows 10 settings binaries.

Rule ID

`process_creation_commandline_125`

Query

```
{'selection': {'CommandLine|contains': '.SettingContent-ms'}, 'filter': {'CommandLine|contains': 'immersivecontrolpanel'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,24de4f3b-804c-4165-b442-5a06a2302c7e

Author: Sreeman

Tactics, Techniques, and Procedures

TA0001, T1566.001, TA0002, T1204, T1059.003

References

- https://posts.specterops.io/the-tale-of-settingcontent-ms-files-f1ea253e4d39

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/03/13	medium	• Unknown

Rule Details: Base64 Encoded Reflective Assembly Load

Detects base64 encoded .NET reflective loading of Assembly.

Rule ID

`process_creation_commandline_127`

Query


```
{'selection': {'CommandLine|contains': ['WwBSAGUAZgBsAGUAYwB0AGkAbwBuAC4AQQBzAHMAZQBtAGIAbAB5AF0AOgA6AEwAbwBhAGQAKA', 'sAUgBlAGYAbABlAGMAdABpAG8AbgAuAEEAcwBzAGUAbQBiAGwAeQBdADoAOgBMAG8AYQBkACgA', 'bAFIAZQBmAGwAZQBjAHQAaQBvAG4ALgBBAHMAcwBlAG0AYgBsAHkAXQA6ADoATABvAGEAZAAoA', 'AFsAcgBlAGYAbABlAGMAdABpAG8AbgAuAGEAcwBzAGUAbQBiAGwAeQBdADoAOgAoACIATABvAGEAZAAiAC', 'BbAHIAZQBmAGwAZQBjAHQAaQBvAG4ALgBhAHMAcwBlAG0AYgBsAHkAXQA6ADoAKAAiAEwAbwBhAGQAIgAp', 'AWwByAGUAZgBsAGUAYwB0AGkAbwBuAC4AYQBzAHMAZQBtAGIAbAB5AF0AOgA6ACgAIgBMAG8AYQBkACIAK', 'WwBSAGUAZgBsAGUAYwB0AGkAbwBuAC4AQQBzAHMAZQBtAGIAbAB5AF0AOgA6ACgAIgBMAG8AYQBkACIAKQ', 'sAUgBlAGYAbABlAGMAdABpAG8AbgAuAEEAcwBzAGUAbQBiAGwAeQBdADoAOgAoACIATABvAGEAZAAiACkA', 'bAFIAZQBmAGwAZQBjAHQAaQBvAG4ALgBBAHMAcwBlAG0AYgBsAHkAXQA6ADoAKAAiAEwAbwBhAGQAIgApA', 'WwByAGUAZgBsAGUAYwB0AGkAbwBuAC4AYQBzAHMAZQBtAGIAbAB5AF0AOgA6AEwAbwBhAGQAKA', 'sAcgBlAGYAbABlAGMAdABpAG8AbgAuAGEAcwBzAGUAbQBiAGwAeQBdADoAOgBMAG8AYQBkACgA', 'bAHIAZQBmAGwAZQBjAHQAaQBvAG4ALgBhAHMAcwBlAG0AYgBsAHkAXQA6ADoATABvAGEAZAAoA']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,62b7ccc9-23b4-471e-aa15-6da3663c4d59

Author: Christian Burkard (Nextron Systems), pH-T (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/Neo23x0/Raccine/blob/20a569fa21625086433dcce8bb2765d0ea08dcb6/yara/mal_revil.yar
- https://thedfirreport.com/2022/05/09/seo-poisoning-a-gootloader-story/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/01	high	• Unlikely

Rule Details: Suspicious NT Resource Kit Auditpol Usage

Threat actors can use an older version of the auditpol binary available inside the NT resource kit to change audit policy configuration to impair detection capability. This can be carried out by selectively disabling/removing certain audit policies as well as restoring a custom policy owned by the threat actor.

Rule ID

```
process_creation_commandline_128
```

Query

```
{'selection': {'CommandLine|contains': ['/logon:none', '/system:none', '/sam:none', '/privilege:none', '/object:none', '/process:none', '/policy:none']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c6c56ada-612b-42d1-9a29-adad3c5c2c1e

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.002

References

- https://github.com/3CORESec/MAL-CL/tree/master/Descriptors/Windows%202000%20Resource%20Kit%20Tools/AuditPol

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/18	high	• Unknown

Rule Details: Weak or Abused Passwords In CLI

Detects weak passwords or often abused passwords (seen used by threat actors) via the CLI. An example would be a threat actor creating a new user via the net command and providing the password inline.

Rule ID

`process_creation_commandline_129`

Query

```
{'selection': {'CommandLine|contains': ['Asd123.aaaa', 'password123', '123456789', 'P@ssw0rd!']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,91edcfb1-2529-4ac2-9ecc-7617f895c7e4

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://symantec-enterprise-blogs.security.com/blogs/threat-intelligence/espionage-asia-governments
- https://thedfirreport.com/2022/09/26/bumblebee-round-two/
- https://www.microsoft.com/en-us/security/blog/2022/10/25/dev-0832-vice-society-opportunistic-ransomware-campaigns-impacting-us-education-sector/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/14	medium	• Legitimate usage of the passwords by users via commandline (should be discouraged) • Other currently unknown false positives

Rule Details: Suspicious Encoded Obfuscated LOAD String

Detects suspicious base64 encoded and obbfuscated LOAD string often used for reflection.assembly load.

Rule ID

`process_creation_commandline_130`

Query


```
{'selection': {'CommandLine|contains': ['OgA6ACgAIgBMACIAKwAiAG8AYQBkACIAKQ', 'oAOgAoACIATAAiACsAIgBvAGEAZAAiACkA', '6ADoAKAAiAEwAIgArACIAbwBhAGQAIgApA', 'OgA6ACgAIgBMAG8AIgArACIAYQBkACIAKQ', 'oAOgAoACIATABvACIAKwAiAGEAZAAiACkA', '6ADoAKAAiAEwAbwAiACsAIgBhAGQAIgApA', 'OgA6ACgAIgBMAG8AYQAiACsAIgBkACIAKQ', 'oAOgAoACIATABvAGEAIgArACIAZAAiACkA', '6ADoAKAAiAEwAbwBhACIAKwAiAGQAIgApA', 'OgA6ACgAJwBMACcAKwAnAG8AYQBkACcAKQ', 'oAOgAoACcATAAnACsAJwBvAGEAZAAnACkA', '6ADoAKAAnAEwAJwArACcAbwBhAGQAJwApA', 'OgA6ACgAJwBMAG8AJwArACcAYQBkACcAKQ', 'oAOgAoACcATABvACcAKwAnAGEAZAAnACkA', '6ADoAKAAnAEwAbwAnACsAJwBhAGQAJwApA', 'OgA6ACgAJwBMAG8AYQAnACsAJwBkACcAKQ', 'oAOgAoACcATABvAGEAJwArACcAZAAnACkA', '6ADoAKAAnAEwAbwBhACcAKwAnAGQAJwApA']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,9c0295ce-d60d-40bd-bd74-84673b7592b1

Author: pH-T (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/Neo23x0/Raccine/blob/20a569fa21625086433dcce8bb2765d0ea08dcb6/yara/mal_revil.yar
- https://thedfirreport.com/2022/05/09/seo-poisoning-a-gootloader-story/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/01	high	• Unlikely

Rule Details: RunXCmd Tool Execution As System

Detects the use of RunXCmd tool for command execution.

Rule ID

`process_creation_commandline_131`

Query


```
{'selection': {'CommandLine|contains|all': [' /account=system ', '/exec=']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,93199800-b52a-4dec-b762-75212c196542

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1569.002, T1059.003

References

- https://www.d7xtech.com/free-software/runx/
- https://www.winhelponline.com/blog/run-program-as-system-localsystem-account-windows/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/24	high	• Legitimate use by administrators

Rule Details: Base64 Encoded Listing of Shadowcopy

Detects base64 encoded listing Win32_Shadowcopy.

Rule ID

process_creation_commandline_2

Query

{'selection': {'CommandLine|contains': ['VwBpAG4AMwAyAF8AUwBoAGEAZABvAHcAYwBvAHAAeQAgAHwAIABGAG8AcgBFAGEAYwBoAC0ATwBiAGoAZQBjAHQA', 'cAaQBuADMAMgBfAFMAaABhAGQAbwB3AGMAbwBwAHkAIAB8ACAARgBvAHIARQBhAGMAaAAtAE8AYgBqAGUAYwB0A', 'XAGkAbgAzADIAXwBTAGgAYQBkAG8AdwBjAG8AcAB5ACAAfAAgAEYAbwByAEUAYQBjAGgALQBPAGIAagBlAGMAdA']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,47688f1b-9f51-4656-b013-3cc49a166a36

Author: Christian Burkard (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/Neo23x0/Raccine/blob/20a569fa21625086433dcce8bb2765d0ea08dcb6/yara/mal_revil.yar

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/03/01	high	• Unlikely

Rule Details: MERCURY Command Line Patterns

Detects suspicious command line patterns as seen being used by MERCURY threat actor.

Rule ID

process_creation_commandline_133

Query

{'selection_base': {'CommandLine|contains|all': ['-exec bypass -w 1 -enc', 'UwB0AGEAcgB0AC0ASgBvAGIAIAAtAFMAYwByAGkAcAB0AEIAbABvAGMAaw']}, 'condition': 'a

ll of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,a62298a3-1fe0-422f-9a68-ffbcbc5a123d

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://www.microsoft.com/security/blog/2022/08/25/mercury-leveraging-log4j-2-vulnerabilities-in-unpatched-systems-to-target-israeli-organizations/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/26	high	• Unknown

Rule Details: DTRACK Process Creation

Detects specific process parameters as seen in DTRACK infections.

Rule ID

process_creation_commandline_134

Query

{'selection': {'CommandLine|contains': ' echo EEEE > '}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f1531fa4-5b84-4342-8f68-9cf3fdbd83d4

Author: Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0040, T1490

References

- https://securelist.com/my-name-is-dtrack/93338/
- https://app.any.run/tasks/4bc9860d-ab51-4077-9e09-59ad346b92fd/
- https://app.any.run/tasks/ce4deab5-3263-494f-93e3-afb2b9d79f14/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2019/10/30	critical	• Unlikely

Rule Details: Suspicious Netsh Discovery Command

Adversaries may look for details about the network configuration and settings of systems they access or through information discovery of remote systems.

Rule ID

`process_creation_commandline_135`

Query

```
{'selection': {'CommandLine|contains|all': ['netsh ', 'show ', 'firewall '], 'CommandLine|contains': ['config ', 'state ', 'rule ', 'name=all']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,0e4164da-94bc-450d-a7be-a4b176179f1f

Author: frack113, Christopher Peacock '@securepeacock', SCYTHE '@scythe_io'

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0007, T1016

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1016/T1016.md#atomic-test-2---list-windows-firewall-rules

Severity

24

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/07	low	• Administrative activity

Rule Details: F-Secure C3 Load by Rundll32

F-Secure C3 produces DLLs with a default exported StartNodeRelay function.

Rule ID

`process_creation_commandline_136`

Query

```
{'selection': {'CommandLine|contains|all': ['rundll32.exe', '.dll', 'StartNodeRelay']
}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b18c9d4c-fac9-4708-bd06-dd5bfacf200f

Author: Alfie Champion (ajpc500)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.011

References

- https://github.com/FSecureLABS/C3/blob/11a081fd3be2aaf2a879f6b6e9a96ecdd24966ef/Src/NodeRelayDll/NodeRelayDll.cpp#L12

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/06/02	critical	• Unknown

Rule Details: Suspicious RunAs-Like Flag Combination

Detects suspicious command line flags that let the user set a target user and command as e.g. seen in PsExec-like tools.

Rule ID

`process_creation_commandline_137`

Query

```
{'selection_user': {'CommandLine|contains': [' -u system ', ' --user system ', ' -
u NT', ' -u "NT', " -u 'NT", ' --system ', ' -
u administrator ']}, 'selection_command': {'CommandLine|contains': [' -c cmd', ' -
c "cmd', ' -c powershell', ' -c "powershell', ' --command cmd', ' --
command powershell', ' -c whoami', ' -c wscript', ' -
c cscript']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,50d66fb0-03f8-4da0-8add-84e77d12a020

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://www.trendmicro.com/en_us/research/22/k/hack-the-real-box-apt41-new-subgroup-earth-longzhi.html

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/11/11	medium	• Unknown

Rule Details: Stop Or Remove Antivirus Service

Detects usage of 'Stop-Service' or 'Remove-Service' powershell cmdlet to disable AV services. Adversaries may disable security tools to avoid possible detection of their tools and activities by stopping antivirus service.

Rule ID

`process_creation_commandline_138`

Query

```
{'selection_action': {'CommandLine|contains': ['Stop-Service ', 'Remove-Service ']}, 'selection_product': {'CommandLine|contains': [' McAfeeDLPAgentService', ' Trend Micro Deep Security Manager', ' TMBMServer', 'Sophos', 'Symantec']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,6783aa9e-0dc3-49d4-a94a-8b39c5fd700b

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1562.001/T1562.001.md
- https://research.nccgroup.com/2022/08/19/back-in-black-unlocking-a-lockbit-3-0-ransomware-attack/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/07/07	high	• Unknown

Rule Details: Adwind RAT / JRAT

Detects javaw.exe in AppData folder as used by Adwind / JRAT.

Rule ID

process_creation_commandline_139

Query



{'selection': [{'CommandLine|contains|all': ['\\AppData\\Roaming\\Oracle', '\\java', '.exe ']}, {'CommandLine|contains|all': ['cscript.exe', 'Retrive', '.vbs ']}], 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,1fac1481-2dbc-48b2-9096-753c49b4ec71

Author: Florian Roth (Nextron Systems), Tom Uelтschi, Jonhnathan Ribeiro, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://www.hybrid-analysis.com/sample/ba86fa0d4b6af2db0656a88b1dd29f36fe362473ae8ad04255c4e52f214a541c?environmentId=100
- https://www.first.org/resources/papers/conf2017/Advanced-Incident-Detection-and-Threat-Hunting-using-Sysmon-and-Splunk.pdf

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/11/10	high	N/A

Rule Details: Suspicious AdvancedRun Runas Priv User

Detects the execution of AdvancedRun utility in the context of the TrustedInstaller, SYSTEM, Local Service or Network Service accounts.

Rule ID

process_creation_commandline_140

Query

{'selection': {'CommandLine|contains': ['/EXEFilename', '/CommandLine']}, 'selection_runas': [{'CommandLine|contains': [' /RunAs 8 ', ' /RunAs 4 ', ' /RunAs 10 ', ' /RunA

s 11 ']}, {'CommandLine|endswith': ['/RunAs 8', '/RunAs 4', '/RunAs 10', '/RunAs 11']}], 'condition': 'all of sel*ion*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,fa00b701-44c6-4679-994d-5a18afa8a707

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://twitter.com/splinter_code/status/1483815103279603714
- https://medium.com/s2wblog/analysis-of-destructive-malware-whispergate-targeting-ukraine-9d5d158f19f3
- https://www.winhelponline.com/blog/run-program-as-system-localsystem-account-windows/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/01/20	high	• Unknown

Rule Details: ShimCache Flush

Detects actions that clear the local ShimCache and remove forensic evidence.

Rule ID

`process_creation_commandline_141`

Query

{'selection1a': {'CommandLine|contains|all': ['rundll32', 'apphelp.dll']}, 'selection1b': {'CommandLine|contains': ['ShimFlushCache', '#250']}, 'selection2a': {'CommandLine|contains|all': ['rundll32', 'kernel32.dll']}, 'selection2b': {'CommandLine|contains': ['BaseFlushAppcompatCache', '#46']}, 'condition': '(selection1a and selection1b) or (selection2a and selection2b)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b0524451-19af-4efa-a46f-562a977f792e

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1112

References

- https://medium.com/@blueteamops/shimcache-flush-89daff28d15e

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2021/02/01	high	• Unknown

Rule Details: Sliver C2 Implant Activity Pattern

Detects process activity patterns as seen being used by Sliver C2 framework implants.

Rule ID

```
process_creation_commandline_142
```

Query

```
{'selection_cmdline': {'CommandLine|contains': '-NoExit -
Command [Console]::OutputEncoding=
[Text.UTF8Encoding]::UTF8'}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,42333b2c-b425-441c-b70e-99404a17170f

Author: Nasreddine Bencherchali (Nextron Systems), Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://github.com/BishopFox/sliver/blob/79f2d48fcdfc2bee4713b78d431ea4b27f733f30/implant/sliver/shell/shell_windows.go#L36
- https://www.microsoft.com/security/blog/2022/08/24/looking-for-the-sliver-lining-hunting-for-emerging-command-and-control-frameworks/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/25	critical	• Unlikely

Rule Details: Disabled IE Security Features

Detects command lines that indicate unwanted modifications to registry keys that disable important Internet Explorer security features.

Rule ID

`process_creation_commandline_143`

Query

```
{'selection1': {'CommandLine|contains|all': [' -name IEHarden ', ' -
value 0 ']}, 'selection2': {'CommandLine|contains|all': [' -name DEPOff ', ' -
value 1 ']}, 'selection3': {'CommandLine|contains|all': [' -
name DisableFirstRunCustomize ', ' -value 2 ']}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,fb50eb7a-5ab1-43ae-bcc9-091818cb8424

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://unit42.paloaltonetworks.com/operation-ke3chang-resurfaces-with-new-tidepool-malware/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/06/19	high	• Unknown, maybe some security software installer disables these features temporarily

Rule Details: Invoke-Obfuscation RUNDLL LAUNCHER

Detects Obfuscated Powershell via RUNDLL LAUNCHER.

Rule ID

`process_creation_commandline_144`

Query

```
{'selection': {'CommandLine|contains|all': ['rundll32.exe', 'shell32.dll', 'shellexec_rundll', 'powershell']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,056a7ee1-4853-4e67-86a0-3fd9ceed7555

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/18	medium	• Unknown

Rule Details: Tasks Folder Evasion

The Tasks folder in system32 and syswow64 are globally writable paths. Adversaries can take advantage of this and load or influence any script hosts or ANY .NET Application in Tasks to load and execute a custom assembly into cscript, wscript, regsvr32, mshta, eventvwr.

Rule ID

`process_creation_commandline_145`

Query


```
{'selection1': {'CommandLine|contains': ['echo ', 'copy ', 'type ', 'file createnew']
}, 'selection2': {'CommandLine|contains': [' C:\\Windows\\System32\\Tasks\\', ' C:\\W
indows\\SysWow64\\Tasks\\']}, 'condition': 'all of selection*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,cc4e02ba-9c06-48e2-b09e-2500cace9ae0

Author: Sreeman

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1574.002

References

- https://twitter.com/subTee/status/1216465628946563073
- https://gist.github.com/am0nsec/8378da08f848424e4ab0cc5b317fdd26

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/01/13	high	• Unknown

Rule Details: Sofacy Trojan Loader Activity

Detects Trojan loader activity as used by APT28.

Rule ID

```
process_creation_commandline_6
```

Query

```
{'selection1': {'CommandLine|contains|all': ['rundll32.exe', '%APPDATA%\\']}, 'selection2': [{'CommandLine|contains': '.dat",'}, {'CommandLine|endswith': ['.dll",#1', '.dll #1', '.dll" #1']}], 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ba778144-5e3d-40cf-8af9-e28fb1df1e20

Author: Florian Roth (Nextron Systems), Jonhnathan Ribeiro, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218.011

References

- https://researchcenter.paloaltonetworks.com/2018/02/unit42-sofacy-attacks-multiple-government-entities/
- https://twitter.com/ClearskySec/status/960924755355369472

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/03/01	high	• Unknown

Rule Details: Suspicious Commandline Escape

Detects suspicious process that use escape characters.

Rule ID

```
process_creation_commandline_147
```

Query

```
{'selection': {'CommandLine|contains': ['h^t^t^p', 'h"t"t"p']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f0cdd048-82dc-4f7a-8a7a-b87a52b6d0fd

Author: juju4

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1140

References

- https://twitter.com/vysecurity/status/885545634958385153
- https://twitter.com/Hexacorn/status/885553465417756673
- https://twitter.com/Hexacorn/status/885570278637678592
- https://www.fireeye.com/blog/threat-research/2017/06/obfuscation-in-the-wild.html
- http://www.windowsinspired.com/understanding-the-command-line-string-and-arguments-received-by-a-windows-program/

Severity

24

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/12/11	low	• False positives depend on scripts and administrative tools used in the monitored environment

Rule Details: Suspicious Rundll32 Invoking Inline VBScript

Detects suspicious process related to rundll32 based on command line that invokes inline VBScript as seen being used by UNC2452.

Rule ID

```
process_creation_commandline_148
```

Query

```
{'selection': {'CommandLine|contains|all': ['rundll32.exe', 'Execute', 'RegRead', 'window.close']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,1cc50f3f-1fc8-4acf-b2e9-6f172e1fdebd

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1055

References

- https://www.microsoft.com/security/blog/2021/03/04/goldmax-goldfinder-sibot-analyzing-nobelium-malware/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/03/05	high	• Unknown

Rule Details: Disabled Volume Snapshots

Detects commands that temporarily turn off Volume Snapshots.

Rule ID

`process_creation_commandline_149`

Query

```
{'selection': {'CommandLine|contains|all': ['reg', ' add ', '\\Services\\VSS\\Diag', '/d Disabled']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,dee4af55-1f22-4e1d-a9d2-4bdc7ecb472a

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://twitter.com/0gtv/status/1354766164166115331

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/01/28	high	• Legitimate administration

Rule Details: PowerShell Get-Clipboard Cmdlet Via CLI

Detects usage of the 'Get-Clipboard' cmdlet via CLI.

Rule ID

`process_creation_commandline_150`

Query

```
{'selection': {'CommandLine|contains': 'Get-Clipboard'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b9aeac14-2ffd-4ad3-b967-1354a4e628c3

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1115

References

- https://github.com/OTRF/detection-hackathon-apt29/issues/16

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/02	medium	• Unknown

Rule Details: Suspicious Reg Add BitLocker

Detects suspicious addition to BitLocker related registry keys via the reg.exe utility.

Rule ID

`process_creation_commandline_151`

Query


```
{'selection': {'CommandLine|contains|all': ['REG', 'ADD', '\\SOFTWARE\\Policies\\Microsoft\\FVE', '/v', '/f'], 'CommandLine|contains': ['EnableBDEWithNoTPM', 'UseAdvancedStartup', 'UseTPM', 'UseTPMKey', 'UseTPMKeyPIN', 'RecoveryKeyMessageSource', 'UseTPMPIN', 'RecoveryKeyMessage']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,0e0255bf-2548-47b8-9582-c0955c9283f5

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0040, T1486

References

- https://thedfirreport.com/2021/11/15/exchange-exploit-leads-to-domain-wide-ransomware/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/11/15	high	• Unlikely

Rule Details: Suspicious Reconnaissance Activity Using Get-LocalGroupMember Cmdlet

Detects suspicious reconnaissance command line activity on Windows systems using the PowerShell Get-LocalGroupMember Cmdlet.

Rule ID

`process_creation_commandline_2`

Query

```
{'selection_cmdlet': {'CommandLine|contains': 'Get-
LocalGroupMember '}, 'selection_group': {'CommandLine|contains': ['domain admins', '
administrator', ' administrateur', 'enterprise admins', 'Exchange Trusted Subsystem',
 'Remote Desktop Users', 'Utilisateurs du Bureau à distance', 'Usuarios de escritorio
 remoto']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c8a180d6-47a3-4345-a609-53f9c3d834fc

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0007, T1087.001

References

- https://www.absolomb.com/2018-01-26-Windows-Privilege-Escalation-Guide/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/10	medium	• Administrative activity

Rule Details: Conti Ransomware Execution

Conti ransomware command line ioc.

Rule ID

`process_creation_commandline_153`

Query

```
{'selection': {'CommandLine|contains|all': ['-m ', '-net ', '-size ', '-nomutex ', '-
p \\\\', '$']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,689308fc-cfba-4f72-9897-796c1dc61487

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0040, T1486

References

- https://news.sophos.com/en-us/2021/09/03/conti-affiliates-use-proxyshell-exchange-exploit-in-ransomware-attacks/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/10/12	critical	• Unlikely

Rule Details: Snatch Ransomware

Detects specific process characteristics of Snatch ransomware word document droppers.

Rule ID

`process_creation_commandline_154`

Query

```
{'selection': {'CommandLine|contains': ['shutdown /r /f /t 00', 'net stop SuperBackup Man']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,5325945e-f1f0-406e-97b8-65104d393fff

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1204, T1059.003

References

- https://news.sophos.com/en-us/2019/12/09/snatch-ransomware-reboots-pcs-into-safe-mode-to-bypass-protection/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2020/08/26	high	• Scripts that shutdown the system immediately and reboot them in safe mode are unlikely

Rule Details: Copy from Volume Shadow Copy

Detects a copy execution that targets a shadow copy (sometimes used to copy registry hives that are in use).

Rule ID

`process_creation_commandline_155`

Query

```
{'selection': {'CommandLine|contains': 'copy \\\\?
\\GLOBALROOT\\Device\\HarddiskVolumeShadowCopy'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c73124a7-3e89-44a3-bdc1-25fe4df754b1

Author: Max Altgelt (Nextron Systems), Tobias Michalski (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0040, T1490

References

- https://twitter.com/vxunderground/status/1423336151860002816?s=20
- https://www.virustotal.com/gui/file/03e9b8c2e86d6db450e5eceec057d7e369ee2389b9daecaf06331a95410aa5f8/detection
- https://pentestlab.blog/2018/07/04/dumping-domain-password-hashes/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/08/09	medium	• Some rare backup scenarios

Rule Details: Suspicious VBScript UN2452 Pattern

Detects suspicious inline VBScript keywords as used by UNC2452.

Rule ID

`process_creation_commandline_156`

Query

```
{'selection': {'CommandLine|contains|all': ['Execute', 'CreateObject', 'RegRead', 'window.close', '\\Microsoft\\Windows\\CurrentVersion']}, 'filter': {'CommandLine|contains': '\\Software\\Microsoft\\Windows\\CurrentVersion\\Run'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,20c3f09d-c53d-4e85-8b74-6aa50e2f1b61

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1547.001

References

- https://www.microsoft.com/security/blog/2021/03/04/goldmax-goldfinder-sibot-analyzing-nobelium-malware/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/03/05	high	• Unknown

Rule Details: Sensitive Registry Access via Volume Shadow Copy

Detects a command that accesses password storing registry hives via volume shadow backups.

Rule ID

`process_creation_commandline_157`

Query

```
{'selection_1': {'CommandLine|contains': '\\\\?
\\GLOBALROOT\\Device\\HarddiskVolumeShadowCopy'}, 'selection_2': {'CommandLine|contai
ns': ['\\NTDS.dit', '\\SYSTEM', '\\SECURITY', 'C:\\tmp\\log']}, 'condition': 'all of
selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f57f8d16-1f39-4dcb-a604-6c73d9b54b3d

Author: Max Altgelt (Nextron Systems), Tobias Michalski (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0040, T1490

References

- https://twitter.com/vxunderground/status/1423336151860002816?s=20
- https://www.virustotal.com/gui/file/03e9b8c2e86d6db450e5eceec057d7e369ee2389b9daecaf06331a95410aa5f8/detection
- https://pentestlab.blog/2018/07/04/dumping-domain-password-hashes/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/08/09	high	• Some rare backup scenarios

Rule Details: Abusable Invoke-ATHRemoteFXvGPUDisablementCommand

RemoteFXvGPUDisablement.exe is an abusable, signed PowerShell host executable that was introduced in Windows 10 and Server 2019 (OS Build 17763.1339).

Rule ID

```
process_creation_commandline_158
```

Query

```
{'selection_cmd': {'CommandLine|contains': 'Invoke-
ATHRemoteFXvGPUDisablementCommand '}, 'selection_opt': {'CommandLine|contains': ['-
ModuleName ', '-ModulePath ', '-ScriptBlock ', '-
RemoteFXvGPUDisablementFilePath']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,a6fc3c46-23b8-4996-9ea2-573f4c4d88c5

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1218/T1218.md
- https://github.com/redcanaryco/AtomicTestHarnesses/blob/7e1e4da116801e3d6fcc6bedb207064577e40572/TestHarnesses/T1218_SignedBinaryProxyExecution/InvokeRemoteFXvGPUDisablementCommand.ps1

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/13	medium	• Unknown

Rule Details: Execute From Alternate Data Streams

Detects execution from an Alternate Data Stream (ADS). Adversaries may use NTFS file attributes to hide their malicious data in order to evade detection.

Rule ID

process_creation_commandline_159

Query



{'selection_stream': {'CommandLine|contains': 'txt:'}, 'selection_tools_type': {'CommandLine|contains|all': ['type ', ' > ']}, 'selection_tools_makecab': {'CommandLine|contains|all': ['makecab ', '.cab']}, 'selection_tools_reg': {'CommandLine|contains|all': ['reg ', ' export ']}, 'selection_tools_regedit': {'CommandLine|contains|all': ['regedit ', ' /E ']}, 'selection_tools_esentutl': {'CommandLine|contains|all': ['esentutl ', ' /y ', ' /d ', ' /o ']}, 'condition': 'selection_stream and (1 of selection_tools_*)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7f43c430-5001-4f8b-aaa9-c3b88f18fa5c

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1564.004

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1564.004/T1564.004.md

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/09/01	medium	• Unknown

Rule Details: Potential Tampering With Security Products Via WMIC

Detects uninstallation or termination of security products using the WMIC utility.

Rule ID

process_creation_commandline_160

Query

{'selection_cli_1': {'CommandLine|contains|all': ['wmic', 'product where ', 'call uninstall', '/nointeractive']}, 'selection_cli_2': {'CommandLine|contains|all': ['wmic', 'caption like '], 'CommandLine|contains': ['call delete', 'call terminate']}, 'selection_cli_3': {'CommandLine|contains|all': ['process ', 'where ', 'delete']}, 'selection_product': {'CommandLine|contains': ['%carbon%', '%cylance%', '%endpoint%', '%eset%', '%malware%', '%Sophos%', '%symantec%', 'Antivirus', 'AVG ', 'Carbon Black', 'CarbonBlack', 'Cb Defense Sensor 64-
bit', 'Crowdstrike Sensor', 'Cylance ', 'Dell Threat Defense', 'DLP Endpoint', 'Endpoint Detection', 'Endpoint Protection', 'Endpoint Security', 'Endpoint Sensor', 'ESET File Security', 'LogRhythm System Monitor Service', 'Malwarebytes', 'McAfee Agent', 'Microsoft Security Client', 'Sophos Anti-
Virus', 'Sophos AutoUpdate', 'Sophos Credential Store', 'Sophos Management Console', 'Sophos Management Database', 'Sophos Management Server', 'Sophos Remote Management System', 'Sophos Update Manager', 'Threat Protection', 'VirusScan', 'Webroot SecureAnywhere', 'Windows Defender']}, 'condition': '1 of selection_cli_* and selection_product'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,847d5ff3-8a31-4737-a970-aeae8fe21765

Author: Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001

References

- https://twitter.com/cglyer/status/1355171195654709249
- https://thedfirreport.com/2021/10/18/icedid-to-xinglocker-ransomware-in-24-hours/
- https://www.mandiant.com/resources/unc2165-shifts-to-evade-sanctions
- https://research.nccgroup.com/2022/08/19/back-in-black-unlocking-a-lockbit-3-0-ransomware-attack/
- https://www.trendmicro.com/en_us/research/23/a/vice-society-ransomware-group-targets-manufacturing-companies.html

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/01/30	high	• Legitimate administration

Rule Details: Potential Download/Upload Activity Using Type Command

Detects usage of the "type" command to download/upload data from WebDAV server.

Rule ID

`process_creation_commandline_161`

Query

```
{'selection_upload': {'CommandLine|contains|all': ['type ', ' > \\\\']}, 'selection_download': {'CommandLine|contains|all': ['type \\\\', ' > ']}, 'condition': '1 of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,aa0b3a82-eacc-4ec3-9150-b5a9a3e3f82f

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0011, T1105

References

- https://mr0range.com/a-new-lolbin-using-the-windows-type-command-to-upload-download-files-81d7b6179e22

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/14	medium	• Unknown

Rule Details: Invoke-Obfuscation Via Stdin

Detects Obfuscated Powershell via Stdin in Scripts.

Rule ID

process_creation_commandline_162

Query



{'selection': {'CommandLine|contains|all': ['set', '&&'], 'CommandLine|contains': ['environment', 'invoke', 'input']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,9c14c9fa-1a63-4a64-8e57-d19280559490

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/12	high	• Unknown

Rule Details: Wscript Shell Run In CommandLine

Detects the presence of the keywords "Wscript", "Shell" and "Run" in the command, which could indicate a suspicious activity.

Rule ID

process_creation_commandline_163

Query

{'selection': {'CommandLine|contains|all': ['Wscript.', '.Shell', '.Run']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,2c28c248-7f50-417a-[illegible]6-a85b223010ee

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- http://blog.talosintelligence.com/2022/08/modernloader-delivers-multiple-stealers.html

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/31	high	• Rare legitimate inline scripting by some administrators

Rule Details: Reg Add RUN Key

Detects suspicious command line reg.exe tool adding key to RUN key in Registry.

Rule ID

`process_creation_commandline_164`

Query

```
{'selection': {'CommandLine|contains|all': ['reg', ' ADD ', 'Software\\Microsoft\\Windows\\CurrentVersion\\Run']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,de587dce-915e-4218-aac4-835ca6af6f70

Author: Florian Roth (Nextron Systems), Swachchhanda Shrawan Poudel (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1547.001

References

- https://app.any.run/tasks/9c0f37bc-867a-4314-b685-e101566766d7/

- https://docs.microsoft.com/en-us/windows/win32/setupapi/run-and-runonce-registry-keys

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/06/28	medium	• Legitimate software automatically (mostly, during installation) sets up autorun keys for legitimate reasons. • Legitimate administrator sets up autorun keys for legitimate reasons. • Discord

Rule Details: Disable or Delete Windows Eventlog

Detects command that is used to disable or delete Windows eventlog via logman Windows utility.

Rule ID

`process_creation_commandline_165`

Query

```
{'selection_tools': {'CommandLine|contains': 'logman '}, 'selection_action': {'Comman
dLine|contains': ['stop ', 'delete ']}, 'selection_service': {'CommandLine|contains':
 'EventLog-System'}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,cd1f961e-0b96-436b-b7c6-38da4583ec00

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1562.001, T1070.001

References

- https://twitter.com/0gtweet/status/1359039665232306183?s=21
- https://ss64.com/nt/logman.html

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/02/11	high	• Legitimate deactivation by administrative staff • Installer tools that disable services, e.g. before log collection agent installation

Rule Details: Java Running with Remote Debugging

Detects a JAVA process running with remote debugging allowing more than just localhost to connect.

Rule ID

`process_creation_commandline_166`

Query

```
{'selection_jdwp_transport': {'CommandLine|contains': 'transport=dt_socket,address='}, 'selection_old_jvm_version': {'CommandLine|contains': ['jre1.', 'jdk1.']}, 'exclusion': [{'CommandLine|contains': 'address=127.0.0.1'}, {'CommandLine|contains': 'address=localhost'}], 'condition': 'all of selection* and not exclusion'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,8f88e3f6-2a49-48f5-a5c4-2f7eedf78710

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1203, T1059.003

References

- https://dzone.com/articles/remote-debugging-java-applications-with-jdwp

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/01/16	medium	• Unknown

Rule Details: Monitoring For Persistence Via BITS

BITS will allow you to schedule a command to execute after a successful download to notify you that the job is finished. When the job runs on the system the command specified in the BITS job will be executed. This can be abused by actors to create a backdoor within the system and for persistence. It will be chained in a BITS job to schedule the download of malware/additional binaries and execute the program after being downloaded.

Rule ID

`process_creation_commandline_167`

Query


```
{'selection_1': {'CommandLine|contains|all': ['bitsadmin', '/SetNotifyCmdLine'], 'Com
mandLine|contains': ['%COMSPEC%', 'cmd.exe', 'regsvr32.exe']}, 'selection_2': {'Comma
ndLine|contains|all': ['bitsadmin', '/Addfile'], 'CommandLine|contains': ['http:', 'h
ttps:', 'ftp:', 'ftps:']}, 'condition': '1 of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b9cbbc17-d00d-4e3d-a827-b06d03d2380d

Author: Sreeman

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1197

References

- https://www.fireeye.com/blog/threat-research/2020/10/kegtap-and-singlemalt-with-a-ransomware-chaser.html
- http://0xthem.blogspot.com/2014/03/t-emporal-persistence-with-and-schtasks.html
- https://isc.sans.edu/diary/Wipe+the+drive+Stealthy+Malware+Persistence+Mechanism+-+Part+1/15394

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/29	medium	• Unknown

Rule Details: Obfuscated Command Line Using Special Unicode Characters

Adversaries may attempt to make an executable or file difficult to discover or analyze by encrypting, encoding, or otherwise obfuscating its contents on the system or in transit.

Rule ID

`process_creation_commandline_168`

Query

```
{'selection': {'CommandLine|contains': ['â', '€', '£', '¯', '®', 'µ', '¶']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e0552b19-5a83-4222-b141-b36184bb8d79

Author: frack113, Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1027

References

- https://www.wietzebeukema.nl/blog/windows-command-line-obfuscation
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1027/T1027.md#atomic-test-6---dlp-evasion-via-sensitive-data-in-vba-macro-over-http

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/15	high	• Unknown

Rule Details: Compress Data and Lock With Password for Exfiltration With 7-ZIP

An adversary may compress or encrypt data that is collected prior to exfiltration using 3rd party utilities.

Rule ID

`process_creation_commandline_9`

Query

```
{'selection_7z': {'CommandLine|contains': ['7z.exe', '7za.exe']}, 'selection_password': {'CommandLine|contains': ' -p'}, 'selection_action': {'CommandLine|contains': [' a ', ' u ']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,9fbf5927-5261-4284-a71d-f681029ea574

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1560.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1560.001/T1560.001.md

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/27	medium	• Command line parameter combinations that contain all included strings

Rule Details: Suspicious DIR Execution

Detects usage of the "dir" command that's part of windows batch/cmd to collect information about directories.

Rule ID

`process_creation_commandline_170`

Query

{'selection': {'CommandLine|contains|all': ['dir ', ' /s', ' /b']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7c9340a9-e2ee-4e43-94c5-c54ebbea1006

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0007, T1217

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1217/T1217.md

Severity

24

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/13	low	• Unknown

Rule Details: Suspicious Diantz Download and Compress Into a CAB File

Download and compress a remote file and store it in a cab file on local machine.

Rule ID

`process_creation_commandline_172`

Query

{'selection': {'CommandLine|contains|all': ['diantz.exe', ' \\\\', '.cab']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,185d7418-f250-42d0-b72e-0c8b70661e93

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0011, T1105

References

- https://lolbas-project.github.io/lolbas/Binaries/Diantz/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/11/26	medium	• Unknown

Rule Details: Invoke-Obfuscation VAR++ LAUNCHER OBFUSCATION

Detects Obfuscated Powershell via VAR++ LAUNCHER.

Rule ID

`process_creation_commandline_173`

Query

```
{'selection': {'CommandLine|contains|all': ['&&set', 'cmd', '/c', '-
f'], 'CommandLine|contains': ['{0}', '{1}', '{2}', '{3}', '{4}', '{5}']}, 'condition'
: 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e9f55347-2928-4c06-88e5-1a7f8169942e

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/13	high	• Unknown

Rule Details: Ps.exe Renamed SysInternals Tool

Detects renamed SysInternals tool execution with a binary named ps.exe as used by Dragonfly APT group and documented in TA17-293A report.

Rule ID

`process_creation_commandline_174`

Query

```
{'selection': {'CommandLine': 'ps.exe -accepteula'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,18da1007-3f26-470f-875d-f77faf1cab31

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1036.003

References

- https://www.us-cert.gov/ncas/alerts/TA17-293A

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/10/22	high	• Renamed SysInternals tool

Rule Details: TropicTrooper Campaign November 2018

Detects TropicTrooper activity, an actor who targeted high-profile organizations in the energy and food and beverage sectors in As

Rule ID

`process_creation_commandline_175`

Query

```
{'selection': {'CommandLine|contains': 'abCCC
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,40b19fa6-d835-400c-b301-41f3a2baacaf

Author: Teymur Kheirkhabarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1003

References

- https://www.slideshare.net/heirhabarov/hunting-for-credentials-dumping-in-windows-environment

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/22	medium	• Legitimate administrator working with shadow copies, access for backup purposes

Rule Details: Suspicious Desktopimgdownldr Command

Detects a suspicious Microsoft desktopimgdownldr execution with parameters used to download files from the Internet.

Rule ID

```
process_creation_commandline_177
```

Query

```
{'selection1': {'CommandLine|contains': ' /lockscreenurl:'}, 'selection1_filter': {'CommandLine|contains': ['.jpg', '.jpeg', '.png']}, 'selection_reg': {'CommandLine|contains|all': ['reg delete', '\\PersonalizationCSP']}, 'condition': '( selection1 and not selection1_filter ) or selection_reg'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,bb58aa4a-b80b-415a-a2c0-2f65a4c81009

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0011, T1105

References

- https://labs.sentinelone.com/living-off-windows-land-a-new-native-file-downldr/
- https://twitter.com/SBousseaden/status/1278977301745741825

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/07/03	high	• False positives depend on scripts and administrative tools used in the monitored environment

Rule Details: Rundll32 JS RunHTMLApplication Pattern

Detects suspicious command line patterns used when rundll32 is used to run JavaScript code.

Rule ID

`process_creation_commandline_178`

Query

```
{'selection1': {'CommandLine|contains|all': ['rundll32', 'javascript', '..\\..\\mshtml,RunHTMLApplication']}, 'selection2': {'CommandLine|contains': ';document.write();GetObject("script'}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,9f06447a-a33a-4cbe-a94f-a3f43184a7a3

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- http://hyp3rlinx.altervista.org/advisories/MICROSOFT_WINDOWS_DEFENDER_DETECTION_BYPASS.txt

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/01/14	high	• Unlikely

Rule Details: ADCSPwn Hack Tool

Detects command line parameters used by ADCSPwn, a tool to escalate privileges in an active directory network by coercing authenticate from machine accounts and relaying to the certificate service.

Rule ID

`process_creation_commandline_179`

Query

```
{'selection': {'CommandLine|contains|all': [' --adcs ', ' --
port ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,cd8c163e-a19b-402e-bdd5-419ff5859f12

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1557.001

References

- https://github.com/bats3c/ADCSPwn

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/31	high	• Unlikely

Rule Details: Potential PowerShell Execution Policy Tampering - ProcCreation

Detects changes to the PowerShell execution policy registry key in order to bypass signing requirements for script execution from the CommandLine.

Rule ID

`process_creation_commandline_180`

Query


```
{'selection_path': {'CommandLine|contains': ['\\ShellIds\\Microsoft.PowerShell\\ExecutionPolicy', '\\Policies\\Microsoft\\Windows\\PowerShell\\ExecutionPolicy']}, 'selection_values': {'CommandLine|contains': ['Bypass', 'RemoteSigned', 'Unrestricted']}, 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,cf2e938e-9a3e-4fe8-a347-411642b28a9f

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://learn.microsoft.com/de-de/powershell/module/microsoft.powershell.security/set-executionpolicy?view=powershell-7.3

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/11	high	• Unknown

Rule Details: CrackMapExec PowerShell Obfuscation

The CrachMapExec pentesting framework implements a PowerShell obfuscation with some static strings detected by this ru

Rule ID

`process_creation_commandline_181`

Query

```
{'powershell_execution': {'CommandLine|contains': ['powershell.exe', 'pwsh.exe']}, 'snippets': {'CommandLine|contains': ['join*split', "
( $ShellId[1]+$ShellId[13]+'x')", '( $PSHome[*]+$PSHOME[*]+', "
( $env:Public[13]+$env:Public[5]+'x')", "( $env:ComSpec[4,*,25]-Join'')", "[1,3]+'x'-Join'')"]}, 'condition': 'powershell_execution and snippets'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,6f8b3439-a203-45dc-a88b-abf57ea15ccf

Author: Thomas Patzke

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027.005

References

- https://github.com/byt3bl33d3r/CrackMapExec
- https://github.com/byt3bl33d3r/CrackMapExec/blob/0a49f75347b625e81ee6aa8c33d3970b5515ea9e/cme/helpers/powershell.py#L242

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/22	high	• Unknown

Rule Details: Copy DMP Files From Share

Detects usage of the copy command to copy files with the .dmp extensions from a remote share.

Rule ID

`process_creation_commandline_182`

Query

{'selection': {'CommandLine|contains|all': ['.dmp', 'copy ', ' \\\\'], 'CommandLine|contains': [' /c ', ' /r ', ' /k ']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,044ba588-dff4-4918-9808-3f95e8160606

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://thedfirreport.com/2022/09/26/bumblebee-round-two/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/27	high	• Unknown

Rule Details: Deletion of Volume Shadow Copies via WMI with PowerShell

Detects deletion of Windows Volume Shadow Copies with PowerShell code and Get-WMIObject. This technique is used by numerous ransomware families such as Sodinokibi/REvil.

Rule ID

process_creation_commandline_183

Query

{'selection_get': {'CommandLine|contains': ['Get-WmiObject', 'gwmi', 'Get-CimInstance', 'gcim']}, 'selection_shadowcopy': {'CommandLine|contains': 'Win32_Shadowcopy'}, 'selection_delete': {'CommandLine|contains': ['.Delete()', 'Remove-WmiObject', 'rwmi', 'Remove-CimInstance', 'rcim']}, 'condition': 'all of selection*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,21ff4ca9-f13a-41ad-[illegible]-0077b2af2e40

Author: Tim Rauch, Elastic (idea)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0040, T1490

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1490/T1490.md#atomic-test-5---windows---delete-volume-shadow-copies-via-wmi-with-powershell
- https://www.elastic.co/guide/en/security/current/volume-shadow-copy-deletion-via-powershell.html

Severity

80

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/20	high	• Unknown

Rule Details: ScreenConnect Remote Access

Detects ScreenConnect program starts that establish a remote access to that system (not meeting, not remote support).

Rule ID

`process_creation_commandline_184`

Query

```
{'selection': {'CommandLine|contains|all': ['e=Access&', 'y=Guest&', '&p=', '&c=', '&k=']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,75bfe6e6-cd8e-429e-91d3-03921e1d7962

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1133

References

- https://www.anomali.com/blog/probable-iranian-cyber-actors-static-kitten-conducting-cyberespionage-campaign-targeting-uae-and-kuwait-government-agencies

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/02/11	high	• Legitimate use by administrative staff

Rule Details: Curl Start Combination

Adversaries can use curl to download payloads remotely and execute them. Curl is included by default in Windows 10 build 17063 and later.

Rule ID

`process_creation_commandline_185`

Query

```
{'selection': {'CommandLine|contains|all': [' /c ', 'curl ', 'http', '-o', '&']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,21dd6d38-2b18-4453-9404-a0fe4a0cc288

Author: Sreeman, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1218, TA0011, T1105

References

- https://medium.com/@reegun/curl-exe-is-the-new-rundll32-exe-lolbin-3f79c5f35983

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/01/13	high	• Administrative scripts (installers)

Rule Details: Suspicious Usage of the Manage-bde.wsf Script

Detects usage of the manage-bde.wsf script that may indicate an attempt of proxy execution from script.

Rule ID

`process_creation_commandline_186`

Query

```
{'selection': {'CommandLine|contains|all': ['cscript', 'manage-bde.wsf']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c363385c-f75d-4753-a108-c1a8e28bdbda

Author: oscd.community, Natalia Shornikova, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1216

References

- https://lolbas-project.github.io/lolbas/Scripts/Manage-bde/
- https://gist.github.com/bohops/735edb7494fe1bd1010d67823842b712
- https://twitter.com/bohops/status/980659399495741441
- https://twitter.com/JohnLaTwC/status/1223292479270600706
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1216/T1216.md

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/13	medium	• Unknown

Rule Details: Potential COM Objects Download Cradles Usage - Process Creation

Detects usage of COM objects that can be abused to download files in PowerShell by CLSID.

Rule ID

`process_creation_commandline_187`

Query


```
{'selection_1': {'CommandLine|contains': '[Type]::GetTypeFromCLSID('}, 'selection_2':
 {'CommandLine|contains': ['0002DF01-0000-0000-C000-000000000046', 'F6D90F16-9C73-
11D3-B32E-00C04F990BB4', 'F5078F35-C551-11D3-89B9-0000F81FE221', '88d96a0a-f192-11d4-
a65f-0040963251e5', 'AFBA6B42-5692-48EA-8141-DC517DCF0EF1', 'AFB40FFD-B609-40A3-9828-
F88BBE11E4E3', '88d96a0b-f192-11d4-a65f-0040963251e5', '2087c2f4-2cef-4953-a8ab-
66779b670495', '000209FF-0000-0000-C000-000000000046', '00024500-0000-0000-C000-
000000000046']}, 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,02b64f1b-3f33-4e67-aede-ef3b0a5a8fcf

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://learn.microsoft.com/en-us/dotnet/api/system.type.gettypefromclsid?view=net-7.0
- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=57

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/25	medium	• Legitimate use of the library

Rule Details: Base64 MZ Header In CommandLine

Detects encoded base64 MZ header in the commandline.

Rule ID

`process_creation_commandline_188`

Query

```
{'selection': {'CommandLine|contains': ['TVqQAAMAAAAEAAAA', 'TVpQAAIAAAAEAA8A', 'TVqA
AAEAAAAEABAA', 'TVoAAAAAAAAAAAAA', 'TVpTAQEAAAAEAAAA']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,22e58743-4ac8-4a9f-bf19-00a0428d8c5f

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://thedfirreport.com/2022/07/11/select-xmrig-from-sqlserver/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/07/12	high	• Unlikely

Rule Details: Capture a Network Trace with netsh.exe

Detects capture a network trace via netsh.exe trace functionality.

Rule ID

`process_creation_commandline_189`

Query

```
{'selection': {'CommandLine|contains|all': ['netsh', 'trace', 'start']}, 'condition':
 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,d3c3861d-c504-4c77-ba55-224ba82d0118

Author: Kutepov Anton, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0007, T1040

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	medium	• Legitimate administrator or user uses netsh.exe trace functionality for legitimate reason

Rule Details: Baby Shark Activity

Detects activity that could be related to Baby Shark malware.

Rule ID

```
process_creation_commandline_190
```

Query

```
{'selection': {'CommandLine|contains': ['reg query "HKEY_CURRENT_USER\\Software\\Microsoft\\Terminal Server Client\\Default"', 'powershell.exe mshta.exe http', 'cmd.exe /c taskkill /im cmd.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,2b30fa36-3a18-402f-a22d-bf4ce2189f35

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1218.005, TA0007, T1012

References

- https://unit42.paloaltonetworks.com/new-babyshark-malware-targets-u-s-national-security-think-tanks/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/02/24	high	• Unknown

Rule Details: Suspicious Ping/Del Command Combination

Detects a method often used by ransomware. Which combines the "ping" to wait a couple of seconds and then "del" to delete the file in question. Its used to hide the file responsible for the initial infection for example.

Rule ID

`process_creation_commandline_191`

Query

```
{'selection_count': {'CommandLine|contains': [' -
n ', ' /n ']}, 'selection_nul': {'CommandLine|contains': 'Nul'}, 'selection_del_param
': {'CommandLine|contains': [' /f ', ' -f ', ' /q ', ' -
q ']}, 'selection_all': {'CommandLine|contains|all': ['ping', 'del ']}, 'condition':
'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,54786ddc-5b8a-11ed-9b6a-0242ac120002

Author: Ilya Krestinichev

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1070.004

References

- https://blog.sygnia.co/kaseya-ransomware-supply-chain-attack

- https://media.kasperskycontenthub.com/wp-content/uploads/sites/4[illegible]2022/06/23093553/Common-TTPs-of-the-modern-ransomware_low-res.pdf
- https://www.acronis.com/en-us/blog/posts/lockbit-ransomware/
- https://symantec-enterprise-blogs.security.com/blogs/threat-intelligence/blackbyte-exbyte-ransomware

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/11/03	high	• False positive could occur in admin scripts that execute inline

Rule Details: Change Default File Association

When a file is opened, the default program used to open the file (also called the file association or handler) is checked. File association selections are stored in the Windows Registry and can be edited by users, administrators, or programs that have Registry access or by administrators using the built-in assoc utility. Applications can modify the file association for a given file extension to call an arbitrary program when a file with the given extension is opened.

Rule ID

`process_creation_commandline_192`

Query

```
{'selection': {'CommandLine|contains|all': ['cmd', 'assoc'], 'CommandLine|contains': [' /c ', ' /k ', ' /r ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,3d3aa6cd-6272-44d6-8afc-7e88dfef7061

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0003, T1546.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1546.001/T1546.001.md

Severity

24

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/21	low	• Admin activity

Rule Details: PowerShell Web Download and Execution

Detects suspicious ways to download files or content and execute them using PowerShell Invoke-Expression.

Rule ID

`process_creation_commandline_193`

Query

```
{'selection_download': {'CommandLine|contains': ['.DownloadString(', '.DownloadFile(', 'Invoke-
WebRequest ', 'iwr ']}, 'selection_iex': {'CommandLine|contains': ['IEX(', 'IEX (', 'I`EX', 'IE`X', 'I`E`X', '| IEX', '|IEX ', 'Invoke-
Expression', ';iex $']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,85b0b087-eddf-4a2b-b033-d771fa2b9775

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://github.com/VirtualAlllocEx/Payload-Download-Cradles/blob/88e8eca34464a547c90d9140d70e9866dcbc6a12/Download-Cradles.cmd

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/03/24	high	• Scripts or tools that download files and execute them

Rule Details: Empire PowerShell Launch Parameters

Detects suspicious powershell command line parameters used in Empire.

Rule ID

`process_creation_commandline_194`

Query

```
{'selection': {'CommandLine|contains': [' -NoP -sta -NonI -W Hidden -Enc ', ' -noP -sta -w 1 -enc ', ' -NoP -NonI -W Hidden -enc ', ' -noP -sta -w 1 -enc', ' -enc  SQB', ' -nop -exec bypass -EncodedCommand ']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,79f4ede3-402e-41c8-bc3e-ebbf5f162581

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059

References

- https://github.com/EmpireProject/Empire/blob/c2ba61ca8d2031dad0cfc1d5770ba723e8b710db/lib/common/helpers.py#L165
- https://github.com/EmpireProject/Empire/blob/e37fb2eef8ff8f5a0a689f1589f424906fe13055/lib/modules/powershell/persistence/powerbreach/deaduser.py#L191
- https://github.com/EmpireProject/Empire/blob/e37fb2eef8ff8f5a0a689f1589f424906fe13055/lib/modules/powershell/persistence/powerbreach/resolver.py#L178
- https://github.com/EmpireProject/Empire/blob/e37fb2eef8ff8f5a0a689f1589f424906fe13055/data/module_source/privesc/Invoke-EventVwrBypass.ps1#L64

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/04/20	high	• Other tools that incidentally use the same command line parameters

Rule Details: Invoke-Obfuscation STDIN+ Launcher

Detects Obfuscated use of stdin to execute PowerShell.

Rule ID

`process_creation_commandline_195`

Query


```
{'selection_main': {'CommandLine|contains|all': ['cmd', 'powershell'], 'CommandLine|contains': ['/c', '/r']}, 'selection_other': [{'CommandLine|contains': 'noexit'}, {'CommandLine|contains|all': ['input', '$']}], 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,6c96fc76-0eb1-11eb-adc1-0242ac120002

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/15	high	• Unknown

Rule Details: Conti NTDS Exfiltration Command

Detects a command used by conti to exfiltrate NTDS.

Rule ID



`process_creation_commandline_196`

Query

```
{'selection': {'CommandLine|contains|all': ['7za.exe', '\\C$\\temp\\log.zip']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,aa92fd02-09f2-48b0-8a93-864813fb8f41

Author: Max Altgelt (Nextron Systems), Tobias Michalski (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1560

References

- https://twitter.com/vxunderground/status/1423336151860002816?s=20
- https://www.virustotal.com/gui/file/03e9b8c2e86d6db450e5eceec057d7e369ee2389b9daecaf06331a95410aa5f8/detection

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/09	high	• Unknown

Rule Details: Covenant Launcher Indicators

Detects suspicious command lines used in Covenant luanchers.

Rule ID

`process_creation_commandline_198`

Query

```
{'selection': {'CommandLine|contains|all': ['-Sta', '-Nop', '-Window', 'Hidden'], 'CommandLine|contains': ['-Command', '-
```

```
EncodedCommand']}, 'selection2': {'CommandLine|contains': ['sv o (New-
Object IO.MemorySteam);sv d ', 'mshta file.hta', 'GruntHTTP', '-
EncodedCommand cwB2ACAAbwAgA', 'condition': 'selection or selection2'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c260b6db-48ba-4b4a-a76f-2f67644e99d2

Author: Florian Roth (Nextron Systems), Jonhnathan Ribeiro, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1564.003

References

- https://posts.specterops.io/covenant-v0-5-eee0507b85ba

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/06/04	high	N/A

Rule Details: UNC2452 PowerShell Pattern

Detects a specific PowerShell command line pattern used by the UNC2452 actors as mentioned in Microsoft and Symantec reports.

Rule ID

```
process_creation_commandline_199
```

Query


```
{'selection1': {'CommandLine|contains|all': ['Invoke-WMIMethod win32_process -
name create -
argumentlist', 'rundll32 c:\\windows']}, 'selection2': {'CommandLine|contains|all': [
'wmic /node:', 'process call create "rundll32 c:\\windows']}, 'condition': '1 of sele
ction*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b7155193-8a81-4d8f-[illegible]d-88de864ca50c

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, T1047

References

- https://symantec-enterprise-blogs.security.com/blogs/threat-intelligence/solarwinds-raindrop-malware
- https://www.microsoft.com/security/blog/2020/12/18/analyzing-solorigate-the-compromised-dll-file-that-started-a-sophisticated-cyberattack-and-how-microsoft-defender-helps-protect/
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1047/T1047.md#atomic-test-7---create-a-process-using-wmi-query-and-an-encoded-command

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/01/20	critical	• Unlikely

Rule Details: Launch-VsDevShell.PS1 Proxy Execution

Detects the use of the 'Launch-VsDevShell.ps1' Microsoft signed script to execute commands.

Rule ID

`process_creation_commandline_200`

Query

```
{'selection_script': {'CommandLine|contains': 'Launch-VsDevShell.ps1'}, 'selection_flags': {'CommandLine|contains': ['VsWherePath ', 'VsInstallationPath ']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,45d3a03d-f441-458c-8883-df101a3bb146

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1216.001

References

- https://twitter.com/nas_bench/status/1535981653239255040

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/19	medium	• Legitimate usage of the script by a developer

Rule Details: Detect Virtualbox Driver Installation OR Starting Of VMs

Adversaries can carry out malicious operations using a virtual instance to avoid detection. This rule is built to detect the registration of the Virtualbox driver or start of a Virtualbox VM.

Rule ID

```
process_creation_commandline_201
```

Query

```
{'selection_1': {'CommandLine|contains': ['VBoxRT.dll,RTR3Init', 'VBoxC.dll', 'VBoxDrv.sys']}, 'selection_2': {'CommandLine|contains': ['startvm', 'controlvm']}, 'condition': '1 of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,bab049ca-7471-4828-9024-38279a4c04da

Author: Janantha Marasinghe

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0005, T1564.006

References

- https://news.sophos.com/en-us/2020/05/21/ragnar-locker-ransomware-deploys-virtual-machine-to-dodge-sec[illegible]/
- https://threatpost.com/maze-ransomware-ragnar-locker-virtual-machine/159350/

Severity

24

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/09/26	low	• This may have false positives on hosts where Virtualbox is legitimately being used for operations

Rule Details: Suspicious RDP Redirect Using TSCON

Detects a suspicious RDP session redirect using tscon.exe.

Rule ID

`process_creation_commandline_202`

Query

```
{'selection': {'CommandLine|contains': ' /dest:rdp-tcp:'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f72aa3e8-49f9-4c7d-bd74-f8ab84ff9bbb

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0008, T1563.002, T1021.001

References

- http://www.korznikov.com/2017/03/0-day-or-feature-privilege-escalation.html
- https://medium.com/@networksecurity/rdp-hijacking-how-to-hijack-rds-and-remoteapp-sessions-transparently-to-move-through-an-da2a1e73a5f6

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/03/17	high	• Unknown

Rule Details: Rar Usage with Password and Compression Level

Detects the use of rar.exe, on the command line, to create an archive with password protection or with a specific compression level. This is pretty indicative of malicious actions.

Rule ID

`process_creation_commandline_203`

Query

```
{'selection_password': {'CommandLine|contains': ' -
hp'}, 'selection_other': {'CommandLine|contains': [' -
m', ' a ']}, 'condition': 'selection_password and selection_other'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,faa48cae-6b25-4f00-a094-08947fef582f

Author: @ROxPinTeddy

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1560.001

References

- https://labs.sentinelone.com/the-anatomy-of-an-apt-attack-and-cobaltstrike-beacons-encoded-configuration/
- https://ss64.com/bash/rar.html
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1560.001/T1560.001.md

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk L	False Positives
test	2020/05/12	high	• Legitimate use of Winrar command line version • Other command line tools, that use these flags

Rule Details: Invoke-Obfuscation VAR+ Launcher

Detects Obfuscated use of Environment Variables to execute PowerShell.

Rule ID

`process_creation_commandline_204`

Query

```
{'selection': {'CommandLine|contains|all': ['cmd', '"set', '-
f'], 'CommandLine|contains': ['/c', '/r']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,27aec9c9-dbb0-4939-8422-1742242471d0

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/15	high	• Unknown

Rule Details: Suspicious SYSVOL Domain Group Policy Access

Detects Access to Domain Group Policies stored in SYSVOL.

Rule ID

`process_creation_commandline_205`

Query

```
{'selection': {'CommandLine|contains|all': ['\\SYSVOL\\', '\\policies\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,05f3c945-dcc8-4393-9f3d-af65077a8f86

Author: Markus Neis, Jonhnathan Ribeiro, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0006, T1552.006

References

- https://adsecurity.org/?p=2288
- https://www.hybrid-analysis.com/sample/f2943f5e45befa52fb12748ca7171d30096e1d4fc3c365561497c618341299d5?environmentId=100

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/04/09	medium	• Administrative activity

Rule Details: AnyDesk Piped Password Via CLI

Detects piping the password to an anydesk instance via CMD and the '--set-password' flag.

Rule ID

```
process_creation_commandline_206
```

Query

```
{'selection': {'CommandLine|contains|all': ['/c ', 'echo ', '.exe --set-password']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b1377339-fda6-477a-[illegible]5-ac0923f9ec2c

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0011, T1219

References

- https://redcanary.com/blog/misbehaving-rats/

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/28	medium	• Legitimate piping of the password to anydesk • Some FP could occure with similar tools that uses the same command line '--set-password'

Rule Details: Suspicious PowerShell Mailbox Export to Share

Detects usage of the powerShell New-MailboxExportRequest Cmdlet to exports a mailbox to a remote or local share, as used in ProxyShell exploitations.

Rule ID

`process_creation_commandline_207`

Query

```
{'selection': {'CommandLine|contains|all': ['New-MailboxExportRequest', ' -Mailbox ', ' -FilePath \\\\']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,889719ef-dd62-43df-86c3-768fb08dc7c0

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003

References

- https://youtu.be/5mqid-8k?t=2481
- https://blog.orange.tw/2021/08/proxylogon-a-new-attack-surface-on-ms-exchange-part-1.html
- https://peterjson.medium.com/reproducing-the-proxyshell-pwn2own-exploit-49743a4ea9a1
- https://m365internals.com/2022/10/07/hunting-in-on-premises-exchange-server-logs/

Severity

95

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/08/07	critical	• Unknown

Rule Details: Compress Data and Lock With Password for Exfiltration With WINZIP

An adversary may compress or encrypt data that is collected prior to exfiltration using 3rd party utilities.

Rule ID

`process_creation_commandline_208`

Query

```
{'selection_winzip': {'CommandLine|contains': ['winzip.exe', 'winzip64.exe']}, 'selection_password': {'CommandLine|contains': '-s"'}, 'selection_other': {'CommandLine|contains': [' -min ', ' -a ']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e2e80da2-8c66-4e00-ae3c-2eebd29f6b6d

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0009, T1560.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1560.001/T1560.001.md

Severity

49

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/07/27	medium	• Unknown

Rule Details: Network Reconnaissance Activity

Detects a set of suspicious network related commands often used in recon stages.

Rule ID

`process_creation_commandline_209`

Query

```
{'selection_nslookup': {'CommandLine|contains|all': ['nslookup', '_ldap._tcp.dc._msdcs.']}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,e6313acd-208c-44fc-a0ff-db85d572e90e

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.003, TA0007, T1087, T1082

References

- https://thedfirreport.com/2022/02/07/qbot-likes-to-move-it-move-it/

Severity

74

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/07	high	• False positives depend on scripts and administrative tools used in the monitored environment

Rule Details: File overwritten by cipher tool

The Windows tool cipher can be used to remove data from available unused disk space on the entire volume. Ransomware could use this technique to prevent the victim from using file recovery tools to recover their files.

Rule ID

`process_creation_commandline_301`

Query

```
{'selection3': {'Image|contains': '\\cipher.exe'}, 'selection5': {'CommandLine|re': '\\/w\\:[A-Z]{1}'}, 'condition': 'selection3 and selection5'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1070.004

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: PowerShell reverse shell one-liner

A PowerShell process with arguments that may indicate a reverse shell execution has been detected.

Rule ID

process_creation_commandline_302

Query



{'selection3': {'Image|contains': 'powershell.exe'}, 'selection5': {'CommandLine|contains': 'Sockets.TCPClient'}, 'selection6': {'CommandLine|contains': 'GetStream()'}, 'selection7': {'CommandLine|contains': 'IEX'}, 'selection8': {'CommandLine|contains': 'DownloadString'}, 'selection9': {'CommandLine|contains': 'mini-reverse.ps1'}, 'condition': 'selection3 and ((selection5 and selection6) or (selection7 and selection8 and selection9))'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Shellcode execution via InstallUtil.exe

Suspicious file/code has been executed via InstallUtil.exe. This is a common technique used by malware to install additional malicious components and/or execute Shellcode.

Rule ID

process_creation_commandline_303

Query

{'selection3': {'Image|contains': 'InstallUtil.exe'}, 'selection4': {'CommandLine|contains': '/LogToConsole=false'}, 'selection5': {'CommandLine|contains': '/logfile= '}, 'condition': 'selection3 and selection4 and selection5'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218.004

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: ALPC Task Scheduler Exploit LPE

Microsoft Windows task scheduler contains a local privilege escalation vulnerability in the Advanced Local Procedure Call (ALPC) interface, which can allow an attacker to perform a local privilege escalation.

Rule ID

```
process_creation_commandline_304
```

Query

```
{'selection3': {'Image|contains': '\\schtasks.exe'}, 'selection5': {'CommandLine|contains': '/change /TN'}, 'selection6': {'CommandLine|contains': '/RU'}, 'selection7': {'CommandLine|contains': '/RP'}, 'condition': 'selection3 and selection5 and selection6 and selection7'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1053.005

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Behavior DNS cache cleared

The DNS cache has been cleared in the system.

Rule ID

`process_creation_commandline_305`

Query


```
{'selection': {'Image|endswith': '\\ipconfig.exe', 'CommandLine|contains': '/flushdns', 'ParentImage|endswith': ['\\cmd.exe', '\\powershell.exe', '\\pwsh.exe', '\\wscript.exe', '\\cscript.exe', '\\mshta.exe']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1070

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: WMIC sending output to clipboard

WMIC command is using /output:clipboard as a way to hide the normal output of process creation that is printed when creating a process with WMIC.

Rule ID

`process_creation_commandline_307`

Query

```
{'selection3': {'Image|contains': '\\wmic.exe'}, 'selection5': {'CommandLine|contains': '/output:clipboard'}, 'selection6': {'CommandLine|contains': 'process call create'}, 'condition': 'selection3 and selection5 and selection6'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1036

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: CnC Channel through Nslookup

A Windows process was detected using Nslookup with abnormal flag(s) usually used by malware to communicate with the Command and Control.

Rule ID

`process_creation_commandline_308`

Query

{'selection3': {'Image|contains': '\\slookup.exe'}, 'selection4': {'CommandLine|contains': ' aaaa'}, 'selection5': {'CommandLine|contains': '=aaaa'}, 'selection6': {'CommandLine|re': '[a-z0-9]{15,45}\\. [a-z0-9]{1,15}\\.[a-z0-9]{1,4}'}, 'condition': 'selection3 and (selection4 or selection5) and selection6'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: WMIC Retrieving Security Configuration

The wmic.exe command was executed to get information from the security configurations. This could be an indication of malicious activity.

Rule ID

`process_creation_commandline_309`

Query

{'selection3': {'Image|contains': '\\wmic.exe'}, 'selection4': {'CommandLine|contains': 'SecurityCenter2'}, 'selection5': {'CommandLine|contains': ['AntiVirusProduct', 'FirewallProduct']}, 'condition': 'selection3 and selection4 and selection5'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0009, T1005

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Taskkill killing Antivirus process

An attempt to kill an Antivirus process has been detected. This can be the result of a manual command used by an attacker or an automated process as part of malware being deployed in the system.

Rule ID

`process_creation_commandline_310`

Query

```
{'selection3': {'Image|contains': 'Taskkill'}, 'selection4': {'CommandLine|re': '(?:fsav32|MsMpEng|FPAVServer|TMBMSRV|Mcshield|avgnsx|AvastSvc|dwengine|secenter|avguard|ccSvcHst|avp|360sd|360tray|AvastUi)\\.exe'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: WSH Injection via PubPrn

An attempt to inject malicious code into a Microsoft signed WSH script has been detected. This can be an attempt to bypass whitelisting restrictions.

Rule ID

```
process_creation_commandline_312
```

Query

```
{'selection3': {'Image|contains': 'wscript.exe'}, 'selection4': {'CommandLine|contains': 'pubprn.vbs'}, 'selection5': {'CommandLine|contains': 'script:'}, 'condition': 'selection3 and selection4 and selection5'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1055

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: AppLocker Bypass

A successful attempt to bypass AppLocker has been detected. This can indicate an attacker is trying to bypass whitelisting technologhies and escalate privileges or/and move laterally in your network.

Rule ID

`process_creation_commandline_314`

Query

```
{'selection3': {'Image|contains': '\\regsvr32.exe'}, 'selection4': {'CommandLine|contains': '/s'}, 'selection5': {'CommandLine|contains': '/i:http'}, 'selection6': {'CommandLine|contains': 'scrobj.dll'}, 'condition': 'selection3 and selection4 and selection5 and selection6'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218.010

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: File Deletion Backup files deleted recursively

An attempt to delete files and folders that migth contain backup data has been detected. This could be an indication of a ransomware infection or an attacker trying to cause damage.

Rule ID

`process_creation_commandline_315`

Query

```
{'selection3': {'Image|contains': '\\cmd.exe'}, 'selection4': {'CommandLine|contains': ' del '}, 'selection5': {'CommandLine|re': '(?:backup|bkup|\\.bak|\\.bac|\\.dsk|\\.
```

win|\\.bkf|\\.wbcat)'}, 'condition': 'selection3 and selection4 and selection5'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1070.004

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Attempt to stop or delete Windows Defender service

Windows Defender Real-time Protection scanning for malware and other potentially unwanted software has been stopped.

Rule ID

`process_creation_commandline_316`

Query

{'selection3': {'Image|contains': '\\et.exe'}, 'selection5': {'Image|contains': '\\sc.exe'}, 'selection7': {'CommandLine|contains': 'stop'}, 'selection8': {'CommandLine|contains': 'delete'}, 'selection9': {'CommandLine|contains': 'WinDefend'}, 'condition': '(selection3 or selection5) and (selection7 or selection8) and selection9'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.001

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows Process Argument contains Base64 Encoded PE Header

A process has been launched with a Base64 encoded argument. Once decoded, the argument corresponds to the PE Header. This can indicate an attacker is trying to bypass any present execution policy.

Rule ID

```
process_creation_commandline_317
```

Query

```
{'selection3': {'CommandLine|contains': 'TVqQAAMAAAAEAAA'}, 'condition': 'selection3'
}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1140

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Cobalt Gang Windows script execution

A known Cobalt Gang script has been executed in the system. This could mean that your computer has been compromised and malicious code is running in your endpoint.

Rule ID

```
process_creation_commandline_319
```

Query

```
{'selection3': {'Image|contains': '\\wscript.exe'}, 'selection5': {'CommandLine|contains': 'error_log.vbe'}, 'condition': '(selection3) and selection5'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows execution using odbcconf tool

The odbcconf tool allows users to configure Open Database Connectivity (ODBC) drivers. The utility can be misused to execute malicious code and evade detection techniques.

Rule ID

```
process_creation_commandline_320
```

Query

{'selection3': {'Image|contains': '\\odbcconf.exe'}, 'selection5': {'CommandLine|contains': 'REGSVR'}, 'condition': 'selection3 and selection5'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows INF file launch

The Advanced INF Package Installer (advpack.dll) can use the LaunchINFSection function to invoke a section from .inf files. This could be used by attackers to remotely launch staged SCT files with malicious code.

Rule ID

`process_creation_commandline_321`

Query

{'selection3': {'Image|contains': '\\rundll32.exe'}, 'selection5': {'CommandLine|re': 'advpack\\.dll, (?:LaunchINFSection|#46)\\s+'}, 'condition': 'selection3 and selection5'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows MavInject DLL Injection

MavInject is a Windows utility that can be used to execute code. Mavinject can be used to inject a DLL into a running process.

Rule ID

`process_creation_commandline_322`

Query


```
{'selection3': {'Image|re': '\\\\Mavinject(?:32|64)?.exe'}, 'selection5': {'CommandLine|contains': '/INJECTRUNNING'}, 'condition': 'selection3 and selection5'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Suspicious ACL Change

A suspicious change was detected to an access control list (ACL). In this case, 'Full Access' was granted to 'Everyone' on a file or folder.

Rule ID

`process_creation_commandline_324`

Query

```
{'selection3': {'Image|contains': '\\icacls.exe'}, 'selection4': {'CommandLine|re': '\\/grant(?::r)?\\s+Everyone:F'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Credential Access Tool Detected - LaZagne

LaZagne is a multiplatform tool capable to retrieve user credentials from several system services and applications, such as web browsers.

Rule ID

`process_creation_commandline_325`

Query

{'selection3': {'Image|contains': '\\lazagne'}, 'selection4': {'CommandLine|contains': '-quiet'}, 'condition': 'selection3 and selection4'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003.002

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Indirect command execution using pcalua.exe

An user tried to use a Windows pcalua.exe utility to execute commands in an alternative way (without using cmd.exe or powershell.exe). Attackers may use this technique to avoid invoking the cmd but still execute commands.

Rule ID

process_creation_commandline_327

Query

{'selection3': {'Image|contains': '\\pcalua.exe'}, 'selection5': {'CommandLine|contains': ' -a '}, 'selection6': {'CommandLine|re': '\\.(?:hta|vbs|vbe|js|jse|wsf|wsh)'}, 'condition': 'selection3 and selection5 and selection6'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1202

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows UAC Bypass

A User Account Control Bypass activity was detected. This can be due to either regular operation or because an attacker is trying to escalate privileges.

Rule ID

```
process_creation_commandline_328
```

Query

```
{'selection3': {'CommandLine|contains': 'TpmInitUACBypass.exe'}, 'condition': 'selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1548.002

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: SAM, SECURITY or SYSTEM Registry Hive Export

These hives can be used with a password cracker or creddump to dump the LANMAN/NTLM hashes, view cached credentials, and decrypt LSA secrets. This could be an indication of a ransomware infection or an attacker trying to cause damage.

Rule ID

```
process_creation_commandline_329
```

Query

```
{'selection3': {'Image|contains': '\\reg.exe'}, 'selection4': {'CommandLine|re': 'save.+ (?:hklm|hkey_local_machine)\\\\(?:system|security|sam)'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003.002

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Suspicious PowerShell Argument

PowerShell was executed with suspicious command line argument. The script is likely attempting to download files from a remote server. This could be an indication of malicious activity.

Rule ID

`process_creation_commandline_330`

Query

```
{'selection3': {'Image|contains': '\\powershell.exe'}, 'selection4': {'CommandLine|contains': 'Net.WebClient'}, 'selection5': {'CommandLine|contains': 'Download'}, 'condition': 'selection3 and selection4 and selection5'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows UAC bypass - UACME tool

User Account Control Bypass activity was detected. This can be due to either a regular operation or because an attacker is trying to escalate privileges.

Rule ID

`process_creation_commandline_331`

Query

```
{'selection9': {'CommandLine|re': '\\.exe\\".*cleanmgr\\.exe \\/autoclean'}, 'condition': 'selection9'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1548.002

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Ransomware Decryption Instructions File Detected

After a ransomware malware infects a host machine, a file with instructions to recover the encrypted files is created. A file with these characteristics was opened in the system, what is an indicator of ransomware infection.

Rule ID

```
process_creation_commandline_332
```

Query

```
{'selection3': {'CommandLine|re': '_Locky_recover_instructions.txt|Coin.Locker.txt DECRYPT_ReadMe.TXT|Contact_Here_To_Recover_Your_Files.txt|DECRYPT_INSTRUCTION.TXT|DECRYPT_INSTRUCTIONS.TXT|DecryptAllFiles.txt|encryptor_raas_readme_liesmich.txt|FILESAREGONE.TXT|help_decrypt_your_files.html|HELP_RECOVER_FILES.txt|HELP_TO_DECRYPT_YOUR_FILES.txt|HELPDECRYPT.TXT|HELPDECYPRT_YOUR_FILES.HTML|How_To_Recover_Files.txt|Howto_Restore_FILES.TXT|HOW TO DECRYPT YOUR DATA.txt|IHAVEYOURSECRET.KEY|INSTRUCCIONES_DESCIFRADO.TXT|ReadDecryptFilesHere.txt|Readme to restore your files.txt|!SBLOCK_INFO!.rtf|КАК ВОССТАНОВИТЬ ЗАШИФРОВАННЫЕ ФАЙЛЫ.TXT|README_LOCKED.txt'}, 'condition': 'selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1486

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows Autorun Registry Entry Added via reg.exe

An executable was added to the Windows Autorun registry. While this may have occurred due to normal software installation, this is a common technique used by malware to ensure it is started after reboots.

Rule ID

```
process_creation_commandline_333
```

Query

```
{'selection3': {'Image|contains': 'reg.exe'}, 'selection4': {'CommandLine|contains': 'SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\Run'}, 'selection5': {'CommandLine|contains': ' add '}, 'condition': 'selection3 and selection4 and selection5'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1547.001

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: File Deletion Backup Catalog Deletion

If the backup catalog is deleted for a computer, you will not be able to access the backups created of that computer using the Windows Server Backup snap-in. This could be an indication of a ransomware infection or an attacker trying to cause damage.

Rule ID

```
process_creation_commandline_334
```

Query

```
{'selection3': {'Image|contains': '\\wbadmin.exe'}, 'selection4': {'CommandLine|contains': 'delete catalog'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1070.004

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Wireless Network Password Retrieval

The password of a wireless network was accessed. This could be an indication of malicious activity.

Rule ID

`process_creation_commandline_335`

Query


```
{'selection3': {'ParentImage|contains': '\\etsh.exe'}, 'selection5': {'CommandLine|contains': 'wlan'}, 'selection6': {'CommandLine|contains': 'key=clear'}, 'condition': 'selection3 and selection5 and selection6'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1555

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Metasploit MSSQL Command Execution

An attacked gained access to the MSSQL Server database and is executing the Metasploit module mssql_exec.

Rule ID

`process_creation_commandline_337`

Query


```
{'selection3': {'ParentImage|contains': 'sqlservr.exe'}, 'selection4': {'CommandLine|contains': 'echo OWNED'}, 'condition': 'selection3 and selection4'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1190

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Internet Explorer executing suspicious wmic command

An attacker can execute code after a successful exploit attack. Internet Explorer is a commonly targeted software in Exploit Kit campaigns.

Rule ID

```
process_creation_commandline_338
```

Query

```
{'selection3': {'ParentImage|contains': '\\iexplore.exe'}, 'selection4': {'Image|cont
ains': '\\WMIC.exe'}, 'selection6': {'CommandLine|contains': 'process call create'},
'selection7': {'CommandLine|contains': '\\Temp\\'}, 'condition': 'selection3 and (sel
ection4 and selection6 and selection7)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1203

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: File Deletion Windows Shadow Copies Deletion via Powershell

An attempt to delete all shadow copies using the Windows Volume Shadow Copy Service (VSS) via Powershell has been detected. This could be an indication of a ransomware infection or an attacker trying to cause damage.

Rule ID

`process_creation_commandline_339`

Query


```
{'selection7': {'Image|contains': '\\powershell.exe'}, 'selection8': {'CommandLine|co
ntains': 'RwBlAHQALQBXAG0AaQBPAGIAagBlAGMAdAAgAFcAaQBuADMAMgBfAFMAaABhAGQAbwB3AGMAbwB
wAHkAIAB8ACAARgBvAHIARQBhAGMAaAAtAE8AYgBqAGUAYwB0ACAAewAkAF8ALgBEAGUAbABlAHQAZQAoACkA
OwB9AA==', 'condition': '(selection7 and selection8)'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1070.004

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: HackTool - Certipy Execution

Detects Certipy execution, a tool for Active Directory Certificate Services enumeration and abuse based on PE metadata characteristics and common command line arguments.

Rule ID

```
process_creation_commandline_340
```

Query

```
{'selection_img': [{'Image|endswith': '\\Certipy.exe'}], 'selection_cli_commands': {'
CommandLine|contains': [' account ', ' auth ', ' cert ', ' find ', ' forge ', ' ptt '
, ' relay ', ' req ', ' shadow ', ' template ']}, 'selection_cli_flags': {'CommandLin
e|contains': [' -bloodhound', ' -ca-pfx ', ' -dc-ip ', ' -kirbi', ' -old-
bloodhound', ' -pfx ', ' -target', ' -template', ' -username ', ' -
vulnerable', 'auth -
pfx', 'shadow auto', 'shadow list']}, 'condition': 'selection_img or all of selection
_cli_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,6938366d-8954-4ddc-baff-c830b3ba8fcd

Author: pH-T (Nextron Systems), Sittikorn Sangrattanapitak

Tactics, Techniques, and Procedures

TA0006, T1649

References

- https://github.com/ly4k/Certipy
- https://research.ifcr.dk/certipy-4-0-esc9-esc10-bloodhound-gui-new-authentication-and-request-methods-and-more-7237d88061f7

Severity

75

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2023-04-17	high	• Unlikely

Rule Details: Findstr GPP Passwords

Look for the encrypted cpassword value within Group Policy Preference files on the Domain Controller. This value can be decrypted with gpp-decrypt.

Rule ID

`process_creation_commandline_341`

Query

```
{'selection_img': [{'Image|endswith': ['\\find.exe', '\\findstr.exe']}], 'selection_cli': {'CommandLine|contains|all': ['cpassword', '\\sysvol\\', '.xml']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,91a2c315-9ee6-4052-a853-6f6a8238f90d

Author: frack113

Tactics, Techniques, and Procedures

TA0006, T1552.006

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1552.006/T1552.006.md#atomic-test-1---gpp-passwords-findstr

Severity

75

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021-12-27	high	• Unknown

Rule Details: Domain Trust Discovery Via Dsquery

Detects execution of "dsquery.exe" for domain trust discovery.

Rule ID

```
process_creation_commandline
```

Query

```
{'selection_img': [{'Image|endswith': '\\dsquery.exe'}], 'selection_cli': {'CommandLine|contains': 'trustedDomain'}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,3bad990e-4848-4a78-9530-b427d854aac0

Author: E.M. Anhaus, Tony Lambert, oscd.community, omkar72

Tactics, Techniques, and Procedures

TA0007, T1482

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1482/T1482.md
- https://posts.specterops.io/an-introduction-to-manual-active-directory-querying-with-dsquery-and-ldapsearch-84943c13d7eb?gi=41b97a644843

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019-10-24	medium	• Legitimate use of the utilities by legitimate user for legitimate reason

Rule Details: PUA - DIT Snapshot Viewer

Detects the use of Ditsnap tool, an inspection tool for Active Directory database, ntds.dit.

Rule ID

```
process_creation_commandline_343
```

Query

```
{'selection': [{'Image|endswith': '\\ditsnap.exe'}, {'CommandLine|contains': 'ditsnap.exe'}], 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,d3b70aad-097e-409c-9df2-450f80dc476b

Author: Furkan Caliskan (@caliskanfurkan_)

Tactics, Techniques, and Procedures

TA0006, T1003.003

References

- https://thedfirreport.com/2020/06/21/snatch-ransomware/
- https://web.archive.org/web/20201124182207/https://github.com/yosqueoy/ditsnap

Severity

75

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020-07-04	high	• Legitimate admin usage

Rule Details: Suspicious Process Patterns NTDS.DIT Exfil

Detects suspicious process patterns used in NTDS.DIT exfiltration.

Rule ID

`process_creation_commandline_344`

Query


```
{'selection_tool': [{'Image|endswith': ['\\NTDSDump.exe', '\\NTDSDumpEx.exe']}, {'Com
mandLine|contains|all': ['ntds.dit', 'system.hiv']}, {'CommandLine|contains': 'NTDSgr
ab.ps1'}], 'selection_oneliner_1': {'CommandLine|contains|all': ['ac i ntds', 'create
 full']}, 'selection_onliner_2': {'CommandLine|contains|all': ['/c copy ', '\\windows
\\ntds\\ntds.dit']}, 'selection_onliner_3': {'CommandLine|contains|all': ['activate i
nstance ntds', 'create full']}, 'selection_powershell': {'CommandLine|contains|all':
['powershell', 'ntds.dit']}, 'set1_selection_ntds_dit': {'CommandLine|contains': 'ntd
s.dit'}, 'set1_selection_image_folder': [{'ParentImage|contains': ['\\apache', '\\tom
cat', '\\AppData\\', '\\Temp\\', '\\Public\\', '\\PerfLogs\\']}, {'Image|contains': [
'\\apache', '\\tomcat', '\\AppData\\', '\\Temp\\', '\\Public\\', '\\PerfLogs\\']}], '
condition': '1 of selection* or all of set1*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,8bc64091-6875-4881-aaf9-7bd25b5dda08

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0006, T1003.003

References

- https://www.ired.team/offensive-security/credential-access-and-credential-dumping/ntds.dit-enumeration
- https://www.n00py.io/2022/03/manipulating-user-passwords-without-mimikatz/
- https://pentestlab.blog/tag/ntds-dit/
- https://github.com/samratashok/nishang/blob/414ee1104526d7057f9adaeee196d91ae447283e/Gather/Copy-VSS.ps1
- https://github.com/zcgonvh/NTDSDumpEx
- https://github.com/rapid7/metasploit-framework/blob/d297adcebb5c1df6fe30b12ca79b161deb71571c/data/post/powershell/NTDSgrab.ps1
- https://blog.talosintelligence.com/2022/08/recent-cyber-attack.html?m=1

Severity

75

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022-03-11	high	• Unknown

Rule Details: Get-ForestTrust with PowerShell

The following analytic detects the execution of the Get-ForestTrust command via PowerShell, commonly used by adversaries to gather domain trust information. This detection leverages data from Endpoint Detection and Response (EDR) agents, focusing on process names and command-line executions. Identifying this activity is crucial as it indicates potential reconnaissance efforts to map out domain trusts, which can inform further attacks. If confirmed

malicious, this activity could allow attackers to understand domain relationships, aiding in lateral movement and privilege escalation within the network.

Rule ID

`process_creation_commandline_345`

Query


```
{'selection1': {'Image|endswith': ['powershell.exe', 'cmd.exe']}, 'selection2': {'CommandLine|contains': 'get-foresttrust'}, 'condition': 'selection1 and selection2'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1482

References

- https://powersploit.readthedocs.io/en/latest/Recon/Get-ForestTrust/

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2024-11-13	medium	• Limited false positives as this requires an active Administrator or adversary to bring in, import, and execute.

Rule Details: Renamed AdFind Execution

Detects the use of a renamed Adfind.exe. AdFind continues to be seen across majority of breaches. It is used to domain trust discovery to plan out subsequent steps in the attack chain.

Rule ID

`process_creation_commandline_346`

Query


```
{'selection_1': {'CommandLine|contains': ['domainlist', 'trustdmp', 'dcmodes', 'adinfo', ' dclist ', 'computer_pwdnotreqd', 'objectcategory=', '-subnets -
```

f', 'name="Domain Admins"', '-
sc u:', 'domainncs', 'dompol', ' oudmp ', 'subnetdmp', 'gpodmp', 'fspdmp', 'users_noe
xpire', 'computers_active', mputers_pwdnotreqd']}, 'selection_2': {'Hashes|contain
s': ['IMPHASH=BCA5675746D13A1F246E2DA3C2217492', 'IMPHASH=53E117A96057EAF19C41380D0E8
7F1C2']}, 'selection_3': {'OriginalFileName': 'AdFind.exe'}, 'filter': {'Image|endswi
th': '\\AdFind.exe'}, 'condition': '1 of selection* and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,df55196f-f105-44d3-a675-e9dfb6cc2f2b

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0007, T1018, T1087.002, T1482, T1069.002

References

- https://www.joeware.net/freetools/tools/adfind/
- https://thedfirreport.com/2020/05/08/adfind-recon/
- https://thedfirreport.com/2021/01/11/trickbot-still-alive-and-well/
- https://www.microsoft.com/security/blog/2021/01/20/deep-dive-into-the-solorigate-second-stage-activation-from-sunburst-to-teardrop-and-raindrop/
- https://social.technet.microsoft.com/wiki/contents/articles/7535.adfind-command-examples.aspx
- https://github.com/center-for-threat-informed-defense/adversary_emulation_library/blob/bf62ece1c679b07b5fb49c4bae947fe24c81811f/fin6/Emulation_Plan/Phase1.md

Severity

75

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022-08-21	high	• Unknown

Rule Details: Enumerating Domain Trusts via NLTEST.EXE

Identifies the use of nltest.exe for domain trust discovery purposes. Adversaries may use this command-line utility to enumerate domain trusts and gain insight into trust relationships, as well as the state of Domain Controller (DC) replication in a Microsoft Windows NT Domain.

Rule ID

`process_creation_commandline_347`

Query

```
{'selection1': {'Image|endswith': '\\nltest.exe'}, 'selection2': {'CommandLine|contains': ['/dclist:', '/dcname:', '/parentdomain', '/domain_trusts', '/bdc_query:']}, 'filter_parent': {'ParentImage|endswith': 'PDQInventoryScanner.exe'}, 'filter_system_users': {'UserId': ['S-1-5-18', 'S-1-5-19', 'S-1-5-20']}, 'condition': 'selection1 and selection2 and (not filter_parent) and (not filter_system_users)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1018, T1482

References

N/A

Severity

25

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/31	low	• Domain administrators may use this command-line utility for legitimate information gathering purposes, but it is not common for environments with Windows Server 2012 and newer.

Rule Details: Potential SPN Enumeration Via Setspn.EXE

Detects service principal name (SPN) enumeration used for Kerberoasting.

Rule ID

`process_creation_commandline_348`

Query

{'selection_pe': [{'Image|endswith': '\\setspn.exe'}], 'selection_cli': {'CommandLine|contains': [' -q ', ' /q ']}, 'selection_cli2': {'CommandLine|contains|all': [' -t ', ' -f ']}, 'condition': 'selection_pe and (selection_cli or selection_cli2)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1558.003

References

- https://web.archive.org/web/20200329173843/https://p16.praetorian.com/blog/how-to-use-kerberoasting-t1208-for-privilege-escalation
- https://www.praetorian.com/blog/how-to-use-kerberoasting-t1208-for-privilege-escalation/?edition=2019

Severity

50

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018-11-14	medium	• Administration activity

Rule Details: HackTool - Mimikatz Execution

Detects well-known mimikatz command line arguments.

Rule ID

`process_creation_commandline_349`

Query

{'selection_tools_name': {'CommandLine|contains': ['DumpCreds', 'mimikatz']}, 'selection_function_names': {'CommandLine|contains': ['::aadcookie', '::detours', '::memssp', '::mflt', '::ncroutemon', '::ngcsign', '::printnightmare', '::skeleton', '::preshutdown', '::mstsc', '::multirdp']}, 'selection_module_names': {'CommandLine|contains': ['rpc::', 'token::', 'crypto::', 'dpapi::', 'sekurlsa::', 'kerberos::', 'lsadump::', 'privilege::', 'process::', 'vault::']}, 'condition': '1 of selection_*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,a642964e-bead-4bed-8910-1bb4d63e3b4d

Author: Teymur Kheirkhabarov, oscd.community, David ANDRE (additional keywords), Tim Shelton

Tactics, Techniques, and Procedures

TA0006, T1003

References

- https://www.slideshare.net/heirhabarov/hunting-for-credentials-dumping-in-windows-environment
- https://tools.thehacker.recipes/mimikatz/modules

Severity

75

Suppression Logic Based On

- computer_name
- event_data.CommandLine
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/08/13	high	• Unlikely

Process Creation Image Rule IDs

Rule Details: Powershell Process Created by Internet Explorer

A Powershell process has been created by Internet Explorer. This can indicate a malicious website has successfully launched an exploit.

Rule ID

`process_creation_image_1`

Query

```
{'selection3': {'ParentImage|contains': 'iexplore.exe'}, 'selection4': {'Image|contains': 'powershell.exe'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Powershell Process Created by Office PowerPoint

A Powershell process has been created by Microsoft Office PowerPoint. This can indicate a malicious document containing a macro or an exploit has been opened by the user.

Rule ID

```
process_creation_image_2
```

Query

```
{'selection3': {'ParentImage|contains': 'POWERPNT.EXE'}, 'selection4': {'Image|contai
ns': 'powershell.exe'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References
N/A

Severity

50

Suppression Logic Based On

- computer_name

- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Executable with Suspicious Extension

An executable was launched with a well-known extension preceding the executable extension. This could be an indication that a user was tricked into executing a malicious program.

Rule ID

```
process_creation_image_5
```

Query

```
{'selection3': {'Image|re': '\\.(jpeg|jpg|png|gif|tiff|ico|zip|rar|pdf)\\.
(exe|msi|scr|hta|bat|hta)$'}, 'selection4': {'CurrentDirectory|re': '(?:\\\\Program F
iles(?:\\(x86\\))?|\\\\PROGRA~
(?:1|2))'}, 'condition': 'selection3 and not selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1036

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Process created by dbgsrv debugger

A known signed debugger software has been detected creating a remote process. This could be used by an attacker trying to bypass whitelisted applications.

Rule ID

`process_creation_image_6`

Query

`{'selection3': {'ParentImage|contains': '\\dbgsrv.exe'}, 'selection4': {'ParentCommandLine|contains': 'clicon='}, 'selection5': {'ParentCommandLine|contains': 'port='}, 'condition': 'selection3 and selection4 and selection5'}`

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Powershell Process Created by Office Word

A Powershell process has been created by Microsoft Office Word. This can indicate a malicious document containing a macro or an exploit has been opened by the user.

Rule ID

`process_creation_image_8`

Query

`{'selection3': {'ParentImage|contains': 'WINWORD.EXE'}, 'selection4': {'Image|contains': 'powershell.exe'}, 'condition': 'selection3 and selection4'}`

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Java Process Spawning Scripting Process

A suspicious process has been created by Java Software. This could be an indication of malicious activity.

Rule ID

`process_creation_image_10`

Query

```
{'selection3': {'ParentImage|re': '\\\\java[w]?
\\.exe'}, 'selection4': {'Image|re': '(?:powershell|wscript|cscript|mshta)\\.exe'}, '
condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1216

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Powershell Process Created by webserver process

A webserver process has created a Powershell session. This could be the result of a successful exploitation of the webserver or the installation of a webshell.

Rule ID

```
process_creation_image_11
```

Query

```
{'selection3': {'Image|contains': 'powershell.exe'}, 'selection4': {'ParentImage|cont
ains': 'w3wp.exe'}, 'selection5': {'ParentImage|contains': 'httpd.exe'}, 'selection6'
: {'ParentImage|contains': 'tomcat6.exe'}, 'selection7': {'ParentImage|contains': 'ng
inx.exe'}, 'selection8': {'ParentImage|contains': 'php-
cgi.exe'}, 'selection9': {'ParentImage|contains': 'tomcat.exe'}, 'condition': 'select
ion3 and (selection4 or selection5 or selection6 or selection7 or selection8 or selec
tion9)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1190

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Process Execution Using pcwutl.dll

A process has been launched using the pcwutl.dll library. This can indicate an attacker is trying to bypass whitelisting technologies.

Rule ID

```
process_creation_image_12
```

Query

```
{'selection3': {'ParentImage|contains': '\\rundll32.exe'}, 'selection4': {'ParentCommandLine|contains': 'pcwutl.dll'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218.011

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows Hacking Tool Detected

A common hacking tool was detected being used on this machine. While hacking tools can be used for System diagnostics during routine maintenance it is also a common indicator of malware performing additional reconnaissance or privilege escalation.

Rule ID

```
process_creation_image_13
```

Query

{'selection3': {'Image|re': '\\\\(?:(?:(?:win32dd|win64dd|wce|mailpv|mdpv|logreader|netpass|iepv|routerpass|pstpass|vncpass|mspass)\\.exe)|WebBrowserPassView|VNCPassView|Cachedump|Fgdump|gsecdump|Lslsass|mimikatz|pwdump|getlsasrvaddr|timestomp|BulletsPassView|WebBrowserPassView|WirelessKeyView|Chromepass|dialupass|lookpass|Fluxay5Beta1|pstpassword|OperaPassView|routerpassview|PasswordFox)'}, 'condition': 'selection3'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Executable launched using Windows PresentationHost tool

Windows Presentation Foundation Host (PresentationHost.exe) enables applications to be hosted in compatible browsers. This tool can bypass code integrity enforcement in Windows Defender Application Control.

Rule ID

process_creation_image_14

Query

{'selection3': {'ParentImage|contains': '\\PresentationHost.exe'}, 'selection4': {'Image|re': '\\\\(?:iexplore|chrome|firefox)\\.exe'}, 'condition': 'selection3 and not selection4'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Executable Launched from System Volume Information

Running executables from the System Volume Information folder is a common technique used by malware in order to hide itself. This could be an indication of malicious activity.

Rule ID

```
process_creation_image_15
```

Query

```
{'selection3': {'Image|contains': ':\\System Volume Information\\'}, 'condition': 'selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1036

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Powershell Process Created by Office Excel

A Powershell process has been created by Microsoft Office Excel. This can indicate a malicious document containing a macro or an exploit has been opened by the user.

Rule ID

```
process_creation_image_16
```

Query

```
{'selection3': {'ParentImage|contains': 'EXCEL.EXE'}, 'selection4': {'Image|contains'
: 'powershell.exe'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Detected scripting process spawned by WinRAR

A scripting process executed with wscript.exe, cscript.exe or mshta.exe was directly executed from WinRAR. This behavior is commonly executed by packed malware.

Rule ID

```
process_creation_image_17
```

Query

```
{'selection3': {'ParentImage|contains': '\\WinRAR.exe'}, 'selection4': {'Image|re': '\\\\(wscript|cscript|mshta)\\.exe$'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: RDP process spawning a suspicious process

An unauthenticated attacker could connect to the target system using RDP and send specially crafted requests. This vulnerability could execute arbitrary code on the target system.

Rule ID

```
process_creation_image_18
```

Query

```
{'selection3': {'ParentImage|contains': '\\svchost.exe'}, 'selection4': {'ParentCommandLine|contains': 'svchost.exe -
k termsvcs'}, 'selection5': {'Image|contains': '\\rdpclip.exe'}, 'condition': 'selection3 and selection4 and not selection5'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0008, T1210

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows UAC bypass - UACME tool

User Account Control Bypass activity was detected. This can be due to either a regular operation or because an attacker is trying to escalate privileges.

Rule ID

```
process_creation_image_19
```

Query

```
{'selection3': {'ParentImage|contains': '\\dism.exe'}, 'selection4': {'ParentCommandLine|contains': '.xml'}, 'selection5': {'Image|re': '\\\\appdata\\\\.*\\\\dismhost\\.exe'}, 'selection6': {'Image|contains': '\\wusa.exe'}, 'selection7': {'CommandLine|contains': '/quiet'}, 'selection8': {'ParentImage|contains': '\\explorer.exe'}, 'selection10': {'ParentImage|contains': 'dccw.exe'}, 'selection11': {'ParentImage|contains': '\\slui.exe'}, 'condition': '((selection3 and selection4 and not selection5) or (selection6 and selection7 and not selection8) or selection10 or selection11)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1548.002

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: MS Exchange transport agent backdoor

Transport agents let you install custom software on an Exchange server. This could be used by malware to gain persistence and install backdoors.

Rule ID

```
process_creation_image_20
```

Query

```
{'selection3': {'ParentImage|contains': '\\EdgeTransport.exe'}, 'condition': 'selecti
on3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1129

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Executable launched using Synaptics Touchpad Enhancements tool

Synaptics Touchpad Enhancements utility allows you to run binaries in the system. This tool can bypass code integrity enforcement in Windows Defender Application Control.

Rule ID

`process_creation_image_21`

Query

```
{'selection3': {'ParentImage|contains': '\\SynTPEnh.exe'}, 'selection4': {'ParentCommandLine|contains': '/SHELLEXEC'}, 'selection5': {'Image|contains': '\\SynTPHelper.exe'}, 'selection6': {'Image|contains': '\\WerFault.exe'}, 'condition': 'selection3 and selection4 and not (selection5 or selection6)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: SharPyShell Process Execution Detected

SharPyShell is a known hacking tool that is able to deploy a shell into the ASP.NET server. This shell can be controlled remotely from a malicious server. A process with these characteristics has been detected, what is an indicator of compromise by SharPyShell.

Rule ID

`process_creation_image_22`

Query

```
{'selection3': {'SubjectDomainName': 'IIS APPPOOL'}, 'selection4': {'SubjectUserName'
: 'sharpy'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1505.003

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Suspicious Process Created by mshta.exe

A suspicious process process has been created by mshta.exe. This can indicate an attacker is using built-in Windows functionality to perform malicious activity.

Rule ID

`process_creation_image_24`

Query

```
{'selection3': {'ParentImage|contains': '\\mshta.exe'}, 'selection4': {'Image|re': '\
\\(?:powershell|
(?:w|c)script|cmd)\\.exe'}, 'selection5': {'CurrentDirectory|re': '(?:\\\\Program Fil
es(?:\\(x86\\))?|\\\\PROGRA~
(?:1|2))'}, 'condition': 'selection3 and selection4 and not selection5'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218.005

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Java Process Spawning WMIC

The wmic.exe process was executed by Java Software. This could be an indication of malicious activity.

Rule ID

```
process_creation_image_25
```

Query

```
{'selection3': {'ParentImage|re': '\\\\java[w]?
\\.exe'}, 'selection4': {'Image|contains': '\\wmic.exe'}, 'condition': 'selection3 an
d selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1047

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Process Spawning Fodhelper

A process has spawned Fodhelper.exe. There is a known UAC bypass that can be used to escalate privileges.

Rule ID

`process_creation_image_26`

Query

```
{'selection3': {'ParentImage|re': '\\\\(?:powershell|(?:w|c)script|cmd)\\.exe'}, 'selection4': {'Image|contains': '\\fodhelper.exe'}, 'condition': 'selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1548.002

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Executable Launched from Recycle Bin

Running executables from the Recycle Bin folder is a common technique used by malware in order to hide itself. This could be an indication of malicious activity.

Rule ID

`process_creation_image_28`

Query


```
{'selection3': {'Image|contains': ':\\$Recycle.Bin\\'}, 'selection4': {'Image|contains': ':\\Recycler\\'}, 'condition': '(selection3 or selection4)'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1036

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Suspicious Process Created by Notepad or Calculator

A potentially suspicious process was started by either Notepad or Calculator. This could be the result of malicious file being opened by the user or a proof-of-concept being tested.

Rule ID

`process_creation_image_31`

Query


```
{'selection3': {'ParentImage|contains': '\\NOTEPAD.EXE'}, 'selection4': {'Image|re': '\\\\
(?:notepad|ctfmon|Microsoft\\.Uev\\.SyncController)\\.exe'}, 'selection5': {'CommandL
```

ine|contains': '\\DRIVERS\\'}, 'selection6': {'ParentImage|contains': '\\CALC.EXE'}, 'selection7': {'Image|contains': 'CALC.EXE'}, 'selection8': {'Image|contains': ':\\Program Files'}, 'selection9': {'Image|contains': '":\\Windows\\splwow64.exe"'}, 'condition': '((selection3 and not (selection4 or selection5)) or (selection6 and not selection7)) and not (selection8 or selection9)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1203

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Suspicious Process Created by Microsoft Office Application

A potentially suspicious process was started by a Microsoft Office application. This can indicate a malicious document containing a macro or an exploit has been opened by the user.

Rule ID

process_creation_image_32

Query

{'selection3': {'ParentImage|re': '(?:winword|excel|powerpnt|msaccess|infopath)\\.exe'}, 'selection6': {'Image|re': '(?:cmd|svchost|wscript|notepad|rundll32|schtasks|ntvdm|bitsadmin|msiexec|regsvr32|certutil|mshta|[A-Z]:\\\\Users\\\\.*)\\.exe$'}, 'selection4': {'Image|contains': '\\AppData\\'}, 'selection5': {'CommandLine|contains': '\\DRIVERS\\'}, 'condition': 'selection3 and selection6 and not (selection4 or selection5)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1203

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Windows mofcomp with suspicious file extension

The Managed Object Format (MOF) compiler parses a file containing MOF statements and adds the classes and class instances defined in the file to the WMI repository. Attackers could use this tool to compile malicious WMI classes.

Rule ID

```
process_creation_image_33
```

Query

```
{'selection3': {'Image': '\\mofcomp.exe'}, 'selection5': {'CommandLine|re': '\\.mof'}
, 'condition': 'selection3 and not selection5'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1047

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Process Creation Parent Child Rule IDs

Rule Details: MSHTA Spawning Windows Shell

It is suspicious for the mshta process to launch a Windows command line executable.

Rule ID

`parent_child_1`

Query


```
{'selection': {'ParentImage|endswith': '\\mshta.exe'}, 'selection2': [{'Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\wscript.exe', '\\cscript.exe', '\\sh.exe', '\\bash.exe', '\\reg.exe', '\\regsvr32.exe']}, {'Image|contains': ['\\BITSADMIN']}], 'condition': 'selection and selection2'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,03cc0c25-389f-4bf8-b48d-11878079f1ca

Author: Michael Haag

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1218.005

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/01/16	high	• Printer software / driver installations • HP software

Rule Details: New Lolbin Process by Office Applications

A Microsoft Office application that launches a new LOLBin process is very suspicious.

Rule ID

`parent_child_2`

Query

```
{'selection1': {'Image|endswith': ['\\regsvr32.exe', '\\rundll32.exe', '\\msiexec.exe', '\\mshta.exe', '\\verclsid.exe']}, 'selection2': {'ParentImage|endswith': ['\\winword.exe', '\\excel.exe', '\\powerpnt.exe']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,23daeb52-e6eb-493c-8607-c4f0246cb7d8

Author: Vadim Khrykov (ThreatIntel), Cyb3rEng (Rule), Michael Haag, Christopher Peacock @securepeacock (Update), SCYTHE @scythe_io (Update)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1204.002, T1047, TA0005, T1218.010

References

- https://thedfirreport.com/2021/03/29/sodinokibi-aka-revil-ransomware/
- https://github.com/vadim-hunter/Detection-Ideas-Rules/blob/main/Threat%20Intelligence/The%20DFIR%20Report/20210329_Sodinokibi_(aka_REvil)_Ransomware.yaml

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/08/23	high	• Unknown

Rule Details: Droppers Exploiting CVE-2017-11882

This is indicative an attempt to exploit vulnerabilities described in CVE-2017-11882, in which exploits often start EQNEDT32.EXE and other sub-processes such as mshta.exe.

Rule ID

`parent_child_3`

Query

```
{'selection': {'ParentImage|endswith': '\\EQNEDT32.EXE'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,678eb5f4-8597-4be6-8be7-905e4234b53a

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0001, T1566.001, XTA0001, XT1002, TA0002, T1203, T1204.002

References

- https://www.hybrid-analysis.com/sample/2a4ae284c76f868fc51d3bb65da8caa6efacb707f265b25c30f34250b76b7507?environmentId=100

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/11/23	critical	• unknown

Rule Details: Exploit for CVE-2017-8759

As described in CVE-2017-8759, launch of csc.exe from Winword may be an exploit attempt.

Rule ID

parent_child_4

Query



{'selection': {'ParentImage|endswith': '\\WINWORD.EXE', 'Image|endswith': '\\csc.exe'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,fdd84c68-a1f6-47c9-9477-920584f94905

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0001, T1566.001, XTA0001, XT1002, TA0002, T1203, T1204.002

References

- https://www.hybrid-analysis.com/sample/0b4ef455e385b750d9f90749f1467eaf00e46e8d6c2885c260e1b78211a51684?environmentId=100

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/09/15	critical	• Unknown

Rule Details: Suspicious Shells Spawn by WinRM

A WinRM host process that launches a shell is suspicious.

Rule ID

parent_child_5

Query

{'selection': {'ParentImage': '*\\wsmprovhost.exe', 'Image': ['*\\cmd.exe', '*\\sh.exe', '*\\bash.exe', '*\\powershell.exe', '*\\schtasks.exe', '*\\certutil.exe', '*\\whoami.exe', '*\\bitsadmin.exe']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,5cc2cda8-f261-4d88-a2de-e9e193c86716

Author: Andreas Hunkeler (@Karneades), Markus Neis

Tactics, Techniques, and Procedures

TA0001, T1190, XTA0001, XT1002

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/05/20	high	• Legitimate WinRM usage

Rule Details: Suspicious Shells Spawned by Java

A Java host process that launches certain child processes, particularly a shell process, is suspicious and may indicate exploitation such as log4j.

Rule ID

`parent_child_6`

Query

```
{'selection': {'ParentImage|endswith': '\\java.exe', 'Image|endswith': ['\\sh.exe', '\\bash.exe', '\\powershell.exe', '\\schtasks.exe', '\\certutil.exe', '\\whoami.exe', '\\bitsadmin.exe', '\\wscript.exe', '\\cscript.exe', '\\scrcons.exe', '\\regsvr32.exe', '\\hh.exe', '\\wmic.exe', '\\mshta.exe', '\\rundll32.exe', '\\forfiles.exe', '\\scriptrunner.exe', '\\mftrace.exe', '\\AppVLP.exe', '\\curl.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,0d34ed8b-1c12-4ff2-828c-16fc860b766d

Author: Andreas Hunkeler (@Karneades), Florian Roth

Tactics, Techniques, and Procedures

XTA0001, XT1002

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/17	high	• Legitimate calls to system binaries • Company specific internal usage

Rule Details: WMI Backdoor Exchange Transport Agent

This indicates that a WMI event filter has been used to create a backdoor in an Exchange Transport Agent.

Rule ID

`parent_child_7`

Query

```
{'selection': {'ParentImage|endswith': '\\EdgeTransport.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,797011dc-44f4-4e6f-9f10-a8ceefbe566b

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0003, T1546.003

References

- https://twitter.com/cglyer/status/1182389676876980224
- https://twitter.com/cglyer/status/1182391019633029120

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/11	critical	• Unknown

Rule Details: Exploit for CVE-2017-0261

Launch of FLTLDR.exe from Winword is uncommon and indicative of exploits described in CVE-2017-0261 and CVE-2017-0262.

Rule ID

`parent_child_8`

Query

```
{'selection': {'ParentImage|endswith': '\\WINWORD.EXE', 'Image|contains': '\\FLTLDR.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,864403a1-36c9-40a2-a982-4c9a45f7d833

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0001, T1566.001, XTA0001, XT1002, TA0002, T1203, T1204.002

References

- https://www.fireeye.com/blog/threat-research/2017/05/eps-processing-zero-days.html

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/02/22	medium	• Several false positives identified, check for suspicious file names or locations (e.g. Temp folders)

Rule Details: Exploited CVE-2020-10189 Zoho ManageEngine

This is indicative of CVE-2020-10189 which describes exploitation of Zoho ManageEngine Desktop Central - Java Deserialization.

Rule ID

`parent_child_9`

Query

```
{'selection': {'ParentImage|endswith': 'DesktopCentral_Server\\jre\\bin\\java.exe', '
Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\bitsadmin.exe']}, 'condition':
'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,846b866e-2a57-46ee-8e16-85fa92759be7

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0001, T1190, XTA0001, XT1002, TA0002, T1059

References

- https://www.fireeye.com/blog/threat-research/2020/03/apt41-initiates-global-intrusion-campaign-using-multiple-exploits.html

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/03/25	critical	• Unknown

Rule Details: Microsoft Office Product Spawning Windows Shell

It is suspicious for a Microsoft Office application to launch a Windows command and scripting interpreter executable.

Rule ID

`parent_child_10`

Query


```
{'selection': {'ParentImage|endswith': ['\\WINWORD.EXE', '\\EXCEL.EXE', '\\POWERPNT.exe', '\\MSPUB.exe', '\\VISIO.exe', '\\MSACCESS.EXE', '\\EQNEDT32.EXE'], 'Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\wscript.exe', '\\cscript.exe', '\\sh.exe', '\\bash.exe', '\\scrcons.exe', '\\schtasks.exe', '\\regsvr32.exe', '\\hh.exe', '\\wmic.exe', '\\mshta.exe', '\\rundll32.exe', '\\msiexec.exe', '\\forfiles.exe', '\\scriptrunner.exe', '\\mftrace.exe', '\\AppVLP.exe', '\\svchost.exe', '\\msbuild.exe']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,438025f9-5856-4663-83f7-52f878a70a50

Author: Florian Roth (Nextron Systems), Markus Neis, FPT.EagleEye Team, Vadim Khrykov, Cyb3rEng, Michael Haag, Christopher Peacock @securepeacock, @scythe_io

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1204.002

References

- https://www.hybrid-analysis.com/sample/465aabe132ccb949e75b8ab9c5bda36d80cf2fd503d52b8bad54e295f28bbc21?environmentId=100
- https://mgreen27.github.io/posts/2018/04/02/DownloadCradle.html

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/04/06	high	• unknown

Rule Details: Suspicious Parent of Csc.exe

It is considered suspicious when certain parent processes (such as wscript or mshta) have launched cwc.exe.

Rule ID

```
parent_child_11
```

Query

```
{'selection': {'Image|endswith': '\\csc.exe', 'ParentImage|endswith': ['\\wscript.exe', '\\cscript.exe', '\\mshta.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b730a276-6b63-41b8-bcf8-55930c8fc6ee

Author: Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems), X__Junior (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1059, TA0005, T1218.005, T1027.004

References

- https://twitter.com/SBousseaden/status/1094924091256176641

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/02/11	high	• Unknown

Rule Details: MSHTA Spawned by SVCHOST

This is indicative of LethalHTA (a lateral movement technique).

Rule ID

```
parent_child_12
```

Query

```
{'selection': {'ParentImage|endswith': '\\svchost.exe', 'Image|endswith': '\\mshta.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ed5d72a6-f8f4-479d-ba79-02f6a80d7471

Author: Markus Neis

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1218.005

References

- https://codewhitesec.blogspot.com/2018/07/lethalhta.html

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/06/07	high	• Unknown

Rule Details: Suspicious HWP Sub Processes

Certain sub-processes of the Hangul Word Processor (Hanword) application may indicate an exploitation attempt.

Rule ID

```
parent_child_13
```

Query

```
{'selection': {'ParentImage|endswith': '\\Hwp.exe', 'Image|endswith': '\\gbb.exe'}, '
condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,023394c4-29d5-46ab-92b8-6a534c6f447b

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0001, T1566.001, XTA[illegible]1, XT1002, TA0002, T1203, T1059.003

References

- https://www.securitynewspaper.com/2016/11/23/technical-teardown-exploit-malware-hwp-files/
- https://twitter.com/cyberwar_15/status/1187287262054076416
- https://blog.alyac.co.kr/1901
- https://en.wikipedia.org/wiki/Hangul_(word_processor)

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	high	• Unknown

Rule Details: Time Travel Debugging Utility Usage

Use of the Time Travel Debugging Utility (tttracer.exe) is suspicious since adversaries can use it to run malicious processes and dump processes, such as lsass.exe.

Rule ID

```
parent_child_14
```

Query

```
{'selection': {'ParentImage|endswith': '\\tttracer.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,0b4ae027-2a2d-4b93-8c7e-962caaba5b2a

Author: Ensar Şamil, @sblmsrsn, @oscd_initiative

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1218, TA0006, T1003.001

References

- https://lolbas-project.github.io/lolbas/Binaries/Tttracer/
- https://twitter.com/mat[illegible]ation/status/1196390321783025666
- https://twitter.com/oulusoyum/status/1191329746069655553

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/06	high	• Legitimate usage by software developers/testers

Rule Details: CMSTP Execution Process Creation

This is an indicator of an attempt to use Microsoft Connection Manager Profile to bypass UAC.

Rule ID

```
parent_child_15
```

Query

```
{'selection': {'ParentImage|endswith': '\\cmstp.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7d4cdc5a-0076-40ca-aac8-f7e714570e47

Author: Nik Seetharaman

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1218.003

References

- https://web.archive.org/web/20190720093911/http://www.endurant.io/cmstp/detecting-cmstp-enabled-code-execution-and-uac-bypass-with-sysmon/

Severity

74

Suppression Logic Based On

- computer_name

- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2018/07/16	high	• Legitimate CMSTP use (unlikely in modern enterprise environments)

Rule Details: Winnti Malware HK University Campaign

This is a characteristic of Winnti malware as reported in a Dec/Jan 2020 campaign against Hong Kong universities.

Rule ID

`parent_child_16`

Query


```
{'selection2': {'ParentImage|startswith': 'C:\\ProgramData\\DRM', 'Image|endswith': '\\wmplayer.exe'}, 'selection3': {'ParentImage|endswith': '\\Test.exe', 'Image|endswith': '\\wmplayer.exe'}, 'selection4': {'Image': 'C:\\ProgramData\\DRM\\CLR\\CLR.exe'}, 'selection5': {'ParentImage|startswith': 'C:\\ProgramData\\DRM\\Windows', 'Image|endswith': '\\SearchFilterHost.exe'}, 'condition': '1 of selection*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,3121461b-5aa0-4a41-b910-66d25524edbb

Author: Florian Roth (Nextron Systems), Markus Neis

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0003, T1574.002

References

- https://www.welivesecurity.com/2020/01/31/winnti-group-targeting-universities-hong-kong/

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/02/01	critical	• Unlikely

Rule Details: Shells Spawned by Web Servers

A web server process that runs a shell process indicates a possible placement of a web shell for malicious use.

Rule ID

```
parent_child_17
```

Query

```
{'selection': {'ParentImage|endswith': ['\\w3wp.exe', '\\httpd.exe', '\\nginx.exe', '\\php-
cgi.exe', '\\tomcat.exe', '\\UMWorkerProcess.exe', '\\ws_TomcatService.exe'], 'Image|
endswith': ['\\cmd.exe', '\\sh.exe', '\\bash.exe', '\\powershell.exe', '\\bitsadmin.e
xe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,8202070f-edeb-4d31-a010-a26c72ac5600

Author: Thomas Patzke, Florian Roth (Nextron Systems), Zach Stanford @svch0st, Tim Shelton, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0001, T1190, XTA0001, XT1002, TA0003, T1505.003

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/01/16	high	• Particular web applications may spawn a shell process legitimately

Rule Details: Sdclt Child Processes

The sdclt process creating a child process indicates a possible attempt to bypass UAC.

Rule ID



`parent_child_18`

Query

`{'selection': {'ParentImage|endswith': '\\sdclt.exe'}, 'condition': 'selection'}`

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,da2738f2-fadb-4394-afa7-0a0674885afa

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1548.002

References

- https://github.com/OTRF/detection-hackathon-apt29/issues/6

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/05/02	medium	• unknown

Rule Details: LOLBins Process Creation with WmiPrvse

A LOLBin process created by wmiprvse is suspicious.

Rule ID

`parent_child_19`

Query

`{'selection1': {'Image|endswith': ['\\regsvr32.exe', '\\rundll32.exe', '\\msiexec.exe', '\\mshta.exe', '\\verclsid.exe']}, 'selection2': {'ParentImage|endswith': '\\wbem\\WmiPrvSE.exe'}, 'condition': 'selection1 and selection2'}`

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,8a582fe2-0882-4b89-a82a-da6b2dc32937

Author: Vadim Khrykov (ThreatIntel), Cyb3rEng, Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1204.002, T1047, TA0005, T1218.010

References

- https://thedfirreport.com/2021/03/29/sodinokibi-aka-revil-ransomware/
- https://github.com/vadim-hunter/Detection-Ideas-Rules/blob/main/Threat%20Intelligence/The%20DFIR%20Report/20210329_Sodinokibi_(aka_REvil)_Ransomware.yaml

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/08/23	high	• Unknown

Rule Details: MMC Spawning Windows Shell

It is suspicious for MMC to launch a Windows command-line executable.

Rule ID

```
parent_child_20
```

Query

```
{'selection': {'ParentImage|endswith': '\\mmc.exe'}, 'selection2': [{'Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\wscript.exe', '\\cscript.exe', '\\sh.exe', '\\bash.exe', '\\reg.exe', '\\regsvr32.exe']}, {'Image|contains': ['\\BITSADMIN']}], 'condition': 'selection and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,05a2ab7e-ce11-4b63-86db-ab32e763e11d

Author: Karneades, Swisscom (CSIRT

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0008, T1021.003

References

- https://enigma0x3.net/2017/01/05/lateral-movement-using-the-mmc20-application-com-object/

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/08/05	high	N/A

Rule Details: Suspicious Shells Spawn by Java Utility Keytool

It is suspicious for the Java utility keytool process to launch a shell and indicates potential exploitations, such as adselfservice.

Rule ID

`parent_child_21`

Query

```
{'selection': {'ParentImage|endswith': '\\keytool.exe', 'Image|endswith': ['\\cmd.exe', '\\sh.exe', '\\bash.exe', '\\powershell.exe', '\\schtasks.exe', '\\certutil.exe', '\\whoami.exe', '\\bitsadmin.exe', '\\wscript.exe', '\\cscript.exe', '\\scrcons.exe', '\\regsvr32.exe', '\\hh.exe', '\\wmic.exe', '\\mshta.exe', '\\rundll32.exe', '\\forfiles.exe', '\\scriptrunner.exe', '\\mftrace.exe', '\\AppVLP.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,90fb5e62-ca1f-4e22-b42e-cc521874c938

Author: Andreas Hunkeler (@Karneades)

Tactics, Techniques, and Procedures

XTA0001, XT1002

References

- https://redcanary.com/blog/intelligence-insights-december-2021
- https://www.synacktiv.com/en/publications/how-to-exploit-cve-2021-40539-on-manageengine-adselfservice-plus.html

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/12/22	high	• unknown

Rule Details: UAC Bypass via Windows Event Viewer

A UAC bypass attempt to run code with elevated permissions may be indicated when eventvwr.exe launches mmc.exe or WerFault.exe.

Rule ID

```
parent_child_22
```

Query

```
{'methprocess': {'ParentImage|endswith': '\\eventvwr.exe'}, 'filterprocess': {'Image': ['?:\\Windows\\SysWOW64\\mmc.exe', '?:\\Windows\\System32\\mmc.exe', '?:\\Windows\\SysWOW64\\WerFault.exe', '?:\\Windows\\System32\\WerFault.exe']}, 'condition': 'methprocess and not filterprocess'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,be344333-921d-4c4d-8bb8-e584cf584780

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1548.002

References

- https://enigma0x3.net/2016/08/15/fileless-uac-bypass-using-eventvwr-exe-and-registry-hijacking/
- https://www.hybrid-analysis.com/sample/e122bc8bf291f15cab182a5d2d27b8db1e7019e4e96bb5cdbd1dfe7446f3f51f?environmentId=100

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2017/03/19	critical	• unknown

Rule Details: Malicious PE Execution by Microsoft Visual Studio Debugger

The MS VS Just-In-Time Debugger (vsjitdebugger.exe), which is a signed/verified binary, can be exploited to launch malicious code.

Rule ID

`parent_child_23`

Query

```
{'selection': {'ParentImage|endswith': '\\vsjitdebugger.exe'}, 'reduction1': {'Image|endswith': '\\vsimmersiveactivatehelper*.exe'}, 'reduction2': {'Image|endswith': '\\devenv.exe'}, 'condition': 'selection and not (reduction1 or reduction2)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,15c7904e-6ad1-4a45-9b46-5fb25df37fd2

Author: Agro (@agro_sev), Ensar Şamil (@sblmsrsn), oscd.community

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1218

References

- https://twitter.com/pabraeken/status/990758590020452353
- https://github.com/LOLBAS-Project/LOLBAS/blob/master/yml/OtherMSBinaries/Vsjitdebugger.yml

- https://docs.microsoft.com/en-us/visualstudio/debugger/debug-using-the-just-in-time-debugger?view=vs-201

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/14	medium	• the process spawned by vsjitdebugger.exe is uncommon.

Rule Details: CVE-2021-26857 Exchange Exploitation

The CVE-2021-26857 vulnerability is indicated when abnormal subprocesses are launched from Microsoft Exchange Server's Unified Messaging service.

Rule ID

`parent_child_24`

Query

```
{'selection': {'ParentImage|endswith': '\\UMWorkerProcess.exe'}, 'filter': {'Image|endswith': ['\\wermgr.exe', '\\WerFault.exe']}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,cd479ccc-d8f0-4c66-ba7d-e06286f3f887

Author: Bhabesh Raj

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1203

References

- https://www.microsoft.com/security/blog/2021/03/02/hafnium-targeting-exchange-servers/

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2021/03/03	critical	• Unknown

Rule Details: MS Office Product Spawning Exe in User Dir

It is suspicious for a Microsoft Office application to launch an executable in the Users directory.

Rule ID

```
parent_child_25
```

Query

```
{'selection': {'ParentImage|endswith': ['\\WINWORD.EXE', '\\EXCEL.EXE', '\\POWERPNT.exe', '\\MSPUB.exe', '\\VISIO.exe'], 'Image|startswith': 'C:\\users\\', 'Image|endswith': '.exe'}, 'filter': {'Image|endswith': '\\Teams.exe'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,aa3a6f94-890e-4e22-b634-ffdfd54792cc

Author: Jason Lynch

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1204.002

References

- https://blog.morphisec.com/fin7-not-finished-morphisec-spots-new-campaign

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/04/02	high	• unknown

Rule Details: Execution via stordiag.exe

The stordiag.exe process launch processes such as systeminfo.exe from a non-standard path is suspicious.

Rule ID

`parent_child_26`

Query


```
{'selection': {'ParentImage|endswith': '\\stordiag.exe', 'Image|endswith': ['\\schtasks.exe', '\\systeminfo.exe', '\\fltmc.exe']}, 'filter': {'ParentImage|startswith': 'c:\\windows\\system32\\', 'c:\\windows\\syswow64\\']}, 'condition': 'selection and not filter'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,961e0abb-1b1e-4c84-a453-aafe56ad0d34

Author: Austin Songer (@austinsonger)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1218

References

- https://strontic.github.io/xcyclopedia/library/stordiag.exe-1F08FC87C373673944F6A7E8B18CD845.html
- https://twitter.com/eral4m/status/1451112385041911809

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/10/21	high	• Legitimate usage of stordiag.exe.

Rule Details: Always Install Elevated MSI Spawned Cmd And Powershell

Detects Windows Installer service (msiexec.exe) spawning "cmd" or "powershell".

Rule ID



```
parent_child_27
```

Query

```
{'selection_img': {'Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\pwsh.exe']}, 'selection_parent': {'ParentImage|contains|all': ['\\Windows\\Installer\\', 'msi'], 'ParentImage|endswith': ['tmp']}, 'filter': {'CommandLine|contains': '\\program files\\aella\\bins'}, 'condition': 'all of selection_* and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,1e53dd56-8d83-4eb4-a43e-b790a05510aa

Author: Teymur Kheirkhabarov (idea), Mangatas Tondang (rule), oscd.community

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1548.002

References

- https://image.slidesharecdn.com/kheirkhabarovoffzonefinal-181117201458/95/hunting-for-privilege-escalation-in-windows-environment-50-638.jpg

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/13	medium	• Penetration test

Rule Details: Wsreset UAC Bypass

The Wsreset.exe tool can be used to reset the Windows Store to bypass UAC.

Rule ID

```
parent_child_28
```

Query

```
{'selection': {'ParentImage|endswith': ['\\WSreset.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,bdc8918e-a1d5-49d1-9db7-ea0fd91aa2ae

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1548.002

References

- https://lolbas-project.github.io/lolbas/Binaries/Wsreset/
- https://www.activecyber.us/activelabs/windows-uac-bypass
- https://twitter.com/ReaQta/status/1222548288731217921

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/01/30	high	• Unknown sub processes of Wsreset.exe

Rule Details: DNS RCE CVE-2020-1350

This indicates possible exploitation of a DNS RCE bug, as described in CVE-2020-1350.

Rule ID

`parent_child_29`

Query

```
{'selection': {'ParentImage|endswith': '\\System32\\dns.exe'}, 'filter': {'Image|endswith': ['\\System32\\werfault.exe', '\\System32\\conhost.exe', '\\System32\\dnscmd.exe', '\\System32\\dns.exe']}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,b5281f31-f9cc-4d0d-95d0-45b91c45b487

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0001, T1190, XTA0001, XT1002, TA0002, T1569.002

References

- https://research.checkpoint.com/2020/resolving-your-way-into-domain-admin-exploiting-a-17-year-old-bug-in-windows-dns-servers/

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/07/15	critical	• Unknown but benign sub processes of the Windows DNS service dns.exe

Rule Details: ScreenConnect Backstage Mode Anomaly

This indicates the use of Backstage mode of the ScreenConnect client, which is suspicious.

Rule ID

```
parent_child_30
```

Query

```
{'selection': {'ParentImage|endswith': '\\ScreenConnect.ClientService.exe', 'Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\pwsh.exe']}, 'selection_cli': {'CommandLine|contains': '\\TEMP\\ScreenConnect\\'}, 'condition': 'selection and selection_cli'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0011, T1219

References

- https://www.mandiant.com/resources/telegram-malware-iranian-espionage

- https://docs.connectwise.com/ConnectWise_Control_Documentation/Get_started/Host_client/View_menu/Backstage_mode

Severity

50

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/02/25	medium	• Case in which administrators are allowed to use ScreenConnect's Backstage mode

Rule Details: Suspicious LSASS Process Clone

This is a suspicious LSASS process clone, which could be a sign of process dumping activity.

Rule ID

`parent_child_31`

Query

```
{'selection': {'Image|endswith': '\\Windows\\System32\\lsass.exe', 'ParentImage|endswith': '\\Windows\\System32\\lsass.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,c8da0dfd-4ed0-4b68-962d-13c9c884384e

Author: Florian Roth (Nextron Systems), Samir Bousseaden

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0006, T1003.001

References

- https://www.matteomalvica.com/blog/2019/12/02/win-defender-atp-cred-bypass/
- https://twitter.com/Hexacorn/status/1420053502554951689
- https://twitter.com/SBousseaden/status/1464566846594691073?s=20

Severity

80

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/11/27	critical	• Unknown

Rule Details: Visual Basic Command Line Compiler Usage

Use of vbc.exe with child process cvtres.exe (Windows Resource to Object Converter) should not be seen in an enterprise environment.

Rule ID

`parent_child_32`

Query

```
{'selection': {'ParentImage|endswith': '\\vbc.exe', 'Image|endswith': '\\cvtres.exe'}
, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7b10f171-7f04-47c7-9fa2-5be43c76e535

Author: Ensar Şamil, @sblmsrsn, @oscd_initiative

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1027.004

References

- https://lolbas-project.github.io/lolbas/Binaries/Vbc/

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/07	high	• Utilization of this tool should not be seen in enterprise environment

Rule Details: Suspicious Service Run-time Directory

The services or svchost process running in a non-standard directory is suspicious.

Rule ID

```
parent_child_33
```

Query

```
{'selection': {'Image|contains': ['\\Users\\Public\\', '\\$Recycle.bin', '\\Users\\All Users\\', '\\Users\\Default\\', '\\Users\\Contacts\\', '\\Users\\Searches\\', 'C:\\Perflogs\\', '\\config\\systemprofile\\', '\\Windows\\Fonts\\', '\\Windows\\IME\\', '\\Windows\\addins\\'], 'ParentImage|endswith': ['\\services.exe', '\\svchost.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,883faa95-175a-4e22-8181-e5761aeb373c

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1202

References

- https://blog.truesec.com/2021/03/07/exchange-zero-day-proxylogon-and-hafnium/

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/03/09	high	• Unknown

Rule Details: Mshta Spawning Windows Shell

The mshta.exe process launching a command shell process is suspicious.

Rule ID

parent_child_34

Query

{'selection': {'ParentImage|endswith': '\\mshta.exe', 'Image|endswith': ['\\powershell.exe', '\\cmd.exe', '\\WScript.exe']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,772bb24c-8df2-4be0-9157-ae4dfa794037

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1059, TA0005, T1218

References

- https://app.any.run/tasks/f0fac90f-84ac-4faa-b5b2-f4353c388969/#
- https://app.any.run/tasks/9c0f37bc-867a-4314-b685-e101566766d7/

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/06/28	high	• Unknown

Rule Details: Bypass UAC via Fodhelper.exe

This could indicate the use of Fodhelper.exe to bypass User Account Control. Adversaries may use this technique to run privileged processes.

Rule ID

parent_child_35

Query

{'selection': {'ParentImage|endswith': '\\fodhelper.exe'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7f741dcf-fc22-4759-87b4-9ae8376676a2

Author: E.M. Anhaus (originally from Atomic Blue Detections, Tony Lambert), oscd.community

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1548.002

References

- https://eqllib.readthedocs.io/en/latest/analytics/e491ce22-792f-11e9-8f5c-d46d6d62a49e.html
- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1548.002/T1548.002.md

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	high	• Legitimate use of fodhelper.exe utility by legitimate user

Rule Details: Suspicious Serv-U Process Pattern

Certain child processes launched by Serve-U.exe indicate possible exploitation.

Rule ID

`parent_child_36`

Query

```
{'selection': {'ParentImage|endswith': '\\Serv-U.exe', 'Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\wscript.exe', '\\cscript.exe', '\\sh.exe', '\\bash.exe', '\\schtasks.exe', '\\regsvr32.exe', '\\wmic.exe', '\\mshta.exe', '\\rundll32.exe', '\\msiexec.exe', '\\forfiles.exe', '\\scriptrunner.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,58f4ea09-0fc2-4520-ba18-b85c540b0eaf

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0006, T1555

References

- https://www.microsoft.com/security/blog/2021/07/13/microsoft-discovers-threat-actor-targeting-solarwinds-serv-u-software-with-0-day-exploit/

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/07/14	critical	• Legitimate uses in which users or programs use the SSH service of Serv-U for remote command execution

Rule Details: HTML Help Shell Spawn

It is a suspicious a child process of the Microsoft HTML Help system.

Rule ID

`parent_child_37`

Query

```
{'selection': {'ParentImage': 'C:\\Windows\\hh.exe', 'Image|endswith': ['\\cmd.exe',
'\\powershell.exe', '\\wscript.exe', '\\cscript.exe', '\\regsvr32.exe', '\\wmic.exe',
 '\\rundll32.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,52cad028-0ff0-4854-8f67-d25dfcbc78b4

Author: Maxim Pavlunin, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1059, T1047, TA0005, T1218

References

- https://www.trustwave.com/en-us/resources/blogs/spiderlabs-blog/chm-badness-delivers-a-banking-trojan/

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/04/01	high	• unknown

Rule Details: Regedit as Trusted Installer

Running the regedit process as a TrustedInstaller is suspicious.

Rule ID

`parent_child_38`

Query

```
{'selection': {'Image|endswith': '\\regedit.exe', 'ParentImage|endswith': ['\\TrustedInstaller.exe', '\\ProcessHacker.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,883835a7-df45-43e4-bf1d-4268768afda4

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1548

References

- https://twitter.com/1kwpeter/status/1397816101455765504

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name

- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/05/27	high	• Unlikely

Rule Details: Script Event Consumer Spawning Process

The scrcons.exe process launching PowerShell or other uncommon processes is suspicious.

Rule ID

`parent_child_39`

Query


```
{'selection': {'ParentImage|endswith': ['\\scrcons.exe'], 'Image|endswith': ['\\svchost.exe', '\\dllhost.exe', '\\powershell.exe', '\\pwsh.exe', '\\wscript.exe', '\\cscript.exe', '\\schtasks.exe', '\\regsvr32.exe', '\\mshta.exe', '\\rundll32.exe', '\\msiexec.exe', '\\msbuild.exe']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,f6d1dd2f-b8ce-40ca-bc23-062efb686b34

Author: Sittikorn S

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1047

References

- https://redcanary.com/blog/child-processes/
- https://docs.paloaltonetworks.com/cortex/cortex-xdr/cortex-xdr-analytics-alert-reference/cortex-xdr-analytics-alert-reference/scrcons-exe-rare-child-process.html

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/06/21	high	• Unknown

Rule Details: WMI Persistence - Script Event Consumer

A persistent scrcons.exe child process indicates a WMI backdoor may have been created.

Rule ID

`parent_child_40`

Query

```
{'selection': {'Image': 'C:\\WINDOWS\\system32\\wbem\\scrcons.exe', 'ParentImage': 'C
:\\Windows\\System32\\svchost.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,ec1d5e28-8f3b-4188-a6f8-6e8df81dc28e

Author: Thomas Patzke

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0003, T1546.003

References

- https://www.eideon.com/2018-03-02-THL03-WMIBackdoors/

Severity

50

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/03/07	medium	• Legitimate event consumers • Dell computers on some versions register an event consumer that is known to cause false positives when brightness is changed by the corresponding keyboard button

Rule Details: Suspicious Svchost Process

Launch of svchost.exe from certain parent processes is suspicious.

Rule ID

parent_child_41

Query




```
{'selection': {'Image|endswith': '\\svchost.exe'}, 'filter': {'ParentImage|endswith':
 ['\\services.exe', '\\MsMpEng.exe', '\\Mrt.exe', '\\rpcnet.exe', '\\svchost.exe', '\
\ngen.exe', '\\TiWorker.exe']}, 'filter_null1': {'ParentImage': None}, 'filter_null2'
: {'ParentImage': ''}, 'filter_emptysysmon': {'ParentImage': '-
'}, 'condition': 'selection and not 1 of filter*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,01d2e2a1-5f09-44f7-9fc1-24faa7479b6d

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1036.005

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2017/08/15	high	• Unknown

Rule Details: Exploit for CVE-2015-1641

Launch of MicroScMgmt.exe from Winword is uncommon and indicative of exploits described in CVE-2015-1641.

Rule ID

parent_child_42

Query


```
{'selection': {'ParentImage|endswith': '\\WINWORD.EXE', 'Image|endswith': '\\MicroScM
gmt.exe'}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,7993792c-5ce2-4475-a3db-a3a5539827ef

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1036.005

References

- https://www.virustotal.com/en/file/5567408950b744c4e846ba8ae726883cb15268a539f3bb21758a466e47021ae8/analysis/
- https://www.hybrid-analysis.com/sample/5567408950b744c4e846ba8ae726883cb15268a539f3bb21758a466e47021ae8?environmentId=100

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2018/02/22	critical	• Unknown

Rule Details: TA505 Dropper Load Pattern

Loading of the mshta process by the wmiprvse process is indicative of TA505 malicious documents.

Rule ID

`parent_child_43`

Query

```
{'selection': {'Image|endswith': '\\mshta.exe', 'ParentImage|endswith': '\\wmiprvse.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,18cf6cf0-39b0-4c22-9593-e244bdc9a2d4

Author: Florian Roth (Nextron S ms)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1106

References

- https://twitter.com/ForensicITGuy/status/1334734244120309760

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/12/08	critical	• unknown

Rule Details: Execution via WorkFolders.exe

It is suspicious for WorkFolders.exe to run an arbitrary control.exe.

Rule ID

```
parent_child_44
```

Query

```
{'selection': {'Image|endswith': '\\control.exe', 'ParentImage|endswith': '\\WorkFolders.exe'}, 'filter': {'Image': 'C:\\Windows\\System32\\control.exe'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation
- Requirements: Sysmon ProcessCreation logging must be activated

Rule Source

SigmaHQ,0bbc6369-43e3-453d-9944-cae58821c173

Author: Maxime Thiebaut (@0xThiebaut)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1218

References

- https://twitter.com/elliotkillick/status/1449812843772227588

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/10/21	high	• Legitimate usage of the uncommon Windows Work Folders feature.

Rule Details: Microsoft Outlook Product Spawning Windows Shell

It is suspicious for Microsoft Outlook to start a Windows command and scripting interpreter executable.

Rule ID

`parent_child_45`

Query


```
{'selection': {'ParentImage|endswith': '\\OUTLOOK.EXE', 'Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\wscript.exe', '\\cscript.exe', '\\sh.exe', '\\bash.exe', '\\scrcons.exe', '\\schtasks.exe', '\\regsvr32.exe', '\\hh.exe', '\\wmic.exe', '\\mshta.exe', '\\msiexec.exe', '\\forfiles.exe', '\\scriptrunner.exe', '\\mftrace.exe', '\\AppVLP.exe', '\\svchost.exe', '\\msbuild.exe']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,208748f7-881d-47ac-a29c-07ea84bf691d

Author: Michael Haag, Florian Roth (Nextron Systems), Markus Neis, Elastic, FPT.EagleEye Team

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1204.002

References

- https://www.hybrid-analysis.com/sample/465aabe132ccb949e75b8ab9c5bda36d80cf2fd503d52b8bad54e295f28bbc21?environmentId=100
- https://mgreen27.github.io/posts/2018/04/02/DownloadCradle.html

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/28	high	• unknown

Rule Details: Bypass UAC via WSReset.exe

This could indicate the use of WSReset.exe to bypass User Account Control. Adversaries may use this technique to run privileged processes.

Rule ID

`parent_child_46`

Query

```
{'selection': {'ParentImage|endswith': '\\wsreset.exe'}, 'filter': {'Image|endswith':
 '\\conhost.exe'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,d797268e-28a9-49a7-b9a8-2f5039011c5c

Author: E.M. Anhaus (originally from Atomic Blue Detections, Tony Lambert), oscd.community, Florian Roth

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1548.002

References

- https://eqllib.readthedocs.io/en/latest/analytics/532b5ed4-7930-11e9-8f5c-d46d6d62a49e.html

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	high	• Unknown

Rule Details: Emissary Panda Malware SLLauncher

This indicates running of DLL side-loading malware which is used by the threat group Emissary Panda, also known as APT27.

Rule ID

```
parent_child_48
```

Query

```
{'selection': {'ParentImage|endswith': '\\sllauncher.exe', 'Image|endswith': '\\svchost.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

SigmaHQ,9aa01d62-7667-4d3b-acb8-8cb5103e2014

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0003, T1574.002

References

- https://app.any.run/tasks/579e7587-f09d-4aae-8b07-472833262965
- https://twitter.com/cyb3rops/status/1168863899531132929

Severity

95

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/09/03	critical	• Unknown

Rule Details: Suspicious JAVA Child Process

This may indicate an attempt to run a malicious JAR file or an attempt to exploit a JAVA-specific vulnerability.

Rule ID

```
parent_child_49
```

Query

```
{'selection1': {'ParentImage|endswith': '/java'}, 'selection2': {'Image|endswith': ['/sh', '/bash', '/dash', '/ksh', '/tcsh', '/zsh', '/curl', '/wget']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber linux configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1059

References

N/A

Severity

49

Suppression Logic Based On

- hostip
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/01/19	medium	N/A

Rule Details: Suspicious SolarWinds Child Process

A SolarWinds process that launches a child process may indicate an attempt to run malicious programs.

Rule ID

```
parent_child_50
```

Query

```
{'selection1': {'ParentImage|endswith': ['\\SolarWinds.BusinessLayerHost.exe', '\\SolarWinds.BusinessLayerHostx64.exe']}, 'selection2': {'Image|endswith': ['\\APMServiceControl.exe', '\\ExportToPDFCmd.Exe', '\\SolarWinds.Credentials.Orion.WebApi.exe', '\\
```

SolarWinds.Orion.Topology.Calculator.exe', '\\Database-Maint.exe', '\\SolarWinds.Orion.ApiPoller.Service.exe', '\\WerFault.exe', '\\WerMgr.exe']}, 'condition': 'selection1 and (not selection2)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1195, XTA0001, XT1002, TA0002, T1106

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/12/14	medium	• Trusted SolarWinds child processes, verify process details such as network connections and file writes.

Rule Details: Execution via MSSQL xp_cmdshell Stored Procedure

Use of MSSQL to run a stored procedure with xp_cmdshell, disabled by default, indicates a user may be attempting to elevate their privileges.

Rule ID

parent_child_51

Query

{'selection1': {'Image|endswith': '\\cmd.exe'}, 'selection2': {'ParentImage|endswith': '\\sqlservr.exe'}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1059

References
N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/08/14	high	N/A

Rule Details: Process Activity via Compiled HTML File

Compiled HTML files (.chm), commonly distributed as help systems, have the capability of concealing malicious code and delivering to a victim system. It is suspicious when the runtime program for .chm files (hh.exe) launches other certain processes (such as a command shell).

Rule ID

```
parent_child_52
```

Query

```
{'selection1': {'ParentImage|endswith': '\\hh.exe'}, 'selection2': {'Image|endswith':
 ['\\mshta.exe', '\\cmd.exe', '\\powershell.exe', '\\pwsh.exe', '\\powershell_ise.exe
', '\\cscript.exe', '\\wscript.exe']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1204, TA0005, T1218

References
N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/02/18	medium	• The HTML Help executable program (hh.exe) runs whenever a user clicks a compiled help (.chm) file or menu item that opens the help file inside the Help Viewer. This is not always malicious, but adversaries may abuse this technology to conceal malicious code.

Rule Details: Signed Proxy Execution via MS WorkFolders

Use of Windows Work Folders to run a control.exe file in the current working directory is indicative of potential malicious activity.

Rule ID

```
parent_child_53
```

Query

```
{'selection1': {'Image|endswith': '\\control.exe'}, 'selection2': {'ParentImage|endswith': '\\WorkFolders.exe'}, 'selection3': {'Image': ['?:\\Windows\\System32\\control.exe', '?:\\Windows\\SysWOW64\\control.exe']}, 'condition': 'selection1 and selection2 and (not selection3)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1218

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/03/02	medium	N/A

Rule Details: Microsoft Exchange Server UM Spawning Suspicious Processes

The CVE-2021-26857 vulnerability may be indicated when Exchange Server UM processes launch unexpected child processes.

Rule ID

```
parent_child_54
```

Query

```
{'selection1': {'ParentImage|endswith': ['\\UMService.exe', '\\UMWorkerProcess.exe']}
, 'selection2': {'Image|endswith': ['\\werfault.exe', '\\wermgr.exe']}, 'condition':
'selection1 and (not selection2)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1190, XTA0001, XT1002

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/03/04	medium	• Legitimate processes may be spawned from the Microsoft Exchange Server Unified Messaging (UM) service. If known processes are causing false positives, they can be exempted from the rule.

Rule Details: Unusual Parent-Child Relationship

A Windows program run from an unexpected parent process could indicate masquerading or other strange activity on a system.

Rule ID

parent_child_55

Query

{'selection1': {'Image|endswith': '\\autochk.exe'}, 'selection2': {'ParentImage|endswith': '\\smss.exe'}, 'selection3': {'Image|endswith': ['\\fontdrvhost.exe', '\\dwm.exe']}, 'selection4': {'ParentImage|endswith': ['\\wininit.exe', '\\winlogon.exe']}, 'selection5': {'Image|endswith': ['\\consent.exe', '\\RuntimeBroker.exe', '\\TiWorker.exe']}, 'selection6': {'ParentImage|endswith': '\\svchost.exe'}, 'selection7': {'Image|endswith': '\\SearchIndexer.exe'}, 'selection8': {'ParentImage|endswith': '\\services.exe'}, 'selection9': {'Image|endswith': '\\SearchProtocolHost.exe'}, 'selection10': {'ParentImage|endswith': ['\\SearchIndexer.exe', '\\dllhost.exe']}, 'selection11': {'Image|endswith': '\\dllhost.exe'}, 'selection12': {'ParentImage|endswith': ['\\services.exe', '\\svchost.exe']}, 'selection13': {'Image|endswith': '\\smss.exe'}, 'selection14': {'ParentImage|endswith': ['System', '\\smss.exe']}, 'selection15': {'Image|endswith': '\\csrss.exe'}, 'selection16': {'ParentImage|endswith': ['\\smss.exe', '\\svchost.exe']}, 'selection17': {'Image|endswith': '\\wininit.exe'}, 'selection18': {'Image|endswith': '\\winlogon.exe'}, 'selection19': {'Image|endswith': ['\\lsass.exe', '\\LsaIso.exe']}, 'selection20': {'ParentImage|endswith': '\\wininit.exe'}, 'selection21': {'Image|endswith': '\\LogonUI.exe'}, 'selection22': {'Image|endswith': '\\services.exe'}, 'selection23': {'Image|endswith': '\\svchost.exe'}, 'selection24': {'ParentImage|endswith': ['\\MsMpEng.exe', '\\services.exe']}, 'selection25': {'Image|endswith': '\\spoolsv.exe'}, 'selection26': {'Image|endswith': '\\taskhost.exe'}, 'selection27': {'Image|endswith': '\\taskhostw.exe'}, 'selection28': {'Image|endswith': '\\userinit.exe'}, 'selection29': {'ParentImage|endswith': ['\\dwm.exe', '\\winlogon.exe']}, 'selection30': {'Image|endswith': ['\\wmiprvse.exe', '\\wsmprovhost.exe', '\\winrshost.exe']}, 'selection31': {'ParentImage|endswith': ['\\SearchProtocolHost.exe', '\\csrss.exe']}, 'selection32': {'Image|endswith': ['\\werfault.exe', '\\wermgr.exe', '\\WerFaultSecure.exe']}, 'selection33': {'ParentImage|endswith': '\\autochk.exe'}, 'selection34': {'Image|endswith': ['\\chkdsk.exe', '\\doskey.exe', '\\WerFault.exe']}, 'selection35': {'Image|endswith': ['\\autochk.exe', '\\smss.exe', '\\csrss.exe', '\\wininit.exe', '\\winlogon.exe', '\\setupcl.exe', '\\WerFault.exe']}, 'selection36': {'ParentImage|endswith': '\\wermgr.exe'}, 'selection37': {'Image|endswith': ['\\WerFaultSecure.exe', '\\wermgr.exe', '\\WerFault.exe']}, 'selection38': {'ParentImage|endswith': '\\conhost.exe'}, 'selection39': {'Image|endswith': ['\\mscorsvw.exe', '\\wermgr.exe', '\\WerFault.exe', '\\WerFaultSecure.exe']}, 'condition': '((selection1 and (not selection2)) or (selection3 and (not selection4)) or (selection5 and (not selection6)) or (selection7 and (not selection8)) or (selection9 and (not selection10)) or (selection11 and (not selection12)) or (selection13 and (not selection14)) or (selection15 and (not selection16)) or (selection17 and (not selection2)) or (selection18 and (not selection2)) or (selection19 and (not selection20)) or (selection21 and (not selection4)) or (selection22 and (not selection20)) or (selection23 and (not selection24)) or (selection25 and (not selection8)) or (selection26 and (not selection12)) or (selection27 and (not selection12)) or (selection28 and (not selection29)) or (selection30 and (not selection6)) or (selection31 and (not selection32)) or (selection33 and (not

selection34)) or (selection2 and (not selection35)) or (selection36 and (not selecti
on37)) or (selection38 and (selection39)))'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1055

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/02/18	medium	N/A

Rule Details: Suspicious Process from Conhost

A suspicious Conhost child process may indicate code injection activity.

Rule ID

`parent_child_56`

Query

{'selection1': {'ParentImage|endswith': '\\conhost.exe'}, 'selection2': {'Image': ['?
:\\Windows\\splwow64.exe', '?:\\Windows\\System32\\WerFault.exe', '?:\\Windows\\Syste
m32\\conhost.exe']}, 'condition': 'selection1 and (not selection2)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1055

References
N/A

Severity
74

Suppression Logic Based On
- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/08/31	high	N/A

Rule Details: Suspicious Zoom Child Process

Launch of Zoom from a command shell may indicate an attempt to run Zoom undetected.

Rule ID

```
parent_child_57
```

Query

```
{'selection1': {'ParentImage|endswith': '\\Zoom.exe'}, 'selection2': {'Image|endswith': ['\\cmd.exe', '\\powershell.exe', '\\pwsh.exe', '\\powershell_ise.exe']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1036, T1055

References
N/A

Severity
49

Suppression Logic Based On
- computer_name
- parent_proc_name
- process_name

- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/09/03	medium	N/A

Rule Details: Unusual Parent Process for cmd.exe

Launching of cmd.exe from an unusual parent process is suspicious.

Rule ID

`parent_child_58`

Query


```
{'selection1': {'Image|endswith': '\\cmd.exe'}, 'selection2': {'ParentImage|endswith'
: ['\\lsass.exe', '\\csrss.exe', '\\epad.exe', '\\regsvr32.exe', '\\dllhost.exe', '\\
LogonUI.exe', '\\wermgr.exe', '\\spoolsv.exe', '\\jucheck.exe', '\\jusched.exe', '\\c
tfmon.exe', '\\taskhostw.exe', '\\GoogleUpdate.exe', '\\sppsvc.exe', '\\sihost.exe',
'\\slui.exe', '\\SIHClient.exe', '\\SearchIndexer.exe', '\\SearchProtocolHost.exe', '
\\FlashPlayerUpdateService.exe', '\\WerFault.exe', '\\WUDFHost.exe', '\\unsecapp.exe'
, '\\wlanext.exe']}, 'condition': 'selection1 and selection2'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0002, T1059

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/08/21	medium	N/A

Rule Details: Suspicious MS Office Child Process

Certain child processes being launched from MS Office applications or documents with macros are indicative of malicious activit

Rule ID

`parent_child_59`

Query

```
{'selection1': {'ParentImage|endswith': ['\\eqnedt32.exe', '\\excel.exe', '\\fltldr.exe', '\\msaccess.exe', '\\mspub.exe', '\\powerpnt.exe', '\\winword.exe']}, 'selection2': {'Image|endswith': ['\\Microsoft.Workflow.Compiler.exe', '\\arp.exe', '\\atbroker.exe', '\\bginfo.exe', '\\bitsadmin.exe', '\\cdb.exe', '\\certutil.exe', '\\cmd.exe', '\\cmstp.exe', '\\control.exe', '\\cscript.exe', '\\csi.exe', '\\dnx.exe', '\\dsget.exe', '\\dsquery.exe', '\\forfiles.exe', '\\fsi.exe', '\\ftp.exe', '\\gpresult.exe', '\\hostname.exe', '\\ieexec.exe', '\\iexpress.exe', '\\installutil.exe', '\\ipconfig.exe', '\\mshta.exe', '\\msxsl.exe', '\\nbtstat.exe', '\\net.exe', '\\net1.exe', '\\netsh.exe', '\\netstat.exe', '\\nltest.exe', '\\odbcconf.exe', '\\ping.exe', '\\powershell.exe', '\\pwsh.exe', '\\qprocess.exe', '\\quser.exe', '\\qwinsta.exe', '\\rcsi.exe', '\\reg.exe', '\\regasm.exe', '\\regsvcs.exe', '\\regsvr32.exe', '\\sc.exe', '\\schtasks.exe', '\\systeminfo.exe', '\\tasklist.exe', '\\tracert.exe', '\\whoami.exe', '\\wmic.exe', '\\wscript.exe', '\\xwizard.exe', '\\explorer.exe', '\\rundll32.exe', '\\hh.exe']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1566, XTA0001, XT1002

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/02/18	medium	N/A

Rule Details: Microsoft Build Engine Started by a System Process

It is unusual for Explorer or the WMI (Windows Management Instrumentation) subsystem to launch MSBuild, the Microsoft Build Engine.

Rule ID

`parent_child_60`

Query

```
{'selection1': {'Image|endswith': '\\MSBuild.exe'}, 'selection2': {'ParentImage|endswith': ['\\explorer.exe', '\\wmiprvse.exe']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1127

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/03/25	medium	• The Build Engine is commonly used by Windows developers but use by non-engineers is unusual.

Rule Details: Microsoft Build Engine Started by an Office Application

Launch of the Microsoft Build Engine from an Office application is unusual and may indicate the associated document has run a malicious script payload.

Rule ID

`parent_child_61`

Query

{'selection1': {'Image|endswith': '\\MSBuild.exe'}, 'selection2': {'ParentImage|endswith': ['\\eqnedt32.exe', '\\excel.exe', '\\fltldr.exe', '\\msaccess.exe', '\\mspub.exe', '\\outlook.exe', '\\powerpnt.exe', '\\winword.exe']}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1127

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/03/25	high	• The Build Engine is commonly used by Windows developers but use by non-engineers is unusual. It is quite unusual for this program to be started by an Office application like Word or Excel.

Rule Details: Command Execution via SolarWinds Process

A SolarWinds process that launches a command-line call or PowerShell command is considered suspicious.

Rule ID

parent_child_62

Query

{'selection1': {'Image|endswith': ['\\cmd.exe', '\\powershell.exe']}, 'selection2': {'ParentImage|endswith': ['\\ConfigurationWizard.exe', '\\NetflowDatabaseMaintenance.exe', '\\NetFlowService.exe', '\\SolarWinds.Administration.exe', '\\SolarWinds.Collector.Service.exe', '\\SolarwindsDiagnostics.exe']}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1195, XTA0001, XT1002, TA0002, T1059

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/12/14	medium	• Trusted SolarWinds child processes. Verify process details such as network connections and file writes.

Rule Details: Suspicious .NET Code Compilation

This may indicate suspicious .NET or Visual Basic compilation of downloaded code.

Rule ID

`parent_child_63`

Query

```
{'selection1': {'Image|endswith': ['\\csc.exe', '\\vbc.exe']}, 'selection2': {'Parent Image|endswith': ['\\wscript.exe', '\\mshta.exe', '\\cscript.exe', '\\wmic.exe', '\\svchost.exe', '\\rundll32.exe', '\\cmstp.exe', '\\regsvr32.exe']}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1027

References
N/A

Severity
49

Suppression Logic Based On
- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/08/21	medium	N/A

Rule Details: Conhost Spawned By Suspicious Parent Process

The Console Window Host (conhost.exe) process being launched by a suspicious parent process is indicative of code injection.

Rule ID
`parent_child_64`

Query

```
{'selection1': {'Image|endswith': '\\conhost.exe'}, 'selection2': {'ParentImage|endswith': ['\\svchost.exe', '\\lsass.exe', '\\services.exe', '\\smss.exe', '\\winlogon.exe', '\\explorer.exe', '\\dllhost.exe', '\\rundll32.exe', '\\regsvr32.exe', '\\userinit.exe', '\\wininit.exe', '\\spoolsv.exe', '\\wermgr.exe', '\\csrss.exe', '\\ctfmon.exe']}, 'condition': 'selection1 and selection2'}
```


Log Source
Stellar Cyber Windows Server Sensor configured for:
- Monitoring process creation

Rule Source
Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures
XTA0001, XT1002, TA0002, T1059

References
N/A

Severity
74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/08/17	high	N/A

Rule Details: Unusual Child Process of dns.exe

Such an unexpected process being launched from dns.exe may indicate activity related to running of remote code or other forms of exploitation.

Rule ID

```
parent_child_65
```

Query

```
{'selection1': {'ParentImage|endswith': '\\dns.exe'}, 'selection2': {'Image|endswith': '\\conhost.exe'}, 'condition': 'selection1 and (not selection2)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0003, T1133

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/07/16	high	• Werfault.exe will legitimately spawn when dns.exe crashes, but the DNS service is very stable and so this is a low occurring event. Denial of Service (DoS) attempts by intentionally crashing the service will also cause werfault.exe to spawn.

Rule Details: Script Process Child of Common Web Processes

A parent web process, such as d.exe, that runs a script process, such as powershell.exe, is suspicious and indicative of possible attempts for remote shell access.

Rule ID

`parent_child_66`

Query


```
{'selection1': {'ParentImage|endswith': ['\\w3wp.exe', '\\httpd.exe', '\\nginx.exe', '\\php.exe', '\\php-cgi.exe', '\\tomcat.exe']}, 'selection2': {'Image|endswith': ['\\cmd.exe', '\\cscript.exe', '\\powershell.exe', '\\pwsh.exe', '\\powershell_ise.exe', '\\wmic.exe', '\\wscript.exe']}, 'condition': 'selection1 and selection2'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0001, T1190, XTA0001, XT1002, TA0003, T1505

References

N/A

Severity

74

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/08/24	high	• Security audits, maintenance, and network administrative scripts may trigger this alert when run under web processes.

Rule Details: Suspicious Endpoint Security Parent Process

A suspicious Endpoint Security parent process was detected, which may indicate process hollowing or other form of code injection.

Rule ID

parent_child_67

Query



```
{'selection1': {'Image|endswith': ['\\esensor.exe', '\\elastic-endpoint.exe']}, 'selection2': {'ParentImage': ['C:\\Program Files\\Elastic\\*', 'C:\\Windows\\System32\\services.exe', 'C:\\Windows\\System32\\WerFault*.exe', 'C:\\Windows\\System32\\wermgr.exe']}, 'condition': 'selection1 and (not selection2)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process creation

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

XTA0001, XT1002, TA0005, T1036

References

N/A

Severity

49

Suppression Logic Based On

- computer_name
- parent_proc_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2020/08/24	medium	N/A

Suspicious AD Kerberos Rule IDs

Rule Details: Suspicious Active Directory Kerberos Certificate Authentication

A Golden Certificate is a persistence technique that expands upon an AD CS compromise. If malicious actors obtain administrative access to a CA, they can extract a CA certificate and private key. Once obtained, these can be used to forge valid certificates for client authentication to impersonate any other user object in the domain. This rule detects unusual certificate usage by monitoring certificate-based authentication.

Rule ID

suspicious_kerberos_certificate_authentication

Query

```
{'selection': {'EventID': 4768}, 'condition': 'selection |
 count() by TargetUserName >  , 'timeframe': '15m'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1558

References

- https://rootguard.gitbook.io/cyberops/detection-engineering/ad-attack-detections-and-mitigations/golden-certificate

Severity

50

Suppression Logic Based On

- event_data.CertIssuerName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/06/16	medium	• False positives are possible if multiple legitimate users requested Kerberos authentication tickets from legitimate Active Directory Certificate Services (AD CS). We recommend excluding known trusted accounts or administrators.

Encoded PowerShell Rule IDs

Rule Details: Encoded PowerShell

A Windows host executed an encoded PowerShell script. Investigate the script contents to see if it is malicious. If so, consider quarantining the host.

Rule ID

`threat_encoded_powershell`

Query

```
{'selection1': {'detection_flag': [2100, 2101]}, 'condition': 'selection1'}
```

Detection Flag

Note: `detection_flag` is a Stellar enriched field.

- **2100:** Encoded PowerShell
- **2101:** Encoded PowerShell with hidden flag

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0002, T1059

References

N/A

Severity

80

Suppression Logic Based On

- srcip
- detection_flag
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2018/12/01	critical	N/A

Windows Identity Threat Detection and Response (ITDR) Rule IDs

Rule Details: Security-Enabled Universal Group was Created

A Security-Enabled Universal Group has been created. This could be an indication of malicious activity.

Rule ID

```
windows_itdr_4
```

Query

```
{'selection1': {'EventID': 4754}, 'selection2': {'SubjectUserName': ''}, 'selection3'
: {'SubjectDomainName': ''}, 'condition': 'selection1 and not selection2 and not sele
ction3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_id
- event_data.SubjectDomainName
- event_data.SubjectUserSid
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Security-Enabled Global Group was Created

A Security-Enabled Global Group has been created. This could be an indication of malicious activity.

Rule ID

```
windows_itdr_5
```

Query

```
{'selection1': {'EventID': 4727}, 'selection2': {'SubjectUserName': ''}, 'selection3'
: {'SubjectDomainName': ''}, 'condition': 'selection1 and not selection2 and not sele
ction3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References
N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_id
- event_data.SubjectDomainName

- event_data.SubjectUserSid
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Security-Enabled Local Group was Created

A Security-Enabled Local Group has been created. This could be an indication of malicious activity.

Rule ID

```
windows_itdr_8
```

Query

```
{'selection1': {'EventID': 4731}, 'selection2': {'SubjectUserName': ''}, 'selection3' : {'SubjectDomainName': ''}, 'condition': 'selection1 and not selection2 and not selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_id
- event_data.SubjectDomainName
- event_data.SubjectUserSid
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Windows Network Connection Rule IDs

Rule Details: Network Activity From MSBuild

MSBuild is a powerful tool used to compile and package code. If the MSBuild utility is accessing network resources, it might be using code from a third party or even downloading malicious code or executables. Malicious executables can even run inside of MSBuild with little indication it is doing so.

Rule ID

`windows_network_connection_1`

Query

```
{'selection': {'EventImage|endswith': '\\MSBuild.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring Windows network connection events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1127

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.Image
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Network Activity From mshta

Mshta is the Microsoft HTML Application Host and allows the execution of .hta files. If the mshta utility is accessing network resources, it might be using code from a third party or even downloading malicious code or executables.

Rule ID

`windows_network_connection_2`

Query

```
{'selection': {'EventImage|endswith': '\\mshta.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring Windows network connection events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218.005

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.Image
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Network Activity From msxsl

Msxsl allows you to perform command line Extensible Stylesheet Language (XSL) transformations. If the msxsl utility is accessing network resources, it might be using code from a third party or even downloading malicious code or executables.

Rule ID

```
windows_network_connection_3
```

Query

```
{'selection': {'EventImage|endswith': '\\msxsl.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring Windows network connection events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.Image
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Network Activity From verclsid

Verclsid allows you to validate shell extensions before they are instantiated by the Windows shell or Windows Explorer. If the verclsid utility is accessing network resources, it might be using code from a third party or even downloading malicious code or executables.

Rule ID

```
windows_network_connection_4
```

Query

```
{'selection': {'EventImage|endswith': '\\verclsid.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring Windows network connection events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.Image
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Unexpected Network Activity from Microsoft Tool

A Microsoft tool was executed with suspicious network connection activity. This could be an indication of malicious activity.

Rule ID

`windows_network_connection_5`

Query

```
{'selection': {'EventImage|endswith': ['\\bginfo.exe', '\\rcsi.exe', '\\control.exe',
 '\\odbcconf.exe']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring Windows network connection events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1218

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.Image
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Windows Process Access Rule IDs

Rule Details: LSASS Memory Access by Tool With Dump Keyword In Name

Detects LSASS process access requests from a source process with the "dump" keyword in its image name.

Rule ID

`windows_process_access_1`

Query

{'selection': {'TargetImage|endswith': '\\lsass.exe', 'SourceImage|contains': 'dump'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process access

Rule Source

SigmaHQ,9bd012ee-0dff-44d7-84a0-aa698cfd87a3

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0006, T1003.001

References

- https://twitter.com/_xpn_/status/1491557187168178176
- https://www.ired.team/offensive-security/credential-access-and-credential-dumping/dump-credentials-from-lsass-process-without-mimikatz

Severity

75

Suppression Logic Based On

- computer_name
- event_data.SourceImage
- event_data.TargetImage
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/02/10	high	• Rare programs that contain the word dump in their name and access lsass

Rule Details: Credential Dumping Activity By Python Based Tool

Detects LSASS process access for potential credential dumping by a Python-like tool such as LaZagne or Pypykatz.

Rule ID

`windows_process_access_2`

Query

{'selection': {'TargetImage|endswith': '\\lsass.exe', 'CallTrace|contains': '_ctypes.pyd'}, 'filter_av': {'SourceImage': ['?:\\Windows\\TEMP\\rapid7\\ir_agent.exe']}, 'condition': 'selection and not filter_av'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process access

Rule Source

SigmaHQ,f8be3e82-46a3-4e4e-ada5-8e538ae8b9c9

Author: Bhabesh Raj, Jonhnathan Ribeiro

Tactics, Techniques, and Procedures

TA0006, T1003.001

References

- https://twitter.com/bh4b3sh/status/1303674603819081728
- https://github.com/skelsec/pypykatz

Severity

75

Suppression Logic Based On

- computer_name
- event_data.SourceImage
- event_data.TargetImage
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2023/11/27	high	• Unknown

Rule Details: LSASS Memory Access by Process in Temp Folder

Identifies suspicious access to LSASS from a source process in Temp folder.

Rule ID

`windows_process_access_3`

Query

```
{'selection': {'TargetImage|endswith': '\\lsass.exe', 'SourceImage': ['*\\Local\\Temp\\*', '*\\LocalLow\\Temp\\*', '*\\Roaming\\Temp\\*']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process access

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003.001

References

N/A

Severity



75

Suppression Logic Based On

- computer_name
- event_data.SourceImage
- event_data.TargetImage
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2024/01/26	high	• Unknown

Rule Details: Suspicious LSASS Access via MalSecLogon

Identifies suspicious access to LSASS handle from a call trace pointing to seclogon.dll and with a suspicious access rights value. This may indicate an attempt to leak an LSASS handle via abusing the Secondary Logon service in preparation for credential access.

Rule ID

`windows_process_access_4`

Query


```
{'selection1': {'TargetImage|endswith': '\\lsass.exe'}, 'selection2': {'CallTrace|contains': 'seclogon.dll'}, 'selection3': {'SourceImage|endswith': 'svchost.exe'}, 'selection4': {'GrantedAccess': '0x14c0'}, 'condition': 'selection1 and selection2 and selection3 and selection4'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process access

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003.001

References

N/A

Severity

75

Suppression Logic Based On

- computer_name
- event_data.SourceImage

- event_data.TargetImage
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/06/29	high	N/A

Rule Details: Potential Credential Access via DuplicateHandle in LSASS

Identifies suspicious access to an LSASS handle via DuplicateHandle from an unknown call trace module. This may indicate an attempt to bypass the NtOpenProcess API to evade detection and dump LSASS memory for credential access.

Rule ID

```
windows_process_access_5
```

Query

```
{'selection1': {'SourceImage|endswith': '\\lsass.exe'}, 'selection2': {'GrantedAccess': '0x40'}, 'selection3': {'CallTrace|contains': 'UNKNOWN'}, 'condition': 'selection1 and selection2 and selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process access

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003.001

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_data.SourceImage
- event_data.TargetImage
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/09/27	medium	N/A

Rule Details: Potential Credential Access via LSASS Memory Dump

Identifies suspicious access to LSASS handle from a call trace pointing to DBGHelp.dll or DBGCore.dll, which both export the MiniDumpWriteDump method that can be used to dump LSASS memory content in preparation for credential access.

Rule ID

`windows_process_access_6`

Query


```
{'selection1': {'TargetImage|endswith': '\\lsass.exe'}, 'selection2': {'CallTrace|contains': ['dbghelp.dll', 'dbgcore.dll']}, 'selection3': {'SourceImage': ['?:\\Windows\\System32\\WerFault.exe', '?:\\Windows\\System32\\WerFaultSecure.exe', '?:\\Windows\\System32\\tasklist.exe']}, 'condition': 'selection1 and selection2 and (not selection3)'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring process access

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003.001

References

N/A

Severity

75

Suppression Logic Based On

- computer_name
- event_data.SourceImage
- event_data.TargetImage
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/10/07	high	N/A

Windows Registry Set Rule IDs

Rule Details: Potential Ransomware Activity Using LegalNotice Message

Detect changes to the "LegalNoticeCaption" or "LegalNoticeText" registry values where the message set contains keywords often used in ransomware ransom messages

Rule ID

windows_registry_set_1

Query



{'selection': {'TargetObject|contains': ['\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\Policies\\System\\LegalNoticeCaption', '\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\Policies\\System\\LegalNoticeText']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring registry events

Rule Source

SigmaHQ,8b9606c9-28be-4a38-b146-0e313cc232c1

Author: frack113

Tactics, Techniques, and Procedures

TA0040, T1491.001

References

- https://github.com/redcanaryco/atomic-red-team/blob/5c1e6f1b4fafd01c8d1ece85f510160fc1275fbf/atomics/T1491.001/T1491.001.md

Severity

75

Suppression Logic Based On

- computer_name
- event_data.TargetObject
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/11	high	• Unknown

Rule Details: Potential Persistence Via Microsoft office Add-in

Detect potential persistence via the creation of a Microsoft office add-in file to make it run automatically.

Rule ID

windows_registry_set_2

Query

{'selection1': {'TargetObject|contains': ['\\Software\\Microsoft\\Office\\']}, 'selection2': {'TargetObject|contains': ['\\Excel\\Options\\OPEN'], 'Details|startswith': '/R ', 'Details|endswith': '.xll'}, 'selection3': {'TargetObject|contains|all': ['\\Po

werPoint\\AddIns', '\\Path'], 'Details|endswith': '.ppam'}, 'condition': 'selection1 and (selection2 or selection3)'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring registry events

Rule Source

SigmaHQ,961e33d1-4f86-4fcf-80ab-930a708b2f82

Author: frack113

Tactics, Techniques, and Procedures

TA0003, T1137.006

References

- https://github.com/redcanaryco/atomic-red-team/blob/4ae9580a1a8772db87a1b6cdb0d03e5af231e966/atomics/T1137.006/T1137.006.md
- https://labs.withsecure.com/publications/add-in-opportunities-for-office-persistence

Severity

75

Suppression Logic Based On

- computer_name
- event_data.TargetObject
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/15	high	• Unknown

Windows Security Rule IDs

Rule Details: Invoke-Obfuscation VAR++ LAUNCHER OBFUSCATION - Security

Detects Obfuscated Powershell via VAR++ LAUNCHER.

Rule ID

`windows_security_1`

Query

{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['&&set', 'cmd', '/c', '-f'], 'ServiceFileName|contains': ['{0}', '{1}', '{2}', '{3}', '{4}', '{5}']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,4c54ba8f-73d2-4d40-8890-d9cf1dca3d30

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/13	high	• Unknown

Rule Details: SysKey Registry Keys Access

Detects handle requests and access operations to specific registry keys to calculate the SysKey.

Rule ID

`windows_security_2`

Query

```
{'selection': {'EventID': [4656, 4663], 'ObjectType': 'Key', 'ObjectName|endswith': [
'\\Lsa\\JD', '\\Lsa\\GBG', '\\Lsa\\Skew1', '\\Lsa\\Data']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,9a4ff3b8-6187-4fd2-8e8b-e0eae1129495

Author: Roberto Rodriguez @Cyb3rWard0g

Tactics, Techniques, and Procedures

TA0007, T1012

References

- https://threathunterplaybook.com/hunts/windows/190625-RegKeyAccessSyskey/notebook.html

Severity

75

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/08/12	high	• Unknown

Rule Details: ETW Logging Disabled In .NET Processes - Registry

Potential adversaries stopping ETW providers recording loaded .NET assemblies.

Rule ID

`windows_security_3`

Query

```
{'selection_etw_enabled': {'EventID': 4657, 'ObjectName|endswith': '\\SOFTWARE\\Microsoft\\.NETFramework', 'ObjectValueName': 'ETWEnabled', 'NewValue': '0'}, 'selection_comp
lus': {'EventID': 4657, 'ObjectName|contains': '\\Environment', 'ObjectValueName':
 ['COMPlus_ETWEnabled', 'COMPlus_ETWFlags'], 'NewValue': '0'}, 'condition': '1 of sel
ection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,a4c90ea1-2634-4ca0-adbb-35eae169b6fc

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research)

Tactics, Techniques, and Procedures

TA0005, T1112, T1562

References

- https://twitter.com/_xpn_/status/1268712093928378368

- https://github.com/dotnet/runtime/blob/ee2355c801d892f2894b0f7b14a20e6cc50e0e54/docs/design/coreclr/jit/viewing-jit-dumps.md#setting-configuration-variables
- https://github.com/dotnet/runtime/blob/f62e93416a1799aecc6b0947adad55a0d9870732/src/coreclr/src/inc/clrconfigvalues.h#L35-L38
- https://github.com/dotnet/runtime/blob/7abe42dc1123722ed385218268bb9fe04556e3d3/src/coreclr/src/inc/clrconfig.h#L33-L39
- http://managed670.rssing.com/chan-5590147/all_p1.html
- https://github.com/dotnet/runtime/blob/4f9ae42d861fcb4be2fcd5d3d55d5f227d30e723/docs/coding-guidelines/clr-jit-coding-conventions.md#1412-disabling-code
- https://i.blackhat.com/EU-21/Wednesday/EU-21-Teodorescu-Veni-No-Vidi-No-Vici-Attacks-On-ETW-Blind-EDRs.pdf

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/06/05	high	• Unknown

Rule Details: NetNTLM Downgrade Attack

Detects NetNTLM downgrade attack.

Rule ID

`windows_security_4`

Query

```
{'selection': {'EventID': 4657, 'ObjectName|contains|all': ['\\REGISTRY\\MACHINE\\SYSTEM', 'ControlSet', '\\Control\\Lsa'], 'ObjectValueName': ['LmCompatibilityLevel', 'NtlmMinClientSec', 'RestrictSendingNTLMTraffic']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- Requirements: Audit Policy : Object Access > Audit Registry (Success)

Rule Source

SigmaHQ,d3abac66-f11c-4ed0-8acb-50cc29c97eed

Author: Florian Roth (Nextron Systems), wagga

Tactics, Techniques, and Procedures

TA0005, T1562.001, T11

References

- https://www.optiv.com/blog/post-exploitation-using-netntlm-downgrade-attacks

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/03/20	high	• Unknown

Rule Details: Windows Defender Discarded Signature

Dynamic Signature Service signature of Windows Defender has been discarded. This may be due to an attacker or a user disabling a security feature that can led the computer exposed to malware and other threats.

Rule ID

```
windows_security_5
```

Query

```
{'selection2': {'EventID': 2013}, 'condition': 'selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562.006

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: PetitPotam Suspicious Kerberos TGT Request

Detect suspicious Kerberos TGT requests. Once an attacer obtains a computer certificate by abusing Active Directory Certificate Services in combination with PetitPotam, the next step would be to leverage the certificate for malicious purposes. One way of doing this is to request a Kerberos Ticket Granting Ticket using a tool like Rubeus. This request will generate a 4768 event with some unusual fields depending on the environment. This analytic will require tuning, we recommend filtering Account_Name to the Domain Controller computer accounts.

Rule ID

`windows_security_7`

Query


```
{'selection': {'EventID': 4768, 'TargetUserName|endswith': '$', 'CertThumbprint|contains': '*'}, 'filter_local': {'IpAddress': '::1'}, 'filter_thumbprint': {'CertThumbprint': ''}, 'condition': 'selection and not 1 of filter_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The advanced audit policy setting "Account Logon > Kerberos Authentication Service" must be configured for Success/Failure

Rule Source

SigmaHQ,6a53d871-682d-40b6-83e0-b7c1a6c4e3a5

Author: Mauricio Velazco, Michael Haag

Tactics, Techniques, and Procedures

TA0006, T1187

References

- https://github.com/topotam/PetitPotam
- https://isc.sans.edu/forums/diary/Active+Directory+Certificate+Services+ADCS+PKI+domain+admin+vulnerability/27668/
- https://github.com/splunk/security_content/blob/develop/detections/endpoint/petitpotam_suspicious_kerberos_tgt_request.yml

Severity

75

Suppression Logic Based On

- event_id

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/09/02	high	• False positives are possible if the environment is using certificates for authentication. We recommend filtering Account_Name to the Domain Controller computer accounts.

Rule Details: Malicious Service Installations

Detects known malicious service installs that only appear in cases of lateral movement, credential dumping, and other suspicious activities.

Rule ID

```
windows_security_8
```

Query

```
{'selection': {'EventID': 4697}, 'malsvc_apt29': {'ServiceName': 'javamtsup'}, 'condition': 'selection and 1 of malsvc_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,cb062102-587e-4414-8efa-dbe3c7bf19c6

Author: Florian Roth (Nextron Systems), Daniil Yugoslavskiy, oscd.community (update)

Tactics, Techniques, and Procedures

TA0002, T1569.002, TA0003, T1543.003, TA0006, T1003

References

- https://awakesecurity.com/blog/threat-hunting-for-paexec/
- https://www.fireeye.com/blog/threat-research/2017/05/wannacry-malware-profile.html
- https://blog.f-secure.com/wp-content/uploads/2019/10/CosmicDuke.pdf

Severity

90

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/03/27	critical	• Unknown

Rule Details: Invoke-Obfuscation Via Use MSHTA - Security

Detects Obfuscated Powershell via use MSHTA in Scripts.

Rule ID

`windows_security_10`

Query

```
{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['mshta', 'vbscript:createobject', '.run', 'window.close']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,9b8d9203-4e0f-4cd9-bb06-4cc4ea6d0e9a

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/09	high	• Unknown

Rule Details: Potential LSASS Clone Creation via PssCaptureSnapShot

Identifies the creation of an LSASS process clone via PssCaptureSnapShot where the parent process is the initial LSASS process instance. This may indicate an attempt to evade detection and dump LSASS memory for credential access.

Rule ID

`windows_security_11`

Query

`{'selection1': {'Image': '?:\\Windows\\System32\\lsass.exe'}, 'selection2': {'ParentImage': '?:\\Windows\\System32\\lsass.exe'}, 'condition': 'selection1 and selection2'}`

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003

References

N/A

Severity

75

Suppression Logic Based On

- computer_name
- process_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/11/27	high	N/A

Rule Details: Suspicious LDAP-Attributes Used

Detects the usage of particular AttributeLDAPDisplayNames, which are known for data exchange via LDAP by the tool LDAPFragger and are additionally not commonly used in companies.

Rule ID

`windows_security_12`

Query

`{'selection': {'EventID': 5136, 'AttributeValue|contains': '*', 'AttributeLDAPDisplayName': ['primaryInternationalISDNNumber', 'otherFacsimileTelephoneNumber', 'primaryTelexNumber']}, 'condition': 'selection'}`

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

- The "Audit Directory Service Changes" logging policy must be configured in order to receive events. Audit events are generated only for objects with configured system access control lists (SACLs). Audit events are generated only for objects with configured system access control lists (SACLs) and only when accessed in a manner that matches their SACL settings. This policy covers the following events ids - 5136, 5137, 5138, 5139, 5141. Note that the default policy does not cover User objects. For that a custom AuditRule need to be setup (See https://github.com/OTRF/Set-AuditRule)

Rule Source

SigmaHQ,d00a9a72-2c09-4459-ad03-5e0a23351e36

Author: xknow @xknow_infosec

Tactics, Techniques, and Procedures

TA0011, T1001.003

References

- https://medium.com/@ivecodoe/detecting-ldapfragger-a-newly-released-cobalt-strike-beacon-using-ldap-for-c2-communication-c274a7f00961
- https://blog.fox-it.com/2020/03/19/ldapfragger-command-and-control-over-ldap-attributes/
- https://github.com/fox-it/LDAPFragger

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/03/24	high	• Companies, who may use these default LDAP-Attributes for personal information

Rule Details: Service Installed By Unusual Client - Security

Detects a service installed by a client which has PID 0 or whose parent has PID 0.

Rule ID

```
windows_security_13
```

Query

```
{'selection': {'EventID': 4697}, 'selection_pid': [{'ClientProcessId': 0}, {'ParentProcessId': 0}], 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,c4e92a97-a9ff-4392-9d2d-7a4c642768ca

Author: Tim Rauch (Nextron Systems), Elastic (idea)

Tactics, Techniques, and Procedures

TA0003, T1543

References

- https://www.elastic.co/guide/en/security/current/windows-service-installed-via-an-unusual-client.html
- https://twitter.com/SBousseaden/status/1490608838701166596

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/15	high	• Unknown

Rule Details: User account exposed to Kerberoasting

Detects when a user account has the servicePrincipalName attribute modified. Attackers can abuse write privileges over a user to configure Service Principle Names (SPNs) so that they can perform Kerberoasting. Administrators can also configure this for legitimate purposes, exposing the account to Kerberoasting.

Rule ID

`windows_security_15`

Query

```
{'selection1': {'EventID': 5136}, 'selection2': {'ObjectClass': 'user'}, 'selection3' : {'AttributeLDAPDisplayName': 'servicePrincipalName'}, 'condition': 'selection1 and selection2 and selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1558

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/02/22	high	N/A

Rule Details: Register new Logon Process by Rubeus

Detects potential use of Rubeus via registered new trusted logon process.

Rule ID

```
windows_security_16
```

Query

```
{'selection': {'EventID': 4611, 'LogonProcessName': 'User32LogonProcesss'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,12e6d621-194f-4f59-90cc-1959e21e69f7

Author: Roberto Rodriguez (source), Ilyas Ochkov (rule), oscd.community

Tactics, Techniques, and Procedures

TA0006, T1558.003

References

- https://posts.specterops.io/hunting-in-active-directory-unconstrained-delegation-forests-trusts-71f2b33688e1

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	high	• Unknown

Rule Details: DPAPI Domain Master Key Backup Attempt

Detects anyone attempting a backup for the DPAPI Master Key. This events gets generated at the source and not the Domain Controller.

Rule ID

```
windows_security_18
```

Query

```
{'selection': {'EventID': 4692}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,39a94fd1-8c9a-4ff6-bf22-c058762f8014

Author: Roberto Rodriguez @Cyb3rWard0g

Tactics, Techniques, and Procedures

TA0006, T1003.004

References

- https://threathunterplaybook.com/hunts/windows/190620-DomainDPAPIBackupKeyExtraction/notebook.html

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/08/10	medium	• If a computer is a member of a domain, DPAPI has a backup mechanism to allow unprotection of the data. Which will trigger this event.

Rule Details: Sysmon Channel Reference Deletion

Potential threat actor tampering  n Sysmon manifest and eventually disabling it

Rule ID

`windows_security_19`

Query

```
{'selection1': {'EventID': 4657, 'ObjectName|contains': ['WINEVT\\Publishers\\{5770385f-c22a-43e0-bf4c-06f5698ffbd9}', 'WINEVT\\Channels\\Microsoft-Windows-Sysmon/Operational'], 'ObjectValueName': 'Enabled', 'NewValue': '0'}, 'selection2': {'EventID': 4663, 'ObjectName|contains': ['WINEVT\\Publishers\\{5770385f-c22a-43e0-bf4c-06f5698ffbd9}', 'WINEVT\\Channels\\Microsoft-Windows-Sysmon/Operational'], 'AccessMask': '0x10000'}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,18beca67-ab3e-4ee3-ba7a-a46ca8d7d0cc

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research)

Tactics, Techniques, and Procedures

TA0005, T1112

References

- https://twitter.com/Flangvik/status/1283054508084473861
- https://twitter.com/SecurityJosh/status/1283027365770276866
- https://securityjosh.github.io/2020/04/23/Mute-Sysmon.html
- https://gist.github.com/Cyb3rWard0g/cf08c38c61f7e46e8404b38201ca01c8

Severity

75

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/07/14	high	• Unknown

Rule Details: Scanner PoC for CVE-2019-0708 RDP RCE Vuln

Detects the use of a scanner by zerosum0x0 that discovers targets vulnerable to CVE-2019-0708 RDP RCE aka BlueKeep.

Rule ID

```
windows_security_21
```

Query

```
{'selection': {'EventID': 4625, 'TargetUserName': 'AAAAAAA'}, 'condition': 'selection
'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,8400629e-79a9-4737-b387-5db940ab2367

Author: Florian Roth (Nextron Systems), Adam Bradbury (idea)

Tactics, Techniques, and Procedures

TA0008, T1210

References

- https://twitter.com/AdamTheAnalyst/status/1134394070045003776
- https://github.com/zerosum0x0/CVE-2019-0708

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/06/02	high	• Unlikely

Rule Details: Suspicious Scheduled Task Update

Detects update to a scheduled task event that contain suspicious keywords.

Rule ID

```
windows_security_23
```

Query

```
{'selection_eid': {'EventID': 4702}, 'selection_paths': {'TaskContentNew|contains': [
'\\AppData\\Local\\Temp\\', '\\AppData\\Roaming\\', '\\Users\\Public\\', '\\WINDOWS\\
```

Temp\\', 'C:\\Temp\\', '\\Desktop\\', '\\Downloads\\', '\\Temporary Internet', 'C:\\ProgramData\\', 'C:\\Perflogs\\']}, 'selection_commands': {'TaskContentNew|contains': ['regsvr32', 'rundll32', 'cmd.exe</Command>', 'cmd</Command>', '<Arguments>/c ', '<Arguments>/k ', '<Arguments>/r ', 'powershell', 'pwsh', 'mshta', 'wscript', 'cscript', 'certutil', 'bitsadmin', 'bash.exe', 'bash ', 'scrcons', 'wmic ', 'wmic.exe', 'forfiles', 'scriptrunner', 'hh.exe']}, 'condition': 'all of selection_*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The Advanced Audit Policy setting Object Access > Audit Other Object Access Events has to be configured to allow this detection. We also recommend extracting the Command field from the embedded XML in the event data.

Rule Source

SigmaHQ,614cf376-6651-47c4-9dcc-6b9527f749f4

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0003, T1053.005

References

- https://learn.microsoft.com/en-us/windows/security/threat-protection/auditing/event-4698

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/05	high	• Unknown

Rule Details: Suspicious Teams Application Related ObjectAcess Event

Detects an access to authentication tokens and accounts of Microsoft Teams desktop application.

Rule ID

`windows_security_24`

Query

{'selection': {'EventID': 4663, 'ObjectName|contains': ['\\Microsoft\\Teams\\Cookies', '\\Microsoft\\Teams\\Local Storage\\leveldb']}, 'filter': {'ProcessName|contains': '\\Microsoft\\Teams\\current\\Teams.exe'}, 'condition': 'selection and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,25cde13e-8e20-4c29-b949-4e795b76f16f

Author: @SerkinValery

Tactics, Techniques, and Procedures

TA0006, T1528

References

- https://www.bleepingcomputer.com/news/security/microsoft-teams-stores-auth-tokens-as-cleartext-in-windows-linux-macs/
- https://www.vectra.ai/blogpost/undermining-microsoft-teams-security-by-mining-tokens

Severity

75

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/09/16	high	• Unknown

Rule Details: Meterpreter or Cobalt Strike Getsystem Service Installation - Security

Detects the use of getsystem Meterpreter/Cobalt Strike command by detecting a specific service installation.

Rule ID

`windows_security_26`

Query

{'selection_id': {'EventID': 4697}, 'selection': [{'ServiceFileName|contains|all': ['cmd', '/c', 'echo', '\\pipe\\']}, {'ServiceFileName|contains|all': ['%COMSPEC%', '/c', 'echo', '\\pipe\\']}, {'ServiceFileName|contains|all': ['cmd.exe', '/c', 'echo', '\\pipe\\']}, {'ServiceFileName|contains|all': ['rundll32', '.dll,a', '/p:']}], 'condition': 'selection_id and selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,ecbc5e16-58e0-4521-9c60-eb9a7ea4ad34

Author: Teymur Kheirkhabarov, Ecco, Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0005, T1134

References

- https://speakerdeck.com/heirhabarov/hunting-for-privilege-escalation-in-windows-environment
- https://blog.cobaltstrike.com/2014/04/02/what-happens-when-i-type-getsystem/

Severity

90

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/26	critical	• Highly unlikely

Rule Details: Powerview Add-DomainObjectAcl DCSync AD Extend Right

Backdooring domain object to grant the rights associated with DCSync to a regular user or machine account using Powerview\Add-DomainObjectAcl DCSync Extended Right cmdlet, will allow to re-obtain the pwd hashes of any user/computer.

Rule ID

`windows_security_27`

Query


```
{'selection': {'EventID': 5136, 'AttributeLDAPDisplayName': 'ntSecurityDescriptor', '
AttributeValue|contains': ['1131f6ad-9c07-11d1-f79f-00c04fc2dcd2', '1131f6aa-9c07-
11d1-f79f-00c04fc2dcd2', '89e95b76-444d-4c62-991a-
0facbeda640c']}, 'filter1': {'ObjectClass': ['dnsNode', 'dnsZoneScope', 'dnsZone']},
'condition': 'selection and not 1 of filter*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The "Audit Directory Service Changes" logging policy must be configured in order to receive events. Audit events are generated only for objects with configured system access control lists (SACLs). Audit events are generated only for objects with configured system access control lists (SACLs) and only when accessed in a manner that matches their SACL settings. This policy covers the following events ids - 5136, 5137, 5138, 5139, 5141. Note that the default policy does not cover User objects. For that a custom AuditRule need to be setup (See https://github.com/OTRF/Set-AuditRule)

Rule Source

SigmaHQ,2c99737c-585d-4431-b61a-c911d86ff32f

Author: Samir Bousseaden, Roberto Rodriguez @Cyb3rWard0g, oscd.community, Tim Shelton, Maxence Fossat

Tactics, Techniques, and Procedures

TA0003, T1098

References

- https://twitter.com/menasec1/status/1111556090137903104
- https://www.specterops.io/assets/resources/an_ace_up_the_sleeve.pdf

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/04/03	high	• New Domain Controller computer account, check user SIDs within the value attribute of event 5136 and verify if it's a regular user or DC computer account.

Rule Details: Windows Defender Disabled

Windows Defender Real-time Protection scanning for malware and other potentially unwanted software was disabled.

Rule ID

```
windows_security_28
```

Query

```
{'selection2': {'EventID': 5001}, 'condition': 'selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1562

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: ADCS Certificate Template Configuration Vulnerability

Detects certificate creation with template allowing risk permission subject.

Rule ID

```
windows_security_29
```

Query

```
{'selection1': {'EventID': 4898, 'TemplateContent|contains': 'CT_FLAG_ENROLLEE_SUPPLIES_SUBJECT'}, 'selection2': {'EventID': 4899, 'NewTemplateContent|contains': 'CT_FLAG_ENROLLEE_SUPPLIES_SUBJECT'}, 'condition': 'selection1 or selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- Certificate services loaded a template would trigger event ID 4898 and certificate Services template was updated would trigger event ID 4899. A risk permission seems to be coming if template contain specific flag.

Rule Source

SigmaHQ,5ee3a654-372f-11ec-8d3d-0242ac130003

Author: Orlinum , BlueDefenZer

Tactics, Techniques, and Procedures

TA0004, T1068

References

- https://www.specterops.io/assets/resources/Certified_Pre-Owned.pdf

Severity

25

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/11/17	low	• Administrator activity • Proxy SSL certificate with subject modification • Smart card enrollement

Rule Details: Security-Enabled Local Group was Deleted

A Security-Enabled Local Group has been deleted. This could be an indication of malicious activity.

Rule ID

`windows_security_31`

Query

```
{'selection1': {'EventID': 4734}, 'selection2': {'SubjectUserName': ''}, 'selection3' : {'SubjectDomainName': ''}, 'condition': 'selection1 and not selection2 and not selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- event_id

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Invoke-Obfuscation RUNDLL LAUNCHER - Security

Detects Obfuscated Powershell via RUNDLL LAUNCHER.

Rule ID

```
windows_security_32
```

Query

```
{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['rundll32.exe', 'she
ll32.dll', 'shellexec_rundll', 'powershell']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,f241cf1b-3a6b-4e1a-b4f9-133c00dd95ca

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/18	medium	• Unknown

Rule Details: Invoke-Obfuscation Via Use Rundll32 - Security

Detects Obfuscated Powershell via use Rundll32 in Scripts.

Rule ID



`windows_security_33`

Query


```
{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['&&', 'rundll32', 'shell32.dll', 'shellexec_rundll'], 'ServiceFileName|contains': ['value', 'invoke', 'comspec', 'iex']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,cd0f7229-d16f-42de-8fe3-fba365fbcb3a

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/09	high	• Unknown

Rule Details: DPAPI Domain Backup Key Extraction

Detects tools extracting LSA secret DPAPI domain backup key from Domain Controllers.

Rule ID

`windows_security_37`

Query

{'selection': {'EventID': 4662, 'ObjectType': 'SecretObject', 'AccessMask': '0x2', 'ObjectName|contains': 'BCKUPKEY'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,4ac1f50b-3bd0-4968-902d-868b4647937e

Author: Roberto Rodriguez @Cyb3rWard0g

Tactics, Techniques, and Procedures

TA0006, T1003.004

References

- https://threathunterplaybook.com/hunts/windows/190620-DomainDPAPIBackupKeyExtraction/notebook.html

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/06/20	high	• Unknown

Rule Details: Addition of Domain Trusts

Addition of domains is seldom and should be verified for legitimacy.

Rule ID

`windows_security_38`

Query

{'selection': {'EventID': 4706}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,0255a820-e564-4e40-af2b-6ac61160335c

Author: Thomas Patzke

Tactics, Techniques, and Procedures

TA0003, T1098

References
N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2019/12/03	medium	• Legitimate extension of domain structure

Rule Details: User Added to Local Administrators

This rule triggers on user accounts that are added to the local Administrators group, which could be legitimate activity or a sign of privilege escalation activity.

Rule ID

```
windows_security_40
```

Query

```
{'selection': {'EventID': 4732}, 'selection_group1': {'TargetUserName|startswith': 'Administr'}, 'selection_group2': {'TargetSid': 'S-1-5-32-544'}, 'filter': {'SubjectUserName|endswith': '$'}, 'condition': 'selection and (1 of selection_group*) and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,c265cf08-3f99-46c1-8d59-328247057d57

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0003, T1078, T1098

References
N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2017/03/14	medium	• Legitimate administrative activity

Rule Details: Sensitive Privilege SeEnableDelegationPrivilege assigned to a User

Identifies the assignment of the SeEnableDelegationPrivilege sensitive "user right" to a user. The SeEnableDelegationPrivilege "user right" enables computer and user accounts to be trusted for delegation. Attackers can abuse this right to compromise Active Directory accounts and elevate their privileges.

Rule ID

`windows_security_41`

Query

```
{'selection1': {'EventID': 4704}, 'selection2': {'PrivilegeList': 'SeEnableDelegation
Privilege'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1212

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/01/27	high	N/A

Rule Details: Suspicious Computer Account Name Change CVE-2021-42287

Detects the renaming of an existing computer account to a account name that doesn't contain a $ symbol as seen in attacks against CVE-2021-42287.

Rule ID

`windows_security_44`

Query


```
{'selection': {'EventID': 4781, 'OldTargetUserName|contains': '$'}, 'filter': {'NewTargetUserName|contains': '$'}, 'condition': 'selection and not filter'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,45eb2ae2-9aa2-4c3a-99a5-6e5077655466

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0005, T1078

References

- https://medium.com/@mvelazco/hunting-for-samaccountname-spoofing-cve-2021-42287-and-domain-controller-impersonation-f704513c8a45

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/12/22	high	• Unknown

Rule Details: Suspicious Remote Logon with Explicit Credentials

Detects suspicious processes logging on with explicit credentials.

Rule ID

`windows_security_45`

Query


```
{'selection': {'EventID': 4648, 'ProcessName|endswith': ['\\cmd.exe', '\\powershell.exe', '\\pwsh.exe', '\\winrs.exe', '\\wmic.exe', '\\net.exe', '\\net1.exe', '\\reg.exe']}, 'filter1': {'TargetServerName': 'localhost'}, 'filter2': {'SubjectUserName|endsw
```

ith': '$', 'TargetUserName|endswith': '$'}, 'condition': 'selection and not 1 of filter*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,941e5c45-cda7-4864-8cea-bbb7458d194a

Author: oscd.community, Teymur Kheirkhabarov @HeirhabarovT, Zach Stanford @svch0st, Tim Shelton

Tactics, Techniques, and Procedures

TA0003, T1078

References

- https://drive.google.com/file/d/1lKya3_mLnR3UQuCoiYruO3qgu052_iS_/view

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/05	medium	• Administrators that use the RunAS command or scheduled tasks

Rule Details: The Password Hash of an Account was Accessed

The Password Hash of an Account was Accessed. This could be an indication of malicious activity.

Rule ID

`windows_security_46`

Query

{'selection1': {'EventID': 4782}, 'condition': 'selection1'}

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Processes Accessing the Microphone and Webcam

Potential adversaries accessing the microphone and webcam in an endpoint.

Rule ID

`windows_security_48`

Query


```
{'selection': {'EventID': [4657, 4656, 4663], 'ObjectName|contains': ['\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\CapabilityAccessManager\\ConsentStore\\microphone\\NonPackaged', '\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\CapabilityAccessManager\\ConsentStore\\webcam\\NonPackaged']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,8cd538a4-62d5-4e83-810b-12d41e428d6e

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research)

Tactics, Techniques, and Procedures

TA0009, T1123

References

- https://twitter.com/duzvik/status/1269671601852813320
- https://medium.com/@7a616368/can-you-track-processes-accessing-the-camera-and-microphone-7e6885b37072

Severity

50

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/06/07	medium	• Unknown

Rule Details: Defrag Deactivation - Security

Detects the deactivation and disabling of the Scheduled defragmentation task as seen by Slingshot APT group.

Rule ID

```
windows_security_49
```

Query

```
{'selection': {'EventID': 4701, 'TaskName': '\\Microsoft\\Windows\\Defrag\\ScheduledDefrag'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- Requirements: Audit Policy : Audit Other Object Access Events > Success

Rule Source

SigmaHQ,c5a178bf-9cfb-4340-b584-e4df39b6a3e7

Author: Florian Roth (Nextron Systems), Bartlomiej Czyz (@bczyz1)

Tactics, Techniques, and Procedures

TA0003, T1053

References

- https://securelist.com/apt-slingshot/84312/

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/03/04	medium	• Unknown

Rule Details: Invoke-Obfuscation STDIN+ Launcher - Security

Detects Obfuscated use of stdin to execute PowerShell.

Rule ID

`windows_security_50`

Query

```
{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['cmd', 'powershell']}, 'selection2': {'ServiceFileName|contains': ['${input}', 'noexit']}, 'selection3': {'ServiceFileName|contains': [' /c ', ' /r ']}, 'condition': 'all of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,0c718a5e-4284-4fb9-b4d9-b9a50b3a1974

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/15	high	• Unknown

Rule Details: Invoke-Obfuscation Via Stdin - Security

Detects Obfuscated Powershell via Stdin in Scripts.

Rule ID

`windows_security_53`

Query

{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['set', '&&'], 'ServiceFileName|contains': ['environment', 'invoke', '${input)']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,80b708f3-d034-40e4-a6c8-d23b7a7db3d1

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/12	high	• Unknown

Rule Details: Microsoft Entra Health Service Agents Registry Keys Access

This detection uses Windows security events to detect suspicious access attempts to the registry key values and sub-keys of Microsoft Entra Health service agents (e.g AD FS). Information from AD Health service agents can be used to potentially abuse some of the features provided by those services in the cloud (e.g. Federation). This detection requires an access control entry (ACE) on the system access control list (SACL) of the following securable object: HKLM:\SOFTWARE\Microsoft\ADHealthAgent. Make sure you set the SACL to propagate to its sub-keys.

Rule ID

`windows_security_54`

Query

{'selection': {'EventID': [4656, 4663], 'ObjectType': 'Key', 'ObjectName': '\\REGISTRY\\MACHINE\\SOFTWARE\\Microsoft\\ADHealthAgent'}, 'filter': {'ProcessName|contains': ['Microsoft.Identity.Health.Adfs.DiagnosticsAgent.exe', 'Microsoft.Identity.Health.Adfs.InsightsService.exe', 'Microsoft.Identity.Health.Adfs.MonitoringAgent.Startup.exe', 'Microsoft.Identity.Health.Adfs.PshSurrogate.exe', 'Microsoft.Identity.Health.Common.Clients.ResourceMonitor.exe']}, 'condition': 'selection and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,1d2ab8ac-1a01-423b-9c39-001510eae8e8

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research), MSTIC

Tactics, Techniques, and Procedures

TA0007, T1012

References

- https://o365blog.com/post/hybridhealthagent/
- https://github.com/OTRF/Set-AuditRule/blob/c3dec5443414231714d850565d364ca73475ade5/rules/registry/aad_connect_health_service_agent.yml

Severity

50

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/26	medium	• Unknown

Rule Details: Invoke-Obfuscation CLIP+ Launcher - Security

Detects Obfuscated use of Clip.exe to execute PowerShell.

Rule ID

windows_security_55

Query

{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['cmd', '&&', 'clipboard]::']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,4edf51e1-cb83-4e1a-bc39-800e396068e3

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/13	high	• Unknown

Rule Details: Password Protected ZIP File Opened (Email Attachment)

Detects the extraction of password protected ZIP archives. See the filename variable for more details on which file has been opened.

Rule ID

`windows_security_59`

Query


```
{'selection': {'EventID': 5379, 'TargetName|contains|all': ['Microsoft_Windows_Shell_ZipFolder:filename', '\\Temporary Internet Files\\Content.Outlook']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,571498c8-908e-40b4-910b-d2369159a3da

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0006, T1212

References

- https://twitter.com/sbousseaden/status/1523383197513379841

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/05/09	high	• Legitimate used of encrypted ZIP files

Rule Details: WMI Persistence - Security

Detects suspicious WMI event filter and command line event consumer based on WMI and Security Logs.

Rule ID

```
windows_security_60
```

Query

```
{'selection': {'EventID': 4662, 'ObjectType': 'WMI Namespace', 'ObjectName|contains':
 'subscription'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,f033f3f3-fd24-4995-97d8-a3bb17550a88

Author: Florian Roth (Nextron Systems), Gleb Sukhodolskiy, Timur Zinniatullin oscd.community

Tactics, Techniques, and Procedures

TA0003, T1546.003

References

- https://twitter.com/mattifestation/status/899646620148539397
- https://www.eideon.com/2018-03-02-THL03-WMIBackdoors/

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/08/22	medium	• Unknown (data set is too small; further testing needed)

Rule Details: Metasploit Or Impacket Service Installation Via SMB PsExec

Detects usage of Metasploit SMB PsExec (exploit/windows/smb/psexec) and Impacket psexec.py by triggering on specific service installation.

Rule ID

`windows_security_61`

Query

```
{'selection': {'EventID': 4697, 'ServiceFileName|re': '^%systemroot%\\\\[a-zA-Z]{8}\\.exe$', 'ServiceName|re': '(^[a-zA-Z]{4}$)|(^[a-zA-Z]{8}$)|(^[a-zA-Z]{16}$)', 'ServiceStartType': '3', 'ServiceType': '0x10'}, 'filter': {'ServiceName': 'PSEXESVC'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,6fb63b40-e02a-403e-9ffd-3bcc1d749442

Author: Bartlomiej Czyz, Relativity

Tactics, Techniques, and Procedures

TA0002, T1569.002, TA0008, T1021.002, T1570

References

- https://bczyz1.github.io/2021/01/30/psexec.html

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/01/21	high	• Possible, different agents with a 8 character binary and a 4, 8 or 16 character service name

Rule Details: AD Privileged Users or Groups Reconnaissance

Detect priv users or groups recon based on 4661 eventid and known privileged users or groups SIDs.

Rule ID

`windows_security_62`

Query


```
{'selection': {'EventID': 4661, 'ObjectType': ['SAM_USER', 'SAM_GROUP']}, 'selection_object': [{'ObjectName|endswith': ['-512', '-502', '-500', '-505', '-519', '-520', '-544', '-551', '-555']}, {'ObjectName|contains': 'admin'}], 'filter': {'SubjectUserName|endswith': '$'}, 'condition': 'selection and selection_object and not filter'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- Requirements: enable Object Access SAM on your Domain Controllers

Rule Source

SigmaHQ,35ba1d85-724d-42a3-889f-2e2362bcaf23

Author: Samir Bousseaden

Tactics, Techniques, and Procedures

TA0007, T1087.002

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/04/03	high	• If source account name is not an admin then its super suspicious

Rule Details: Password Protected ZIP File Opened (Suspicious Filenames)

Detects the extraction of password protected ZIP archives with suspicious file names. See the filename variable for more detail on which file has been opened.

Rule ID

```
windows_security_63
```

Query

```
{'selection': {'EventID': 5379, 'TargetName|contains': 'Microsoft_Windows_Shell_ZipFolder:filename'}, 'selection_filename': {'TargetName|contains': ['invoice', 'new order', 'rechnung', 'factura', 'delivery', 'purchase', 'order', 'payment']}, 'condition': 'selection and selection_filename'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,54f0434b-726f-48a1-b2aa-067df14516e4

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0006, T1212

References

- https://twitter.com/sbousseaden/status/1523383197513379841

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/05/09	high	• Legitimate used of encrypted ZIP files

Rule Details: Microsoft Entra Health Monitoring Agent Registry Keys Access

This detection uses Windows security events to detect suspicious access attempts to the registry key of Microsoft Entra Health monitoring agent. This detection requires an access control entry (ACE) on the system access control list (SACL) of the following securable object HKLM\SOFTWARE\Microsoft\Microsoft Online\Reporting\MonitoringAgent.

Rule ID

```
windows_security_70
```

Query


```
{'selection': {'EventID': [4[illegible] 4663], 'ObjectType': 'Key', 'ObjectName': '\\REGISTRY\\MACHINE\\SOFTWARE\\Microsoft\\Microsoft Online\\Reporting\\MonitoringAgent'}, 'filter': {'ProcessName|contains': ['Microsoft.Identity.Health.Adfs.DiagnosticsAgent.exe', 'Microsoft.Identity.Health.Adfs.InsightsService.exe', 'Microsoft.Identity.Health.Adfs.MonitoringAgent.Startup.exe', 'Microsoft.Identity.Health.Adfs.PshSurrogate.exe', 'Microsoft.Identity.Health.Common.Clients.ResourceMonitor.exe']}, 'condition': 'selection and not filter'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,ff151c33-45fa-475d-af4f-c2f93571f4fe

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research), MSTIC

Tactics, Techniques, and Procedures

TA0007, T1012

References

- https://o365blog.com/post/hybridhealthagent/
- https://github.com/OTRF/Set-AuditRule/blob/c3dec5443414231714d850565d364ca73475ade5/rules/registry/aad_connect_health_monitoring_agent.yml

Severity

50

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/08/26	medium	• Unknown

Rule Details: Invoke-Obfuscation Obfuscated IEX Invocation - Security

Detects all variations of obfuscated powershell IEX invocation code generated by Invoke-Obfuscation framework from the code block linked in the references.

Rule ID

`windows_security_71`

Query

{'selection_eid': {'EventID': 4697}, 'selection_servicefilename': [{'ServiceFileName|re': '\\$PSHome\\[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$PSHome\\
['}, {'ServiceFileName|re': '\\$ShellId\\[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$ShellId\\
['}, {'ServiceFileName|re': '\\$env:Public\\
[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$env:Public\\
['}, {'ServiceFileName|re': '\\$env:ComSpec\\[(\\s*\\d{1,3}\\s*,)
{2}'}, {'ServiceFileName|re': '*mdr*\\W\\s*\\)\\.Name'}, {'ServiceFileName|re': '
\\$VerbosePreference\\.ToString\\
('}, {'ServiceFileName|re': '\\String\\]\\s*\\$VerbosePreference'}], 'condition': 'al
l of selection_*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,fd0f5778-d3cb-4c9a-9695-66759d04702a

Author: Daniel Bohannon (@Mandiant/@FireEye), oscd.community

Tactics, Techniques, and Procedures

TA0005, T1027

References

- https://github.com/danielbohannon/Invoke-Obfuscation/blob/f20e7f843edd0a3a7716736e9eddfa423395dd26/Out-ObfuscatedStringCommand.ps1#L873-L888

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/11/08	high	• Unknown

Rule Details: Possible Shadow Credentials Added

Detects possible addition of shadow credentials to an active directory object.

Rule ID

windows_security_72

Query

{'selection': {'EventID': 51 'AttributeLDAPDisplayName': 'msDS-KeyCredentialLink'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The "Audit Directory Service Changes" logging policy must be configured in order to receive events. Audit events are generated only for objects with configured system access control lists (SACLs). Audit events are generated only for objects with configured system access control lists (SACLs) and only when accessed in a manner that matches their SACL settings. This policy covers the following events ids - 5136, 5137, 5138, 5139, 5141. Note that the default policy does not cover User objects. For that a custom AuditRule need to be setup (See https://github.com/OTRF/Set-AuditRule)

Rule Source

SigmaHQ,f598ea0c-c25a-4f72-a219-50c44411c791

Author: Nasreddine Bencherchali (Nextron Systems), Elastic (idea)

Tactics, Techniques, and Procedures

TA0005, T1556

References

- https://www.elastic.co/guide/en/security/8.4/potential-shadow-credentials-added-to-ad-object.html
- https://cyberstoph.org/posts/2022/03/detecting-shadow-credentials/
- https://twitter.com/SBousseaden/status/1581300963650187264?

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/17	high	• Modifications in the msDS-KeyCredentialLink attribute can be done legitimately by the Microsoft Entra Connect synchronization account or the ADFS service account. These accounts can be added as Exceptions. (From elastic FP section)

Rule Details: Potential Shadow Credentials added to AD Object

Identify the modification of the msDS-KeyCredentialLink attribute in an Active Directory Computer or User Object. Attackers can abuse control over the object and create a key pair,

append to raw public key in the attribute, and obtain persistent and stealthy access to the target user or computer object.

Rule ID

`windows_security_73`

Query

```
{'selection1': {'EventID': 5136}, 'selection2': {'AttributeLDAPDisplayName': 'msDS-KeyCredentialLink'}, 'selection3': {'AttributeValue': 'B:828*'}, 'condition': 'selection1 and selection2 and selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1556

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/01/26	high	• Modifications in the msDS-KeyCredentialLink attribute can be done legitimately by the Microsoft Entra Connect synchronization account or the ADFS service account. These accounts can be added as Exceptions.

Rule Details: Invoke-Obfuscation Via Use Clip - Security

Detects Obfuscated Powershell via use Clip.exe in Scripts.

Rule ID

`windows_security_76`

Query

```
{'selection': {'EventID': 4697, 'ServiceFileName|contains': '(Clipboard|i'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,1a0a2ff1-611b-4dac-8216-8a7b47c618a6

Author: Nikita Nazarov, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/09	high	• Unknown

Rule Details: AD Object WriteDAC Access

Detects WRITE_DAC access to a domain object.

Rule ID

`windows_security_77`

Query

```
{'selection': {'EventID': 4662, 'ObjectServer': 'DS', 'AccessMask': '0x40000', 'Objec
tType': ['19195a5b-6da0-11d0-afd3-
00c04fd930c9', 'domainDNS']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,028c7842-4243-41cd-be6f-12f3cf1a26c7

Author: Roberto Rodriguez @Cyb3rWard0g

Tactics, Techniques, and Procedures

TA0005, T1222.001

References

- https://threathunterplaybook.com/hunts/windows/180815-ADObjectAccessReplication/notebook.html
- https://threathunterplaybook.com/library/windows/active_directory_replication.html
- https://threathunterplaybook.com/hunts/windows/190101-ADModDirectoryReplication/notebook.html

Severity

90

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/09/12	critical	• Unknown

Rule Details: Access to a Sensitive LDAP Attribute

Identify access to sensitive Active Directory object attributes that contains credentials and decryption keys such as unixUserPassword, ms-PKI-AccountCredentials and msPKI-CredentialRoamingTokens.

Rule ID

`windows_security_81`

Query

```
{'selection1': {'EventID': 4662}, 'selection2': {'SubjectUserSid': 'S-1-5-18'}, 'selection3': {'Properties': ['*612cb747-c0e8-4f92-9221-fdd5f15b550d*', '*b8dfa744-31dc-4ef1-ac7c-84baf7ef9da7*', '*b3f93023-9239-4f7c-b99c-6745d87adbc2*', '*b7ff5a38-0818-42b0-8110-d3d154c97f24*']}, 'selection4': {'AccessMask': ['0x0', '0x100']}, 'condition': 'selection1 and (not selection2) and selection3 and (not selection4)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003

References
N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/11/09	medium	N/A

Rule Details: Security Eventlog Cleared

One of the Windows Eventlogs has been cleared. e.g. caused by "wevtutil cl" command execution.

Rule ID

```
windows_security_82
```

Query

```
{'selection_517': {'EventID': 517, 'ProviderName': 'Security'}, 'selection_1102': {'EventID': 1102, 'ProviderName': 'Microsoft-Windows-Eventlog'}, 'condition': '1 of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,d99b79d2-0a6f-4f46-ad8b-260b6e17f982

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0005, T1070.001

References

- https://twitter.com/deviouspolack/status/832535435960209408
- https://www.hybrid-analysis.com/sample/027cc450ef5f8c5f653329641ec1fed91f694e0d229928963b30f6b0d7d3a745?environmentId=100

Severity

75

Suppression Logic Based On

- computer_name
- event_id
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/01/10	high	• Rollout of log collection agents (the setup routine often includes a reset of the local Eventlog) • System provisioning (system reset before the golden image creation)

Rule Details: Operation Wocao Activity - Security

Detects activity mentioned in Operation Wocao report.

Rule ID

`windows_security_83`

Query

```
{'selection': {'EventID': 4799, 'TargetUserName|startswith': 'Administr', 'CallerProcessName|endswith': '\\checkadmin.exe'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,74ad4314-482e-4c3e-b237-3f7ed3b9ca8d

Author: Florian Roth (Nextron Systems), frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0003, T1053.005, TA0005, T1036.004, T1027, TA0007, T1012

References

- https://twitter.com/SBousseaden/status/1207671369963646976

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/12/20	high	Administrators that use checkadmin.exe tool to enumerate local administrators

Rule Details: Kerberos Manipulation

This method triggers on rare Kerberos Failure Codes caused by manipulations of Kerberos messages.

Rule ID

`windows_security_84`

Query


```
{'selection': {'EventID': [675, 4768, 4769, 4771], 'FailureCode': ['0x9', '0xA', '0xB', '0xF', '0x10', '0x11', '0x13', '0x14', '0x1A', '0x1F', '0x21', '0x22', '0x23', '0x24', '0x26', '0x27', '0x28', '0x29', '0x2C', '0x2D', '0x2E', '0x2F', '0x31', '0x32', '0x3E', '0x3F', '0x40', '0x41', '0x43', '0x44']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,f7644214-0eb0-4ace-9455-331ec4c09253

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0006, T1212

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/02/10	high	• Faulty legacy applications

Rule Details: Windows Login Default Point Of Sale Credentials

Windows has reported a login from a user with the default username used by a Point of Sale system. These are well known and are often used as the targets of brute force attacks leading to unauthorized access of the payment infrastructure.

Rule ID

windows_security_85

Query

{'selection2': {'EventID': 4625}, 'selection3': {'TargetUserName': 'aloha'}, 'selection4': {'TargetUserName': 'micros'}, 'selection5': {'TargetUserName': 'posi'}, 'selection7': {'TargetUserName': 'ddpos'}, 'selection8': {'TargetUserName': 'term1'}, 'selection9': {'TargetUserName': 'pos'}, 'selection10': {'TargetUserName': 'pos2'}, 'condition': 'selection2 and (selection3 or selection4 or selection5 or selection7 or selection8 or selection9 or selection10)'}

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1110

References

N/A

Severity

50

Suppression Logic Based On

- computer_name
- event_id
- event_data.TargetUserName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: SCM Database Privileged Operation

Detects non-system users performing privileged operation os the SCM database.

Rule ID

windows_security_86

Query

{'selection': {'EventID': 4674, 'ObjectType': 'SC_MANAGER OBJECT', 'ObjectName': 'servicesactive', 'PrivilegeList': 'SeTakeOwnershipPrivilege'}, 'filter': {'SubjectLogonId': '0x3e4', 'ProcessName|endswith': ':\\Windows\\System32\\services.exe'}, 'condition': 'selection and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,dae8171c-5ec6-4396-b210-8466585b53e9

Author: Roberto Rodriguez @Cyb3rWard0g, Tim Shelton

Tactics, Techniques, and Procedures

TA0005, T1548

References

- https://threathunterplaybook.com/hunts/windows/190826-RemoteSCMHandle/notebook.html

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/08/15	medium	• Unknown

Rule Details: Security-Enabled Universal Group was Deleted

A Security-Enabled Universal Group has been deleted. This could be an indication of malicious activity.

Rule ID

```
windows_security_87
```

Query

```
{'selection1': {'EventID': 4758}, 'selection2': {'SubjectUserName': ''}, 'selection3' : {'SubjectDomainName': ''}, 'condition': 'selection1 and not selection2 and not selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Reconnaissance Activity

Detects activity as "net user administrator /domain" and "net group domain admins /domain".

Rule ID

```
windows_security_88
```

Query

```
{'selection': {'EventID': 4661, 'AccessMask': '0x2d', 'ObjectType': ['SAM_USER', 'SAM
_GROUP'], 'ObjectName|startswith': 'S-1-5-21-
', 'ObjectName|endswith': ['-500', '-512']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The volume of Event ID 4661 is high on Domain Controllers and therefore "Audit SAM" and "Audit Kernel Object" advanced audit policy settings are not configured in the recommendations for server systems

Rule Source

SigmaHQ,968eef52-9cff-4454-8992-1e74b9cbad6c

Author: Florian Roth (Nextron Systems), Jack Croock (method), Jonhnathan Ribeiro (improvements), oscd.community

Tactics, Techniques, and Procedures

TA0007, T1087.002, T1069.002

References

- https://findingbad.blogspot.de/2017/01/hunting-what-does-it-look-like.html

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/03/07	high	• Administrator activity

Rule Details: Kerberos Policy was Changed

The Kerberos policy was changed. This could be an indication of malicious activity.

Rule ID

```
windows_security_89
```

Query

```
{'selection1': {'EventID': 4713}, 'condition': 'selection1'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Invoke-Obfuscation VAR+ Launcher - Security

Detects Obfuscated use of Environment Variables to execute PowerShell.

Rule ID

windows_security_90

Query



{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['cmd', '"set', '-f'], 'ServiceFileName|contains': ['/c', '/r']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,dcf2db1f-f091-425b-a821-c05875b8925a

Author: Jonathan Cheong, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/15	high	• Unknown

Rule Details: Hacking Tool detected by Antivirus

The Windows Defender AntiVirus has detected a hacking tool in the system. This is an indication that an attacker has access to your system and is trying to install tools to gain persistence, compromise other systems, etc.

Rule ID

windows_security_92

Query

{'selection2': {'EventID': 1116}, 'selection3': {'MalwareFamily|re': '(?:hacktool|meterpreter|metasploit|powersploit|cobalt|mimikatz|wpdump|htool|wce)'}, 'selection4': {'

FileName': ''}, 'selection5': {'MalwareFamily': ''}, 'condition': 'selection2 and selection3 and not selection4 and not selection5'}

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0007, T1518

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: WCE wceaux.dll Access

Detects wceaux.dll access while WCE pass-the-hash remote command execution on source host.

Rule ID

`windows_security_93`

Query

{'selection': {'EventID': [4656, 4658, 4660, 4663], 'ObjectName|endswith': '\\wceaux.dll'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,1de68c67-af5c-4097-9c85-fe5578e09e67

Author: Thomas Patzke

Tactics, Techniques, and Procedures

TA0006, T1003

References

- https://www.jpcert.or.jp/english/pub/sr/ir_research.html
- https://jpcertcc.github.io/ToolAnalysisResultSheet

Severity

90

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/06/14	critical	• Unknown

Rule Details: Important Scheduled Task Deleted/Disabled

Detects when adversaries stop services or processes by deleting or disabling their respective scheduled tasks in order to conduct data destructive activities.

Rule ID

```
windows_security_95
```

Query

```
{'selection': {'EventID': [4699, 4701], 'TaskName|contains': ['\\Windows\\SystemRestore\\SR', '\\Windows\\Windows Defender\\', '\\Windows\\BitLocker', '\\Windows\\Windows Backup\\', '\\Windows\\WindowsUpdate\\', '\\Windows\\UpdateOrchestrator\\Schedule', '\\Windows\\ExploitGuard']}, 'filter_sys_username': {'EventID': 4699, 'SubjectUserName|endswith': '$', 'TaskName|contains': '\\Windows\\Windows Defender\\'}, 'condition': 'selection and not 1 of filter_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The Advanced Audit Policy setting Object Access > Audit Other Object Access Events has to be configured to allow this detection. We also recommend extracting the Command field from the embedded XML in the event data.

Rule Source

SigmaHQ,7595ba94-cf3b-4471-aa03-4f6baa9e5fad

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0003, T1053.005

References

- https://learn.microsoft.com/en-us/windows/security/threat-protection/auditing/event-4699
- https://learn.microsoft.com/en-us/windows/security/threat-protection/auditing/event-4701

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/05	high	• Unknown

Rule Details: Account Tampering - Suspicious Failed Logon Reasons

This method uses uncommon error codes on failed logons to determine suspicious activity and tampering with accounts that have been disabled or somehow restricted.

Rule ID

`windows_security_97`

Query

```
{'selection': {'EventID': [4625, 4776], 'Status': ['0xC0000072', '0xC000006F', '0xC000070', '0xC0000413', '0xC000018C', '0xC000015B']}, 'filter': {'SubjectUserSid': 'S-1-0-0'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,9eb99343-d336-4020-a3cd-67f3819e68ee

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0003, T1078

References

- https://docs.microsoft.com/en-us/windows/security/threat-protection/auditing/event-4625
- https://twitter.com/SBousseaden/status/1101431884540710913

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2017/02/19	medium	• User using a disabled account

Rule Details: Encrypted Data Recovery Policy was Changed

The Encrypted Data policy was changed. This could be an indication of malicious activity.

Rule ID

`windows_security_99`

Query

```
{'selection1': {'EventID': 4714}, 'condition': 'selection1'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Secure Deletion with SDelete

Detects renaming of file while deletion with SDelete tool.

Rule ID

`windows_security_101`

Query

{'selection': {'EventID': [4656, 4663, 4658], 'ObjectName|endswith': ['.AAA', '.ZZZ']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,39a80702-d7ca-4a83-b776-525b1f86a36d

Author: Thomas Patzke

Tactics, Techniques, and Procedures

TA0005, T1070.004, T1027.005, T1553.002, TA0040, T1485

References

- https://jpcertcc.github.io/ToolAnalysisResultSheet/details/sdelete.htm
- https://www.jpcert.or.jp/english/pub/sr/ir_research.html
- https://docs.microsoft.com/en-gb/sysinternals/downloads/sdelete

Severity

50

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/06/14	medium	• Legitimate usage of SDelete

Rule Details: Invoke-Obfuscation COMPRESS OBFUSCATION - Security

Detects Obfuscated Powershell via COMPRESS OBFUSCATION.

Rule ID

`windows_security_102`

Query

{'selection': {'EventID': 4697, 'ServiceFileName|contains|all': ['new-object', 'text.encoding]::ascii', 'readtoend'], 'ServiceFileName|contains': ['system.io.compression.deflatestream', 'system.io.streamreader']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,7a922f1b-2635-4d6c-91ef-af228b198ad3

Author: Timur Zinniatullin, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0005, T1027

References

- https://github.com/SigmaHQ/sigma/issues/1009

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2020/10/18	medium	• Unknown

Rule Details: ADCS Certificate Template Configuration Vulnerability with Risky EKU

Detects certificate creation with template allowing risk permission subject and risky EKU.

Rule ID

`windows_security_104`

Query


```
{'selection10': {'EventID': 4898, 'TemplateContent|contains': ['1.3.6.1.5.5.7.3.2', '
1.3.6.1.5.2.3.4', '1.3.6.1.4.1.311.20.2.2', '2.5.29.37.0']}, 'selection11': {'Templat
eContent|contains': 'CT_FLAG_ENROLLEE_SUPPLIES_SUBJECT'}, 'selection20': {'EventID':
4899, 'NewTemplateContent|contains': ['1.3.6.1.5.5.7.3.2', '1.3.6.1.5.2.3.4', '1.3.6.
1.4.1.311.20.2.2', '2.5.29.37.0']}, 'selection21': {'NewTemplateContent|contains': 'C
T_FLAG_ENROLLEE_SUPPLIES_SUBJECT'}, 'condition': '(selection10 and selection11) or (s
election20 and selection21)'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- Certificate services loaded a template would trigger event ID 4898 and certificate Services template was updated would trigger event ID 4899. A risk permission seems to be coming if template contain specific flag with risky EKU.

Rule Source

SigmaHQ,bfbd3291-de87-4b7c-88a2-d6a5deb28668

Author: Orlinum , BlueDefenZer

Tactics, Techniques, and Procedures

TA0004, T1068

References

- https://www.specterops.io/assets/resources/Certified_Pre-Owned.pdf

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/11/17	high	• Administrator activity • Proxy SSL certificate with subject modification • Smart card enrollement

Rule Details: PowerShell Scripts Installed as Services - Security

Detects powershell script installed as a Service.

Rule ID

`windows_security_106`

Query

```
{'selection': {'EventID': 4697, 'ServiceFileName|contains': ['powershell', 'pwsh']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,2a926e6a-4b81-4011-8a96-e36cc8c04302

Author: oscd.community, Natali ornikova

Tactics, Techniques, and Procedures

TA0002, T1569.002

References

- https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/06	high	• Unknown

Rule Details: AdminSDHolder Backdoor

Detects modifications in the AdminSDHolder object. Attackers can abuse the SDProp process to implement a persistent backdoor in Active Directory. SDProp compares the permissions on protected objects with those defined on the AdminSDHolder object. If the permissions on any of the protected accounts and groups do not match, the permissions on the protected accounts and groups are reset to match those of the domain's AdminSDHolder object, regaining their Administrative Privileges.

Rule ID

```
windows_security_108
```

Query

```
{'selection1': {'EventID': 5136}, 'selection2': {'ObjectDN': 'CN=AdminSDHolder,CN=System*'}, 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/01/31	high	N/A

Rule Details: KRBTGT Delegation Backdoor

Identifies the modification of the msDS-AllowedToDelegateTo attribute to KRBTGT. Attackers can use this technique to maintain persistence to the domain by having the ability to request tickets for the KRBTGT service.

Rule ID

```
windows_security_109
```

Query

```
{'selection1': {'EventID': 4738}, 'selection2': {'AllowedToDelegateTo': '*krbtgt*'},
'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098, TA0006, T1558

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/01/27	high	N/A

Rule Details: HybridConnectionManager Service Installation

Rule to detect the Hybrid Connection Manager service installation.

Rule ID



`windows_security_110`

Query


```
{'selection': {'EventID': 4697, 'ServiceName': 'HybridConnectionManager', 'ServiceFileName|contains': 'HybridConnectionManager'}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,0ee4d8a5-4e67-4faf-acfa-62a78457d1f2

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research)

Tactics, Techniques, and Procedures

TA0003, T1554

References

- https://twitter.com/Cyb3rWard0g/status/1381642789369286662

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2021/04/12	high	• Legitimate use of Hybrid Connection Manager via Azure function apps.

Rule Details: Windows Defender Exclusion Set

Detects scenarios where an windows defender exclusion was added in registry where an entity would want to bypass antivirus scanning from windows defender.

Rule ID

`windows_security_111`

Query

{'selection': {'EventID': [4657, 4656, 4660, 4663], 'ObjectName|contains': '\\Microsoft\\Windows Defender\\Exclusions\\'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- Requirements: Audit Policy : Security Settings/Local Policies/Audit Policy, Registry System Access Control (SACL): Auditing/User

Rule Source

SigmaHQ,e9c8808f-4cfb-4ba9-97d4-e5f3beaa244d

Author: @BarryShooshooga, Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0005, T1562.001

References

- https://www.bleepingcomputer.com/news/security/gootkit-malware-bypasses-windows-defender-by-setting-path-exclusions/

Severity

75

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/26	high	• Intended inclusions by administrator

Rule Details: Password Change on Directory Service Restore Mode (DSRM) Account

The Directory Service Restore Mode (DSRM) account is a local administrator account on Domain Controllers. Attackers may change the password to gain persistence.

Rule ID

`windows_security_112`

Query

{'selection': {'EventID': 4794}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,53ad8e36-f573-46bf-4-15ba5bf4bb51

Author: Thomas Patzke

Tactics, Techniques, and Procedures

TA0003, T1098

References

- https://adsecurity.org/?p=1714

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
stable	2017/02/19	high	• Initial installation of a domain controller

Rule Details: Hacktool Ruler

This events that are generated when using the hacktool Ruler by Sensepost.

Rule ID

`windows_security_113`

Query

```
{'selection1': {'EventID': 4776, 'Workstation': 'RULER'}, 'selection2': {'EventID': [
4624, 4625], 'WorkstationName': 'RULER'}, 'condition': '(1 of selection*)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,24549159-ac1b-479c-8175-d42aea947cae

Author: Florian Roth (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059, TA0005, T1550.002, TA0007, T1087, TA0009, T1114

References

- https://github.com/sensepost/ruler
- https://github.com/sensepost/ruler/issues/47

- https://github.com/staaldraad/go-ntlm/blob/cd032d41aa8[illegible]5751c07cb7945400c0f5c81e2eb/ntlm/ntlmv1.go#L427
- https://docs.microsoft.com/en-us/windows/security/threat-protection/auditing/event-4776
- https://docs.microsoft.com/en-us/windows/security/threat-protection/auditing/event-4624

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/05/31	high	• Go utilities that use staaldraad awesome NTLM library

Rule Details: Tap Driver Installation - Security

Well-known TAP software installation. Possible preparation for data exfiltration using tunnelling techniques.

Rule ID

`windows_security_114`

Query

```
{'selection': {'EventID': 4697, 'ServiceFileName|contains': 'tap0901'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,9c8afa4d-0022-48f0-9456-3712466f9701

Author: Daniil Yugoslavskiy, Ian Davis, oscd.community

Tactics, Techniques, and Procedures

TA0010, T1048

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	medium	• Legitimate OpenVPN TAP insntallation

Rule Details: Suspicious Scheduled Task Creation

Detects suspicious scheduled task creation events. Based on attributes such as paths, commands line flags, etc.

Rule ID

`windows_security_115`

Query


```
{'selection_eid': {'EventID': 4698}, 'selection_paths': {'TaskContent|contains': ['\\AppData\\Local\\Temp\\', '\\AppData\\Roaming\\', '\\Users\\Public\\', '\\WINDOWS\\Temp\\', 'C:\\Temp\\', '\\Desktop\\', '\\Downloads\\', '\\Temporary Internet', 'C:\\ProgramData\\', 'C:\\Perflogs\\']}, 'selection_commands': {'TaskContent|contains': ['regsvr32', 'rundll32', 'cmd.exe</Command>', 'cmd</Command>', '<Arguments>/c ', '<Arguments>/k ', '<Arguments>/r ', 'powershell', 'pwsh', 'mshta', 'wscript', 'cscript', 'certutil', 'bitsadmin', 'bash.exe', 'bash ', 'scrcons', 'wmic ', 'wmic.exe', 'forfiles', 'scriptrunner', 'hh.exe']}, 'condition': 'all of selection_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The Advanced Audit Policy setting Object Access > Audit Other Object Access Events has to be configured to allow this detection. We also recommend extracting the Command field from the embedded XML in the event data.

Rule Source

SigmaHQ,3a734d25-df5c-4b99-8034-af1ddb5883a4

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0003, T1053.005

References

- https://learn.microsoft.com/en-us/windows/security/threat-protection/auditing/event-4698

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/12/05	high	• Unknown

Rule Details: User Couldn't Call a Privileged Service 'LsaRegisterLogonProcess

The 'LsaRegisterLogonProcess' function verifies that the application making the function call is a logon process by checking that it has the SeTcbPrivilege privilege set. Possible Rubeus tries to get a handle to LSA.

Rule ID

`windows_security_116`

Query

```
{'selection': {'EventID': 4673, 'Service': 'LsaRegisterLogonProcess()', 'Keywords': '0x8010000000000000'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,6daac7fc-77d1-449a-a71a-e6b4d59a0e54

Author: Roberto Rodriguez (source), Ilyas Ochkov (rule), oscd.community

Tactics, Techniques, and Procedures

TA0006, T1558.003

References

- https://posts.specterops.io/hunting-in-active-directory-unconstrained-delegation-forests-trusts-71f2b33688e1

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	high	• Unknown

Rule Details: User Account Deleted

A user account has been deleted. This could be an indication of malicious activity.

Rule ID

```
windows_security_118
```

Query

```
{'selection1': {'EventID': 4726}, 'condition': 'selection1'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Possible DC Shadow Attack

Detects DCShadow via create new SPN.

Rule ID

```
windows_security_121
```

Query

```
{'selection1': {'EventID': 4742, 'ServicePrincipalNames|contains': 'GC/'}, 'selection
2': {'EventID': 5136, 'AttributeLDAPDisplayName': 'servicePrincipalName', 'AttributeV
alue|startswith': 'GC/'}, 'condition': '1 of selection*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The "Audit Directory Service Changes" logging policy must be configured in order to receive events. Audit events are generated only for objects with configured system access control lists (SACLs). Audit events are generated only for objects with configured system access control lists (SACLs) and only when accessed in a manner that matches their SACL settings. This policy covers the following events ids - 5136, 5137, 5138, 5139, 5141. Note that the default policy does not cover User objects. For that a custom AuditRule need to be setup (See https://github.com/OTRF/Set-AuditRule)

Rule Source

SigmaHQ,32e19d25-4aed-4860-a55a-be99cb0bf7ed

Author: Ilyas Ochkov, oscd.community, Chakib Gzenayi (@Chak092), Hosni Mribah

Tactics, Techniques, and Procedures

TA0005, T1207

References

- https://twitter.com/gentilkiwi/status/1003236624925413376
- https://gist.github.com/gentilkiwi/dcc132457408cf11ad2061340dcb53c2

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/10/25	medium	• Valid on domain controllers; exclude known DCs

Rule Details: Replay Attack Detected

Detects possible Kerberos Replay Attack on the domain controllers when "KRB_AP_ERR_REPEAT" Kerberos response is sent to the client.

Rule ID

```
windows_security_124
```

Query

```
{'selection': {'EventID': 4649}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,5a44727c-3b85-4713-8c44-4401d5499629

Author: frack113

Tactics, Techniques, and Procedures

TA0008, T1550

References

- https://github.com/Yamato-Security/EnableWindowsLogSettings/blob/7f6d755d45ac7cc9fc35b0cbf498e6aa4ef19def/ConfiguringSecurityLogAuditPolicies.md
- https://learn.microsoft.com/en-us/windows/security/threat-protection/auditing/event-4649

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/14	high	• Unknown

Rule Details: Security-Enabled Global Group was Deleted

A Security-Enabled Global Group has been deleted. This could be an indication of malicious activity.

Rule ID

`windows_security_127`

Query

```
{'selection1': {'EventID': 4730}, 'selection2': {'SubjectUserName': ''}, 'selection3': {'SubjectDomainName': ''}, 'condition': 'selection1 and not selection2 and not selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: Credential Dumping Tools Service Execution - Security

Detects well-known credential dumping tools execution via service execution events.

Rule ID

`windows_security_128`

Query


```
{'selection': {'EventID': 4697, 'ServiceFileName|contains': ['fgexec', 'dumpsvc', 'cachedump', 'mimidrv', 'gsecdump', 'servpw', 'pwdump']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The 'System Security Extension' audit subcategory need to be enabled to log the EID 4697

Rule Source

SigmaHQ,f0d1feba-4344-4ca9-8121-a6c97bd6df52

Author: Florian Roth (Nextron Systems), Teymur Kheirkhabarov, Daniil Yugoslavskiy, oscd.community

Tactics, Techniques, and Procedures

TA0002, T1569.002, TA0006, T1003

References

- https://www.slideshare.net/heirhabarov/hunting-for-credentials-dumping-in-windows-environment

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/03/05	high	• Legitimate Administrator using credential dumping tool for password recovery

Rule Details: Modification of the msPKIAccountCredentials

Identify the modification of the msPKIAccountCredentials attribute in an Active Directory User Object. Attackers can abuse the credentials roaming feature to overwrite an arbitrary file for privilege escalation. ms-PKI-AccountCredentials contains binary large objects (BLOBs) of encrypted credential objects from the credential manager store, private keys, certificates, and certificate requests.

Rule ID

```
windows_security_129
```

Query

```
{'selection1': {'EventID': 5136}, 'selection2': {'AttributeLDAPDisplayName': 'msPKIAccountCredentials'}, 'selection3': {'OperationType': '%%14674'}, 'selection4': {'SubjectUserSid': 'S-1-5-18'}, 'condition': 'selection1 and selection2 and selection3 and (not selection4)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0004, T1068

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2022/11/09	medium	N/A

Rule Details: Device Installation Blocked

Detects an installation of a device that is forbidden by the system policy.

Rule ID

`windows_security_130`

Query

```
{'selection': {'EventID': 6423}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,c9eb55c3-b468-40ab-9089-db2862e42137

Author: frack113

Tactics, Techniques, and Procedures

TA0001, T1200

References

- https://github.com/Yamato-Security/EnableWindowsLogSettings/blob/7f6d755d45ac7cc9fc35b0cbf498e6aa4ef19def/ConfiguringSecurityLogAuditPolicies.md
- https://learn.microsoft.com/en-us/windows/security/threat-protection/auditing/event-6423

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/10/14	medium	• Unknown

Rule Details: Webshell detected by Antivirus

The Windows Defender AntiVirus has detected a webshell in the system. This is an indication that an attacker gained access to your server and he is trying to deploy a webshell in the webserver.

Rule ID

windows_security_131

Query

```
{'selection1': {'EventID': 1116}, 'selection2': {'MalwareFamily|contains': 'webshell'
}, 'selection3': {'MalwareFamily|contains': 'chopper'}, 'selection4': {'MalwareFamily
|re': '(?:PHP|JSP|ASP) [\\/]Backdoor'}, 'selection5': {'MalwareFamily|re': 'Backdoor[
.:]
(?:PHP|JSP|ASP)'}, 'condition': 'selection1 and (selection2 or selection3 or selectio
n4 or selection5)'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1505.003

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2022/05/01	medium	N/A

Rule Details: OilRig APT Schedule Task Persistence - Security

Detects OilRig schedule task persistence as reported by Nyotron in their March 2018 report.

Rule ID

windows_security_132

Query

```
{'selection_service': {'EventID': 4698, 'TaskName': ['SC Scheduled Scan', 'UpdatMachi
ne']}, 'condition': 'selection_service'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,c0580559-a6bd-4ef6-b9b7-83703d98b561

Author: Florian Roth (Nextron Systems), Markus Neis, Jonhnathan Ribeiro, Daniil Yugoslavskiy, oscd.community

Tactics, Techniques, and Procedures

TA0003, T1053.005, T1543.003, TA0005, T1112, TA0011, T1071.004

References

- https://web.archive.org/web/20180402134442/https://nyotron.com/wp-content/uploads/2018/03/Nyotron-OilRig-Malware-Report-March-2018C.pdf

Severity

90

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/03/23	critical	• Unlikely

Rule Details: Remote WMI ActiveScriptEventConsumers

Detect potential adversaries leveraging WMI ActiveScriptEventConsumers remotely to move laterally in a network.

Rule ID

`windows_security_134`

Query

```
{'selection': {'EventID': 4624, 'LogonType': '3', 'ProcessName|endswith': 'scrcons.exe'}, 'filter': {'TargetLogonId': '0x3e7'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,9599c180-e3a8-4743-8f92-7fb96d3be648

Author: Roberto Rodriguez (Cyb3rWard0g), OTR (Open Threat Research)

Tactics, Techniques, and Procedures

TA0003, T1546.003

References

- https://threathunterplaybook.com/hunts/windows/200902-RemoteWMIActiveScriptEventConsumers/notebook.html

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/09/02	high	• SCCM

Rule Details: RottenPotato Like Attack Pattern

Detects logon events that have characteristics of events generated during an attack with RottenPotato and the like.

Rule ID

```
windows_security_136
```

Query

```
{'selection': {'EventID': 4624, 'LogonType': '3', 'TargetUserName|re': '(?:ANONYMOUS(
_| )LOGON)$', 'WorkstationName': ['-
', ''], 'IpAddress': ['127.0.0.1', '::1']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,16f5d8ca-44bd-47c8-acbe-6fc95a16c12f

Author: @SBousseaden, Florian Roth

Tactics, Techniques, and Procedures

TA0004, T1068

References

- https://twitter.com/SBousseaden/status/1195284233729777665

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/11/15	high	• Unknown

Rule Details: Successful Overpass the Hash Attempt

Detects successful logon with logon type 9 (NewCredentials) which matches the Overpass the Hash behavior of e.g Mimikatz's sekurlsa::pth module.

Rule ID

```
windows_security_138
```

Query

```
{'selection': {'EventID': 4624, 'LogonType': '9', 'LogonProcessName': 'seclogo', 'AuthenticationPackageName': 'Negotiate'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,192a0330-c20b-4356-90b6-7b7049ae0b87

Author: Roberto Rodriguez (source), Dominik Schaudel (rule)

Tactics, Techniques, and Procedures

TA0005, T1550.002

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/02/12	high	• Runas command-line tool using /netonly parameter • Legitimate use of Active Directory management tools (e.g., ADManager Plus) • Group Policy Client service (gpsvc) applying user-specific settings

Rule Details: DiagTrackEoP Default Login Username

Detects the default "UserName" used by the DiagTrackEoP POC.

Rule ID

`windows_security_140`

Query

```
{'selection': {'EventID': 4624, 'LogonType': '9', 'TargetOutboundUserName': 'thisisnotvaliduser'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,2111118f-7e46-4fc8-974a-59fd8ec95196

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0005, T1078

References

- https://github.com/Wh04m1001/DiagTrackEoP/blob/3a2fc99c9700623eb7dc7d4b5f314fd9ce5ef51f/main.cpp#L46

Severity

90

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/08/03	critical	• Unlikely

Rule Details: Access Token Abuse

This rule tries to detect token impersonation and theft. (Example: DuplicateToken(Ex) and ImpersonateLoggedOnUser with the LOGON32_LOGON_NEW_CREDENTIALS flag.)

Rule ID

`windows_security_142`

Query

{'selection': {'EventID': 4624, 'LogonType': '9', 'LogonProcessName': 'Advapi', 'AuthenticationPackageName': 'Negotiate', 'ImpersonationLevel': '%%1833'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,02f7c9c1-1ae8-4c6a-8add-04693807f92f

Author: Michaela Adams, Zach Mathis

Tactics, Techniques, and Procedures

TA0005, T1134.001

References

- https://www.elastic.co/fr/blog/how-attackers-abuse-access-token-manipulation
- https://www.manageengine.com/log-management/cyber-security/access-token-manipulation.html

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/11/06	medium	• Anti-Virus

Rule Details: KrbRelayUp Attack Pattern

Detects logon events that have characteristics of events generated during an attack with KrbRelayUp and the like.

Rule ID

windows_security_143

Query

{'selection1': {'EventID': 4624, 'LogonType': '3', 'AuthenticationPackageName': 'Kerberos', 'TargetUserSid|startswith': 'S-1-5-21-
', 'TargetUserSid|endswith': '-500'}, 'selection2': {'IpAddress': ['::1', '127.0.0.1']}, 'condition': 'selection1 and selection2'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,749c9f5e-b353-4b90-a9c1-05243357ca4b

Author: Elastic, @SBousseaden

Tactics, Techniques, and Procedures

TA0008, T1550

References

- https://github.com/elastic/detection-rules/blob/fb6ee2c69864ffdfe347bf3b050cb931f53067a6/rules/windows/privilege_escalation_krbrelayup_suspicious_logon.toml

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2022/04/27	high	• Unknown

Rule Details: Password Dumper Activity on LSASS

Detects process handle on LSASS process with certain access mask and object type SAM_DOMAIN.

Rule ID

`windows_security_146`

Query

```
{'selection': {'EventID': 4656, 'ProcessName|endswith': '\\lsass.exe', 'AccessMask': '0x705', 'ObjectType': 'SAM_DOMAIN'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,aa1697b7-d611-4f9a-9cb2-5125b4ccfd5c

Author: sigma

Tactics, Techniques, and Procedures

TA0006, T1003.001

References

- https://twitter.com/jackcr/status/807385668833968128

Severity

75

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2017/02/12	high	• Unknown

Rule Details: SAM Registry Hive Handle Request

Detects handles requested to SAM registry hive.

Rule ID

```
windows_security_147
```

Query

```
{'selection': {'EventID': 4656, 'ObjectType': 'Key', 'ObjectName|endswith': '\\SAM'},
 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,f8748f2c-89dc-4d95-afb0-5a2dfdbad332

Author: Roberto Rodriguez @Cyb3rWard0g

Tactics, Techniques, and Procedures

TA0007, T1012, TA0006, T1552.002

References

- https://threathunterplaybook.com/hunts/windows/190725-SAMRegistryHiveHandleRequest/notebook.html

Severity

75

Suppression Logic Based On

- computer_name
- event_data.ObjectNam
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/08/12	high	• Unknown

Rule Details: Impacket PsExec Execution

Detects execution of Impacket's psexec.py.

Rule ID

```
windows_security_150
```

Query

```
{'selection1': {'EventID': 5145, 'ShareName': '\\\\*\\IPC$', 'RelativeTargetName|contains': ['RemCom_stdin', 'RemCom_stdout', 'RemCom_stderr']}, 'condition': 'selection1'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The advanced audit policy setting "Object Access > Audit Detailed File Share" must be configured for Success/Failure

Rule Source

SigmaHQ,32d56ea1-417f-44ff-822b-882873f5f43b

Author: Bhabesh Raj

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/12/14	high	• Unknown

Rule Details: Remote Task Creation via ATSVC Named Pipe

Detects remote task creation vi exe or API interacting with ATSVC namedpipe.

Rule ID

`windows_security_151`

Query

```
{'selection': {'EventID': 5145, 'ShareName': '\\\\*\\IPC$', 'RelativeTargetName': 'atsvc', 'Accesses|contains': ['WriteData', '%%4417']}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The advanced audit policy setting "Object Access > Audit Detailed File Share" must be configured for Success/Failure

Rule Source

SigmaHQ,f6de6525-4509-495a-8a82-1f8b0ed73a00

Author: Samir Bousseaden

Tactics, Techniques, and Procedures

TA0003, T1053.002

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/04/03	medium	• Unknown

Rule Details: Protected Storage Service Access

Detects access to a protected_storage service over the network. Potential abuse of DPAPI to extract domain backup keys from Domain Controllers.

Rule ID

`windows_security_152`

Query

{'selection': {'EventID': 5145, 'ShareName|contains': 'IPC', 'RelativeTargetName': 'protected_storage'}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,45545954-4016-43c6-855e-eae8f1c369dc

Author: Roberto Rodriguez @Cyb3rWard0g

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

- https://threathunterplaybook.com/hunts/windows/190620-DomainDPAPIBackupKeyExtraction/notebook.html

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/08/10	high	• Unknown

Rule Details: Persistence and Execution at Scale via GPO Scheduled Task

Detect lateral movement using GPO scheduled task, usually used to deploy ransomware at scale.

Rule ID

`windows_security_153`

Query

{'selection': {'EventID': 5145, 'ShareName': '*\\SYSVOL', 'RelativeTargetName|endswith': 'ScheduledTasks.xml', 'Accesses|contains': ['WriteData', '%%4417']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

- The advanced audit policy setting "Object Access > Audit Detailed File Share" must be configured for Success/Failure

Rule Source

SigmaHQ,a8f29a7b-b137-4446-80a0-b804272f3da2

Author: Samir Bousseaden

Tactics, Techniques, and Procedures

TA0003, T1053.005

References

- https://twitter.com/menasec1/status/1106899890377052160
- https://www.secureworks.com/blog/ransomware-as-a-distraction

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/04/03	high	• If the source IP is not localhost then it's super suspicious, better to monitor both local and remote changes to GPO scheduledtasks

Rule Details: First Time Seen Remote Named Pipe

This detection excludes known named pipes accessible remotely and notify on newly observed ones, may help to detect lateral movement and remote exec using named pipes.

Rule ID

`windows_security_154`

Query

```
{'selection1': {'EventID': 5145, 'ShareName': '\\\\*\\IPC$'}, 'false_positives': {'RelativeTargetName': ['atsvc', 'samr', 'lsarpc', 'lsass', 'winreg', 'netlogon', 'srvsvc', 'protected_storage', 'wkssvc', 'browser', 'netdfs', 'svcctl', 'spoolss', 'ntsvcs', 'LSM_API_service', 'HydraLsPipe', 'TermSrv_API_service', 'MsFteWds', 'sql\\query', 'eventlog']}, 'condition': 'selection1 and not false_positives'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

- The advanced audit policy setting "Object Access > Audit Detailed File Share" must be configured for Success/Failure

Rule Source

SigmaHQ,52d8b0c6-53d6-439a-9e41-52ad442ad9ad

Author: Samir Bousseaden

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

- https://twitter.com/menasec1/status/1104489274387451904

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/04/03	high	• Update the excluded named pipe to filter out any newly observed legit named pipe

Rule Details: DCERPC SMB Spoolss Named Pipe

Detects the use of the spoolss named pipe over SMB. This can be used to trigger the authentication via NTLM of any machine that has the spoolservice enabled.

Rule ID

`windows_security_155`

Query

```
{'selection': {'EventID': 5145, 'ShareName': '\\\\*\\IPC$', 'RelativeTargetName': 'spoolss'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,214e8f95-100a-4e04-bb31-ef6cba8ce07e

Author: OTR (Open Threat Research)

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

- https://posts.specterops.io/hunting-in-active-directory-unconstrained-delegation-forests-trusts-71f2b33688e1
- https://dirkjanm.io/a-different-way-of-abusing-zerologon/
- https://twitter.com/_dirkjan/status/1309214379003588608

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2018/11/28	medium	• Domain Controllers acting as printer servers too? :)

Rule Details: T1047 Wmiprvse Wbemcomn DLL Hijack

Detects a threat actor creating a file named `wbemcomn.dll` in the `C:\Windows\System32\wbem\` directory over the network for a WMI DLL Hijack scenario.

Rule ID

`windows_security_157`

Query

```
{'selection': {'EventID': 5145, 'RelativeTargetName|endswith': '\\wbem\\wbemcomn.dll'}, 'filter': {'SubjectUserName|endswith': '$'}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,f6c68d5f-e101-4b86-8c84-7d96851fd65c

Author: Roberto Rodriguez @Cyb3rWard0g, Open Threat Research (OTR)

Tactics, Techniques, and Procedures

TA0002, T1047, TA0008, T1021.002

References

- https://threathunterplaybook.com/hunts/windows/201009-RemoteWMIWbemcomnDLLHijack/notebook.html

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/12	high	• Unknown

Rule Details: CVE-2021-1675 Print Spooler Exploitation IPC Access

Detects remote printer driver load from Detailed File Share in Security logs that are a sign of successful exploitation attempts against print spooler vulnerability CVE-2021-1675 and CVE-2021-34527.

Rule ID

```
windows_security_159
```

Query

```
{'selection': {'EventID': 5145, 'ShareName': '\\\\*\\IPC$', 'RelativeTargetName': 'spoolss', 'AccessMask': '0x3', 'ObjectType': 'File'}, 'condition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,8fe1c584-ee61-444b-be21-e9054b229694

Author: INIT_6

Tactics, Techniques, and Procedures

TA0002, T1569

References

- https://twitter.com/INIT_3/status/1410662463641731075

Severity

90

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/07/02	critical	• Unknown

Rule Details: Possible PetitPotam Coerce Authentication Attempt

Detect PetitPotam coerced authentication activity.

Rule ID

`windows_security_161`

Query

```
{'selection': {'EventID': 5145, 'ShareName|startswith': '\\\\', 'ShareName|endswith':
 '\\IPC$', 'RelativeTargetName': 'lsarpc', 'SubjectUserName': 'ANONYMOUS LOGON'}, 'co
ndition': 'selection'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The advanced audit policy setting "Object Access > Detailed File Share" must be configured for Success/Failure

Rule Source

SigmaHQ,1ce8c8a3-2723-48ed-8246-906ac91061a6

Author: Mauricio Velazco, Michael Haag

Tactics, Techniques, and Procedures

TA0006, T1187

References

- https://github.com/topotam/PetitPotam
- https://github.com/splunk/security_content/blob/0dd6de32de2118b2818550df9e65255f4109a56d/detections/endpoint/petitpotam_network_share_access_request.yml

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/09/02	high	• Unknown. Feedback welcomed.

Rule Details: Possible Impacket SecretDump Remote Activity

Detect AD credential dumping using impacket secretdump HKTL.

Rule ID



`windows_security_162`

Query


```
{'selection': {'EventID': 5145, 'ShareName': '\\\\*\\ADMIN$', 'RelativeTargetName|contains|all': ['SYSTEM32\\', '.tmp']}, 'condition': 'selection'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The advanced audit policy setting "Object Access > Audit Detailed File Share" must be configured for Success/Failure

Rule Source

SigmaHQ,252902e3-5830-4cf6-bf21-c22083dfd5cf

Author: Samir Bousseaden, wagga

Tactics, Techniques, and Procedures

TA0006, T1003

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/04/03	high	• Unknown

Rule Details: Suspicious PsExec Execution

Detects execution of psexec or paexec with renamed service name, this rule helps to filter out the noise if psexec is used for legit purposes or if attacker uses a different psexec client other than sysinternal one.

Rule ID

`windows_security_164`

Query

{'selection1': {'EventID': 5145, 'ShareName': '*\\IPC$', 'RelativeTargetName|endswith': ['-stdin', '-stdout', 'stderr']}, 'filter': {'RelativeTargetName|startswith': 'PSEXESVC'}, 'condition': 'selection1 and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events
- The advanced audit policy setting "Object Access > Audit Detailed File Share" must be configured for Success/Failure

Rule Source

SigmaHQ,c462f537-a1e3-41a6-b5fc-b2c2cef9bf82

Author: Samir Bousseaden

Tactics, Techniques, and Procedures

TA0008, T1021.002

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/04/03	high	• Unknown

Rule Details: DCOM InternetExplorer.Application Iertutil DLL Hijack - Security

Detects a threat actor creating a file named `iertutil.dll` in the `C:\Program Files\Internet Explorer\` directory over the network for a DCOM InternetExplorer DLL Hijack scenario.

Rule ID

`windows_security_165`

Query

{'selection': {'EventID': 5145, 'RelativeTargetName|endswith': '\\Internet Explorer\\iertutil.dll'}, 'filter': {'SubjectUserName|endswith': '$'}, 'condition': 'selection and not filter'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,c39f0c81-7348-4965-ab27-2fde35a1b641

Author: Roberto Rodriguez @Cyb3rWard0g, Open Threat Research (OTR)

Tactics, Techniques, and Procedures

TA0008, T1021

References

- https://threathunterplaybook.com/hunts/windows/201009-RemoteDCOMIErtUtilDLLHijack/notebook.html

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2020/10/12	high	• Unknown

Rule Details: Remote PowerShell Sessions Network Connections (WinRM)

Detects basic PowerShell Remoting (WinRM) by monitoring for network inbound connections to ports 5985 OR 5986.

Rule ID

```
windows_security_166
```

Query

```
{'selection': {'EventID': 5156, 'DestPort': ['5985', '5986'], 'LayerRTID': '44'}, 'filter': {'Application': ['System']}, 'condition': 'selection and not filter'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,13acf386-b8c6-4fe0-9a6e-c4756b974698

Author: Roberto Rodriguez @Cyb3rWard0g

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://threathunterplaybook.com/hunts/windows/190511-RemotePwshExecution/notebook.html

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/09/12	high	• Legitimate use of remote PowerShell execution

Rule Details: Suspicious Outbound Kerberos Connection - Security

Detects suspicious outbound network activity via kerberos default port indicating possible lateral movement or first stage PrivEsc via delegation.

Rule ID

`windows_security_167`

Query


```
{'selection': {'EventID': 5156, 'DestPort': '88', 'Direction': '%%14593'}, 'filter_exact': {'Application': ['System', '\\device\\harddiskvolume*\\windows\\system32\\lsass.exe', '\\device\\harddiskvolume*\\*\\nmap.exe', '\\device\\harddiskvolume*\\*\\chrome.exe', '\\device\\harddiskvolume*\\*\\firefox.exe', '\\device\\harddiskvolume*\\*\\msedge.exe', '\\device\\harddiskvolume*\\*\\iexplore.exe']}, 'condition': 'selection and not 1 of filter_*'}
```


Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,eca91c7c-9214-47b9-b4c5-cb1d7e4f2350

Author: Ilyas Ochkov, oscd.community

Tactics, Techniques, and Procedures

TA0006, T1558.003

References

- https://github.com/GhostPack/Rubeus

Severity

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019/10/24	high	• Web Browsers

Rule Details: Potentially Suspicious AccessMask Requested From LSASS

Detects process handle on LSASS process with certain access mask.

Rule ID

`windows_security_169`

Query


```
{'selection_1': {'EventID': 4656, 'ObjectName|endswith': '\\lsass.exe', 'AccessMask|c
ontains': ['0x40', '0x1400', '0x100000', '0x1410', '0x1010', '0x1438', '0x143a', '0x1
418', '0x1f0fff', '0x1f1fff', '0x1f2fff', '0x1f3fff']}, 'selection_2': {'EventID': 46
63, 'ObjectName|endswith': '\\lsass.exe', 'AccessList|contains': ['4484', '4416']}, '
filter_main_specific': {'ProcessName|endswith': ['\\csrss.exe', '\\GamingServices.exe
', '\\lsm.exe', '\\MicrosoftEdgeUpdate.exe', '\\minionhost.exe', '\\MRT.exe', '\\MsMp
Eng.exe', '\\perfmon.exe', '\\procexp.exe', '\\procexp64.exe', '\\svchost.exe', '\\ta
skmgr.exe', '\\thor.exe', '\\thor64.exe', '\\vmtoolsd.exe', '\\VsTskMgr.exe', '\\wini
nit.exe', '\\wmiprvse.exe', '\\WmiPrvSE.exe', 'RtkAudUService64'], 'ProcessName|conta
ins': [':\\Program Files (x86)\\', ':\\Program Files\\', ':\\ProgramData\\Microsoft\\
Windows Defender\\Platform\\', ':\\Windows\\SysNative\\', ':\\Windows\\System32\\', '
:\\Windows\\SysWow64\\', ':\\Windows\\Temp\\asgard2-
agent\\']}, 'filter_main_generic': {'ProcessName|contains': ':\\Program Files'}, 'fil
ter_main_exact': {'ProcessName|endswith': [':\\Windows\\System32\\taskhostw.exe', ':\
\Windows\\System32\\msiexec.exe', ':\\Windows\\CCM\\CcmExec.exe', '\\Windows\\explore
r.exe', '\\jre\\bin\\java.exe', ':\\Windows\\LTSvc\\LTSVC.exe']}, 'filter_main_sysmon
': {'ProcessName|endswith': ':\\Windows\\Sysmon64.exe', 'AccessList|contains': '%%448
4'}, 'filter_main_aurora': {'ProcessName|contains': ':\\Windows\\Temp\\asgard2-agent-
sc\\aurora\\', 'ProcessName|endswith': '\\aurora-agent-
64.exe', 'AccessList|contains': '%%4484'}, 'filter_main_scenarioengine': {'ProcessNam
e|endswith': '\\x64\\SCENARIOENGINE.EXE', 'AccessList|contains': '%%4484'}, 'filter_m
ain_avira1': {'ProcessName|contains|all': [':\\Users\\', '\\AppData\\Local\\Temp\\is-
'], 'ProcessName|endswith': '\\avira_system_speedup.tmp', 'AccessList|contains': '%%4
484'}, 'filter_main_avira2': {'ProcessName|contains': ':\\Windows\\Temp\\', 'ProcessN
ame|endswith': '\\avira_speedup_setup_update.tmp', 'AccessList|contains': '%%4484'},
'filter_main_snmp': {'ProcessName|endswith': ':\\Windows\\System32\\snmp.exe', 'Acces
sList|contains': '%%4484'}, 'filter_main_googleupdate': {'ProcessName|contains': ':\\
Windows\\SystemTemp\\', 'ProcessName|endswith': '\\GoogleUpdate.exe', 'AccessList|con
tains': '%%4484'}, 'filter_optional_procmon': {'ProcessName|endswith': ['\\procmon64.
```

exe', '\\procmon.exe'], 'AccessList|contains': '%%4484'}, 'condition': '1 of selection_* and not 1 of filter_main_* and not 1 of filter_optional_*'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

SigmaHQ,4a1b6da0-d94f-4fc3-98fc-2d9cb9e5ee76

Author: Roberto Rodriguez, Teymur Kheirkhabarov, Dimitrios Slamaris, Mark Russinovich, Aleksey Potapov, oscd.community (update)

Tactics, Techniques, and Procedures

TA0006, T1003.001

References

- https://web.archive.org/web/20230208123920/https://cyberwardog.blogspot.com/2017/03/chronicles-of-threat-hunter-hunting-for_22.html
- https://www.slideshare.net/heirhabarov/hunting-for-credentials-dumping-in-windows-environment

Severity

50

Suppression Logic Based On

- computer_name
- event_data.ObjectName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2019/11/01	medium	• Legitimate software accessing LSASS process for legitimate reason; update the whitelist with it

Rule Details: Transferring Files with Credential Data via Network Shares

Transferring files with well-known filenames (sensitive files with credential data) using network shares.

Rule ID

windows_security_170

Query

{'selection': {'EventID': 5145, 'RelativeTargetName|contains': ['\\mimidrv.sys', '\\windows\\minidump\\', '\\hiberfil.sys', '\\ntds.dit']}, 'condition': 'selection'}

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0006, T1003

References

- https://www.slideshare.net/heirhabarov/hunting-for-credentials-dumping-in-windows-environment

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2019-10-22	medium	• Transferring sensitive files for legitimate administration work by legitimate administrator

Rule Details: Startup/Logon Script added to Group Policy Object

Detects the modification of Group Policy Objects (GPO) to add a startup/logon script to users or computer objects.

Rule ID

```
windows_security_171
```

Query

```
{'selection1': {'EventID': 5136}, 'selection2': {'AttributeLDAPDisplayName': ['gPCMachineExtensionNames', 'gPCUserExtensionNames']}, 'selection3': {'AttributeValue|contains': '42B5FAAE-6536-11D2-AE5A-0000F87571E3'}, 'selection4': {'AttributeValue|contains': ['40B66650-4972-11D1-A7CA-0000F87571E3', '40B6664F-4972-11D1-A7CA-0000F87571E3']}, 'condition': 'selection1 and selection2 and selection3 and selection4'}
```

Log Source

Stellar Cyber Windows Server Sensor configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0004, T1484.001, T1547

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021/11/08	medium	• Legitimate Administrative Activity

Rule Details: Windows Privilege Escalation through Security Group Modification

This rule detects request for privilege escalation by modifying windows security group.

Rule ID

```
windows_security_201
```

Query

```
{'selection1': {'EventID': [632, 4728, 636, 4732, 660, 4756]}, 'selection2': {'Target
UserName': ['Group Policy Creator Owners', 'Administrators', 'DHCP Administrators', '
DNS Admins', 'Domain Admins', 'Enterprise Admins', 'Enterprise Key Admins', 'Hyper-
V Administrators', 'Key Admins', 'Schema Admins', 'Storage Replica Administrators']},
 'condition': 'selection1 and selection2'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1078, T1098

References

N/A

Severity

50

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
test	2023/06/22	high	• Legitimate administrative activity

Rule Details: Windows AD SID History Attribute Modified

Detects modifications to the SID History attribute in Active Directory. This detection identifies changes to the sIDHistory attribute which can be exploited by adversaries to inherit permissions from other accounts, potentially granting unauthorized access. If confirmed malicious, this activity could allow attackers to maintain persistent access and escalate privileges within the domain, posing a significant security risk.

Rule ID

```
windows_security_300
```

Query

```
{'selection1': {'EventID': 5136}, 'selection2': {'AttributeLDAPDisplayName': 'sIDHistory'}, 'selection3': {'OperationType': '%%14674'}, 'condition': 'selection1 and selection2 and selection3'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Collecting Windows security events

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0005, T1134.005

References

N/A

Severity

75

Suppression Logic Based On

- event_id
- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/08/14	high 	• Domain mergers and migrations • Legitimate administrative operations involving SID history • ADMT (Active Directory Migration Tool) operations

© 2026 Stellar Cyber . All rights reserved.