Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Configuring Broadcom (Symantec) Email Security.cloud Connectors

The Broadcom (Symantec) Email Security.cloud connector allows you to ingest email related log reports to the Stellar Cyber data lake.

Stellar Cyber connectors with the Collect function (collectors) may skip collecting some data when the ingestion volume is large, which potentially can lead to data loss. This can happen when the processing capacity of the collector is exceeded.

Connector Overview: Broadcom (Symantec) Email Security.cloud

Capabilities

- Collect: **Yes**
- Respond: **No**
- Native Alerts Mapped: **No**
- Runs on: **DP**
- Interval: **Configurable**

Collected Data

Content Type	Index	Locating Records

Clicktime
Delivery
EC Reports
Isolation
Malware
Spam
	Syslog	msg_class:
		`symantec_email_clicktime`
		`symantec_email_delivery_data`
		`symantec_email_threat_analytics`
		`symantec_email_threat_isolation`

Content Type	Index	Locating Records

		`symantec_email_malware`
		`symantec_email_anti_spam`
		
		msg_origin.source:
		`symantec_email_security_cloud`
		
		msg_origin.vendor:
		`symantec`
		
		msg_origin.category:
		`email`

Domain

https://datafeeds.emailsecurity.symantec.com

Response Actions

N/A

Third Party Native Alert Integration Details

N/A

Required Credentials and Configurations

- Username and Password

Adding a Broadcom (Symantec) Email Security.cloud Connector

To add the Broadcom (Symantec) Email Security.cloud connector:

1. Obtain the required credentials
2. Add the connector in Stellar Cyber
3. Test the connector

Obtaining the Required Credentials

To configure this connector in Stellar Cyber, you will need the following information from your Broadcom (Symantec) Email Security.cloud deployment:

- Username and password for an account with **View Statistics** permissions.

  The password should not include non-ASCII special characters.

- The type of data feed to collect:


- **clicktime**: Contains metadata from events generated by end-user clicks in URLs that were rewritten by the Click-time URL Protection.
- **delivery**: Contains metadata that describes both inbound and outbound email delivery to provide visibility into email tracing, TLS compliance, and routing.
- **ec_reports**: Contains contextual information about all emails blocked by the Email Security.cloud's Anti-Malware service, as well as emails blocked because their attachments are determined to be malicious.
- **isolation**: Contains data from events logged by the URL and Attachment Isolation features, which ensure threats are executed in an isolation platform.
- **malware**: Contains data about malware-containing email only.
- **spam**: Contains metadata about email that the Anti-Spam service has detected as spam, as well as the action taken as a result of that detection.

More details on the requirements for users and the nature of the feeds are described in Symantec's Data Feeds API Guide for Email Security.cloud.


Adding the Connector in Stellar Cyber

With the configuration information handy, you can add the Broadcom (Symantec) Email Security.cloud connector in Stellar Cyber:

1. Log in to Stellar Cyber.
2. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.




3. Click **Create** and select **Connector**.



The **General** tab of the **Add Connector** screen appears. The information on this tab cannot be changed after you add the connector.

4. Choose **Email** from the **Category** dropdown.
5. Choose **Symantec Email Security.cloud** from the **Type** dropdown.




The asterisk (*) indicates a required field.

6. For this connector, the supported **Function** is **Collect**, which is enabled already.
7. Enter a **Name**.

> Notes:
> - This field does not accept multibyte characters.
> - It is recommended that you follow a naming convention such as tenantname-connectortype.

8. Choose a **Tenant Name**. The Interflow records created by this connector include this tenant name.
9. Choose the device on which to run the connector .
10. (Optional) When the **Function** is **Collect**, you can apply **Log Filters**. For information, see Managing Log Filters.
11. Click **Next**. The **Configuration** tab appears.




The asterisk (*) indicates a required field.

12. Enter the **Username** you noted above in Obtaining the Required Credentials.
13. Enter the **Password** you noted above.
14. Choose the **Interval (min)**. This is how often the logs are collected.
15. Select the **Content Type** you want to collect:
    - **Clicktime**: Contains metadata from events generated by end-user clicks in URLs that were rewritten by the Click-time URL Protection.
    - **Delivery**: Contains metadata that describes both inbound and outbound email delivery to provide visibility into email tracing, TLS compliance, and routing.
    - **EC Reports**: Contains contextual information about all emails blocked by Email Security.cloud's Anti-Malware service, as well as emails blocked because their attachments are determined to be malicious.
    - **Isolation**: Contains data from events logged by the URL and Attachment Isolation features, which ensure threats are executed in an isolation platform.

- **Malware**: Contains data about malware-containing email only.
- **Spam**: Contains metadata about email that the Anti-Spam service has detected as spam, as well as the action taken as a result of that detection.

Descriptions of this content type (the data feeds) and requirements for those to be available in your deployment are provided in Symantec's Data Feeds API Guide for Email Security.cloud.

16. Click **Next**. The final confirmation tab appears.



17. Click **Submit**.


The new connector is immediately active.

Testing the Connector

When you add (or edit) a connector, we recommend that you run a test to validate the connectivity parameters you entered. The test validates authentication and connectivity.

For connectors running on a sensor, Stellar Cyber recommends that you allow 30-60 seconds for new or modified configuration details to be propagated to the sensor before performing a test.

1. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.



2. Locate the connector by name that you added, or modified, or that you want to test.
3. Click **Test** at the right side of that row. The test runs immediately.

Note that you may run only one test at a time.

Stellar Cyber conducts a basic connectivity test for the connector and reports a success or failure result. A successful test indicates that you entered all of the connector information correctly.

To aid troubleshooting your connector, the dialog remains open until you explicitly close it by using the **X** button. If the test fails, you can select the button from the same row to review and correct issues.

The connector status is updated every five (5) minutes. A successful test clears the connector status, but if issues persist, the status reverts to failed after a minute.


Repeat the test as needed.

Display sample messages...


Success !



Failure with summary of issue:



Show More example detail:



If the test fails, the common HTTP status error codes are as follows:

HTTP Error Code	HTTP Standard Error Name	Explanation	Recommendation
400	Bad Request	This error occurs when there is an error in the connector configuration.	Did you configure the connector correctly?
401	Unauthorized	This error occurs when an authentication credential is invalid or when a user does not have sufficient privileges to access a specific API.	Did you enter your credentials correctly? Are your credentials expired? Are your credentials entitled or licensed for that specific resource?
403	Forbidden	This error occurs when the permission or scope is not correct in a valid credential.	Did you enter your credentials correctly? Do you have the required role or permissions for that credential?
404	Not Found	This error occurs when a URL path does not resolve to an entity.	Did you enter your API URL correctly?
429	Too Many Requests	This error occurs when the API server receives too much traffic or if a user's license or entitlement quota is exceeded.	The server or user license/quota will eventually recover. The connector will periodically retry the query. If this occurs unexpectedly or too often, work with your API provider to investigate the server limits, user licensing, or quotas.

For a full list of codes, refer to HTTP response status codes.

Verifying Ingestion

To verify ingestion:

1. Select **Threat Hunting**.

   The **Interflow Search** appears.

2. Change the **Indices** to **Syslog**.

   The table immediately updates to show ingested Interflow records.

© 2026 Stellar Cyber . All rights reserved.