Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Configuring Broadcom Symantec Endpoint Security (SES) Connectors 6.1.0

This connector allows Stellar Cyber to ingest logs from Broadcom SES and add the records to the data lake.

This connector requires the Broadcom Symantec Endpoint Security Enterprise subscription, except for Incidents, which requires the Broadcom Symantec Endpoint Security Complete subscription.

Stellar Cyber connectors with the Collect function (collectors) may skip collecting some data when the ingestion volume is large, which potentially can lead to data loss. This can happen when the processing capacity of the collector is exceeded.

Connector Overview: Broadcom SES

Capabilities

- Collect: **Yes**
- Respond: **No**
- Native Alerts Mapped: **Yes** 6.1.0
- Runs on: **DP**
- Interval: **Configurable**

Collected Data

Content Type	Index	Locating Records
Devices	Syslog	msg_class:
Events	Assets (for Devices)	`broadcom_devices`
Incidents		`broadcom_events`
		`broadcom_ses_incidents`

Content Type	Index	Locating Records
		msg_origin.source: `broadcom_ses` msg_origin.vendor: `broadcom` msg_origin.category: `endpoint`

Domain

https://<Hostname>

where <Hostname> is a variable from the configuration of this connector

Response Actions

N/A

Third Party Native Alert Integration Details 6.1.0

This connector ingests logs from Broadcom Symantec Endpoint Security (SES) to get the raw alerts that are stored in the Syslog index. Select the Incidents content type.

Stellar Cyber maps Broadcom SES incidents. The incidents are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index.

Deduplication is by `tenantid` and `broadcom.incident_uid`.

For details, see Integration of Third Party Native Alerts.

Required Credentials and Configurations

- OAuth credentials

Locating Records 6.1.0

To search the alerts in the Alerts index or the Original Records in the Syslog index, use the query: `msg_class: broadcom_ses_incidents AND _exists_: event.threat.name`

Adding a Broadcom SES Connector

To add a Broadcom SES connector:

1. Obtain Broadcom SES credentials
2. Add the connector in Stellar Cyber
3. Test the connector
4. Verify ingestion

Obtaining Broadcom SES Credentials


Follow guidance on Broadcom documentation pages to generate a bearer token used for Stellar Cyber API calls and set minimum privileges.

1. Login to your **Symantec Endpoint Security** console.
2. Navigate to **Integratio Client Applications**.
3. Select **Add Client Application**.
4. Enter a **Name** for the application, then click the **Add** button.
5. Within the client application details screen that displays, ensure the following minimum privileges are enabled.
    - **Devices**: View
    - **Alerts & Events**: View
    - **Investigation** (Incident and Incident Rules): View
    - **Policies**: View
6. Click **Save**.
7. Click the **ellipsis** and then select **Client Secret**.
8. Click the **copy** icon for the **OAuth Credentials** value for the Stellar Cyber connector to generate a bearer token.


Adding the Connector in Stellar Cyber

With the access information handy, you can add a Broadcom SES connector in Stellar Cyber:

1. Log in to Stellar Cyber.
2. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.




3. Click **Create** and select **Connector**.



The **General** tab of the **Add Connector** screen appears. The information on this tab cannot be changed after you add the connector.

4. Choose **Endpoint Security** from the **Category** dropdown.
5. Choose **Broadcom Symantec Endpoint Security** from the **Type** dropdown.




The asterisk (*) indicates a required field.

6. For this connector, the supported **Function** is **Collect**, which is enabled already.
7. Enter a **Name**.

   Notes:
   - This field does not accept multibyte characters.
   - It is recommended that you follow a naming convention such as tenantname-connectortype.

8. Choose a **Tenant Name**. This identifies which tenant is allowed to use the connector.
9. Choose the device on which to run the connector.
10. (Optional) When the **Function** is **Collect**, you can apply **Log Filters**. For information, see Managing Log Filters.
11. Click **Next**. The **Configuration** tab appears.



The asterisk (*) indicates a required field.

12. Enter the **Hostname** for example: `api.sep.securitycloud.symantec.com`.

    Do not include the https prefix or a trailing "/" symbol.


13. In the **OAuth Credentials** field, enter the value you copied in Obtaining Broadcom SES Credentials.
14. Enter the **Interval (min)**. This is how often the logs for Events and Incidents are collected.

    The interval for Devices is always 24 hours.

15. Choose the **Content Type**. The logs for **Devices**, **Events**, and **Incidents** are supported.

    The **Devices** content type is always selected and cannot be removed from the configuration as it is required for host information.

16. Click **Next**. The final confirmation tab appears.



17. Click **Submit**.


The new connector is immediately active.

Testing the Connector

When you add (or edit) a connector, we recommend that you run a test to validate the connectivity parameters you entered. The test validates authentication and connectivity.

For connectors running on a sensor, Stellar Cyber recommends that you allow 30-60 seconds for new or modified configuration details to be propagated to the sensor before performing a test.

1. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.



2. Locate the connector by name that you added, or modified, or that you want to test.
3. Click **Test** at the right side of that row. The test runs immediately.

Note that you may run only one test at a time.

Stellar Cyber conducts a basic connectivity test for the connector and reports a success or failure result. A successful test indicates that you entered all of the connector information correctly.

To aid troubleshooting your connector, the dialog remains open until you explicitly close it by using the **X** button. If the test fails, you can select the button from the same row to review and correct issues.

The connector status is updated every five (5) minutes. A successful test clears the connector status, but if issues persist, the status reverts to failed after a minute.


Repeat the test as needed.

Display sample messages...


Success !

Failure with summary of issue:





Show More example detail:



If the test fails, the common HTTP status error codes are as follows:

HTTP Error Code	HTTP Standard Error Name	Explanation	Recommendation
400	Bad Request	This error occurs when there is an error in the connector configuration.	Did you configure the connector correctly?
401	Unauthorized	This error occurs when an authentication credential is invalid or when a user does not have sufficient privileges to access a specific API.	Did you enter your credentials correctly? Are your credentials expired? Are your credentials entitled or licensed for that specific resource?
403	Forbidden	This error occurs when the permission or scope is not correct in a valid credential.	Did you enter your credentials correctly? Do you have the required role or permissions for that credential?
404	Not Found	This error occurs when a URL path does not resolve to an entity.	Did you enter your API URL correctly?
429	Too Many Requests	This error occurs when the API server receives too much traffic or if a user's license or entitlement quota is exceeded.	The server or user license/quota will eventually recover. The connector will periodically retry the query. If this occurs unexpectedly or too often, work with your API provider to investigate the server limits, user licensing, or quotas.

For a full list of codes, refer to HTTP response status codes.

Connection Test Failure

For this Broadcom SES connector, the credential and connection test may not work for all content types. But even it it fails for one content type, it will still get the logs for the other content types.

For example, if the connection test fails for the Incident content type, the following message displays with the **Show More** button:

```
Fail to collect Broadcom SES logs for content type of incidents: <error message>
Please make sure the token has complete subscription.
```

Verifying Ingestion

To verify ingestion:

1. Select **Threat Hunting**.

   The **Interflow Search** tab appears.

2. Change the **Indices** for the type of content you collected:

   - For **Devices**, **Events**, and **Incidents**, change the **Indices** to **Syslog**.
   - For **Devices** only, change the **Indices** to **Assets**.

   The table immediately updates to show ingested Interflow records.

© 2026 Stellar Cyber . All rights reserved.