Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Configuring CYRISMA Connectors

Connectors allow Stellar Cyber to collect data from external sources and add it to the data lake. Review the content in this topic to understand what type of data can be collected and acted upon for this connector type.

Stellar Cyber connectors with the Collect function (collectors) may skip collecting some data when the ingestion volume is large, which potentially can lead to data loss. This can happen when the processing capacity of the collector is exceeded.

Connector Overview: CYRISMA

Capabilities

- Collect: **Yes**
- Respond: **No**
- Native Alerts Mapped: **No**
- Runs on: **DP**
- Interval: **Configurable**

Collected Data

Content Type	Index	API
Vulnerabilities	Syslog, Linux	https://msp.cyrisma.com/app/vulnerability/report/tenants (fetches tenant IDs, tenant access URL, and temporary access token) https://tenant_access_url/

Content Type	Index	API
		app/vulnerability/report/json (fetches vulnerabilities)
Hosts	Syslog, Assets	*Automatically extracted with Vulnerabilities*

Domain

https://msp.cyrisma.com/

https://<customer_instance_URL>.cyrisma.com

The <customer_instance_URL> is not provided in the configuration of this connector, but is returned from previous API calls.

Response Actions

N/A

Third Party Native Alert Integration Details

N/A

Required Credentials and Configurations

- API Name and API Key

Locating Records

Use the following to query for records:

- **msg_origin.source**: `cyrisma`
- **msg_origin.vendor**: `cyrisma`
- **msg_origin.category**: `security_scan`
- **msg_class**: `cyrisma_host`, `cyrisma_vulnerability`

Adding a CYRISMA Connector

To add a CYRISMA connector:

1. Obtain credentials and prepare CYRISMA
2. Add the connector in Stellar Cyber
3. Test the connector
4. Verify ingestion


Obtaining Credentials and Preparing CYRISMA

CYRISMA is a SaaS service with MSSP accounts managing data for multiple organizations. Each organization is considered a “tenant” to Stellar Cyber.


Set up one connector for each CYRISMA tenant from which you want to pull data.

To support this connector configuration and function:

- **Obtain the MSSP API Name and API Key**: These are provided to the MSSP by CYRISMA Customer Support.
- **Add Stellar Cyber Tenant IDs**: For any organization that the MSSP wants to retrieve data from CYRISMA, the MSSP must do the following:
    1. Set up a tenant in Stellar Cyber corresponding to each of the organizations in CYRISMA for which they want to collect data.
    2. Access the Stellar Cyber Tenant screen and make note of the ID number associated with each of the organizations.




    3. Access the CYRISMA console (https://msp.cyrisma.com).
    4. Display each organization page and locate the field labeled MDR/XDR Tenant, as shown below.
    5. Click the field and add the tenant ID you obtained from Stellar Cyber.




Adding the Connector in Stellar Cyber

To add the CYRISMA connector in Stellar Cyber:

1. Log in to Stellar Cyber.
2. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.




3. Click **Create** and select **Connector**.



The **General** tab of the **Add Connector** screen appears. The information on this tab cannot be changed after you add the connector.

4. Choose **Vulnerability Scanner** from the **Category** dropdown.
5. Choose **CYRISMA** from the **Type** dropdown.




The asterisk (*) indicates a required field.

6. For this connector, the supported **Function** is **Collect**, which is enabled already.
7. Enter a **Name**.

Notes:

- This field does not accept multibyte characters.
- It is recommended that you follow a naming convention such as tenantname-connectortype.

8. Choose a **Tenant Name**. The connector will pull data for this tenant. The Interflow records created by this connector include this tenant name.
9. Choose the device on which to run the connector.
10. (Optional) When the **Function** is **Collect**, you can apply **Log Filters**. For information, see Managing Log Filters.
11. Click **Next**. The **Configuration** tab appears.




The asterisk (*) indicates a required field.

12. Enter the **API Name** you obtained from CYRISMA Customer Support.
13. In the **API Key** you obtained from CYRISMA Customer Support.
14. Enter the **Interval (hour)**. This is how often Stellar Cyber collects information.

Note that the typical interval for connectors is in minutes. The CYRISMA API supports intervals in hours.

15. Choose the **Content Type**. The logs for **Vulnerabilities** are supported.
16. Click **Next**. The final confirmation tab appears.



17. Click **Submit**.


The new connector is immediately active.

Testing the Connector

When you add (or edit) a connector, we recommend that you run a test to validate the connectivity parameters you entered. The test validates authentication and connectivity.

For connectors running on a sensor, Stellar Cyber recommends that you allow 30-60 seconds for new or modified configuration details to be propagated to the sensor before performing a test.

1. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.



2. Locate the connector by name that you added, or modified, or that you want to test.
3. Click **Test** at the right side of that row. The test runs immediately.

Note that you may run only one test at a time.

Stellar Cyber conducts a basic connectivity test for the connector and reports a success or failure result. A successful test indicates that you entered all of the connector information correctly.

To aid troubleshooting your connector, the dialog remains open until you explicitly close it by using the **X** button. If the test fails, you can select the button from the same row to review and correct issues.

The connector status is updated every five (5) minutes. A successful test clears the connector status, but if issues persist, the status reverts to failed after a minute.


Repeat the test as needed.

Display sample messages...


Success !



Failure with summary of issue:



Show More example detail:



If the test fails, the common HTTP status error codes are as follows:

HTTP Error Code	HTTP Standard Error Name	Explanation	Recommendation
400	Bad Request	This error occurs when there is an error in the connector configuration.	Did you configure the connector correctly?
401	Unauthorized	This error occurs when an authentication credential is invalid or when a user does not have sufficient privileges to access a specific API.	Did you enter your credentials correctly? Are your credentials expired? Are your credentials entitled or licensed for that specific resource?
403	Forbidden	This error occurs when the permission or scope is not correct in a valid credential.	Did you enter your credentials correctly? Do you have the required role or permissions for that credential?
404	Not Found	This error occurs when a URL path does not resolve to an entity.	Did you enter your API URL correctly?
429	Too Many Requests	This error occurs when the API server receives too much traffic or if a user's license or entitlement quota is exceeded.	The server or user license/quota will eventually recover. The connector will periodically retry the query. If this occurs unexpectedly or too often, work with your API provider to investigate the server limits, user licensing, or quotas.

For a full list of codes, refer to HTTP response status codes.

Verifying Ingestion

To verify ingestion:

1. Select **Threat Hunting**.

   The **Interflow Search** tab appears.

2. Set the **Indices** to match the type of content you collected:

- For **Vulnerabilities**, change the **Indices** to **Scans**.
- For **Host** data, change the **Indices** to **Assets**.

The table immediately updates to show ingested Interflow records.

© 2026 Stellar Cyber . All rights reserved.