Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

# Configuring Check Point Harmony Email Connectors 6.4.0 6.5.0

This connector allows Stellar Cyber to ingest logs from Check Point Harmony Email and add the records to the data lake. This connector integrates with the Harmony Email & Collaboration Smart API to query Security events.

Stellar Cyber connectors with the Collect function (collectors) may skip collecting some data when the ingestion volume is large, which potentially can lead to data loss. This can happen when the processing capacity of the collector is exceeded.

## Connector Overview: Check Point Harmony Email

### Capabilities

- Collect: **Yes**
- Respond: **No**
- Native Alerts Mapped: **Yes** 6.5.0
- Runs on: **DP**
- Interval: **Configurable**

### Collected Data

| Content Type | Index | Locating Records |
|---|---|---|
| Security Event | Syslog | msg_class: `checkpoint_harmony_security_event`<br>msg_origin.source: `checkpoint_harmony`<br>msg_origin.vendor: |

| Content Type | Index | Locating Records |
| --- | --- | --- |
|  | | `checkpoint`<br><br>msg_origin.category:<br>`email` |

## Domain

<Base URL>

where <Base URL> is a variable from the configuration of this connector

## Response Actions

N/A

## Third Party Native Alert Integration Details 6.5.0

This connector ingests logs from Check Point Harmony Email to get the raw alerts that are stored in the Syslog index. Select the Security Event content type.

Stellar Cyber maps Check Point Harmony Email events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index.

Deduplication is by `tenantid` and `checkpoint_harmony.eventId`.

For details, see Integration of Third Party Native Alerts.

## Required Credentials and Configurations

- Base URL, API Key, and Domain ID

## Locating Records 6.5.0

To search the alerts in the Alerts index or the Original Records in the Syslog index, use the query: `(msg_class:\"checkpoint_harmony_security_event\") AND (checkpoint_harmony.type:(\"phishing\" OR \"malware\" OR \"alert\" OR \"dlp\") OR (checkpoint_harmony.severity:[4 TO *]) )`

# Adding a Check Point Harmony Email Connector

To add a Check Point Harmony Email connector:

1. Obtain credentials
2. Add the connector in Stellar Cyber
3. Test the connector
4. Verify ingestion

# Obtaining Check Point Harmony Email Credentials

Before you configure the connector in Stellar Cyber, you must obtain the following Check Point Harmony Email credentials:

- Base URL—The base URL for API access. The default is: https://cloudinfra-gw-us.portal.checkpoint.com
- Client ID—The client ID part of the API Key. See Creating API Keys.

- Access Key—The client secret part of the API Key. See Creating API Keys.

### Creating API Keys

AN API Key consists of a client ID and client secret. When creating an API Key, make sure to select **Harmony Email & Collaboration**.

Follow the guidance in the *Infinity Portal Administration Guide* for API Keys. For example, the basic steps to create an Account API Key are:


1. Log in to the Infinity Portal.
2. Click the Gear icon (Settings).
3. Select **API Keys**.
4. Click **New**.
5. Select **New account API key**.
6. Select the **Harmony Email & Collaboration** service.
7. Enter the information, such as Expiration and Description.
8. Click **Create**.
9. Copy the credentials.

   Store the credentials in a safe location.
10. Click **Close**.


## Adding the Connector in Stellar Cyber

To add a Check Point Harmony Email connector in Stellar Cyber:

1. Log in to Stellar Cyber.
2. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.




3. Click **Create** and select **Connector**.





   The **General** tab of the **Add Connector** screen appears. The information on this tab cannot be changed after you add the connector.

4. Choose **Email** from the **Category** dropdown.
5. Choose **Check Point Harmony Email** from the **Type** dropdown.





   The asterisk (*) indicates a required field.
6. For this connector, the supported **Function** is **Collect**, which is enabled already.
7. Enter a **Name**.

   Notes:
   - This field does not accept multibyte characters.
   - It is recommended that you follow a naming convention such as tenantname-connectortype.
8. Choose a **Tenant Name**. The Interflow records created by this connector include this tenant name.
9. Choose the device on which to run the connector.
10. (Optional) When the **Function** is **Collect**, you can apply **Log Filters**. For information, see Managing Log Filters.
11. Click **Next**. The **Configuration** tab appears.




   The asterisk (*) indicates a required field.
12. Enter the **Base URL** you noted above in Obtaining Check Point Harmony Email Credentials.
13. Enter the **Client ID** you noted above.
14. Enter the **Access Key** you noted above.
15. Choose the **Interval (min)**. This is how often the logs are collected.
16. (Optional) Click **Disable SSL Certificate Verification** if you want to disable SSL certificate verification. Only disable SSL certificates if you have a necessary reason to, otherwise, it is not a good security practice and may expose the connection to security risks.
17. Choose the **Content Type** you would like to collect. The logs for **Security Event** are supported.

18. Click **Next**. The final confirmation tab appears.




19. Click **Submit**.

The new connector is immediately active.


# Testing the Connector

In addition to testing for connectivity, the **Test** button for the Check Point Harmony Email connector tests that the Base URL, Client ID, and Access Key are correct and data requests for the requested content types return successful responses.

When you add (or edit) a connector, we recommend that you run a test to validate the connectivity parameters you entered. The test validates authentication and connectivity.

For connectors running on a sensor, Stellar Cyber recommends that you allow 30-60 seconds for new or modified configuration details to be propagated to the sensor before performing a test.

1. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.



2. Locate the connector by name that you added, or modified, or that you want to test.
3. Click **Test** at the right side of that row. The test runs immediately.

   Note that you may run only one test at a time.

Stellar Cyber conducts a basic connectivity test for the connector and reports a success or failure result. A successful test indicates that you entered all of the connector information correctly.

To aid troubleshooting your connector, the dialog remains open until you explicitly close it by using the **X** button. If the test fails, you can select the button from the same row to review and correct issues.

The connector status is updated every five (5) minutes. A successful test clears the connector status, but if issues persist, the status reverts to failed after a minute.


Repeat the test as needed.

Display sample messages...


Success !




Failure with summary of issue:




Show More example detail:




If the test fails, the common HTTP status error codes are as follows:

| HTTP Error Code | HTTP Standard Error Name | Explanation | Recommendation |
|---|---|---|---|
| 400 | Bad Request | This error occurs when there is an error in the connector configuration. | Did you configure the connector correctly? |
| 401 | Unauthorized | This error occurs when an authentication credential is invalid or when a user does not have sufficient privileges to access a specific API. | Did you enter your credentials correctly?<br>Are your credentials expired?<br>Are your credentials entitled or licensed for that specific resource? |
| 403 | Forbidden | This error occurs when the permission or scope is not correct in a valid credential. | Did you enter your credentials correctly?<br>Do you have the required role or permissions for that credential? |
| 404 | Not Found | This error occurs when a URL path does not resolve to an entity. | Did you enter your API URL correctly? |
| 429 | Too Many Requests | This error occurs when the API server receives too much traffic or if a user's license or entitlement quota is exceeded. | The server or user license/quota will eventually recover. The connector will periodically retry the query.<br>If this occurs unexpectedly or too often, work with your API provider to investigate the server limits, user licensing, or quotas. |

For a full list of codes, refer to HTTP response status codes.

# Verifying Ingestion

To verify ingestion:

1. Select **Threat Hunting**.

   The **Interflow Search** tab appears.

2. Change the **Indices** to **Syslog**.

The table immediately updates to show ingested Interflow records.





© 2026 Stellar Cyber . All rights reserved.