Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Configuring CyberArk CEF Log Ingestion

For CyberArk CEF log ingestion, configure CyberArk to forward the Syslog messages (in CEF format) to the Stellar Cyber sensor IP address on port 5143/UDP.

To ingest CyberArk CEF:

1. Configure CyberArk Enterprise Password Vault
2. Verify Ingestion

Configuring CyberArk Enterprise Password Vault

To configure CyberArk Enterprise Password Vault to send Syslog messages (in CEF format) to the Stellar Cyber sensor:

1. In the `DBParm.ini` file, configure the following parameters:
    - **SyslogServerIP** — Enter the IP address of the Stellar Cyber sensor.
    - **SyslogServerPort** — Enter port 5143/UDP to forward the logs to the Stellar Cyber sensor.
    - **SyslogMessageCodeFilter** — Specify the message codes that will be sent from the CyberArk Enterprise Password Vault to the Stellar Cyber sensor through the Syslog protocol. You can specify message numbers (separated by commas), ranges of numbers, or both. For example, to specify messages 1, 2, 3, 30, and 5-10, use the following: 1,2,3,5-10,30.
    - **SyslogTranslatorFile** — Specify the `XSL` file used to parse CyberArk audit records data into the Syslog protocol. The `Syslog` subfolder in the CyberArk Server installation folder contains sample XSL translator files.
2. Copy the `Arcsight.sample.xsl` XSL translator file from the `Syslog` subfolder of the CyberArk Server installation folder to the location specified in the `SyslogTranslatorFile` parameter in the `DBParm.ini` file.

Verifying Ingestion

To verify ingestion:

1. Select **Threat Hunting**.

   The **Interflow Search**  appears.

2. Set **Indices** as **Syslog**.

   The table immediately updates to show ingested Interflow records.

© 2026 Stellar Cyber . All rights reserved.