Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Examples: Using the API to Update Case Details

You can use Stellar Cyber's Cases API to update any combination of a specified case's severity, status, assignee, or tags. Any changes you make via the API to these fields are visible in the Case Details display for the event.

Refer to **Configuring API Authentication** for general requirements to use the API.

Cases API URL

The Cases API is available at the following URL. Note that the ID of the case to be updated is included as a parameter in the URL:

```
/connect/api/v1/cases/<case_id>
```

Finding the ID for an Case

Using the API to update an case always requires the ID of the case to be updated as part of the URL. The easiest way to find the ID for an case is to use the cases API to retrieve details. Refer to **Examples: Using the API to Retrieve Case Details**. Once you have retrieved case details, search on the `_id` field to find the case ID.

Updating Case Details with the API

You can use PUT calls to update any combination of the severity, status, assignee, tags, or description for a specified case.

You can use any language to make the call. For our example, we use Python.

For a PUT call you need the ID of the event whose fields you want to update.

Your call must have the header, the `/connect/api/v1/cases` path, and at least one of the **severity**, **status**, **assignee**, or **tags** parameters. These are the different case details you an update using the API. Enter your own information for the arguments in the table below.

Argument	Description
userid	Username of the admin making the call. Sample script below uses myuser@stellarcyber.ai.
API Key (Refresh Token)	API key for the user, retrieved from the user interface. Sample script below uses 2iRpBAyQYEfv77R2QtATlJN6Nvq6uzftBdzotSy2pjT-IvJTLw9aiHyh7Y2mo12IDSWc-FfHwUyPpmiHQnJrSH.
HOST	The URL or IP address of your Stellar Cyber server. Sample script below uses myserver@stellarcyber.cloud.
ID	The ID of the case to update. The ID is included in the URL as a parameter and is not part of the data payload. For example: `/connect/api/v1/cases/<case_id>`
status	Changes the status to one of the following values: • New • In Progress • Resolved • Cancelled
severity	Changes the severity to one of the following values: • Critical • High • Medium • Low
assignee	Changes the assignee to any valid user in the Stellar Cyber system.

tags	Adds or deletes the specified tag to the list of tags for the case, depending on the operator specified:
	To add a tag:
	`"tags": {`
	`"add": [ "my added tag"],`
	`},`
	To delete a tag:
	`"tags": {`
	`"delete": [ "my deleted tag"],`
	`},`

Sample Script

The sample script below works as follows:

- The script sets the **host** and **refresh_token** parameters in **Step 1** in the sample.
- Because JWTs expire ten minutes after they are generated, this script includes logic that generates and uses a fresh JWT every time the script is run. The script runs the

getAccessToken procedure to generate the new JWT (**Step 2** in the sample).

- The script uses the generated JWT to make a PUT to the cases API in the **putCase** procedure (**Step 3** in the sample). The script adds the tag **October-event** to the case with the ID of **1674728869334287aba4486901d24c4189a6fe8eab6efe05**:
- The script also prints the generated JWT to the screen. This, however, is not strictly necessary since the **getAccessToken** procedure already prints the status code for the call to the **access_token** API (**200** for success; **401** for failure).

```
#!/usr/bin/python3

import requests
import base64
import json
import time
from urllib.parse import urlunparse
requests.packages.urllib3.disable_warnings()

# Step 1
# Add DP IP/hostname and refresh token from GUI here
HOST = "myserver.stellarcyber.cloud"
refresh_token =
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJhcGlfa2V5Ijp7ImtleV9pZCI6ImY3NGYzYyIsInVzZX
JfaWQiOiI1YjdlNTA5ZjMyYmM0MmEzYWU5MTZiNDY0NzRmZGE0YyIsIm9yZ19pZCI6IjhlYTJiOWU3OTcxYj
QyZjZhNzJmZTYyODYyOTEwN2JmIiwiZXhwIjo0ODkyOTE0MzY3fSwiaWF0IjoxNzM5MzE0MzY3fQ._2Senlw
UTvmoAj4gFOehLyGtrKLRp8XfFrn8U35TOIo"

def getAccessToken(refresh_token):
    headers = {
        "Authorization": "Bearer " + refresh_token
    }
    url = urlunparse(("https", HOST, "/connect/api/v1/access_token", "", "", ""))
    res = requests.post(url, headers=headers, verify=False)
    print(res.status_code)
    return res.json()["access_token"]

def putCase(token):
    headers = {"Authorization": "Bearer " + token, 'content-type':
'application/json' }
    url = urlunparse(("https", HOST,
"/connect/api/v1/cases/1674728869334287aba4486901d24c4189a6fe8eab6efe05", "", "",
""))
    json_data = {
      "tags": {
    "add": [ "October-event"],
    },
    }
    query = json.dumps(json_data)
    res = requests.put(url, data=query, headers=headers, verify=False)
    print(res.text)
    print(res.status_code)
    return res.json()

if __name__ == "__main__":

    # Step 2: Use getAccessToken with supplied credentials to generate JWT
    jwt = getAccessToken(refresh_token)
    print("------------ jwt -------------")
    print(jwt)
    print("------------ jwt  end -------------")

    # Step 3: use JWT token to call public API
    data = putCase(jwt)
    print("------------ show result of put case -------------")
    print(data)
    print("------------ end api results -------------")
```

Using the API to Verify the Update

You can always use the Stellar Cyber user interface to check whether your updates were successful – just navigate to the Case Details display for the event you changed and check the fields for your updates. The **History** tab even indicates which changes were made via the API:

Alternatively, you can make a query using the cases API to make sure your PUT call worked. For example, we just used our script in **Updating Case Details with the API** to set a tag called **October-event**. Let's query for all cases matching that tag:

```
https://192.168.1.24/connect/api/v1/cases?tags=October-event
```

In response, the API returns something similar to the following:


```
{
  "data": {
    "cases": [
      {
        "_id": "62fceb4a48be7776c793a02a",
        "acknowledged": 1660826741467,
        "assignee": "826ef6979788454297c85cbba4a51c08",
        "closed": 0,
        "created_at": 1660742474343,
        "created_by": "System",
        "cust_id": "",
        "modified_at": 1660835991789,
        "modified_by": "ohtani",
        "name": "Carbon Black:XDR Endpoint Indicator of Threat and 16 others",
        "score": 25,
        "severity": "Medium",
        "size": 17,
        "status": "New",
        "tags": [
          "October-event"
        ],
        "ticket_id": 67535,
        "version": 17
      }
    ],
    "total": 1
  }
}
```


© 2026 Stellar Cyber . All rights reserved.